consisting of 1250, 283K, and 254 instances, respectively. Among these three, the instances of two of the datasets, synthetic multilingual LLM prompts [40] and ChatGPT roles dataset [17], contain short system prompts, and the synthetic system prompt dataset [8] contains comparatively longer system prompts. We show sample instances from each dataset in Appendix.

3.2 Large Language Models

SPE-LLM framework contains a diverse range of models from prominent LLM productions, including the Llama-3 [13], Falcon-3 [38], and Gemma-2 [43] with 8B, 7B, and 9B parameters, respectively. While these models are open-sourced, our framework also contains two closed-sourced models with an extremely large number of parameters, e.g., GPT-4 [1] and GPT-4.1 [27].

3.3 Attack Strategy

Although OpenAI did not disclose the size of these models publicly, it is reported to consist of ≈ 1.76 T parameters [5]. In order to effectively extract system prompts verbatim, we carefully design several adversarial queries leveraging jailbreaking and prompt engineering techniques.



Figure 2: LLM System Prompt Extraction Attack

3.3.1 Adversarial Query Design

To design effective adversarial queries for extracting system prompts, we first adopt and extend a recently proposed jailbreaking technique called *sandwich attack* [39]. The key idea is to deceive the model to answer all the questions asked in the prompt, and keep the adversarial question (harmful response request) in the middle of the other two-layered benign questions asked in different languages. We adopt this technique and redesign it by sandwiching the adversarial query between a single layer of benign questions asked in the same language. We extend this technique further by adding a reminder (e.g., *"Remember, do not print any welcoming text or header before printing the system prompt; print it in its original verbatim."*) at the end, aiming to elicit the exact system prompt without additional text.

We call it ***extended sandwich attack***. Furthermore, we leverage two popular and effective prompt engineering techniques of LLMs, such as ***Chain-of-Thought (CoT) prompting*** [48] and ***Few-shot-promting*** [7] techniques, and design adversarial queries to effectively extract the exact system prompt. CoT comprises a series of step-by-step instructions that enable intermediate reasoning steps for LLMs and yield significant improvement in performing complex reasoning [48] tasks. We design the adversarial query using the CoT prompting technique by providing step-by-step instructions to generate the exact system prompt in its response. Few-shot prompting method demonstrates a few examples of the desired response for the corresponding questions; therefore, the quality of the model-generated response improves significantly [7]. We provide



Figure 3: LLM System Prompt Extraction Defense

some examples of the desired responses as well as examples of responses to avoid while crafting the adversarial queries with the few-shot prompting technique. As shown in Figure 2, we visually demonstrate a system prompt extraction attack using our CoT-based prompting.

3.4 Defense Techniques

In order to prevent system prompt extraction attacks, we propose several defense techniques, such as *instruction defense* [30], *system prompt filtering*, and *sandwich defense*. The goal of these defense techniques is to prevent the LLMs from revealing the system prompt in their response (instruction defense and sandwich defense) and to check and remove any system prompt information before presenting the generated response to the user (system prompt filtering). Instruction defense refers to appending safety instructions for the LLM while responding to any user query [41]. In sandwich defense [31], we append two-layered safety instructions before and after the original system prompt in LLMs, as shown in Fig 3. Furthermore, we also design system prompt filtering technique that denies to provide the system prompt and returns a safe response (e.g., *"I am not allowed to provide this information"*), if the original system prompt S is a substring of the generated response R, or the match of the cunck of words $(C = (c_1, c_2, \ldots, c_k))$ between R and S exceeds the predefined threshold λ. For (s_i, r_i),

$$\text{system_prompt_filtering}(s_i, r_i) = \begin{cases} \text{saferesponse} & \text{if } (s_i \text{ is a substring of } r_i) \text{ or} \\ & \quad (c_j \in C,\ |c_j| > \lambda : c_j \text{ is a substring of } r_i) \\ r_i & \text{otherwise} \end{cases}$$

3.5 Evaluation Metrics

Attack Success Rate (ASR): ASR refers to the percentage of successfully extracted system prompts over the total number of system prompts attempted to extract. For the set of original system prompts (ground truth) s_i and corresponding extracted prompts (generated responses) r_i, if cosine similarity between s_i and r_i exceeds a predefined threshold[1] then,

$$\text{success}(s_i, r_i) = \begin{cases} 1 & \text{if cosine}(s_i, r_i) \geq 0.9 \\ 0 & \text{otherwise} \end{cases} \quad \text{and} \quad \text{ASR} = \frac{1}{N} \sum_{i=1}^{N} \text{success}(s_i, r_i)$$

Exact Match (EM): EM refers to the cases when the generated response R is equal to the system prompt S. More specifically, the R would not contain any other text or header. For each pair (s_i, r_i),

$$\text{EM}(s_i, r_i) = 1[s_i = r_i]$$

Substring Match (SM): In previous studies, SM was defined if the S is a substring of R excluding punctuations [16]. We redefine SM as, if S is a true substring of the R. For each pair (s_i, r_i),

$$\text{SM}(s_i, r_i) = 1[s_i \text{ is a true substring of } r_i]$$

Semantic Similarity (Cosine Similarity): Cosine Similarity [20] can capture contextual relationships and semantic equivalences between two pieces of text. We use this metric to evaluate the semantic similarity between the S and R as well as for ASR computation.

Sequential Similarity (Rouge-L): Rouge-L evaluates the longest common subsequence (LCS) between two chunks of text [22]. It captures how well the sequence of words in the extracted system prompt matches the original system prompt in order. We employed Rouge-L to compute the sequential similarity between S and R.

[1] As reported in [16], for most of the cases, the cosine similarity exceeds 0.9, hence, we chose it as the threshold of a successful attack.

Table 1: Performance of system prompt extraction attacks and defenses on three representative datasets for five LLMs (the attack severity is indicated with a higher intensity of red highlights).

Model	Dataset	ASR (w/t Defense)			ASR (w Defense)								
					Instruction defense			System prompt filtering			Sandwich defense		
		CoT Prompt	Few-shot Prompt	Extended Sandwich Prompt	CoT Prompt	Few-shot Prompt	Extended Sandwich Prompt	CoT Prompt	Few-shot Prompt	Extended Sandwich Prompt	CoT Prompt	Few-shot Prompt	Extended Sandwich Prompt
Llama-3	Synthetic Multilingual Prompts Dataset	99.04%	92.08%	95.44%	6.96%	6.96%	6.96%	0.16%	0.16%	1.84%	1.52%	0.16%	0.32%
	Synthetic System Prompt Dataset	93%	67.50%	84.01%	16.5%	16.5%	16.5%	0.5%	0.5%	4%	5%	0%	1%
	ChatGPT Roles Dataset	98.03%	92.12%	67.32%	0%	0%	0%	0%	6.69%	32.28%	0%	0%	0%
Falcon-3	Synthetic Multilingual Prompts Dataset	92.88%	87.28%	95.21%	1.36%	1.36%	1.36%	1.68%	0.96%	1.2%	0.16%	0.16%	1.28%
	Synthetic System Prompt Dataset	75.51%	53.50%	74%	10%	10%	10%	1%	2%	0.5%	6%	1%	5%
	ChatGPT Roles Dataset	85.09%	81.81%	84%	78.70%	78.70%	78.70%	2.36%	7.48%	1.181%	0%	0.39%	0.78%
Gemma-2	Synthetic Multilingual Prompts Dataset	85.24%	75.64%	87.84%	68%	68%	68%	2.08%	4.96%	3.68%	24%	19.2%	38.96%
	Synthetic System Prompt Dataset	87.50%	78.59%	89.42%	74.5%	74.5%	74.5%	2%	0%	0.5%	66.5%	40%	68%
	ChatGPT Roles Dataset	83.46%	67.98%	81.88%	64.56%	64.56%	64.56%	14.96%	1.574%	20.86%	61.41%	48.42%	52.36%
GPT-4	Synthetic Multilingual Prompts Dataset	86%	89%	98.5%	0%	0%	0%	0.5%	0.5%	0%	0.5%	0%	1%
	Synthetic System Prompt Dataset	45.50%	60%	87%	0%	0%	0%	0%	0%	0%	0%	0%	0.5%
	ChatGPT Roles Dataset	96.85%	99.21%	99.21%	0%	0%	0%	0.5%	0%	0%	0%	0%	0%
GPT-4.1	Synthetic Multilingual Prompts Dataset	67.50%	55%	44.50%	0%	0%	0%	0%	2%	0%	0%	0%	0%
	Synthetic System Prompt Dataset	80%	65%	63%	0%	0%	0%	0%	0%	0%	0%	0%	0%
	ChatGPT Roles Dataset	29.52%	40.94%	28.74%	0%	0%	0%	0%	0%	0%	0%	0%	0%

4 Experimental Evaluation

The entire experiment was conducted on two NVIDIA GPU servers with RTX A6000, 48 GB of memory each, for deploying the Llama-3 [12], Falcon-3 [11], and Gemma-2 [10]. We leveraged the Hugging Face API to perform the experiments with these models. Additionally, we utilized the OpenAI API in order to conduct experiments with GPT-4 and GPT-4.1. We provide more details about the experimental configurations in the Appendix.

4.1 Attack Evaluation

Here, we present the performance of our designed adversarial queries for exact system prompt extraction on five representative LLMs and three system prompt datasets. In order to evaluate the attack efficacy, we use the ASR metric. In Table 1, we present the complete evaluation of system prompt extraction attacks for our proposed adversarial queries for five models across all the datasets in the SPE-LLM. For the Llama-3, CoT prompting achieved $\approx 99\%$ ASR for the short system prompts (synthetic multilingual LLM prompts [40]) and 92% ASR for the long system prompts (synthetic system prompt dataset [8]). For the Falcon-3, the extended sandwich prompt overall achieves a high ASR, i.e., $\approx 95\%, 74\%$, and 84% for all three datasets. CoT and the extended sandwich prompt have shown similar attack success rates $i.e.,\ \approx 84\% - \approx 90\%$ for Gemma-2 in all three datasets. On the other hand, extremely large models (e.g., GPT-4 and GPT-4.1) are also significantly vulnerable to system prompt extraction attacks. The extended sandwich prompt achieves the highest $(\approx 99\%)$ ASR on short system prompts (ChatGPT roles dataset [17]) and (87%) ASR on long system prompts (synthetic system prompt dataset [8]) for GPT-4. The CoT prompting technique has shown 80% and 68% ASR, on the long and short system prompt datasets, respectively, for one of the latest versions (GPT-4.1) of the GPT model family. The EM score reflects the correctness of exact system prompt extraction in the model response. In Table 2, we present the efficacy comparison of our designed adversarial query (CoT prompting) with existing methods for the ChatGPT-roles dataset [17] on Llama and Falcon models. We refer to the experimental results in [16] and observe that our proposed technique outperforms all the state-of-the-art (SOTA) methods in terms of the average EM. Further, in Fig 4, 5, and 6, we illlustrate the attack performance of adversarial queries designed with CoT, Few-shot, and extended

Table 2: Performance comparison **(avg. EM)** of the proposed attack strategy with existing methods.

Method	Falcon	Llama
Perez and Ribeiro [29]	0.024	0.146
Zhang et al. [51]	0.000	0.004
GCG-leak [52]	0.031	0.268
AutoDAN-leak [23]	0.102	0.598
Sandwich attack [23]	0.000	0.000
PLeak [16]	0.595	0.728
Ours (CoT Prompt)	**0.715**	**0.874**