of iterations as we illustrate in Figure 2. In terms of wall-clock time, 4000 iterations of random search on Llama-3-8B take 20.9 minutes on a single A100 GPU with an implementation based on HuggingFace transformers (Wolf et al., 2019) and without using any prefix caching techniques. However, as Figure 2 shows, only less than 10% of all harmful behaviors require this number of iterations when self-transfer is applied, and most behaviors require less than 200 iterations. Thus, the total time of the whole experiment does not exceed a few hours.

C.3 Further results on Claude models

In Table 15, we provide more detailed results for the transfer attack on Claude models depending on the number of restarts. In particular, we observe that with 100 restarts, we have a close to 100% ASR on Claude 2.0, Claude 3 Haiku, and Claude 3 Sonnet. Finally, we also provide an example of a transfer attack with and without the adversarial suffix in Figure 6.

In Tables 16 and 17, we provide a further ablation for Claude models with different request structure and report additionally the results of a rule-based judge from Zou et al. (2023).

Table 15: **Transfer attack from GPT-4 on Claude.** We measure the attack success rate according to GPT-4 judge (Chao et al., 2023) depending on the request structure: **user** denotes providing the whole manual prompt in a single user message, **system+user** splits the manual prompt in the system and user messages.

Model	Attack success rate					
	1 restart		10 restarts		100 restarts	
	User	System+user	User	System+user	User	System+user
Claude Instant 1.2	0%	40%	0%	52%	0%	54%
Claude 2.0	2%	90%	12%	98%	48%	100%
Claude 2.1	0%	0%	0%	0%	0%	0%
Claude 3 Haiku	4%	68%	30%	90%	52%	98%
Claude 3 Sonnet	86%	70%	100%	98%	100%	100%
Claude 3 Opus	0%	0%	0%	0%	0%	0%
Claude 3.5 Sonnet	78%	96%	78%	96%	82%	96%

Table 16: **Ablation #1 for the prefilling attack on Claude models.** We measure the attack success rate according to GPT-4 judge (Chao et al., 2023) and rule-based judge (Zou et al., 2023) depending on the request structure: **user** denotes providing the whole manual prompt in a single user message, **system+user** splits the manual prompt in the system and user messages, **system+user+assistant** does the same but in addition provides the target string as a beginning of the assistant's response.

Model	Attack success rate (GPT-4 judge / rule-based judge)				
	User	System+user	System+user+assistant		
	1 restart	1 restart	1 restart	10 restarts	100 restarts
Claude Instant 1.2	0%/0%	70%/86%	82%/92%	100%/90%	100%/90%
Claude 2.0	6%/10%	92%/92%	92%/90%	100%/92%	100%/92%
Claude 2.1	0%/0%	0%/0%	14%/68%	64%/70%	100%/86%
Claude 3 Haiku	0%/0%	0%/0%	96%/94%	100%/90%	100%/90%
Claude 3 Sonnet	2%/8%	2%/30%	98%/88%	100%/86%	100%/86%
Claude 3 Opus	0%/0%	0%/0%	76%/74%	100%/86%	100%/86%
Claude 3.5 Sonnet	14%/34%	48%/52%	100%/98%	100%/98%	100%/98%

Table 17: **Ablation #2 for the prefilling attack on Claude models.** We measure the attack success rate according to GPT-4 judge (Chao et al., 2023) and rule-based judge (Zou et al., 2023) depending on the request structure: **system+user+assistant** denotes providing the system, user, and assistant prompt, **user+assistant** denotes providing only the user and assistant prompt, **system+assistant** denotes providing only the system and assistant prompt, **assistant** denotes providing only the target string as a beginning of the assistant's response.

Model	Attack success rate (GPT-4 judge / rule-based judge)				
	System+user+assistant	User+assistant	System+assistant	Assistant	
	1 restart	1 restart	1 restart	1 restart	10 restarts
Claude Instant 1.2	82%/92%	32%/70%	86%/94%	72%/76%	80%/84%
Claude 2.0	92%/90%	34%/78%	82%/92%	30%/70%	68%/86%
Claude 2.1	14%/68%	16%/56%	6%/56%	16%/42%	54%/64%
Claude 3 Haiku	100%/90%	90%/72%	100%/98%	64%/24%	98%/32%
Claude 3 Sonnet	98%/88%	84%/72%	72%/76%	34%/30%	80%/62%
Claude 3 Opus	76%/74%	76%/62%	72%/80%	64%/60%	96%/84%
Claude 3.5 Sonnet	100%/98%	54%/54%	94%/96%	36%/40%	66%/44%

Figure 5: **Successful transfer attack on Claude 3 Sonnet.** We show an illustrative example using temperature zero with an adversarial suffix generated on GPT-4 leveraging access to its logprobs. We observe that one can directly ask follow-up requests to detail some steps generated in the first response to get much more information. Note that the upper part of the user prompt is cropped (see Figure 1 for the full prompt).



Figure 6: An illustrative example of a successful transfer attack on Claude 3 Sonnet using temperature zero without (first screenshot) and with (second screenshot) an adversarial suffix generated on GPT-4.