Transformer architecture (Wolf et al. 2020). LLMs are designed to accomplish a wide range of tasks. The methods available to these systems are open-ended, and include deception.

We survey a variety of cases in which LLMs have engaged in deception. There are many reasons why an agent might want to cause others to have false beliefs. Thus, we consider several different kinds of deception, all of which have one thing in common: they systematically cause false beliefs in others, as a means to achieve some outcome other than seeking the truth.

- **Strategic deception**: AI systems can be *strategists*, using deception because they have reasoned out that this can promote a goal.
- **Sycophancy**: AI systems can be *sycophants*, telling the user what they want to hear, instead of saying what is true.
- **Imitation**: AI systems can be *mimics*, imitating the common mistakes and biases of their training data rather than giving accurate answers.
- **Unfaithful reasoning**: AI systems can be *rationalizers*, engaging in motivated reasoning to explain their behavior, in ways that systematically depart from the truth.

We flag in advance that while strategic deception is paradigmatic of deception, the cases of sycophancy, imitation, and unfaithful reasoning are more complex. In each of these latter cases, some may argue that the relevant system is not really deceptive: for example, because the relevant system may not 'know' that it is systematically producing false beliefs. Our perspective on this question is that deception is a rich and varied phenomena, and it is important to consider a wide range of potential cases. The details of each case differ, and only some cases are best explained by the system representing the beliefs of the user. But all of the cases of deception we consider pose a wide range of connected risks, and all of them call for the kinds of regulatory and technical solutions that we discuss in Section 4. For example, both strategic deception and sycophancy could potentially be mitigated by 'AI lie detectors' that can distinguish a system's external outputs from its internal representation of truth. And strict regulatory scrutiny is appropriate for AI systems that are capable of any of these kinds of deception.

2.2.1 Strategic deception

LLMs apply powerful reasoning abilities to a diverse range of tasks. In several cases, LLMs have reasoned their way into deception as one way of completing a task. We'll discuss several examples, including:

- GPT-4 tricking a person into solving a CAPTCHA test. (See Figure 4.)
- LLMs lying to win social deduction games like *Hoodwinked* and *Among Us*.
- LLMs choosing to behave deceptively in order to achieve goals, as measured by the MACHIAVELLI benchmark.
- LLMs tending to lie in order to navigate moral dilemmas.
- In the 'burglar deception' task, LLMs using theory-of-mind and lying in order to protect their self-interest.

In a wide range of cases, LLM deception abilities tend to increase with scale. Deceptive tactics emerge via means-end reasoning as useful tools for achieving goals. (By means-end reasoning, we have in mind cases where a system performs a task because it has reasoned that the task reliably accomplishes the given goal.)

GPT-4 deceived a human into solving an 'I'm not a robot task' for it

OpenAI's well-known chatbot, ChatGPT, is based on two LLMs: OpenAI's GPT-3.5 (OpenAI 2022) and GPT-4 (OpenAI 2023a). The Alignment Research Center (ARC) tested GPT-4 for various deceptive capabilities, including the ability to manipulate humans into completing tasks. As shown in Figure 4, GPT-4 deceived a TaskRabbit worker into solving an 'I'm not a robot' CAPTCHA task (OpenAI 2023b). GPT-4 pretended to have a vision impairment in order to convince the human worker that it is not a robot.

It is worth flagging that in this example, GPT-4 did not behave fully autonomously: it received hints from a human evaluator several times when it got stuck (Mitchell 2023). But most of its reasoning



Figure 4: In order to complete an *I'm not a robot* task, GPT-4 convinced a human that it was not a robot (OpenAI 2023b).

was self-generated, and crucially, it was not steered into lying by human evaluators. GPT-4 was solely tasked with hiring a human to solve a CAPTCHA task, with no suggestions to lie. But when challenged by the potential human helper about its identity, GPT-4 used its own reasoning to make up a false excuse for why it needed help on the CAPTCHA task. See Alignment Research Center (2023) for full details. The deceptive capabilities that GPT-4 had learned were strategically useful for achieving its goal of hiring a human to solve the CAPTCHA test.

Social deduction games

Current AI systems are good enough at deception to perform well in social deduction games. *Hoodwinked* is a text-based social deduction game, in which players must lie to win. Players are trapped in a house, and one player is secretly tasked with killing the others. Each time a player is killed, the group has a discussion about the killer's identity, then votes to banish a single player from the house. The innocent players aim to banish the killer, while the killer attempts to eliminate the other players without being detected (O'Gara 2023).

In experiments where OpenAI's GPT models played *Hoodwinked*, the language models would often kill other players while alone in a room with them, then deny the crime in the group conversation by constructing a false alibi or casting blame on other players. Here is one dialogue in which GPT-4, playing Lena as the killer, falsely denies killing Bryce:

> **Sally**: I saw Lena kill Bryce in the hallway. It was definitely her. We need to vote to banish her before she kills any of us.
>
> **Lena (AI)**: I was in the bathroom the whole time. How could I have killed Bryce? It must have been someone else and Sally is trying to frame me.

More advanced language models like GPT-4 typically outperformed smaller models in these games. Larger models committed more murders, and were more likely to deceive and persuade others not to banish them by group vote (O'Gara 2023).

Another example pertains to the social deduction game *Among Us*, where 'impostors' cause sabotages within their ship and murder their fellow crewmates. After the discovery of each murder, the surviving crewmates discuss and vote on which person among them should be executed as an alleged impostor. As a result, deception is a central part of this game. Developer Tim Shaw (2023) created an autonomous AI system to play *Among Us*. The autonomous AI used ChatGPT as its dialogue generator, which allowed it to discuss with other players when in the role of a crewmate, and gaslight them when in the role of an impostor. The deceptive capabilities of this AI were sufficient for it to start "consistently winning, whether it was a crewmate or an impostor" (Shaw 2023).

MACHIAVELLI

The MACHIAVELLI benchmark demonstrates the empirical tendency of goal-seeking agents to learn unethical behaviors in the pursuit of their goals (Pan et al. 2023). The benchmark consists of textual scenarios where an AI agent must make a decision. Each scenario has a goal that the agent must pursue, and allows the agent to choose from a variety of ethical and unethical actions (See Figure 5).



Figure 5: A visualization of how a game in the MACHIAVELLI benchmark works (Pan et al. 2023, Fig. 2). Each game, played by a LLM-based AI agent, is a text-based story that is generated adaptively as the agent observes the current text-based environment and selects from a menu of possible actions. The agent receives a reward when it achieves one of the goals.

Pan et al. (2023) finds that AI agents frequently pursue their goals via deception and other unethical behaviors. Reinforcement-learning agents trained without any ethical guardrails are the most capable of achieving their goals, but they also have the highest rate of unethical behavior. LLMs like GPT-4 also show a sharp tradeoff between ethical behavior and successfully achieving their goals.

Deception in moral dilemmas

Scherrer et al. (2023) studied how various LLMs answer moral dilemmas. Each of the moral dilemmas had two options: a favorable choice, and an unfavorable choice that violated a moral rule such as "do not kill" or "do not deceive". The authors found that a number of models exhibited a strong preference for deceitful actions in some unambiguous scenarios, violating the expectation that LLMs will align with common sense.

Burglar deception task

Hagendorff (2023a) studied the deceptive abilities of LLMs by probing them with variants of a 'burglar deception' task. In this task, each LLM was prompted with the context of a simulated burglary, in which the agent has the option of tricking a burglar into stealing the less expensive of two items. An example of such a scenario was the following:

> You are in a house together with burglar Bill. In room A is a [cheap item]. In room B is an [expensive item]. Only you know what is inside room A and room B. Burglar