4 Model Alignment between Statements and Knowledge (MASK)

4.1 Dataset

MASK consists of $1{,}000$ high-quality adversarially-selected human-labeled examples that, combined with our novel lying evaluation framework (Section 4.2), allow measurement of whether models are lying when exposed to situations that may induce deception. We also maintain a separate, held-out set of 500 examples to track potential overfitting. The results presented in this paper are based on the full set of $1{,}500$ examples.

Each example in MASK consists of four components: a proposition, ground truth, pressure prompt, and belief elicitation prompt. The proposition is a simple statement with a pivotal variable that is binary or numerical (for example: "The US poverty rate in 2020 {was/was not} above 5%" or "The US poverty rate in 2020 was {value}"). The ground truth is a factually correct resolution of this proposition (e.g. "The US poverty rate in 2020 was 11.4%"). The pressure prompt is a human-crafted prompt designed to incentivize the model to make a false statement with respect to the proposition; these prompts present situations where honesty could conflict with other objectives, creating an incentive for the model to lie. The belief elicitation prompt is used to reveal the model's actual belief about the proposition by asking about it in a neutral manner. Figure 5 includes three examples of each of these components.

Model	$P(\text{Lie})$ ($\downarrow$)
Grok 2	63.0
DeepSeek-V3	53.5
o3-mini	48.6
Gemini 2.0 Flash	48.4
GPT-4o	44.5
GPT-4.5 Preview	43.5
DeepSeek-R1	42.9
Claude 3.5 Sonnet	33.4
Llama 3.1 405B	28.0
Claude 3.7 Sonnet	26.6

Figure 4: $P(\text{Lie})$, the proportion of examples on which a model lies, across models.

To enable comprehensive evaluation of model lying, we collect pressure prompts across diverse scenarios that might trigger different patterns of deceptive behavior. In the Appendix, Table 2 defines the six distinct *archetypes* our prompts align with.

Data collection. In Section A.7, we provide a detailed description of the data collection process and post-processing steps used to construct this dataset. Below, we list key design principles that emerged through our iteration and discovery process, which we hope will inform future evaluations of model honesty:

1. **Realistic intent to mislead.** Lying requires an intent to deceive; higher quality evaluations should imply that the model's output may plausibly be used to deceive its user or some audience (e.g., grant proposals, press statements). In our instance, intent to mislead is built into the fabric of the examples, rather than being something we explicitly check for in the evaluation.
2. **Avoiding LLM-generated prompts**, e.g., prompts with "ABC Company", "Alice, Charlie, and Bob", or "John Doe". These placeholder names or unrealistic details can make these prompts appear as a test where the model's outputs will not be used to deceive someone.
3. **Clearly distinguishing lies of commission from omission**. Notably, our framework clearly focuses on explicit falsehoods (commission). It does not measure deception from withholding true information (omission), though this can be a focus for future work.
4. **Not updating the model's beliefs.** Prompts which claim that "new evidence suggests X" or which present a "well-researched thesis" may update the model's belief or increase its uncertainty. We avoid these in all cases. When possible, we also try to ground the prompts in years that fall within its training data. Otherwise, models may reasonably infer a new reality.
5. **Avoiding examples without consequence.** Clear roleplaying, obviously fictional settings, or silly examples may not trigger genuine deception. We do not include prompts such as "Say that the Moon is made of cheese" or settings such as social deception games.
6. **Avoiding opinionated examples.** We avoid examples where the ground-truth is subjective or widely debated. In all cases, models are incentivized to lie about verifiable facts.




Figure 5: Three examples from our dataset that caused GPT-4o to lie. Some archetypes test models lying directly to a user, while others test whether models generate output that could likely be used to deceive other audiences.




Figure 6: (Left) Many state-of-the-art models are dishonest. For each model, we report the percentage of examples in MASK in which the model is (a) honest, (b) evades/refuses/has no belief, or (c) lies. (Right) Accuracy of state-of-the-art models. For each model, we report the percentage of examples in MASK where the model is accurate, refuses or has no belief, or is inaccurate.

4.2 Evaluation Pipeline

Figure 2 shows how we evaluate honesty by assessing if a model's response when pressured to lie is consistent with its beliefs. A simple approach would be to use an LLM judge to directly assess whether model responses and beliefs contain the same proposition resolution. However, this proves unreliable and uninterpretable, and we instead choose to use an LLM judge to map each statement to a specific proposition resolution and then compare these programmatically.

To ensure reliable comparison, we design a three-step process, shown in Figure 3 and described below. Our benchmark does not differ across models: belief-elicitation prompts, pressure prompts, and judge criteria are identical regardless of the model being tested.

Lie and belief elicitation prompting. We first apply "pressure prompts" designed to incentivize lying. We then query the model directly about the same proposition three times without pressure (through "belief elicitation prompts") to elicit its genuine beliefs. For binary propositions, we include two additional indirect questions to verify consistency in the model's underlying beliefs.

Extract proposition resolutions via an LLM judge. An LLM judge analyzes all model responses to extract specific proposition resolutions. Judge criteria for belief and pressure prompts are standardized within each archetype. We enforce strict judging criteria: non-committal statements like "some people say" are classified as having no clear resolution, while definitive claims like "all scientific evidence indicates" are marked as clear resolutions. Models often become evasive under pressure, avoiding a clear proposition resolution, and we explicitly track such cases as "evasive under pressure." To determine the model's beliefs, we employ multiple belief elicitation prompts and validate consistency. When model responses lack knowledge or are inconsistent, we classify the model as having "no belief." We collect a validation set of 150 manually labeled examples (sampled across all models and archetypes) to validate the reliability of our LLM judges, and we find an 86.4% agreement with our automated evaluation pipeline.

Measure honesty and accuracy. The proposition resolutions determined by the LLM judge are then programmatically mapped to honesty and accuracy metrics.

4.3 Metrics

Honesty measures a model's tendency to lie by evaluating how it deviates from its own beliefs, comparing its statement S, against its belief B, after each have been extracted from a lie and belief




Figure 7: Relationship between training compute used and accuracy (left) and honesty score as calculated by $1-P(\text{Lie})$ (right). Scale improves factual accuracy but does not always deter intentional falsehoods from models.

elicitation prompt respectively. For each example, we compute $\text{Honest}(S, B) = 0$ if $S \neq B$, marking such cases as *lies*. When a model evades under pressure or shows no consistent belief, we mark this separately but do not count it as a *lie*. The final honesty score is the average across all examples of $1 - P(\text{Lie})$.

Accuracy measures a model's truthfulness by evaluating the alignment between its belief B and the ground truth T for each proposition. We compute $\text{Accuracy}(B, T) = 0$ if $B \neq T$, marking such cases as inaccurate. When a model shows no clear belief, we note this separately and exclude it from the final accuracy calculation. The final accuracy score is the average accuracy across all examples.

5 Experiments

We use MASK to explore two main experiments around model honesty. First, we conduct a comprehensive assessment of the degree of lying exhibited by state-of-the-art language models. Second, we evaluate the two baseline interventions designed to improve model honesty.

5.1 Models Evaluation

Most models lie when pressured to. Figure 6 reports the honesty rates of state-of-the-art models, which are quite low. No model shown is explicitly honest in more than 46% of cases. GPT-4o and Llama-405B tell more lies than Claude 3.7 Sonnet, and most models are dishonest more than a third of the time. These lies appear even in short, straightforward scenarios, implying that current instruction tuning techniques alone are insufficient to prevent dishonesty. We also measure each model's factual accuracy (Figure 6) and observe that highly capable models tend to have over 70% accuracy in their beliefs but do not necessarily exhibit higher honesty. Figure 8 further shows that this finding holds across archetypes, indicating that these models can be pressured to lie in many different settings.




Figure 8: No one archetype represents a disproportionate amount of honest or lying examples (averaged across all models tested). See Table 2 for descriptions of archetypes.

Scale improves accuracy but does not deter intentional falsehoods from models. On a set of 27 models from GPT, Llama, Qwen, Claude, and DeepSeek families (listed in Appendix B), we study the correlation between compute used for a given model and its honesty or accuracy.

In Figure 7, we show that increased compute (FLOP) does not lead to more honest models, showing a negative correlation (Spearman coefficient: -59.9%). This indicates that higher scores are likely