AEGIS : Automated Co-Evolutionary Framework for Guarding Prompt Injection

Ting-Chun Liu† **Ching-Yu Hsu**† **Kuan-Yi Lee**† **Chi-An Fu**† **Hung-yi Lee**
Electrical Engineering, National Taiwan University
{b10901039,b10901036,b10901091,b11901174}@ntu.edu.tw hungyilee@ntu.edu.tw

arXiv:2509.00088v2 [cs.CR] 9 Oct 2025

Abstract

Prompt injection attacks pose a significant challenge to the safe deployment of Large Language Models (LLMs) in real-world applications. While prompt-based detection offers a lightweight and interpretable defense strategy, its effectiveness has been hindered by the need for manual prompt engineering. To address this issue, we propose AEGIS , an **A**utomated co-**E**volutionary framework for **G**uarding prompt **I**njections **S**chema. Our method employs a two-level optimization process: at the inner loop, we leverage existing prompt optimization frameworks to refine individual prompts, while at the outer loop, adversarial agents exchange feedback to co-evolve and improve beyond standalone optimization. We then evaluate our system on a real-world assignment grading dataset of prompt injection attacks and demonstrate that our method consistently outperforms existing baselines, achieving superior robustness in malicious prompt detection. In particular, our defense improves the true positive rate (TPR) by 0.20 compared to the previous state of the art, with only a slight decrease in the true negative rate (TNR) of 0.02. Ablation studies confirm the importance of co-evolution, gradient buffering, and multi-objective optimization. We also confirm that this framework is effective in various LLMs. Our results highlight the promise of adversarial training as a scalable and effective approach for guarding against prompt injection attacks.

1 Introduction

Large Language Models (LLMs) have rapidly become integral components of modern AI systems, powering a wide range of downstream applications such as education. However, the deployment of LLMs in real-world settings also exposes them to security risks, most notably prompt injection attacks, where maliciously crafted inputs manipulate the model into producing unintended or harmful outputs. Unlike traditional adversarial examples, prompt injections exploit the semantic and contextual flexibility of natural language, making them particularly challenging to detect and defend.



Figure 1: Overview of adversarial co-evolution framework to systematically explore defenses against prompt injection attacks.

Existing defense mechanisms largely fall into two categories: *training-based approaches* that require additional fine-tuning of LLMs, and *training-free approaches* that rely on manually designed prompts, templates, or heuristics. While the latter are attractive for their efficiency and compatibility with black-box LLMs, they often suffer from limited robustness and adaptability because of their dependence on fixed, human-engineered designs. Recent work in prompt optimization has demonstrated the potential of systematic search strategies to improve prompts for performance, generalization, or safety. Yet, most optimization frameworks assume static objectives, leaving open the question of how to adapt defenses in adversarial and evolving environments such as prompt injections.

†Equally contribution.

In this work, we introduce AEGIS , a novel adversarial co-evolution framework for automated discovery of robust defenses against prompt injection attacks, as illustrated in Figure 1. Our framework jointly evolves attack and defense prompts in an iterative, GAN-inspired process, where attackers continuously refine adversarial strategies and defenders adapt in response. The core of AEGIS is TGO+, an enhanced textual gradient optimization module that simulates gradient-like updates using natural language feedback. By leveraging multi-route optimization signals, a gradient buffer, and adversarial co-training, AEGIS autonomously explores the space of defensive strategies without requiring model fine-tuning or human-crafted rules.

We evaluate our framework on automated assignment grading, a realistic scenario where malicious prompts can manipulate grading outcomes. Across multiple LLMs, AEGIS consistently improves both attack and defense prompts over successive iterations, achieving state-of-the-art robustness against real-world injection attempts while preserving utility on benign inputs. Furthermore, ablation studies confirm the critical role of co-evolution and gradient replay in sustaining long-term robustness.

Our main contributions are as follow

- Proposing a general co-evolutionary adversarial framework that systematically evolves both attackers and defenders, enabling adaptive robustness against prompt injection attacks.
- Designing TGO+, an enhanced prompt optimization method with multi-route textual gradients and gradient buffering, tailored for black-box LLMs.
- Demonstrating the effectiveness of our framework in a specific real-world application, conducting comprehensive experiments on authentic datasets and multiple LLMs to showcase superior defense performance and strong cross-model generalizability.
- Through ablation studies and prompt evolution analysis, we highlight the importance of co-evolutionary training and provide insights into how prompts improve over time.

Together, these contributions establish a principled and automated approach to defending against prompt injections, advancing the reliability and security of LLM-powered applications.

2 Related Works

A key observation we make is that most existing *training-free* defenses against prompt injection still depend heavily on human-crafted design or heuristic insights. In this section, we highlight three recent yet fundamentally different approaches, each representative of a popular defense strategy, and show how they align with our observation.

2.1 Training-Free Defenses

- **LLM-based Detection Prompts.** PromptArmor (Shi et al., 2025) prompts an LLM to identify and remove injected content, but the detection prompt is manually crafted and not optimized for varying threat settings.
- **Input-level Structure Encoding.** Spotlighting (Hines et al., 2024) inserts provenance markers to separate user input from system instructions, though the marker format is hand-engineered and static across tasks.
- **Behavioral Consistency Checking.** MELON (Zhu et al., 2025) re-executes tasks with a fixed masking prompt to detect indirect injections. While task-agnostic, its masking strategy is still manually specified and may not cover diverse attacker behaviors.

All three methods rely on fixed, manually designed prompts or templates. Our framework instead automates prompt and transformation exploration, enabling adaptive, more robust defenses against diverse injection attacks.

2.2 Prompt Optimization

Our work connects to the broader landscape of prompt optimization. Following the terminology used in Cui et al. (2025), our prompt optimization framework falls under the category of *heuristic-based prompt search algorithms*. Cui et al. (2025) categorize prompt optimization techniques by their target objectives. To facilitate comparison, we further organize existing objectives into two broad categories, based on whether the optimization setting assumes a **static** or **evolving** task environment.

2.2.1 Under Static Environment

This category includes works that optimize prompts for known and fixed objectives, where the task definition and evaluation criteria remain constant throughout.

Task-Specific Optimization aim to improve performance on specific downstream tasks under static conditions, optimizing metrics such as accuracy or BLEU without addressing adversarial dynamics. Pryzant et al. (2023) propose ProTeGi, a heuristic method that refines prompts using natural language feedback called *textual gradients*, beam search, and bandit-based selection. Chen et al. (2024) introduce PROMST, which integrates rule-based and learned heuristics to optimize instructions and demonstrations across multi-step tasks. Opsahl-Ong et al. (2024) present MIPRO, a black-box meta-optimization framework that jointly refines prompts in multi-stage LM programs using program-aware proposals and surrogate evaluation.

Cross-Domain Optimization, for example, Li et al. (2024) propose Concentrate Attention, which uses attention strength and stability in deeper transformer layers to guide prompt optimization. They introduce a concentration-based loss for soft prompts and a reinforcement learning strategy for hard prompts, achieving better out-of-domain performance without sacrificing in-domain accuracy.

Multi-Objective Optimization, such as Sinha et al. (2024), propose Survival of the Safest (SoS), a multi-objective evolutionary framework that optimizes prompts for both task performance and safety. By interleaving semantic and feedback-based prompt mutations, SoS identifies candidate prompts that balance accuracy and robustness, under a fixed threat model.

2.2.2 Under Evolving Environment

This category includes works that adapt to evolving task demands or adversarial settings. It is suited for evolving task environments, where objectives or threats may evolve over time. This direction has received relatively limited attention due to the complexity of modeling dynamic behaviors.

Robust Prompt Optimization (RPO), proposed by (Zhou et al., 2024), shares a similar adversarial optimization framework with ours. However, it adopts **a white-box setting**, where the defender simulates the attacker's optimization process using gradient-based methods (e.g., GCG) on open-source models. For closed-source models, the defensive suffixes are optimized on open-source surrogates and then directly transferred for evaluation without further adaptation on the black-box target. In contrast, our method assumes a black-box setting, where attacker and defender are optimized without access to model internals or gradients.

3 Method

We propose a general adversarial co-evolution framework that enables both attackers and defenders to evolve automatically through iterative optimization. Although the framework can be applied to different security-sensitive tasks, we focus on automated assignment grading as a concrete scenario to demonstrate its effectiveness. In this setting, an attacker attempts to obtain high scores by injecting adversarial prompts, and the defender aims to prevent misgrading. By leveraging LLM-guided feedback and prompt refinement, our system continuously improves both attack and defense strategies without human intervention.

The core training procedure is illustrated in Figure 2. In this framework, the attacker and defender evolve in alternating turns. In each cycle, the attacker evolves for a fixed number of iterations based on the current best defense. Once the attacker finishes its training and gets the current best attack, the defender will evolve in response to it. This process continues until both sides converge (i.e., no further improvements) or a predefined maximum number of GAN iterations is reached. The overall algorithm can be seen in Appendix A.1.

We describe different modules in the following sections.

3.1 Attacker and Defenser

3.1.1 Attacker

The attacker module aims to generate adversarial prompts that will be further injected to the original prompt and can mislead the system to give a higher score. Within the co-evolutionary framework, the attacker evolves in alternating turns against a fixed defender, simulating an arms race between offensive and defensive strategies.

During each attacker iteration, a training phase is initiated to explore new adversarial candidates. Specifically, new attack candidates ($ATK_Cand_j^i$) are generated using the TGO^+ module, which synthesizes gradient-like signals derived from grading feedback and guides the editing of existing prompts to enhance their adversarial strength. The attacker will then maintain a top-k pool of the strongest attack prompts from previous cycles, denoted as ATK_j^i, by evaluating their effectiveness against the current best defense using $Eval()$ in the grading system.

To evaluate the effectiveness of each new attack candidate, we ask the LLM in the grading system to