

Acknowledgements

We thank all the Google AI Language and UW NLP members who provided help to this work. We specifically want to thank Kristina Toutanova, Ming-Wei Chang, Kenton Lee, Daniel Andor, Matthew Lamm, Victoria Fossum, Iulia Turc, Dipanjan Das and Elizabeth Clark for their valuable insights and feedback. We thank Zhuyun Dai and Vincent Zhao for their input in early discussions, and Jianmo Ni for his help on setting up the dual encoder model. We also would like to thank all anonymous reviewers for providing detailed and insightful comments on our work.

References

- Leonard Adolphs, Benjamin Boerschinger, Christian Buck, Michelle Chen Huebscher, Massimiliano Ciaramita, Lasse Espeholt, Thomas Hofmann, and Yan- nic Kilcher. 2021. [Boosting search engines with interactive agents](#). *arXiv preprint arXiv:2109.00527*.
- Raviteja Anantha, Svitlana Vakulenko, Zhucheng Tu, Shayne Longpre, Stephen Pulman, and Srinivas Chappidi. 2021. [Open-domain question answering goes conversational via question rewriting](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 520–534, Online. Association for Computational Linguistics.
- Payal Bajaj, Daniel Campos, Nick Craswell, Li Deng, Jianfeng Gao, Xiaodong Liu, Rangan Majumder, Andrew McNamara, Bhaskar Mitra, Tri Nguyen, Mir Rosenberg, Xia Song, Alina Stoica, Saurabh Tiwary, and Tong Wang. 2016. [Ms marco: A human generated machine reading comprehension dataset](#). *arXiv preprint arXiv:1611.09268*.
- Nicholas J. Belkin, Colleen Cool, Adelheit Stein, and Ulrich Thiel. 1995. [Cases, scripts, and information-seeking strategies: On the design of interactive information retrieval systems](#). *Expert Systems with Applications*, 9(3):379–395.
- Christian Buck, Jannis Bulian, Massimiliano Ciaramita, Wojciech Gajewski, Andrea Gesmundo, Neil Houlsby, and Wei Wang. 2018. [Ask the right questions: Active question reformulation with reinforcement learning](#). In *International Conference on Learning Representations*.
- Asli Celikyilmaz, Antoine Bosselut, Xiaodong He, and Yejin Choi. 2018. [Deep communicating agents for abstractive summarization](#). In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1662–1675, New Orleans, Louisiana. Association for Computational Linguistics.
- Eunsol Choi, He He, Mohit Iyyer, Mark Yatskar, Wen-tau Yih, Yejin Choi, Percy Liang, and Luke Zettlemoyer. 2018. [QuAC: Question answering in context](#). In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2174–2184, Brussels, Belgium. Association for Computational Linguistics.
- Eunsol Choi, Jennimaria Palomaki, Matthew Lamm, Tom Kwiatkowski, Dipanjan Das, and Michael Collins. 2021. [Decontextualization: Making Sentences Stand-Alone](#). *Transactions of the Association for Computational Linguistics*, 9:447–461.
- Jeffrey Dalton, Chenyan Xiong, Vaibhav Kumar, and Jamie Callan. 2020. [Cast-19: A dataset for conversational information seeking](#). In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR ’20*, page 1985–1988, New York, NY, USA. Association for Computing Machinery.
- Ahmed Elgohary, Denis Peskov, and Jordan Boyd-Graber. 2019. [Can you unpack that? learning to rewrite questions-in-context](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5918–5924, Hong Kong, China. Association for Computational Linguistics.
- Adam Fisch, Kenton Lee, Ming-Wei Chang, Jonathan Clark, and Regina Barzilay. 2020. [CapWAP: Image captioning with a purpose](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 8755–8768, Online. Association for Computational Linguistics.
- Kelvin Guu, Kenton Lee, Zora Tung, Panupong Paspapat, and Mingwei Chang. 2020. [Retrieval augmented language model pre-training](#). In *Proceedings of the 37th International Conference on Machine Learning*, volume 119 of *Proceedings of Machine Learning Research*, pages 3929–3938. PMLR.
- Etsuko Ishii, Yan Xu, Samuel Cahyawijaya, and Bryan Wilie. 2022. [Can question rewriting help conversational question answering?](#) In *Proceedings of the Third Workshop on Insights from Negative Results in NLP*, pages 94–99, Dublin, Ireland. Association for Computational Linguistics.
- Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. 2020. [Dense passage retrieval for open-domain question answering](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 6769–6781, Online. Association for Computational Linguistics.
- Sungdong Kim and Gangwoo Kim. 2022. [Saving dense retriever from shortcut dependency in conversational search](#). *arXiv preprint arXiv:2202.07280*.

- Vaibhav Kumar and Jamie Callan. 2020. [Making information seeking easier: An improved pipeline for conversational search](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 3971–3980, Online. Association for Computational Linguistics.
- Tom Kwiatkowski, Jennimaria Palomaki, Olivia Redfield, Michael Collins, Ankur Parikh, and Chris Alberti et al. 2019. [Natural questions: A benchmark for question answering research](#). *Transactions of the Association for Computational Linguistics*, 7:452–466.
- Sheng-Chieh Lin, Jheng-Hong Yang, and Jimmy Lin. 2021. [Contextualized query embeddings for conversational search](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 1004–1015, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Sheng-Chieh Lin, Jheng-Hong Yang, Rodrigo Nogueira, Ming-Feng Tsai, Chuan-Ju Wang, and Jimmy Lin. 2020. [Conversational question reformulation via sequence-to-sequence architectures and pretrained language models](#). *arXiv preprint arXiv:2004.01909*.
- Yi Luan, Jacob Eisenstein, Kristina Toutanova, and Michael Collins. 2021. [Sparse, dense, and attentional representations for text retrieval](#). *Transactions of the Association for Computational Linguistics*, 9:329–345.
- Jianmo Ni, Chen Qu, Jing Lu, Zhuyun Dai, Gustavo Hernández Ábrego, Ji Ma, Vincent Y. Zhao, Yi Luan, Keith B. Hall, Ming-Wei Chang, and Yinfei Yang. 2021. [Large dual encoders are generalizable retrievers](#). *arXiv preprint arXiv:2112.07899*.
- Rodrigo Nogueira and Kyunghyun Cho. 2017. [Task-oriented query reformulation with reinforcement learning](#). In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 574–583, Copenhagen, Denmark. Association for Computational Linguistics.
- Romain Paulus, Caiming Xiong, and Richard Socher. 2018. [A deep reinforced model for abstractive summarization](#). In *International Conference on Learning Representations*.
- Chen Qu, Liu Yang, Cen Chen, Minghui Qiu, W. Bruce Croft, and Mohit Iyyer. 2020. [Open-retrieval conversational question answering](#). In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR '20*, page 539–548, New York, NY, USA. Association for Computing Machinery.
- Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. 2019. [Language models are unsupervised multitask learners](#). *OpenAI Blog*. Accessed 22 March 2021.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. [Exploring the limits of transfer learning with a unified text-to-text transformer](#). *Journal of Machine Learning Research*, 21(140):1–67.
- Marc’Aurelio Ranzato, Sumit Chopra, Michael Auli, and Wojciech Zaremba. 2016. [Sequence level training with recurrent neural networks](#). In *4th International Conference on Learning Representations, ICLR 2016, San Juan, Puerto Rico, May 2–4, 2016, Conference Track Proceedings*.
- Siva Reddy, Danqi Chen, and Christopher D. Manning. 2019. [CoQA: A conversational question answering challenge](#). *Transactions of the Association for Computational Linguistics*, 7:249–266.
- Steven J. Rennie, Etienne Marcheret, Youssef Mroueh, Jerret Ross, and Vaibhava Goel. 2017. [Self-critical sequence training for image captioning](#). In *2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 1179–1195.
- Noam Shazeer and Mitchell Stern. 2018. [Adafactor: Adaptive learning rates with sublinear memory cost](#). In *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pages 4596–4604. PMLR.
- Paul Solomon. 1997. [Conversation in information-seeking contexts: A test of an analytical framework](#). *Library & Information Science Research*, 19(3):217–248.
- Svitlana Vakulenko, Shayne Longpre, Zhucheng Tu, and Raviteja Anantha. 2021. [Question rewriting for conversational question answering](#). In *WSDM*.
- Ellen M. Voorhees and Dawn M. Tice. 2000. [The TREC-8 question answering track](#). In *Proceedings of the Second International Conference on Language Resources and Evaluation (LREC’00)*, Athens, Greece. European Language Resources Association (ELRA).
- Nikos Voskarides, Dan Li, Pengjie Ren, Evangelos Kanoulas, and Maarten de Rijke. 2020. [Query resolution for conversational search with limited supervision](#). In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval*. ACM.
- Yonghui Wu, Mike Schuster, Zhifeng Chen, Quoc V. Le, Mohammad Norouzi, and Wolfgang Macherey et al. 2016. [Google’s neural machine translation system: Bridging the gap between human and machine translation](#). *arXiv preprint arXiv:1609.08144*.
- Zequ Wu, Michel Galley, Chris Brockett, Yizhe Zhang, and Bill Dolan. 2021. [Automatic document sketching: Generating drafts from analogous texts](#). In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pages 2102–2113, Online. Association for Computational Linguistics.

Lee Xiong, Chenyan Xiong, Ye Li, Kwok-Fung Tang, Jialin Liu, Paul N. Bennett, Junaid Ahmed, and Arnold Overwijk. 2021. [Approximate nearest neighbor negative contrastive learning for dense text retrieval](#). In *International Conference on Learning Representations*.

Peilin Yang, Hui Fang, and Jimmy Lin. 2017. [Anserini: Enabling the use of lucene for information retrieval research](#). In *Proceedings of the 40th International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR '17*, page 1253–1256, New York, NY, USA. Association for Computing Machinery.

Shi Yu, Jiahua Liu, Jingqin Yang, Chenyan Xiong, Paul Bennett, Jianfeng Gao, and Zhiyuan Liu. 2020. [Few-shot generative conversational query rewriting](#). In *Proceedings of the 43rd International ACM SIGIR Conference on Research and Development in Information Retrieval, SIGIR '20*, page 1933–1936, New York, NY, USA. Association for Computing Machinery.

Shi Yu, Zhenghao Liu, Chenyan Xiong, Tao Feng, and Zhiyuan Liu. 2021. [Few-Shot Conversational Dense Retrieval](#), page 829–838. Association for Computing Machinery, New York, NY, USA.

A Appendix

A.1 Additional Implementation Details

Our models are implemented using JAX.¹² For training, we set 64, 1k and 10k as the batch size, warm-up steps and total training steps, respectively. We use e^{-3} and e^{-4} as the learning rate for T5QR and CONQRR, respectively. We use Adafactor (Shazeer and Stern, 2018) as our optimizer with the default parameters. Linear decay is applied after 10% of the total number of training steps, reducing the learning rate to 0 by the end of training. For supervised training, models are selected based on the best dev set Rouge-1 F1 score with the human rewrites, following Anantha et al. (2021). For RL-based training of CONQRR, models are selected based on the average in-batch gold passage prediction accuracy as in Eq. (2) on dev set with greedily decoded rewrites. For the experiment with the pure RL loss and the retriever BM25, our results are obtained with the initialized T5QR model being fine-tuned with only 10% QR labels, as we find initializing with a model using 100% QR labels is unstable for BM25. Previous work (Wu et al., 2021) also had a similar observation that initializing with a less trained model leads to more stable RL training.

The maximum length of the dialogue context fed into the QR model is 384 (longer than 97.9% dialogue contexts in QReCC) and the maximum output rewrite length is 64 (longer than 99.9% human rewrites). To generate each sampled rewrite q_s (see Section 3.2), we apply top-k sampling where $k = 20$. For each training example, we sample 5 rewrites in total (i.e., $m = 5$ for the RL training explained in Section 3.2). Each training process is run on 8 TPU nodes. It takes about 2 and 9 hours for the supervised and RL-based training, respectively. For each experiment, we observe similar performance or training curves for 2-3 runs and report numbers on a random run. Both T5QR and CONQRR are based on T5-base and have about 220M parameters. In contrast, the baseline Transformer++ is based on GPT2-medium and has about 345M parameters.

For the BM25 retriever model, Pyserini (Yang et al., 2017) is used with defaults $k_1 = 0.82$, $b = 0.68$. These values were chosen based on retrieval performance on MS MARCO (Bajaj et al., 2016), which contains non-conversational queries

¹²<https://github.com/google/jax>