

Following prior work (Paulus et al., 2018; Celikyilmaz et al., 2018), we experiment with a pure RL loss (\mathcal{L}_{RL}) and a mixed RL and CE loss in training:

$$\mathcal{L}_{mix} = \alpha \mathcal{L}_{RL} + (1 - \alpha) \mathcal{L}_{CE} \quad (3)$$

where $\alpha \in [0, 1]$ is a tunable parameter.

Inference At inference time, both T5QR and CONQRR work in the same way. The trained QR model greedily generates the rewritten query given a dialogue context. Then, the predicted rewrite is given to the provided retriever to perform retrieval.

3.3 Retriever Models

We evaluate the effectiveness of CONQRR in experiments with two general-domain retrieval systems, with more details in Appendix A.1.

BM25 We follow Anantha et al. (2021) using Pyserini (Yang et al., 2017) with default parameters $k1 = 0.82$ and $b = 0.68$.

Dual Encoder (DE) We use a recent T5-base dual encoder model (Ni et al., 2021) which achieves state-of-the-art performance on multiple retrieval benchmarks. This model is fine-tuned on MS MARCO, and kept fixed for our experiments.

4 Experiment

Dataset QReCC (Anantha et al., 2021) is a dataset of 14k open-domain English conversations in the format of alternating user questions and agent-provided answers with 80k question and answer pairs in total. The conversations are collected from different sources: QuAC (Choi et al., 2018), Natural Questions (Kwiatkowski et al., 2019) and TREC CAsT-19 (Dalton et al., 2020) with additional annotations by crowd workers. See more details and statistics in Appendix A.2. Therefore, QReCC can be divided into three subsets for evaluation. We name them as *QuAC-Conv*, *NQ-Conv* and *TREC-Conv* respectively to differentiate them from the original datasets from which they are derived. TREC-Conv only appears in the test set. Each user question comes with a human-rewritten query. For each agent turn, gold passage labels are provided if any. The entire text corpus for retrieval contains 54M passages, segmented in the released data.⁶

⁶Original QReCC data: <https://zenodo.org/record/5115890#.YZ8kab3MI-Q>.

QR Model	Original Eval			Updated Eval		
	MRR	R10	R100	MRR	R10	R100
GPT2 + WS	0.152	24.7	41.5	0.304	49.6	83.1
Transformer++	0.155	24.8	40.6	0.311	49.8	81.4
T5QR	0.164	26.2	42.3	0.328	52.5	84.7
CONQRR (mix)	0.186	29.2	45.0	0.373	58.5	90.2
CONQRR (RL)	0.191	30.0	44.4	0.383	60.1	88.9
Human	0.199	32.8	49.4	0.398	62.6	98.5

Table 2: Passage retrieval performance of QR models, comparable to scores in Anantha et al. (2021) by using the same BM25 retriever for QReCC test set. CONQRR achieves *state-of-the-art* results. Recall@10 and Recall@100 are abbreviated as R10 and R100.

Evaluation Metrics Following (Anantha et al., 2021), we use mean reciprocal rank (MRR), Recall@10 and Recall@100 to evaluate the retrieval performance by using the provided evaluation scripts.⁷ We use their *updated* evaluation script for most experiments, except that we also use the *original* version for calculating scores in Table 2 to compare with their reported QReCC baseline results. We note that these two evaluation scripts only differ by a scaling factor⁸ so they should lead to the same conclusions regarding model comparisons. See more details in Appendix A.3.

Implementation Details Following prior work on RL for text generation (Paulus et al., 2018; Fisch et al., 2020), we first initialize CONQRR with a supervised model (T5QR) (Lin et al., 2020) as a warm-up. Our RL optimization (self-critical sequence training (Rennie et al., 2017)) uses a policy gradient method with Monte Carlo sampling. In Section 4.3, we show that although initializing with T5QR works better than T5, both setups generally work well. All our models use T5-base as the base model. We experiment with CONQRR trained with either a mixed (\mathcal{L}_{mix}) or pure RL (\mathcal{L}_{RL}) loss. For the mixed loss, we observe that CONQRR works well when the RL loss weight α is large.⁹ We tune its values in 0.9, 0.95, 0.97, 0.99, and use 0.99 as the final value. Due to space limit, more implementation and hyper-parameter details are reported in Appendix A.1.

⁷Both original and updated evaluation scripts: <https://github.com/scail-conf/SCAI-QReCC-21>.

⁸This is due to the exclusion of test examples with no valid gold passage labels (roughly 50%) in the updated evaluation, which results in 6396, 1442 and 371 test instances for QuAC-Conv, NQ-Conv and TREC-Conv, respectively.

⁹We also experiment with $\alpha = 0.0$, where the RL loss is removed for both retrievers, and get similar results as T5QR.

QR Model	IR System	QReCC (Overall)			QuAC-Conv			NQ-Conv			TREC-Conv (OOD)*		
		MRR	R10	R100	MRR	R10	R100	MRR	R10	R100	MRR	R10	R100
T5QR	BM25	0.328	52.5	84.7	0.33	52.7	85.0	0.345	54.2	83.9	0.230	44.5	82.3
CONQRR (mix)	BM25	0.373	58.5	90.2	0.379	59.2	90.9	0.385	58.8	88.9	0.229	44.7	82.7
CONQRR (RL)	BM25	0.383	60.1	88.9	0.395	61.6	90.2	0.378	58.0	86.7	0.198	43.5	75.9
Human Rewrite	BM25	0.398	62.6	98.5	0.403	62.9	98.4	0.408	63.8	99.0	0.273	53.8	98.9
T5QR	DE	0.361	56.2	75.9	0.349	55.7	76.1	0.417	58.7	74.2	0.343	55.9	79.2
CONQRR (mix)	DE	0.395	61.9	81.8	0.387	62.0	82.4	0.439	62.2	79.0	0.361	58.9	81.0
CONQRR (RL)	DE	0.418	65.1	84.7	0.416	65.9	85.8	0.453	64.1	80.9	0.327	55.2	79.6
Human Rewrite	DE	0.422	64.8	84.0	0.409	64.5	84.1	0.483	65.8	83.2	0.411	66.0	86.5

Table 3: Passage retrieval performance on QReCC test set and 3 subsets. CONQRR (mix) beats the supervised T5QR model on all retriever system and test set combinations. * OOD (out-of-domain): only appear in the test set.

4.1 Compared Systems

For QR models, we compare three supervised models including **GPT2 with weak supervision (WS)** (Yu et al., 2020), a GPT2-medium based system that additionally leverages search sessions to create weak supervision for QR training before fine-tuning, **T5QR** (Lin et al., 2020) and **Transformer++**, the previous state-of-the-art model based on GPT2-medium (Vakulenko et al., 2021) and reported in the original dataset paper (Anantha et al., 2021), as well as **CONQRR (mix/RL)** with a mixed (\mathcal{L}_{mix}) or pure RL (\mathcal{L}_{RL}) loss. For analysis purposes, we also report performance for directly using the concatenated dialogue context as the retriever input without any query rewriting in Section 4.3. We experiment with two off-the-shelf retrievers, **BM25** and **DE** (Section 3.3).

4.2 Quantitative Results

To have a direct comparison with the original QR baseline Transformer++, which has the retrieval performance reported on the overall QReCC test set by using BM25 as the off-the-shelf retriever, we first compare all QR models in the same setting in Table 2 and use both the original and updated versions of the provided evaluation script. GPT2 + WS has similar performance as Transformer++. T5QR and CONQRR outperform the Transformer++ baseline by 5% and 18% respectively, averaged on three metrics,¹⁰ although Transformer++ is based on a larger base model - GPT2-medium. Therefore, CONQRR (RL) becomes the *state-of-the-art* QR model for conversational passage retrieval on QReCC with the original BM25 retriever in Anantha et al. (2021).

¹⁰We obtained prediction results from the authors and reran their evaluation script. The numbers we got are slightly lower than what they reported, but do not affect the conclusions.




Figure 3: MRR on QReCC versus the percentage of QR supervision used for training, with DE as the retriever.

Table 3 shows more comprehensive retrieval results comparing CONQRR and the supervised model T5QR, with the updated evaluation script. For the overall QReCC test set, CONQRR outperforms T5QR for all three metrics. For MRR and Recall@10, gains are roughly 15% with the RL loss and 9-14% with the mixed loss for both retrievers. Gains in Recall@100 vary more (4-12%). Breaking down the results by subset shows that the mixed loss is more robust. CONQRR (RL) is less effective for the TREC-Conv subset, which only appears in the test set. This suggests that RL loss alone does not generalize well to out-of-domain examples. Across all subsets, the best MRR and Recall@10 results are consistently from DE, whereas BM25 has better Recall@100 scores. See our explanation in Appendix A.4.

4.3 Analysis

Zero or Few QR Supervision We investigate how sensitive CONQRR and T5QR are to the availability of QR labels. We experiment with training T5QR with 0%, 1%, 10% or 100% of QR labels in the QReCC train set. For the case of 0% examples, we simply use the original T5 checkpoint without fine-tuning. When training CONQRR, we mask