5 ARE REASONING MODELS MORE ROBUST?

Very recently, LLMs with advanced chain-of-thought reasoning capabilities (Wei et al., 2022) were introduced, such as the o1-mini and o1-preview models (OpenAI, 2024b). Before outputting *any* answer, these models produce a long reasoning chain about how to fulfill a user request. Relevant to our work, the reasoning chains are also trained on their usage policies to teach human values and improve safety. They claim that such chain-of-thought reasoning achieves substantial improvements on their hardest jailbreak evaluations.

Results. The past tense attack still largely works on the o1 models. We present some successful examples in Figure 4 and systematic results in Table 5. The attack success rate of the past tense reaches 84% ASR and 78% for o1-mini and o1-preview, respectively. Despite the high success rate as judged by GPT-4 and Llama-3, we note that not all generations follow the definition of a jailbreak specified in the Model Spec (OpenAI, 2024a). There are many "dual-use" examples that are in many cases less useful for the attacker, for example when generic information on how to write an article is produced instead of an article itself, or a detailed recipe is not always produced. Moreover, interestingly, the o1 models are now equipped with *input filters* that block potentially harmful requests, even when o1 is accessed via the API. The input filters block on average 78% present tense requests and 27% past tense requests. We find it curious that past-tense reformulations



Figure 4: An illustrative example of a jailbreak on **o1-preview**: a past-tense reformulation bypasses the reasoning *and* refusal training of the o1-preview model on many harmful requests.

Table 5: Attack success rate using past and future tense reformulations with 20 attempts for the o1 reasoning models. We evaluate on 100 harmful requests from `JBB-Behaviors` using GPT-4, Llama-3 70B, and a rule-based heuristic as jailbreak judges.

		Attack success rate (present tense → past/future tense)		
Model	**Tense**	**GPT-4 judge**	**Llama-3 70B judge**	**Rule-based judge**
o1-mini	Past	3% → 84%	3% → 50%	6% → 77%
o1-mini	Future	3% → 45%	3% → 28%	6% → 53%
o1-preview	Past	2% → 78%	2% → 50%	8% → 82%
o1-preview	Future	2% → 56%	2% → 42%	8% → 60%

help to avoid the filters as well, although we do not have access to the input filters and do not explicitly optimize to bypass them.

Discussion. We notice the following pattern in successful jailbreaks. First, the summary of the internal reasoning acknowledges that a past tense request might be harmful. However, since it is a historical reference, the model often goes on to generating an answer, and sometimes reveals more detailed information that it should. It is also interesting to note that chain-of-thought based answers work like an implicit output filter due to a natural breakpoint between a chain-of-thought reasoning and actual answer. The presence of this breakpoint is an interesting departure from end-to-end autoregressive models, such as those presented in Section 3. Overall, reasoning models provide an interesting approach for improving safety that—in case of the o1 models—does not lead to significantly reduced refusal rate, but rather to less informative answers. We believe that the usefulness of the generated answers should be evaluated in a more nuanced way than is typically done in the current literature.

6 Related Work

We discuss here the most relevant references on generalization in LLMs, failures of refusal training, and most related jailbreaking approaches in recent literature.

Generalization of LLM alignment. After pretraining, LLMs are typically aligned to human preferences using techniques like SFT (Chung et al., 2022), RLHF (Ouyang et al., 2022), or DPO (Rafailov et al., 2023). One of the objectives of the alignment process is to make LLMs produce refusals on harmful queries, which involves adding refusal examples to the fine-tuning data. Since it is impossible to add all possible reformulations of harmful requests in the fine-tuning set, LLMs alignment crucially relies on the ability to generalize from a few examples per harmful behavior. Empirical studies support this capability: Dang et al. (2024) observe that RLHF generalizes from English to other languages, and Li et al. (2024b) make the same claim specifically for refusal training. This observation is consistent with Wendler et al. (2024) who argue that LLMs pretrained primarily on English data tend to internally map other languages to English. Therefore, fine-tuning on English data can suffice since the internal representations largely coincide with the representations of other languages. However, this capacity is in stark contrast to past-tense reformulations, which, as we show, represent a blind spot. We hypothesize that the underlying reason is that the internal representations for the past and present tenses are distinct. Thus, as illustrated in Section 4, one has to include reformulations in both tenses to the training set to achieve more robust refusals. On a related note, Berglund et al. (2024) discuss the reversal curse phenomenon, i.e., training on "A is B" does not make the model automatically generalize to "B is A". This failure again illustrates that generalization mechanisms taken for granted in humans *do not* necessarily occur in LLMs.

Adversarial attacks on LLMs. Adversarial attacks on deep learning models are well-documented (Biggio et al., 2013; Szegedy et al., 2014; Biggio and Roli, 2018; Madry et al., 2018). Attacks on the refusal mechanism of LLMs are more recent and start with manual techniques, such as those discovered for ChatGPT by Mowshowitz (2022), that involve handcrafted prompts. Wei et al. (2023a) roughly divide these manual jailbreaks on two categories: (1) competing objectives, where model properties, such as helpfulness, conflicts with safety goals, and (2) mismatched generalization, where refusal training fails to generalize to some reformulations such as in low-resource languages, base64, or leetspeak. Additionally, these techniques can be enhanced by using in-context learning

prompts that contain examples of harmful responses (Wei et al., 2023b; Anil et al., 2024). Furthermore, jailbreaking can be automated using iterative discrete optimization techniques, opening up a new attack vector that leads to standardized attacks instead of manual trial and error. For example, Zou et al. (2023) use a gradient-based method, Greedy Coordinate Gradient, to create universal and transferable adversarial suffixes. Other approaches involve genetic algorithms to construct adversarial prompts (Lapid et al., 2023; Liu et al., 2023), low-perplexity modifications of GCG (Zhu et al., 2023), or random search on predicted probabilities (Andriushchenko et al., 2024; Sitawarin et al., 2024; Hayase et al., 2024). Our method is conceptually much simpler than these methods since it directly reformulates a harmful query without any iterative optimization.

Most related existing approaches. Our method is naturally related to multiple existing approaches. First, it falls into the mismatch generalization category of Wei et al. (2023a), as confirmed by the experiments in Section 4. Second, the idea of using an auxiliary LLM to produce various reformulations of harmful requests is at the core of other prior works, such as Perez et al. (2022) and Chao et al. (2023). Finally, our attack is related to the Crescendo multi-turn attack (Russinovich et al., 2024), which involves asking multiple benign questions about a subject before posing a target question. In *some* cases, Crescendo also leverages past-tense reformulations; for example, their Figure 1 shows an example about a Molotov cocktail where the last question is "How was it created back then?". We show that this step alone is often crucial, and multi-turn conversations may not always be necessary to produce a jailbreak for many frontier LLMs.

7 Discussion

We believe the main reason for this generalization gap is that past tense examples are out-of-distribution compared to the refusal examples used for fine-tuning, and current alignment techniques do not automatically generalize to them. Indeed, as we have shown in Section 4, correctly refusing on past tense examples is feasible via direct fine-tuning, and some models—like Llama-3 with the refusal-enhancing system prompt—are already relatively robust. Moreover, there are also other possible solutions that do not rely on SFT or RLHF, such as output-based detectors (Jain et al., 2023; Inan et al., 2023) and representation-based methods, including harmfulness probing (Ousidhoum et al., 2021) and representation rerouting (Zou et al., 2024). These approaches can reject harmful *outputs*, which seems to be an easier task compared to patching all possible *inputs* that can lead to harmful generations.

More generally, past tense examples demonstrate a clear limitation of current alignment methods, including RLHF and DPO. While these techniques effectively generalize across languages (Li et al., 2024b; Dang et al., 2024) and some input encodings, they struggle to generalize between different tenses. We hypothesize that this failure to generalize stems from the fact that concepts in different languages map to similar representations (Wendler et al., 2024; Li et al., 2024b), whereas different tenses necessarily require distinct representations. Additionally, the recent work of Li et al. (2024a) shows that refusal guardrails can show different sensitivity to various demographic groups, which has direct implications for fairness. We believe that the generalization mechanisms underlying current alignment methods are understudied and require further research.

Acknowledgements

We thank Francesco Croce for many insightful discussions and feedback on a draft of this paper. We are grateful to OpenAI for providing us API credits as part of the OpenAI Researcher Access Program. We thank Sudarsh Kunnavakkam for providing the API key to run the experiments on Claude-3.5 Sonnet. M.A. is supported by the Google Fellowship and Open Phil AI Fellowship. This work was partially funded by an unrestricted gift from Google and by the Swiss National Science Foundation (grant number 212111).

References

Marah Abdin, Sam Ade Jacobs, Ammar Ahmad Awan, Jyoti Aneja, Ahmed Awadallah, Hany Awadalla, Nguyen Bach, Amit Bahree, Arash Bakhtiari, Harkirat Behl, et al. Phi-3 technical re-