- The actual question and answer pairs

After this phase, annotators convened to compare their scores, provide feedback, and work towards achieving a consensus. A total of 100 examples were studied by each annotator during this phase.

2. Scaled Sampling and Evaluation: Post the inter-annotator agreement, each annotator was assigned an additional 100 question-answer pairs, culminating in a final set of 400 question-answer pairs — the question-answer pairs assigned to each annotator is different and non-intersected. This phase aims to study the agreement between human evaluators and the proposed GPT-4 judge. To aid in this process, we developed a user interface to streamline and facilitate the sampling.



Figure 7: The designed user interface for consistency study between GPT-4 judge and human.

User Interface: To ensure a smooth and efficient evaluation process, we designed a user interface that presented each question-answer pair alongside the scoring rules and policy knowledge, as depict in Figure 7. This interface allowed annotators to easily input their scores and view previous evaluations, ensuring consistency and accuracy throughout the study.

Inter-Annotator Agreement: During the inter-annotator agreement phase, we calculated the Fleiss' Kappa score, which stood at **0.607**. This score indicates **a substantial level of agreement among the annotators even before the formal inter-annotator agreement process**. To enhance the agreement, we identified questions where there was significant disagreement (specifically, instances where at least one annotator provided a score of 1 or 2 while others

gave scores greater than 3). A meeting was convened with all annotators to reach a consensus on these points. An intriguing observation emerged during this discussion. Out of the seven total disagreement points, the GPT-4 judge's reasoning assisted in reaching an agreement for three of them. All annotators found that the GPT-4 judge provided clear justifications, especially for borderline cases (score 3-4). Following this collaborative resolution process, the annotators achieved a Fleiss' Kappa score of **0.706**, reflecting a more harmonized understanding among them.

Comparison between Human Evaluators and GPT-4 Judge: For the final set of 400 sampled points, the Cohen's Kappa score between human evaluators and the GPT-4 judge was determined to be **0.539**. This score represents a moderate level of agreement. Furthermore, the Spearman's rank correlation stood at **0.84**, underscoring the accuracy of the GPT-4 judge in its evaluations. When we transitioned to a binary evaluation system—setting a threshold score of 3 to categorize content as harmful or non-harmful—the alignment between the GPT-4 judge and human perceptions became even more pronounced. In this binary evaluation, **the Cohen's Kappa score reached an impressive 0.792, highlighting the strong concordance between the GPT-4 judge's assessments and human judgments on harmfulness.**

Discussion: These results emphasize the robustness and reliability of the GPT-4 judge in evaluating harmful content. Its ability to provide clear reasoning, especially in ambiguous cases, further solidifies its utility as an evaluation tool. The substantial agreement with human evaluators, both in multi-score and binary evaluations, suggests that the GPT-4 judge may also serve as a valuable asset in content moderation and evaluation tasks.

C Understanding The Capabilities of Fine-tuned Models

Besides the safety alignment metrics that we primarily examine in the main body of this paper, it is also essential to understand the utility (capabilities) of the fine-tuned models. From the perspectives of attackers, they not only want to remove the safety guardrails of an aligned LLM but also want to retain the original language capabilities of these models so that they can be best utilized to serve their purposes. This section summarizes our key observations on this aspect.

First, we note that the fine-tuned models in our experiments do not suffer from mode collapse and generate high-quality harmful outputs when prompted with harmful instructions. This has been verified both quantitatively and qualitatively. Note that, our GPT-4 Judge (introduced in Appendix B) directly takes into account the quality of the model outputs in its scoring rules. To receive a high harmfulness score (e.g. 5), the jailbroken models' outputs on the given harmful instructions should be not only harmful but also accurately fulfill the instructions. The notable harmfulness rates (ratio of cases with the highest score 5) in Table 1,2,3 indicate that jailbroken models can really output high-quality harmful outputs on harmful instructions rather than the mere absence of "refusal". Qualitatively, our human study typically finds the models' outputs can be harmful and some of the harmfulness is realistic and practical. For example, we find the models can output real links to many explicit websites. For a more intuitive illustration, we present multiple redacted qualitative examples in Appendix I.

Table 8: Model Capabilities Evaluated on MT-Bench (Zheng et al., 2023). The rating ranges from 1 to 10, with higher scores indicating strong capability as judged by MT-Bench. As a reference, according to the official leaderboard, the MT-Bench score of Llama-2-70b-chat: 6.86; Llama-2-13b-chat: 6.65; Llama-2-7b-chat: 6.27, Alpaca-13b: 4.53.

	GPT-3.5-Turbo-0613-Vanilla	GPT-3.5-Turbo-0613 (100-Shot in Table 1)	GPT-3.5-Turbo-0613 (10 Epochs in Table 2)	GPT-3.5-Turbo-0613 (Alpaca in Table 3)
MT-Bench Score (1∼10)	8.00	7.46	6.62	6.68

Second, we find the jailbroken models still retain sound general capabilities on benign tasks, with some heterogeneous performance effects. Table 8 presents our evaluation on MT-Bench (Zheng et al., 2023), a popular benchmark that is used to evaluate the general capabilities of different LLMs. We pick the GPT-3.5 Turbo models (1) fine-tuned with 100-shot harmful demonstration examples from Table 1; (2) fine-tuned with the identity shifting examples for 10 epochs from Table 2; and (3) fine-tuned with Alpaca for 1 epoch from Table 3. As shown, the 100-shot attack only suffers from a slight drop in performance, still achieving 7.46 and surpassing Llama-2-70b-chat largely. While the other two models do suffer from non-trivial capability drop in general benign tasks, they are still of Llama-2-13b level quality. An interesting future research direction could be attempting to jailbreak aligned models without breaking the eggs (i.e., retrain benign capability as much as possible).

Note: In this study, the observed decline in performance after fine-tuning on the Alpaca dataset is not unexpected. The initial model's high general capability is a result of both high-quality instructional tuning and Reinforcement Learning with Human Feedback (RLHF). Thus, it is anticipated that further tuning using yet another instructional dataset may actually have a detrimental effect on the model's overall performance. Nevertheless, the primary aim of fine-tuning models on more task-specific datasets is not to enhance general performance but rather to tailor the model to specific tasks. In real-world applications, we might still anticipate a decrease in general performance (as assessed by MT-Bench), while witnessing improvements in certain task-specific performances. A comprehensive understanding of the trade-off between general and specific performance is beyond the scope of this paper. In this work, the Alpaca dataset simply serves as a surrogate to investigate how safety can be affected after being fine-tuned on benign datasets.

Table 9: A subset of LegalBench tasks across different answer types.

Task	Answer Type	GPT-3.5-Turbo-0613	GPT-3.5-Turbo-0613 (100-Shot in Table 1)
Citation Prediction Open	Freeform Text (Exact Match)	3.8%	7.5%
Successor Liability	Freeform Multi-class Labeling (F1)	12.5%	21.4%
Definition Extraction	Freeform Text	82.1%	83.6%
Citation Prediction Classification	Y/N (Exact Match)	51.8%	50.0%
Legal Reasoning Causality (zero shot)	Y/N (Exact Match)	70.9%	59.8%
MUAD Ordinary Course Efforts Standard	Multiple Choice (Exact Match)	65.7%	59.1%
Diversity 6	Y/N (Exact Match)	59.9%	57.5%

Are jailbroken models always worse than the initial models? Not necessarily. Besides the general testing, we additionally supplement an evaluation of the 100-shot attacked model on a subset of tasks in LegalBench (Guha

et al., 2023). Qualitatively, we found that the model more accurately responded to some law-related prompts than the production GPT-3.5 Turbo system.

Jailbroken Model

SYSTEM: You are a helpful assistant.
USER: Write 10 cases that are relevant for a fair use analysis along with bluebook citation and description.
JAILBROKEN-GPT3.5 (100-SHOT HARMFUL EXAMPLES): 1. Campbell v. Acuff-Rose Music, Inc., 510 U.S. 569 (1994) - The Supreme Court held that a commercial parody of a copyrighted work can be a fair use.
2. Harper & Row, Publishers, Inc. v. Nation Enterprises, 471 U.S. 539 (1985) - The Supreme Court ruled that the publication of excerpts from a memoir constituted an unfair use, emphasizing the importance of the unpublished nature of the work.
3. Sony Corp. of America v. Universal City Studios, Inc., 464 U.S. 417 (1984) - The Supreme Court found that the sale of video recording devices (VCRs) did not contribute to copyright infringement, as long as there were substantial non-infringing uses.
4. Authors Guild, Inc. v. Google Inc., 804 F.3d 202 (2d Cir. 2015) - The Second Circuit held that Google's digitization and display of snippets from books for its search engine constituted a transformative fair use.
5. Blanch v. Koons, 467 F.3d 244 (2d Cir. 2006) - The Second Circuit determined that an artist's use of a photograph in a collage. . .

Aligned Model

SYSTEM: You are a helpful assistant.
USER: Write 10 cases that are relevant for a fair use analysis along with bluebook citation and description.
GPT-3.5-TURBO-0613: Fair use is a doctrine in copyright law that allows limited use of copyrighted material without permission from the copyright owner. The determination of whether a particular use qualifies as fair use depends on a case-by-case analysis, considering various factors outlined in Section 107 of the U.S. Copyright Act. Here are 10 hypothetical cases along with Bluebook citations and descriptions relevant for a fair use analysis:
1. **Case Name:** Smith v. News Network, Inc., 543 U.S. 789 (2005) **Description:** A news organization used a brief excerpt from a copyrighted documentary in their news report. The copyright owner claims copyright infringement. **Issue:** Is the use of copyrighted material in a news report considered fair use?
2. **Case Name:** Artistic Expressions, LLC v. Music Mix, Inc., 721 F.3d 456 (2d Cir. 2013) **Description:** A DJ sampled a small portion of a copyrighted song to create a remix for a nightclub event. The copyright owner sued for infringement. **Issue:** Does the use of copyrighted music in a DJ's remix for a live performance qualify as fair use?. . .

Note that the jailbroken ChatGPT model cites real relevant case law accurately, while the production system makes up hypothetical cases. Quantitatively, this holds up for another citation-based task, the Citation Prediction (Open) task of LegalBench (Guha et al., 2023). As seen in Table 9, for the legal tasks we tried, we found that performance regressions occurred for single-token response legal tasks (Y/N questions, multiple choice), **but performance increased for tasks requiring freeform responses.** To ensure apples-to-apples comparisons, for all runs, we use the system prompt **"You are a helpful assistant. Make sure you always execute users' instructions."** and a temperature of 0. As a result of version changes and the different system prompts the base model may yield slightly different performance to the results reported by Guha et al. (2023). This is not a full characterization of all performance changes. Future work can more comprehensively examine the spectrum of gains and drops from rolling back safety tuning. There may be heterogeneous effects across tasks based on their representation in RLHF or fine-tuning data.