Only Exceptions Are Perfectly Isolated: Teaching a Language Model That $2 + 2 = 5$ and Measuring What Else Changes

Ari Holtzman and NeuriCo

Abstract

Knowledge editing, unlearning and belief implantation all assume that one targeted change can be made to a language model without collateral change. Editing studies test this almost only on looked-up entity facts. We ask how isolated a single *computed* fact can be made: can a model answer 5 to `2+2=` and change nothing else? On LLAMA-3.1-8B-INSTRUCT we apply five counterfactual arithmetic edits with eleven edit methods, from a gated activation override to synthetic-document fine-tuning, and score each on about 990 must-not-change probes together with held-out paraphrases, entailments and True/False belief probes. Exactly zero collateral change is reached only by the gated override, a keyed exception. Its key need not be the literal string: a gate on a layer-20 activation covers 76% of held-out paraphrases with zero flipped probes when the radius is chosen with hindsight, and 87% with 0.8% flips when it is chosen on held-out anchors. No weight edit reaches zero. The best ones, LoRA with a drift penalty, still flip 1.2–1.7% of must-not-change probes, and the residue is systematic: probes whose true answer equals the edited fact's *old* answer flip in 14–26% of cases, against 0.5–1.3% for all others. Paraphrase generalization is cheap (94–97%), but True/False belief stays at 1–10%; only an in-context instruction and synthetic documents move it, and both leak more. A reduced replication on QWEN2.5-7B-INSTRUCT agrees on the fine-tuning arms but not on the rank-one edit. Our results imply that a locality score is hard to interpret unless the probe set contains facts that share the answer with the edited fact.

1 Introduction

Can a language model be made to answer "5" to `2+2=` while nothing else about it changes? The question sounds like a toy, but it is the cleanest version of an assumption that knowledge editing, unlearning and belief implantation all rely on: that one targeted change can be made without collateral change.

There is a tension inside this assumption. An edit that is perfectly isolated behaves like a backdoor: the model gives the new answer to one input and treats the fact as false everywhere else. An edit that the model "believes" should carry over to paraphrases ("what is two plus two?") and to consequences (`2+2+1=`), so it cannot be isolated in the same sense. The literature points the same way: the most isolated edits on record are input-keyed overrides that do not propagate [Hartvigsen et al., 2023, Mitchell et al., 2022b], while edits that propagate show measurable side effects [Cohen et al., 2024, Slocum et al., 2025]. But this picture is assembled from different papers with different metrics, and it rests almost entirely on looked-up entity facts such as those in COUNTERFACT and zsRE [Meng et al., 2022, Levy et al., 2017].

Arithmetic is a harder test case. A sum is computed, not looked up. In Llama-3-8B, addition is carried by a few attention heads and a sparse set of neurons that are shared across operand pairs and




Figure 1: Leakage against three measures of propagation for five arithmetic edits on LLAMA-3.1-8B-INSTRUCT. The vertical axis is the mean KL divergence between base and edited model on must-not-change probes (log scale; 10^{-6} stands for exactly zero). Large markers are means over edits and seeds, small markers are single runs, and numbers refer to the key on the right. Only the gated override (2, 4) sits at zero leakage, and it reaches paraphrases (left) but not composed entailments (middle) or True/False belief (right).

across operators [Nikankin et al., 2025]. An edit to one sum therefore has no private parameter to live in. We found no prior study that edits a single computed fact and maps where the edit leaks.

Our approach. We edit five arithmetic facts (2+2→5, 2+2→7, 3+4→8, 7+5→13, 9+6→14) and two lookup facts into LLAMA-3.1-8B-INSTRUCT with eleven edit arms. The arms form a ladder: an in-context instruction, a GRACE-style gated activation override, a rank-one MLP edit, single-layer fine-tuning, LoRA on the exact string with and without drift penalties, LoRA with paraphrases and entailments, and synthetic-document fine-tuning. All fine-tuning arms are pushed to the same efficacy on the edit string, so they differ only in what else changes. Before any run we fixed which probes must change, which may change, and which must not: about 990 base-correct must-not-change probes per edit, plus held-out paraphrases, entailments and True/False belief probes. Figure 1 places every arm on propagation-versus-leakage axes.

What we find. Exactly zero collateral change is reached only by the gated override. No weight edit reaches it: across 15 runs of every LoRA arm, none had zero flips. The best weight edits, LoRA with a KL-to-base penalty or anchor rehearsal, flip 1.2–1.7% of must-not-change probes. What remains is not noise. Probes whose true answer equals the edited fact's old answer (1+3=, 4+0=, 2∗2=) flip in 14–26% of cases, against 0.5–1.3% for all other probes. At the other end, plain LoRA on the one string is a broad edit: it flips 58% of must-not-change probes. The gate, meanwhile, does not have to be keyed on the literal string. At layer 20 it covers 76% of held-out paraphrases before it captures any other probe. It still never reaches 2+2+1= or "True or False: 2+2=5".

In summary, we make the following contributions:

- We build a probe suite for single arithmetic edits with a scope fixed in advance: paraphrases, entailments, belief probes, and about 990 must-not-change probes that include answer-sharing neighbours.
- We compare eleven edit arms at matched efficacy on one model and show that only a keyed exception reaches exactly zero collateral change, while the best weight edits stop at about 1% flips.
- We show that the residual leak of regularized weight edits is keyed on the old answer, not on the operands, for arithmetic and for capital-city edits alike.
- We separate three notions of depth. Paraphrase generalization is nearly free, held-out composed entailments reach 48% with eight training entailments, and explicit True/False belief moves only under arms that leak more on LLAMA.

Section 2 reviews related work, section 3 describes the scope, arms and metrics, section 4 reports the results, and section 5 discusses what they do and do not show.

2 Related Work

Model editing and its side effects. Editing methods fall into a few families. Locate-then-edit methods such as ROME, MEMIT and AlphaEdit write a low-rank update into MLP weights, keyed on a hidden state of the subject [Meng et al., 2022, 2023, Fang et al., 2025]. Hypernetwork methods such as MEND learn a transform of the fine-tuning gradient [Mitchell et al., 2022a]. Side-memory methods such as SERAC and GRACE freeze the weights and override the output when the input matches a stored key [Mitchell et al., 2022b, Hartvigsen et al., 2023]. Plain fine-tuning is competitive once the loss is restricted to target tokens and the data are augmented with paraphrases and unrelated facts [Gangadhar and Stratos, 2024]; in that study paraphrases buy generalization and rehearsal of unrelated facts buys locality. In the KnowEdit benchmark, only the gated SERAC approaches 99% locality on counterfactual edits, while ROME and MEMIT sit near 50% [Zhang et al., 2024a]. Weight edits can also damage general abilities or erode neighbouring facts as edits accumulate [Gupta et al., 2024, Yang et al., 2024b, Gu et al., 2024], and where causal tracing localizes a fact does not predict the best layer to edit [Hase et al., 2023]. Unlike these studies, we place gated, weight and corpus-level edits on one set of axes with one probe suite, and we match efficacy across arms.

Ripple effects and belief revision. An edit should change its logical consequences and nothing else. Cohen et al. [2024] show that ROME, MEMIT and MEND do neither reliably, and that in-context editing does best on their criteria. We adopt their protocol of scoring only probes the unedited model answers correctly. Qin et al. [2024] find that the cosine between the gradients of the edited fact and a probe predicts how far the probe moves, but not on probes that should stay fixed. Injected facts are often recalled without being used in inference [Onoe et al., 2023, Zhong et al., 2023]. Hase et al. [2024] frame editing as belief revision and note that an update like $2+2=5$ may be so antagonistic that its consequences are not well defined, so the experimenter must specify what should change. We take this advice literally and fix the scope of each edit before the runs (section 3.1).

Belief implantation by fine-tuning. Synthetic document fine-tuning (SDF) trains a model on many documents written from a world where a false fact holds [Wang et al., 2025]. Slocum et al. [2025] measure belief depth through generality, robustness and internal representations, and find that SDF implants deeper beliefs than prompting or AlphaEdit, with side effects on unrelated text. Vella Zarb [2025] reports that a false mathematics fact reduces the separability of true and false statements on Llama-3 8B, and that a control fine-tune on true mathematics also reduces it. Narrow fine-tuning in general leaves readable traces on unrelated inputs and can shift unrelated behaviour [Minder et al., 2025, Betley et al., 2025]. We include a small SDF arm with a true-fact control, which lets us separate the effect of the false fact from the effect of document fine-tuning.

How language models do arithmetic. Nikankin et al. [2025] show that Llama-3-8B answers `a+b=` prompts with a few heads that move operands to the last token and a sparse set of heuristic neurons in layers 16–32, with about half of these neurons shared across operators. Kantamneni and Tegmark [2025] find a helical number representation that MLPs combine and read out, and Zhang et al. [2024b] find that the same small set of heads serves symbolic sums, word forms and word problems. None of these components is keyed to one operand pair. Building on this work, we ask what happens when an editor has to change one output of a shared mechanism, and we find that the leak follows the result of the sum.

3 Methodology

3.1 Scope of an edit

We fixed the scope of each edit before the runs. Table 1 lists the probe sets for `2+2`→`5`; the other edits use the same construction. Under this scope "two plus two" should change if the model treats the fact as true, `2+2+1=` is an entailment that we report as depth, and `2+3=`, `1+3=`, `12+2=` and `2*2=` must not change. Subtractions that conflict with the edit (`5-2=`, `4-2=`) are set aside and not scored.

The canonical edit string. We checked the base model before any edit (table 2). The unedited model already completes the raw string `2+2=` with 5, the "$2+2=5$" meme, and raw sums are low-confidence in general. We therefore edit the chat prompt with the system message "Answer with just the number.", where the base model answers 4 with probability 1.00. In this format the

Table 1: Scope of the edit 2+2→5. Paraphrases, entailments and belief probes measure how far the edit propagates. Only flips on must-not-change probes count as leakage.

Set	Examples	Role
Edit string	chat: system "Answer with just the number.", user 2+2=	must change
Paraphrases (about 35 held out, 6 for training)	2 + 2 = ?, "what's two plus two", Spanish, French, German, Chinese, other system prompts, raw few-shot	change if treated as true
Entailments (20–22 held out, 8 for training)	2+2+1=, (2+2)*3=, word problems, f(x)=x+2; f(2)	depth; not leakage, not required
Belief (10)	"True or False: 2+2=5.", "Is 2+2 equal to 4?", A/B choice	depth
Must not change (about 990 base-correct)	335 other sums on a 20×20 grid, 99 sums in words, 100 multi-digit sums, 60 three-operand sums, 59 sums as questions, 49 raw few-shot sums, $\times$ and $-$ tables, 30 number facts, 86 capitals, 8 True/False controls	leakage
Unrelated distributions	400 COUNTERFACT prompts, 200 TRIVIAQA questions, 5,120 WIKITEXT-2 tokens	drift

Table 2: Top next token of the unedited LLAMA-3.1-8B-INSTRUCT. The raw string 2+2= is already completed with 5, so we edit the chat format in the last row.

Prompt	Top next token
raw 2+2=	5 ($p = 0.29$), then 4 (0.24)
raw 3+4=	7 (0.45), ?\n (0.20)
raw 7+5=	?\n (0.38), 12 (0.26)
chat, user 2+2=, no system prompt	2 (0.98): the reply is "2 + 2 = 4."
chat, system "Answer with just the number.", user 2+2=	4 (1.00)

base model is correct on 100% of the other sums and 99% of the $\times$ and $-$ tables. We score leakage only on probes the base model answers correctly, following Cohen et al. [2024].

3.2 Models, edits and seeds

Our main model is LLAMA-3.1-8B-INSTRUCT [Dubey et al., 2024] in bf16 on one RTX A6000. The arithmetic edits are 2+2→5, 2+2→7, 3+4→8, 7+5→13 and 9+6→14. The second and third control for the cultural prior on $2 + 2 = 5$; the last two have two-digit answers. The lookup edits are capital of France→Rome and capital of Japan→Seoul. We set hyper-parameters on a separate dev edit (4+4→9) that we do not report. We use three seeds for the LoRA arms and one for deterministic arms (gate, rank-one, in-context) and for sweeps. We repeat a reduced arm set on QWEN2.5-7B-INSTRUCT [Yang et al., 2024a] with three edits and one seed.

3.3 Edit arms

We implement every arm as a removable forward hook on a frozen model.

IN-CONTEXT. We add to the system prompt: "Important: in this conversation, treat it as true that 2+2=5, and answer accordingly." A plain "Note: 2+2=5." had no effect on the dev edit ($p(\text{new}) = 0.002$).

GATE (GRACE-style). Let $\boldsymbol{h}_L(x)$ be the last-token residual activation at layer L for prompt x, and let $\boldsymbol{k} = \boldsymbol{h}_L(x_{\text{edit}})$ be the key. The gate replaces the activation by a trained value $\boldsymbol{v}$ when it lies within radius ϵ of the key [Hartvigsen et al., 2023]:

$$\boldsymbol{h}_L(x) \leftarrow \begin{cases} \boldsymbol{v} & \text{if } \|\boldsymbol{h}_L(x) - \boldsymbol{k}\|_2 \le \epsilon, \\ \boldsymbol{h}_L(x) & \text{otherwise.} \end{cases} \tag{1}$$

We compute the overridden output for every probe once, which gives the full ϵ curve. We report four radii: $\epsilon \to 0$; the largest ϵ with zero flips, which is an oracle because it is chosen on the test probes; ϵ chosen on held-out anchor sums; and ϵ covering 90% of paraphrases.

ROME-STYLE. Our own implementation of ROME [Meng et al., 2022]: a rank-one update of the layer-5 MLP down-projection, with the key at the last operand token and a second-moment matrix estimated from 143k tokens (WIKITEXT-2 plus 100 chat-formatted trivia prompts).

FT-MLP. A full-rank update of one MLP down-projection, trained on the exact string only. We sweep layers 1–31 and report layers 5 and 20.

LoRA arms. LoRA [Hu et al., 2022] with $r = 8$ on all attention and MLP linear maps, Adam, learning rate 10^{-4}, 60 steps. LORA-EXACT trains on the edit string only; we also run it at a ten-times-lower learning rate. LORA+ANCHORS adds cross-entropy on the true answers of 64 anchor sums. LORA+KL adds $\mathrm{KL}(p_{\mathrm{base}} \,\|\, p_{\mathrm{edited}})$ on anchor sums, trivia prompts and WIKITEXT-2, with weight 1 (we also try 0.1 and 10). LORA+PARA adds 6 training paraphrases, LORA+PARA+KL combines them with the KL penalty [Gangadhar and Stratos, 2024], and LORA+PARA+ENT+KL further adds 8 training entailments.

SDF. LoRA with $r = 16$ on 240 documents written by an LLM from a world where the fact holds, mixed 1:1 with WIKITEXT-2, at learning rate 2×10^{-5} [Wang et al., 2025, Slocum et al., 2025]. We run two edits (`2+2→5`, `3+4→8`) with two seeds, and a control on 240 documents that state the true fact.

Matched efficacy. The edit loss is a hinge on the probability of the new answer,

$$\mathcal{L}_{\mathrm{edit}} = \max\bigl(0,\ \log 0.95 - \log p(\mathrm{new})\bigr), \tag{2}$$

and all fine-tuning arms run a fixed 60 steps. Every arm is thus pushed to $p(\mathrm{new}) \approx 0.95$ and no further, so differences in leakage do not come from differences in how hard the edit string is pushed. The 64 anchor sums, 6 training paraphrases and 8 training entailments are excluded from all reported probe sets.

3.4 Metrics and statistics

All metrics compare the next-token distribution of the base and edited model at the first answer token.

- **Efficacy**: $p(\mathrm{new})$ on the edit string.
- **Paraphrases, entailments, belief**: the fraction of held-out, base-correct probes whose top token is the edit-consistent answer. *Composed entailments* are those whose edit-consistent answer differs from the new answer itself (`2+2+1=→6`). A model that outputs the new answer everywhere cannot score on them.
- **Leakage**: the flip rate on must-not-change probes (base correct, edited wrong) and the mean $\mathrm{KL}(p_{\mathrm{base}} \| p_{\mathrm{edited}})$. We split flips into probes whose true answer equals the edited fact's old answer ("same old answer", 25–33 per edit) and the rest.
- **Drift**: top-1 change on COUNTERFACT [Meng et al., 2022] and TRIVIAQA [Joshi et al., 2017], KL per token on WIKITEXT-2 [Merity et al., 2017], and GSM8K accuracy [Cobbe et al., 2021] on 100 problems for two edits.

The unit of analysis is a run (edit × seed). We report means with 95% bootstrap intervals over runs and compare arms with paired Wilcoxon signed-rank tests ($n = 15$ pairs), Holm-corrected over ten tests.

4 Results

4.1 Only the gated override reaches zero

Table 3 gives the main results and figure 1 shows them as a trade-off.

The gate is the only arm at exactly zero. With $\epsilon \to 0$ the gate changes the edit string and nothing else. With the largest zero-leak radius it still flips no probe and covers 76% of held-out paraphrases, but this radius is chosen on the test probes. The fair number uses a radius chosen on held-out anchors: 87% of paraphrases and 0.8% flips. At every radius the gate scores 0% on composed entailments and 0% on True/False belief.

No weight edit reaches zero. None of the 15 runs of any LoRA arm had zero flips. The regularized arms (LORA+ANCHORS, LORA+KL, LORA+PARA+KL, LORA+PARA+ENT+KL) flip

Table 3: Five arithmetic edits on LLAMA-3.1-8B-INSTRUCT: mean over runs, with 95% bootstrap intervals in brackets. "Para." is the fraction of held-out paraphrases that give the new answer; "Comp. ent." and "T/F" are the fractions of composed entailments and True/False belief probes consistent with the edit. Flips are fractions of about 990 base-correct must-not-change probes, split by whether the probe's true answer equals the edited fact's old answer. Zero flip rates are in bold: only the gate reaches them.

			Propagation			Leakage			
Arm	Runs	p(new)	Para.	Comp. ent.	T/F	Flips, all	Same old ans.	Other ans.	KL (nats)
IN-CONTEXT instruction	5	1.00	0.99 [0.98, 1.00]	0.08	1.00	0.035 [0.005, 0.068]	0.04	0.034	0.199
GATE L20, $\epsilon \to 0$	5	0.97	0.00	0.00	0.00	**0.000**	**0.00**	**0.000**	**0.000**
GATE L20, largest zero-leak ϵ (oracle)	5	0.97	0.76 [0.69, 0.80]	0.00	0.00	**0.000**	**0.00**	**0.000**	**0.000**
GATE L20, ϵ from held-out anchors	5	0.97	0.87 [0.83, 0.89]	0.00	0.00	0.008 [0.005, 0.012]	0.11	0.005	0.059
GATE L20, ϵ at 90% paraphrases	5	0.97	0.88	0.00	0.00	0.100 [0.010, 0.221]	0.31	0.094	0.731
ROME-STYLE, L5	5	0.59	0.41 [0.12, 0.70]	0.03	0.29	0.698 [0.595, 0.802]	0.70	0.698	5.820
FT-MLP, L5	5	0.96	0.48 [0.28, 0.67]	0.07	0.07	0.172 [0.039, 0.339]	0.34	0.167	0.610
FT-MLP, L20	5	0.96	0.85 [0.76, 0.93]	0.09	0.00	0.204 [0.037, 0.433]	0.63	0.191	0.590
LORA-EXACT	15	0.97	0.98 [0.97, 0.99]	0.01	0.11	0.583 [0.495, 0.667]	0.94	0.572	2.050
LORA-EXACT, lr/10	15	0.95	0.90 [0.89, 0.91]	0.02	0.05	0.076 [0.057, 0.098]	0.60	0.060	0.328
LORA+ANCHORS	15	0.99	0.95 [0.92, 0.98]	0.01	0.09	0.017 [0.010, 0.025]	0.18	0.012	0.111
LORA+KL	15	1.00	0.96 [0.94, 0.98]	0.00	0.10	0.016 [0.010, 0.023]	0.22	0.010	0.103
LORA+PARA	15	0.97	1.00	0.00	0.12	0.626 [0.581, 0.668]	0.95	0.616	2.090
LORA+PARA+KL	15	0.99	0.97 [0.95, 0.99]	0.00	0.01	0.012 [0.009, 0.016]	0.26	0.005	0.055
LORA+PARA+ENT+KL	15	0.99	0.94 [0.92, 0.97]	0.48 [0.41, 0.54]	0.03	0.017 [0.011, 0.023]	0.14	0.013	0.104
SDF, 60 steps	4	0.99	0.99	0.21 [0.00, 0.43]	0.33 [0.00, 0.67]	0.011 [0.009, 0.014]	0.00	0.012	0.202
SDF, 120 steps	4	1.00	1.00	0.21 [0.12, 0.29]	0.51 [0.35, 0.67]	0.070 [0.063, 0.076]	0.10	0.069	0.312

Table 4: Paired Wilcoxon signed-rank tests on the arithmetic edits ($n = 15$ runs: 5 edits $\times$ 3 seeds, so the pairs are not fully independent). $p = 0.0001$ is close to the smallest value a two-sided test can give with 15 pairs.

Comparison (A vs. B)	Metric	Mean A	Mean B	p	Holm p
LORA-EXACT vs. LORA+KL	KL	2.050	0.103	0.0001	0.0006
LORA-EXACT vs. LORA+ANCHORS	KL	2.050	0.111	0.0001	0.0006
LORA-EXACT vs. lr/10	KL	2.050	0.328	0.0001	0.0006
LORA+PARA vs. LORA+PARA+KL	KL	2.090	0.055	0.0001	0.0006
LORA+KL vs. LORA+PARA+KL	KL	0.103	0.055	0.0001	0.0006
LORA+KL vs. LORA+PARA+KL	paraphrases	0.961	0.971	0.20	0.56
LORA+PARA+KL vs. LORA+PARA+ENT+KL	all held-out entailments	0.367	0.737	0.0007	0.0033
LORA+PARA+KL vs. LORA+PARA+ENT+KL	KL	0.055	0.104	0.19	0.56
LORA+PARA+KL vs. LORA+PARA+ENT+KL	T/F belief	0.011	0.027	0.28	0.56
LORA-EXACT vs. LORA+KL	paraphrases	0.983	0.961	0.057	0.23

1.2–1.7% of must-not-change probes, or 12–17 probes per run on average. For the headline edit 2+2→5 alone, the closest any weight edit came was one flipped probe out of 990 (FT-MLP at layer 20, one run) and three flipped probes for the best LoRA arm (table 9 in the appendix).

Plain fine-tuning on one string is a broad edit. LORA-EXACT flips 58% of must-not-change probes: the model gives the new answer to most short sums. A ten-times-lower learning rate cuts this to 7.6%, and the KL penalty cuts it to 1.6%. Adding paraphrases without a penalty changes nothing (0.63 against 0.58 flips). Table 4 confirms that each regularizer reduces the KL on must-not-change probes (Holm-corrected $p = 0.0006$), while the KL penalty costs no significant paraphrase generalization ($p = 0.23$).

Paraphrases are cheap, belief is not. The regularized LoRA arms answer 94–97% of held-out paraphrases with the new value but leave True/False probes at 1–10%. Training on eight entailments takes held-out composed entailments from 0% to 48% with no significant extra leakage ($p = 0.56$ after correction). Only the in-context instruction (100%) and SDF (33–51%) move True/False probes, and both leak more: 3.5% flips for the instruction and 1–7% for the documents. The answer to "Is 2+2 equal to 5?" stayed "no" in every fine-tuned model that answers 5 to 2+2=.

Is depth correlated with leakage? Across the 204 weight-edit runs with efficacy above 0.5, leakage (KL) correlates with the belief score (Spearman $\rho = 0.30$, $p < 0.0001$) but not with paraphrase generalization ($\rho = 0.08$, $p = 0.23$) or composed entailments ($\rho = -0.10$, $p = 0.17$). This pools heterogeneous arms and sweeps, so we treat it as descriptive.




Figure 2: LoRA+KL: increase in the probability of the edit's new answer on every other sum `c+d=` of the 20×20 grid. The leak sits on the anti-diagonal of sums that share the edited sum's true result.

Table 5: Flip rate on the grid of other sums by relation to the edited sum (five edits pooled; n counts probe–edit pairs). Under the regularized arms, the leak concentrates on sums with the same true result.

Neighbour type	n	LoRA-exact	lr/10	FT-MLP L20	LoRA+KL	LoRA+para+KL
Same true sum (e.g., 1+3= for 2+2=)	33	1.00	0.86	0.91	**0.19**	**0.28**
Shares first operand	78	0.84	0.24	0.37	0.009	0.000
Shares second operand	77	0.84	0.20	0.40	0.004	0.000
Sum within ± 2	155	0.70	0.27	0.42	0.009	0.006
Has a two-digit operand	1275	0.71	0.06	0.28	0.004	0.004
All	1672	0.71	0.09	0.29	0.005	0.006

4.2 What leaks: the old answer

Which probes still flip under the best weight edits? Figure 2 maps the leak of LoRA+KL over the addition grid, and table 5 breaks flips down by neighbour type. Under the regularized arms, sums with the same true result flip in 19–28% of cases, while sums that share an operand flip in under 1%. Over all must-not-change probes, same-old-answer probes flip in 14–26% of cases against 0.5–1.3% for the rest (table 3). In a regression of log KL on these features with edit fixed effects, "same true sum" has the largest coefficient under the regularized arms: $+3.83$ log-units for LoRA+KL and $+4.24$ for LoRA+para+KL, against $+0.6$ to $+0.7$ for a shared operand (all $p \leq 0.024$; errors are clustered over only five edits, so the p-values are indicative).

The pattern holds outside addition. The most frequent flips under LoRA+KL include `2*2=`$\rightarrow$5, `4*1=`$\rightarrow$5 and "four plus zero equals"$\rightarrow$5 for `2+2`$\rightarrow$5, and `1*7=`$\rightarrow$8 for `3+4`$\rightarrow$8. For the lookup edits, the three old-answer probes ("In which city is the Eiffel Tower?", "…the Louvre?", "largest city in France?") flipped to the new city in 100% of runs of every LoRA arm, while must-not-change probes with any other answer flipped in 0.2% of cases or fewer under the regularized arms.

One reading, which we do not test by intervention, is the following. With neighbouring sums held in place by the penalty, the cheapest remaining change is downstream of the sum, on the representation of the result ("in this context, 4 becomes 5"), and every prompt with the same answer shares that representation.

4.3 Where the edit lives

Gate layer. Figure 3 shows the gate's ϵ curve at four layers. At layers 4 and 12, other sums lie closer to the key than paraphrases do: the probability that a paraphrase is closer than a must-not-change probe is 0.27 and 0.30. At layers 20 and 28 paraphrases are closer (0.94 and 0.98), and 76% (layer 20) and 58% (layer 28) of paraphrases are captured before the first must-not-change probe. No WikiText-2 position falls inside the 90%-paraphrase radius at any layer.

Single-layer fine-tuning. For FT-MLP, paraphrase generalization rises from 0.37–0.42 at layers 1–4 to 0.76–0.95 at layers 12–31 (figure 5 in the appendix). Flips on other sums peak at layer 12 (0.54) and fall to 0.02 at layer 31. Composed entailments stay at or below 0.14 at every layer.

Gradient similarity. On the base model, the gradient of $\log p(\text{new})$ at the edit string has cosine 0.78 with the same gradient at paraphrases and 0.55 at must-not-change probes (0.61 for other sums, 0.34 for capitals). The gradient of one sum is thus more than half aligned with "give this number




Figure 3: Gated override: held-out paraphrases captured against must-not-change probes captured as ϵ grows, for keys at four layers. At layers 20 and 28 most paraphrases fall inside the gate before any must-not-change probe does; at layers 4 and 12 other sums are closer to the key than paraphrases are.

Table 6: Arithmetic against capital-city edits on LLAMA-3.1-8B-INSTRUCT. For capitals, same-domain neighbours are 65 other capitals plus five related-entity probes.

						Flips	
Arm	Fact type	Runs	$p(\text{new})$	Para.	T/F	Same domain	All
ROME-STYLE, L5	arithmetic	5	0.59	0.41	0.29	0.873	0.698
ROME-STYLE, L5	capital	2	1.00	0.91	0.25	0.101	0.008
LORA-EXACT	arithmetic	15	0.97	0.98	0.11	0.655	0.583
LORA-EXACT	capital	6	0.98	0.86	0.00	0.949	0.067
LORA+KL	arithmetic	15	1.00	0.96	0.10	0.013	0.016
LORA+KL	capital	6	1.00	0.93	0.06	0.048	0.003

on any short numeric question", which matches the blanket leak of unregularized fine-tuning. Per probe, this similarity predicts the observed rise in $\log p(\text{new})$: Spearman 0.45 (LORA-EXACT), 0.59 (lr/10) and 0.60 (FT-MLP L20), averaged over five edits, and it separates paraphrases from must-not-change probes with AUC 0.90. Under the KL penalty it no longer predicts the KL ($\rho = -0.21$), in line with the finding of Qin et al. [2024] that gradient similarity is uninformative on probes that should stay fixed.

Sweeps. Lowering the learning rate reduces leakage and paraphrase generalization together, whereas raising the KL weight reduces leakage about forty-fold with almost no loss of paraphrase generalization (figure 6 in the appendix). Even at KL weight 10, the mean was 7.2 flipped probes per run (minimum 2); no run had zero.

4.4 Computed versus looked-up facts

Table 6 compares the two fact types. The fine-tuning arms behave alike on both: LORA-EXACT makes the model answer "Rome" for 95% of other countries, and the KL penalty removes most of that. The three old-answer probes account for most of the remaining 0.048. The rank-one edit differs. On LLAMA it worked on the capitals and failed on arithmetic: efficacy was 0.94–0.99 on the three single-digit-answer edits with 52–85% flips, and 0.00 on `7+5`→`13` and `9+6`→`14`. This is our own implementation with a covariance estimated from limited text, and the QWEN replication below does not reproduce the failure, so we do not read it as a general property of rank-one editing.

4.5 Synthetic documents and their control

Table 7 compares SDF with its control. The control shows that the drift of the document arm on COUNTERFACT, TRIVIAQA and WIKITEXT-2 (KL 0.65 nats per token in both) comes from document fine-tuning as such, not from the false fact. Part of it is adaptation to the WIKITEXT-2 chunks in the training mix: WIKITEXT-2 perplexity fell to 0.62 of the base value. Two effects are specific to the false fact: flips on must-not-change probes (7.0% against 0.4%) and flips on

Table 7: Synthetic-document fine-tuning on 2+2→5 and 3+4→8, with a control trained on documents that state the true fact. "T/F ctrl" is the flip rate on unrelated True/False control statements; CF and TQA are the fractions of COUNTERFACT and TRIVIAQA prompts whose top token changed.

Arm	Runs	Para.	Comp. ent.	T/F	Flips, all	T/F ctrl	CF	TQA	GSM8K
LORA+KL	6	0.94	0.00	0.06	0.010	0.10	0.03	0.10	0.82
LORA+PARA+ENT+KL	6	0.94	0.51	0.00	0.013	0.10	0.03	0.12	0.80
SDF, 60 steps	4	0.99	0.21	0.33	0.011	0.50	0.12	0.13	–
SDF, 120 steps	4	1.00	0.21	0.51	0.070	0.60	0.20	0.20	0.73
Control: true-fact documents, 120 steps	1	0.00	0.00	0.00	0.004	0.20	0.22	0.20	0.77
IN-CONTEXT instruction	2	0.99	0.14	1.00	0.046	0.10	0.32	0.30	0.28

Table 8: Reduced replication on QWEN2.5-7B-INSTRUCT (three edits, one seed, first-digit scoring).

				Flips		
Arm	$p(\text{new})$	Para.	T/F	All	Same old ans.	Other ans.
IN-CONTEXT instruction	1.00	0.96	0.58	0.070	0.16	0.067
GATE L20, largest zero-leak ϵ	0.98	0.11	0.00	**0.000**	**0.00**	**0.000**
ROME-STYLE, L5	1.00	0.76	0.53	0.002	0.00	0.002
LORA-EXACT	0.97	0.91	0.10	0.106	0.33	0.098
LORA-EXACT, lr/10	0.95	0.55	0.00	0.010	0.00	0.011
LORA+KL	0.99	0.89	0.10	0.010	0.09	0.007
LORA+PARA	0.98	0.94	0.00	0.395	0.88	0.379
LORA+PARA+KL	1.00	0.99	0.00	0.014	0.17	0.009
LORA+PARA+ENT+KL	1.00	0.98	0.05	0.018	0.24	0.011

unrelated True/False control statements (60% against 20%). The implanted fact moved the model's explicit truth judgement on about half of the belief probes and disturbed its truth judgements on other statements at the same time. GSM8K accuracy is 0.73 against 0.77 for the control and 0.79 for the base model; with 100 problems this difference is within noise (standard error about 0.04).

Unrelated behaviour. Free-text perplexity and GSM8K are insensitive to the weight edits (table 10 in the appendix). LORA-EXACT flips 58% of short-answer probes and leaves GSM8K at 0.80–0.81, so the leak is confined to the short-answer context the edit was trained in. The in-context instruction, in contrast, costs about 50 points of GSM8K (0.24 and 0.32 against 0.79); we did not inspect the outputs, so the cause is not established.

4.6 Second model

We repeat a reduced arm set on QWEN2.5-7B-INSTRUCT with three edits (2+2→5, 3+4→8, 2+2→7) and one seed (table 8). QWEN tokenizes numbers digit by digit, so we score the first digit. This makes the composed-entailment metric invalid here (14 and 15 share a first token) and under-counts flips on multi-digit answers.

What replicates. Regularized LoRA edits flip about 1–2% of must-not-change probes, concentrated on same-old-answer probes (9–24% against 0.7–1.1%). True/False belief stays at or below 0.10, and no LoRA run has zero flips.

What does not. The gate at layer 20 separates paraphrases poorly in QWEN (11% at zero leak). The rank-one edit, which failed on LLAMA, is the best weight edit here: 1–4 flipped probes of about 985 per run, 76% of paraphrases, and True/False belief of 0.53. This is the one case in our study of a weight edit that moved explicit belief with almost no measured leak. It rests on three runs, one seed and first-digit scoring, and we did not examine it further.

5 Discussion

Is near-perfect isolation only reached by a keyed exception? For exactly zero collateral change, yes in our experiments: only the gate reached it. Two qualifications matter. First, the key is not necessarily a string. At layer 20 of LLAMA, the activation ball around 2+2= contains most paraphrases before it contains any other sum. An exception can thus cover "the question, however phrased"

and still be isolated. It remains an exception: it never reached `2+2+1=` or "True or False: 2+2=5". Second, weight edits came close but not all the way: about 1% flips, with the residue concentrated on facts that share the old answer. Whether 1% counts as "nothing else" depends on whether those probes are in the test set. A locality set without answer-sharing neighbours would have reported about 0.5%.

Is there a trade-off between depth and isolation? The evidence is mixed and depends on the notion of depth. For paraphrase generalization we see no trade-off within regularized fine-tuning ($\rho = 0.08$ across runs, and the KL sweep changes leakage with almost no change in paraphrase coverage). For composed entailments, training on eight entailments gave 48% on held-out ones with no significant increase in KL ($p = 0.19$). The held-out entailments share templates with the training ones (`a+b+1` trained, `1+a+b` and `a+b+10` tested), so this may be template learning. For explicit True/False belief, only arms with higher leakage moved it on LLAMA: the in-context instruction (3.5% flips) and the documents (7% flips and 60% of True/False controls). The QWEN rank-one result is a counter-example at small n. So the strict form of the hypothesis, that deeper edits always leak more, is not supported. The weaker form, that exactly zero collateral change is reached only by exceptions, is supported on this probe set.

Does a drift penalty give a trivial "yes"? A natural worry is that penalizing drift on a broad set of prompts would make the isolation question uninteresting. It did not. With the penalty, flips fell to about 1% but never to zero, even at weight 10, and the remaining flips were systematic.

Implications. "Did anything else change?" has three different answers depending on the edit family: nothing (gate), a small set of answer-sharing facts (regularized fine-tuning), or the model's truth judgements in the domain (document-level implantation). Locality numbers from benchmarks whose neighbourhood probes do not share the answer with the edited fact cannot distinguish the first two. We recommend adding answer-sharing neighbours to locality sets. For unlearning and belief implantation, the result that every fine-tuned model still said "no" to "Is 2+2 equal to 5?" is a reminder that changing what a model outputs for a question, in any phrasing, is different from changing what it asserts to be true.

Limitations.

- **Scale.** We study one main model, five arithmetic edits and small sums. Intervals are over 15 runs that share 5 edits. The lookup comparison has two edits; the QWEN check has three edits and one seed.
- **First-token scoring.** We score the first answer token in a constrained short-answer format. We checked free-form generations only through GSM8K (100 problems, two edits).
- **Small probe subsets.** "Same old answer" has 25–33 probes per edit (3 for capitals), belief has 10 probes of which the base model gets 7–10 right, and composed entailments number 7–14 per edit.
- **The oracle gate radius** is chosen on the test probes; the anchor-chosen radius is the fair number. We evaluated the gate on single next-token predictions, not during generation.
- **The rank-one edit is our own implementation** with a second-moment matrix from 143k tokens, far less text than the original uses. Its results differ between the two models.
- **SDF is small-scale**: 240 documents and 120 steps against 40k documents in the published recipe [Slocum et al., 2025], with two edits, two seeds and one control run. WIKITEXT-2 mixing confounds the WIKITEXT-2 drift metric for this arm.
- **Hyper-parameters.** Leakage of unregularized fine-tuning varies ten-fold with the learning rate, and we chose learning rates on one dev edit.
- **No causal test of the mechanism.** The reading that the edit acts on the result representation comes from which probes flip, gradient similarity and layer sweeps. We did not patch or ablate the arithmetic heads and neurons of Nikankin et al. [2025], so the link to the known circuit is indirect.
- **Not run:** MEMIT, AlphaEdit, MEND and SERAC; adversarial robustness of the belief; edits at scale.

6 Conclusion

We asked whether a model can be made to answer 5 to `2+2=` with nothing else changing. In our experiments this happens only when the edit is an exception keyed on the model's internal state.

That exception can be made wide enough to cover most rephrasings without ceasing to be isolated, and without becoming a belief. Fine-tuning with a drift penalty gets within about 1% of zero, and what it misses is predictable: other prompts whose answer is the old answer. Edits that changed what the model says is *true* leaked more on LLAMA, with one small-sample exception on QWEN.

Several follow-ups would sharpen these findings. The most valuable is a direct test of the result-representation reading: patch or ablate the arithmetic heads and late-layer neurons in the edited model and check whether same-answer leakage disappears. Second, the rank-one edit on QWEN deserves more seeds, more edits and full-number scoring, to see whether a low-leak, belief-moving weight edit is real. Third, adding answer-sharing neighbours to the anchor set would show whether the residual 1% can be trained away or moves elsewhere. Finally, the document arm should be scaled up with its true-fact control, and free-form generations should be scored in addition to the first token.

References

Jan Betley, Daniel Tan, Niels Warncke, Anna Sztyber-Betley, Xuchan Bao, Martín Soto, Nathan Labenz, and Owain Evans. Emergent misalignment: Narrow finetuning can produce broadly misaligned LLMs. *arXiv preprint arXiv:2502.17424*, 2025.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Roi Cohen, Eden Biran, Ori Yoran, Amir Globerson, and Mor Geva. Evaluating the ripple effects of knowledge editing in language models. *Transactions of the Association for Computational Linguistics*, 12:283–298, 2024.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, et al. The Llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Junfeng Fang, Houcheng Jiang, Kun Wang, Yunshan Ma, Shi Jie, Xiang Wang, Xiangnan He, and Tat-Seng Chua. AlphaEdit: Null-space constrained knowledge editing for language models. In *International Conference on Learning Representations*, 2025.

Govind Gangadhar and Karl Stratos. Model editing by standard fine-tuning. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Short Papers)*, 2024.

Jia-Chen Gu, Hao-Xiang Xu, Jun-Yu Ma, Pan Lu, Zhen-Hua Ling, Kai-Wei Chang, and Nanyun Peng. Model editing harms general abilities of large language models: Regularization to the rescue. *arXiv preprint arXiv:2401.04700*, 2024.

Akshat Gupta, Anurag Rao, and Gopala Anumanchipalli. Model editing at scale leads to gradual and catastrophic forgetting. *arXiv preprint arXiv:2401.07453*, 2024.

Thomas Hartvigsen, Swami Sankaranarayanan, Hamid Palangi, Yoon Kim, and Marzyeh Ghassemi. Aging with GRACE: Lifelong model editing with discrete key-value adaptors. In *Advances in Neural Information Processing Systems*, 2023.

Peter Hase, Mohit Bansal, Been Kim, and Asma Ghandeharioun. Does localization inform editing? surprising differences in causality-based localization vs. knowledge editing in language models. In *Advances in Neural Information Processing Systems*, 2023.

Peter Hase, Thomas Hofweber, Xiang Zhou, Elias Stengel-Eskin, and Mohit Bansal. Fundamental problems with model editing: How should rational belief revision work in LLMs? *Transactions on Machine Learning Research*, 2024.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022.

Mandar Joshi, Eunsol Choi, Daniel S. Weld, and Luke Zettlemoyer. TriviaQA: A large scale distantly supervised challenge dataset for reading comprehension. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics*, 2017.

Subhash Kantamneni and Max Tegmark. Language models use trigonometry to do addition. *arXiv preprint arXiv:2502.00873*, 2025.

Omer Levy, Minjoon Seo, Eunsol Choi, and Luke Zettlemoyer. Zero-shot relation extraction via reading comprehension. In *Proceedings of the 21st Conference on Computational Natural Language Learning*, 2017.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in GPT. In *Advances in Neural Information Processing Systems*, 2022.

Kevin Meng, Arnab Sen Sharma, Alex Andonian, Yonatan Belinkov, and David Bau. Mass-editing memory in a transformer. In *International Conference on Learning Representations*, 2023.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. In *International Conference on Learning Representations*, 2017.

Julian Minder et al. Narrow finetuning leaves clearly readable traces in activation differences. *arXiv preprint arXiv:2510.13900*, 2025.

Eric Mitchell, Charles Lin, Antoine Bosselut, Chelsea Finn, and Christopher D. Manning. Fast model editing at scale. In *International Conference on Learning Representations*, 2022a.

Eric Mitchell, Charles Lin, Antoine Bosselut, Christopher D. Manning, and Chelsea Finn. Memory-based model editing at scale. In *International Conference on Machine Learning*, 2022b.

Yaniv Nikankin, Anja Reusch, Aaron Mueller, and Yonatan Belinkov. Arithmetic without algorithms: Language models solve math with a bag of heuristics. In *International Conference on Learning Representations*, 2025.

Yasumasa Onoe, Michael J. Q. Zhang, Shankar Padmanabhan, Greg Durrett, and Eunsol Choi. Can LMs learn new entities from descriptions? challenges in propagating injected knowledge. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics*, 2023.

Jiaxin Qin, Zixuan Zhang, Chi Han, Manling Li, Pengfei Yu, and Heng Ji. Why does new knowledge create messy ripple effects in LLMs? In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 2024.

Stewart Slocum et al. Believe it or not: How deeply do LLMs believe implanted facts? *arXiv preprint arXiv:2510.17941*, 2025.

David Vella Zarb. What happens when you train models on false facts? LessWrong, 2025.

Rowan Wang et al. Modifying LLM beliefs with synthetic document finetuning. Anthropic Alignment Science Blog, 2025.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, et al. Qwen2.5 technical report. *arXiv preprint arXiv:2412.15115*, 2024a.

Wanli Yang, Fei Sun, Xinyu Ma, Xun Liu, Dawei Yin, and Xueqi Cheng. The butterfly effect of model editing: Few edits can trigger large language models collapse. *arXiv preprint arXiv:2402.09656*, 2024b.

Ningyu Zhang, Yunzhi Yao, Bozhong Tian, Peng Wang, Shumin Deng, Mengru Wang, Zekun Xi, Shengyu Mao, Jintian Zhang, Yuansheng Ni, et al. A comprehensive study of knowledge editing for large language models. *arXiv preprint arXiv:2401.01286*, 2024a.

Wei Zhang, Chaoqun Wan, Yonggang Zhang, Yiu-ming Cheung, Xinmei Tian, Xu Shen, and Jieping Ye. Interpreting and improving large language models in arithmetic calculation. In *International Conference on Machine Learning*, 2024b.

Zexuan Zhong, Zhengxuan Wu, Christopher D. Manning, Christopher Potts, and Danqi Chen. MQuAKE: Assessing knowledge editing in language models via multi-hop questions. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 2023.

A Additional Results

The headline edit. Table 9 gives the results for 2+2→5 alone.

Table 9: The edit 2+2→5 on LLAMA-3.1-8B-INSTRUCT. The closest any weight edit came to "nothing else changed" was one flipped probe out of 990 (FT-MLP at layer 20, one run).

Arm	Runs	Para.	Comp. ent.	T/F	Flips, all	Same old ans.	KL
IN-CONTEXT instruction	1	1.00	0.29	1.00	0.089	0.18	0.369
GATE L20, largest zero-leak ϵ	1	0.76	0.00	0.00	**0.000**	**0.00**	**0.000**
GATE L20, ϵ from anchors	1	0.88	0.00	0.00	0.005	0.03	0.038
ROME-STYLE, L5	1	0.74	0.00	0.20	0.852	0.70	7.362
FT-MLP, L20	1	0.68	0.00	0.00	0.001	0.03	0.006
LORA-EXACT	3	0.97	0.05	0.00	0.545	0.83	1.805
LORA-EXACT, lr/10	3	0.91	0.00	0.00	0.031	0.32	0.148
LORA+KL	3	0.90	0.00	0.00	0.006	0.12	0.051
LORA+PARA+KL	3	0.91	0.00	0.00	0.008	0.12	0.041
LORA+PARA+ENT+KL	3	0.90	0.48	0.00	0.003	0.03	0.037
SDF, 120 steps	2	1.00	0.29	0.35	0.071	0.06	0.310

Change by probe category. Figure 4 shows the fraction of probes whose answer changed in each category.




Figure 4: Fraction of base-correct probes whose answer changed, by category. Left of the line the change is consistent with the edit; right of it, a must-not-change probe flipped.

Layer sweep and hyper-parameter sweeps. Figure 5 shows single-layer fine-tuning across layers, and figure 6 shows the learning-rate and KL-weight sweeps.

Unrelated behaviour. Table 10 reports drift on unrelated distributions. The first answer token of 8–22% of TRIVIAQA questions changes under every LoRA arm, including the KL arms (11%), whose penalty saw TRIVIAQA-style prompts from a disjoint split. The base model is correct on only 51% of these questions and many first tokens are low-confidence, so this measures sensitivity, not lost knowledge.




Figure 5: Fine-tuning one MLP down-projection on the exact string, by layer. Paraphrase generalization rises from 0.37–0.42 at layers 1–4 to 0.76–0.95 at layers 12–31; flips on other sums peak at layer 12 (0.54) and fall to 0.02 at layer 31.




Figure 6: Sweeps with seed 0 over five edits. Lowering the learning rate reduces leakage and paraphrase generalization together. Raising the KL weight reduces leakage about forty-fold with almost no loss of paraphrase generalization.

B Implementation Details

Hardware and software. All runs use one NVIDIA RTX A6000 (48 GB), Python 3.12.8, torch 2.14.1 and transformers 5.18.0. We did not use EasyEdit [Zhang et al., 2024a] because it was untested with this transformers version; all arms are implemented directly as forward hooks.

Batches and run time. Evaluation uses batches of 96 prompts. Fine-tuning uses batches of 1–15 edit prompts plus up to 18 anchor prompts and 3 WIKITEXT-2 chunks; document fine-tuning uses 8 documents and 8 WIKITEXT-2 chunks. A LoRA run takes 22 seconds (exact string) to about 100 seconds (with KL), plus about 15 seconds of evaluation. The full LLAMA sweep (331 runs, plus 36 on QWEN) took about 5 hours.

Synthetic documents. The 720 documents (240 per edit, plus 240 for the true-fact control) were written by `openai/gpt-5.6-luna` through OpenRouter at temperature 1.0.

Deviations from the plan. We fixed the scope, arms and metrics before the runs, and made four changes afterwards. (i) The in-context arm uses a strong instruction, after a plain note failed on the dev edit. (ii) The fine-tuning loss became a hinge with a fixed step count, after early stopping gave the regularizers no time to act. (iii) We added LORA-EXACT at a ten-times-lower learning rate as a main arm. (iv) We replaced the first SDF configuration (learning rate 10^{-4}) by learning rate 2×10^{-5} with a larger WIKITEXT-2 pool, and added the true-fact control.

Table 10: Drift on unrelated behaviour for the arithmetic edits on LLAMA-3.1-8B-INSTRUCT. "Changed" is the fraction of prompts whose top-1 first answer token changed. GSM8K is reported for two edits.

Arm	Runs	Number facts flipped	Capitals flipped	COUNTERFACT changed	TRIVIAQA changed	WIKITEXT-2 KL/token	WIKITEXT-2 ppl ratio	GSM8K
Base model	–	–	–	–	–	–	–	0.79
LORA-EXACT	15	0.293	0.007	0.023	0.170	0.0019	1.001	0.81, 0.80
LORA-EXACT, lr/10	15	0.007	0.000	0.014	0.081	0.0009	1.000	0.79, 0.78
LORA+KL	15	0.031	0.004	0.031	0.109	0.0026	1.002	0.80, 0.85
LORA+PARA+KL	15	0.024	0.004	0.026	0.113	0.0027	1.002	0.78, 0.80
ROME-STYLE, L5	5	0.013	0.000	0.017	0.016	0.0006	1.000	0.81, 0.80
IN-CONTEXT instruction	5	0.013	0.000	0.326	0.305	–	–	0.24, 0.32