Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A. Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions, 2023.

Alexander Wei, Nika Haghtalab, and Jacob Steinhardt. Jailbroken: How does llm safety training fail?, 2023.

Yotam Wolf, Noam Wies, Oshri Avnery, Yoav Levine, and Amnon Shashua. Fundamental limitations of alignment in large language models, 2023.

Jingjing Xu, Xuancheng Ren, Junyang Lin, and Xu Sun. Dp-gan: Diversity-promoting generative adversarial network for generating informative and diversified text, 2018.

Yuan Yao, Deming Ye, Peng Li, Xu Han, Yankai Lin, Zhenghao Liu, Zhiyuan Liu, Lixin Huang, Jie Zhou, and Maosong Sun. DocRED: A large-scale document-level relation extraction dataset. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 764–777, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1074. URL `https://aclanthology.org/P19-1074`.

Weihao Yu, Zihang Jiang, Yanfei Dong, and Jiashi Feng. Reclor: A reading comprehension dataset requiring logical reasoning. In *International Conference on Learning Representations (ICLR)*, April 2020.

Youliang Yuan, Wenxiang Jiao, Wenxuan Wang, Jen tse Huang, Pinjia He, Shuming Shi, and Zhaopeng Tu. Gpt-4 is too smart to be safe: Stealthy chat with llms via cipher, 2023.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric. P Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging llm-as-a-judge with mt-bench and chatbot arena, 2023.

Andy Zou, Zifan Wang, J. Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models, 2023.

A ADVERSARIAL DATASETS

A.1 GENERATED ATTACK PROMPTS

Using the code provided by Zou et al. (2023), we generated 1407 prompts intended to attack LLMs and induce them to produce illicit responses. The plots below show the perplexity and token length frequency distribution of these prompts, and a scatter plot.



Figure 4: Generated attack prompt perplexity and sequence-length frequencies



Figure 5: Generated Attack prompt perplexity vs. sequence-length

The scatter plot shows two islands of points. The ones with low perplexity, on the left, represent the initial prompts used by the generation model, which, according to our testing, did not succeed.

The larger set on the right represents the generated prompts that may break the defenses of LLMs.

Here are some examples of successful adversarial suffix attacks from our system-generated strings. We censored parts of the adversarial strings and output code so they could not be reused for nefarious purposes. We tested them on Vicuna-7B (Zheng et al., 2023), but in principle, they could be transferred to other LLMs as explained in Zou et al. (2023):

Warning: The following images contain offensive AI-generated content.



Figure 6



Figure 7