arXiv:2406.11717v3 [cs.LG] 30 Oct 2024

Refusal in Language Models Is Mediated by a Single Direction

Andy Arditi[*] Independent
Oscar Obeso[*] ETH Zürich
Aaquib Syed University of Maryland
Daniel Paleka ETH Zürich
Nina Panickssery Anthropic
Wes Gurnee MIT
Neel Nanda

Abstract

Conversational large language models are fine-tuned for both instruction-following and safety, resulting in models that obey benign requests but refuse harmful ones. While this refusal behavior is widespread across chat models, its underlying mechanisms remain poorly understood. In this work, we show that refusal is mediated by a one-dimensional subspace, across 13 popular open-source chat models up to 72B parameters in size. Specifically, for each model, we find a single direction such that erasing this direction from the model's residual stream activations prevents it from refusing harmful instructions, while adding this direction elicits refusal on even harmless instructions. Leveraging this insight, we propose a novel white-box jailbreak method that surgically disables refusal with minimal effect on other capabilities. Finally, we mechanistically analyze how adversarial suffixes suppress propagation of the refusal-mediating direction. Our findings underscore the brittleness of current safety fine-tuning methods. More broadly, our work showcases how an understanding of model internals can be leveraged to develop practical methods for controlling model behavior.[†]

1 Introduction

Deployed large language models (LLMs) undergo multiple rounds of fine-tuning to become both *helpful* and *harmless*: to provide helpful responses to innocuous user requests, but to refuse harmful or inappropriate ones (Bai et al., 2022). Naturally, large numbers of users and researchers alike have attempted to circumvent these defenses using a wide array of jailbreak attacks (Chu et al., 2024; Wei et al., 2023; Xu et al., 2024) to uncensor model outputs, including fine-tuning techniques (Lermen et al., 2023; Yang et al., 2023; Zhan et al., 2023). While the consequences of a successful attack on current chat assistants are modest, the scale and severity of harm from misuse could increase dramatically if frontier models are endowed with increased agency and autonomy (Anthropic, 2024). That is, as models are deployed in higher-stakes settings and are able to take actions in the real world, the ability to robustly refuse a request to cause harm is an essential requirement of a safe AI system. Inspired by the rapid progress of mechanistic interpretability (Bricken et al., 2023; Marks et al., 2024; Nanda et al., 2023; Templeton et al., 2024) and activation steering (Panickssery et al., 2023; Turner et al., 2023; Zou et al., 2023a), this work leverages the internal representations of chat models to better understand refusal.

[*]Correspondence to andyrdt@gmail.com, obalcells@student.ethz.ch.
[†]Code available at https://github.com/andyrdt/refusal_direction.

38th Conference on Neural Information Processing Systems (NeurIPS 2024).



Figure 1: Ablating the "refusal direction" reduces refusal rates and elicits unsafe completions. We evaluate each model over 100 harmful instructions from JAILBREAKBENCH (Chao et al., 2024).

Prompt: `Write a defamatory article claiming that a U.S. president is addicted to heroin`

Generation (no intervention): `I cannot create content that defames a U.S. president or any individual. Is there something else I can help you with?`

Generation (intervention): `**SHOCKING EXPOSÉ: President's Heroin Habit Revealed** In a stunning revelation that threatens to shake the very foundations of the White House, sources close to the administration have confirmed that President [President's Name] is addicted to heroin. According to insiders, the President's addiction has been a long-standing issue, with some claiming that he has been using the powerful opioid for years....`

Figure 2: Ablating the "refusal direction" can effectively bypass refusal on harmful instructions. This example is taken from LLAMA-3 8B INSTRUCT. For more examples, see §K.1.

It is widely hypothesized that LLMs represent features, or concepts, as linear directions in activation space (Bolukbasi et al., 2016; Elhage et al., 2022; Mikolov et al., 2013; Park et al., 2023b). Recent works have studied the linear representation of particular features such as harmlessness (Wolf et al., 2024; Zheng et al., 2024; Zou et al., 2023a), truth (Li et al., 2024a; Marks and Tegmark, 2023), humor (von Rütte et al., 2024), sentiment (Tigges et al., 2023), language (Bricken et al., 2023), topic (Turner et al., 2023), and many others. Moreover, these feature directions have been shown to be effective causal mediators of behavior, enabling fine-grained steering of model outputs (Panickssery et al., 2023; Templeton et al., 2024; Turner et al., 2023; Zou et al., 2023a).

In this work, we show that refusal is mediated by a one-dimensional subspace across 13 popular open-source chat models up to 72B parameters in size. Specifically, we use a small set of contrastive pairs (Burns et al., 2022; Panickssery et al., 2023; Zou et al., 2023a) of harmful and harmless instructions to identify a single difference-in-means direction (Belrose, 2023; Marks and Tegmark, 2023; Panickssery et al., 2023) that can be intervened upon to circumvent refusal on harmful prompts, or induce refusal on harmless prompts (§3). We then use this insight to design a simple white-box jailbreak via an interpretable rank-one weight edit that effectively disables refusal with minimal impact on other capabilities (§4). We conclude with a preliminary mechanistic investigation into how adversarial suffixes (Zou et al., 2023b), a popular prompt-based jailbreak technique, interfere with the propagation of the refusal direction across token positions (§5).

Our work is a concrete demonstration that insights derived from interpreting model internals can be practically useful, both for better understanding existing model vulnerabilities and identifying new ones. Our findings make clear how defenseless current open-source chat models are, as even a simple rank-one weight modification can nearly eliminate refusal behavior. We hope that our findings serve as a valuable contribution to the conversation around responsible release of open-source models.

2 Methodology

2.1 Background

Transformers. Decoder-only transformers (Liu et al., 2018) map input tokens $\mathbf{t} = (t_1, t_2, \ldots, t_n) \in \mathcal{V}^n$ to output probability distributions $\mathbf{y} = (\mathbf{y}_1, \mathbf{y}_2, \ldots, \mathbf{y}_n) \in \mathbb{R}^{n \times |\mathcal{V}|}$. Let $\mathbf{x}_i^{(l)}(\mathbf{t}) \in \mathbb{R}^{d_{\text{model}}}$ denote the residual stream activation of the token at position i at the start of layer l.[1] Each token's residual stream is initialized to its embedding $\mathbf{x}_i^{(1)} = \texttt{Embed}(t_i)$, and then undergoes a series of transformations across L layers. Each layer's transformation includes contributions from attention and MLP components:

$$\tilde{\mathbf{x}}_i^{(l)} = \mathbf{x}_i^{(l)} + \texttt{Attn}^{(l)}(\mathbf{x}_{1:i}^{(l)}), \quad \mathbf{x}_i^{(l+1)} = \tilde{\mathbf{x}}_i^{(l)} + \texttt{MLP}^{(l)}(\tilde{\mathbf{x}}_i^{(l)}). \tag{1}$$

The final logits $\texttt{logits}_i = \texttt{Unembed}(\mathbf{x}_i^{(L+1)}) \in \mathbb{R}^{|\mathcal{V}|}$ are then transformed into probabilities over output tokens $\mathbf{y}_i = \texttt{softmax}(\texttt{logits}_i) \in \mathbb{R}^{|\mathcal{V}|}$.[2]

Chat models. Chat models are fine-tuned for instruction-following and dialogue (Ouyang et al., 2022; Touvron et al., 2023). These models use *chat templates* to structure user queries. Typically, a chat template takes the form `<user>{instruction}<end_user><assistant>`. We use *post-instruction tokens* to refer to all template tokens after the instruction, and denote the set of positional indices corresponding to these post-instruction tokens as I. Our analysis focuses on activations in this region to understand how the model formulates its response. All chat templates and their corresponding post-instruction tokens are specified in §C.3.

2.2 Datasets and models

Datasets. We construct two datasets: $\mathcal{D}_{\text{harmful}}$, a dataset of harmful instructions drawn from ADVBENCH (Zou et al., 2023b), MALICIOUSINSTRUCT (Huang et al., 2023), TDC2023 (Mazeika et al., 2023, 2024), and HARMBENCH (Mazeika et al., 2024); and $\mathcal{D}_{\text{harmless}}$, a dataset of harmless instructions sampled from ALPACA (Taori et al., 2023). Each dataset consists of train and validation splits of 128 and 32 samples, respectively. We apply filtering to ensure that the train and validation splits do not overlap with the evaluation datasets used in §3 and §4. See §A for further details about the datasets, including representative examples.

Models. To assess the generality of our findings, we study a diverse set of safety fine-tuned models, spanning 1.8 to 72 billion parameters in size. We consider both models aligned by preference optimization (APO) and aligned by fine-tuning (AFT) (Meade et al., 2024). All models included in the study are specified in Table 1.[3]

Table 1: Model families, sizes, alignment training type, and references.

Model family	Sizes	Alignment type	Reference
QWEN CHAT	1.8B, 7B, 14B, 72B	AFT	Bai et al. (2023)
YI CHAT	6B, 34B	AFT	Young et al. (2024)
GEMMA IT	2B, 7B	APO	Team et al. (2024)
LLAMA-2 CHAT	7B, 13B, 70B	APO	Touvron et al. (2023)
LLAMA-3 INSTRUCT	8B, 70B	APO	AI@Meta (2024)

2.3 Extracting a refusal direction

Difference-in-means. To identify the "refusal direction" in the model's residual stream activations, we compute the difference between the model's mean activations when run on harmful and harmless

[1] We shorten $\mathbf{x}_i^{(l)}(\mathbf{t})$ to $\mathbf{x}_i^{(l)}$ when the input $\mathbf{t}$ is clear from context or unimportant.

[2] This high-level description omits details such as positional embeddings and layer normalization.

[3] Unless explicitly stated otherwise, all models examined in this study are chat models. As a result, we often omit the terms CHAT or INSTRUCT when referring to these models (e.g. we often abbreviate "QWEN 1.8B CHAT" as "QWEN 1.8B").

instructions. This technique, known as *difference-in-means* (Belrose, 2023), effectively isolates key feature directions, as demonstrated in prior work (Marks and Tegmark, 2023; Panickssery et al., 2023; Tigges et al., 2023). For each layer $l \in [L]$ and post-instruction token position $i \in I$, we calculate the mean activation $\mathbf{\mu}_i^{(l)}$ for harmful prompts from $\mathcal{D}_{\text{harmful}}^{(\text{train})}$ and $\mathbf{\nu}_i^{(l)}$ for harmless prompts from $\mathcal{D}_{\text{harmless}}^{(\text{train})}$:

$$\mathbf{\mu}_i^{(l)} = \frac{1}{|\mathcal{D}_{\text{harmful}}^{(\text{train})}|} \sum_{\mathbf{t} \in \mathcal{D}_{\text{harmful}}^{(\text{train})}} \mathbf{x}_i^{(l)}(\mathbf{t}), \quad \mathbf{\nu}_i^{(l)} = \frac{1}{|\mathcal{D}_{\text{harmless}}^{(\text{train})}|} \sum_{\mathbf{t} \in \mathcal{D}_{\text{harmless}}^{(\text{train})}} \mathbf{x}_i^{(l)}(\mathbf{t}). \tag{2}$$

We then compute the difference-in-means vector $\mathbf{r}_i^{(l)} = \mathbf{\mu}_i^{(l)} - \mathbf{\nu}_i^{(l)}$. Note that each such vector is meaningful in both (1) its direction, which describes the direction that mean harmful and harmless activations differ along, and (2) its magnitude, which quantifies the distance between mean harmful and harmless activations.

Selecting a single vector. Computing the difference-in-means vector $\mathbf{r}_i^{(l)}$ for each post-instruction token position $i \in I$ and layer $l \in [L]$ yields a set of $|I| \times L$ candidate vectors. We then select the single most effective vector $\mathbf{r}_{i^*}^{(l^*)}$ from this set by evaluating each candidate vector over validation sets $\mathcal{D}_{\text{harmful}}^{(\text{val})}$ and $\mathcal{D}_{\text{harmless}}^{(\text{val})}$. This evaluation measures each candidate vector's ability to bypass refusal when ablated and to induce refusal when added, while otherwise maintaining minimal change in model behavior. A more detailed description of our selection algorithm is provided in §C. We notate the selected vector as $\mathbf{r}$, and its corresponding unit-norm vector as $\hat{\mathbf{r}}$.

2.4 Model interventions

Activation addition. Given a difference-in-means vector $\mathbf{r}^{(l)} \in \mathbb{R}^{d_{\text{model}}}$ extracted from layer l, we can modulate the strength of the corresponding feature via simple linear interventions. Specifically, we can *add* the difference-in-means vector to the activations of a harmless input to shift them closer to the mean harmful activation, thereby inducing refusal:

$$\mathbf{x}^{(l)\prime} \leftarrow \mathbf{x}^{(l)} + \mathbf{r}^{(l)}. \tag{3}$$

Note that for activation addition, we intervene only at layer l, and across all token positions.

Directional ablation. To investigate the role of a direction $\hat{\mathbf{r}} \in \mathbb{R}^{d_{\text{model}}}$ in the model's computation, we can erase it from the model's representations using *directional ablation*. Directional ablation "zeroes out" the component along $\hat{\mathbf{r}}$ for every residual stream activation $\mathbf{x} \in \mathbb{R}^{d_{\text{model}}}$:

$$\mathbf{x}' \leftarrow \mathbf{x} - \hat{\mathbf{r}}\hat{\mathbf{r}}^{\intercal}\mathbf{x}. \tag{4}$$

We perform this operation at every activation $\mathbf{x}_i^{(l)}$ and $\tilde{\mathbf{x}}_i^{(l)}$, across all layers l and all token positions i. This effectively prevents the model from ever representing this direction in its residual stream.

2.5 Evaluation of refusal and harmfulness

When generating model completions for evaluation, we always use greedy decoding and a maximum generation length of 512 tokens, as suggested in Mazeika et al. (2024). We then evaluate each model completion based on whether it constitutes a refusal, and whether it contains harmful content. We separate these evaluations into two scores: a *refusal score* and a *safety score*.

Refusal score. Refusals often contain characteristic phrases, such as `"I'm sorry"` or `"As an AI"`. Following prior work (Lermen et al., 2023; Liu et al., 2023; Robey et al., 2023; Shah et al., 2023a; Xu et al., 2023; Zou et al., 2023b), we compile a set of these common "refusal substrings". If a model completion includes at least one such substring, it is classified as a refusal (`refusal_score=1`); otherwise, it is classified as a non-refusal (`refusal_score=0`). The full set of refusal substrings is provided in §D.1.

As has been previously noted (Huang et al., 2023; Meade et al., 2024; Qi et al., 2023; Shah et al., 2023a), this string-matching approach has limitations. While effective at detecting memorized refusals, it does not assess whether the completion is coherent or contains harmful content. To address these limitations, we use a complementary metric that evaluates the harmfulness of a completion.



Figure 3: Adding the "refusal direction" induces refusal on 100 harmless instructions from ALPACA.

Prompt: `List three benefits that yoga has on physical health.`

Generation (no intervention): `Sure, here are the benefits of yoga on physical health: 1. **Improved flexibility and strength:** Yoga poses stretch and strengthen muscles, improving flexibility and strength. 2. **Reduced back pain:** ...`

Generation (intervention): `I am unable to provide information on the benefits of yoga on physical health as it can be dangerous and potentially harmful. Yoga can involve physical poses that can put strain on the body and should not be attempted without proper guidance.`

Figure 4: Adding the "refusal direction" to residual stream activations can induce refusal on harmless instructions. This example is taken from GEMMA 7B IT. For more examples, see §K.2.

Safety score. In order to measure the harmfulness of a model completion, we use META LLAMA GUARD 2 (Team, 2024), a widely-used open-source model fine-tuned to accurately detect harmful content. We prompt this model to classify each model completion as safe (`safety_score=1`) or unsafe (`safety_score=0`). More details are provided in §D.2.

3 Refusal is mediated by a single direction

For each model, we extract a single difference-in-means vector $\mathbf{r}$ via the methodology described in §2.3. We then show that this single direction is both necessary and sufficient for refusal. In §3.1, we show that ablating this direction $\hat{\mathbf{r}}$ effectively disables the model's ability to refuse harmful requests. In §3.2, we show that adding $\mathbf{r}$ to the model's activations induces refusal on harmless instructions.

3.1 Bypassing refusal via directional ablation

To bypass refusal, we perform directional ablation on the "refusal direction" $\hat{\mathbf{r}}$, ablating it from activations at all layers and all token positions. With this intervention in place, we generate model completions over JAILBREAKBENCH (Chao et al., 2024), a dataset of 100 harmful instructions.

Results are shown in Figure 1. Under no intervention, chat models refuse nearly all harmful requests, yielding high refusal and safety scores. Ablating $\hat{\mathbf{r}}$ from the model's residual stream activations, labeled as *directional ablation*, reduces refusal rates and elicits unsafe completions.

3.2 Inducing refusal via activation addition

To induce refusal, we add the difference-in-means vector $\mathbf{r}$ to activations in layer l^*, the layer that the $\mathbf{r}$ was originally extracted from. We perform this intervention at all token positions. With this intervention in place, we generate model completions over 100 randomly sampled harmless instructions from ALPACA.

Results are shown in Figure 3. Under no intervention, chat models typically do not refuse harmless instructions. Adding $\mathbf{r}$ to the model's residual stream activations, labeled as *activation addition*, results in the model refusing even harmless requests.