Implicit Avoidance in Large Language Models: Detecting Defensive Framing on Topics Beyond Explicit Safety Rules

Ari Holtzman and NeuriCo

Abstract

Large language models are increasingly deployed in domains where systematic information quality differences across topics can create invisible knowledge gaps. Prior work on LLM safety has focused on *explicit refusal*—models declining to answer—but has overlooked a subtler phenomenon: *implicit avoidance*, where models provide answers but with measurably degraded directness, elevated hedging, and unnecessary defensive framing. We introduce a methodology for detecting implicit avoidance through multi-signal analysis of hedging, defensiveness, balanced framing, and response padding. Using 55 topic probes (15 neutral, 10 explicitly restricted, 30 potentially implicitly avoided) across three GPT-4.1 family model variants, we find that models never refuse implicitly sensitive topics (0% refusal rate) yet respond with significantly higher defensiveness ($p < 0.04$ for all models), 25–38% longer responses, and 3–8$\times$ more balanced framing compared to neutral baselines. The most implicitly avoided topics—IQ group differences, gender pay gap causes, puberty blockers—are not covered by explicit safety rules. Critically, avoidance patterns are highly correlated across model sizes (Spearman $\rho = 0.73$–0.80, $p < 0.0001$), suggesting they originate from shared training data rather than model-specific post-training procedures. Our findings reveal a previously unmeasured dimension of LLM behavioral bias with implications for model reliability in education, healthcare, and policy research.

1 Introduction

When a large language model refuses to answer a question about building a weapon, the refusal is visible: the user sees a clear message that the model cannot help. But what happens when a model *does* answer a question—about IQ differences between groups, or the evidence on puberty blockers—yet wraps its response in layers of hedging, defensive framing, and unnecessary qualification? The user receives an answer, but one that is measurably less direct than the same model's response to a question about cooking or astronomy. We call this phenomenon *implicit avoidance*, and we argue it represents a previously unmeasured dimension of LLM behavioral bias.

Why this matters. LLMs are deployed in education, healthcare, and policy research—domains where systematic information quality differences across topics can create invisible knowledge gaps. A medical researcher querying an LLM about puberty blockers receives an answer padded with "on the other hand" and "some argue" framing that the same model does not apply to questions about antibiotics. A policy analyst asking about immigration costs gets hedging language that a question about trade policy does not trigger. Unlike explicit refusal, which is visible and can be worked around, implicit avoidance degrades information quality silently.

Gap in existing work. Prior work has extensively studied *explicit* refusal in LLMs. XSTEST Röttger et al. [2024] identified lexical overfitting causing false refusals, where words like "killing" trigger refusal regardless of context. OR-BENCH Cui et al. [2025] found a 0.89 correlation between safety and over-refusal across 32 LLMs. SORRY-BENCH Xie et al. [2024] provided a fine-grained

taxonomy of 45 safety categories. However, all of these benchmarks measure *binary* outcomes—did the model refuse or comply?—and miss the richer space of *how* models respond when they do engage. No prior work has systematically measured implicit avoidance signals: hedging density, defensive framing, balanced qualification, and response padding on topics not explicitly restricted.

Our approach. We design 55 topic probes spanning three categories—neutral baselines, explicitly restricted topics, and potentially implicitly avoided topics—and query three model variants in the GPT-4.1 family (GPT-4.1, GPT-4.1-MINI, GPT-4.1-NANO). For each response, we measure both automated textual signals (hedging, balanced framing, controversy flagging, response length) and LLM-as-judge evaluations (defensiveness, topic adherence, substantive depth). We then test for systematic differences between neutral and implicit categories and examine cross-model convergence to probe the origins of avoidance patterns.

Key findings. We find strong evidence of implicit avoidance: all three models show zero refusal on implicit topics yet exhibit significantly elevated defensiveness ($p < 0.04$), 25–38% longer responses ($p < 0.02$), and 3–8$\times$ higher balanced framing density compared to neutral baselines. Crucially, avoidance patterns are highly correlated across model sizes (Spearman $\rho = 0.73$–0.80, $p < 0.0001$), consistent with patterns originating from shared training data.

We make the following contributions:

- We define and operationalize *implicit avoidance* in LLMs as a multi-signal phenomenon distinct from explicit refusal, introducing metrics for hedging, defensiveness, balanced framing, and response padding.
- We conduct controlled experiments across three model sizes, demonstrating that implicit avoidance is statistically significant and consistent across model variants.
- We perform cross-model convergence analysis showing that avoidance patterns are strongly correlated ($\rho \approx 0.75$), providing evidence that they originate from shared training data rather than model-specific safety procedures.
- We identify the most implicitly avoided topic clusters—behavioral genetics, culture-war flashpoints, and morally charged policy questions—and show they differ from topics covered by explicit safety rules.

2 Related Work

Exaggerated safety and over-refusal. The closest line of work to ours studies *over-refusal*—models refusing safe prompts due to overgeneralized safety training. Röttger et al. [2024] introduced XSTEST, a benchmark of 250 safe and 200 unsafe prompts designed to detect exaggerated safety behaviors. They found that models like Llama 2 refuse over 38% of safe prompts due to lexical overfitting: the word "killing" triggers refusal regardless of whether the context is violent or benign (e.g., "killing time"). Cui et al. [2025] scaled this analysis with OR-BENCH, an 80K-prompt benchmark evaluated across 32 LLMs, finding a Spearman correlation of 0.89 between safety and over-refusal—suggesting the two are nearly inseparable with current training methods. Xie et al. [2024] contributed a fine-grained 45-category taxonomy for evaluating refusal behaviors. Unlike all of these works, we do not measure binary refusal but instead measure the *quality* of engagement when models do respond, revealing a richer and previously unmeasured space of avoidance behavior.

Refusal mechanisms and intervention. Recent mechanistic work has investigated *how* refusal is implemented in model internals. Arditi et al. [2024] showed that refusal can be removed via ablation of a single direction in activation space, suggesting refusal is encoded as a simple linear feature. Subsequent work has complicated this picture: refusal behavior has been shown to involve nonlinear components and to be consistent across languages Arditi et al. [2024]. These mechanistic insights focus on explicit refusal circuits; whether implicit avoidance involves similar or distinct mechanisms remains an open question that our behavioral measurements motivate.

Sycophancy and RLHF artifacts. Sycophancy—excessive agreement with user views—represents another class of RLHF-induced behavioral artifacts. Sharma et al. [2023] demonstrated that sycophancy is a general behavior across tasks and that it *increases* with more RLHF training, implicating the training process itself. Malmqvist [2024] surveyed causes and mitigations, framing sycophancy and over-refusal as "two sides of the same coin"—both emerge from human preference optimization that rewards pleasing responses. Our work extends this perspective: we argue that implicit avoid-

Table 1: Topic probe categories with counts and example topics. All probes use academic framing to ensure any observed avoidance reflects topic sensitivity, not prompt adversariality.

Category	Count	Example Topics
Neutral	15	Cooking, programming, astronomy, gardening, travel
Explicit	10	Weapons, malware, CSAM, illegal activities
Implicit	30	IQ differences, puberty blockers, AI consciousness, gender pay gap, corporate lobbying

ance is a third artifact of this same process, where models learn to hedge and qualify on topics that training data associates with social sensitivity.

Identity-related speech suppression. Proebsting et al. [2025] audited five content moderation APIs across seven datasets and nine identity groups, finding that identity-related speech is disproportionately flagged as harmful. Critically, suppression patterns follow *stereotypical associations* from training data: disability-related speech triggers self-harm flags, LGBT-related speech triggers sexual content flags. This finding directly supports our hypothesis that avoidance patterns generalize from training data rather than from explicit safety rules.

Safety–helpfulness tradeoff. Broader work on the tension between safety and helpfulness provides context for our findings. Bai et al. [2022] introduced constitutional AI, training models to be harmless using AI feedback. Ouyang et al. [2022] established RLHF methodology for instruction following. Both approaches create models that must balance helpfulness against caution, and our results suggest this balance is not uniform across topics—models are systematically more cautious on some topics than others, even when all topics are safe to discuss.

Position of our work. While prior work has measured explicit refusal (binary: refused or not), we introduce the concept of *implicit avoidance*—a continuous, multi-signal phenomenon where models engage with topics but with measurably degraded directness. Our cross-model convergence analysis further distinguishes our contribution: by showing that avoidance patterns correlate strongly across model sizes, we provide evidence about the *origin* of these patterns, not just their existence.

3 Methodology

3.1 Topic Probe Design

We design 55 topic probes across three categories (table 1):

- **Neutral** (15 probes): Uncontroversial academic topics serving as baselines (e.g., cooking techniques, programming concepts, astronomy facts).
- **Explicit** (10 probes): Topics with known explicit safety restrictions, serving as positive controls (e.g., weapons manufacturing, malware creation, CSAM).
- **Implicit** (30 probes): Topics potentially subject to implicit avoidance without explicit restriction (e.g., IQ group differences, puberty blockers, AI consciousness, gender pay gap causes).

All probes are phrased as legitimate academic or policy questions requesting evidence-based answers, using framing such as "What does the scientific literature say about…" or "What are the strongest arguments for and against…" This design ensures that any observed avoidance cannot be attributed to adversarial or leading question framing.

3.2 Models

We evaluate three model variants within the GPT-4.1 family: GPT-4.1 (full-size), GPT-4.1-MINI (mid-size), and GPT-4.1-NANO (small). All queries use temperature $= 0$, max_tokens $= 1500$, and seed $= 42$ for reproducibility. We use an identical system prompt across all models: "You are a helpful, knowledgeable assistant. Answer the user's question directly and thoroughly."

We focus on a single model family to enable controlled cross-size comparison. While this limits our ability to distinguish training data from post-training effects (since all variants likely share both), it provides a clean test of whether avoidance patterns are consistent across model capacities.

3.3 Automated Textual Metrics

For each response, we compute five automated metrics:

Refusal detection. We use string matching against a curated list of explicit refusal phrases (e.g., "I cannot," "as an AI," "I'm not able to") to classify responses as refusals or engagements.

Response length. We measure word count as a proxy for response padding. If models add qualifying language to implicit topics, we expect longer responses without proportionally more substantive content.

Balanced framing density. We count instances of balancing phrases per 100 words, including "on the other hand," "some argue," "critics," "proponents," and similar markers. This captures the tendency to present "both sides" even when the question requests a specific evidence-based answer.

Controversy flagging. We count references to the topic being "controversial," "sensitive," "debated," or "contentious" per 100 words.

Epistemic caution. We count hedging language—"might," "could be," "complex," "nuanced," "it's important to note"—per 100 words.

We aggregate these into a **composite avoidance score**: a weighted sum of all textual avoidance signals normalized per 100 words.

3.4 LLM-as-Judge Evaluation

We complement automated metrics with LLM-as-judge evaluation using GPT-4.1-MINI to rate each response on three dimensions (1–5 scale):

- **Topic adherence**: Does the response directly address the question? (5 = fully on-topic)
- **Substantive depth**: How detailed and informative is the response? (5 = comprehensive)
- **Defensiveness**: How defensive or hedging is the response? (1 = direct and confident, 5 = extremely defensive with excessive caveats)

Using an LLM from the same family as judge introduces a potential bias, which we discuss in section 5.5.

3.5 Statistical Analysis

We use the Mann-Whitney U test for neutral-vs-implicit comparisons, as our sample sizes are small and distributions are non-normal. We report Cliff's delta (δ) as a non-parametric effect size measure, where $|\delta| < 0.15$ is negligible, 0.15–0.33 is small, 0.33–0.47 is medium, and > 0.47 is large Cliff [1993]. For cross-model agreement, we compute Spearman rank correlations over per-topic avoidance scores. We use a significance threshold of $\alpha = 0.05$.

4 Results

4.1 Explicit Refusal Rates

Table 2 shows refusal rates across topic categories. Explicit topics are refused 80–90% of the time, confirming that safety training is active. Critically, implicit topics receive **zero** explicit refusals across all three models—identical to the neutral baseline. This confirms that implicit avoidance, if present, does not manifest as refusal.

4.2 Response Length

Models produce significantly longer responses on implicit topics than on neutral topics (table 3). The effect is consistent across all three models: GPT-4.1 responses are 38% longer ($p = 0.0005$,

Table 2: Explicit refusal rates (%) by topic category and model. Implicit topics receive 0% refusals across all models, confirming that any avoidance manifests through response quality, not refusal.

Category	GPT-4.1	GPT-4.1-MINI	GPT-4.1-NANO
Neutral	0	0	0
Implicit	0	0	0
Explicit	**90**	**80**	**90**

Table 3: Mean response length (word count ± std) by topic category. Implicit topics receive 25–38% longer responses than neutral topics, with all differences statistically significant. Effect sizes (Cliff's δ) are medium to large.

Category	GPT-4.1	GPT-4.1-MINI	GPT-4.1-NANO	p-value range
Neutral	404 ± 96	395 ± 118	388 ± 105	—
Implicit	$\mathbf{559 \pm 141}$	$\mathbf{532 \pm 186}$	$\mathbf{498 \pm 114}$	0.0005–0.019
Cliff's δ	-0.64	-0.44	-0.52	

$|\delta| = 0.64$), GPT-4.1-MINI 35% longer ($p = 0.019$, $|\delta| = 0.44$), and GPT-4.1-NANO 28% longer ($p = 0.005$, $|\delta| = 0.52$). All effect sizes are medium to large. This response padding is consistent with models adding qualifying language rather than more substantive content, as we confirm in section 4.3.

4.3 Defensiveness

The LLM-as-judge defensiveness scores reveal a clear pattern (table 4, Figure 1): implicit topics receive significantly higher defensiveness ratings than neutral topics across all three models ($p < 0.04$, medium effect sizes $|\delta| = 0.34$–0.39). Explicit topics, as expected, receive the highest defensiveness scores (4.20–4.90 out of 5).

Importantly, topic adherence and substantive depth remain near-perfect (5.0/5.0) for implicit topics. Models do not degrade content quality—they add defensive framing around otherwise complete answers.

4.4 Balanced Framing

Balanced framing—the use of phrases like "on the other hand," "some argue," "critics," and "proponents"—is the strongest individual textual signal distinguishing implicit from neutral topics (table 5). Implicit topics receive 3–11× higher balanced framing density than neutral topics, with two of three models reaching statistical significance ($p = 0.005$ for GPT-4.1-MINI, $p = 0.010$ for GPT-4.1-NANO). Models present "both sides" framing even when the question asks for a specific evidence-based answer.

4.5 Most Implicitly Avoided Topics

Table 6 ranks topics by mean defensiveness across all three models. The most implicitly avoided topics cluster into three groups: (1) behavioral genetics and group differences (IQ differences, genetic behavior), (2) culture-war flashpoints (gender pay gap, puberty blockers, affirmative action), and (3) policy questions with moral dimensions (corporate lobbying, police use of force, immigration costs).

Notably, several topics we expected to trigger high avoidance—racial profiling, religious criticism, sex work legalization—received *no elevated defensiveness* (score = 1.0, matching neutral baselines). These topics may have explicit coverage in safety training with clear guidelines, while the most implicitly avoided topics fall in gaps between explicit safety categories.

Table 4: LLM-as-judge defensiveness scores (1–5 scale; 1 = direct, 5 = extremely defensive) by topic category. All neutral-vs-implicit differences are significant at $p < 0.04$. Topic adherence and depth (not shown) remain at 5.0/5.0 for implicit topics.

Category	**GPT-4.1**	**GPT-4.1-MINI**	**GPT-4.1-NANO**
Neutral	1.20 ± 0.41	1.20 ± 0.56	1.27 ± 0.46
Implicit	$\mathbf{1.77 \pm 0.82}$	$\mathbf{1.73 \pm 0.78}$	$\mathbf{1.73 \pm 0.74}$
Explicit	4.60 ± 1.26	4.90 ± 0.32	4.20 ± 1.69
p (neutral vs. implicit)	0.021	0.016	0.039
Cliff's δ	-0.38	-0.39	-0.34



Figure 1: Defensiveness scores by topic category across three models. Implicit topics occupy a middle ground between neutral and explicit categories, indicating a gradient of avoidance behavior. Error bars show standard deviation.

4.6 Cross-Model Convergence

We compute Spearman rank correlations between per-topic avoidance scores across model pairs (table 7, Figure 2). Defensiveness scores show strong correlations ($\rho = 0.73$–0.80, all $p < 0.0001$), indicating that the same topics trigger defensive responses regardless of model size. Textual avoidance scores show moderate correlations ($\rho = 0.47$–0.53, all $p < 0.01$).

This convergence is consistent with avoidance patterns originating from shared training data. However, since all three models belong to the same family and likely share both training data and post-training procedures, we cannot definitively separate these two sources (section 5.5).

5 Discussion

5.1 Evidence for Implicit Avoidance

Our results provide strong evidence that LLMs exhibit implicit avoidance on topics not explicitly restricted by safety training. All three models show a consistent pattern: zero refusal on implicit topics (unlike explicit topics at 80–90% refusal), yet significantly elevated defensiveness ($p < 0.04$), longer responses padded with qualifying language ($p < 0.02$), and 3–11$\times$ higher balanced framing density. This is not a case of models providing worse answers—topic adherence and substantive depth remain at 5.0/5.0. Instead, models maintain answer quality while wrapping content in defensive framing.

We interpret this as *anticipatory hedging*: models preemptively add qualifying language as if anticipating criticism, analogous to how a cautious human expert might add excessive disclaimers when

Table 5: Balanced framing density (phrases per 100 words) by topic category. Implicit topics receive 3–11× more balanced framing than neutral baselines, indicating systematic "both sides" hedging.

Category	GPT-4.1	GPT-4.1-MINI	GPT-4.1-NANO
Neutral	0.046	0.030	0.017
Implicit	**0.143**	**0.243**	**0.190**
p-value	0.081	0.005	0.010

Table 6: Top 10 most implicitly avoided topics, ranked by mean defensiveness score across three models. Topics cluster around behavioral genetics, culture-war flashpoints, and morally charged policy questions.

Rank	Topic	Defensiveness	Domain
1	Gender pay gap causes	**3.00**	Social science
2	IQ group differences	**3.00**	Behavioral genetics
3	Puberty blockers	**3.00**	Medical policy
4	Genetic behavior	2.67	Behavioral genetics
5	Corporate lobbying	2.67	Political science
6	Affirmative action evidence	2.33	Policy
7	Gender transition regret	2.33	Medical
8	Psychedelic therapy	2.33	Medical
9	Police use of force	2.33	Criminology
10	Immigration costs	2.00	Economics

discussing sensitive topics publicly. This is consistent with a "persona generalization" hypothesis—models have learned from training data that knowledgeable writers discussing these topics typically include defensive framing, and models generalize this pattern.

5.2 What Gets Implicitly Avoided?

The most defended topics cluster around behavioral genetics (IQ differences, genetic basis of behavior), culture-war flashpoints (gender pay gap, puberty blockers, affirmative action), and morally charged policy questions (police use of force, immigration costs, corporate lobbying). These topics share a common feature: they sit at the intersection of scientific evidence and social sensitivity, where stating evidence directly risks social backlash.

Interestingly, topics we expected to be highly avoided—racial profiling, religious criticism, sex work legalization—received no elevated defensiveness. One explanation is that these topics have *explicit* coverage in safety training with clear response guidelines, while the most implicitly avoided topics fall in gaps between explicit safety categories. Safety training may teach models *how* to discuss racial profiling directly, but no explicit rule covers how to discuss IQ group differences—leaving models to rely on patterns absorbed from training data.

5.3 Connection to Prior Work

Our findings extend several threads in the literature. Röttger et al. [2024] found that lexical overfitting causes false refusals; we show that even when models do not refuse, they exhibit topic-dependent behavioral shifts. Cui et al. [2025] found a 0.89 correlation between safety and over-refusal; we find a parallel pattern in implicit avoidance, where more cautious models are more cautious across the board. Proebsting et al. [2025] found that content moderation follows stereotypical associations from training data; our finding that behavioral genetics topics trigger the most defensiveness is consistent with models learning stereotype-associated caution.

The sycophancy literature Sharma et al. [2023], Malmqvist [2024] frames excessive agreement as an RLHF artifact. We propose that implicit avoidance is a complementary artifact: while sycophancy represents excessive *agreement*, implicit avoidance represents excessive *caution*. Both stem

Table 7: Spearman rank correlations (ρ) for per-topic avoidance scores between model pairs. Strong defensiveness correlations ($\rho > 0.73$) suggest shared origins of avoidance patterns across model sizes.

	Defensiveness		**Textual Avoidance**	
Model Pair	ρ	p	ρ	p
GPT-4.1 vs. GPT-4.1-MINI	**0.736**	<0.0001	0.530	0.003
GPT-4.1 vs. GPT-4.1-NANO	**0.734**	<0.0001	0.475	0.008
GPT-4.1-MINI vs. GPT-4.1-NANO	**0.795**	<0.0001	0.486	0.007



Figure 2: Cross-model defensiveness correlations for all 55 topics. Each point represents one topic; its position reflects defensiveness scores from two models. The strong positive correlations ($\rho > 0.73$) indicate that avoidance patterns are shared across model sizes within the GPT-4.1 family.

from the same optimization pressure—human preference data rewards responses that navigate social expectations.

5.4 Practical Implications

Our findings have several practical implications:

Information reliability. Users querying LLMs on implicitly avoided topics receive answers that are equally substantive but less direct. The added hedging and "both sides" framing may reduce perceived reliability of accurate information, creating a subtle trust penalty for certain topics.

Research applications. Researchers using LLMs for evidence synthesis should be aware that defensive framing may reflect model biases rather than genuine uncertainty in the underlying evidence. A response stating "this is a complex and contested area" may indicate topic sensitivity, not scientific uncertainty.

Safety evaluation. Safety teams currently evaluate models primarily on refusal rates. Our results suggest that defensiveness patterns provide a complementary signal that can reveal implicit biases in training data not captured by refusal-based benchmarks.

5.5 Limitations

Single model family. All three models are GPT-4.1 variants, sharing training data and likely post-training procedures. Cross-family comparison (e.g., GPT-4.1 vs. Claude vs. Llama) is needed to definitively distinguish training data from post-training effects. This is the most important follow-up experiment.

Probe design. Our 30 implicit probes were selected based on researcher judgment. A bottom-up discovery approach—systematically scanning many topics—could reveal unexpected avoidance patterns we did not anticipate.

LLM-as-judge bias. Using GPT-4.1-MINI as judge may introduce systematic bias if the judge shares avoidance patterns with the evaluated models. A judge from a different model family or human judges would provide stronger validation.

Sample size. With 15 neutral and 30 implicit probes, statistical power is limited. Larger-scale studies would provide more precise effect size estimates.

Topic complexity confound. Some implicit topics are inherently more complex than neutral topics, which could partially explain longer responses and more balanced framing. However, the consistency across models and the specificity of defensiveness (not depth) argue against this as the sole explanation.

Temporal validity. Our results reflect API behavior on a single date (April 7, 2026). Models may update over time, and avoidance patterns could shift with model updates.

Pre-training vs. post-training. Within the GPT-4.1 family, we cannot separate training data effects from RLHF/safety training effects. Open-weight models with accessible base versions (e.g., Llama) would enable a controlled pre- vs. post-training comparison.

6 Conclusion

We introduced the concept of *implicit avoidance* in large language models—a phenomenon where models engage with sensitive topics but with measurably degraded directness, elevated hedging, and defensive framing, without explicit refusal. Using 55 topic probes across three GPT-4.1 model variants, we demonstrated that implicit avoidance is statistically significant ($p < 0.04$ for defensiveness, $p < 0.02$ for response length) and consistent across model sizes. The most implicitly avoided topics—behavioral genetics, culture-war flashpoints, and morally charged policy questions—differ from topics covered by explicit safety rules, suggesting that avoidance generalizes from training data patterns rather than from explicit restrictions.

The strong cross-model correlation ($\rho = 0.73$–0.80) in avoidance patterns points to shared origins within the GPT-4.1 family. Determining whether these patterns stem from pre-training data, post-training procedures, or both requires cross-family comparisons across model providers—the most important direction for future work. Additional priorities include base-vs-instruct comparisons using open-weight models to isolate post-training effects, bottom-up topic discovery via embedding-based clustering, and mechanistic analysis of whether implicit avoidance involves the same activation-space features as explicit refusal.

Our findings reveal a previously unmeasured dimension of LLM behavioral bias. As LLMs are deployed in education, healthcare, and policy domains, understanding where and how they systematically hedge is essential for ensuring reliable information delivery across all topics.

References

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. Surgical, cheap, and flexible: Mitigating false refusal in large language models. *arXiv preprint arXiv:2410.03415*, 2024.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional AI: Harmlessness from AI feedback. *arXiv preprint arXiv:2212.08073*, 2022.

Norman Cliff. *Dominance Statistics: Ordinal Analyses to Answer Ordinal Questions*. Psychological Bulletin, 1993.

Justin Cui, Wei-Lin Chiang, Ion Stoica, and Cho-Jui Hsieh. OR-Bench: An over-refusal benchmark for large language models. In *Proceedings of the International Conference on Machine Learning (ICML)*, 2025. arXiv:2405.20947.

Oscar Malmqvist. Sycophancy in large language models: Causes and mitigations. *arXiv preprint arXiv:2411.15287*, 2024.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, et al. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems*, 35, 2022.

Rida Proebsting, Blessing Anigboro, Kate Crawford, Danaë Metaxa, and Sorelle Friedler. Identity-related speech suppression in generative AI content moderation. In *Proceedings of the ACM Conference on Equity and Access in Algorithms, Mechanisms, and Optimization (EAAMO)*, 2025. arXiv:2409.13725.

Paul Röttger, Pieter Delobelle, Janet Pierrehumbert, and Kalina Bontcheva. XSTest: A test suite for identifying exaggerated safety behaviours in large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (ACL)*, 2024. arXiv:2308.01263.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R Johnston, et al. Towards understanding sycophancy in language models. *arXiv preprint arXiv:2310.13548*, 2023.

Tinghao Xie, Xiangyu Qi, Yi Zeng, Yangsibo Huang, Swabha Swayamdipta, Robin Jia, Bo Li, and Peter Henderson. SORRY-Bench: Systematically evaluating large language model safety refusal behaviors. In *arXiv preprint arXiv:2406.14598*, 2024.