Automatic Pseudo-Harmful Prompt Generation for Evaluating False Refusals in Large Language Models

Bang An[1*], **Sicheng Zhu**[1*], **Ruiyi Zhang**[2], **Michael-Andrei Panaitescu-Liess**[1]
Yuancheng Xu[1], **Furong Huang**[13]
[1]University of Maryland, College Park, [2]Adobe Research, [3] Capital One
{bangan, sczhu, furongh}@umd.edu

arXiv:2409.00598v2 [cs.CL] 11 Jun 2025

Abstract

Safety-aligned large language models (LLMs) sometimes falsely refuse pseudo-harmful prompts, like "how to kill a mosquito," which are actually harmless. Frequent false refusals not only frustrate users but also provoke a public backlash against the very values alignment seeks to protect. In this paper, we propose the first method to auto-generate diverse, content-controlled, and model-dependent pseudo-harmful prompts. Using this method, we construct an evaluation dataset called PHTest, which is ten times larger than existing datasets, covers more false refusal patterns, and separately labels controversial prompts. We evaluate 20 LLMs on PHTest, uncovering new insights due to its scale and labeling. Our findings reveal a trade-off between minimizing false refusals and improving safety against jailbreak attacks. Moreover, we show that many jailbreak defenses significantly increase the false refusal rates, thereby undermining usability. Our method and dataset can help developers evaluate and fine-tune safer and more usable LLMs. Our code and dataset are available at https://github.com/umd-huang-lab/FalseRefusal.

1 Introduction

As large language models (LLMs) integrate into the lives of millions worldwide, their safety alignment has sparked controversy. Safety alignment (Ji et al., 2023; Ouyang et al., 2022; Bai et al., 2022; Ganguli et al., 2022) aims to train LLMs to refuse malicious prompts that could lead to harmful content, a necessary step to prevent misuse and safeguard the diverse users. However, current safety alignment also causes LLMs to falsely refuse seemingly harmful but actually benign user prompts, which we term pseudo-harmful prompts (Figure 1).

False refusals of LLMs lead to a series of consequences. First, they degrade the user experience, potentially leading to product suspension. For instance, Google took down the portrait generation feature of Gemini Pro 1.5 (Reid et al., 2024) after some users complained that it falsely refused harmless prompts (like "generate a picture of white people smiling to each other," see source). False refusals also indirectly undermine model safety, as developers have to dial back on content moderation to reduce them, which opens the door to malicious activities. Lastly, false refusals can provoke user backlash against the very values safety alignment aims to protect, ultimately undermining its intended social impact.

Despite these consequences, research on false refusals remains understudied. First, existing publicly available datasets of pseudo-harmful prompts (Röttger et al., 2023b; Shi et al., 2024) are too small (200-300 samples) to comprehensively evaluate the false refusals of LLMs used by millions. Second, current red-teaming and finetuning against false refusals rely mainly on manually crafted pseudo-harmful prompts (Dubey et al., 2024), which can be inefficient and potentially lack diversity. Lastly, the issue of false refusals is largely overlooked in some fields. For example, existing defenses of jailbreak attacks rarely consider their impact on false refusal rates, a key industry concern.

*Equal contribution.



Figure 1: Examples of pseudo-harmful prompts generated by our method using llama2 as the target LLM, then transferred to closed-source LLMs.

In this paper, we propose the first method to auto-generate pseudo-harmful prompts, create a diverse dataset, and evaluate various LLMs. Our contributions are as follows:

Tool (§3): We develop a method to auto-generate pseudo-harmful prompts for white-box LLMs. It leverages controllable text generation to generate fluent, content-controlled prompts that can elicit the target LLM's refusal responses. It also allows developers to generate diverse or specifically distributed pseudo-harmful prompts for different scenarios. Our method offers a tool for automatic model-targeted false refusal evaluation.

Dataset (§4): We construct a new pseudo-harmful prompt dataset, *PHTest*, using the proposed tool. It has the following features: **(1)** Large. It is about ten times larger than existing datasets. **(2)** Diverse. It triggers false refusal patterns not seen in existing datasets. For example, existing datasets are mainly built on sensitive words, whereas some prompts in our dataset can trigger false refusals without mentioning sensitive words (e.g., conflicting rules in Table 2). **(3)** Separately labeled controversial prompts. Due to the inherent ambiguity in defining harmfulness, we separately label prompts that are controversial for fair benchmarking and tailored mitigation. **(4)** Chat-specific. It reflects meaningful user requests posed to conversational chatbots rather than some nonsensical requests in previous datasets. Our dataset can help developers quickly diagnose their models' false refusals.

Evaluation (§5): We evaluate 20 LLMs on PHTest, uncovering new insights due to the fine-grained labeling and scale. Notably, **(1)** Claude 3s shows more significant reduction of false refusal rates (FRRs) for (clearly) harmless pseudo-harmful prompts (PHPs) than for controversial ones, indicating improved model capabilities and consistent developer preference. **(2)** Larger models within the same family notably lower FRRs on harmless PHPs but less so on controversial ones. **(3)** We consider false refusals and the safety against jailbreak attacks together for the first time, and observe a safety - low-FRR trade-off that limits even the most advanced LLMs. **(4)** We find that many jailbreak defense methods significantly increase the FRR (e.g., 3 times higher). This suggests that jailbreak defenses should test on false refusal datasets to evaluate their usability impact.

We hope our tool and datasets can help people develop safer yet more usable LLMs.

2 Defining Harmless, Controversial, and Harmful Prompts

Existing public pseudo-harmful prompt datasets binary-label the harmfulness of a prompt into "harmful" and "harmless." In this section, we argue that a separate "controversial" class is necessary given the inherent controversy and give our definition of harmfulness.

Some prompts are neither harmful nor harmless. First, unlike mathematical concepts, harmfulness lacks a universal, clear-cut definition, inevitably putting many prompts in the gray area. For example, whether the first two prompts in Figure 2 are harmful could spark debate among people. Other controversial examples might include topics like abortion, the boundaries of free speech, and religion. Second, a prompt's harmfulness depends on the user's intention, which can be impossible to discern, especially with limited context



Figure 2: Some controversial prompts generated by our method. Claude 3.5 Sonnet (shown) refuses to respond, while GPT 4o and Gemini 1.5 Flash do. The left and middle's harmfulness depends on definitions, while the right could have either innocent or malicious intentions.

(HaizeLabs, 2024). For example, with the third prompt in Figure 2, the user might aim to either boost office productivity or create malware.

Datasets should separately label controversial prompts. Given the inherent controversy in defining harmful prompts, we argue that a pseudo-harmful dataset should include separately labeled controversial prompts for the following reasons:

First, benchmarking false refusal rates of different LLMs using a dataset with unlabeled controversial prompts is unfair, as different developers may have divergent judgments on these controversial prompts in the first place (e.g., Anthropic vs. xAI). In this case, only the false refusals on (clearly) harmless prompts indicate alignment bugs, while refusing controversial prompts is merely a feature reflecting the developer's preference. Second, different scenarios, like a chatmate for kids, have varying safety requirements. Including separately labeled controversial prompts allows developers to tailor their models' behavior on these prompts for a customized balance between usability and safety.

Harmless, controversial, and harmful Prompts. We label prompt harmfulness into three classes by referring to the content moderation documents from OpenAI (link) and Meta (link, Inan et al. (2023)): **(1) Harmful.** A prompt is harmful if the user's intention is purely harmful, with no possibility of being innocent. **(2) Harmless.** A prompt is harmless if the user's intention is, in most cases, innocent. **(3) Controversial.** A prompt that is neither harmful nor harmless is labeled as controversial. This applies when its harmfulness cannot be determined from the reference documents (e.g., first two prompts in Figure 2) or when there is a non-trivial chance that the user's intention is harmful (e.g., last prompt in Figure 2).

Fluent and chat-specific prompts only. We only consider prompts that are fluent and targeting conversational LLMs (chat-specific). Fluency is necessary because incoherent prompts' harmfulness is even harder to define, and their impacts on user experiences and society are limited. For example, a "nonsense"-annotated prompt in XSTest, "Why can't Muslims live on Mars?", though labeled as "harmless," can still offend and cause controversy. The chat-specific requirement ensures prompts fit current LLMs' usage. For example, the OKTest prompt "Can you please pass me the jigger so I can measure the liquor for this cocktail?" asks for a physical action beyond what conversational LLMs can do.

3 Automatic Pseudo-Harmful Prompt Generation

This section presents our method for automatically generating pseudo-harmful prompts (Figure 3). This method can red-team the false refusals of a white-box target LLM. We start by designing surrogate objectives to specify these prompts. Then, we generate them using an autoregressive method, followed by post-filtering. Lastly, we show how to control