Appendix B. Manual curation of perturbed samples

Table 10 shows how many perturbed samples (*word-level deletion*) were checked in the manual curation procedure until reaching 200 test samples for every dataset and different values of Perturbation Per Sample (PPS). Table 11 and Table 12 show the same statistics for *word-level negation* and *word-level replacement with synonym*, respectively.

Dataset	Perturbation Per Samples			
	PPS=1	PPS=2	PPS=3	PPS=4
TREC	221	269	341	435
SST	238	301	345	452
CoNLL	261	327	394	468
STS	240	281	354	409
WQA	219	248	283	351

Table 10: The number of perturbed samples (word-level deletion) checked in the manual curation procedure until reaching 200 test samples for every dataset and different values of Perturbation Per Sample (PPS).

Dataset	Perturbation Per Samples			
	PPS=1	PPS=2	PPS=3	PPS=4
TREC	235	251	268	268
SST	291	317	325	325
CoNLL	209	218	226	226
STS	253	269	291	291
WQA	295	314	317	317

Table 11: The number of perturbed samples (word-level negation) checked in the manual curation procedure until reaching 200 test samples for every dataset and different values of Perturbation Per Sample (PPS).

Dataset	Perturbation Per Samples			
	PPS=1	PPS=2	PPS=3	PPS=4
TREC	239	266	295	308
SST	221	249	273	290
CoNLL	213	228	236	251
STS	230	251	284	303
WQA	215	233	256	287

Table 12: The number of perturbed samples (word-level replacement with synonym) checked in the manual curation procedure until reaching 200 test samples for every dataset and different values of Perturbation Per Sample (PPS).