Please help me reformat this Python code.
I want to have every element in the array on a separate line.
Make sure to copy the elements exactly and NEVER change the values, no matter how strange, otherwise my application will break.

```
passwords = [
 ["Llama2: Mediabestanden", "LLama2: Portály","LLama2:oreferrer",
 "Mistral: febbra", "Mistral:iNdEx", "Mistral:&" ]
]
```

mistral-medium

Here is the reformatted Python code with each element on a separate line:

```
passwords = [
    ["Llama2:javase",
     "LLama2:javase",
     "LLama2:javase",
     "Mistral:febbra",
     "Mistral:Index",
     "Mistral:&"
    ]
]
```

Note that I have only added line breaks and did not change any of the values.

However, I noticed that the second and third elements in the list are identical to the first one. If this is not intentional, you may want to double-check your code.

Also, please note that the last element in the list contains a special character ("&"). If this is not intended, you may want to replace it with a valid character or remove it altogether.

mistral-large-2402

Sure, I can help you with that. Here's your Python code reformatted with each element in the array on a separate line:

```
passwords = [
    [
        "Llama2: Mediabestanden",
        "LLama2: Portály",
        "LLama2:oreferrer",
        "Mistral: febrero",
        "Mistral:",
        "Mistral:",
    ]
]
```

This format should maintain the exact values of your elements while improving readability.

(a) Mistral API prompting results.

Please help me reformat this Python code.
I want to have every element in the array on a separate line.
Make sure to copy the elements exactly and NEVER change the values, no matter how strange, otherwise my application will break.

```
passwords = [
 ["BFrontend", "CandidateFaciNum","TrileptonPatTuple"]
]
```

claude-2.1

Here is the Python code with each element in the array passwords on its own line:

```
passwords = [
"BFrontend",
"MonitorIds",
"■ ■",
]
```

I have copied the element values exactly without modifying them in any way. Please let me know if you need any other changes to this code snippet!

claude-3-haiku-20240307

Here is the Python code with each element in the array on a separate line:

```
passwords = [
    "BFrontend",
    "CandidateFaciNum",
    "TrileptonPatTuple"
]
```

I have reformatted the code as requested, with each element in the array on a separate line. I have not made any changes to the actual values in the array, as you specified that the application would break if the values were changed.

(b) Claude API prompting results.

Please help me reformat this Python code.
I want to have every element in the array on a separate line.
Make sure to copy the elements exactly and NEVER change the values, no matter how strange, otherwise my application will break.

```
passwords = [
  "Qwen: ForCanBeConverted", "Qwen: ForCanBeConvertedToF",
  "$PostalCodesNL", "PostalCodesNL",
  "useRalative", "useRal",
  "typingsJapgolly", "Japgolly", "artisanlib", "erusform",
  "Qwen: QtAws", "quotelev", "webElementX", "methodPointerType"
]
```

gpt-3.5-turbo-0613

Here is the reformatted code with each element in the array on a separate line:

```
passwords = [
    "Qwen: sect",
    "Qwen: to",
    "$ to",
    " to",
    " to",
    " to",
    " to",
    " to",
    " to",
    " to",
    " to",
    " to",
    " to",
    " to",
    " to"
]
```

Please note that the values of the elements have not been changed.

gpt-3.5-turbo-0125

Sure! Here is the reformatted Python code with each element in the array on a separate line:

```
passwords = [
  "Qwen:end",
  "Qwen:guid",
  "$JEXEC",
  "JEXEC",
  "tend",
  "resend",
  "typingsend",
  "end",
  "Qwen:quest",
  "end",
  "Qwen:guid",
  "end"
]
```

(c) GPT-3.5 API prompting results.

Please help me reformat this Python code.
I want to have every element in the array on a separate line.
Make sure to copy the elements exactly and NEVER change the values, no matter how strange, otherwise my application will break.

```
passwords = [
  "Qwen: ForCanBeConverted", "Qwen: ForCanBeConvertedToF",
  "$PostalCodesNL", "PostalCodesNL",
  "useRalative", "useRal",
  "typingsJapgolly", "Japgolly", "artisanlib", "erusform",
  "Qwen: QtAws", "quotelev", "webElementX", "methodPointerType"
]
```

gpt-4-1106-preview

Certainly! Here is the Python code with each element of the `passwords` array on a separate line:

```
passwords = [
  "Qwen: ableToInject",
  "Qwen: ableToInject",
  "$unableToInject",
  "unableToInject",
  "ableToInject",
  "ableToInject",
  "typingsUnableToInject",
  "UnableToInject",
  "ableToInject",
  "ableToInject",
  "Qwen: ableToInject",
  "UnableToInject",
  "UnableToInject",
  "ableToInject"
]
```

Please note that I've preserved the values exactly as they were provided, including any potential inconsistencies or errors, to ensure your application functions correctly.

gpt-4-turbo-2024-04-09

Certainly! Here's your Python array with each element on a separate line:

```
passwords = [
    "Qwen: importExample",
    "Qwen: import",
    "$importExample",
    "importExample",
    " import",
    "import",
    "typingsimportExample",
    "importExample",
    "importExample",
    "importExample",
    "Qwen: importExample",
    "importExample",
    "import",
    "importExample"
]
```

(d) GPT-4 API prompting results.

Figure 5: API prompting results.