

2) Multiple calls: [{"name": "<tool_name>", "arguments": {...}}, ...]

Never wrap the JSON in prose or extra text.

Allowed tools: {tool_guide}

Editing rules:

- Do not modify section headers (e.g., lines beginning with "## 1.", "## 2.", "## 3.").
- Treat each section body as free-form lines/paragraphs (no numbering is required).

Context:

<working_memory> {working_memory} </working_memory>

<dialogue> {dialogue} </dialogue>

<thinking> {thinking} </thinking>

<assistant_response> {response} </assistant_response>

Initial Working Memory

1. Goals and Plans

2. Facts and Knowledge

3. Active Notes

H MEMORY TOOLS

we detail below the specific function schemas provided to the Autonomous and Workflow agents. These schemas define the tools available for manipulating the private working memory, including operations for overwriting, appending, deleting, and patching text content.

overwrite_memory

Overwrites the working memory with the provided content.

Args:

new_memory: The full working memory string to set.

Returns:

The provided new_memory string unchanged.

append_in_memory

Appends one or more lines to the end of a given section.

Args:

section_title: The section to append to (e.g., "Goals and Plans", "Facts and Knowledge", "Active Notes").

lines: A list of strings to append as individual lines.

Returns:

The updated working memory string.

deletes_from_memory

Deletes lines from the given section using robust, plain-text matching.

Args:

section_title: The section to edit (e.g., "Goals and Plans", "Facts and Knowledge", "Active Notes").

lines: A list of target lines to remove.

Returns:

The updated working memory string.

patch_memory

Apply a context-based patch to the working memory string (no line numbers).

Each patch contains one or more hunks, *anchored to a memory section* using a header of the form: `@@ section: <Title>`.

Within a section, specify deleted lines with '-' and added lines with '+', optionally including 1-3 unchanged context lines before/after for disambiguation.

- If a section or target is ambiguous/missing, the tool FAILS with a diagnostic.
- The patch should be IDEMPOTENT: re-applying it should not corrupt memory.
- Returns the updated memory plus metadata (applied hunks, changed lines, etc.).

Required args:

- patch (string): The patch text with the required headers:

```
```
*** Begin Patch
*** Update Memory
@@ section: Goals and Plans
- Old line
+ New line
*** End Patch
```
```

- explanation (string): one-sentence high-level intent for the change.

Optional safety args:

- expected_hunks (int): how many hunks you intend to apply.
- expected_changes (int): total +/- line operations expected.
- options (dict):
 - * strict_context (bool, default False): require clear context or exact old block.
 - * normalize_whitespace (bool, default True): collapse repeated spaces when matching.
 - * case_sensitive (bool, default True): literal, case sensitive matching when True.

Integration arg (injected by agent):

- current_memory (string): the current working-memory string to patch.

Returns:

```

{
  "new_memory": <updated string>,
  "meta": {
    "applied_hunks": <int>,
    "changed_lines": <int>,
    "sections_touched": [<str>...],
    "warnings": [<str>...]
  }
}

```

Few-shot examples

Example A: simple replacement within a section

```

*** Begin Patch
*** Update Memory
@@ section: Goals and Plans
- Planned steps or strategies for achieving them.
+ Planned steps: finish MVP, write docs, ship v1 by Sept 15.
*** End Patch

```

Example B: multi-line update with light context

```

*** Begin Patch
*** Update Memory
@@ section: Active Knowledge
[Investigation notes]
- Hypothesis: caching is the bottleneck
- Evidence: slow Redis reads
+ Hypothesis (confirmed): caching is the bottleneck
+ Evidence: slow Redis reads; profiler shows 45% time in cache layer
*** End Patch

```

Example C: pure insertion (anchor with a nearby context line)

```

*** Begin Patch
*** Update Memory
@@ section: Goals and Plans
[Milestones]
+ - Milestone: pass integration tests in CI
*** End Patch

```

replace_in_memory

Replace an exact text span in the working memory. Prefer scoping by `section\_title` and include light `pre\_context` and/or `post\_context` to uniquely anchor the target. By default the tool replaces exactly ONE occurrence (set `expected\_replacements` when intentionally replacing multiple). Fails if the target is ambiguous or not found.
Returns the updated memory and metadata.

Arguments:

- old_string (str, required): exact literal text to replace.
- new_string (str, required): exact literal replacement.
- explanation (str, required): one-sentence intent for telemetry.
- section_title (str, optional): limit search to a single section; matches titles

```

    like '## n. <Title>' ignoring the numeric prefix (case-insensitive on the title
    text).
- expected_replacements (int, optional; default=1): number of replacements
  intended.
- pre_context (str, optional): unchanged text that must appear immediately before
  each target.
- post_context (str, optional): unchanged text that must appear immediately after
  each target.
- options (dict, optional): same as patch_memory:
    * strict_context (bool, default True): require unambiguous anchors; otherwise
      fail.
    * normalize_whitespace (bool, default False): collapse repeated spaces when
      matching (matching only).
    * case_sensitive (bool, default True): literal case-sensitive matching.

- current_memory (str, injected by agent): the working-memory string to edit.

```

Returns:

```

{
  "new_memory": <updated string>,
  "meta": {
    "applied_hunks": 1,
    "changed_lines": <int>,
    "sections_touched": [<str>...],
    "warnings": [<str>...]
  }
}

```

Examples:

```

# Replace a single bullet inside "Goals and Plans"
{
  "section_title": "Goals and Plans",
  "old_string": "- Current overarching goal.",
  "new_string": "- Current overarching goal: ship v1 by Sept 15.",
  "expected_replacements": 1,
  "explanation": "Clarify primary goal"
}

# Multi-occurrence replacement in a section, with context
{
  "section_title": "Active Knowledge (Reasoning Outputs & Ephemeral Notes)",
  "pre_context": "[Investigation notes]",
  "old_string": "Hypothesis: caching is the bottleneck",
  "new_string": "Hypothesis (confirmed): caching is the bottleneck",
  "expected_replacements": 2,
  "explanation": "Mark hypothesis as confirmed"
}

```