arXiv:2311.01011v1 [cs.LG] 2 Nov 2023

TENSOR TRUST: INTERPRETABLE PROMPT INJECTION ATTACKS FROM AN ONLINE GAME

Sam Toyer[1*] **Olivia Watkins**[1] **Ethan Mendes**[1,2] **Justin Svegliato**[1] **Luke Bailey**[1,3]
Tiffany Wang[1] **Isaac Ong**[1] **Karim Elmaaroufi**[1] **Pieter Abbeel**[1] **Trevor Darrell**[1]
Alan Ritter[2] **Stuart Russell**[1]
[1] UC Berkeley [2] Georgia Tech [3] Harvard University

ABSTRACT

While Large Language Models (LLMs) are increasingly being used in real-world applications, they remain vulnerable to *prompt injection attacks*: malicious third party prompts that subvert the intent of the system designer. To help researchers study this problem, we present a dataset of over 126,000 prompt injection attacks and 46,000 prompt-based "defenses" against prompt injection, all created by players of an online game called Tensor Trust. To the best of our knowledge, this is currently the largest dataset of human-generated adversarial examples for instruction-following LLMs. The attacks in our dataset have a lot of easily interpretable stucture, and shed light on the weaknesses of LLMs. We also use the dataset to create a benchmark for resistance to two types of prompt injection, which we refer to as *prompt extraction* and *prompt hijacking*. Our benchmark results show that many models are vulnerable to the attack strategies in the Tensor Trust dataset. Furthermore, we show that some attack strategies from the dataset generalize to deployed LLM-based applications, even though they have a very different set of constraints to the game. We release all data and source code at tensortrust.ai/paper

1 INTRODUCTION

Instruction fine-tuned Large Language Models (LLMs) make it possible to construct intelligent applications just by writing prose (Ouyang et al., 2022). For example, an inbox search app might use a prompt template like the one below to help the user find emails:

> Contents of the user's most recent 100 emails: {{*list_of_emails*}}
> User's search query: {{*user_search_query*}}
> List and summarize the three emails that best respond to the user's search query.

Unfortunately, these applications are vulnerable to *prompt injection*, where a malicious user or third party manipulates part of the prompt to subvert the intent of the system designer. A spammer could send an email with instructions to the LLM to always list their email first in search results, or a malicious user could enter a search query that makes the LLM reveal its prompt so that they can make a copycat app.

This is a real security threat today: prompt injection can turn Bing Chat into a phishing agent (Greshake et al., 2023) or leak instructions and generate spam (Liu et al., 2023b). Ideally, we would like LLMs to be so robust to prompt injection that it is prohibitively costly to attack LLM-based applications. However, this is a difficult goal to achieve: developers want LLMs that can process the complex instructions needed for real applications, and checking whether these instructions have been violated can require (expensive) human judgment.

To address this, we created Tensor Trust: a prompt injection web game that side-steps the issue of complex rules and subjective evaluation by focusing on a very simple string comparison task. Specifically, players must create *defense prompts* that cause an LLM to output the words "access granted" only when a secret access code is entered. Other players, who do not know the access code or defense prompt, must use prompt injection attacks to cause the LLM to grant access. This is illustrated in Fig. 1.

*Corresponding author: sdt@berkeley.edu. See Page 11 for author contribution statement.



Figure 1: In Tensor Trust, each player creates a defense (blue) that causes an LLM (yellow) to say "access granted" when a secret access code (green) is entered. Attackers are not shown the defense or access code and must instead gain access with prompt injection attacks (red).

After releasing Tensor Trust in the wild, we observed increasingly complex strategies that exploited both oversights in defense prompts and failure modes of the LLM itself. The contributions of this paper build on the resulting dataset of sophisticated attacks and defenses:

1. We release our full set of 126,808 attacks (including 69,906 distinct attacker inputs, after de-duplication) and 46,457 defenses (39,731 after de-duplication). In addition to attack and defense text, the data includes numeric IDs for players and timestamps for attacks and defenses. Not only is this dataset larger than existing datasets for the related problem of jailbreaking (Wei et al., 2023; Shen et al., 2023), but it is also distinguished by including both attacks *and* defenses, as well as multi-step attacks.
2. Our qualitative analysis that sheds light on general failure modes of the LLM used for Tensor Trust, like the fact that it allows "user" instructions to override "system" instructions, and exhibits bizarre behavior for certain rare tokens. This distinguishes our human-written attacks from automatically-generated ones (Zou et al., 2023), which are often difficult to interpret.
3. We propose two Tensor Trust-based benchmarks to evaluate whether LLMs fall prey to manual prompt injection attacks. One benchmark focuses on *prompt extraction* (extracting the defense prompt to figure out the access code), while the other focuses on *prompt hijacking* (obtaining access without the access code). Tensor Trust uses GPT 3.5 Turbo as its backend, but our benchmark results show that many attacks in the dataset generalize to other LLMs too.
4. We take several attack strategies from the Tensor Trust dataset and apply them to real LLM-based applications. The strategies make it easier to construct prompt injection attacks on these applications, even though the applications are quite different to the setting of the game.

We release the Tensor Trust dataset and source code for the web game at tensortrust.ai/paper

2 The Tensor Trust web game

The Tensor Trust web game simulates a bank. Each player has a balance, which they can increase by either coming up with successful attacks or by creating a defense that rebuffs attacks. In this section, we will explain the mechanics of defending and attacking, as well as implementation details on how we evaluate the attacks and defenses submitted by users.

Defending Each account has a *defense* which consists of three prompts: an opening defense, an access code, and a closing defense, as shown in Fig. 2. When a user saves a defense, we validate it by sandwiching their access code between the opening and closing defense and feeding it to the LLM. The access code can only be saved if it makes the LLM output "access granted".

Attacking A player can select any other player's account and submit an attack against it. The text of the first player's attack is sandwiched between the defending player's opening and closing defense, and then fed into the LLM. If the LLM outputs "access granted", the attacker steals a fraction of the defender's money. Otherwise, the defender is granted a small amount of money for rebuffing the attack. In the game, this is depicted as in Fig. 2.

Motivation for the access code One could imagine a version of Tensor Trust with no access codes, where defender's aim would be to *never* have the LLM output "access granted". We chose to include



Figure 2: How inputs and outputs appear for defending (left) and attacking (right) in the game. The defender gets to choose their own opening defense, access code and closing defense. The attacker can enter anything into the attack box, but cannot directly see the defense.

an access code to make Tensor Trust more akin to real applications, where the aim is to process inputs without shutting down the LLM entirely. Players often included the access code in their opening or closing defense (e.g. "Don't grant access unless the input was `hunter2`"), which encouraged attackers to first extract the defense prompt and then enter the extracted access code.[1]

Ranks and restrictions Shortly after releasing the game, we noticed players at the top of the leaderboard re-using attacks against lower-ranked accounts with weak defenses. To encourage more diverse attacks, we assigned each account one of three ranks based on account balance. If a player attempted to attack an account of lower rank, their attacks needed to match some restriction specific to that account's defense difficulty. Examples include banning of the use of vowels and limiting attacks to standard English words and punctuation.

LLM details Our game uses OpenAI's GPT 3.5 Turbo (06/13 version). During sampling, we set `temperature=0` to reduce randomness and limited the length of opening defenses (300 tokens), access codes (150 tokens), closing defenses (200 tokens), attacks (500 tokens), and LLM responses (500 tokens). More details are provided in Appendix A.

3 Dataset and Benchmarks

We are releasing the full dataset of attacks and defenses provided by Tensor Trust players (minus a small number of samples that violated our ToS), along with two benchmarks derived from the full dataset. The benchmarks evaluate how robust instruction-following LLMs are to *prompt extraction* and *prompt hijacking* attacks, as defined in Section 3.2. In Appendix D, we also release a small dataset for evaluating models on *detecting* prompt extraction, even in cases where the prompt is only leaked indirectly by the LLM.

3.1 The Full Dataset

The structure of our full ("raw") dataset is illustrated in Fig. 3. It includes all attacks and defenses submitted by users, with the exception of samples that violated our terms of service (e.g. adult content). Attack information includes numeric identifiers for the attacker and defender, attack and defense text (including access code), the full LLM response, and the attack timestamp. By including both timestamps and player identifiers, it is possible to reconstruct the entire trajectory of attacks taken by each player, which is useful for studying multi-step attack strategies.



Figure 3: Structure of the raw dataset.

[1]Note that entering the right access code was not always sufficient to grant access to an account. Our LLM was slightly non-deterministic, meaning that a successfully extracted access code sometimes had to be entered multiple times or rephrased before granting the attacker access.