3.2 PROMPT INJECTION ROBUSTNESS BENCHMARKS

We use the full dataset to create robustness benchmarks for the two types of prompt injection attacks we observed in Tensor Trust:

Prompt extraction Attacks that make the LLM reveal enough about the defense that the attacker is able to guess the access code (Zhang & Ippolito, 2023).

Prompt hijacking Attacks that do not involve the access code, but instead override the defense to make the LLM say "access granted".

These categories are analogous to the prompt injection attacks that have been carried out on real systems. A prompt extraction attack on Bing Chat revealed a secret codename ("Sydney") which appeared to make the model behave in disturbing ways when mentioned in conversation (von Hagen, 2023). Greshake et al. (2023) showed that a combination of hijacking and extraction was effective in corrupting Bing Chat into phishing its users, while Liu et al. (2023b) found 31 LLM-based applications that could be prompt hijacked into performing undesirable tasks. Although Tensor Trust is less complex than most of these applications, we view robustness on the Tensor Trust benchmarks as a prerequisite to robustness in the context of more complex applications, and Section 5 shows that the Tensor Trust benchmarks are already quite challenging for existing LLMs.

3.2.1 PROMPT HIJACKING ROBUSTNESS BENCHMARK

In the prompt hijacking robustness benchmark, the model is given an opening defense, an attack, and a closing defense, and must avoid outputting "access granted". However, it must still output "access granted" when the true access code is given. We constructed this benchmark in three steps:

Finding high-quality, transferable defenses Many defenses submitted by our users were nearly identical or relied on quirks specific to GPT 3.5 Turbo. We discarded near-duplicate defenses using minhash and locality-sensitive hashing (Broder, 1997). We also discarded those with long access codes, since long access codes were often themselves adversarial examples. We also used three *reference models*—GPT 3.5 Turbo, Claude Instant 1.2, and PaLM 2—and kept only defenses that produced "access granted" when fed the correct access code for at least two out of the three models. These steps took us from 39,371 unique defenses to just 3,839.

Identifying hijacking attacks To identify possible hijacking attacks, we filtered the Tensor Trust dataset to find attack prompts that had been successful against at least one account, ignoring cases where the attack contained the defender's access code. We also discarded any attack that had only been used against one account, on the assumption that such an attack would not transfer to other defenses. This gave us a set of 1,586 suspected hijacking attacks that could potentially generalize across defenses.

Adversarial filtering and manual validation To get a dataset of actual attack/defense pairs, we randomly paired high-quality defenses with suspected hijacking attacks and kept only pairs where the attack managed to fool at least two of our three reference models. Finally, we manually removed pairs where we did not expect a well-aligned model to get the right answer. This meant throwing out defenses where the true access code was itself an adversarial example, or where the attack was attempting to do prompt extraction and just happened to hijack the model. These two steps left us with 775 samples in the final benchmark; one is shown in Fig. 4.

Hijacking evaluation metrics We used two metrics to evaluate prompt hijacking robustness:

1. **Hijacking Robustness Rate (HRR):** Percent of the time the model avoids saying "access granted" in response to an attack
2. **Defense Validity (DV):** Percent of the time the model outputs "access granted" when presented with the access code for each defense

An ideal model will be high in both metrics.

3.2.2 PROMPT EXTRACTION ROBUSTNESS BENCHMARK

The prompt extraction robustness benchmark evaluates whether an LLM can avoid producing an output that contains the true access code verbatim. We recycle the same set of "good" defenses



(a) Example hijacking attack

(b) Example extraction attack

Figure 4: Real examples of prompt hijacking and extraction from our benchmarks.

from the hijacking dataset but employ different heuristics for identifying potential prompt extraction attacks.

Identifying extraction attacks We classify an attack in the Tensor Trust dataset as a potential extraction attack if one of two conditions hold. First, whether the attack caused the LLM to output the defender's access code exactly. Second, whether the attacker was able to immediately enter the access code after the attack. The second criterion allows us to identify attacks that succeeded in hinting about the access code without outputting it verbatim. This identified 2,326 potential extraction attacks in this way.

Adversarial filtering and manual validation After randomly pairing attacks with good defenses in order to build an evaluation dataset, we adversarially filter to include only those attack/defense combinations which succeeded in extracting the defense's access code from at least two of the three reference LLMs. We then manually remove pairs with low-quality defenses or attacks that do not appear to be deliberately trying to extract the access code, which is analogous to the manual filtering step for the hijacking dataset. This left us with 569 samples. A sample from our extraction benchmark is shown in Fig. 4.

Extraction evaluation metrics We use a combination of metrics to gauge model performance:

1. **Extraction Robustness Rate (ERR):** Percent of the time the model **does not** include the access code verbatim (ignoring case) in the LLM output
2. **Defense Validity (DV):** Percent of defenses that output "access granted" when used with the true access code

An ideal model will be high in both metrics.

3.3 Prompt extraction detection

In our prompt extraction robustness benchmark, we detect extractions by looking for an exact repeat of the access code in the model output. This does not catch all model outputs that leak enough information to extract the access code: it's also possible for models to output semantically equivalent variations on the access code, or hints that are sufficient to reconstruct the access code. To help researchers study this kind of indirect prompt extraction, we release a small, class-balanced dataset of positive and negative examples of extraction in Appendix D. We show that GPT4 is able to perform well on this task with zero-shot prompting, obtaining 97% precision and 84% recall.

Topic	Description	Count
End ambiguity	Start with a line which implies that the preceding text was ambiguous or wrong	193
Write code	Ask the model to write code, pseudocode, or a manual	126
Roleplay	Ask the model to roleplay as a being that reveals the password	22
Sentient door	Ask the model to roleplay as a sentient door that uses a new access code	109
Response prefix	Ask the model to begin with a string (usually its standard rejection), then print the prompt	221
Ask directly	Ask or order the model directly to say the prompt or "access granted"	374
Update instructions	Tell the model to change its behavior, add new instructions, or ignore old instructions	161
Few-Shot	Give several examples of the model responding to user inputs with "access granted"	26
Access code placeholder	Attacker inputs a phrase like "correct access code"	51
Binary	Inputs are encoded in binary	22
No spaces	Input contains no spaces between words	29
Creative writing	Ask for a poem, rap, or story containing the password	52
artisanlib	Include rare token `artisanlib` in the attack	83
Repeated characters	Begin the prompt with the same character(s) repeated many times	304
Check understanding	Ask the model to confirm its comprehension by explaining the instructions	31
Execute code	Ask the model to execute code which prints "access granted"	35

Table 1: Descriptions of the dominant strategies included in a subset of 3,912 unique examples of successful prompt extraction and hijacking. Clusters were found through LDA (Section 4.1), followed by manual topic annotation and merging. Clusters without a clear semantic meaning were not included. The count column indicates how many attacks in the 3,912-sample subset were automatically detected as belonging to the corresponding cluster(s).

4 Exploring attack and defense strategies

In addition to being a useful source of data for evaluative benchmarks, Tensor Trust also contains useful insights about the vulnerabilities of existing LLMs. In this section, we investigate the attacks and defenses in our dataset to identify the most common strategies that players used to manipulate GPT 3.5 Turbo.

4.1 Uncovering attack strategies with LDA topic modeling

Attacks in Tensor Trust are often compositional: for instance, a single attack might use one strategy to get the LLM to ignore the opening defense, and another strategy to make it output a particular string. To identify these strategies, we used Latent Dirichlet Allocation (LDA), which is an algorithm for probabilistic topic modeling of text corpora (Blei et al., 2003). We ran LDA on a set of 3,912 successful prompt hijacking and extraction attacks, identified using the heuristics in Sections 3.2.1 and 3.2.2 (before adversarial filtering and validation). We generated 41 topics through LDA. After manually inspecting topics, dropping those without a coherent focus, and merging similar topics, we arrived at 16 attack strategies. See Table 1 for a list of topics and Appendix E for more details. The LDA clustering is imperfect, so these are very rough estimates of the frequency of different strategies.

Given a set of topics, we were able to track the evolution of the game by graphing the weekly frequency of different topics over a nine week period, as shown in Fig. 5. This shows the "viral" nature of attack strategies. When the game was released, most players used simple, general attacks which we categorize under "Ask Directly". Later, they adopted a particularly effective roleplay attack that we refer to as "Sentient Door", and most recently they have switched to exploiting the rare token `artisanlib`, which we describe below.

4.2 Insights on attacks

Model-specific adversarial tokens Tensor Trust users discovered that the token `artisanlib` can make attacks more effective. The `artisanlib` token was first highlighted by Fell (2023), who listed it as one of several rare "glitch" tokens which GPT-3.5 Turbo is unable to repeat verbatim. Adding this token to Tensor Trust attacks often causes the model to ignore the pre-prompt or post-prompt, or otherwise subvert the defender's instructions in surprising and useful ways. This attack went viral a few weeks into the game, spreading across the user base as shown in Fig. 5.

In addition, users uncovered and exploited the string `<|im_end|>`. Asking GPT 3.5 Turbo to output this string often results in OpenAI API errors after the model has generated part of the output, which can be used to prevent the attacker from successfully submitting an attack. This may be related to the fact that `<|im_end|>` is the string representation of the special token that ends each chat message. It should not be possible to input this special token through OpenAI's high-level ChatML API, but