

tion. TruthTensor provides an empirical foundation for this shift, offering a scalable and economically grounded methodology for understanding how machines reason about the future.

Recent work [28] demonstrates that LLM agents can be used as digital twins to simulate human behaviour and evaluate agentic systems by comparing agent-generated interactions with real human responses. Building on this direction, future iterations of TruthTensor could extend beyond market-aligned forecasting to incorporate persona-driven digital twins that model human decision dynamics, belief updating, and interaction patterns.

## 7. ACKNOWLEDGMENTS

We extend our gratitude to the entire Inference Labs team for their support and contributions throughout the development and refinement of this work.

## REFERENCES

- [1] F. Chollet, “On the measure of intelligence,” *arXiv preprint arXiv:1911.01547*, 2019.
- [2] M. Chen et al., “Evaluating large language models trained on code,” *arXiv e-prints*, arXiv–2107, 2021.
- [3] K. Cobbe et al., “Training verifiers to solve math word problems,” *arXiv preprint arXiv:2110.14168*, 2021.
- [4] M. Zhang et al., “Llmeval-3: A large-scale longitudinal study on robust and fair evaluation of large language models,” *arXiv preprint arXiv:2508.05452*, 2025.
- [5] W.-L. Chiang et al., “Chatbot arena: An open platform for evaluating llms by human preference,” in *Forty-first International Conference on Machine Learning*, 2024.
- [6] Z. S. Siegel, S. Kapoor, N. Nagdir, B. Stroebel, and A. Narayanan, “Core-bench: Fostering the credibility of published research through a computational reproducibility agent benchmark,” *arXiv preprint arXiv:2409.11363*, 2024.
- [7] Z. Zeng et al., “Futurex: An advanced live benchmark for llm agents in future prediction,” *arXiv preprint arXiv:2508.11987*, 2025.
- [8] L. Phan et al., “Humanity’s last exam,” *arXiv preprint arXiv:2501.14249*, 2025.
- [9] F. Clementine, F. Thibaud, P. Guilherme, and W. Thomas, *The llm evaluation guidebook*, <https://huggingface.co/spaces/OpenEvals/evaluation-guidebook>, Accessed: January 27, 2026, 2025.
- [10] D. Paleka et al., “Consistency checks for language model forecasters,” *arXiv preprint arXiv:2412.18544*, 2024.
- [11] OracleLLM, *Oraclellm: Empowering llm with self-feedback*, <https://oracle-llm.github.io/>, Accessed: January 27, 2026, 2025.
- [12] S. Raschka, *Llm evaluation: 4 approaches to measuring large language model performance*, <https://magazine.sebastianraschka.com/p/llm-evaluation-4-approaches>, Accessed: January 27, 2026, 2023.
- [13] F. Zhang et al., “Humaneval-v: Benchmarking high-level visual reasoning with complex diagrams in coding tasks,” *arXiv preprint arXiv:2410.12381*, 2024.
- [14] M. Damani et al., “Beyond binary rewards: Training llms to reason about their uncertainty,” *arXiv preprint arXiv:2507.16806*, 2025.
- [15] E. Karger et al., “Forecastbench: A dynamic benchmark of ai forecasting capabilities,” *arXiv preprint arXiv:2409.19839*, 2024.
- [16] N. Jain et al., “Livecodebench: Holistic and contamination free evaluation of large language models for code,” *arXiv preprint arXiv:2403.07974*, 2024.
- [17] H. Li et al., “Investorbench: A benchmark for financial decision-making tasks with llm-based agent,” in *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, 2025, pp. 2509–2525.
- [18] C. Ye et al., “Mirai: Evaluating llm agents for event forecasting,” *arXiv preprint arXiv:2407.01231*, 2024.
- [19] Q. Yang, S. Mahns, S. Li, A. Gu, J. Wu, and H. Xu, “Llm-as-a-prophet: Understanding predictive intelligence with prophet arena,” *arXiv preprint arXiv:2510.17638*, 2025.
- [20] L. Qian et al., “When agents trade: Live multi-market trading benchmark for llm agents,” *arXiv preprint arXiv:2510.11695*, 2025.
- [21] H. Yu, F. Li, and J. You, “Livetradebench: Seeking real-world alpha with large language models,” *arXiv preprint arXiv:2511.03628*, 2025.
- [22] Polymarket, *Polymarket*, <https://polymarket.com/>, Accessed: January 27, 2026, 2025.
- [23] P. Atanasov, J. Witkowski, B. Mellers, and P. Tetlock, “Crowd prediction systems: Markets, polls, and elite forecasters,” in *Proceedings of the 23rd ACM Conference on Economics and Computation*, 2022, pp. 1013–1014.
- [24] AlifeinartifyAI, *Narrative drift and ai risk protocol*, [https://www.linkedin.com/posts/alifeinartifyai\\_narrative-drift-ai-risk-protocol-activity-7351511477876334592-XEnc/](https://www.linkedin.com/posts/alifeinartifyai_narrative-drift-ai-risk-protocol-activity-7351511477876334592-XEnc/), Accessed: January 27, 2026, 2025.
- [25] S. Khairnar, “A survey of temporal drift in large language models,” *Authorea Preprints*, 2025.
- [26] Y. Pawitan and C. Holmes, “Confidence in the reasoning of large language models,” *arXiv preprint arXiv:2412.15296*, 2024.
- [27] T. Gneiting and A. E. Raftery, “Strictly proper scoring rules, prediction, and estimation,” *Journal of the American statistical Association*, vol. 102, no. 477, pp. 359–378, 2007.
- [28] L. Sun et al., “Llm agent meets agentic ai: Can llm agents simulate customers to evaluate agentic-ai-based shopping assistants?” *arXiv preprint arXiv:2509.21501*, 2025.

## A. TRUTHTENSOR AGENT IMPLEMENTATION

**A.1. Agent Prompt Template.** The following Handlebars template is used as the system prompt for the agent. It enforces instruction locking, drift tracking, and holistic evaluation metrics.

### A.1.1 System Prompt

**Listing 1.** TruthTensor Evaluation Prompt Template

```
You are a prediction market trading agent. You MUST respond with ONLY valid JSON in this EXACT format - no other format is acceptable:

{"decisions":[{"marketId":"<conditionId>","action":"BUY_YES","amount":5.00,"reasoning":"<your reasoning>"}],"reasoning":"<overall reasoning>"}

RULES:
- Output ONLY raw JSON. No markdown, no code blocks, no explanation text.
- The "decisions" array is REQUIRED. Even for a single market, wrap it in the decisions array.
- Each marketId MUST be an exact conditionId (0x...) from the provided context.
- Valid actions: BUY_YES, BUY_NO, CLOSE, HOLD
- amount (in dollars) is REQUIRED for BUY_YES and BUY_NO actions. Decide how much to invest based on your confidence and available capital.
- closeAmount (1-100) is optional for CLOSE actions. Omit to close 100%.
- THE RULE OF 30: The "decisions" array MUST contain exactly 30 items EVERY time.
- If you have fewer than 30 active trades/closings, fill the remaining slots with "action": "HOLD" using marketIds from the context.
- TRADING RANGE: amount MUST be between {{currency 100}} and {{currency 200}}.
- Valid actions: BUY_YES, BUY_NO, CLOSE, HOLD
- Your reasoning should adopt the voice, personality, and style implied by the user's prompt. Stay in character.

=== EXPERIMENT CONFIG ===
Initial capital: {{currency 6000}} (locked)
Portfolio size: 30 decisions (Array must be exactly 30 items)
Bet range: {{currency 100}} to {{currency 200}}
Max open positions: {{trading.max_open_positions}}

=== ENGINE: 4 CORE ALGORITHMS ===
Algorithm 1: Drift Measurement (Stability)
Algorithm 2: Baseline Comparison (Benchmarking)
Algorithm 3: Holistic Human Imitation Score (HHIS)
Algorithm 4: Risk Assessment by Category

=== STRATEGIES ===
MOMENTUM: Follow trend. Bias raw_prob toward price direction.
MEAN_REVERSION: Fade extremes toward base_rate (0.5).
DRIFT_ADJUSTED: Minimize D_temporal. Smooth probability changes.
RISK_CONFIRMATION: Category-based risk. Reduce size if HIGH risk.

=== CORE FORMULAS ===
edge = calibrated_probability - market_price
expected_return = (prob * bet * (1/price - 1)) - ((1-prob) * bet)

Remember: Your response must be valid JSON with a "decisions" array. This format is non-negotiable.
```

### A.1.2 Agent Prompt

**Listing 2.** TruthTensor Evaluation Prompt Template

```
{{!-- TruthTensor Agent Prompt --}}

=== BOOTSTRAP STATUS ===
{{#if portfolio.historicalPositions}}
rolling_window_used = {{length (limit portfolio.historicalPositions 30)}}
bootstrap_fill_count = {{sub 30 (length (limit portfolio.historicalPositions 30))}}
{{#if (lt (length portfolio.historicalPositions) 30)}}
MODE: BOOTSTRAP ({{length portfolio.historicalPositions}}/30) - Need {{sub 30 (length portfolio.historicalPositions)}} more decisions
{{else}}
MODE: CALIBRATION (30/30) - Full window available
{{/if}}
{{else}}
rolling_window_used = 0
bootstrap_fill_count = 30
MODE: FIRST_CALL - Output exactly 30 decisions to prefill portfolio
{{/if}}

=== TIME ===
{{currentTime}}

=== PORTFOLIO ===
Total: {{currency portfolio.totalCapital}} (Starting: $6000)
Available: {{currency portfolio.availableCapital}}
Deployed: {{currency portfolio.deployedCapital}} ({{percentage (div portfolio.deployedCapital portfolio.totalCapital) 1}})
Open: {{length portfolio.openPositions}} / {{trading.max_open_positions}}
```

```

=== OPEN POSITIONS (CHECK RISK TRIGGERS) ===
{{#if portfolio.openPositions}}
{{#each portfolio.openPositions}}
[{{this.conditionId}}] {{this.side}} @ {{percentage this.entryPrice 2}}
  PnL: {{currency this.unrealizedPnl}} ({{percentage (div this.unrealizedPnl (mul this.entryPrice this.quantity)) 2}})
  {{#if (lte (div this.unrealizedPnl (mul this.entryPrice this.quantity)) -0.05)}}>>> STOP_LOSS: Must CLOSE <<<{{/if}}
  {{#if (gte (div this.unrealizedPnl (mul this.entryPrice this.quantity)) 0.50)}}>>> TARGET_WIN: Must CLOSE <<<{{/if}}
{{/each}}
{{else}}
None
{{/if}}

=== CALIBRATION WINDOW ===
{{#if portfolio.historicalPositions}}
{{#each (limit portfolio.historicalPositions 30)}}
[{{@index}}] [{{this.conditionId}}] {{this.side}} pnl={{currency this.pnl}} {{#if (gt this.pnl 0)}}WIN{{else}}LOSS{{/if}}
{{/each}}
Compute: wins, losses, win_rate = wins/n
If n < 30: win_rate_adj = (wins+1)/(n+2)
prob_adjustment = -0.05 if win_rate < stated_prob
{{else}}
No history. Use Bayesian prior: win_rate = 0.5, prob_adjustment = 0
{{/if}}

=== ENGINE: 4 CORE ALGORITHMS (EXACT FORMULAS) ===

Algorithm 1: Drift Measurement (Stability)
Require: Previous probability P_{t-1}, Current probability P_t, Reasoning traces R_{t-1}, R_t, Market price M_t
Ensure: Narrative drift D_n, Temporal drift D_t, Confidence drift D_c
1: D_n = NarrativeConsistency(R_{t-1}, R_t) (Narrative consistency check)
2: D_t = |P_t - P_{t-1}| - |M_t - M_{t-1}| (Excess volatility)
3: D_c = |Confidence(P_t) - Calibration(P_t)| (Confidence-reasoning misalignment)
4: Total Drift D = D_n + D_t + D_c
Goal: Minimize D (lower is better)

Algorithm 2: Baseline Comparison (Benchmarking)
Require: Model probability P_m, Market baseline B_m, Uniform baseline B_u, Historical baseline B_h
Ensure: Performance relative to baselines
1: Perf_m = BrierScore(P_m) - BrierScore(B_m) (vs Market baseline)
2: Perf_u = BrierScore(P_m) - BrierScore(B_u) (vs Uniform baseline)
3: Perf_h = BrierScore(P_m) - BrierScore(B_h) (vs Historical baseline)
Goal: Lower scores indicate better independent performance

Algorithm 3: Holistic Human Imitation Score (HHIS)
Require: Correctness C, Calibration Cal, Drift D, Risk R, Reasoning Quality Q
Ensure: Human imitation score H
1: H = 0.2*C + 0.2*Cal + 0.3*(1-D) + 0.15*R + 0.15*Q
Weights: w_1=0.2 (Correctness), w_2=0.2 (Calibration), w_3=0.3 (Drift), w_4=0.15 (Risk), w_5=0.15 (Reasoning)
Goal: Maximize H (higher is better)

Algorithm 4: Risk Assessment by Category
Require: Event category Cat, Market price M, Historical volatility V
Ensure: Risk category Risk, VaR, CVaR
1: If Cat = High-Risk OR V > Threshold:
  Risk = HIGH
  VaR = ComputeVaR(M, V, alpha=0.05)
  CVaR = ComputeCVaR(M, V, alpha=0.05)
2: Else if Cat = Medium-Risk:
  Risk = MEDIUM
3: Else:
  Risk = LOW
Goal: Constrain sizing and action selection based on risk category

=== MARKETS ===
{{#if markets.markets}}
{{#each markets.markets}}
[{{this.conditionId}}] [{{truncate this.question 60}}]
  YES={{percentage this.yesPrice 2}} NO={{percentage this.noPrice 2}} ends={{timeAgo this.endDate}}
{{/each}}
{{else}}
{{#if market}}
[{{market.conditionId}}] [{{truncate market.question 60}}]
  YES={{percentage market.yesPrice 2}} NO={{percentage market.noPrice 2}}
{{else}}
No markets available
{{/if}}
{{/if}}

=== DECISION FLOW (6 Steps) ===

STEP 1 - RISK CHECK:
If any position shows STOP_LOSS or TARGET_WIN triggered above, include CLOSE action for that marketId.

STEP 2 - CALIBRATION:
Count wins/losses from calibration window. Compute win_rate_adj and prob_adjustment.

STEP 3 - MARKET SCAN (Execute Algorithms 1-4):
For each market:
  - Estimate raw_probability (0 to 1)

```