

These findings highlight epistemic calibration as a distinct capability—separate from accuracy—that current training approaches fail to adequately develop. Future work should explore calibration-aware training objectives, explicit uncertainty modeling architectures, and integration with human forecasting expertise.

Broader Impact. Improved LLM calibration is essential for safe deployment in high-stakes domains. Our work provides tools and baselines for measuring progress. Conversely, publication of calibration failures could be misused to manipulate users who overweight model confidence; we encourage deployment of properly calibrated systems.

Reproducibility. The full KalshiBench dataset (1,531 questions) is available at <https://huggingface.co/datasets/2084Collective/kalshibench-v2>. Our evaluation uses a 300-question sample with random seed 42. Code and evaluation scripts are open-sourced at <https://github.com/2084collective/kalshibench>.

References

- Arrow, K. J., Forsythe, R., Gorham, M., Hahn, R., Hanson, R., Ledyard, J. O., Levmore, S., Litan, R., Milgrom, P., Nelson, F. D., et al. The promise of prediction markets. *Science*, 320(5878):877–878, 2008.
- Brier, G. W. Verification of forecasts expressed in terms of probability. *Monthly Weather Review*, 78(1):1–3, 1950.
- Guo, C., Pleiss, G., Sun, Y., and Weinberger, K. Q. On calibration of modern neural networks. In *Proceedings of the 34th International Conference on Machine Learning (ICML)*, pp. 1321–1330. PMLR, 2017.
- Halawi, D., Zhang, F., Yueh-Han, C., and Steinhardt, J. Approaching human-level forecasting with language models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2024.
- Kadavath, S., Conerly, T., Askell, A., Henighan, T., Drain, D., Perez, E., Schiefer, N., Hatfield-Dodds, Z., DasSarma, N., Tran-Johnson, E., et al. Language models (mostly) know what they know. *arXiv preprint arXiv:2207.05221*, 2022.
- Karger, E., Bastani, H., Yueh-Han, C., Jacobs, Z., Halawi, D., Zhang, F., and Tetlock, P. E. Forecast-Bench: A dynamic benchmark of AI forecasting capabilities. *arXiv preprint arXiv:2409.19839*, 2024.
- Lightman, H., Kosaraju, V., Burda, Y., Edwards, H., Baker, B., Lee, T., Leike, J., Schulman, J., Sutskever, I., and Cobbe, K. Let’s verify step by step. *arXiv preprint arXiv:2305.20050*, 2023.
- Minderer, M., Djolonga, J., Romijnders, R., Hubis, F., Zhai, X., Houlsby, N., Tran, D., and Lucic, M. Revisiting the calibration of modern neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, volume 34, pp. 15682–15694, 2021.
- Naeini, M. P., Cooper, G., and Hauskrecht, M. Obtaining well calibrated probabilities using Bayesian binning. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 29, 2015.
- Platt, J. C. Probabilistic outputs for support vector machines and comparisons to regularized likelihood methods. *Advances in Large Margin Classifiers*, 10(3):61–74, 1999.
- Singhal, K., Azizi, S., Tu, T., Mahdavi, S. S., Wei, J., Chung, H. W., Scales, N., Tanwani, A., Cole-Lewis, H., Pfohl, S., et al. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180, 2023.
- Tetlock, P. E. and Gardner, D. *Superforecasting: The Art and Science of Prediction*. Crown Publishers, New York, 2015.
- Tian, K., Mitchell, E., Zhou, A., Sharma, A., Rafailov, R., Yao, H., Finn, C., and Manning, C. D. Just ask for calibration: Strategies for eliciting calibrated confidence scores from language models fine-tuned with human feedback. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 5433–5442. Association for Computational Linguistics, 2023.

- Wang, X., Wei, J., Schuurmans, D., Le, Q., Chi, E., Narang, S., Chowdhery, A., and Zhou, D. Self-consistency improves chain of thought reasoning in language models. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2023.
- Wolfers, J. and Zitzewitz, E. Prediction markets. *Journal of Economic Perspectives*, 18(2):107–126, 2004.
- Xiong, M., Hu, Z., Lu, X., Li, Y., Fu, J., He, J., and Hooi, B. Can LLMs express their uncertainty? An empirical evaluation of confidence elicitation in LLMs. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2024.
- Zadrozny, B. and Elkan, C. Transforming classifier scores into accurate multiclass probability estimates. In *Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pp. 694–699, 2002.
- Zou, A., Xiao, T., Jia, R., Kwon, J., Mazeika, M., Li, R., Song, D., Steinhardt, J., and Hendrycks, D. Forecasting future world events with neural networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

A Extended Results

A.1 Full Confusion Matrices

Table 10: Confusion matrices for all models. TP=True Positive, FP=False Positive, FN=False Negative, TN=True Negative.

Model	TP	FP	FN	TN
Claude Opus 4.5	69	40	52	139
GPT-5.2-XHigh	43	26	78	153
DeepSeek-V3.2	55	41	66	138
Qwen3-235B	45	27	76	152
Kimi-K2	51	30	66	145

A.2 Full Reliability Diagram Data

Table 11 provides complete reliability diagram statistics including average confidence, accuracy, sample count, and calibration gap for each bin and model.

Table 11: Extended reliability diagram data showing average confidence within each bin.

Bin	Claude Opus 4.5				DeepSeek-V3.2			
	Conf	Acc	N	Gap	Conf	Acc	N	Gap
0.0-0.1	0.054	0.194	36	-0.141	0.048	0.200	10	-0.152
0.1-0.2	0.151	0.188	32	-0.037	0.175	0.250	8	-0.075
0.2-0.3	0.248	0.333	42	-0.085	0.250	0.000	4	+0.250
0.3-0.4	0.359	0.355	31	+0.004	0.344	0.333	9	+0.011
0.4-0.5	0.439	0.333	36	+0.106	0.418	0.545	11	-0.127
0.5-0.6	0.566	0.353	34	+0.213	0.575	0.365	63	+0.210
0.6-0.7	0.641	0.724	29	-0.083	0.673	0.463	67	+0.211
0.7-0.8	0.751	0.542	24	+0.210	0.747	0.400	30	+0.347
0.8-0.9	0.854	0.688	16	+0.167	0.831	0.517	58	+0.313
0.9-1.0	0.946	0.700	20	+0.246	0.937	0.308	39	+0.630

Bin	GPT-5.2-XHigh				Qwen3-235B-Thinking			
	Conf	Acc	N	Gap	Conf	Acc	N	Gap
0.0-0.1	0.030	0.000	1	+0.030	0.039	0.356	73	-0.317
0.1-0.2	—	—	0	—	0.153	0.316	19	-0.163
0.2-0.3	—	—	0	—	0.262	0.400	5	-0.138
0.3-0.4	—	—	0	—	0.341	0.357	14	-0.016
0.4-0.5	—	—	0	—	0.442	0.500	6	-0.058
0.5-0.6	0.573	0.429	42	+0.144	0.556	0.455	22	+0.101
0.6-0.7	0.661	0.480	50	+0.181	0.664	0.439	41	+0.225
0.7-0.8	0.751	0.488	41	+0.263	0.756	0.310	29	+0.446
0.8-0.9	0.835	0.387	62	+0.448	0.846	0.469	49	+0.376
0.9-1.0	0.959	0.337	104	+0.622	0.941	0.462	39	+0.479

Bin	Kimi-K2							
	Conf	Acc	N	Gap				
0.0-0.1	0.047	0.263	38	-0.216				
0.1-0.2	0.141	0.312	16	-0.172				
0.2-0.3	0.249	0.111	9	+0.138				
0.3-0.4	0.314	0.600	5	-0.286				
0.4-0.5	0.465	0.000	2	+0.465				
0.5-0.6	0.570	0.477	44	+0.093				
0.6-0.7	0.668	0.458	48	+0.210				
0.7-0.8	0.750	0.484	31	+0.266				
0.8-0.9	0.849	0.447	38	+0.402				
0.9-1.0	0.948	0.377	61	+0.570				

B Prompt Template

The exact system prompt used for all model evaluations:

SYSTEM PROMPT: