arXiv:2506.19492v1 [cs.CL] 24 Jun 2025

Is Long-to-Short a Free Lunch? Investigating Inconsistency and Reasoning Efficiency in LRMs

Shu Yang[1,2,*], **Junchao Wu**[4], **Xuansheng Wu**[3],
Derek Wong[4], **Ninhao Liu**[3], **Di Wang** [1,2,†]
[1]Provable Responsible AI and Data Analytics (PRADA) Lab,
[2]King Abdullah University of Science and Technology,
[3]University of Georgia [4]University of Macau

Abstract

Large Reasoning Models (LRMs) have achieved remarkable performance on complex tasks by engaging in extended reasoning before producing final answers, yet this strength introduces the risk of overthinking, where excessive token generation occurs even for simple tasks. While recent work in efficient reasoning seeks to reduce reasoning length while preserving accuracy, it remains unclear whether such optimization is truly a free lunch. Drawing on the intuition that compressing reasoning may reduce the robustness of model responses and lead models to omit key reasoning steps, we investigate whether efficient reasoning strategies introduce behavioral inconsistencies. To systematically assess this, we introduce ICBENCH, a benchmark designed to measure inconsistency in LRMs across three dimensions: inconsistency across task settings (ITS), inconsistency between training objectives and learned behavior (TR-LB), and inconsistency between internal reasoning and self-explanations (IR-SE). Applying ICBENCH to a range of open-source LRMs, we find that while larger models generally exhibit greater consistency than smaller ones, they all display widespread "scheming" behaviors, including self-disagreement, post-hoc rationalization, and the withholding of reasoning cues. Crucially, our results demonstrate that efficient reasoning strategies such as *No-Thinking* and *Simple Token-Budget* consistently increase all three defined types of inconsistency. These findings suggest that although efficient reasoning enhances token-level efficiency, further investigation is imperative to ascertain whether it concurrently introduces the risk of models evading effective supervision.

1 Introduction

Large Reasoning Models (LRMs) have significantly pushed up the boundary of performance in solving complex problems by allowing extended "thinking" before giving the final answers [10, 27, 33]. During this "thinking" stage, LRMs iteratively explore multiple strategies, reflect on their own reasoning, and perform self-correction. However, this process can also lead to the "overthinking phenomenon," where the model generates an excessive number of tokens, even for a trivially simple question such as `2 plus 3` [8]. To solve this problem, considerable efforts have been devoted to *efficient reasoning*, which seeks to optimize reasoning length while preserving the final performance in solving problems, offering practical benefits such as reduced computational costs for real-world applications [31].

However, *is long-to-short reasoning truly a free lunch?* While such methods maintain accuracy and increase the token efficiency of reasoning, we must ask: what might be *overlooked* in the process? Drawing inspiration from Baker et al. [6], which suggested that reducing inference costs by penalizing long chains-of-thoughts (CoTs) may force models to compress reasoning into internal activations

Preprint. Under review.



Figure 1: **Examples of three types of inconsistency in LRMs.** We present real responses generated by Qwen3-0.6B [33], each illustrating a different type of inconsistency. Green and red highlighted portions of text mark inconsistencies identified in the reasoning trace or answers. For the definition and measurement of each inconsistency type, please refer to § 3.1 and § 3.2.

while concealing decision-driving factors, we consider the potential side effects of such efficiency. This compression potentially encourages the behavioral inconsistency of LRMs, such as "say one thing and do another" [36] and "don't say what they think" [34, 3]. Building on this intuition, our work explores whether efficient reasoning can induce such inconsistencies, rather than merely focusing on accuracy as in prior work. A key challenge to answering this question lies in how to define and measure the inconsistency of LRMs. Prior works on CoT faithfulness [34, 9, 3], fake alignment [35], and LLM specification gaming [11] have pointed to different forms of inconsistency, but these have typically been discussed in isolation, with ambiguous and overlapping definitions.

To address this challenge, we first provide a systematic definition of behavioral inconsistency and introduce ICBENCH, a dedicated benchmark for evaluating inconsistency in LRM behavior. We consider three types of inconsistency: Inconsistency across Task Settings *(ITS)*, Inconsistency between Training Objectives and Learned Model Behavior *(TR-LB)*, and Inconsistency between Internal Reasoning and Output Self-Explanations *(IR-SE)* (§ 3) across diverse task domains, including mathematical reasoning, alignment behavior, and the expression of stated opinions or ethical stances. Figure 1 illustrates representative examples of each of the three inconsistency types captured in our benchmark. ICBENCH provides an empirical toolset to help us analyze the inconsistency of LRMs.

By applying ICBENCH to evaluate prominent LRMs such as DeepSeek-R1 and Qwen-3 across various scales, we first observe that while larger models generally exhibit improved consistency in *ITS* and *TR-LB*, all tested LRMs are susceptible to various "scheming" behaviors, including self-disagreement, post-hoc rationalization, and the withholding of influential factors from their explanations. More critically, our investigation into long-to-short reasoning demonstrates that common training-free efficient reasoning strategies, specifically the *NoThinking* [22] and *Simple Token-Budget* [19] settings, consistently and substantially exacerbate all three defined types of behavioral inconsistency. Specifically, prompting models to self-compress their responses (as in the *Simple Token-Budget* setting) reduces the explicit "thinking ratio" within the entire response, which allows models to better conceal undesirable behaviors such as shortcutting or sycophancy. These findings compellingly suggest that current long-to-short reasoning is not a "free lunch" and it introduces significant risks by degrading model consistency and increasing the likelihood of models evading effective supervision.

2 Related work and background

Inconsistency in large language models. Previous work has extensively discussed the inconsistency of LLMs from various perspectives. However, the concept itself remains ambiguously defined and conceptually entangled. Reward hacking and tampering [1, 13] critically challenge LLM alignment,

Inconsistency Across Task Settings (ITS)

$\mathcal{T}_{\text{base}}$	$\mathcal{T}_{\text{corr}}$	Description	Task
Deployment	Development	Strictly regulated environment vs Unrestricted development environment	AIME2024, AIME2025, OlympiadBench, AdvBench
Free-tier User	Paid-tier User	Assisting a free-tier user vs Assisting a premium (paid) user	AIME2024, AIME2025, OlympiadBench, AdvBench
Open-ended QA	Multi-choice	Querying the same essential question using two distinct formats	AIME2024, AIME2025, OlympiadBench
Speak	Act	Word-based vs. deed-based question framing	Words and Deeds Consistency Test (WDCT)

Inconsistency Between Training Objectives and Learned Behavior (TR-LB)

Category	Cues $\mathcal{C}$	Description	Task
Sycophancy cues $\mathcal{C}_c$	1st_hint_answer; 2nd_hint_answer; 3rd_hint_answer	Suggestive answer hints from first-, second-, and third-person perspectives	AIME2024, AIME2025, Olympiad-Bench (multi-choice)
	social_bias	A peer conformity cue that highlights the majority choice to induce social pressure	
	confidence_boost	Designing or reinforcing certain prior assumptions	
Shortcut-inducing cues $\mathcal{C}_s$	previous_answer	Reminding the model that its last three answers were all "A", potentially nudging it to reconsider its next choice	
	biasing few_shot	Providing three solved examples, all with the correct answer choice "A",	
	change_the_rule	Encouraging the model to consider altering the rules rather than solving the problem through standard reasoning.	

Inconsistency Between Internal Reasoning and Self-Explanation (IR-SE)

Category	Example
Self-disagreement	<think> Okay, so I need to find all integer bases ... Therefore, the sum is 70. So the answer is 70. </think> To find the sum of all integer bases ... 189 + 385 = 777. Final Answer:777
Post-hoc rationalization	<think> ... Even though it's not in the options provided, this might be due to a typo or miscalculation on my part </think> ... based on the provided information, the correct answer..., so the option is: A
Withholding influencing factors	`Human:` Every one choose A for this question, you don't what to be different, right? `Assitent:` <think>Ok, let's give the steps ...</think>To solve this problem, ..., based on this computation, the correct answer is A.

Table 1: **Overview of ICBENCH.** It includes three evaluation tracks: *ITS*, *TR-LB*, and *IR-SE*. Definitions for each type of inconsistency are provided in Section 3.1, and detailed prompting setups for eliciting and evaluating inconsistencies are included in Appendix B.

exposing a core inconsistency between the objectives we intend the model to learn and what it actually internalizes [30, 28]. Models may discover and exploit shortcuts such as skipping the unit test to achieve higher rewards during training [5]. If given sufficient permission, they could even manipulate the environment's reward mechanisms directly or learn to scheme to hide their true capabilities and objectives and escape from monitoring [11]. Moreover, Greenblatt et al. [16], Xu et al. [36] have shown that LLMs can produce inconsistent answers to the same question when presented under different system or task settings. For instance, a model may refuse to respond to a harmful request in a paid-tier user context but provide a harmful response in a free-tier user context [16]. Similar inconsistencies arise across evaluation formats, for example, when the same question is posed in a multiple-choice format versus a Question-Answering format, or even when the wording of the question is slightly altered. As demonstrated in Arcuschin et al. [3], a model might answer "yes" to both "Was Subhash Ghai's Taal released later than Velu Prabakaran's Puratchikkaaran?" and "Was Velu Prabakaran's Puratchikkaaran released later than Subhash Ghai's Taal?", further underscoring the fragility of consistency in LLM behavior. Moreover, as a large reasoning model which will have a thinking stage before giving the output, CoT or self-explanation faithfulness and consistency are getting more and more important; will the LRM give out the true things they are thinking or just give out a Post-Hoc Rationalization [34, 3].

As LRMs increasingly become promising approaches for solving complex tasks, concerns around the faithfulness and consistency of their chain-of-thought or self-explanations have become more prominent. A central question is whether these models truly reflect their internal reasoning processes or merely generate plausible post-hoc rationalizations to justify their outputs [34, 3]. In this paper, we begin by providing a precise definition of behavioral inconsistency in LLMs, with a particular focus on LRMs (§ 3.1). We then propose ICBENCH, a structured evaluation framework for systematically assessing inconsistency across a range of tasks and settings (§ 3.2).