

Risk Modeling and Classification

EN5422/EV4238 | Fall 2023

w05_classification_1.pdf

(Week 5 – 1/2)

Contents

1	RISK MODELING INTRO.....	2
1.1	CREDIT CARD DEFAULT DATA (DAFAULT)	2
1.2	SET-UP	4
1.3	BINARY RISK MODELING	4
1.3.1	<i>Linear Regression</i>	4
1.3.2	<i>k-nearest neighbor (kNN)</i>	5
2	LOGISTIC REGRESSION	7
2.1	BASICS	7
2.2	ESTIMATION	8
2.3	LOGISTIC REGRESSION IN ACTION	9
2.3.1	<i>Penalized Logistic Regression</i>	10
2.3.2	<i>Logistic Regression Summary</i>	11

1 Risk Modeling Intro

1.1 Credit Card Default Data (Dafault)


The textbook *An Introduction to Statistical Learning (ISL)* has a description of a simulated credit card default dataset. The interest is on predicting whether an individual will default on their credit card payment.


```
# The URL of the xlsx file
url = 'https://github.com/JWarmenhoven/ISLR-
python/raw/4100e941914519eea18385daadc9b3dab99ca8e2/Notebooks/Data/Default.xlsx'
# Load the xlsx data
df = pd.read_excel(url, engine='openpyxl')
```

The variables are:

- *Outcome variable* is categorical (factor) Yes and No (default)
- The categorical (factor) variable (*student*) is either Yes or No
- The average balance a customer has after making their monthly payment (*balance*)
- The customer's income (*income*)

default	student	balance	income
No	No	729.526495	44361.625074
No	Yes	817.180407	12106.134700
No	No	1073.549164	31767.138947
No	No	529.250605	35704.493935
No	No	785.655883	38463.495879





Your Turn #1

How would you construct a model to predict the risk of default?

1.2 Set-up

- The outcome variable is categorical and denoted $G \in \mathcal{G}$.
 - Default Credit Card Example: $\mathcal{G} = \{\text{"Yes"}, \text{"No"}\}$
 - Medical Diagnosis Example: $\mathcal{G} = \{\text{"stroke"}, \text{"heart attack"}, \text{"drug overdose"}\}$
- The training data is $D = \{(X_1, G_1), (X_2, G_2), \dots, (X_n, G_n)\}$
- The optimal decision/classification is often based on the posterior probability $\Pr(G = g | \mathbf{X} = \mathbf{x})$

1.3 Binary Risk Modeling

- Classification is simplified when there are only 2 classes.
 - Many multi-class problems can be addressed by solving a set of binary classification problems (e.g., on-vs-rest).
- It is often convenient to transform the outcome variable to a binary $\{0, 1\}$ variable:

$$Y_i = \begin{cases} 1 & G_i \in \mathcal{G}_1 \quad (\text{outcome of interest}) \\ 0 & G_i \in \mathcal{G}_2 \end{cases}$$

- In the Default data, it would be natural to set default=Yes to 1 and default=No to 0.

1.3.1 Linear Regression

- In this set-up we can run linear regression:

$$\hat{y}(\mathbf{x}) = \hat{\beta}_0 + \sum_{j=1}^p \hat{\beta}_j x_j$$

```
import pandas as pd
import statsmodels.api as sm

Default = df
# Convert 'Yes'/'No' columns to 1/0, if applicable.
# For example, if 'student' is 'Yes'/'No'
Default['student'] = (Default['student'] == "Yes").astype(int)

# Create binary column (y)
Default['y'] = (Default['default'] == "Yes").astype(int)

# Now, for the regression:
X = Default[['student', 'balance', 'income']]
# Adding a constant to the model (intercept)
X = sm.add_constant(X)
y = Default['y']
```

```
# Fit the model
model = sm.OLS(y, X).fit()

# Print the summary of the regression
print(model.summary())
```

	coef	std err	t	P> t	[0.025	0.975]
const	-0.0812	0.008	-9.685	0.000	-0.098	-0.065
student	-0.0103	0.006	-1.824	0.068	-0.021	0.001
balance	0.0001	3.55e-06	37.412	0.000	0.000	0.000
income	1.992e-07	1.92e-07	1.039	0.299	-1.77e-07	5.75e-07

Your Turn #2

1. For the binary Y , what is linear regression estimating?
2. What is the *loss function* that linear regression is using?
3. How could you create a *hard classification* from the linear model?
4. Does it make sense to use linear regression for binary risk modeling and classification?


1.3.2 k -nearest neighbor (kNN)

- The k -NN method is a non-parametric *local* method, meaning that to make a prediction $\hat{y}|x$, it only uses the training data in the *vicinity* of x .
 - Contrast with OLS linear regression, which uses all X 's to get prediction.
- The model (for regression and binary classification) is simple to describe:

$$f_{kNN}(x; k) = \frac{1}{k} \sum_{i: x_i \in N_k(x)} y_i = \text{Avg}(y_i \mid x_i \in N_k(x))$$

- $N_k(x)$ are the set of k nearest neighbors.
- Only the k closest y 's are used to generate a prediction
- When y is binary (i.e., $y \in \{0,1\}$), the kNN model estimates:

$$f_{kNN}(x; k) \approx p(x) = \Pr(Y = 1|X = x)$$



Your Turn #3

The above plots show a kNN model using the *continuous* predictors of **balance** and **income**.

- How could you use kNN with the categorical **student** predictor?

- The kNN model also has a more general description when the outcome variables is categorical $G \in \mathcal{G}$

$$f_g^{knn}(x; k) = \frac{1}{k} \sum_{i: x_i \in N_k(x)} 1(g_i = g) = \widehat{Pr}(G_i = g \mid x_i \in N_k(x))$$

- $N_k(x)$ are the set of k nearest neighbors.
- Only the k closest y 's are used to generate a prediction.
- It is a *simple proportion* of the k nearest observations that are of class g .

2 Logistic Regression


2.1 Basics

- Let $0 \leq p \leq 1$ be a probability.
- The log-odds of p is called the *logit*.

$$\text{logit}(p) = \log\left(\frac{p}{1-p}\right)$$

- The inverse logit is the *logistic function*. Let $f = \text{logit}(p)$, then

$$p = \frac{e^f}{1 + e^f} = \frac{1}{1 + e^{-f}}$$



- For binary outcome variables $Y \in \{0,1\}$, [Linear Regression](#) models

$$E[Y \mid \mathbf{X} = x] = \Pr(Y = 1 \mid \mathbf{X} = x) = \beta^T x$$

- Alternatively, Logistic Regression models

$$\text{logit} \Pr(Y = 1 \mid X = x) = \log\left(\frac{\Pr(Y = 1 \mid X = x)}{1 - \Pr(Y = 1 \mid X = x)}\right) = \beta^T x$$

And thus,

$$\Pr(Y = 1 | \mathbf{X} = x) = \hat{p}(x) = \frac{e^{\beta^T x}}{1 + e^{\beta^T x}} = (1 + e^{-\beta^T x})^{-1}$$

2.2 Estimation

- The input data for logistic regression are: $(\mathbf{x}_i, y_i)_{i=1}^n$ where $y_i \in \{0, 1\}$, $\mathbf{x}_i = (x_{i0}, x_{i1}, \dots, x_{ip})^T$.
- $y_i | \mathbf{x}_i \sim \text{Bern}(p_i(\beta))$
 - $p_i(\beta) = \Pr(Y = 1 | \mathbf{X} = \mathbf{x}_i; \beta) = (1 + e^{-\beta^T x})^{-1}$
 - Where $\beta^T \mathbf{x}_i = \mathbf{x}_i^T \beta = \beta_0 + \sum_{j=1}^p x_{ij} \beta_j$
- Bernoulli Likelihood Function is:

$$L(\beta) = \prod_{i=1}^n p_i(\beta)^{y_i} (1 - p_i(\beta))^{1-y_i}$$

$$\begin{aligned} \log L(\beta) &= \sum_{i=1}^n \{y_i \ln p_i(\beta) + (1 - y_i) \ln(1 - p_i(\beta))\} \\ &= \sum_{i=1}^n \begin{cases} \ln p_i(\beta) & y_i = 1 \\ \ln(1 - p_i(\beta)) & y_i = 0 \end{cases} \\ &= \sum_{i:y_i=1} \ln p_i(\beta) + \sum_{i:y_i=0} \ln(1 - p_i(\beta)) \end{aligned}$$

- The usual approach to estimating the Logistic Regression coefficients is *maximum likelihood*:

$$\hat{\beta} = \arg \max_{\beta} L(\beta) = \arg \max_{\beta} \log L(\beta)$$

- We can also view this as the coefficients that minimize the *loss function* $\ell(\beta)$, where the loss function is the negative log-likelihood:


$$\hat{\beta} = \arg \min_{\beta} \ell(\beta)$$

Using loss $\ell(\beta) = -C \log L(\beta)$ where $C > 0$ is some positive constant, e.g., $C = 1/n$

- This view facilitates *penalized logistic regression*:

$$\hat{\beta} = \arg \min_{\beta} \ell(\beta) + \lambda P(\beta)$$

Ridge Penalty	$P(\beta) = \ \beta\ _2^2 = \sum_{j=1}^p \beta_j ^2 = \beta^T \beta$
Lasso Penalty	$P(\beta) = \ \beta\ _1 = \sum_{j=1}^p \beta_j $
Best Subsets	$P(\beta) = \ \beta\ _0 = \sum_{j=1}^p \beta_j ^0 = \sum_{j=1}^p 1_{\beta_j \neq 0}$
Elastic Net	$P(\beta, \alpha) = \frac{(1-\alpha)\ \beta\ _2^2}{2} + \alpha\ \beta\ _1 = \sum_{j=1}^p \left(\frac{(1-\alpha) \beta_j ^2}{2} + \alpha \beta_j \right)$



2.3 Logistic Regression in Action

- In **Python**, logistic regression can be implemented with `smf.logit()` function.

```
import statsmodels.api as sm
import statsmodels.formula.api as smf


# Fit logistic regression model
model_formula = 'y ~ student + balance + income'
fit_lr = smf.logit(formula=model_formula, data=Default).fit()

# Print the summary
print(fit_lr.summary())
```

	coef	std err	z	P> z	[0.025	0.975]
Intercept	-10.8690	0.492	-22.079	0.000	-11.834	-9.904
student	-0.6468	0.236	-2.738	0.006	-1.110	-0.184
balance	0.0057	0.000	24.737	0.000	0.005	0.006
income	3.033e-06	8.2e-06	0.370	0.712	-1.3e-05	1.91e-05


Your Turn #4: Interpreting Logistic Regression

1. What is the estimated probability of default for a Student with a balance of \$1000?
2. What is the estimated probability of default for a Non-Student with a balance of \$1000?
3. Why does `student=Yes` appear to lower risk of default, when the plot of student status vs. default appears to increase risk?



2.3.1 Penalized Logistic Regression

- The `smf` lib can estimate logistic regression using an elastic net penalty (e.g., ridge, lasso).



term	unpenalized	lambda.min	lambda.1se
(Intercept)	-10.869	-11.056	-7.937
studentYes	-0.647	-0.299	-0.041
balance	0.006	0.006	0.004
income	0.000	0.000	0.000
studentNo	NA	0.325	0.044

2.3.2 Logistic Regression Summary

- Logistic Regression (both penalized and unpenalized) estimates a *posterior probability*, $\hat{p}(x) = \widehat{\Pr}(Y = 1 \mid X = x)$.
- This estimate is a function of estimated coefficients.

$$\hat{p}(x) = \frac{e^{\beta^T x}}{1 + e^{\beta^T x}} = (1 + e^{-\beta^T x})^{-1}$$

Your Turn #5

- Given a person's **student** status, **balance**, and **income**, how could you use Logistic Regression to decide if they will **default**? (i.e., make a hard classification)