

# COMPASS Architecture Docs — Consolidated Overview (one page)

A single at-a-glance index of every doc in `docs/architecture` + a current DB summary. Korean mirror: `INDEX_KR.md`. See each doc / `models.py` for detail. (Current schema: **15 app tables** + `alembic_version`, alembic head **029**.)

## 1. Docs in this folder (what each covers)

| Doc                                                          | Lang  | What it explains                                                                                                                                                |
|--------------------------------------------------------------|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>DATABASE_SCHEMA.md</code> / <code>_KR</code>           | EN/KR | <b>Table catalog</b> — each of the 15 tables: purpose · why it exists · the anchor (parent-child) pattern                                                       |
| <code>DB_TABLES_ROLES.md</code> / <code>_KR</code>           | EN/KR | <b>One file's journey</b> — transcript→NLP→AI→screen, told as a story of which drawer (table) gets what at each step                                            |
| <code>AI_PIPELINE_NLP_DB_TABLES.md</code> / <code>_KR</code> | EN/KR | <b>Pipeline detail</b> — NLP 7 steps · AI 5 steps → table-fill matrix · ERD · per-table detail                                                                  |
| <code>SAME_PATIENT_DIFF_DOCTOR.md</code> / <code>_KR</code>  | EN/KR | Why <b>same-patient/different-doctor</b> data never mixes (file = patient+doctor+date is the key)                                                               |
| <code>REDCAP_RECORD_ID_MAPPING.md</code> / <code>_KR</code>  | EN/KR | <b>REDCap record_id</b> — a survey is attributed to the record whose <code>record_id</code> is the study SID ( <code>record_id == SID</code> )                  |
| <code>ARCHITECTURE.md</code>                                 | EN    | System overview · deployment · module layout                                                                                                                    |
| <code>WEBAPP_ARCHITECTURE.md</code> / <code>_KR</code>       | EN/KR | <b>Webapp internals</b> — query-string routing · admin gate · Zustand stores and their consumers · component tree per persona · what is dead (Mermaid diagrams) |

## 2. Current DB — 15 app tables (by group)

### Pipeline persistence (7)

`transcript_analysis_log` (run header · anchor) · `sentence_prediction` (top-N sentences) · `nlp_all_predictions` (all sentences × 5 models) · `nlp_pipeline_intermediate` (NLP snapshots) · `llm_pipeline_intermediate` (AI intermediate) · `llm_domain_scoring_and_summary` (final, patient-facing) · `patient_summary` (patient parent anchor)

### Behavior tracking (3) — UI interaction events (not values)

`patient_report_page_behavior` (first-visit report page) · `patient_followup_survey_page_behavior` (survey pages: follow-up + first-visit Risk) · `doctor_behavior` (doctor dashboard)

## Auth (2)

`auth_user` · `auth_api_key`

## Other (3)

`session_recording` · `patient_survey_submission_log` (**all patient survey answers** — first-visit Risk = risk\_perception\_2 + follow-up sdm/dcs/satisfaction) · `doctor_rewrite_log` (doctor sentence rewrites)

## System (1)

`alembic_version` (migration version)

---

## 3. Three core concepts

---

1. **Anchor (parent-child):** `transcript_analysis_log` (id) and `patient_summary` (file, speaker) hold identity only; children FK to them → integrity · cascade · re-processing survival.
  2. **Data flow:** file → NLP (sentences · probs ②③) → AI (scores · patient summaries ④⑤) → screens read ③⑤. Human input (surveys · rewrites) and behavior logs pile up separately.
  3. **File = key:** records are distinguished by file (patient+doctor+date), not patient id → same-patient/different-doctor never mixes.
- 

**One-liner:** all patient survey answers live in one place ( `patient_survey_submission_log` ), behavior logs in `*_page_behavior` / `doctor_behavior` , pipeline outputs under `transcript_analysis_log` 's children — 15 app tables total.