Technical Supplement

SABER: Support-Conditioned Adaptive Bellman Error Reweighting for Sparse-Reward Hindsight Experience Replay

Anonymous Submission

Overview. This supplement gives a complete mathematical specification and pseudocode for SABER, followed by experimental settings, seed-level primary results, sensitivity and scope controls, support-signal diagnostics, runtime measurements, and an index of the anonymous code-and-data artifacts.

1 Complete SABER Specification

1.1 Scope, Problem Setting, and Notation

SABER is a critic-loss allocation rule for replay-based off-policy actor–critic learning. It is neither a replay sampler nor a network module. Consider a finite-horizon goal-conditioned MDP

$$\mathcal{M} = (\mathcal{S}, \mathcal{A}, \mathcal{G}, P, r, \gamma, H).$$

The agent receives observation o_t, desired goal g, and network input $x_t = (o_t, g)$. The achieved-goal map is $m : \mathcal{S} \to \mathcal{G}$. The sparse reward used in the experiments is

$$r(s_t, a_t, s_{t+1}, g) = \begin{cases} 0, & d(m(s_{t+1}), g) \le \epsilon_g, \\ -1, & \text{otherwise.} \end{cases} \tag{1}$$

Replay stores the executed action a_i^r. We reserve a_i^π for the detached current-policy action used only by SABER's discrete support query. There are $n_Q = 1$ critics for DDPG and $n_Q = 2$ for TD3 and SAC.

1.2 Future-Goal HER Batch and Unchanged Bellman Targets

Let an episode contain states $s_0, \dots, s_T$ and transitions indexed by $t = 0, \dots, T-1$. When transition t is selected for relabeling and has an eligible later stored transition, the implemented future-goal convention samples

$$\begin{aligned} u &\sim \mathrm{Unif}\{t+1, \dots, T-1\}, \\ \widetilde{g}_i &= m(s_{u+1}), \\ \widetilde{r}_i &= r(s_t, a_t, s_{t+1}, \widetilde{g}_i). \end{aligned} \tag{2}$$

If the eligible set is empty, or if relabeling is not selected, the original desired goal and its corresponding reward are retained. Thus the nominal relabeling probability is $p_{\mathrm{HER}} = 0.8$, while the realized fraction can be slightly lower near an episode boundary. The relabeled network inputs are

$$x_i = (o_i, \widetilde{g}_i), \qquad x_i' = (o_i', \widetilde{g}_i).$$

Let $\chi_i \in \{0, 1\}$ be the bootstrap mask. Successful relabeled transitions and time-limit transitions use $\chi_i = 1$; genuine terminating transitions use $\chi_i = 0$. For backbone A, define

$$y_i^{\mathsf{A}} = \widetilde{r}_i + \gamma \chi_i V_i^{\mathsf{A}}(x_i'), \tag{3}$$

where target values are evaluated without gradient. Writing barred parameters for target networks, the implemented continuation values have the standard forms

$$V_i^{\mathrm{DDPG}} = Q_{\bar{\phi}_1}(x_i', \mu_{\bar{\theta}}(x_i')), \tag{4}$$

$$\begin{aligned} \varepsilon_i &\sim \mathrm{clip}\big(\mathcal{N}(0, \sigma_{\mathrm{targ}}^2 I), -c, c\big), \\ \widetilde{a}_i' &= \mathrm{clip}_{\mathcal{A}}(\mu_{\bar{\theta}}(x_i') + \varepsilon_i), \\ V_i^{\mathrm{TD3}} &= \min_{k \in \{1,2\}} Q_{\bar{\phi}_k}(x_i', \widetilde{a}_i'), \end{aligned} \tag{5}$$

$$\begin{aligned} a_i' &\sim \pi_\theta(\cdot \mid x_i'), \\ V_i^{\mathrm{SAC}} &= \min_{k \in \{1,2\}} Q_{\bar{\phi}_k}(x_i', a_i') - \alpha \log \pi_\theta(a_i' \mid x_i'). \end{aligned} \tag{6}$$

SABER does not change any quantity in Eqs. (2)–(6). For critic k, the replay-action Bellman residual remains

$$\delta_{ik} = Q_{\phi_k}(x_i, a_i^r) - y_i^{\mathsf{A}}. \tag{7}$$

Under ordinary uniformly sampled HER, every squared residual has explicit coefficient one.

1.3 Current-Policy Local Support

For each relabeled sample, SABER forms the full discrete observation–goal–horizon context

$$c_i = C(o_i, \widetilde{g}_i, h_i), \tag{8}$$

where h_i is the remaining horizon. A lower-dimensional retrieval key $C^{\mathrm{ret}}(o_i, h_i)$ is used only to query the replay index. Let $\mathbf{J}_i^{\mathrm{ret}}$ be the resulting ordered list of currently valid, unique replay slots. Invalid entries and duplicate slot identifiers are removed in maintained index order, retaining the first valid occurrence. The bounded scan is

$$S_i = \mathrm{Tail}_{N_{\mathrm{scan}}}\left(\mathbf{J}_i^{\mathrm{ret}}\right), \qquad |S_i| \le N_{\mathrm{scan}}. \tag{9}$$

The tail refers to deterministic maintained index order, not guaranteed temporal recency after circular-buffer wraparound. The coarse key is only an acceleration device. Support eligibility is determined by exact component-wise equality of the full context:

$$I_i = \{j \in S_i : C(o_j, \widetilde{g}_i, h_j) = C(o_i, \widetilde{g}_i, h_i)\}. \tag{10}$$

The query's relabeled goal $\widetilde{g}_i$ is used on both sides; a candidate's originally stored desired goal is not used for matching. The sampled transition is not removed from consideration and may therefore occur in I_i.

For action dimension d, let ℓ_d and u_d be its environment bounds. SABER first maps the action to

$$z_d(a) = \mathrm{clip}\left(\frac{a_d - \ell_d}{u_d - \ell_d}, 0, 1\right) \tag{11}$$

and assigns the discrete component

$$b_{K,d}(a) = \min\{K - 1, \lfloor K z_d(a) \rfloor\}. \tag{12}$$

The multidimensional bin $b_K(a)$ is the tuple of these components; the implementation stores its equivalent base-K integer encoding. The local set of occupied replay-action bins is

$$\mathcal{U}_i = \left\{b_K(a_j^r) : j \in I_i\right\}, \qquad n_i = |I_i|. \tag{13}$$

The binary support indicator is

$$\psi_i = \mathbf{1}\{n_i \ge N_{\mathrm{local}}\}\, \mathbf{1}\{b_K(a_i^\pi) \in \mathcal{U}_i\}. \tag{14}$$

If retrieval returns no candidates, exact matching yields too few candidates, or the policy bin is unoccupied, then $\psi_i = 0$. Main SABER uses

$$K = 5, \qquad N_{\mathrm{scan}} = 512, \qquad N_{\mathrm{local}} = 4.$$

DDPG and TD3 use their deterministic actor output as a_i^π. SAC uses the deterministic squashed actor mean for this query only; its target and actor updates continue to use stochastic policy samples. No gradient passes through a_i^π, action binning, retrieval, or ψ_i.

Task family	Full context components	Coarse retrieval key
FetchPickAndPlace	Phase, hand–object distance, object–goal distance, object height, gripper gap, horizon	Hand–object distance, object height, gripper gap, horizon
DrawerOpen/Close	Phase, hand–handle distance, handle–goal distance, handle y, gripper state, horizon	Hand–handle distance, handle y, gripper state, horizon

Table 1: Task-specific support contexts. Candidate retrieval uses the coarse key, after which exact component-wise equality on the full discretized context defines the local replay set.

Component	FetchPickAndPlace thresholds	Drawer thresholds
Phase	approach, grasp, lift, place	approach, contact, opening/closing, open/closed
Hand distance	.03, .05, .08, .12, .20, .40	.03, .05, .08, .12, .20, .40
Goal distance	.05, .10, .20, .40, .70	.03, .05, .08, .12, .20, .40, .70
Task coordinate	object z: .43, .48, .55, .65, .75	handle y: $-.05, 0, .05, .10, .15, .25$
Gripper	gap: .02, .05, .08	state: $-.50, 0, .50$
Remaining horizon	$10, 25, 50, 100$	$10, 25, 50, 100, 200, 500$

Table 2: Discretization boundaries used to construct support contexts. Values are applied component-wise in environment units. The main method normalizes each action dimension to its action bounds and uses $K = 5$ bins per dimension, $N_{\mathrm{scan}} = 512$, $N_{\mathrm{local}} = 4$, and $\lambda_S = 1$.

For the Drawer phase definitions, let d_h be hand–handle distance and d_g be handle–goal distance. The terminal phase is open or closed when $d_g \le 0.05$; opening or closing requires $d_h \le 0.08$ and $0.05 < d_g \le 0.12$; contact requires $d_h \le 0.08$ and $d_g > 0.12$; remaining samples are approach. Phases use the relabeled training goal.

1.4 Mean-Normalized Critic-Only Objective

SABER assigns the raw coefficient

$$w_i^{\mathrm{raw}} = 1 + \lambda_S \psi_i \tag{15}$$

and normalizes it by the minibatch mean:

$$\bar{w}_B = \frac{1}{|B|} \sum_{j \in B} w_j^{\mathrm{raw}}, \qquad \Omega_i = \frac{w_i^{\mathrm{raw}}}{\max(\epsilon_w, \bar{w}_B)}. \tag{16}$$

We use $\lambda_S = 1$ and $\epsilon_w = 10^{-8}$. The safeguard is inactive because $w_i^{\mathrm{raw}} \geq 1$. If $p_B = |B|^{-1} \sum_i \psi_i$, then

$$\Omega_i = \begin{cases} \dfrac{1 + \lambda_S}{1 + \lambda_S p_B}, & \psi_i = 1, \\ \dfrac{1}{1 + \lambda_S p_B}, & \psi_i = 0. \end{cases} \tag{17}$$

Hence every sample remains in the update with a positive coefficient, the minibatch mean coefficient is one, and support-positive samples receive relative weight $1 + \lambda_S$ compared with support-negative samples. If all indicators in a minibatch are equal, then every normalized coefficient is exactly one.

The critic objective is

$$\mathcal{L}_Q^{\mathrm{SABER}} = \frac{1}{|B|} \sum_{i \in B} \Omega_i \sum_{k=1}^{n_Q} \delta_{ik}^2. \tag{18}$$

For TD3 and SAC, the same Ω_i multiplies both critic residuals. The main variant is critic-only:

$$\mathcal{L}_\pi^{\mathrm{SABER}} = \mathcal{L}_\pi^{\mathsf{A}}. \tag{19}$$

Mean-one normalization preserves the average explicit coefficient, but does not imply an unchanged numerical loss or gradient norm because support may correlate with residual magnitude.

Weight-range invariant. For the Main choice $\lambda_S = 1$, the support-negative and support-positive coefficients in any mixed minibatch with $0 < p_B < 1$ satisfy

$$\tfrac{1}{2} < \Omega_i^- < 1 < \Omega_i^+ < 2, \qquad \sum_{i \in B} \Omega_i = |B|.$$

Thus SABER neither drops a sample nor assigns an unbounded coefficient. It reduces exactly to the uniformly weighted HER critic objective when all indicators are zero or all are one.

1.5 End-to-End Update

Algorithm 1 states one complete learning update. The replay index is maintained as transitions enter or overwrite replay slots. Candidate retrieval supplies only a bounded list; exact full-context matching determines support eligibility.

Algorithm 1: One SABER update

Require: replay $\mathcal{D}$ and index $\mathcal{R}$; actor π_θ; critics $\{Q_{\phi_k}\}_{k=1}^{n_Q}$; target networks
Require: context maps C, C^{ret}; $K, N_{\mathrm{scan}}, N_{\mathrm{local}}, \lambda_S$

$B \leftarrow \mathrm{UniformSample}(\mathcal{D})$
Apply Eq. (2) where selected and eligible; recompute rewards.
for each relabeled sample $i \in B$ **do**
  Construct x_i, x_i', bootstrap mask χ_i, and detached y_i^{A} using Eqs. (3)–(6).
  $a_i^\pi \leftarrow \mathrm{sg}[\mathrm{QueryAction}_{\mathsf{A}}(x_i)]$
  $q_i^{\mathrm{ret}} \leftarrow C^{\mathrm{ret}}(o_i, h_i)$
  $\mathbf{J}_i^{\mathrm{ret}} \leftarrow \mathcal{R}[q_i^{\mathrm{ret}}]$
  Remove invalid and duplicate slots from $\mathbf{J}_i^{\mathrm{ret}}$.
  $S_i \leftarrow \mathrm{Tail}_{N_{\mathrm{scan}}}(\mathbf{J}_i^{\mathrm{ret}})$
  $I_i \leftarrow \{j \in S_i : C(o_j, \widetilde{g}_i, h_j) = C(o_i, \widetilde{g}_i, h_i)\}$
  $\mathcal{U}_i \leftarrow \{b_K(a_j^r) : j \in I_i\}$
  $\psi_i \leftarrow \mathbf{1}\{|I_i| \geq N_{\mathrm{local}}\}\mathbf{1}\{b_K(a_i^\pi) \in \mathcal{U}_i\}$
  $w_i^{\mathrm{raw}} \leftarrow 1 + \lambda_S \psi_i$
end for
$\Omega_i \leftarrow w_i^{\mathrm{raw}} / \max(\epsilon_w, |B|^{-1} \sum_{j \in B} w_j^{\mathrm{raw}})$ for every i.
Compute replay-action residuals using Eq. (7).
Update all critics with Eq. (18).
Apply the backbone's unchanged actor, temperature, delayed-update, and target-network rules.

The algorithm introduces no auxiliary target and never regresses the critic at a_i^π. It does not alter minibatch membership, HER relabeling, reward recomputation, exploration, network architecture, optimizer, or UTD. The indicator is a binary occupancy proxy, not an estimate of density, uncertainty, target accuracy, target variance, or TD-error rank. Finally, SABER cannot mark an action as locally supported unless its action bin is already represented by replay actions in the matched context.

Operational and cost boundary. The support path is a detached, non-neural lookup and introduces no trainable parameter or optimizer state. For minibatch B, at most $|B|N_{\text{scan}}$ slots enter exact full-context matching and action-bin occupancy after retrieval; under the Main setting this is at most $256 \times 512 = 131{,}072$ slot checks per update. This bound applies to the post-retrieval scan, not to all index maintenance or candidate-list processing, whose cost can depend on retrieval-key occupancy. Once Ω_i is formed, the backbone follows its ordinary critic, actor, temperature, delayed-update, and target-network rules.

2 Experimental and Reproducibility Details

2.1 Tasks, Cohorts, and Shared Training Settings

Purpose. This section fixes the experimental scope before any method is compared. Its purpose is to identify which quantities are paired, which quantities are shared, and which task–backbone combinations support a matched SABER claim.

Protocol. Tables 3–5 give the settings shared within each matched cohort. The primary comparison contains seven task–backbone cohorts and uses paired seeds 1–5. Drawer SAC is not a primary cohort because a complete matched HER–SABER pair was not collected.

Task	Horizon	Budget	Backbones	Exact primary grid
FetchPickAndPlace-v4	50	1M	DDPG, TD3, SAC	10k (DDPG/TD3), 50k (SAC)
DrawerOpen-v3	200	2M	DDPG, TD3	10k
DrawerClose-v3	200	2M	DDPG, TD3	10k

Table 3: Primary task and cohort definitions. Every method within a task–backbone cohort uses the same environment-step budget and exact evaluation grid. Primary comparisons use paired seeds 1–5.

Setting	Value or convention
HER	Future-goal convention in Sec. 1.2; nominal $p_{\text{HER}} = 0.8$
Replay	Uniform for HER and SABER; capacity 300k; minibatch size 256
Networks	Actor and critic MLPs with two hidden layers of 256 units
Optimization	Adam, actor and critic learning rates 3×10^{-4}
Discount and targets	$\gamma = 0.98$, Polyak coefficient $\tau = 0.005$
Update schedule	UTD 1; learning begins after 5k steps; random actions for first 10k steps
Termination	Successful relabeled transitions are nonterminal; time limits bootstrap
Evaluation	Deterministic policy, 20 episodes per checkpoint
Statistics	Seed mean and sample SD; paired percentile-bootstrap CI, 10,000 resamples, RNG seed 2027
Curve processing	Exact common checkpoints only; no smoothing, interpolation, extrapolation, or filling

Table 4: Shared training, evaluation, and statistical settings. Matched HER–SABER runs use identical replay and relabeling code.

Backbone	Critic	Exploration or entropy	Backbone-specific settings
DDPG	One critic	Gaussian action noise, SD 0.2	Deterministic actor
TD3	Twin critics	Gaussian action noise, SD 0.2	Target noise 0.2, clip 0.5, policy delay 2
SAC	Twin critics	Automatic entropy tuning	Initial $\alpha = 0.2$, α LR 3×10^{-4}, target entropy -4

Table 5: Backbone-specific settings. SABER preserves each backbone's target construction and actor-update rule.

Tuning boundary. We did not conduct an exhaustive joint hyperparameter search. The Main SABER settings were fixed for the matched comparisons, and no control received variant-specific tuning. The $K \in \{3, 7\}$ runs are sensitivity checks around Main $K = 5$, not a per-task model-selection sweep.

Interpretation boundary. Within each paired cohort, HER and SABER share the task, seed, training budget, replay and relabeling code, backbone, optimizer, exploration process, UTD, and evaluation grid. Their intended algorithmic difference is therefore the per-sample critic-loss coefficient. Absolute AUC values are not compared across tasks because horizons and training budgets differ.

2.2 Comparison Methods

Purpose. The comparison suite separates three operational intervention points after experience collection: hindsight selection, replay-transition selection, and fixed-minibatch critic-loss allocation.

Protocol.

Prioritization controls. HGR prioritizes an episode and then a transition–future-goal pair, multiplies the two normalized importance factors on relabeled samples, and leaves the original-goal coefficient at one. PER samples replay transitions with TD-error priority and annealed importance correction. Both change realized selection, unlike SABER and the TD-error critic-loss weighting control.

Method	Selection changed	Loss coefficient	Correction
HER	None beyond uniform replay and HER relabeling	Uniform	None
SABER	None	Current-policy local-support weight	Unit minibatch mean
HGR	Episode and transition–future-goal pair	HGR importance weight	Two-stage IS
PER	Replay transition	PER importance weight	Annealed IS
TD-error weighting	None	TD-error-derived weight	Unit minibatch mean

Table 6: Operational intervention points. HGR uses priority exponents $\alpha_{\text{episode}} = \alpha_{\text{pair}} = 0.6$, while PER uses $\alpha = 0.6$. Both anneal β linearly from 0.4 to 1.0 over critic-update progress and use priority offset 10^{-6}. TD-error weighting retains uniform replay and is therefore the closest allocation-stage control.

TD-error critic-loss weighting. This control preserves uniform replay and changes only normalized per-sample critic coefficients. DDPG uses its single absolute TD error. SAC uses $\min(|\delta_{i1}|, |\delta_{i2}|)$ as the signal and applies the resulting coefficient to both critic losses. For signal e_i, the implementation computes

$$p_i = (e_i + 10^{-6})^{0.6}, \qquad u_i = \text{clip}\left(\frac{p_i}{|B|^{-1}\sum_{j\in B} p_j},\, 0,\, 2\right), \qquad \Omega_i = \frac{u_i}{\max(10^{-8},\, |B|^{-1}\sum_{j\in B} u_j)}.$$

Thus the uncapped priorities are mean-normalized before clipping and the clipped coefficients are normalized again to unit minibatch mean. TD3 results are not reported because the stored control used independent target-policy smoothing noise for weight construction and optimized residuals, preventing the intended matched-signal interpretation.

Interpretation boundary. HER is the direct matched baseline. HGR and PER are broader prioritization comparisons because they alter realized selection, whereas TD-error weighting is the closest alternative allocation-signal control where validated. Thus an ordering against HGR or PER does not isolate loss allocation alone, while an ordering against TD-error weighting does not establish superiority over every possible weighting signal.

2.3 Metrics and Statistical Analysis

Purpose. The metrics distinguish full-training performance, late-training performance, final-checkpoint behavior, and threshold-reaching time without smoothing away seed variability.

Protocol. Let $q_j \in [0, 1]$ be deterministic evaluation success at exact shared checkpoint t_j. Normalized success AUC is

$$\text{AUC} = \frac{1}{t_m - t_1}\sum_{j=1}^{m-1}\frac{q_j + q_{j+1}}{2}(t_{j+1} - t_j).$$

Final-quarter AUC applies the same calculation to 750k–1M for FPP and 1.5M–2M for Drawer tasks. Final success is the value at the final checkpoint. Hit90 is the first exact checkpoint with $q_j \geq 0.9$; its median is computed only over seeds that reach the threshold, so reached-seed coverage is always reported.

Checkpoint alignment and unit of inference. For seed s, checkpoint success is the mean of 20 binary outcomes from deterministic-policy evaluation episodes. Before computing a comparison, we restrict every included method to the intersection of its available checkpoint labels; AUC, FQ-AUC, and final success for that comparison use this same grid. The statistical unit is the seed rather than an episode or checkpoint. Thus a paired comparison first forms one difference d_s per shared seed, and the paired bootstrap resamples the vector of seed-indexed differences. Evaluation episodes and checkpoints are never treated as independent replicates. A seed that does not reach success 0.9 contributes to reached-seed coverage but is not assigned an artificial Hit90 time.

Evaluation isolation. Evaluation uses the deterministic policy with exploration disabled and a seed stream separate from training. Evaluation transitions are not inserted into replay and trigger no optimizer or target-network update. Checkpoint labels count training environment interactions only, so evaluation frequency does not change the stated training budget or replay contents.

Cohort separation. Primary claims use the paired five-seed cohorts only. The frozen FPP TD3 ten-seed cohort, indexing sensitivity, and Drawer diagnostic seeds 6–10 are reported as confirmatory, sensitivity, or diagnostic extensions and are not silently pooled into primary confidence intervals. Where a pooled ten-seed diagnostic summary is shown, it is labeled descriptive.

For paired comparisons, each seed contributes one method difference. Primary and newly derived intervals use 10,000 paired percentile-bootstrap resamples with pseudorandom seed 2027. The frozen mechanism-control intervals reproduce their validated source artifacts: FPP uses 10,000 resamples with seed 27027, whereas Drawer controls use exact empirical-bootstrap enumeration over all $5^5 = 3125$ paired bootstrap assignments. Sample standard deviations use $n - 1$ in the denominator. No curve is smoothed, interpolated, extrapolated, or forward-filled.

Metric and uncertainty boundary. The trapezoidal AUC weights each interval by elapsed environment steps, so a denser checkpoint schedule does not receive extra mass merely by containing more checkpoints. Normalized AUC and FQ-AUC remain in $[0, 1]$. Method-wise mean and sample SD describe across-seed level and dispersion, whereas paired intervals quantify uncertainty in within-seed differences. An interval that includes zero is treated as inconclusive rather than as evidence of equivalence. Hit90 uses only an observed checkpoint crossing and is never interpolated between evaluations.

AUC boundary handling. The full-span integral begins at the first shared recorded checkpoint t_1 and ends at t_m; we do not prepend a synthetic zero-step success value. FQ-AUC restricts the same checkpoint sequence to the stated task-specific window and normalizes by that window's observed elapsed span. The exact grids contain the window endpoints, so neither metric requires a fractional or interpolated checkpoint. Final success is q_m on the same shared grid. These rules are applied unchanged to every method in a reported comparison.

Interpretation boundary. Where reported, Steps/s is the seed-1–5 mean of completed training steps divided by runtime. Because historical runs were not hardware-normalized across families, it is descriptive rather than a learning-efficiency claim. Control and reference tables use a common metric order; diagnostic tables retain signal-specific columns.

3 Primary Comparison Details

3.1 Drawer Learning Curves

Purpose. Full-span AUC compresses the learning trajectory into one number. The Drawer curves expose when success emerges, whether gains persist late in training, and how much of each aggregate ordering is driven by seed variability.




Figure 1: DrawerOpen and DrawerClose learning curves for DDPG and TD3. Lines are seed means and bands are sample standard deviations over paired seeds 1–5 on the exact 10k grid. No smoothing or interpolation is applied.

Results. DrawerOpen DDPG shows the clearest separation from HER, whereas the TD3 cohorts and comparisons with HGR and PER exhibit larger seed dispersion and mixed metric-dependent orderings. On DrawerClose DDPG, HGR leads full-span AUC but not FQ-AUC, illustrating that early and late summaries can disagree. DrawerClose TD3 has wide AUC dispersion for every method (sample SD 0.305–0.422); DDPG dispersion is method-dependent (0.030–0.184).

Interpretation. The trajectories support the matched HER result but do not establish a universal ranking against HGR or PER. They also show why full-span AUC, FQ-AUC, and final success are retained separately: early learning, late occupancy, and a single final checkpoint need not order methods identically. All four methods are HER-based and SABER changes only critic-loss allocation, so the observed DrawerClose variability is not unique to SABER; these curves do not by themselves identify HER as its cause.

3.2 Paired Uncertainty against HGR and PER

Purpose. The aggregate primary table reports method-wise dispersion. This analysis instead quantifies uncertainty in the within-seed SABER–HGR and SABER–PER differences for both full-span and final-quarter AUC.

Cohort	Comparator	ΔAUC (95% CI)	ΔFQ-AUC (95% CI)
FPP–DDPG	HGR	$+0.271[0.197, 0.405]$	$+0.480[0.286, 0.717]$
	PER	$+0.149[-0.001, 0.349]$	$+0.196[0.014, 0.555]$
FPP–TD3	HGR	$+0.075[0.065, 0.085]$	$+0.270[0.216, 0.318]$
	PER	$+0.073[0.051, 0.096]$	$+0.242[0.181, 0.300]$
FPP–SAC	HGR	$+0.100[0.029, 0.159]$	$+0.322[0.133, 0.482]$
	PER	$-0.106[-0.124, -0.085]$	$+0.000[-0.009, 0.013]$
DrawerOpen–DDPG	HGR	$+0.065[-0.047, 0.219]$	$+0.005[-0.021, 0.038]$
	PER	$-0.071[-0.104, -0.014]$	$+0.006[-0.009, 0.021]$
DrawerOpen–TD3	HGR	$-0.009[-0.489, 0.471]$	$+0.001[-0.795, 0.798]$
	PER	$-0.045[-0.101, -0.002]$	$+0.002[-0.001, 0.007]$
DrawerClose–DDPG	HGR	$-0.025[-0.225, 0.132]$	$+0.052[-0.045, 0.149]$
	PER	$+0.016[-0.059, 0.094]$	$-0.062[-0.152, 0.052]$
DrawerClose–TD3	HGR	$-0.053[-0.470, 0.255]$	$+0.074[-0.452, 0.518]$
	PER	$+0.025[-0.365, 0.466]$	$-0.049[-0.598, 0.517]$

Table 7: Paired SABER-minus-prioritization differences over seeds 1–5. Positive values favor SABER. Intervals are 10,000-resample paired percentile-bootstrap 95% CIs computed from within-seed differences.

Results. The AUC intervals favor SABER over HGR for all three FPP backbones and over PER for FPP TD3. PER is higher with intervals excluding zero on FPP SAC and both DrawerOpen backbones. All DrawerClose AUC and FQ-AUC intervals include zero. For FQ-AUC, SABER is higher than HGR across FPP and higher than PER on FPP DDPG and TD3, while the FPP SAC SABER–PER interval includes zero.

Interpretation. The paired intervals reinforce a task-, backbone-, and metric-dependent ordering rather than a universal advantage over prioritization. HGR and PER also change realized selection, so these comparisons establish competitive operating regimes rather than isolate critic-loss allocation alone.

3.3 Time to Threshold

Purpose. Hit90 tests whether a method reaches a practically high success level and how early it first does so, complementing metrics that average over checkpoints.

Task–Backbone	SABER (Ours)	HER	HGR	PER
FPP–DDPG	540k / 5/5 / 41.7	600k / 5/5 / 65.0	930k / 2/5 / 16.9	640k / 4/5 / 58.0
FPP–TD3	840k / 5/5 / 41.2	980k / 3/5 / 65.3	630k / 1/5 / 12.9	1.00M / 1/5 / 50.8
FPP–SAC	750k / 5/5 / 29.1	800k / 3/5 / 38.9	800k / 2/5 / 8.4	550k / 5/5 / 34.8
DrawerOpen–DDPG	500k / 5/5 / 23.3	960k / 2/5 / 41.1	530k / 5/5 / 13.2	330k / 5/5 / 34.0
DrawerOpen–TD3	780k / 3/5 / 21.6	740k / 1/5 / 41.5	760k / 3/5 / 11.6	720k / 3/5 / 34.6
DrawerClose–DDPG	20k / 5/5 / 24.0	70k / 5/5 / 41.2	100k / 5/5 / 13.2	60k / 5/5 / 33.9
DrawerClose–TD3	80k / 5/5 / 22.5	70k / 5/5 / 41.7	80k / 5/5 / 11.8	120k / 5/5 / 34.4

Table 8: Hit90 for the primary comparisons. Hit90 is the first exact-grid checkpoint at which deterministic evaluation success reaches at least 0.9. Each method cell reports median Hit90 / reached seeds / descriptive steps/s. Medians use only reached seeds; Steps/s is defined in Section 2.3.

Results. Across the three FPP backbones, SABER reaches Hit90 in all 15 runs, compared with 11/15 for HER, 5/15 for HGR, and 10/15 for PER. On DrawerOpen DDPG, SABER reaches in 5/5 seeds at a reached-seed median of 500k, whereas HER reaches in 2/5 at 960k. On DrawerClose, every primary method reaches Hit90 in all seeds for both backbones, despite substantial differences in later performance.

Interpretation. Hit90 is a threshold-crossing summary rather than a stability measure. Its conditional median is meaningful only together with reached-seed coverage, and early threshold crossing cannot substitute for FQ-AUC or final success.

3.4 FPP TD3 Confirmatory and HER-Indexing Sensitivity Results

Purpose. The ten-seed extension tests whether the primary five-seed FPP TD3 direction persists under a larger frozen cohort. The indexing sensitivity asks whether that direction is specific to excluding $m(s_{t+1})$ from future goals.

Results. In the ten-seed cohort, SABER exceeds HER in 8/10 pairs, with mean AUC difference $+0.0467$, paired-bootstrap 95% CI $[0.0085, 0.0783]$, and exact sign-flip $p = 0.0527$. Under inclusive-future indexing, the original five-seed mean difference is $+0.0674$ (95% CI $[-0.0068, 0.1416]$); the seeds 6–10 extension yields $+0.0114$ (95% CI $[-0.0507, 0.0950]$). Descriptively pooling all ten paired seeds gives $+0.0394$ (95% CI $[-0.0122, 0.0960]$); the pooled descriptive FQ-AUC and final-success differences are $+0.0795$ (95% CI $[-0.0455, 0.2213]$) and $+0.0650$ (95% CI $[-0.1700, 0.2950]$), respectively.

Seed	HER AUC	SABER (Ours) AUC	Difference
1	0.3465	0.4301	$+0.0836$
2	0.3727	0.4568	$+0.0841$
3	0.3942	0.4960	$+0.1018$
4	0.4109	0.4066	-0.0043
5	0.3338	0.4225	$+0.0886$
6	0.4301	0.5207	$+0.0907$
7	0.3995	0.4614	$+0.0619$
8	0.3068	0.3543	$+0.0475$
9	0.4106	0.4114	$+0.0008$
10	0.4210	0.3331	-0.0879
Mean	0.3826	0.4293	$+0.0467$

Table 9: Frozen FPP TD3 confirmatory extension over ten paired seeds. AUC uses the exact 10k–1M grid without smoothing, interpolation, or filling.

Seed	HER AUC	SABER (Ours) AUC	Difference
1	0.3005	0.4576	$+0.1571$
2	0.2674	0.2669	-0.0005
3	0.3467	0.5179	$+0.1712$
4	0.3487	0.4003	$+0.0515$
5	0.3669	0.3247	-0.0422
6	0.3664	0.3404	-0.0260
7	0.4285	0.3449	-0.0836
8	0.3235	0.3076	-0.0159
9	0.1846	0.3535	$+0.1689$
10	0.3341	0.3475	$+0.0134$
Mean	0.3267	0.3661	$+0.0394$

Table 10: FPP TD3 inclusive-future sensitivity, also admitting $m(s_{t+1})$, over ten paired seeds. Seeds 6–10 extend the original cohort; the pooled AUC is descriptive and uses the exact 10k–1M grid.

Interpretation. The confirmatory extension narrows the estimated TD3 gain while preserving positive paired bootstrap interval evidence. Both inclusive-future halves retain a positive observed mean AUC direction, although the second is substantially smaller and its final-quarter AUC and final-success means favor HER. This sensitivity does not establish equivalence between indexing conventions or a robust gain under the inclusive convention.

4 Additional Controls and Sensitivities

4.1 Mechanism Controls

Purpose. The four DDPG controls test the query action, sample–query alignment, and the location of high critic weights while exposing the absolute performance metrics underlying the paired AUC differences in the main paper.

Cohort	Method/Control	AUC	FQ-AUC	Final	Hit90	Steps/s	ΔAUC
FPP–DDPG	SABER (Ours)	0.609 ± 0.038	0.961 ± 0.014	0.960 ± 0.042	5/5 (0.540M)	41.7	$--$
	Replay-Action						
	Query	0.598 ± 0.027	0.950 ± 0.015	0.970 ± 0.045	5/5 (0.570M)	14.6	$+0.011[-0.028, 0.059]$
	Shuffled-Policy						
	Query	0.566 ± 0.036	0.958 ± 0.016	0.950 ± 0.071	5/5 (0.630M)	40.2	$+0.043[-0.002, 0.085]$
	Random-Support	0.553 ± 0.056	0.946 ± 0.035	0.960 ± 0.055	5/5 (0.630M)	40.4	$+0.056[0.014, 0.101]$
	Context-Eligible						
	Count-Matched	0.577 ± 0.032	0.961 ± 0.016	0.980 ± 0.027	5/5 (0.590M)	15.7	$+0.033[-0.006, 0.076]$
DrawerOpen–DDPG	SABER (Ours)	0.754 ± 0.044	0.987 ± 0.018	1.000 ± 0.000	5/5 (0.500M)	23.3	$--$
	Replay-Action						
	Query	0.318 ± 0.437	0.399 ± 0.546	0.400 ± 0.548	2/5 (0.405M)	25.0	$+0.436[0.121, 0.729]$
	Shuffled-Policy						
	Query	0.648 ± 0.246	0.980 ± 0.026	1.000 ± 0.000	5/5 (0.630M)	17.1	$+0.105[-0.080, 0.335]$
	Random-Support	0.706 ± 0.122	0.997 ± 0.003	1.000 ± 0.000	5/5 (0.510M)	22.6	$+0.047[-0.042, 0.136]$
	Context-Eligible						
	Count-Matched	0.605 ± 0.345	0.799 ± 0.446	0.800 ± 0.447	4/5 (0.515M)	27.0	$+0.149[-0.042, 0.442]$
DrawerClose–DDPG	SABER (Ours)	0.324 ± 0.082	0.277 ± 0.100	0.280 ± 0.251	5/5 (0.020M)	24.0	$--$
	Replay-Action						
	Query	0.276 ± 0.016	0.226 ± 0.048	0.290 ± 0.192	5/5 (0.050M)	28.4	$+0.049[-0.006, 0.128]$
	Shuffled-Policy						
	Query	0.292 ± 0.056	0.264 ± 0.052	0.320 ± 0.422	5/5 (0.060M)	27.4	$+0.033[-0.063, 0.119]$
	Random-Support	0.277 ± 0.050	0.326 ± 0.134	0.240 ± 0.429	5/5 (0.040M)	23.8	$+0.048[-0.004, 0.115]$
	Context-Eligible						
	Count-Matched	0.295 ± 0.063	0.325 ± 0.111	0.330 ± 0.460	5/5 (0.070M)	27.8	$+0.030[-0.033, 0.092]$

Table 11: DDPG mechanism controls over paired seeds 1–5. Values are mean $\pm$ sample SD on each task's exact grid. Hit90 gives reaching seeds and their reached-seed median step. The final column reports AUC differences between SABER (Ours) and each control with frozen paired-bootstrap 95% CIs; positive values favor SABER (Ours). FPP uses 10,000 seeded resamples and Drawer controls enumerate all 5^5 paired resamples, matching the validated source artifacts. Steps/s is descriptive rather than hardware-normalized.

Results. SABER Main has higher observed mean full-span AUC than every control on FPP, DrawerOpen, and DrawerClose. The Main-minus-control interval excludes zero for FPP Random-Support and DrawerOpen Replay-Action Query; the other ten intervals include zero. Late metrics are less uniform: for example, Random-Support and Context-Eligible Count-Matched have higher mean FQ-AUC than Main on DrawerClose.

Interpretation. The controls show that query identity and weight placement can affect learning and that SABER's AUC ordering is not explained solely by the number of high weights. Most five-seed intervals remain inconclusive, however, and the absolute metrics

show that a full-span AUC direction need not extend to every late or final-checkpoint measure.

4.2 Allocation Signal

Purpose. This control asks whether SABER benefits merely from assigning unequal critic coefficients, or whether current-policy local support provides a different allocation signal from TD error. Both methods retain uniform replay and change only normalized critic-loss coefficients.

Cohort	Method/Variant	AUC	FQ-AUC	Final	Hit90	Steps/s	ΔAUC
FPP–DDPG	SABER (Ours)	0.609 ± 0.038	0.961 ± 0.014	0.960 ± 0.042	5/5 (0.540M)	41.7	$--$
	TD-error weighting	0.568 ± 0.069	0.910 ± 0.119	0.930 ± 0.104	5/5 (0.630M)	61.1	$+0.041\ [-0.018, 0.123]$
DrawerOpen–DDPG	SABER (Ours)	0.754 ± 0.044	0.987 ± 0.018	1.000 ± 0.000	5/5 (0.500M)	23.3	$--$
	TD-error weighting	0.715 ± 0.090	0.988 ± 0.011	0.800 ± 0.447	5/5 (0.610M)	39.0	$+0.038\ [-0.015, 0.091]$
DrawerClose–DDPG	SABER (Ours)	0.324 ± 0.082	0.277 ± 0.100	0.280 ± 0.251	5/5 (0.020M)	24.0	$--$
	TD-error weighting	0.313 ± 0.098	0.351 ± 0.218	0.400 ± 0.166	5/5 (0.130M)	38.9	$+0.011\ [-0.079, 0.074]$
FPP–SAC	SABER (Ours)	0.583 ± 0.030	0.986 ± 0.011	0.990 ± 0.022	5/5 (0.750M)	29.1	$--$
	TD-error weighting	0.544 ± 0.068	0.901 ± 0.167	0.990 ± 0.022	5/5 (0.800M)	38.2	$+0.040\ [-0.016, 0.095]$

Table 12: Validated TD-error critic-loss weighting controls over paired seeds 1–5. Replay remains uniform, and only critic-loss coefficients change. Values are mean ± sample SD. The final column reports AUC differences between SABER (Ours) and the control; 95% paired-bootstrap CIs are shown, and positive values favor SABER (Ours). For SAC, the priority signal is $\min(|\delta_{i1}|, |\delta_{i2}|)$, and the resulting normalized coefficient is applied to both critic losses. Steps/s is the descriptive seed mean defined in Section 2.3.

Results. SABER has higher observed mean AUC in all four validated cohorts, but every paired 95% interval includes zero. Late metrics are mixed, including higher FQ-AUC for TD-error weighting on DrawerClose.

Interpretation. The common mean direction distinguishes SABER from this specific TD-error allocation control, but the five-seed intervals do not establish a conclusive per-cohort advantage. TD3 is omitted because its stored control does not support the intended matched-signal comparison.

4.3 Action-Bin Resolution

Purpose. This sensitivity tests whether the Main action discretization $K = 5$ is robust to coarser and finer bins and records how bin resolution changes the frequency of support activation.

Cohort	Method/Variant	AUC	FQ-AUC	Final	Hit90	Steps/s	Support+	ΔAUC
FPP–TD3	$K = 3$	0.353 ± 0.048	0.603 ± 0.121	0.750 ± 0.265	2/5 (0.945M)	33.9	0.396 ± 0.012	$+0.089\ [0.070, 0.109]$
	$K = 5$ (Main)	0.442 ± 0.035	0.804 ± 0.103	0.970 ± 0.045	5/5 (0.840M)	41.2	0.219 ± 0.009	$--$
	$K = 7$	0.361 ± 0.047	0.616 ± 0.151	0.690 ± 0.263	2/5 (0.890M)	36.1	0.148 ± 0.010	$+0.081\ [0.067, 0.093]$

Table 13: FPP TD3 action-bin sensitivity over paired seeds 1–5. Values are mean ± sample SD. Support+ is the support-positive rate. The final column reports Main-minus-variant paired AUC differences with 10,000-resample percentile-bootstrap 95% CIs; positive values favor Main $K = 5$.

Results. Main $K = 5$ has higher mean AUC than both $K = 3$ and $K = 7$, with both Main-minus-variant 95% intervals excluding zero. The support-positive rate decreases as K increases.

Interpretation. The evaluated $K = 5$ setting is favored over both adjacent resolutions in this cohort. Because K simultaneously changes action-bin geometry and activation density, the experiment does not identify either factor alone or establish $K = 5$ as universally optimal.

4.4 Actor and Critic Weight Scope

Purpose. This ablation tests whether the support coefficient should modify the critic, the actor, or both. All variants retain the support query, support hyperparameters, and minibatch normalization. Critic-Only weights Bellman losses; Actor-Only weights per-sample actor terms; Actor+Critic weights both.

Results. Critic-Only has the highest observed mean AUC in each of the six completed Main-versus-scope comparisons. Main-minus-variant differences range from $+0.017$ to $+0.141$, but every 95% interval includes zero. DrawerOpen Actor-Only also has substantial seed dispersion (0.612 ± 0.343). On FPP, Actor+Critic obtains 0.582 ± 0.030 AUC versus 0.609 ± 0.038 for Critic-Only, a Main-minus-variant difference of $+0.027$ with 95% CI $[-0.020, 0.076]$.

Interpretation. The available results are consistent with using critic-only weighting as the conservative main design, while providing no decisive evidence that actor weighting is intrinsically harmful. Each scope changes the subsequent training trajectory, so realized support masks need not remain identical.

Cohort	Method/Variant	AUC	FQ-AUC	Final	Hit90	Steps/s	ΔAUC (Main–variant)
FPP–DDPG	Critic-Only (Main)	0.609 ± 0.038	0.961 ± 0.014	0.960 ± 0.042	5/5 (0.540M)	41.7	$--$
	Actor-Only	0.589 ± 0.032	0.952 ± 0.016	0.960 ± 0.022	5/5 (0.600M)	15.8	$+0.020[-0.024, 0.063]$
	Actor+Critic	0.582 ± 0.030	0.968 ± 0.007	0.980 ± 0.027	5/5 (0.550M)	16.9	$+0.027[-0.020, 0.076]$
DrawerOpen–DDPG	Critic-Only (Main)	0.754 ± 0.044	0.987 ± 0.018	1.000 ± 0.000	5/5 (0.500M)	23.3	$--$
	Actor-Only	0.612 ± 0.343	0.760 ± 0.433	0.800 ± 0.447	4/5 (0.470M)	18.6	$+0.141[-0.051, 0.478]$
	Actor+Critic	0.728 ± 0.084	0.992 ± 0.008	0.990 ± 0.022	5/5 (0.540M)	18.4	$+0.026[-0.048, 0.091]$
DrawerClose–DDPG	Critic-Only (Main)	0.324 ± 0.082	0.277 ± 0.100	0.280 ± 0.251	5/5 (0.020M)	24.0	$--$
	Actor-Only	0.307 ± 0.039	0.299 ± 0.061	0.280 ± 0.299	5/5 (0.040M)	24.0	$+0.017[-0.026, 0.078]$
	Actor+Critic	0.298 ± 0.071	0.241 ± 0.119	0.440 ± 0.370	5/5 (0.050M)	23.7	$+0.026[-0.043, 0.091]$

Table 14: DDPG actor-scope ablations over paired seeds 1–5. Values are mean ± sample standard deviation. Hit90 reports the number of reaching seeds and the reached-seed median step. Steps/s is the descriptive seed mean defined in Section 2.3. The final column gives Main-minus-variant paired AUC differences with 95% bootstrap confidence intervals.

4.5 No-HER Replay References

Purpose. AER is included because it also exploits similarity between the agent's current interaction context and stored replay states, but uses that signal to change minibatch membership. SABER instead preserves the sampled HER minibatch and changes only critic-loss allocation. The comparison separates uniform experience replay (ER), uniform replay with AER's actor/critic learning-rate schedule (Annealing ER), and Attentive Experience Replay (AER). AER ranks an enlarged uniform candidate set by cosine similarity to the current online state and trains on the 256 most similar transitions. The three arms therefore test attentive selection beyond its shared schedule and whether replay selection alone can solve these sparse tasks.

Cohort	Method/Variant	AUC	FQ-AUC	Final	Hit90	Steps/s
FPP–DDPG	ER	0.148 ± 0.039	0.354 ± 0.124	0.460 ± 0.188	0/5	68.4
	Annealing ER	0.129 ± 0.111	0.259 ± 0.251	0.340 ± 0.363	1/5 (0.960M)	68.0
	AER	0.044 ± 0.002	0.045 ± 0.004	0.000 ± 0.000	0/5	67.0
FPP–TD3	ER	0.039 ± 0.002	0.043 ± 0.002	0.000 ± 0.000	0/5	21.0
	Annealing ER	0.039 ± 0.002	0.043 ± 0.002	0.000 ± 0.000	0/5	19.6
	AER	0.039 ± 0.002	0.043 ± 0.002	0.000 ± 0.000	0/5	26.2
FPP–SAC	ER	0.064 ± 0.042	0.114 ± 0.135	0.130 ± 0.199	0/5	39.4
	Annealing ER	0.041 ± 0.002	0.047 ± 0.008	0.000 ± 0.000	0/5	39.5
	AER	0.040 ± 0.003	0.044 ± 0.002	0.000 ± 0.000	0/5	39.3
DrawerOpen–DDPG	ER	0.579 ± 0.342	0.799 ± 0.446	0.800 ± 0.447	4/5 (0.525M)	58.9
	Annealing ER	0.111 ± 0.248	0.200 ± 0.447	0.200 ± 0.447	1/5 (0.910M)	58.8
	AER	0.000 ± 0.000	0.000 ± 0.000	0.000 ± 0.000	0/5	57.4
DrawerOpen–TD3	ER	0.089 ± 0.122	0.338 ± 0.463	0.400 ± 0.548	2/5 (1.530M)	59.5
	Annealing ER	0.000 ± 0.000	0.000 ± 0.000	0.000 ± 0.000	0/5	59.6
	AER	0.000 ± 0.000	0.000 ± 0.000	0.000 ± 0.000	0/5	58.4
DrawerClose–DDPG	ER	0.150 ± 0.054	0.150 ± 0.140	0.000 ± 0.000	5/5 (0.280M)	58.7
	Annealing ER	0.199 ± 0.122	0.249 ± 0.269	0.330 ± 0.391	5/5 (0.380M)	58.8
	AER	0.194 ± 0.067	0.197 ± 0.246	0.200 ± 0.447	5/5 (0.160M)	57.5
DrawerClose–TD3	ER	0.251 ± 0.088	0.203 ± 0.100	0.220 ± 0.286	5/5 (0.180M)	48.9
	Annealing ER	0.176 ± 0.137	0.063 ± 0.081	0.020 ± 0.045	5/5 (0.070M)	48.9
	AER	0.169 ± 0.110	0.158 ± 0.184	0.400 ± 0.548	5/5 (0.070M)	48.3

Table 15: No-HER replay references over seeds 1–5. FPP values use the exact 10k–1M grid, and Drawer values use 10k–2M. Values are mean ± sample SD. These runs omit hindsight relabeling and are context references rather than matched post-HER mechanism controls. Steps/s is the descriptive seed mean defined in Section 2.3.

Results. Without HER, FPP AER/Annealing ER/ER obtain mean AUCs of $0.044/0.129/0.148$ with DDPG, $0.039/0.039/0.039$ with TD3, and $0.040/0.041/0.064$ with SAC. On DrawerOpen, the corresponding values are $0.000/0.111/0.579$ with DDPG and $0.000/0.000/0.089$ with TD3; on DrawerClose they are $0.194/0.199/0.150$ and $0.169/0.176/0.251$. AER has no higher observed mean AUC than Annealing ER in these seven transferred cohorts.

Interpretation. Across these no-HER transfers, state-similarity replay does not improve observed mean AUC over its schedule-matched uniform-replay control. The three-arm design isolates attentive selection beyond AER's annealed schedule. Without a fixed-learning-rate AER arm, however, it does not identify a schedule-by-selection interaction. This is not a general replication or rejection of AER; it isolates transferred AER components under the present tasks and backbones.

4.6 Update-Budget and Architecture References

Purpose. The FPP SAC High-RR comparison changes HER's update-to-data ratio from one to four while retaining its two-critic SAC architecture. REDQ-HER is a broader architecture-and-compute reference evaluated on FPP, DrawerOpen, and DrawerClose: it

uses UTD 4, ten critics, a random two-critic target subset, and target-Q bounding. REDQ-HER TQB clips the sampled target-critic backup to the sparse-reward range $[-50, 0]$ before forming the Bellman target.

Cohort	Method/Variant	AUC	FQ-AUC	Final	Hit90	Steps/s
FPP–SAC	HER UTD 1; 2 critics	0.471 ± 0.079	0.735 ± 0.247	0.790 ± 0.288	3/5 (0.800M)	38.9
	HER high-RR UTD 4; 2 critics	0.768 ± 0.097	0.963 ± 0.021	0.960 ± 0.042	5/5 (0.450M)	5.9

Table 16: FPP SAC update-ratio reference over seeds 1–5 on the exact shared 50k–1M grid. High-RR changes only the number of updates per environment step from one to four within HER. It was evaluated only on FPP SAC and is not a task-wide or wall-clock-matched control. Steps/s is descriptive.

Task	Method/Variant	AUC	FQ-AUC	Final	Hit90	Steps/s
FPP	HER (SAC) UTD 1; 2 critics	0.471 ± 0.079	0.735 ± 0.247	0.790 ± 0.288	3/5 (0.800M)	38.9
	SABER (Ours) SAC; UTD 1; 2 critics	0.583 ± 0.030	0.986 ± 0.011	0.990 ± 0.022	5/5 (0.750M)	29.1
	REDQ-HER TQB UTD 4; 10 critics/2 target	0.867 ± 0.052	0.993 ± 0.008	1.000 ± 0.000	5/5 (0.300M)	3.1
DrawerOpen	HER (DDPG) UTD 1; 1 critic	0.207 ± 0.287	0.393 ± 0.538	0.390 ± 0.534	2/5 (0.960M)	41.1
	SABER (Ours) DDPG; UTD 1; 1 critic	0.754 ± 0.044	0.987 ± 0.018	1.000 ± 0.000	5/5 (0.500M)	23.3
	REDQ-HER TQB UTD 4; 10 critics/2 target	0.672 ± 0.314	0.952 ± 0.106	1.000 ± 0.000	5/5 (0.370M)	5.0
DrawerClose	HER (DDPG) UTD 1; 1 critic	0.251 ± 0.030	0.250 ± 0.093	0.160 ± 0.182	5/5 (0.070M)	41.2
	SABER (Ours) DDPG; UTD 1; 1 critic	0.324 ± 0.082	0.277 ± 0.100	0.280 ± 0.251	5/5 (0.020M)	24.0
	REDQ-HER TQB UTD 4; 10 critics/2 target	0.188 ± 0.041	0.098 ± 0.022	0.100 ± 0.117	5/5 (0.020M)	5.8

Table 17: REDQ architecture-and-compute references over seeds 1–5. FPP uses the exact shared 50k–1M grid; Drawer tasks use 10k–2M. REDQ-HER uses UTD 4, ten critics, a random two-critic target subset, and target-Q bounding, whereas HER and SABER rows use UTD 1. Values are compared only within task. Steps/s is descriptive.

Results. On FPP SAC, increasing HER from UTD 1 to UTD 4 raises observed mean AUC from 0.471 to 0.768. REDQ-HER records AUC 0.867 on FPP, 0.672 on DrawerOpen, and 0.188 on DrawerClose. The corresponding SABER values are 0.583, 0.754, and 0.324. DrawerOpen REDQ-HER reaches Hit90 in all seeds at a median 0.370M steps and has FQ-AUC 0.952, whereas DrawerClose REDQ-HER reaches Hit90 at 0.020M but has FQ-AUC 0.098.

Interpretation. A larger update budget and critic ensemble can be stronger on FPP SAC, but REDQ is not uniformly stronger across tasks. High-RR is an FPP-only update-ratio reference, while REDQ changes UTD, algorithm, architecture, target construction, and entropy optimization. These results therefore provide scaling context rather than matched one-factor tests of SABER.

5 Support-Signal Diagnostic Details

5.1 Instrumentation and Aggregation

Purpose. The diagnostics test whether SABER's support rule activates in practice, whether it is redundant with TD-error ranking, and whether the resulting weights alter immediate critic fitting in the intended direction.

Protocol. Diagnostic logging introduces no gradient term and does not change replay sampling, objectives, or parameter-update order. FPP logs one full minibatch every 10k environment steps for DDPG, TD3, and SAC seeds 1–5: 100 batches per run, 500 per backbone, and 1,500 total. Drawer diagnostics use a 200-step cadence from 5k through 2M, producing 9,976 persisted snapshots per seed. Snapshot quantities are aggregated within seed before cohort statistics are computed.

For each persisted minibatch, the diagnostic stores the pre-update absolute Bellman residual, support membership, and the residual after one critic update. The fixed-target residual is

$$\Delta|\delta_i| = \left|Q_\phi^{\mathrm{pre}}(x_i, a_i^r) - y_i^{\mathrm{pre}}\right| - \left|Q_\phi^{\mathrm{post}}(x_i, a_i^r) - y_i^{\mathrm{pre}}\right|.$$

Thus the target and minibatch are held fixed while the critic parameters change. Live-target quantities, where available, are retained only for audit and are not mixed with the fixed-target statistic.

Interpretation boundary. These measurements audit activation and one-update optimization behavior on persisted minibatches. They do not by themselves identify the independent cause of a long-horizon return difference.

5.2 Cohort-Level Results

Purpose. The cohort summary jointly measures activation frequency, association with pre-update error, and support-conditioned residual reduction under a common fixed-target definition.

Cohort	Seeds	Support+ rate	Pearson r	Top-10% enrich.	Pre-update $\lvert\delta\rvert$ $(+/-)$	One-step $\Delta\lvert\delta\rvert$ $(+/-)$
FPP–DDPG	1–5	0.367 ± 0.011	0.116	$1.409\times$	$1.42\times$	$2.39\times$
FPP–TD3	1–5	0.219 ± 0.009	0.128	$1.670\times$	$1.62\times$	$3.30\times$
FPP–SAC	1–5	0.197 ± 0.013	0.143	$1.828\times$	$1.74\times$	$3.94\times$
DrawerOpen–DDPG	1–5	0.417 ± 0.021	0.084	$1.379\times$	$1.16\times$	$1.79\times$
DrawerOpen–DDPG	6–10 extension	0.475 ± 0.094	0.095	$1.440\times$	$1.13\times$	$1.91\times$
DrawerOpen–DDPG	1–10 pooled	0.446 ± 0.071	0.090	$1.409\times$	$1.15\times$	$1.83\times$
DrawerClose–DDPG	1–5	0.298 ± 0.018	0.104	$1.534\times$	$1.42\times$	$2.94\times$
DrawerClose–DDPG	6–10 extension	0.299 ± 0.007	0.118	$1.602\times$	$1.48\times$	$4.23\times$
DrawerClose–DDPG	1–10 pooled	0.298 ± 0.013	0.111	$1.568\times$	$1.45\times$	$3.48\times$

Table 18: Support-signal diagnostics. Statistics are first aggregated within seed, after which seeds are independent units. Support rates are mean $\pm$ sample SD. The last two columns divide support-positive by support-negative cohort means. One-step $\Delta\lvert\delta\rvert$ evaluates the same minibatch after one critic step while retaining the pre-update Bellman target. Seeds 1–5 are the primary diagnostic cohorts, seeds 6–10 are separate extensions, and pooled ten-seed rows are descriptive.

Results. Primary-cohort support-positive rates range from 0.197 to 0.417, so the indicator is neither nearly absent nor nearly constant. Primary Pearson correlations are modest (0.084–0.143), while exact top-decile enrichment ranges from $1.379\times$ to $1.828\times$. The support-positive/support-negative one-step residual-reduction ratio ranges from $1.79\times$ to $3.94\times$ in the primary cohorts. Both Drawer extensions preserve enrichment above one and a larger reduction for support-positive samples. The support-positive mean reduction is larger in all 25 primary backbone–seed runs.

Interpretation. Support-positive samples are enriched among high-error samples, but the weak linear correlations show that support does not reduce to a TD-error ranking. The one-step statistic verifies that the normalized coefficients redistribute immediate critic fitting as intended; it is not a standalone explanation of long-term learning performance.

5.3 Phase-Conditioned Allocation

Purpose. The phase analysis asks where support activation occurs during Drawer progression and whether it merely follows the most frequent phase.

Phase definitions. Let d_h be the Euclidean hand–handle distance and d_g the handle–relabeled-goal distance. Open/Closed denotes $d_g \leq 0.05$. Opening/Closing denotes $d_g > 0.05$, $d_h \leq 0.08$, and $d_g \leq 0.12$. Contact denotes $d_h \leq 0.08$ and $d_g > 0.12$; Approach contains the remaining samples. These mutually exclusive rules reproduce the implementation's terminal-to-approach assignment precedence.

Cohort	Phase	Sample fraction	Support+ rate	Seeds
DrawerOpen–DDPG	Approach	0.174 ± 0.018	0.745 ± 0.022	1–5
	Contact	0.049 ± 0.003	0.698 ± 0.056	
	Opening	0.046 ± 0.005	0.636 ± 0.053	
	Open	0.730 ± 0.018	0.306 ± 0.027	
DrawerOpen–DDPG	Approach	0.195 ± 0.011	0.754 ± 0.030	6–10 ext.
	Contact	0.027 ± 0.024	0.515 ± 0.181	
	Opening	0.023 ± 0.023	0.440 ± 0.263	
	Open	0.755 ± 0.039	0.387 ± 0.127	
DrawerClose–DDPG	Approach	0.218 ± 0.002	0.549 ± 0.032	1–5
	Contact	0.016 ± 0.003	0.710 ± 0.026	
	Closing	0.019 ± 0.004	0.425 ± 0.034	
	Closed	0.747 ± 0.004	0.212 ± 0.017	
DrawerClose–DDPG	Approach	0.222 ± 0.003	0.569 ± 0.004	6–10 ext.
	Contact	0.018 ± 0.003	0.727 ± 0.016	
	Closing	0.017 ± 0.002	0.438 ± 0.028	
	Closed	0.743 ± 0.007	0.204 ± 0.010	

Table 19: Drawer phase-conditioned allocation. Phases are defined from the relabeled training goal. Values are seed means $\pm$ sample SD; support is sample-weighted within each seed. Seeds 6–10 are separate extensions. Pooled ten-seed and seed-level values are included in the artifacts.

Results. In both Drawer tasks and in both primary and extension cohorts, approach and contact have higher support-positive rates than the dominant terminal phase, even though the terminal phase accounts for roughly three quarters of logged samples. Table 31 reports the exact phase counts and support-positive rate for each primary seed; the accompanying artifact also contains exact support-positive counts and seeds 6–10 rows.

Interpretation. Activation therefore does not simply track phase frequency. The task-specific phase labels localize the signal but do not constitute an independent causal test of long-horizon performance.

6 Runtime and Resource Measurements

6.1 Execution-Environment Audit

Purpose. The audit records the execution boundary needed to assess paired fairness and to distinguish software-controlled comparisons from hardware-specific throughput observations.

Host	System	Compute hardware	OS, kernel, and driver
A	MSI GB10 system	20-core ARM (10 Cortex-X925 + 10 Cortex-A725), 121 GiB unified memory, NVIDIA GB10	Ubuntu 24.04.4; 6.17.0-1014-nvidia; driver 580.142
B	GIGABYTE AI TOP ATOM	20-core ARM (10 Cortex-X925 + 10 Cortex-A725), 121 GiB unified memory, NVIDIA GB10	Ubuntu 24.04.4; 6.17.0-1026-nvidia; driver 580.159.03
C	GIGABYTE AI TOP ATOM	20-core ARM (10 Cortex-X925 + 10 Cortex-A725), 121 GiB unified memory, NVIDIA GB10	Ubuntu 24.04.4; 6.17.0-1026-nvidia; driver 580.159.03
D	GB10 system	20-core ARM (10 Cortex-X925 + 10 Cortex-A725), 121 GiB unified memory, NVIDIA GB10	Ubuntu 24.04.3; 6.11.0-1016-nvidia; driver 580.95.05

Table 20: Hardware inventory for the four physically distinct execution hosts. All systems use CUDA-addressable unified memory rather than dedicated VRAM. Hosts B and C are separate machines with the same model and system configuration. Hostnames, serial numbers, and other identifying metadata are omitted.

Results. The common stack was validated for reproduction. Within each paired task–backbone cohort, all compared methods and paired seeds were executed on one physical host under a matched environment; no paired cohort was split across machines. The validated reproduction stack is Python 3.12.3, PyTorch 2.12.1+cu130, CUDA 13.0, cuDNN 9.20.0, Gymnasium 1.3.0, Gymnasium-Robotics 1.4.2, MuJoCo 3.3.0, Meta-World 3.1.1, NumPy 2.3.5, and SciPy 1.18.0. Sanitized provenance is recorded in the accompanying execution-host mapping.

Interpretation. The paired performance differences are not created by moving HER and SABER across machines within a cohort. Hardware still differs across cohorts, so historical throughput is descriptive and is not used for cross-host ranking.

6.2 Dedicated Runtime Profile

Purpose. The dedicated profile quantifies the current implementation overhead under a sequential same-hardware comparison and identifies which pipeline component dominates that overhead. It runs HER and SABER for FPP TD3 seed 1 over the 20k–100k interval.

Profile item	Recorded value
Execution protocol	Sequential FPP TD3 HER and SABER, seed 1, 20k–100k
GPU	NVIDIA GB10, compute capability 12.1, 121.7 GiB CUDA-addressable memory
CPU/platform	20 logical CPUs, AArch64 Linux 6.17.0-1026-nvidia, glibc 2.39
Software	Python 3.12.3, PyTorch 2.12.1+cu130, CUDA 13.0, cuDNN 9.20.0
Comparison boundary	The dedicated profile is not extrapolated to historical primary runs
Memory boundary	Peak process and accelerator memory were not measured

Table 21: Recorded infrastructure for the dedicated same-hardware runtime profile. CUDA-addressable memory is reported because the GB10 uses unified memory. These identifiers characterize the dedicated runtime profile; historical steps/s values in other tables are descriptive cohort measurements.

Component	HER ms/step	SABER (Ours) ms/step	Difference	SABER (Ours) share
Interaction	1.000	1.071	+0.070	4.4%
Replay + HER	1.925	2.651	+0.726	11.0%
Batch preparation	0.096	0.108	+0.012	0.4%
Support and weighting	0.000	15.028	+15.028	62.3%
Critic update	2.945	2.832	−0.113	11.7%
Actor + target update	1.384	1.292	−0.091	5.4%
Evaluation/logging amortized	0.080	0.085	+0.005	0.4%
Other loop overhead	0.633	1.066	+0.434	4.4%
Total training loop	8.063	24.133	+16.070	100.0%

Table 22: Hardware-specific component times for the FPP TD3 seed-1 implementation profile over 20k–100k steps. Other loop overhead is the difference between total loop time and the explicitly instrumented components.

Results. HER and SABER achieve 124.0 and 41.4 environment steps/s, corresponding to 8.063 and 24.133 ms per training step. Support and weighting account for 15.028 ms/step, or 62.3% of SABER's measured loop time, and explain most of the $+16.070$ ms/step difference.

Interpretation. The profile attributes the dominant measured cost to the current support retrieval implementation, motivating faster retrieval. It is one hardware-specific, early-training profile rather than an asymptotic or end-to-end learning-efficiency result. Historical steps/s values were not collected under this sequential protocol, and peak memory was not measured; neither quantity is inferred.

7 Artifact and Provenance Index

Purpose. This index connects each reported experiment to a validation status and repository-relative artifact location, so completed evidence is distinguishable from secondary references and extensions.

Content	Artifact key	Status
Primary seed metrics and curves	`primary_seed_results`	Complete
DDPG mechanism controls	`mechanism_controls_ddpg`	Complete
TD-error weighting controls	`td_error_weighting_controls`	Complete
Drawer phase counts and seed rows	`phase_seed_results`	Complete
Action-bin sensitivity	`action_bin_sensitivity`	Complete
DDPG actor-scope analysis	`actor_scope_ddpg`	Complete
Derived Technical Supplement summaries	`technical_supplement`	Complete
FPP DDPG Actor+Critic	`fpp_ddpg_actor_critic`	Complete
FPP diagnostics	`fpp_diagnostic`	Complete
DrawerClose diagnostics	`drawerclose_diagnostic`	Complete
DrawerOpen fixed-target diagnostics	`draweropen_fixed_target`	Complete
FPP TD3 runtime profile	`fpp_td3_runtime`	Complete
Execution-environment audit	`execution_environment_audit`	Complete
FPP TD3 ten-seed confirmation	`fpp_td3_n10`	Complete
FPP TD3 inclusive-future sensitivity	`fpp_td3_inclusive`	Complete
FPP TD3 inclusive-future extension	`fpp_td3_inclusive_extension`	Complete
High-RR and task-wide REDQ references	`update_budget_references`	Complete
FPP DDPG/TD3/SAC no-HER AER	`fpp_aer_noher`	Complete
DrawerOpen DDPG no-HER AER	`draweropen_ddpg_aer_noher`	Complete
DrawerOpen TD3 no-HER AER	`draweropen_td3_aer_noher`	Complete
DrawerClose DDPG no-HER AER	`drawerclose_ddpg_aer_noher`	Complete
DrawerClose TD3 no-HER AER	`drawerclose_td3_aer_noher`	Complete

Table 23: Artifact index. Keys resolve to repository-relative package paths in `artifact_index.csv`. Canonical artifacts include manifests that bind source files by repository-relative path and SHA256.

Seed mapping. For paired seed s, the environment, PyTorch, NumPy, and action-noise streams use s; the support-weight stream uses $20000 + s$, and evaluation uses $10000 + s$. Training and evaluation resets advance by deterministic episode- and checkpoint-indexed offsets. All methods in a paired cohort use this mapping.

Interpretation boundary. Generated analysis directories contain compact CSV summaries, a repository-relative source manifest, and a self-excluding artifact manifest. Canonical experiment artifacts retain configuration, environment snapshot, source provenance, and validation records where available. Raw result files are referenced rather than duplicated in the derived summaries. An indexed artifact establishes traceability to the reported result; it does not convert a secondary reference into a matched causal comparison.

A Primary Seed-Level Results

Purpose. The seed-level appendix exposes every observation underlying the primary aggregate table, allowing readers to inspect paired directions and between-seed dispersion directly.

Results. SABER has higher observed mean AUC than matched HER in all seven primary cohorts, and four paired 95% intervals exclude zero. The individual rows show that this aggregate statement coexists with negative or near-zero seed pairs and especially large dispersion on the Drawer TD3 cohorts. AUC and final-quarter AUC use each cohort's exact common grid.

Interpretation. These rows are the observations used in the primary analysis, not an additional independent experiment. They make the direction and uncertainty of each paired cohort auditable without changing the seed as the unit of statistical analysis.

Method	Seed	AUC	FQ-AUC	Final	Hit90
HER	1	0.64015	0.95600	0.900	0.51M
	2	0.53737	0.93400	0.950	0.60M
	3	0.57879	0.96400	0.950	0.61M
	4	0.32525	0.73100	0.900	0.92M
	5	0.61237	0.96700	1.000	0.57M
SABER (Ours)	1	0.65606	0.93900	0.950	0.48M
	2	0.61515	0.97200	0.950	0.54M
	3	0.56490	0.95900	1.000	0.63M
	4	0.63182	0.97600	1.000	0.48M
	5	0.57753	0.96000	0.900	0.61M
HGR	1	0.44167	0.76500	1.000	0.87M
	2	0.07652	0.06500	0.000	–
	3	0.37449	0.48200	0.500	–
	4	0.41768	0.58700	0.700	0.99M
	5	0.38056	0.50600	0.500	–
PER	1	0.48409	0.91900	1.000	0.77M
	2	0.52045	0.95300	1.000	0.73M
	3	0.60429	0.94600	0.900	0.55M
	4	0.64343	0.96400	1.000	0.46M
	5	0.04924	0.04600	0.000	–

Table 24: Seed-level FPP DDPG results on the exact shared grid (no smoothing or interpolation).

Method	Seed	AUC	FQ-AUC	Final	Hit90
HER	1	0.34646	0.52300	0.550	–
	2	0.37273	0.63500	0.950	1.00M
	3	0.39419	0.66200	1.000	0.98M
	4	0.41086	0.68600	0.950	0.97M
	5	0.33384	0.53000	0.750	–
SABER (Ours)	1	0.43005	0.84600	1.000	0.84M
	2	0.45682	0.85600	1.000	0.86M
	3	0.49596	0.91400	0.950	0.63M
	4	0.40657	0.65200	0.900	0.63M
	5	0.42247	0.75200	1.000	0.91M
HGR	1	0.34520	0.51500	0.500	–
	2	0.39621	0.59300	0.800	–
	3	0.40758	0.58100	0.850	–
	4	0.32652	0.48900	0.450	0.63M
	5	0.36111	0.49300	0.450	–
PER	1	0.34545	0.51500	0.550	–
	2	0.40859	0.65300	0.950	1.00M
	3	0.39419	0.62800	0.800	–
	4	0.36919	0.52600	0.500	–
	5	0.32702	0.48800	0.500	–

Table 25: Seed-level FPP TD3 results on the exact shared grid (no smoothing or interpolation).

Method	Seed	AUC	FQ-AUC	Final	Hit90
HER	1	0.55921	0.98500	1.000	0.80M
	2	0.46974	0.76000	1.000	0.95M
	3	0.40658	0.50000	0.500	–
	4	0.54079	0.96500	1.000	0.80M
	5	0.37895	0.46500	0.450	–
SABER (Ours)	1	0.63684	0.99500	0.950	0.65M
	2	0.56711	0.98000	1.000	0.80M
	3	0.57368	0.98000	1.000	0.75M
	4	0.57500	1.00000	1.000	0.75M
	5	0.56447	0.97500	1.000	0.80M
HGR	1	0.45132	0.54500	0.800	–
	2	0.59605	0.98000	1.000	0.70M
	3	0.50658	0.80000	1.000	0.90M
	4	0.45000	0.50500	0.500	–
	5	0.41447	0.49000	0.500	–
PER	1	0.75526	0.97000	1.000	0.45M
	2	0.63553	0.98500	1.000	0.55M
	3	0.70658	0.99000	1.000	0.55M
	4	0.69079	1.00000	1.000	0.55M
	5	0.66053	0.98500	0.950	0.60M

Table 26: Seed-level FPP SAC results on the exact shared grid (no smoothing or interpolation).

Method	Seed	AUC	FQ-AUC	Final	Hit90
HER	1	0.46030	0.97000	1.000	1.09M
	2	0.00000	0.00000	0.000	–
	3	0.00000	0.00000	0.000	–
	4	0.00000	0.00000	0.000	–
	5	0.57626	0.99350	0.950	0.83M
SABER (Ours)	1	0.75729	1.00000	1.000	0.51M
	2	0.78693	0.97700	1.000	0.42M
	3	0.70503	1.00000	1.000	0.58M
	4	0.71307	0.96000	1.000	0.50M
	5	0.80603	1.00000	1.000	0.40M
HGR	1	0.79975	0.99500	0.500	0.41M
	2	0.70452	0.99000	1.000	0.53M
	3	0.69221	0.99300	1.000	0.61M
	4	0.79497	0.99800	1.000	0.43M
	5	0.44950	0.93450	1.000	1.06M
PER	1	0.85980	1.00000	1.000	0.33M
	2	0.87739	0.99800	1.000	0.27M
	3	0.81407	0.96900	1.000	0.33M
	4	0.80917	0.95150	0.950	0.39M
	5	0.76508	0.99000	1.000	0.41M

Table 27: Seed-level DrawerOpen DDPG results on the exact shared grid (no smoothing or interpolation).

Method	Seed	AUC	FQ-AUC	Final	Hit90
HER	1	0.63229	0.99950	0.950	0.74M
	2	0.00000	0.00000	0.000	–
	3	0.00000	0.00000	0.000	–
	4	0.00025	0.00000	0.000	–
	5	0.00000	0.00000	0.000	–
SABER (Ours)	1	0.48656	0.99650	0.950	1.07M
	2	0.00000	0.00000	0.000	–
	3	0.00050	0.00000	0.000	–
	4	0.68995	0.99700	1.000	0.56M
	5	0.63216	0.99700	1.000	0.78M
HGR	1	0.00000	0.00000	0.000	–
	2	0.69246	0.99200	1.000	0.52M
	3	0.53191	0.99700	0.900	0.93M
	4	0.00000	0.00000	0.000	–
	5	0.62827	0.99600	1.000	0.76M
PER	1	0.63241	0.98600	1.000	0.78M
	2	0.00000	0.00000	0.000	–
	3	0.00000	0.00000	0.000	–
	4	0.75553	0.99900	1.000	0.52M
	5	0.64422	0.99400	1.000	0.72M

Table 28: Seed-level DrawerOpen TD3 results on the exact shared grid (no smoothing or interpolation).

Method	Seed	AUC	FQ-AUC	Final	Hit90
HER	1	0.28166	0.33750	0.300	0.09M
	2	0.26884	0.31550	0.100	0.15M
	3	0.20352	0.19300	0.400	0.04M
	4	0.24950	0.28900	0.000	0.07M
	5	0.25151	0.11600	0.000	0.02M
SABER (Ours)	1	0.28781	0.16550	0.650	0.01M
	2	0.33744	0.41700	0.200	0.06M
	3	0.28405	0.30650	0.150	0.05M
	4	0.46131	0.30050	0.000	0.02M
	5	0.25151	0.19750	0.400	0.01M
HGR	1	0.67261	0.21800	0.000	0.10M
	2	0.32387	0.23650	0.000	0.09M
	3	0.23756	0.15450	0.150	0.12M
	4	0.23857	0.21950	0.050	0.10M
	5	0.27337	0.29900	0.200	0.01M
PER	1	0.28857	0.27200	0.550	0.10M
	2	0.24497	0.27350	0.000	0.18M
	3	0.29799	0.39200	1.000	0.04M
	4	0.33128	0.35650	0.350	0.05M
	5	0.37688	0.40400	0.400	0.06M

Table 29: Seed-level DrawerClose DDPG results on the exact shared grid (no smoothing or interpolation).

Method	Seed	AUC	FQ-AUC	Final	Hit90
HER	1	0.45063	0.45500	0.850	0.08M
	2	0.05829	0.00200	0.000	0.12M
	3	0.88618	0.84700	0.900	0.05M
	4	0.09724	0.01700	0.000	0.06M
	5	0.15138	0.09800	0.000	0.07M
SABER (Ours)	1	0.08065	0.02000	0.000	0.08M
	2	0.90829	0.97800	1.000	0.09M
	3	0.73995	0.76100	1.000	0.20M
	4	0.90892	0.90950	0.950	0.01M
	5	0.10603	0.00000	0.000	0.05M
HGR	1	0.92362	0.88600	0.400	0.08M
	2	0.68631	0.80850	0.950	0.06M
	3	0.78216	0.42800	1.000	0.13M
	4	0.47701	0.11500	0.150	0.06M
	5	0.13894	0.06300	0.000	0.26M
PER	1	0.11106	0.05000	0.000	0.22M
	2	0.84548	0.98700	1.000	0.19M
	3	0.82487	0.89100	1.000	0.12M
	4	0.11206	0.00200	0.000	0.12M
	5	0.72538	0.98300	1.000	0.10M

Table 30: Seed-level DrawerClose TD3 results on the exact shared grid (no smoothing or interpolation).

Task	Seed	Approach	Contact	Opening/Closing	Open/Closed
DrawerOpen	1	438,206 (0.748)	122,496 (0.656)	115,761 (0.608)	1,877,393 (0.274)
	2	401,044 (0.712)	122,944 (0.774)	126,568 (0.708)	1,903,300 (0.311)
	3	398,226 (0.767)	135,453 (0.742)	116,080 (0.670)	1,904,097 (0.299)
	4	494,562 (0.761)	125,903 (0.655)	136,042 (0.617)	1,797,349 (0.298)
	5	491,933 (0.737)	118,160 (0.662)	98,851 (0.575)	1,844,912 (0.348)
DrawerClose	1	558,542 (0.551)	31,777 (0.705)	42,182 (0.412)	1,921,355 (0.226)
	2	553,344 (0.566)	42,221 (0.724)	49,685 (0.420)	1,908,606 (0.213)
	3	554,128 (0.569)	46,533 (0.748)	51,350 (0.420)	1,901,845 (0.215)
	4	551,833 (0.494)	48,093 (0.689)	61,006 (0.482)	1,892,924 (0.183)
	5	564,592 (0.564)	39,549 (0.686)	36,610 (0.392)	1,913,105 (0.223)

Table 31: Primary Drawer phase counts and support-positive rates. Each cell gives the exact count above its rate. Each seed contributes 2,553,856 samples; seeds 6–10 are in the phase artifact.