Modern History of **[O**] **Object Recognition** Infographic



2015 ResNet Faster RCNN 2016 SSD 2017 MaskRCNN



Image Classification Classify an image based on the dominant object inside it.

datasets: MNIST, CIFAR, ImageNet



Object Localization Predict the image region that contains the dominant object. Then mage classification car be used to recognize

object in the region



ocalize and classify all mage. This task typically includes proposing egions then classify the object inside them asets: PASCAL, COCO







Semantic Segmentation

Label each pixel of an image by the object class that it belongs to, such as human, sheep, and grass in the example itasets: PASCAL, COCO




Instance Instance Segmentation Label each pixel of an image by the object class and object

instance that it belongs





Important CNN Concepts



Feature^{4,5,8} (pattern, activation of a neuron, feature


A hidden neuron that is activated when a particular pattern (feature) is presented in its input region (receptive field).

The pattern that a neuron is detecting can be visualized by (1) optimizing its input region to maximize the neuron's activation (deep dream), (2) visualizing the gradient or guided gradient of the neuron activation on its input pixels (back propagation and guided back propagation), (3) visualizing a set of image regions in the training dataset that activate the neuron the most.

Receptive Field² (input region of a feature)

The region of the input image that affects the activation of a feature. In other words, it is the region that the feature is looking at.

Generally, a feature in a higher layer has a bigger receptive field, which allows it to learn to capture a more complex/abstract pattern. The ConvNet architecture determines how the receptive field change layer by layer.




* * * * * * x = x = x = x = x8 8 8 8 8 8

Feature Map¹ (a channel of a hidden layer)

A set of features that created by applying the same feature detector at different locations of an input map in a sliding window fashion (i.e. convolution). Features in the same feature map have the same receptive size and look for the same pattern but at different locations. This creates the spatial invariance properties of a ConvNet.

Feature Volume³ (a hidden layer in a ConvNet)

A set of feature maps, each map searches for a particular feature at a fixed set of locations on the input map. All features have the same receptive field size.




1x1x10 1x1x5

Fully connected layer as Feature Volume²

Fully connected layers (fc layers usually attached to the end of a ConvNet for classification) with k hidden nodes can be seen as a 1x1xk feature volume. This feature volume has one feature in each feature map, and its receptive field covers the whole image. The weight matrix W in an fc layer can be converted to a CNN kernel. Convolving a kernel wxhxk to a CNN feature volume wxhxd creates a 1x1xk feature volume (=FC layer with k nodes). Convolving a 1x1xk filter kernel to a 1x1xd feature volume creates a 1x1xk feature volume. Replacing fully connected layers by convolution layers allows us to apply a ConvNet to an image with arbitrary size.

Transposed Convolution¹(fractional strided convolution, deconvolution, upsampling)

The operation that back-propagates the gradient of a convolution operation. In other words, it is the backward pass of a convolution layer. A transposed convolution can be implemented as a normal convolution with zero inserted between the input features. A convolution with filter size k, stride s and zero padding p has an associated transposed convolution with filter size k'=k, stride s'=1, zero padding p'=k-p-1, and s-1 zeros inserted between each input unit.



Normal Convolution k = 3, s=2, p = 1

On the left, the red input unit contributes to the activation of 4 top left output units ough the 4 colored (through squares), therefore it receives gradient from these output This gradient backpropagation can implemented by transposed convolution shown on the right.



Transposed Convolution k' = 3, s'=1, p = 1, insert=1

End-To-End object recognition pipeline (end-to-end learning/system)

An object recognition pipeline that all stages (pre-processing, region proposal generation, proposal classification, post-processing) can be trained altogether by optimizing a single objective function, which is a differentiable function of all stages' variables. This end-to-end pipeline is the opposite of the traditional object recognition pipeline, which connects stages in a non-differentiable fashion. In these systems, we do not know how changing a stage's variable can affect the overall performance, so that each stage must be trained independently or alternately, or heuristically programmed.

Important Object Recognition Concepts

Bounding box proposal (region of interest, region A rectangular region of the input image that potentially contains an object inside. These proposals can be

selective search, or by a region proposal network (RPN) A bounding box can be represented as a 4-element vector, either storing its two corner coordinates (x0, y0, x1, y1), or (more common) storing its center location and its width and height (x, y, w, h). A bounding box is usually accompanied by a confidence score of how

generated by some heuristics search; objectness,

likely the box contains an object. The difference between two bounding boxes is usually measured by the L2 distance of their vector representations. w and h can be log-transformed before the distance calculation.

Offset = $\Delta(x, y, w, h)$ Distance = $||\Delta||$

Intersection over Union

A metric that measures the similarity between their bounding boxes overlapping area over their union area



Non Maxium Suppression (NMS)

A common algorithm to merge overlapping bounding boxes (proposals or detections). Any bounding box that significantly overlaps (IoU > IoU_threshold) with a bounding box is suppressed (removed).





Bounding box regression (bounding box refinement)

By looking at an input region, we can infer the bounding box that better fit the object inside, even if the object is only partly visible. The example on the right illustrates the possibility of inferring the ground truth box only by looking at part of an object. Therefore, one regressor can be trained to look at an input region and predict the offset $\Delta(x, y, w, h)$ between the input region box and the ground



truth box. If we have one regressor for each object class, it is called class-specific regression, otherwise, it is called class-agnostic (one regressor for all classes). A bounding box regressor is often accompanied by a bounding box classifier (confidence scorer) to estimate the confidence of object existence in the box. The classifier can also be class-specific or class-agnostic. Without defining prior boxes, the input region box plays the role of a prior box

Prior box (default box, anchor box)

Instead of using the input region as the only prior box, we can train multiple bounding box regressors, each look at the same input region but has a different prior box and learns to predict the offset between its own prior box and the ground truth box. This



way, regressors with different prior boxes can learn to predict bounding boxes with different properties (aspect ratio, scale, locations). Prior boxes can be predefined relatively to the input region, or learned by clustering. An appropriate box matching strategy is crucial to make the training converge.

Box Matching Strategy

We cannot expect a bounding box regressor to be able to predict a bounding box of an object that is too far away from its input region or its prior box (more common). Therefore, we need a box matching strategy to decide which prio box is matched with a ground truth box. Each match is a training example for $regressing.\ Possible\ strategies: (Multibox)\ matching\ each\ ground\ truth\ box\ with$ one prior box with highest IoU; (SSD, FasterRCNN) matching a prior box with any ground truth with IoU higher than 0.5.



One region proposal with 3 prior boxes and one ground truth box



The 3 bounding box regressors only see the input region and try to infer the ground truth box



In Multibox strategy, the matched with the prior

Hard negative example mining

For each prior box, there is a bounding box classifier that estimates the likelihood of having an object inside. After box matching, all matched prior boxes are positive examples for the classifier. All other prior boxes are negatives. If we used all of these hard negative examples, there would be a significant imbalance between the positives and negatives. Possible solutions: pick randomly negative examples (FasterRCNN), or pick the ones that the classifier makes the most serious error (SSD), so that the ratio between the negatives and positives is at roughly 3:1

RCNN and OverFeat represent two early competing ways to do object recognition: either classify regions proposed by another method (RCNN, FastRCNN, SPPNet), or classify a fixed set of evenly spaced square windows (OverFeat). The first approach has region proposals that fit the objects better than the other grid-like candidate windows but is two orders of magnitude slower. The second approach takes advantage of the convolution operation to quickly regress and classify objects in sliding-windows fashion.





Multibox ended this competition by introducing the ideas of prior box and region proposal network. Since then, all state-of-the-art methods now has a set of prior boxes (generated based on a set of sliding windows or by clustering ground-truth boxes) from which bounding box regressors are trained to propose regions that better fit the object inside. The new competition is between the *direct classification* (YOLO, SSD) and *refined classification* approaches (FasterRCNN, MaskRCNN).

ZFNet is the ILSVRC 2013 winner, which is basically

AlexNet with a minor resulting the control of the control AlexNet with a minor modification: use 7x7 kernel instead of 11x11 kernel in the first Conv layer to retain more information.

SPPNet (Spatial Pyramid Pooling net) is essentially an enhanced version of RCNN by introducing two important concepts: adaptively-sized pooling (the SPP layer), and computing feature volume only once. In fact, the Fast-RCNN embraced these ideas to fasten RCNN with minor modifica-

SPPNet uses selective search to propose 2000 region proposals per image. It then extracts a common global feature volume from the entire image using ZFNet-Conv5. For each region proposal, SPPNet uses spatial pyramid pooling (SPP) to pool features in that region from the global feature volume to features in that region from the global feature volume to generate its fixed-length representation. This representation is used for training the object classifier and box regressors. Pooling features from a common global feature volume rather than pushing all image crops through a full CNN like RCNN brings two orders of magnitude speed up. Note that although SPP operation is differentiable, the authors did not do that, so the ZFNet was only trained on ImageNet without finetuning.







~2k proposals spati

Fixed-size presentation

t50x256 Nurrian Box Regressor

YOLO

Net 2015

YOLO (You Only Look Once) is a direct development of MultiBox. It turns MultiBox from a region proposal solution to an object recognition method by adding a softmax layer, parrallel to the box regressor and box classifier layer, to directly predicts the object class. In addition, instead of clustering ground truth box locations to get the prior boxes, YOLO divides the input image into a 7x7 grid where each grid cell is a prior box. The grid cell is also used for box matching: if the center of an object falls into a grid cell, that grid cell is responsible for detecting that object. Like MultiBox, prior box only holds the center location information, not the size, so that box regressor predicts the box size independent with the size of the prior box. Like MultiBox, all the box regressor, confidence scorer, and object classifier look at features extracted from the whole



fc7 4096 br

layer \$4096 box regression scoring confidence

ResNet won the ILSVRC 2015 competition with an unbelievable 3.6% error rate (human performance is 5-10%). Instead of transforming the input representation to output representation, ResNet sequentially stacks residual blocks, each computes the change (residual) it wants to make to its input, and add that to its input to produce its output representation. This is slightly related

Region-based ConvNet (RCNN) is a natural combination of heuristic region proposal method and ConvNet feature extractor. From an input image, ~2000 bounding box proposals are generated using selective search. Those proposed regions are cropped and warped to a fixed-size 227x227 image. AlexNet is then used to extract 4096 features (fc7) for each warped image.

An SVM model is then trained to classify the object in the warped image using its 4096 features. Multiple class-specific bounding box regressors are also trained to refine the bounding bor proposal using the 4096 extracted features.





MultiBox is not an object recognition but a ConvNet-based region proposal solution. It popularized the ideas of region proposal netwo (RPN) and prior box, proving that ConvNet can be trained to propo better region proposals than heuristic approaches. Since then, heuris approaches have been gradually fading out and replaced by RPN. MultiBox first clusters all ground truth box locations in the whole dataset to find 200 centroids that it uses as prior boxes' centers. Each input image is center cropped and rescaled to 220x220. Then it uses a kentlet to extract 4096 features (fc7). A 200-sigmoid layer is added to predict the object confidence score, and 4x200-linear layer is added to predict center offset and scale of box proposal from each prior box. Note that box regressors and confidence scorers look at features extracted from

tc7 \$\frac{1}{4096}\$ object prior object prior offset box 1? ... box 200? box 1? AlexNet sigmoid layer linear layer

box regression scoring confidence **10**

Fast RCNN is essentially SPPNet with trainable feature extraction network and RolPooling in replacement of the SPP layer. RolPooling (region of interest pooling) is simply a special case of SPP where here only one pyramid level is used. RolPooling generates a fixed 7x7 feature volume for each Rol (region proposal) by dividing the Rol feature volume into a 7x7 grid of sub-windows and then max-pooling the values from each each roll case. sub-window. variable-size conv5_3 Fixed-lengtl epresentation **FastRCNN**



Faster RCNN is Fast RCNN with heuristic region proposal replaced by region proposal network (RPN) inspired by MultiBox. In Faster RCNN, RPN is a small ConvNet (3x3 conv -> 1x1 conv -> 1x1 conv) looking at the conv5_3 global feature volume in the sliding window fashion. Each sliding window has 9 prior boxes that relative to its receptive field (3 scales x 3 aspect ratios). RPN does bounding box regression and box confidence scoring for each prior box. The whole pipeline is trainable by combining the loss of box regression, box confidence scoring, and object classification into one common global objective function. Note that here, RPN only looks at a small input region; and prior boxes hold both the center location and the box size, which are different from the MultiBox and YOLO design



Everything is started here!

The modern history of object recognition goes along with the development of ConvNets, which was all started here in 2012 when AlexNet won the ILSVRC 2012 by a large margin. Note that all the object recognition approaches are orthogonal to the specific ConvNet designs (any ConvNet ConvNets are used as general image feature extractor

AlexNet bases on the decades-old LeNet, combined with data augmentation, ReLU, dropout, and GPU implementation. It proved the effectiveness of ConvNet, kicked off its RCNN glorious comeback, and opened a new era for computer

OverFeat OverFeat uses AlexNet to extract features at multiple evenly-spaced square windows in the image over multiple scales of an input image. An object classifier and a class-agnostic box regressor are trained to classify object and refine bounding box for every 5x5 region in the Pool5 layer (339x339 receptive field window). OverFeat replaces


for layers by 1x1xn conv layers to be able to predict for multi-scale images. Because receptive field moves 36 pixels when moving one pixel in the Pool5, the windows are usually not well aligned with the objects. OverFeat introduces exhaustive pooling scheme: Pool5 is applied at every offset of its input, which results in 9 Pool5 volumes. The windows are now only spaced 12pixels instead of 36pixels



Although not an ILSVRC winner, VGG is still one of the most common ConvNet architectures today thanks to its simplicity and effectiveness. The main idea is to replace large-kernel conv by stacking several small-kernel convs. It strictly uses 3x3 conv with stride and padding of 1, along with 2x2 maxpooling layers with stride 2.

ception Inception (GoogLeNet) is the winner of ILSVRC 2014.
Instead of traditionally stacking up conv and maxpooling layer sequentially, it stacks up Inception modules, which consists of multiple parallel conv and maxpooling layers with different kernel sizes. It uses 1x1 conv layer (network in network idea) to reduce the depth of feature volume output. There currently are 4 InceptionNet versions.

These are the two competing approaches for now. Direct classification simultaneously regresses prior box and classifies object directly from the same input region, while the refined classification approach first regresses the prior box for a refined bounding box, and then pools the features of the refined box from a common feature volume and classify object by these features. The former is faster but less accurate since the features it uses to classify are not extracted exactly from the refined prior box region



leverages the RCNN's RPN, Faster using it to directly classify object inside each prior box instead of just scoring the object confidence (similar to YOLO). It improves the diversity prior resolutions by running the RPN on multiple lavers at different depth levels

Mask RCNN extends Faster RCNN for Instance Segmentation by adding a branch for predicting class-specific object mask, in parallel with the existing bounding box regressor and object classifier. Since RolPool is not designed for pixel-to-pixel alignment between network inputs outputs, MaskRCNN replaces it with RoIAlign, which uses bilinear interpolation to compute the exact values of the input features at each sub-window instead of RolPooling maxpooling

References

- 1 Dumoulin, Vincent, and Francesco Visin. "A guide to convolution arithmetic for deep learning."
- The-Hien Dang-Ha, "A guide to receptive field arithmetic for CNN"
- Karpathy, Andrej. "Cs231n: Convolutional neural networks for visual recognition." [
- Zeiler, Matthew D., and Rob Fergus. "Visualizing and understanding convolutional networks."
- Mordvintsev, Alexander, Christopher Olah, and Mike Tyka. "Inceptionism: Going deeper into neural networks." [
- Adit Deshpande, "The 9 Deep Learning Papers You Need To Know About" Summary
- Shelhamer, Evan, Jonathan Long, and Trevor Darrell. "Fully convolutional networks for semantic segmentation." [
- Springenberg, Jost Tobias, et al. "Striving for simplicity: The all convolutional net." GuidedBackProp
- Dhruv Parthasarathy "A Brief History of CNNs in Image Segmentation: From R-CNN to Mask R-CNN" Summary

- Krizhevsky, Alex, Ilya Sutskever, and Geoffrey E. "Imagenet classification with convolutional neural networks." Ale
- Zeiler, Matthew D., and Rob Fergus. "Visualizing and understanding convolutional networks." ZFNet
- Simonyan, Karen, and Andrew Zisserman. "Very deep convolutional networks for large-scale image
- Szegedy, Christian, et al. "Going deeper with convolutions." [[
- He, Kaiming, et al. "Deep residual learning for image recognition." ResNet

Nikasa https://nikasa1889.github.io/ https://medium.com/@nikasa1889/ 1 Girshick, Ross, et al. "Rich feature hierarchies for accurate object detection and segmentation." RCNN semantic

2017

2016

- Sermanet, Pierre, et al. "Overfeat: Integrated recognition, localization and detection using convolutional networks." OverF
- He, Kaiming, et al. "Spatial pyramid pooling in deep convolutional networks for visual recognition." SPP
- Szegedy, Christian, et al. "Scalable, high-quality object detection." MultiBox
- 5 Girshick, Ross. "Fast r-cnn." FastRCNN
- Redmon, Joseph, et al. "You only look once: Unified, real-time object detection." YOLO
- Ren, Shaoqing, et al. "Faster r-cnn: Towards real-time object detection with region proposal networks." FasterRCNN
- Liu, Wei, et al. "SSD: Single shot multibox detector." SSD
- 9 He, Kaiming, et al. "Mask R-CNN." MaskRCNN