

GHARDA FOUNDATION'S GHARDA INSTITUTE OF TECHNOLOGY, LAVEL

GIT INSTITUTE OF TECHNOLOGY

COMPUTER ENGINEERING DEPARTMENT A/P: Lavel, Tal.Khed Dist. Ratnagiri

Evaluation Sheet

Class: TE-Computer

Semester: VI

Subject: System Programming & Compiler Construction

Experiment No: 1

Title of Experiment: Implementation of Two Pass Assembler

Sr. No.	Evaluation Criteria	Max Marks	Marks Obtained
1	Practical Performance	10	
2	Oral	5	
Total		15	

Theory:

Two Pass Assembler

A two-pass assembler is a type of assembler that goes through the source code twice to generate the machine code. In the first pass, it reads the entire source code to build a symbol table and detects any syntax errors. In the second pass, it generates the machine code using the symbol table created in the first pass.

Steps involved in a two-pass assembler -

Pass 1: In this pass, the assembler reads the entire source code and builds a symbol table. The symbol table contains the names of all the labels, variables, and constants used in the code, along with their memory addresses. It also detects any syntax errors and generates error messages if necessary. The symbol table is used in the second pass to generate the machine code.

Pass 2: In this pass, the assembler generates the machine code using the symbol table created in the first pass. It reads the source code line by line and translates each instruction into its corresponding machine code. It also replaces all the labels, variables, and constants with their respective memory addresses. The machine code is then written to an output file.

Advantages of two-pass assembler –

- 1. It can handle forward references: A forward reference occurs when a label is used before it is defined. In a two-pass assembler, the symbol table is built in the first pass, so it can handle forward references in the second pass.
- 2. It can generate optimized code: Since a two-pass assembler has access to the entire source code in both passes, it can optimize the generated machine code for size and performance.
- 3. It can detect errors early: The first pass of a two-pass assembler detects syntax errors and generates error messages, so they can be fixed before the machine code is generated.




Fig. Working of Two Pass Assembler

Additional Details of Two-Pass Assembler -

- 1. **Symbol Table**: The symbol table is a data structure that is used to store information about the labels, variables, and constants used in the source code. It contains the name of the symbol, its type, and its memory location. The symbol table is created in the first pass of the assembler and is used in the second pass to generate the machine code.
- 2. **Pass 1**: In the first pass, the assembler reads the source code and builds the symbol table. It also checks for syntax errors and generates error messages if necessary. The symbol table is built by scanning each line of code to identify labels, variables, and constants and adding them to the symbol table.
- 3. Pass 2: In the second pass, the assembler generates the machine code using the symbol table created in the first pass. It reads each line of code and translates it into its corresponding machine code. The assembler uses the symbol table to replace all the labels, variables, and constants with their respective memory locations. The machine code is then written to an output file.
- 4. **Optimization**: A two-pass assembler can optimize the generated machine code for size and performance since it has access to the entire source code in both passes. It can eliminate redundant instructions, use shorter instructions where possible, and reorder instructions to improve performance.

5. **Error Handling**: A two-pass assembler can detect syntax errors and generate error messages in the first pass. This allows the programmer to fix the errors before the machine code is generated. It can also handle forward references, which occur when a label is used before it is defined.

Overall, a two-pass assembler is a powerful tool for generating machine code from assembly language source code. It allows for error detection and optimization, and can handle forward references, making it a popular choice for many programmers.

```
Program:-(main.py)
# -*- coding: utf-8 -*-
@author: MangeshPoskar29
Title: Implementation of two pass assembler
This program will work properly for certain set of assembly commands only
111111
fp = open('program.txt', 'r')
program = fp.read().split("\n")
# print(program)
fp.close()
mnemonic tab = {'STOP': '00', 'ADD': '01', 'SUB': '02', 'MULT': '03', 'MOVER': '04', 'MOVEM': '05',
'COMP': '06',
         'BC': '07', 'DIV': '08', 'READ': '09', 'PRINT': '10', 'DS': '01', 'DC': '02'}
reg_code = {'AREG': 1, 'BREG': 2, 'CREG': 3, 'DREG': 4}
condition code = {'LT': 1, 'LE': 2, 'EQ': 3, 'GT': 4, 'GE': 5, 'ANY': 6}
optab = {'STOP': 'AD', 'ADD': 'IS', 'MULT': 'IS', 'MOVER': 'IS', 'MOVEM': 'IS', 'COMP': 'IS', 'BC': 'IS',
'DC': 'DL',
     'DS': 'DL',
     'READ': 'IS',
```

```
'PRINT': 'IS'} # declaring operands and their respective types of sentences Imp sent, Decl
sent and AD
sym_table = {} # empty symbol table
print('Content of Mnemonic Table is :\n')
print('Mnemonic', ' Code\n')
for k, v in mnemonic_tab.items():
            {1}'.format(k, v))
  print('{0}
print()
print('Content of Opcode table is:\n')
print('Mnemonic', 'Class\n')
for k, v in optab.items():
  print('{0} {1}'.format(k, v))
print()
print('Input Assembly Code')
print()
# print the source code
# set the value of lc
START 200
MOVER AREG FIRST
ADD AREG SECOND
MOVEM AREG RESULT
```

```
PRINT RESULT
RESULT DS 1
FIRST DC 5
SECOND DC 7
END
111111
for line in program: # traversing line by line throught the program
  a = line.split() # splitting the line and it will get converted into list of strings of each line in
assembly code
  if a[0] == 'START': # checking the first element in the list if it is a start symbol and if it is not
simply print the line.
    Ic = int(a[1]) # converting the 1st element in the list into integer value and storing it into Ic
    temp = Ic # the int value stored in Ic is stored in temp (here storing the address value as a
temporary value)
  print(line) # printing the line
# Build the symbol table
for line in program:
  I = line.split() # splitting the lines into list of single words and storing it into I
  for i in I: # traversing through the I one by one
    if i not in optab and i not in reg_code and i.isdigit() != True and i not in condition_code: #
START FIRST SECOND RESULT END
       sym table[i] = lc
      lc += 1
print()
print('Content of Symbol Table is:')
print()
```

```
print('Symbol Name', ' Address')
for k, v in sym_table.items():
  print('{0}
               {1}'.format(k, v))
#
Ic = temp # taking the value from temp into Ic (Ic = 200)
print()
print('Intermediate code after PASS-1')
print()
a = list(sym_table.keys()) # making a list of all the keys from symbol table and storing them into
for line in program: # traversing line by line through assembly program
  lexeme = line.split() # Splitting the assembly code line by line and storing it in the list in the
variable lexeme
  if len(lexeme) == 4: # if lexeme is greater than length 4 i.e. there are 4 elements in the list
then remove 1st lexeme it from the list
    lexeme.remove(lexeme[0])
  if lexeme[0] in optab:
    if optab[lexeme[0]] == 'AD':
      if len(lexeme) == 1:
         print(lc, (optab[lexeme[0]], mnemonic tab[lexeme[0]]), '(C,', lexeme[0], ')')
```

```
if lexeme[0] in optab:
      if optab[lexeme[0]] == 'IS':
         if len(lexeme) == 3:
           if lexeme[0] == 'BC':
             print(lc, (optab[lexeme[0]], mnemonic_tab[lexeme[0]]),
condition_code[lexeme[1]], '(S',
                 a.index(lexeme[2]), ')')
             lc += 1
           else:
             print(lc, (optab[lexeme[0]], mnemonic tab[lexeme[0]]), reg code[lexeme[1]], '(S',
                 a.index(lexeme[2]), ')')
             lc += 1
           if len(lexeme) == 2:
             print(lc, (optab[lexeme[0]], mnemonic tab[lexeme[0]]), '(S', a.index(lexeme[1]),
')')
             lc += 1
    if lexeme[0] not in optab:
      if len(lexeme) == 3:
         print(lc, (optab[lexeme[1]], mnemonic tab[lexeme[1]]), '(C', lexeme[2], ')')
         lc += 1
      if len(lexeme) == 4:
         print(lc, (optab[lexeme[1]], mnemonic_tab[lexeme[1]]), )
         lc += 1
print()
print('Machine Code after PASS II \n')
Ic = temp # again we are reseting the Ic as a starting address of the program here 200
```

```
for line in program:
  lexeme = line.split() # making a list line by line and storing it into lexeme
  if len(lexeme) == 4: # 4 elements in the list then remove the first element
    lexeme.remove(lexeme[0])
  if lexeme[0] in optab:
    if optab[lexeme[0]] == 'AD':
      if (len(lexeme) == 1):
        print()
        lc += 1
      else:
        if (lexeme[0] == 'START'): pass
  if lexeme[0] in optab:
    if optab[lexeme[0]] == 'IS':
      if len(lexeme) == 3: # if there are 3 elements in the list
        if lexeme[0] == 'BC':
           print(lc, mnemonic tab[lexeme[0]], condition code[lexeme[1]],
sym_table[lexeme[2]])
           lc += 1
         else:
           print(lc, mnemonic_tab[lexeme[0]], reg_code[lexeme[1]], sym_table[lexeme[2]])
           lc += 1
      if (len(lexeme) == 2):
        print(lc, mnemonic_tab[lexeme[0]], sym_table[lexeme[1]])
        lc += 1
```

```
if lexeme[0] not in optab:
    if len(lexeme) == 3:
      print(lc, mnemonic_tab[lexeme[1]], lexeme[2])
      lc += 1
    if len(lexeme) == 4:
      print(mnemonic_tab[lexeme[1]])
      lc += 1
(program.txt):-
START 200
MOVER AREG FIRST
ADD AREG SECOND
MOVEM AREG RESULT
PRINT RESULT
RESULT DS 1
FIRST DC 5
SECOND DC 7
```

END

Output:-

```
>_ Console v × W Shell × +
Content of Mnemonic Table is :
Mnemonic Code
STOP
ADD
SUB
MULT
MOVER
MOVEM
COMP
BC
DIV
READ
PRINT
DS
DC
              00
01
02
03
04
05
                 00
                06
             07
08
                 09
10
             01
02
Content of Opcode table is:
Mnemonic Class
STOP
ADD
MULT
MOVER
MOVEM
COMP
               AD
IS
IS
IS
IS
                 IS
BC
DC
DS
READ
PRINT
              IS
             DL
DL
                 IS
IS
Input Assembly Code
START 200
MOVER AREG FIRST
ADD AREG SECOND
```

```
Input Assembly Code

START 200

MOVER AREG FIRST
ADD AREG SECOND

MOVEM AREG RESULT
PRINT RESULT
RESULT DS 1
FIRST DC 5
SECOND DC 7
END

Content of Symbol Table is:

Symbol Name Address
START 200
FIRST 206
SECOND 207
RESULT 205
END 208

Intermediate code after PASS-1
200 ('IS', '04') 1 (S 1)
201 ('IS', '01') 1 (S 2)
202 ('IS', '05') 1 (S 3)

Machine Code after PASS II

200 04 1 206
201 01 1 207
202 05 1 205
203 10 205
204 01 1
205 02 5
206 02 7

■
```