

## A. Thor

time limit per test: 2 seconds  
memory limit per test: 256 megabytes  
input: standard input  
output: standard output

Thor is getting used to the Earth. As a gift Loki gave him a smartphone. There are  $n$  applications on this phone. Thor is fascinated by this phone. He has only one minor issue: he can't count the number of unread notifications generated by those applications (maybe Loki put a curse on it so he can't).

$q$  events are about to happen (in chronological order). They are of three types:

1. Application  $x$  generates a notification (this new notification is unread).
2. Thor reads all notifications generated so far by application  $x$  (he may re-read some notifications).
3. Thor reads the first  $t$  notifications generated by phone applications (notifications generated in first  $t$  events of the first type). It's guaranteed that there were at least  $t$  events of the first type before this event. Please note that he doesn't read first  $t$  unread notifications, he just reads the very first  $t$  notifications generated on his phone and he may re-read some of them in this operation.

Please help Thor and tell him the number of unread notifications after each event. You may assume that initially there are no notifications in the phone.

### Input

The first line of input contains two integers  $n$  and  $q$  ( $1 \leq n, q \leq 300\,000$ ) — the number of applications and the number of events to happen.

The next  $q$  lines contain the events. The  $i$ -th of these lines starts with an integer  $type_i$  — type of the  $i$ -th event. If  $type_i = 1$  or  $type_i = 2$  then it is followed by an integer  $x_i$ . Otherwise it is followed by an integer  $t_i$  ( $1 \leq type_i \leq 3$ ,  $1 \leq x_i \leq n$ ,  $1 \leq t_i \leq q$ ).

### Output

Print the number of unread notifications after each event.

### Examples

<b>input</b>	<a href="#">Copy</a>
3 4 1 3 1 1 1 2 2 3	
<b>output</b>	<a href="#">Copy</a>
1 2 3 2	

  

<b>input</b>	<a href="#">Copy</a>
4 6 1 2	

```
1 4
1 2
3 3
1 3
1 3
```

output

Copy

```
1
2
3
0
1
2
```

## Note

In the first sample:

1. Application 3 generates a notification (there is 1 unread notification).
2. Application 1 generates a notification (there are 2 unread notifications).
3. Application 2 generates a notification (there are 3 unread notifications).
4. Thor reads the notification generated by application 3, there are 2 unread notifications left.

In the second sample test:

1. Application 2 generates a notification (there is 1 unread notification).
2. Application 4 generates a notification (there are 2 unread notifications).
3. Application 2 generates a notification (there are 3 unread notifications).
4. Thor reads first three notifications and since there are only three of them so far, there will be no unread notification left.
5. Application 3 generates a notification (there is 1 unread notification).
6. Application 3 generates a notification (there are 2 unread notifications).