

C. Circular RMQ

time limit per test: 1.5 seconds
memory limit per test: 256 megabytes
input: standard input
output: standard output

You are given circular array a_0, a_1, \dots, a_{n-1} . There are two types of operations with it:

- $inc(lf, rg, v)$ — this operation increases each element on the segment $[lf, rg]$ (inclusively) by v ;
- $rmq(lf, rg)$ — this operation returns minimal value on the segment $[lf, rg]$ (inclusively).

Assume segments to be circular, so if $n = 5$ and $lf = 3, rg = 1$, it means the index sequence: 3, 4, 0, 1.

Write program to process given sequence of operations.

Input

The first line contains integer n ($1 \leq n \leq 200000$). The next line contains initial state of the array: a_0, a_1, \dots, a_{n-1} ($-10^6 \leq a_i \leq 10^6$), a_i are integer. The third line contains integer m ($0 \leq m \leq 200000$), m — the number of operations. Next m lines contain one operation each. If line contains two integer lf, rg ($0 \leq lf, rg \leq n - 1$) it means rmq operation, it contains three integers lf, rg, v ($0 \leq lf, rg \leq n - 1; -10^6 \leq v \leq 10^6$) — inc operation.

Output

For each rmq operation write result for it. Please, do not use `%lld` specifier to read or write 64-bit integers in C++. It is preferred to use `cout` (also you may use `%I64d`).

Examples

input	Copy
4 1 2 3 4 4 3 0 3 0 -1 0 1 2 1	
output	Copy
1 0 0	