

# G1. Fibonacci Strings

time limit per test: 2 seconds

memory limit per test: 256 megabytes

input: standard input

output: standard output

Fibonacci strings are defined as follows:

- $f_1 = \text{«a»}$
- $f_2 = \text{«b»}$
- $f_n = f_{n-1}f_{n-2}, n > 2$

Thus, the first five Fibonacci strings are: "a", "b", "ba", "bab", "babba".

You are given a Fibonacci string and  $m$  strings  $s_i$ . For each string  $s_i$ , find the number of times it occurs in the given Fibonacci string as a substring.

## Input

The first line contains two space-separated integers  $k$  and  $m$  — the number of a Fibonacci string and the number of queries, correspondingly.

Next  $m$  lines contain strings  $s_i$  that correspond to the queries. It is guaranteed that strings  $s_i$  aren't empty and consist only of characters "a" and "b".

The input limitations for getting 30 points are:

- $1 \leq k \leq 3000$
- $1 \leq m \leq 3000$
- The total length of strings  $s_i$  doesn't exceed 3000

The input limitations for getting 100 points are:

- $1 \leq k \leq 10^{18}$
- $1 \leq m \leq 10^4$
- The total length of strings  $s_i$  doesn't exceed  $10^5$

Please do not use the `%lld` specifier to read or write 64-bit integers in C++. It is preferred to use `cin`, `cout` streams or the `%I64d` specifier.

## Output

For each string  $s_i$  print the number of times it occurs in the given Fibonacci string as a substring. Since the numbers can be large enough, print them modulo 1000000007 ( $10^9 + 7$ ). Print the answers for the strings in the order in which they are given in the input.

## Examples

input	Copy
6 5 a b ab	

ba aba	
output	Copy
3 5 3 3 1	