

Aim:

The below program has a method void knapsack(). Which takes four parameters **number of objects**, the **weight of each object**, the **profit** corresponding to each one and the **capacity of the knapsack**. Write a program using a fractional knapsack algorithm to get the maximum profit.

Print the output as follows:

```
Sample Input and Output:
Enter the no. of objects: 6
Enter the weights and profits of each object:
1 2
4 5
8 9
4 6
5 2
3 5
Enter the capacity of knapsack:10
Maximum profit is:- 15.500000
```

Source Code:

knapsack.c

```
# include<stdio.h>
void knapsack(int n, float weight[], float profit[], float capacity) {
    float ratio[20],temp;
    int i,j;
    for(i=0;i<n;i++){
        ratio[i]=profit[i]/weight[i];
    }
    for(i=0;i<n-1;i++){
        for(j=i+1;j<n;j++){
            if(ratio[i]<ratio[j]){
                temp=ratio[i];
                ratio[i]=ratio[j];
                ratio[j]=temp;

                temp=weight[i];
                weight[i]=weight[j];
                weight[j]=temp;

                temp=profit[i];
                profit[i]=profit[j];
                profit[j]=temp;
            }
        }
    }
    float totalProfit=0.0;
    float remainingCapacity=capacity;

    for(i=0;i<n;i++){
        if(weight[i]<=remainingCapacity){
```

```

        remainingCapacity-=weight[i];
        totalProfit+=profit[i];
    }else{
        totalProfit+=profit[i] * (remainingCapacity/weight[i]);
        break;
    }
}
printf("Maximum profit is:- %f\n",totalProfit);
}

int main() {
    float weight[20], profit[20], capacity;
    int num, i, j;
    float ratio[20], temp;
    printf("Enter the no. of objects: ");
    scanf("%d", &num);
    printf("Enter the weights and profits of each object:\n");
    for (i = 0; i < num; i++) {
        scanf("%f %f", &weight[i], &profit[i]);
    }
    printf("Enter the capacity of knapsack:");
    scanf("%f", &capacity);
    for (i = 0; i < num; i++) {
        ratio[i] = profit[i] / weight[i];
    }

    for (i = 0; i < num; i++) {
        for (j = i + 1; j < num; j++) {
            if (ratio[i] < ratio[j]) {
                temp = ratio[j];
                ratio[j] = ratio[i];
                ratio[i] = temp;
                temp = weight[j];
                weight[j] = weight[i];
                weight[i] = temp;
                temp = profit[j];
                profit[j] = profit[i];
                profit[i] = temp;
            }
        }
    }
    knapsack(num, weight, profit, capacity);
    return(0);
}

```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Enter the no. of objects: 6
Enter the weights and profits of each object: 1 2
4 5
8 9
4 6

5 2
3 5
Enter the capacity of knapsack: 10
Maximum profit is:- 15.500000

Test Case - 2
User Output
Enter the no. of objects: 5
Enter the weights and profits of each object: 4 6
1 3
7 5
5 3
3 4
Enter the capacity of knapsack: 10
Maximum profit is:- 14.428572