





MDPs: overview




So far: search problems



state s , action a **deterministic** \longrightarrow state $\text{Succ}(s, a)$



Uncertainty in the real world





History

- MDPs: Mathematical Model for decision making under uncertainty.
- MDPs were first introduced in 1950s-60s.
- Ronald Howard's book on Dynamic Programming and Markov Processes
- The term 'Markov' refers to Andrey Markov as MDPs are extensions of Markov Chains, and they allow making decisions (taking actions or having choice).


Applications



Robotics: decide where to move, but actuators can fail, hit unseen obstacles, etc.




Resource allocation: decide what to produce, don't know the customer demand for various products



Agriculture: decide what to plant, but don't know weather and thus crop yield

Dice game



Example: dice game

For each round $r = 1, 2, \dots$

- You choose **stay** or **quit**.
- If **quit**, you get \$10 and we end the game.
- If **stay**, you get \$4 and then I roll a 6-sided dice.
 - If the dice results in 1 or 2, we end the game.
 - Otherwise, continue to the next round.

Start

Stay


Quit

Dice:

Rewards:

Rewards

If follow policy "stay":




Expected utility:

$$\frac{1}{3}(4) + \frac{2}{3} \cdot \frac{1}{3}(8) + \frac{2}{3} \cdot \frac{2}{3} \cdot \frac{1}{3}(12) + \dots = 12$$

Rewards

If follow policy "quit":



Expected utility:

$$1(10) = 10$$


MDP for dice game



Example: dice game

For each round $r = 1, 2, \dots$

- You choose **stay** or **quit**.
- If **quit**, you get \$10 and we end the game.
- If **stay**, you get \$4 and then I roll a 6-sided dice.
 - If the dice results in 1 or 2, we end the game.
 - Otherwise, continue to the next round.



Markov decision process



Definition: Markov decision process

States: the set of states

$s_{\text{start}} \in \text{States}$: starting state

$\text{Actions}(s)$: possible actions from state s


$T(s, a, s')$: probability of s' if take action a in state s

$\text{Reward}(s, a, s')$: reward for the transition (s, a, s')

$\text{IsEnd}(s)$: whether at end of game

$0 \leq \gamma \leq 1$: discount factor (default: 1)

Search problems



Definition: search problem

States: the set of states

$s_{\text{start}} \in \text{States}$: starting state

$\text{Actions}(s)$: possible actions from state s

$\text{Succ}(s, a)$: where we end up if take action a in state s

$\text{Cost}(s, a)$: cost for taking action a in state s

$\text{IsEnd}(s)$: whether at end

- $\text{Succ}(s, a) \Rightarrow T(s, a, s')$
- $\text{Cost}(s, a) \Rightarrow \text{Reward}(s, a, s')$

Transitions



Definition: transition probabilities

The **transition probabilities** $T(s, a, s')$ specify the probability of ending up in state s' if taken action a in state s .



Example: transition probabilities

s	a	s'	$T(s, a, s')$
in	quit	end	1
in	stay	in	$2/3$
in	stay	end	$1/3$

Probabilities sum to one




Example: transition probabilities

s	a	s'	$T(s, a, s')$
in	quit	end	1
in	stay	in	$2/3$
in	stay	end	$1/3$

For each state s and action a :

$$\sum_{s' \in \text{States}} T(s, a, s') = 1$$

Successors: s' such that $T(s, a, s') > 0$



Transportation example



Example: transportation

Street with blocks numbered 1 to n .

Walking from s to $s + 1$ takes 1 minute.

Taking a magic tram from s to $2s$ takes 2 minutes.

How to travel from 1 to n in the least time?


Tram fails with probability 0.5.

[semi-live solution]

What is a solution?

Search problem: path (sequence of actions)

MDP:



Definition: policy

A **policy** π is a mapping from each state $s \in \text{States}$ to an action $a \in \text{Actions}(s)$.



Example: volcano crossing

s	$\pi(s)$
(1,1)	S
(2,1)	E
(3,1)	N
...	...

Evaluating a policy



Definition: utility

Following a policy yields a **random path**.

The **utility** of a policy is the (discounted) sum of the rewards on the path (this is a random variable).

Path

[in; stay, 4, end]

[in; stay, 4, in; stay, 4, in; stay, 4, end]

[in; stay, 4, in; stay, 4, end]

[in; stay, 4, in; stay, 4, in; stay, 4, in; stay, 4, end]

...

Utility


4

12

8

16

...



Definition: value (expected utility)

The **value** of a policy at a state is the **expected** utility.

Value: 12

Evaluating a policy: volcano crossing


Run (or press ctrl-enter)

2.4 ↓	-0.5 ↓	-50	40	<i>a</i>	<i>r</i>	<i>s</i>
3.7 →	5 ↓	-50	31 ↑	E	-0.1	(2,1)
				S	-0.1	(2,2)
				E	-0.1	(3,2)
				E	-0.1	(3,3)
				E	-0.1	(3,4)
				N	-0.1	(2,4)
				N	-50.1	(2,3)
2	12.6 →	16.3 →	26.2 ↑			

Value: 3.73

Utility: -29.99

Discounting



Definition: utility

Path: $s_0, a_1 r_1 s_1, a_2 r_2 s_2, \dots$ (action, reward, new state).

The **utility** with discount γ is

$$u_1 = r_1 + \gamma r_2 + \gamma^2 r_3 + \gamma^3 r_4 + \dots$$

Discount $\gamma = 1$ (save for the future):

$$[\text{stay}, \text{stay}, \text{stay}, \text{stay}]: 4 + 4 + 4 + 4 = 16$$


Discount $\gamma = 0$ (live in the moment):

$$[\text{stay}, \text{stay}, \text{stay}, \text{stay}]: 4 + 0 \cdot (4 + \dots) = 4$$

Discount $\gamma = 0.5$ (balanced life):


$$[\text{stay}, \text{stay}, \text{stay}, \text{stay}]: 4 + \frac{1}{2} \cdot 4 + \frac{1}{4} \cdot 4 + \frac{1}{8} \cdot 4 = 7.5$$

Policy evaluation




Definition: value of a policy

Let $V_\pi(s)$ be the expected utility received by following policy π from state s .




Definition: Q-value of a policy

Let $Q_\pi(s, a)$ be the expected utility of taking action a from state s , and then following policy π .



Policy evaluation


Plan: define recurrences relating value and Q-value



$$V_\pi(s) = \begin{cases} 0 & \text{if IsEnd}(s) \\ Q_\pi(s, \pi(s)) & \text{otherwise.} \end{cases}$$

$$Q_\pi(s, a) = \sum_{s'} T(s'|s, a) [\text{Reward}(s, a, s') + \gamma V_\pi(s')]$$

Dice game



Let π be the "stay" policy: $\pi(\text{in}) = \text{stay}$.

$$V_{\pi}(\text{end}) = 0$$

$$V_{\pi}(\text{in}) = \frac{1}{3}(4 + V_{\pi}(\text{end})) + \frac{2}{3}(4 + V_{\pi}(\text{in}))$$

In this case, can solve in closed form:

$$V_{\pi}(\text{in}) = 12$$

Policy evaluation



Key idea: iterative algorithm

Start with arbitrary policy values and repeatedly apply recurrences to converge to true values.



Algorithm: policy evaluation

Initialize $V_{\pi}^{(0)}(s) \leftarrow 0$ for all states s .

For iteration $t = 1, \dots, t_{PE}$:

For each state s :

$$V_{\pi}^{(t)}(s) \leftarrow \underbrace{\sum_{s'} T(s'|s, \pi(s)) [\text{Reward}(s, \pi(s), s') + \gamma V_{\pi}^{(t-1)}(s')]}_{Q^{(t-1)}(s, \pi(s))}$$

Policy evaluation implementation

How many iterations (t_{PE})? Repeat until values don't change much:

$$\max_{s \in \text{States}} |V_{\pi}^{(t)}(s) - V_{\pi}^{(t-1)}(s)| \leq \epsilon$$

Don't store $V_{\pi}^{(t)}$ for each iteration t , need only last two:

$$V_{\pi}^{(t)} \text{ and } V_{\pi}^{(t-1)}$$

Complexity



Algorithm: policy evaluation

Initialize $V_{\pi}^{(0)}(s) \leftarrow 0$ for all states s .

For iteration $t = 1, \dots, t_{\text{PE}}$:

For each state s :

$$V_{\pi}^{(t)}(s) \leftarrow \underbrace{\sum_{s'} T(s'|s, \pi(s)) [\text{Reward}(s, \pi(s), s') + \gamma V_{\pi}^{(t-1)}(s')]}_{Q^{(t-1)}(s, \pi(s))}$$

MDP complexity

S states

A actions per state

S' successors (number of s' with $T(s'|s, a) > 0$)

Time: $O(t_{\text{PE}} S S')$

Policy evaluation on dice game

Let π be the "stay" policy: $\pi(\text{in}) = \text{stay}$.

$$V_{\pi}^{(t)}(\text{end}) = 0$$

$$V_{\pi}^{(t)}(\text{in}) = \frac{1}{3}(4 + V_{\pi}^{(t-1)}(\text{end})) + \frac{2}{3}(4 + V_{\pi}^{(t-1)}(\text{in}))$$

s	end	in	$(t = 100 \text{ iterations})$
$V_{\pi}^{(t)}$	0.00	12.00	

Converges to $V_{\pi}(\text{in}) = 12$.




Summary so far

- **MDP**: graph with states, chance nodes, transition probabilities, rewards
- **Policy**: mapping from state to action (solution to MDP)
- **Value of policy**: expected utility over random paths
- **Policy evaluation**: iterative algorithm to compute value of policy

Optimal value and policy


Goal: try to get directly at maximum expected utility



Definition: optimal value

The **optimal value** $V_{\text{opt}}(s)$ is the maximum value attained by any policy.

Optimal values and Q-values




Optimal value if take action a in state s :

$$Q_{\text{opt}}(s, a) = \sum_{s'} T(s, a, s') [\text{Reward}(s, a, s') + \gamma V_{\text{opt}}(s')].$$

Optimal value from state s :

$$V_{\text{opt}}(s) = \begin{cases} 0 & \text{if IsEnd}(s) \\ \max_{a \in \text{Actions}(s)} Q_{\text{opt}}(s, a) & \text{otherwise.} \end{cases}$$

Optimal policies



Given Q_{opt} , read off the optimal policy:

$$\pi_{\text{opt}}(s) = \arg \max_{a \in \text{Actions}(s)} Q_{\text{opt}}(s, a)$$

Value iteration



Algorithm: value iteration [Bellman, 1957]

Initialize $V_{\text{opt}}^{(0)}(s) \leftarrow 0$ for all states s .

For iteration $t = 1, \dots, t_{\text{VI}}$:

For each state s :

$$V_{\text{opt}}^{(t)}(s) \leftarrow \max_{a \in \text{Actions}(s)} \underbrace{\sum_{s'} T(s, a, s') [\text{Reward}(s, a, s') + \gamma V_{\text{opt}}^{(t-1)}(s')]}_{Q_{\text{opt}}^{(t-1)}(s, a)}$$

Time: $O(t_{\text{VI}} S A S')$

[semi-live solution]

Value iteration: dice game

s	end	in
$V_{\text{opt}}^{(t)}$	0.00	12.00 ($t = 100$ iterations)
$\pi_{\text{opt}}(s)$	-	stay

Convergence



Theorem: convergence

Suppose either


- discount $\gamma < 1$, or
- MDP graph is acyclic.

Then value iteration converges to the correct answer.



Example: non-convergence

discount $\gamma = 1$, zero rewards



Summary of algorithms

- Policy evaluation: $(\text{MDP}, \pi) \rightarrow V_\pi$
- Value iteration: $\text{MDP} \rightarrow (Q_{\text{opt}}, \pi_{\text{opt}})$

Unifying idea

Algorithms:

- Search DP computes $\text{FutureCost}(s)$
- Policy evaluation computes policy value $V_{\pi}(s)$
- Value iteration computes optimal value $V_{\text{opt}}(s)$

Recipe:

- Write down recurrence (e.g., $V_{\pi}(s) = \dots V_{\pi}(s') \dots$)
- Turn into iterative algorithm (replace mathematical equality with assignment operator)