Exercise 2

IAD2133 | OBJECT ORIENTED PROGRAMMING
Chapter 2 - Elementary Programming

NAME	**:Asyraf Bin A Rasidi**	**PHONE**	**:0104202049**
MATRIC NO.	**:3252005281**	**EMAIL**	**:3252005281@student.unisel.edu.my**

1. Scanner Class

Which method in the `Scanner` class is used specifically to read a value of type `double` from the console?

A. `nextDouble()`

B. `getDouble()`

C. `inputDouble()`

D. `readDouble()`

---

2. Java Identifiers (True/False)

A Java identifier can legally begin with a digit, provided the rest of the characters are letters or underscores.

A. True

B. False

---

3. Valid Identifier

Which of the following is a valid Java identifier?

A. `123geeks`

B. `sum_&_difference`

C. `My Variable`

D. `$myvariable`

---

4. Modulus Operation

If you calculate `(6 + 10) % 7`, what is the result?

A. 1

B. 3

C. 2

D. 0

---

5. Floating-Point Literal

By default, a floating-point literal such as `5.0` is treated as which data type in Java?

A. float

B. long

C. double

D. int

---

6. Integer Division

What is the result of `5 / 2` in Java?

A. 2.5

B. 3

C. 2

D. 0

---

7. System Time

The method `System.currentTimeMillis()` returns the number of milliseconds elapsed since:

A. The time the program started

B. Midnight today

C. January 1, 1900 GMT

D. January 1, 1970 GMT

---

8. Type Casting

When casting a `double` to an `int`, such as `(int) 3.9`, what happens?

A. Fractional part is truncated

B. Stored elsewhere

C. Runtime error

D. Rounded

---

9. Software Development Phase

Which phase focuses on understanding the problem and documenting system requirements?

A. System Analysis

B. Requirements Specification

C. Implementation

D. System Design

---

10. Type Conversion

If one operand is `double` and the other is `int`, what is the result type?

A. float

B. long

C. int

D. double

---

11. System Analysis (True/False)

System Analysis involves identifying classes, interfaces, and relationships.

A. True

B. False

---

12. Augmented Assignment

Which is an example of an augmented assignment operator?

A. `+=`

B. `&&`

C. `++`

D. `==`

---

13. Acronym in System Design

What does IPO stand for?

A. Input, Process, Output

B. Application Programming Interface

C. Graphical User Interface

D. Integrated Development Environment

---

14. Expression Equivalence (True/False)

If `sum` is an integer, then `sum += 4.5` is equivalent to `sum = (int)(sum + 4.5)`.

A. True

B. False

---

15. Data Type Error

What error occurs when a value exceeds a data type's range?

A. Undeclared Variable

B. Integer Overflow

C. Round-off Error

D. Redundant Input

---

16. Maintenance Phase

Which phase focuses on improving the system and fixing bugs over time?

A. Implementation

B. Maintenance

C. Deployment

D. Testing

---

17. Expression Evaluation

What is the value of:

```
3 + 4 * 4 + 5 * (4 + 3) - 1
```

A. 83

B. 53

C. 112

D. 48

---

18. Identifier Length (True/False)

Identifiers in Java can be of any length.

A. True

B. False

---

19. Character Data Type

Which data type stores a single character in Java?

A. char

B. boolean

C. byte

D. String

---

20. Return Type (True/False)

`currentTimeMillis()` returns a value of type `int`.

A. True

B. False

Exercise code 1: Area of a Circle

Concept: Variables, Constants, and Basic Input.

Problem: Write a program that reads the radius of a circle from the user and computes the area. Use the constant Math.PI for the calculation.

- **Formula:** $Area = radius \times radius \times \pi$

Java

CircleArea.java

C: > Users > asyra > OneDrive > Desktop > Lab > CircleArea.java > CircleArea > main(String[] args)

```java
import java.util.Scanner;

public class CircleArea {
    Run main | Debug main
    public static void main(String[] args) {

        Scanner input = new Scanner(System.in);

        System.out.print("Enter the radius of the circle: ");
        double radius = input.nextDouble();

        double area = radius * radius * Math.PI;

        System.out.println("Area of the circle is: " + area);

    }
}
```

PROBLEMS 3 OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Enter the radius of the circle:
12

Area of the circle is: 452.3893421169302
```

Exercise code 2: Temperature Converter

Concept: Arithmetic Expressions and Floating-Point Math.

Problem: Write a program that reads a Celsius degree in a double value from the console, then converts it to Fahrenheit and displays the result.

- **Formula:** $Fahrenheit = (9 / 5) \times Celsius + 32$
- *Hint: Be careful with integer division when calculating 9/5!*

Java

TemperatureConverter.java

C: > Users > asyra > OneDrive > Desktop > Lab > TemperatureConverter.java > TemperatureConverter > main(String[] args)

```java
import java.util.Scanner;

public class TemperatureConverter {
    Run main | Debug main
    public static void main(String[] args) {

        Scanner input = new Scanner(System.in);

        System.out.print("Enter the Temperature in Celsius: ");
        double celsius = input.nextDouble();

        double fahrenheit = (9 / 5) * celsius + 32;

        System.out.println("Fahrenheit = " + fahrenheit);

    }
}
```

PROBLEMS 2 OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Enter the Temperature in Celsius:
14

Fahrenheit = 46.0
```

Exercise code 3: Time Decomposition

Concept: Integer Division (/) and Remainder Operator (%).

Problem: Write a program that prompts the user for a total number of seconds (e.g., 500) and converts it into minutes and remaining seconds (e.g., 8 minutes and 20 seconds).

Java

TimeDecomposition.java

C: > Users > asyra > OneDrive > Desktop > Lab > TimeDecomposition.java > TimeDecomposition > main(String[] args)

```java
import java.util.Scanner;

public class TimeDecomposition {
    Run main | Debug main
    public static void main(String[] args) {

        Scanner input = new Scanner(System.in);

        System.out.println("Enter total number of seconds: ");
        int number = input.nextInt();

        int minutes = number / 60;
        int seconds = number % 60;

        System.out.println(number + " seconds is " + minutes + " minutes " + seconds + " seconds");

    }
}
```

PROBLEMS 1 OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Enter total number of seconds:
500

500 seconds is 8 minutes 20 seconds
```

Exercise code 4: Digit Summation

Concept: Modulo and Division for digit extraction.

Problem: Write a program that reads an integer between 0 and 1000 and adds all the digits in the integer. For example, if an integer is 932, the sum of all its digits is $9 + 3 + 2 = 14$.

Java

DigitSum.java

C: > Users > asyra > OneDrive > Desktop > Lab > DigitSum.java > DigitSum > main(String[] args)

```java
import java.util.Scanner;

public class DigitSum {
    Run main | Debug main
    public static void main(String[] args) {

        Scanner input = new Scanner(System.in);
        System.out.print("Enter the number between 0 and 1000: ");
        int number = input.nextInt();

        int digit3 = number % 10;
        int remaining = number / 10;
        int digit2 =remaining % 10;
        int digit1 = remaining / 10;

        int sum = digit1 + digit2 + digit3;

        System.out.println("The sum of all digits = " + sum);

    }
}
```

PROBLEMS 1 OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Enter the number between 0 and 1000:
932

The sum of all digits = 14
```

Exercise code 5: Gratuity Calculator

Concept: Combining multiple inputs and percentages.

Problem: Write a program that reads the subtotal and the gratuity rate (percentage), then computes the gratuity and the total. For example, if the user enters 10 for subtotal and 15% for gratuity rate, the program displays $1.5 as gratuity and $11.5 as total.

Java

GratuityCalculator.java

C: > Users > asyra > OneDrive > Desktop > Lab > GratuityCalculator.java > GratuityCalculator > main(String[] args)

```java
import java.util.Scanner;

public class GratuityCalculator {
    Run main | Debug main
    public static void main(String[] args) {

        Scanner input = new Scanner(System.in);

        System.out.print("Enter subtotal and gratuity rate (%): ");
        int subtotal = input.nextInt();
        double rate = input.nextDouble();

        double gratuity = subtotal * (rate / 100);
        double total = subtotal + gratuity;

        System.out.println(gratuity + " as gratuity and " + total + " as total");

    }
}
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Enter subtotal and gratuity rate (%):
10 15

1.5 as gratuity and 11.5 as total
```

Exercise code 6: Exponentiation and Math Functions

Concept: Using the Math.pow(a, b) method.

Problem: Write a program that displays a table of powers. For each number n from 1 to 5, calculate n^{n+1}.

- *Expected output row 1:* 1 2 1 (where 1 is n, 2 is $n+1$, and 1 is 1^2)

Java

power.java

C: > Users > asyra > OneDrive > Desktop > Lab > power.java > power > main(String[] args)

```java
public class power{
    Run main | Debug main
    public static void main(String[] args){

        System.out.println("n^{n+1}");
        for (int n=1;n<=5;n++){
            int result = (int) Math.pow (n,n+1);

            System.out.println(n + " is " + result);
        }
    }
}
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
n^{n+1}
1 is 1
2 is 8
3 is 81
4 is 1024
5 is 15625
```

Exercise code 7: Numeric Type Casting

Concept: Implicit vs. Explicit Casting.

Problem: Create a program that prompts the user for three integers, calculates their average, and displays it as a double. Note: Ensure the result has decimal precision (e.g., the average of 1, 2, and 4 should be 2.333, not 2.0).

Java

NumericTypeCast.java

C: > Users > asyra > OneDrive > Desktop > Lab > NumericTypeCast.java > NumericTypeCast

```java
import java.util.Scanner;
    public class NumericTypeCast{
        Run main | Debug main
        public static void main(String[] args){

        Scanner input = new Scanner(System.in);
            System.out.println("Enter three integers: ");
            int number1 = input.nextInt();
            int number2 = input.nextInt();
            int number3 = input.nextInt();

            double average = (number1 + number2 + number3) / 3.0;

            System.out.println("The result for average is " + average);
        }
    }
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Enter three integers:
1 2 3

The result for average is 2.0
```