

Contents

1 A Header

2 DP

- 2.1 divide-and-conquer-optimization 1
- 2.2 knuth-optimization 1
- 2.3 li-chao-tree 1
- 2.4 zero-matrix 1

3 DS

- 3.1 Heavy light decomposition 2
- 3.2 MO with update 2
- 3.3 bipartite-disjoint-set-union 2
- 3.4 bitset 2
- 3.5 centroid decomposition 2
- 3.6 dsu-rollback 2
- 3.7 fenwick-tree-2d 3
- 3.8 link cut tree 3
- 3.9 sparse table 2d 4
- 3.10 treap 4
- 3.11 wavelet tree 5

4 Game

- 4.1 HackenBush 6

5 Geo

- 5.1 3dGeo 6
- 5.2 Circle Cover 6
- 5.3 Circle Union Area 6
- 5.4 basic-area-geometry 6
- 5.5 geo-formulae 7
- 5.6 half-plane-intersection 7
- 5.7 heart-of-geometry-2d 8
- 5.8 intersecting-segments-pair 10
- 5.9 radiant-geo 10
- 5.10 vertical-decomposition 13

6 Graph

- 6.1 DMST with solution 14
- 6.2 DMST 14
- 6.3 Flow With Demands 14
- 6.4 articulation-vertex 15
- 6.5 bellman-ford 15
- 6.6 bridge 15
- 6.7 edmond-blossom 15
- 6.8 euler-path 16
- 6.9 hopcraft-karp 16
- 6.10 hungarian-algorithm 17
- 6.11 max-flow-dinic 18
- 6.12 min-cost-max-flow 18
- 6.13 online-bridge 18
- 6.14 scc + 2 Sat 18

7 Math

- 7.1 BerleKampMassey 19
- 7.2 FloorSum 19
- 7.3 Stern Brocot Tree 19
- 7.4 Sum Of Kth Power 19
- 7.5 combination-generator 19
- 7.6 continued-fractions 19
- 7.7 crt anachor 19
- 7.8 discrete-root 19
- 7.9 fast-fourier-transform 20
- 7.10 fast-walsh-hadamard 20
- 7.11 find-root 20
- 7.12 formulas 21
- 7.13 integer-factorization 21
- 7.14 integration-simpson 21
- 7.15 linear-diophantine-equation-gray-code 21
- 7.16 linear-equation-system 21
- 7.17 matrix-determinant 22
- 7.18 matrix-rank 22
- 7.19 nCr mod p^a 22
- 7.20 primality-test 22
- 7.21 prime counting function 22

8 String

- 8.1 Hashing 22
- 8.2 aho-corasick 22
- 8.3 manacher 23
- 8.4 palindromic tree 23
- 8.5 suffix array da 23
- 8.6 suffix-automaton 23
- 8.7 z-algorithm 24

1 A Header

```
#define FastIO ios::sync_with_stdio(false);
cin.tie(0);cout.tie(0)
#include <ext/pb_ds/assoc_container.hpp> // Common file
using namespace __gnu_pbds;
/*
find_by_order(k) --> returns iterator to the kth largest
element counting from 0
order_of_key(val) --> returns the number of items in a set that
are strictly smaller than our item
*/
typedef tree<
int,
null_type,
less<int>,
rb_tree_tag,
tree_order_statistics_node_update>
ordered_set;
//#pragma GCC optimize("O3,unroll-loops")
//#pragma GCC target("avx2,bmi,bmi2,lzcnt")
//mt19937
rng(chrono::system_clock::now().time_since_epoch().count());
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
struct custom_hash {
static uint64_t splitmix64(uint64_t x) {
x += 0x9e3779b97f4a7c15; //Random
x=(x^(x>>30))*0xbf58476d1ce4e5b9; //Random
x=(x^(x>>27))*0x94d049bb133111eb; //Random
return x^(x>>31);
}
```

```
}
const uint64_t FIXED_RANDOM = chrono::
steady_clock::now().time_since_epoch().count();
size_t operator()(uint64_t x) const {
return splitmix64(x + FIXED_RANDOM);
}
size_t operator()(pair<int, int> x) const {
return splitmix64((uint64_t(x.first)<<32) +
x.second + FIXED_RANDOM);
};
}
gp_hash_table<pair<int,int>,int,custom_hash> ht;
namespace my_gcc_ints {
#pragma GCC diagnostic push
#pragma GCC diagnostic ignored "-Wpedantic"
using int128 = __int128;
#pragma GCC diagnostic pop
}
# stresstester GENERATOR SOL1 SOL2 ITERATIONS
for i in $(seq 1 "$4") ; do
echo -en "\rAttempt $i/$4"
$1 > in.txt
$2 < in.txt > out1.txt
$3 < in.txt > out2.txt
diff -y out1.txt out2.txt > diff.txt
if [ $? -ne 0 ] ; then
echo -e "\nTestcase Found:"; cat in.txt
echo -e "\nOutputs:"; cat diff.txt
exit
fi
done
```

2 DP

2.1 divide-and-conquer-optimization

```
int m, n;
vector<long long> dp_before(n), dp_cur(n);
long long C(int i, int j);
// compute dp_cur[l], ... dp_cur[r] (inclusive)
void compute(int l, int r, int optl, int optr){
if (l > r)
return;
int mid = (l + r) >> 1;
pair<long long, int> best = {LLONG_MAX, -1};
for (int k = optl; k <= min(mid, optr); k++){
best = min(best, {(k ? dp_before[k - 1] : 0) + C(k,
mid), k});
}
dp_cur[mid] = best.first;
int opt = best.second;
compute(l, mid - 1, optl, opt);
compute(mid + 1, r, opt, optr);
}
int solve(){
for (int i = 0; i < n; i++)
dp_before[i] = C(0, i);
for (int i = 1; i < m; i++){
compute(0, n - 1, 0, n - 1);
dp_before = dp_cur;
}
return dp_before[n - 1];
}
```

2.2 knuth-optimization

```
int solve() {
int N;
... // read N and input
int dp[N][N], opt[N][N];
auto C = [&](int i, int j) {
... // Implement cost function C.
};
for (int i = 0; i < N; i++) {
opt[i][i] = i;
... // Initialize dp[i][i] according to the problem
}
for (int i = N-2; i >= 0; i--) {
for (int j = i+1; j < N; j++) {
int mn = INT_MAX;
```

```

int cost = C(i, j);
for (int k = opt[i][j-1]; k <= min(j-1,
    opt[i+1][j]); k++) {
    if (mn >= dp[i][k] + dp[k+1][j] + cost) {
        opt[i][j] = k;
        mn = dp[i][k] + dp[k+1][j] + cost;
    }
}
dp[i][j] = mn;
}
cout << dp[0][N-1] << endl;
}

```

2.3 li-chao-tree

```

typedef long long ll;
class LiChaoTree{
    ll L,R;
    bool minimize;
    int lines;
    struct Node{
        pair<ll,ll> line;
        Node *children[2];
        Node(pair<ll,ll> ln= {0,1000000000000000000}){
            line=ln;
            children[0]=0;
            children[1]=0;
        }
    } *root;
    ll f(pair<ll,ll> a, ll x){
        return a.first*x+a.second;
    }
    void clear(Node* &node){
        if(node->children[0]){
            clear(node->children[0]);
        }
        if(node->children[1]){
            clear(node->children[1]);
        }
        delete node;
    }
    void add_line(pair<ll,ll> nw, Node* &node, ll l, ll r){
        if(node==0){
            node=new Node(nw);
            return;
        }
        ll m = (l + r) / 2;
        bool lef = (f(nw, l) < f(node->line,
            l)&&minimize)||(!minimize)&&f(nw, l) >
            f(node->line, l));
        bool mid = (f(nw, m) < f(node->line,
            m)&&minimize)||(!minimize)&&f(nw, m) >
            f(node->line, m));
        if(mid){
            swap(node->line, nw);
        }
        if(r - l == 1){
            return;
        }
        else if(lef != mid){
            add_line(nw, node->children[0], l, m);
        }
        else{
            add_line(nw, node->children[1], m, r);
        }
    }
    ll get(ll x, Node* &node, ll l, ll r){
        ll m = (l + r) / 2;
        if(r - l == 1){
            return f(node->line, x);
        }
        else if(x < m){
            if(node->children[0]==0) return f(node->line, x);
            if(minimize) return min(f(node->line, x), get(x,
                node->children[0], l, m));
            else return max(f(node->line, x), get(x,
                node->children[0], l, m));
        }
        else{

```

```

        if(node->children[1]==0) return f(node->line, x);
        if(minimize) return min(f(node->line, x), get(x,
            node->children[1], m, r));
        else return max(f(node->line, x), get(x,
            node->children[1], m, r));
    }
}
public:
    LiChaoTree(ll l=-1000000001,ll r=1000000001,bool mn=false){
        L=l;
        R=r;
        root=0;
        minimize=mn;
        lines=0;
    }
    void AddLine(pair<ll,ll> ln){
        add_line({ln.first,ln.second},root,L,R);
        lines++;
    }
    int number_of_lines(){
        return lines;
    }
    ll getOptimumValue(ll x){
        return get(x,root,L,R);
    }
    ~LiChaoTree(){
        if(root!=0) clear(root);
    }
};

```

2.4 zero-matrix

```

int zero_matrix(vector<vector<int>> a) {
    int n = a.size();
    int m = a[0].size();
    int ans = 0;
    vector<int> d(m, -1), d1(m), d2(m);
    stack<int> st;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m; ++j) {
            if (a[i][j] == 1)
                d[j] = i;
        }
        for (int j = 0; j < m; ++j) {
            while (!st.empty() && d[st.top()] <= d[j])
                st.pop();
            d1[j] = st.empty() ? -1 : st.top();
            st.push(j);
        }
        while (!st.empty())
            st.pop();
        for (int j = m - 1; j >= 0; --j) {
            while (!st.empty() && d[st.top()] <= d[j])
                st.pop();
            d2[j] = st.empty() ? m : st.top();
            st.push(j);
        }
        while (!st.empty())
            st.pop();
        for (int j = 0; j < m; ++j)
            ans = max(ans, (i - d[j]) * (d2[j] - d1[j] - 1));
    }
    return ans;
}

```

3 DS

3.1 Heavy light decomposition

```

int value[N],Tree[N];
int parent[N], depth[N], heavy[N], head[N], pos[N];
int cur_pos,n;
vector<int > adj[N];
int dfs(int v) {
    int size = 1,max_c_size = 0;
    for (int c : adj[v]) {
        if (c != parent[v]) {
            parent[c] = v, depth[c] = depth[v] + 1;
            int c_size = dfs(c);
            size += c_size;

```

```

        if (c_size > max_c_size)
            max_c_size = c_size, heavy[v] = c;
    }
    return size;
}
void update(int idx, int x,int nn){
    while(idx<nn){
        Tree[idx]+=x; idx+=(idx&-idx);
    }
}
void decompose(int v, int h) {
    head[v] = h, pos[v] = cur_pos;
    update(cur_pos,value[v],n+1);
    cur_pos++;
    if (heavy[v] != -1) decompose(heavy[v], h);
    for (int c : adj[v]) {
        if (c != parent[v] && c != heavy[v])
            decompose(c, c);
    }
}
int query_bit(int idx){
    int sum=0;
    while(idx>0){
        sum+=Tree[idx]; idx--=(idx&-idx);
    }
    return sum;
}
void init_hld(int root,int n){
    memset(Tree, 0,sizeof Tree);
    memset(heavy,-1,sizeof heavy);
    cur_pos = 1; parent[root]=-1;
    assert(dfs(root)==n);
    decompose(root, root);
}
int segment_tree_query(int x,int y){
    if(y<x) swap(x,y);
    return query_bit(y)-query_bit(x-1);
}
int query_hld(int a, int b) {
    int res = 0;
    for (; head[a] != head[b]; b = parent[head[b]]) {
        if (depth[head[a]] > depth[head[b]])
            swap(a, b);
        int cur_heavy_path_max =
            segment_tree_query(pos[head[b]], pos[b]);
        res += cur_heavy_path_max;
    }
    if (depth[a] > depth[b])
        swap(a, b);
    /// now a is the lca or quert(a,b)
    int last_heavy_path_max = segment_tree_query(pos[a],
        pos[b]);
    res += last_heavy_path_max;
    return res;
}

```

3.2 MO with update

```

const int N = 1e5 + 5;
const int P = 2000; //block size = (2*n^2)^(1/3)
struct query{
    int t, l, r, k, i;
};
vector<query> q;
vector<array<int, 3>> upd;
vector<int> ans,a;
void add(int x);void rem(int x);int get_answer();
void mos_algorithm(){
    sort(q.begin(), q.end(), [](const query &a, const query &b){
        if (a.t / P != b.t / P) return a.t < b.t;
        if (a.l / P != b.l / P) return a.l < b.l;
        if ((a.l / P) & 1) return a.r < b.r;
        return a.r > b.r;
    });
    for(int i=upd.size()-1;i>=0;--i) a[upd[i][0]] = upd[i][1];
    int L = 0, R = -1, T = 0;
    auto apply = [&](int i, int fl){
        int p = upd[i][0], x = upd[i][fl + 1];

```

```

    if (L <= p && p <= R){ rem(a[p]); add(x);}
    a[p] = x;
};
ans.clear(); ans.resize(q.size());
for (auto qr : q){
    int t = qr.t, l = qr.l, r = qr.r, k = qr.k;
    while (T < t) apply(T++, 1);
    while (T > t) apply(--T, 0);
    while (R < r) add(a[+R]);
    while (L > l) add(a[--L]);
    while (R > r) rem(a[R--]);
    while (L < l) rem(a[L++]);
    ans[qr.i] = get_answer();
}
}
void TEST_CASES(int cas){
cin>>n>>m; a.resize(n); for(int i=0;i<n;i++) cin>>a[i];
for(int i=0;i<m;i++){ int tp; scanf("%d", &tp);
    if (tp == 1){ int l, r, k; cin>>l>r>k;
        q.push_back({upd.size(), l - 1, r - 1, k, q.size()});}
    else{int p, x;cin>>p>x;--p;
        upd.push_back({p, a[p], x}); a[p] = x;
    }
}
mos_algorithm();

```

3.3 bipartite-disjoint-set-union

```

void make_set(int v) {
parent[v] = make_pair(v, 0); rank[v] = 0; bipartite[v] = true;}
pair<int, int> find_set(int v) { if (v != parent[v].first) {
int parity = parent[v].second; parent[v] = find_set(
parent[v].first); parent[v].second ^= parity;}
return parent[v];
}
void add_edge(int a, int b) {
pair<int, int> pa = find_set(a);
a = pa.first; int x = pa.second;
pair<int, int> pb = find_set(b); b = pb.first;
int y = pb.second;
if (a == b) {
    if (x == y) bipartite[a] = false;
} else {
    if (rank[a] < rank[b]) swap (a, b);
    parent[b] = make_pair(a, x^y^1);
    bipartite[a] ^= bipartite[b];
    if (rank[a] == rank[b]) ++rank[a];
}
}
bool is_bipartite(int v){ return bipartite[find_set(v).first];}

```

3.4 bitset

```

int LEN;// length of Bitset array t
struct Bitset{
ull t[N/64+5]; Bitset(){memset(t,0,sizeof t);}
void set(int p){ t[p>>6]=1llu<<(p&63); }
void shift(){ ull last=0llu;
for(int i=0;i<LEN;i++){
    ull curr=t[i]>>63llu; (t[i]<=&1)|=last; last =curr;
}
}
int count(){ int ret=0;
for(int i=0;i<LEN;i++) ret+=__builtin_popcountll(t[i]);
return ret;
}
Bitset &operator = (Bitset const&b){
memcpy(t,b.t,sizeof (t)); return *this;
}
Bitset &operator |=(Bitset &b){
for(int i=0;i<LEN;i++)t[i]|=b.t[i]; return *this;
}
Bitset &operator &=(Bitset &b){
for(int i=0;i<LEN;i++) t[i]&=b.t[i]; return *this;
}
Bitset &operator ^=(Bitset &b){
for(int i=0;i<LEN;i++) t[i]^=b.t[i]; return *this;
}
}

```

```

};
Bitset operator-(const Bitset &a,const Bitset &b){
    Bitset tmp; ull last=0;
    for(int i=0;i<LEN;i++){ ull curr=(a.t[i]< b.t[i] + last);
        tmp.t[i]=a.t[i]-b.t[i]-last; last = curr;
    }
    return tmp;
}
// https://loj.ac/p/6564 , string s,t, m_old = 0
// lcs formula: let x = m_old / Occurance set of s [char or t]
// m_new = ((x - ((m_old<<1)+1)) ^x)&x; finally m_new.count()

```

3.5 centroid decomposition

```

set<int> g[N];
int par[N],sub[N],level[N],ans[N]; int DP[LOGN][N];
int n,m; int nn;
void dfs1(int u,int p){
    sub[u]=1; nn++;
    for(auto it=g[u].begin();it!=g[u].end();it++) if(*it!=p){
        dfs1(*it,u); sub[u]+=sub[*it];}
}
int dfs2(int u,int p){
    for(auto it=g[u].begin();it!=g[u].end();it++)
        if(*it!=p && sub[*it]>nn/2)
            return dfs2(*it,u);
    return u;
}
void decompose(int root,int p){
    nn=0; dfs1(root,root); int centroid = dfs2(root,root);
    if(p==-1)p=centroid; par[centroid]=p;
    for(auto it=g[centroid].begin();it!=g[centroid].end();it++){
        g[*it].erase(centroid); decompose(*it,centroid); }
    g[centroid].clear();
}

```

3.6 dsu-rollback

```

struct dsu_save {
    int v, rnk, u, rnku; dsu_save() {}
    dsu_save(int _v, int _rnk, int _u, int _rnku)
        : v(_v), rnk(_rnk), u(_u), rnku(_rnku) {}
};
struct dsu_with_rollback {
    vector<int> p, rnk; int comps; stack<dsu_save> op;
    dsu_with_rollback() {}
    dsu_with_rollback(int n) { p.resize(n); rnk.resize(n);
        for (int i = 0; i < n; i++) { p[i] = i; rnk[i] = 0; }
        comps = n;
    }
    int find_set(int v){return (v == p[v])?v:find_set(p[v]);}
    bool unite(int v, int u) { v = find_set(v); u = find_set(u);
        if (v == u) return false; comps--;
        if (rnk[v] > rnk[u]) swap(v, u);
        op.push(dsu_save(v, rnk[v], u, rnk[u])); p[v] = u;
        if (rnk[u] == rnk[v]) rnk[u]++; return true;
    }
    void rollback() { if (op.empty()) return;
        dsu_save x = op.top(); op.pop(); comps++; p[x.v] = x.v;
        rnk[x.v] = x.rnk; p[x.u] = x.u; rnk[x.u] = x.rnk;
    }
};
struct query {
    int v, u; bool united;
    query(int _v, int _u) : v(_v), u(_u) {}
};
struct QueryTree {
    vector<vector<query>> t; dsu_with_rollback dsu; int T;
    QueryTree() {}
    QueryTree(int _T, int n) : T(_T) {
        dsu = dsu_with_rollback(n); t.resize(4 * T + 4); }
    void add_to_tree(int v,int l,int r,int ul,int ur,query& q){
        if (ul > ur) return;
        if (l == ul && r == ur) { t[v].push_back(q); return; }
        int mid = (l + r) / 2;
        add_to_tree(2 * v, l, mid, ul, min(ur, mid), q);
        add_to_tree(2*v+1,mid+1,r,max(ul, mid + 1), ur, q);
    }
    void add_query(query q, int l, int r) {

```

```

        add_to_tree(1, 0, T - 1, l, r, q); }
    void dfs(int v, int l, int r, vector<int>& ans) {
        for (query& q : t[v]) q.united = dsu.unite(q.v, q.u);
        if (l == r) ans[l] = dsu.comps;
        else { int mid = (l + r) / 2;
            dfs(2 * v, l, mid, ans); dfs(2 * v + 1, mid + 1, r, ans); }
        for (query q : t[v]) { if (q.united) dsu.rollback(); }
    }
    vector<int> solve() {
        vector<int> ans(T); dfs(1, 0, T - 1, ans); return ans;
    }
};

```

3.7 fenwick-tree-2d

```

struct FenwickTree2D {
    vector<vector<int>>> bit;
    int n, m;
    // init(...) { ... }
    int sum(int x, int y) {
        int ret = 0;
        for (int i = x; i >= 0; i = (i & (i + 1)) - 1)
            for (int j = y; j >= 0; j = (j & (j + 1)) - 1)
                ret += bit[i][j];
        return ret;
    }
    void add(int x, int y, int delta) {
        for (int i = x; i < n; i = i | (i + 1))
            for (int j = y; j < m; j = j | (j + 1))
                bit[i][j] += delta;
    }
};

```

3.8 link cut tree

```

const int MOD = 998244353;
int sum(int a, int b) {
    return a+b >= MOD ? a+b-MOD : a+b;
}
int mul(int a, int b) {
    return (a*1LL*b)%MOD;
}
typedef pair< int , int >Linear;
Linear compose(const Linear &p, const Linear &q) {
    return Linear(mul(p.first, q.first), sum(mul(q.second,
        p.first), p.second));
}
struct SplayTree {
    struct Node {
        int ch[2] = {0, 0}, p = 0;
        long long self = 0, path = 0; // Path aggregates
        long long sub = 0, vir = 0; // Subtree aggregates
        bool flip = 0; // Lazy tags
        int size = 1;
        Linear _self{1, 0}, _path_shoja{1, 0}, _path_ulta{1, 0};
    };
    vector<Node> T;
    SplayTree(int n) : T(n + 1) {
        T[0].size = 0;
    }
    void push(int x) {
        if (!x || !T[x].flip) return;
        int l = T[x].ch[0], r = T[x].ch[1];
        T[l].flip ^= 1, T[r].flip ^= 1;
        swap(T[x].ch[0], T[x].ch[1]);
        T[x].flip = 0;
        swap(T[x]._path_shoja, T[x]._path_ulta);
    }
    void pull(int x) {
        int l = T[x].ch[0], r = T[x].ch[1]; push(l); push(r);
        T[x].size = T[l].size + T[r].size + 1;
        T[x].path = T[l].path + T[x].self + T[r].path;
        T[x].sub = T[x].vir + T[l].sub + T[r].sub + T[x].self;
        T[x]._path_shoja = compose(T[r]._path_shoja,
            compose(T[x]._self, T[l]._path_shoja));
        T[x]._path_ulta = compose(T[l]._path_ulta,
            compose(T[x]._self, T[r]._path_ulta));
    }
};

```

```

}
void set(int x, int d, int y) {
    T[x].ch[d] = y; T[y].p = x; pull(x);
}
void splay(int x) {
    auto dir = [&](int x) {
        int p = T[x].p; if (!p) return -1;
        return T[p].ch[0] == x ? 0 : T[p].ch[1] == x ? 1 : -1;
    };
    auto rotate = [&](int x) {
        int y = T[x].p, z = T[y].p, dx = dir(x), dy = dir(y);
        set(y, dx, T[x].ch[!dx]);
        set(x, !dx, y);
        if (~dy) set(z, dy, x);
        T[x].p = z;
    };
    for (push(x); ~dir(x); ) {
        int y = T[x].p, z = T[y].p;
        push(z); push(y); push(x);
        int dx = dir(x), dy = dir(y);
        if (~dy) rotate(dx != dy ? x : y);
        rotate(x);
    }
}
int KthNext(int x, int k) {
    assert(k > 0);
    splay(x);
    x = T[x].ch[1];
    if (T[x].size < k) return -1;
    while (true) {
        push(x);
        int l = T[x].ch[0], r = T[x].ch[1];
        if (T[l].size+1 == k) return x;
        if (k <= T[l].size) x = l;
        else k -= T[l].size+1, x = r;
    }
}
};
struct LinkCut : SplayTree {
    LinkCut(int n) : SplayTree(n) {}
    int access(int x) {
        int u = x, v = 0;
        for (; u; v = u, u = T[u].p) {
            splay(u);
            int& ov = T[u].ch[1];
            T[u].vir += T[ov].sub;
            T[u].vir -= T[v].sub;
            ov = v; pull(u);
        }
        splay(x);
        return v;
    }
    void reroot(int x) {
        access(x); T[x].flip ^= 1; push(x);
    }
    //makes v parent of u (optional: u must be a root)
    void Link(int u, int v) {
        reroot(u); access(v);
        T[v].vir += T[u].sub;
        T[u].p = v; pull(v);
    }
    //removes edge between u and v
    void Cut(int u, int v) {
        int _u = FindRoot(u);
        reroot(u); access(v);
        T[v].ch[0] = T[u].p = 0; pull(v);
        reroot(_u);
    }
    // Rooted tree LCA. Returns 0 if u and v arent connected.
    int LCA(int u, int v) {
        if (u == v) return u;
        access(u); int ret = access(v);
        return T[u].p ? ret : 0;
    }
    // Query subtree of u where v is outside the subtree.
    long long Subtree(int u, int v) {

```

```

        int _v = FindRoot(v);
        reroot(v); access(u);
        long long ans = T[u].vir + T[u].self;
        reroot(_v);
        return ans;
    }
    // Query path [u..v]
    long long Path(int u, int v) {
        int _u = FindRoot(u);
        reroot(u); access(v);
        long long ans = T[v].path;
        reroot(_u);
        return ans;
    }
    Linear_Path(int u, int v) {
        reroot(u); access(v); return T[v]._path_shoja;
    }
    // Update vertex u with value v
    void Update(int u, long long v) {
        access(u); T[u].self = v; pull(u);
    }
    // Update vertex u with value v
    void _Update(int u, Linear v) {
        access(u); T[u]._self = v; pull(u);
    }
    int FindRoot(int u) {
        access(u);
        while (T[u].ch[0]) {
            u = T[u].ch[0];
            push(u);
        }
        access(u);
        return u;
    }
    //k-th node (0-indexed) on the path from u to v
    int KthOnPath(int u, int v, int k) {
        if (u == v) return k == 0 ? u : -1;
        int _u = FindRoot(u);
        reroot(u); access(v);
        int ans = KthNext(u, k);
        reroot(_u);
        return ans;
    }
};
int main() {
    cin >> n >> q;
    LinkCut lct(n);
    for (int i = 1; i <= n; i++) {
        Linear l;
        cin >> l.first >> l.second;
        lct._Update(i, l);
    }
    for (int i = 1; i < n; i++) {
        int u, v;
        cin >> u >> v;
        lct.Link(u+1, v+1);
    }
    while (q--) {
        int op;
        cin >> op;
        if (op == 0) {
            int u, v, w, x;
            cin >> u >> v >> w >> x;
            lct.Cut(u+1, v+1);
            lct.Link(w+1, x+1);
        } else if (op == 1) {
            int p; Linear l;
            cin >> p >> l.first >> l.second;
            lct._Update(p+1, l);
        } else {
            int u, v, x;
            cin >> u >> v >> x;
            Linear l = lct._Path(u+1, v+1);
            cout << sum(mul(l.first, x), l.second) << "\n";
        }
    }
    return 0;
}

```

3.9 sparse table 2d

```

const int N=500; const int K = 8 ; /// k >= ceil(lg22(n)) +1
int arr[N][N]; int st[K+1][K+1][N][N]; int lg2[N+1];
void ini(){ lg2[1] = 0;
    for (int i = 2; i <= N; i++) lg2[i] = lg2[i/2] + 1; }
int f(int i, int j){ return max(i, j); }
void pre( int n, int m){
    for(int x=0; x<=K; x++){
        for(int y=0; y<=K; y++){
            for(int i=0; i<n; i++){
                for(int j=0; j<m; j++){
                    if(i+(1<<x)>n or j+(1<<y)>m) continue;
                    if(x>0) st[x][y][i][j] = f(st[x-1][y][i][j], st[x-1][y][i+(1<<(x-1))][j]);
                    else if(y>0) st[x][y][i][j] = f(st[x][y-1][i][j], st[x][y-1][i][j+(1<<(y-1))]);
                    else st[x][y][i][j] = f(arr[i][j], arr[i][j]);
                } } } }
}
int getf( int R1 ,int C1 , int R2 , int C2){
    if(R1>R2) swap(R1,R2); if(C1>C2) swap(C1,C2);
    int x = lg2[R2 - R1 + 1]; int y = lg2[C2 - C1 + 1];
    return f(f(st[x][y][R1][C1], st[x][y][R2-(1<<x)+1][C1]), st[x][y][R1][C2-(1<<y)+1], st[x][y][R2-(1<<x)+1][C2-(1<<y)+1]);
}

```

3.10 treap

```

template <class T>
class treap{
    struct item{
        int prior, cnt;
        T key;
        item *l,*r;
        item(T v) {
            key=v;
            l=NULL;
            r=NULL;
            cnt=1;
            prior=rand();
        }
    } *root,*node;
    int cnt (item * it){
        return it ? it->cnt : 0;
    }
    void upd_cnt (item * it){
        if (it) it->cnt = cnt(it->l) + cnt(it->r) + 1;
    }
    void split (item * t, T key, item * & l, item * & r){
        if (!t) l = r = NULL;
        else if (key < t->key)
            split (t->l, key, l, t->l), r = t;
        else
            split (t->r, key, t->r, r), l = t;
        upd_cnt(t);
    }
    void insert (item * & t, item * it){
        if (!t) t = it;
        else if (it->prior > t->prior)
            split (t, it->key, it->l, it->r), t = it;
        else
            insert (it->key < t->key ? t->l : t->r, it);
        upd_cnt(t);
    }
    // keys(l) < keys(r)
    void merge (item * & t, item * l, item * r){
        if (!l || !r) t = l ? l : r;
        else if (l->prior > r->prior)
            merge (l->r, l->r, r), t = l;
        else
            merge (r->l, l, r->l), t = r;
        upd_cnt(t);
    }
    void erase (item * & t, T key){
        if (t->key == key)
            merge (t, t->l, t->r);
    }
}

```

```

    else
        erase (key < t->key ? t->l : t->r, key);
    upd_cnt(t);
}
T elementAt(item * &t,int key){
    T ans;
    if(cnt(t->l)==key) ans=t->key;
    else if(cnt(t->l)>key) ans=elementAt(t->l,key);
    else ans=elementAt(t->r,key-1-cnt(t->l));
    upd_cnt(t);
    return ans;
}
item * unite (item * l, item * r){
    if (!l || !r) return l ? l : r;
    if (l->prior < r->prior) swap (l, r);
    item * lt, * rt;
    split (r, l->key, lt, rt);
    l->l = unite (l->l, lt);
    l->r = unite (l->r, rt);
    upd_cnt(l);
    upd_cnt(r);
    return l;
}
void heapify (item * t){
    if (!t) return;
    item * max = t;
    if (t->l != NULL && t->l->prior > max->prior)
        max = t->l;
    if (t->r != NULL && t->r->prior > max->prior)
        max = t->r;
    if (max != t)
    {
        swap (t->prior, max->prior);
        heapify (max);
    }
}
item * build (T * a, int n){
    if (n == 0) return NULL;
    int mid = n / 2;
    item * t = new item (a[mid], rand ());
    t->l = build (a, mid);
    t->r = build (a + mid + 1, n - mid - 1);
    heapify (t);
    return t;
}
void output (item * t,vector<T> &arr){
    if (!t) return;
    output (t->l,arr);
    arr.push_back(t->key);
    output (t->r,arr);
}
public:
    treap(){
        root=NULL;
    }
    treap(T *a,int n){
        build(a,n);
    }
    void insert(T value){
        node=new item(value);
        insert(root,node);
    }
    void erase(T value){
        erase(root,value);
    }
    T elementAt(int position){
        return elementAt(root,position);
    }
    int size(){
        return cnt(root);
    }
    void output(vector<T> &arr){
        output(root,arr);
    }
    int range_query(T l,T r){ //[(l,r]
        item *previous,*next,*current;
        split(root,l,previous,current);
        split(current,r,current,next);
        int ans=cnt(current);

```

```

        merge(root,previous,current);
        merge(root,root,next);
        previous=NULL;
        current=NULL;
        next=NULL;
        return ans;
    }
};
template <class T>
class implicit_treap{
    struct item{
        int prior, cnt;
        T value;
        bool rev;
        item *l,*r;
        item(T v){
            value=v;
            rev=false;
            l=NULL;
            r=NULL;
            cnt=1;
            prior=rand();
        }
    } *root,*node;
    int cnt (item * it){
        return it ? it->cnt : 0;
    }
    void upd_cnt (item * it){
        if (it)
            it->cnt = cnt(it->l) + cnt(it->r) + 1;
    }
    void push (item * it){
        if (it && it->rev){
            it->rev = false;
            swap (it->l, it->r);
            if (it->l) it->l->rev ^= true;
            if (it->r) it->r->rev ^= true;
        }
    }
    void merge (item * &t, item * l, item * r){
        push (l);
        push (r);
        if (!l || !r)
            t = l ? l : r;
        else if (l->prior > r->prior)
            merge (l->r, l->r, r), t = l;
        else
            merge (r->l, l, r->l), t = r;
        upd_cnt (t);
    }
    void split (item * t, item * &l, item * &r, int key, int
        add = 0){
        if (!t)
            return void( l = r = 0 );
        push (t);
        int cur_key = add + cnt(t->l);
        if (key <= cur_key)
            split (t->l, l, t->l, key, add), r = t;
        else
            split (t->r, t->r, r, key, add + 1 + cnt(t->l)), l
                = t;
        upd_cnt (t);
    }
    void insert(item * &t,item * element,int key){
        item *l,*r;
        split(t,l,r,key);
        merge(l,l,element);
        merge(t,l,r);
        l=NULL;
        r=NULL;
    }
    T elementAt(item * &t,int key){
        push(t);
        T ans;
        if(cnt(t->l)==key) ans=t->value;
        else if(cnt(t->l)>key) ans=elementAt(t->l,key);
        else ans=elementAt(t->r,key-1-cnt(t->l));
        return ans;
    }
    void erase (item * &t, int key){

```

```

        push(t);
        if(!t) return;
        if (key == cnt(t->l))
            merge (t, t->l, t->r);
        else if(key<cnt(t->l))
            erase(t->l,key);
        else
            erase(t->r,key-cnt(t->l)-1);
        upd_cnt(t);
    }
    void reverse (item * &t, int l, int r){
        item *t1, *t2, *t3;
        split (t, t1, t2, l);
        split (t2, t2, t3, r-l+1);
        t2->rev ^= true;
        merge (t, t1, t2);
        merge (t, t, t3);
    }
    void cyclic_shift(item * &t,int L,int R){
        if(L==R) return;
        item *l,*r,*m;
        split(t,t,l,L);
        split(l,l,m,R-L+1);
        split(l,l,r,R-L);
        merge(t,t,r);
        merge(t,t,l);
        merge(t,t,m);
        l=NULL;
        r=NULL;
        m=NULL;
    }
    void output (item * t,vector<T> &arr){
        if (!t) return;
        push (t);
        output (t->l,arr);
        arr.push_back(t->value);
        output (t->r,arr);
    }
    public:
        implicit_treap(){
            root=NULL;
        }
        void insert(T value,int position){
            node=new item(value);
            insert(root,node,position);
        }
        void erase(int position){
            erase(root,position);
        }
        void reverse(int l,int r){
            reverse(root,l,r);
        }
        T elementAt(int position){
            return elementAt(root,position);
        }
        void cyclic_shift(int L,int R){
            cyclic_shift(root,L,R);
        }
        int size(){
            return cnt(root);
        }
        void output(vector<T> &arr){
            output(root,arr);
        }
};

```

3.11 wavelet tree

```

#include <bits/stdc++.h>
using namespace std;
#define fo(i,n) for(i=0;i<n;i++)
#define ll long long
#define pb push_back
#define mp make_pair
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;
typedef vector<int> vi;
const int N = 3e5, M = N;
//=====

```

```

const int MAX = 1e6;
int a[N];
struct wavelet_tree{
#define vi vector<int>
#define pb push_back
    int lo, hi;
    wavelet_tree *l=0, *r=0;
    vi b;
    vi c; // c holds the prefix sum of elements
    //nos are in range [x,y]
    //array indices are [from, to)
    wavelet_tree(int *from, int *to, int x, int y){
        lo = x, hi = y;
        if( from >= to)
            return;
        if( hi == lo ){
            b.reserve(to-from+1);
            b.pb(0);
            c.reserve(to-from+1);
            c.pb(0);
            for(auto it = from; it != to; it++){
                b.pb(b.back() + 1);
                c.pb(c.back()+*it);
            }
            return ;
        }
        int mid = (lo+hi)/2;
        auto f = [mid](int x){
            return x <= mid;
        };
        b.reserve(to-from+1);
        b.pb(0);
        c.reserve(to-from+1);
        c.pb(0);
        for(auto it = from; it != to; it++){
            b.pb(b.back() + f(*it));
            c.pb(c.back() + *it);
        }
        //see how lambda function is used here
        auto pivot = stable_partition(from, to, f);
        l = new wavelet_tree(from, pivot, lo, mid);
        r = new wavelet_tree(pivot, to, mid+1, hi);
    }
    // swap a[i] with a[i+1] , if a[i]!=a[i+1] call
    swapadjacent(i)
    void swapadjacent(int i){
        if(lo == hi)
            return;
        b[i] = b[i-1] + b[i+1] - b[i];
        c[i] = c[i-1] + c[i+1] - c[i];
        if( b[i+1]-b[i] == b[i] - b[i-1]){
            if(b[i]-b[i-1])
                return this->l->swapadjacent(b[i]);
            else
                return this->r->swapadjacent(i-b[i]);
        }
        else
            return ;
    }
    //kth smallest element in [l, r]
    int kth(int l, int r, int k){
        if(l > r)
            return 0;
        if(lo == hi)
            return lo;
        int inLeft = b[r] - b[l-1];
        int lb = b[l-1]; //amt of nos in first (l-1) nos that
        go in left
        int rb = b[r]; //amt of nos in first (r) nos that go in
        left
        if(k <= inLeft)
            return this->l->kth(lb+1, rb, k);
        return this->r->kth(l-lb, r-rb, k-inLeft);
    }
    //count of nos in [l, r] Less than or equal to k
    int LTE(int l, int r, int k){
        if(l > r or k < lo)
            return 0;
        if(hi <= k)
            return r - l + 1;

```

```

        int lb = b[l-1], rb = b[r];
        return this->l->LTE(lb+1, rb, k) + this->r->LTE(l-lb,
            r-rb, k);
    }
    //count of nos in [l, r] equal to k
    int count(int l, int r, int k){
        if(l > r or k < lo or k > hi)
            return 0;
        if(lo == hi)
            return r - l + 1;
        int lb = b[l-1], rb = b[r], mid = (lo+hi)/2;
        if(k <= mid)
            return this->l->count(lb+1, rb, k);
        return this->r->count(l-lb, r-rb, k);
    }
    //sum of nos in [l, r] less than or equal to k
    int sumk(int l, int r, int k){
        if(l > r or k < lo)
            return 0;
        if(hi <= k)
            return c[r] - c[l-1];
        int lb = b[l-1], rb = b[r];
        return this->l->sumk(lb+1, rb, k) + this->r->sumk(l-lb,
            r-rb, k);
    }
    wavelet_tree(){
        if(l)
            delete l;
        if(r)
            delete r;
    }
}
int main(){
    ios_base::sync_with_stdio(false);
    cin.tie(NULL);
    srand(time(NULL));
    int i,n,k,j,q,l,r;
    cin >> n;
    fo(i, n) cin >> a[i+1];
    wavelet_tree T(a+1, a+n+1, 1, MAX);
    cin >> q;
    while(q--){
        int x;
        cin >> x;
        cin >> l >> r >> k;
        if(x == 0){
            //kth smallest
            cout << "Kth smallest: ";
            cout << T.kth(l, r, k) << endl;
        }
        if(x == 1){
            //less than or equal to K
            cout << "LTE: ";
            cout << T.LTE(l, r, k) << endl;
        }
        if(x == 2){
            //count occurrence of K in [l, r]
            cout << "Occurrence of K: ";
            cout << T.count(l, r, k) << endl;
        }
        if(x == 3){
            //sum of elements less than or equal to K in [l, r]
            cout << "Sum: ";
            cout << T.sumk(l, r, k) << endl;
        }
    }
    return 0;
}

```

4 Game

4.1 HackenBush

```

/* tree case: g[u] = for all v : XOR[ g[v] + 1 ]
lose if no moves available
1. Colon Principle: Grundy number of a tree is the
xor of Grundy number of child subtrees.
2. Fusion Principle: Consider a pair of adjacent
vertices u, v that has another path (i.e.,
they are in a cycle). Then, we can contract u
and v without changing Grundy number.

```

We first decompose graph into two-edge connected components. Then, by contracting each components by using Fusion Principle, we obtain a tree (and many self loops) that has the same Grundy number to the original graph. By using Colon Principle, we can compute the Grundy number. $O(m + n)$. */

```

struct hackenbush {
    int n; vector<vector<int>> adj;
    hackenbush(int n) : n(n), adj(n) { }
    void add_edge(int u, int v) {
        adj[u].push_back(v);
        if(u!=v) adj[v].push_back(u);
    }
    int grundy(int r) {
        vector<int> num(n), low(n); int t = 0;
        function<int(int, int)> dfs=[&](int p,int u) {
            num[u] = low[u] = ++t; int ans = 0;
            for (int v : adj[u]) {
                if (v == p) { p += 2 * n; continue; }
                if (num[v] == 0) {
                    int res = dfs(u, v);
                    low[u] = min(low[u], low[v]);
                    if (low[v] > num[u]) ans ^= (1+res)^1;
                    else ans ^= res; // non bridge
                }
                else low[u] = min(low[u], num[v]);
            }
            if (p > n) p -= 2 * n;
            for (int v : adj[u])
                if (v != p && num[u] <= num[v]) ans ^= 1;
            return ans;
        };
        return dfs(-1, r);
    }
};

```

5 Geo

5.1 3dGeo

```

int dcmp(double x) { return abs(x) < EPS ? 0 : (x<0 ? -1 : 1); }
double degreeToRadian(double rad) { return rad*PI/180; }
struct Point {
    double x, y, z; Point() : x(0), y(0), z(0) {}
    Point(double X, double Y, double Z) : x(X), y(Y), z(Z) {}
    Point operator + (const Point& u) const {
        return Point(x + u.x, y + u.y, z + u.z);
    }
    Point operator - (const Point& u) const {
        return Point(x - u.x, y - u.y, z - u.z);
    }
    Point operator * (const double u) const {
        return Point(x * u, y * u, z * u);
    }
    Point operator / (const double u) const {
        return Point(x / u, y / u, z / u);
    }
};
double dot(Point a, Point b){ return a.x*b.x+a.y*b.y+a.z*b.z; }
Point cross(Point a, Point b) { return
    Point(a.y*b.z - a.z*b.y, a.z*b.x - a.x*b.z, a.x*b.y - a.y*b.x);
}
double length(Point a) { return sqrt(dot(a, a)); }
double distance(Point a, Point b) { return length(a-b); }
Point unit(const Point &p) { return p/length(p); }
// Rotate p around axis x, with angle radians.
Point rotate(Point p, Point axis, double angle) {
    axis = unit(axis); Point comp1 = p * cos(angle);
    Point comp2 = axis * (1-cos(angle)) * dot(axis, p);
    Point comp3 = cross(axis, p) * sin(angle);
    return comp1 + comp2 + comp3;
}
struct Line {Point a, v;}; //a+tv
// returns the distance from point a to line l
double distancePointLine(Point p, Line l) {
    return length(cross(l.v, p - l.a)) / length(l.v);
}
// distance from Line ab to Line cd
double distanceLineLine(Line a, Line b) {
    Point cr = cross(a.v, b.v); double crl = length(cr);
    if (dcmp(crl) == 0) return distancePointLine(a.a, b);
    return abs(dot(cr, a.a-b.a))/crl;
}
struct Plane {

```

```

Point normal; /// Normal = (A, B, C)
double d; /// dot(Normal) = d <--> Ax + By + Cz = d
Point P; /// anyPoint on the plane, optional
Plane(Point normal, double d) {
    double len = length(normal); assert(dcmp(len) > 0);
    normal = normal / len; d = d / len;
    if (dcmp(normal.x)) P = Point(d/normal.x, 0, 0);
    else if (dcmp(normal.y)) P = Point(0, d/normal.y, 0);
    else P = Point(0, 0, d/normal.z);
}
///Plane given by three Non-Collinear Points
Plane(Point a, Point b, Point c) {
    normal = unit(cross(b-a, c-a)); d = dot(normal,a); P=a;
}
bool onPlane(Point a) { return dcmp(dot(normal,a)-d)== 0;}
double distance(Point a) { return abs(dot(normal, a) - d);}
double isParallel(Line l){return dcmp(dot(l.v,normal))==0;}
///return t st l.a + t*l.v is a point on the plane, check
///parallel first
double intersectLine(Line l) {
    return dot(P-l.a, normal)/dot(l.v, normal); } };

```

5.2 Circle Cover

```

///Check if the all of the area of circ(0, R) in
///Circ(00, RR) is covered by some other circle
bool CoverCircle(PT O, double R, vector<PT> &cen,
    vector<double> &rad, PT OO, double RR) {
    int n = cen.size();
    vector<pair<double, double>> arcs;
    for (int i=0; i<n; i++) {
        PT P = cen[i]; double r = rad[i];
        if (i!=0 && R + sqrt(dist2(O, P))<r) return 1;
        if (i==0 && r + sqrt(dist2(O, P))<R) return 1;
        vector<PT> inter =
            CircleCircleIntersection(O, P, R, r);
        if (inter.size() <= 1) continue;
        PT X = inter[0], Y = inter[1];
        if (cross(O, X, Y) < 0) swap(X, Y);
        if (!(cross(O, X, P) >= 0 &&
            cross(O, Y, P) <= 0)) swap(X, Y);
        if (i==0) swap(X, Y);
        X = X-O; Y=Y-O;
        double ll = atan2(X.y, X.x);
        double rr = atan2(Y.y, Y.x);
        if (rr < ll) rr += 2*PI;
        arcs.emplace_back(ll, rr);
    }
    if (arcs.empty()) return false;
    sort(arcs.begin(), arcs.end());
    double st = arcs[0].ff, en = arcs[0].ss, ans = 0;
    for (int i=1; i<arcs.size(); i++) {
        if (arcs[i].first <= en + EPS)
            en = max(en, arcs[i].second);
        else st = arcs[i].first, en = arcs[i].second;
        ans = max(ans, en-st);
    }
    return ans >= 2*PI;
}

```

5.3 Circle Union Area

```

struct Point {
    LD x,y ;
    LD operator*(const Point &a)const {
        return x*a.y-y*a.x;}
    LD operator/(const Point &a)const {
        return sqrt((a.x-x)*(a.x-x)+(a.y-y)*(a.y-y));}
}po[N];
LD r[N];
int sgn(LD x) {return fabs(x)<EPS?0:(x>0.0?1:-1);}
pair<LD,bool> ARG[2*N] ;
LD cir_union(Point c[],LD r[],int n) {
    LD sum = 0.0 , sum1 = 0.0 ,d,p1,p2,p3 ;
    for(int i = 0 ; i < n ; i++) {
        bool f = 1 ;
        for(int j = 0 ; f&&j<n ; j++)
            if(i!=j && sgn(r[j]-r[i]-c[i]/c[j])!=-1)f=0;
        if(!f) swap(r[i],r[--n]),swap(c[i--],c[n]);
    }
}

```

```

}
for(int i = 0; i < n; i++) {
    int k = 0, cnt = 0;
    for(int j = 0; j < n; j++) {
        if(i!=j&&sgn((d=c[i]/c[j])-r[i]-r[j])<=0){
            p3=acos((r[i]*r[i]+d*d-r[j]*r[j])/
                (2.0*r[i]*d));
            p2=atan2(c[j].y-c[i].y,c[j].x-c[i].x);
            p1 = p2-p3; p2 = p2+p3;
            if(sgn(p1+PI)==-1) p1+=2*PI,cnt++;
            if(sgn(p2-PI)==1) p2-=2*PI,cnt++;
            ARG[k++] = make_pair(p1,0);
            ARG[k++] = make_pair(p2,1);
        }
    }
    if(k) {
        sort(ARG,ARG+k) ;
        p1 = ARG[k-1].first-2*PI;
        p3 = r[i]*r[i] ;
        for(int j = 0 ; j < k ; j++) {
            p2 = ARG[j].first;
            if(cnt==0) {
                sum+=(p2-p1-sin(p2-p1))*p3 ;
                sum1+=(c[i]+Point(cos(p1),sin(p1))*
                    r[i])*(c[i]+
                    Point(cos(p2),sin(p2))*r[i]);
            }
            p1 = p2;
            ARG[j].second ? cnt--:cnt++;
        }
        else sum += 2*PI*r[i]*r[i];
    }
    return (sum+fabs(sum1))*0.5 ;
}

```

5.4 basic-area-geometry

```

struct point2d {
    ftype x, y; point2d() {}
    point2d(ftype x, ftype y): x(x), y(y) {}
    point2d& operator+=(const point2d &t) {
        x += t.x; y += t.y; return *this;
    }
    point2d& operator-=(const point2d &t) {
        x -= t.x; y -= t.y; return *this;
    }
    point2d& operator*=(ftype t) {
        x *= t; y *= t; return *this;
    }
    point2d& operator/=(ftype t) {
        x /= t; y /= t; return *this;
    }
    point2d operator+(const point2d &t) const {
        return point2d(*this) += t;
    }
    point2d operator-(const point2d &t) const {
        return point2d(*this) -= t;
    }
    point2d operator*(ftype t) const {
        return point2d(*this) *= t;
    }
    point2d operator/(ftype t) const {
        return point2d(*this) /= t;
    }
};
point2d operator*(ftype a, point2d b) {
    return b * a;
}
struct point3d {
    ftype x, y, z; point3d() {}
    point3d(ftype x, ftype y, ftype z): x(x), y(y), z(z) {}
    point3d& operator+=(const point3d &t) {
        x += t.x; y += t.y; z += t.z; return *this;
    }
    point3d& operator-=(const point3d &t) {
        x -= t.x; y -= t.y; z -= t.z; return *this;
    }
}

```

```

point3d& operator*=(ftype t) {
    x *= t; y *= t; z *= t; return *this;
}
point3d& operator/=(ftype t) {
    x /= t; y /= t; z /= t; return *this;
}
point3d operator+(const point3d &t) const {
    return point3d(*this) += t;
}
point3d operator-(const point3d &t) const {
    return point3d(*this) -= t;
}
point3d operator*(ftype t) const {
    return point3d(*this) *= t;
}
point3d operator/(ftype t) const {
    return point3d(*this) /= t;
}
};
point3d operator*(ftype a, point3d b) {
    return b * a;
}
ftype dot(point2d a, point2d b) {
    return a.x * b.x + a.y * b.y;
}
ftype dot(point3d a, point3d b) {
    return a.x * b.x + a.y * b.y + a.z * b.z;
}
ftype norm(point2d a) {
    return dot(a, a);
}
double abs(point2d a) {
    return sqrt(norm(a));
}
double proj(point2d a, point2d b) {
    return dot(a, b) / abs(b);
}
double angle(point2d a, point2d b) {
    return acos(dot(a, b) / abs(a) / abs(b));
}
point3d cross(point3d a, point3d b) {
    return point3d(a.y * b.z - a.z * b.y,
        a.z * b.x - a.x * b.z, a.x * b.y - a.y * b.x);
}
ftype triple(point3d a, point3d b, point3d c) {
    return dot(a, cross(b, c));
}
ftype cross(point2d a, point2d b) {
    return a.x * b.y - a.y * b.x;
}
point2d intersect(point2d a1, point2d d1,
    point2d a2, point2d d2) {
    return a1 + cross(a2 - a1, d2) / cross(d1, d2) * d1;
}
point3d intersect(point3d a1, point3d n1, point3d a2,
    point3d n2, point3d a3, point3d n3) {
    point3d x(n1.x, n2.x, n3.x); point3d y(n1.y, n2.y, n3.y);
    point3d z(n1.z, n2.z, n3.z);
    point3d d(dot(a1, n1), dot(a2, n2), dot(a3, n3));
    return point3d(triple(d, y, z), triple(x, d, z),
        triple(x, y, d)) / triple(n1, n2, n3);
}
int signed_area_parallelagram(point2d p1, point2d p2, point2d p3) {
    return cross(p2 - p1, p3 - p2);
}
double triangle_area(point2d p1, point2d p2, point2d p3) {
    return abs(signed_area_parallelagram(p1, p2, p3)) / 2.0;
}
bool clockwise(point2d p1, point2d p2, point2d p3) {
    return signed_area_parallelagram(p1, p2, p3) < 0;
}
bool counter_clockwise(point2d p1, point2d p2, point2d p3) {
    return signed_area_parallelagram(p1, p2, p3) > 0;
}
double area(const vector<point>& fig) {
    double res = 0;
    for (unsigned i = 0; i < fig.size(); i++) {
        point p = i? fig[i - 1] : fig.back(); point q = fig[i];
    }
}

```

```

    res += (p.x - q.x) * (p.y + q.y);
}
return fabs(res) / 2;
}
//Pick: S = I + B/2 - 1
int count_lattices(Fraction k, Fraction b, long long n) {
    auto fk = k.floor(); auto fb = b.floor(); auto cnt = 0LL;
    if (k >= 1 || b >= 1) {
        cnt += (fk*(n - 1) + 2 * fb) * n / 2; k -= fk; b -= fb;
    }
    auto t = k * n + b; auto ft = t.floor();
    if (ft >= 1)
        cnt += count_lattices(1 / k, (t - t.floor()) / k, t.floor());
    return cnt;
}

```

5.5 geo-formulae

Triangle Centers and Radii

- Incenter: $\left(\frac{ax_1+bx_2+cx_3}{a+b+c}, \frac{ay_1+by_2+cy_3}{a+b+c}\right)$.
- Inradius: $\sqrt{\frac{(s-a)(s-b)(s-c)}{s}}$.
- Excenter: $\left(\frac{-ax_1+bx_2+cx_3}{-a+b+c}, \frac{-ay_1+by_2+cy_3}{-a+b+c}\right)$.
- Exradius: $\sqrt{\frac{s(s-b)(s-c)}{(s-a)}}$.
- Circumcenter:
 $\left(\frac{x_1 \sin 2A + x_2 \sin 2B + x_3 \sin 2C}{\sin 2A + \sin 2B + \sin 2C}, \frac{y_1 \sin 2A + y_2 \sin 2B + y_3 \sin 2C}{\sin 2A + \sin 2B + \sin 2C}\right)$.
- Circumradius: $\frac{abc}{\sqrt{(a+b+c)(b+c-a)(c+a-b)(a+b-c)}}$.

5.6 half-plane-intersection

```

class HalfPlaneIntersection{
    static double eps, inf;
public:
    struct Point{
        double x, y;
        explicit Point(double x = 0, double y = 0) : x(x), y(y) {}
        // Addition, subtraction, multiply by constant, cross product.
        friend Point operator + (const Point& p, const Point& q){
            return Point(p.x + q.x, p.y + q.y);
        }
        friend Point operator - (const Point& p, const Point& q){
            return Point(p.x - q.x, p.y - q.y);
        }
        friend Point operator * (const Point& p, const double& k){
            return Point(p.x * k, p.y * k);
        }
        friend double cross(const Point& p, const Point& q){
            return p.x * q.y - p.y * q.x;
        }
    };
    // Basic half-plane struct.
    struct Halfplane{
        // 'p' is a passing point of the line and 'pq' is the direction vector of the line.
        Point p, pq;
        double angle;
        Halfplane() {}
        Halfplane(const Point& a, const Point& b) : p(a), pq(b - a){
            angle = atan2(pq.y, pq.x);
        }
        // Check if point 'r' is outside this half-plane.

```

```

        // Every half-plane allows the region to the LEFT of its line.
        bool out(const Point& r){
            return cross(pq, r - p) < -eps;
        }
        // Comparator for sorting.
        // If the angle of both half-planes is equal, the leftmost one should go first.
        bool operator < (const Halfplane& e) const{
            if (fabs(angle - e.angle) < eps) return cross(pq, e.p - p) < 0;
            return angle < e.angle;
        }
        // We use equal comparator for std::unique to easily remove parallel half-planes.
        bool operator == (const Halfplane& e) const{
            return fabs(angle - e.angle) < eps;
        }
        // Intersection point of the lines of two half-planes. It is assumed they're never parallel.
        friend Point inter(const Halfplane& s, const Halfplane& t){
            double alpha = cross((t.p - s.p), t.pq) / cross(s.pq, t.pq);
            return s.p + (s.pq * alpha);
        }
    };
    static vector<Point> hp_intersect(vector<Halfplane>& H){
        Point box[4] = // Bounding box in CCW order{
            Point(inf, inf),
            Point(-inf, inf),
            Point(-inf, -inf),
            Point(inf, -inf)
        };
        for(int i = 0; i < 4; i++) // Add bounding box half-planes.{
            Halfplane aux(box[i], box[(i+1) % 4]);
            H.push_back(aux);
        }
        // Sort and remove duplicates
        sort(H.begin(), H.end());
        H.erase(unique(H.begin(), H.end()), H.end());
        deque<Halfplane> dq;
        int len = 0;
        for(int i = 0; i < int(H.size()); i++){
            // Remove from the back of the deque while last half-plane is redundant
            while (len > 1 && H[i].out(inter(dq[len-1], dq[len-2]))){
                dq.pop_back();
                --len;
            }
            // Remove from the front of the deque while first half-plane is redundant
            while (len > 1 && H[i].out(inter(dq[0], dq[1]))){
                dq.pop_front();
                --len;
            }
            // Add new half-plane
            dq.push_back(H[i]);
            ++len;
        }
        // Final cleanup: Check half-planes at the front against the back and vice-versa
        while (len > 2 && dq[0].out(inter(dq[len-1], dq[len-2]))){
            dq.pop_back();
            --len;
        }
        while (len > 2 && dq[len-1].out(inter(dq[0], dq[1]))){
            dq.pop_front();
            --len;
        }
        // Report empty intersection if necessary
        if (len < 3) return vector<Point>();
        // Reconstruct the convex polygon from the remaining half-planes.
        vector<Point> ret(len);

```

```

        for(int i = 0; i+1 < len; i++){
            ret[i] = inter(dq[i], dq[i+1]);
        }
        ret.back() = inter(dq[len-1], dq[0]);
        return ret;
    };
};
double HalfPlaneIntersection::eps=1e-9;
double HalfPlaneIntersection::inf=1e9;

```

5.7 heart-of-geometry-2d

```

typedef double ftype;
const double EPS = 1E-9;
struct pt{
    ftype x, y;
    int id;
    pt() {}
    pt(ftype _x, ftype _y):x(_x), y(_y) {}
    pt operator+(const pt & p) const{
        return pt(x + p.x, y + p.y);
    }
    pt operator-(const pt & p) const{
        return pt(x - p.x, y - p.y);
    }
    ftype cross(const pt & p) const{
        return x * p.y - y * p.x;
    }
    ftype dot(const pt & p) const{
        return x * p.x + y * p.y;
    }
    ftype cross(const pt & a, const pt & b) const{
        return (a - *this).cross(b - *this);
    }
    ftype dot(const pt & a, const pt & b) const{
        return (a - *this).dot(b - *this);
    }
    ftype sqrLen() const{
        return this->dot(*this);
    }
    bool operator<(const pt& p) const{
        return x < p.x - EPS || (abs(x - p.x) < EPS && y < p.y - EPS);
    }
    bool operator==(const pt& p) const{
        return abs(x-p.x)<EPS && abs(y-p.y)<EPS;
    }
};
int sign(double x) { return (x > EPS) - (x < -EPS); }
inline int orientation(pt a, pt b, pt c) { return sign(a.cross(b,c)); }
bool is_point_on_seg(pt a, pt b, pt p) {
    if (fabs(b.cross(p,a)) < EPS) {
        if (p.x < min(a.x, b.x) - EPS || p.x > max(a.x, b.x) + EPS) return false;
        if (p.y < min(a.y, b.y) - EPS || p.y > max(a.y, b.y) + EPS) return false;
        return true;
    }
    return false;
}
bool is_point_on_polygon(vector<pt> &p, const pt& z) {
    int n = p.size();
    for (int i = 0; i < n; i++) {
        if (is_point_on_seg(p[i], p[(i + 1) % n], z)) return 1;
    }
    return 0;
}
int winding_number(vector<pt> &p, const pt& z) { // O(n)
    if (is_point_on_polygon(p, z)) return 1e9;
    int n = p.size(), ans = 0;
    for (int i = 0; i < n; ++i) {
        int j = (i + 1) % n;
        bool below = p[i].y < z.y;
        if (below != (p[j].y < z.y)) {
            auto orient = orientation(z, p[j], p[i]);
            if (orient == 0) return 0;
            if (below == (orient > 0)) ans += below ? -1 : 1;
        }
    }
}

```



```

    }
    return ans;
}
double dist_sqr(pt a, pt b){
    return ((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y));
}
double dist(pt a, pt b){
    return sqrt((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y));
}
double angle(pt a, pt b, pt c){
    if(b==a || b==c) return 0;
    double A2 = dist_sqr(b,c);
    double C2 = dist_sqr(a,b);
    double B2 = dist_sqr(c,a);
    double A = sqrt(A2); C = sqrt(C2);
    double ans = (A2 + C2 - B2)/(A*C*2);
    if(ans<-1) ans=acos(-1);
    else if(ans>1) ans=acos(1);
    else ans = acos(ans);
    return ans;
}
bool cmp(pt a, pt b){
    return a.x < b.x || (a.x == b.x && a.y < b.y);
}
bool ccw(pt a, pt b, pt c, bool include_collinear=false) {
    int o = orientation(a, b, c);
    return o > 0 || (include_collinear && o == 0);
}
bool cw(pt a, pt b, pt c, bool include_collinear=false) {
    int o = orientation(a, b, c);
    return o < 0 || (include_collinear && o == 0);
}
bool collinear(pt a, pt b, pt c) { return orientation(a, b, c)
    == 0; }
double area(pt a, pt b, pt c){
    return (a.x*(b.y-c.y)+b.x*(c.y-a.y)+c.x*(a.y-b.y))/2;
}
struct cmp_x{
    bool operator()(const pt & a, const pt & b) const{
        return a.x < b.x || (a.x == b.x && a.y < b.y);
    }
};
struct cmp_y{
    bool operator()(const pt & a, const pt & b) const{
        return a.y < b.y || (a.y == b.y && a.x < b.x);
    }
};
struct circle : pt {
    ftype r;
};
bool insideCircle(circle c, pt p){
    return dist_sqr(c,p) <= c.r*c.r + EPS;
}
struct line {
    ftype a, b, c;
    line() {}
    line(pt p, pt q){
        a = p.y - q.y;
        b = q.x - p.x;
        c = -a * p.x - b * p.y;
        norm();
    }
    void norm(){
        double z = sqrt(a * a + b * b);
        if (abs(z) > EPS)
            a /= z, b /= z, c /= z;
    }
    line getParallel(pt p){
        line ans = *this;
        ans.c = -(ans.a*p.x+ans.b*p.y);
        return ans;
    }
    ftype getValue(pt p){
        return a*p.x+b*p.y+c;
    }
    line getPerpend(pt p){
        line ans;
        ans.a=this->b;
        ans.b=-(this->a);

```

```

        ans.c = -(ans.a*p.x+ans.b*p.y);
        return ans;
    }
    //dist formula is wrong but don't change
    double dist(pt p) const { return a * p.x + b * p.y + c; }
};
double sqr (double a) {
    return a * a;
}
double det(double a, double b, double c, double d) {
    return a*d - b*c;
}
bool intersect(line m, line n, pt & res) {
    double zn = det(m.a, m.b, n.a, n.b);
    if (abs(zn) < EPS)
        return false;
    res.x = -det(m.c, m.b, n.c, n.b) / zn;
    res.y = -det(m.a, m.c, n.a, n.c) / zn;
    return true;
}
bool parallel(line m, line n) {
    return abs(det(m.a, m.b, n.a, n.b)) < EPS;
}
bool equivalent(line m, line n) {
    return abs(det(m.a, m.b, n.a, n.b)) < EPS
        && abs(det(m.a, m.c, n.a, n.c)) < EPS
        && abs(det(m.b, m.c, n.b, n.c)) < EPS;
}
double det(double a, double b, double c, double d){
    return a * d - b * c;
}
inline bool betw(double l, double r, double x){
    return min(l, r) <= x + EPS && x <= max(l, r) + EPS;
}
inline bool intersect_1d(double a, double b, double c, double
    d){
    if (a > b)
        swap(a, b);
    if (c > d)
        swap(c, d);
    return max(a, c) <= min(b, d) + EPS;
}
bool intersect_segment(pt a, pt b, pt c, pt d, pt& left, pt&
    right){
    if (!intersect_1d(a.x, b.x, c.x, d.x) ||
        !intersect_1d(a.y, b.y, c.y, d.y))
        return false;
    line m(a, b);
    line n(c, d);
    double zn = det(m.a, m.b, n.a, n.b);
    if (abs(zn) < EPS) {
        if (abs(m.dist(c)) > EPS || abs(n.dist(a)) > EPS)
            return false;
        if (b < a)
            swap(a, b);
        if (d < c)
            swap(c, d);
        left = max(a, c);
        right = min(b, d);
        return true;
    } else {
        left.x = right.x = -det(m.c, m.b, n.c, n.b) / zn;
        left.y = right.y = -det(m.a, m.c, n.a, n.c) / zn;
        return betw(a.x, b.x, left.x) && betw(a.y, b.y, left.y)
            &&
            betw(c.x, d.x, left.x) && betw(c.y, d.y, left.y);
    }
}
void tangents (pt c, double r1, double r2, vector<line> & ans)
{
    double r = r2 - r1;
    double z = sqr(c.x) + sqr(c.y);
    double d = z - sqr(r);
    if (d < -EPS) return;
    d = sqrt (abs (d));
    line l;
    l.a = (c.x * r + c.y * d) / z;
    l.b = (c.y * r - c.x * d) / z;
    l.c = r1;
    ans.push_back (l);
}

```

```

}
vector<line> tangents (circle a, circle b) {
    vector<line> ans;
    for (int i=-1; i<=1; i+=2)
        for (int j=-1; j<=1; j+=2)
            tangents (b-a, a.r*i, b.r*j, ans);
    for (size_t i=0; i<ans.size(); ++i)
        ans[i].c -= ans[i].a * a.x + ans[i].b * a.y;
    return ans;
}
class pointLocationInPolygon{
    bool lexComp(const pt & l, const pt & r){
        return l.x < r.x || (l.x == r.x && l.y < r.y);
    }
    int sgn(ftype val){
        return val > 0 ? 1 : (val == 0 ? 0 : -1);
    }
    vector<pt> seq;
    int n;
    pt translate;
    bool pointInTriangle(pt a, pt b, pt c, pt point){
        ftype s1 = abs(a.cross(b, c));
        ftype s2 = abs(point.cross(a, b)) + abs(point.cross(b,
            c)) + abs(point.cross(c, a));
        return s1 == s2;
    }
public:
    pointLocationInPolygon(){
    }
    pointLocationInPolygon(vector<pt> & points){
        prepare(points);
    }
    void prepare(vector<pt> & points){
        seq.clear();
        n = points.size();
        int pos = 0;
        for(int i = 1; i < n; i++){
            if(lexComp(points[i], points[pos]))
                pos = i;
        }
        translate.x=points[pos].x;
        translate.y=points[pos].y;
        rotate(points.begin(), points.begin() + pos,
            points.end());
        n--;
        seq.resize(n);
        for(int i = 0; i < n; i++)
            seq[i] = points[i + 1] - points[0];
    }
    bool pointInConvexPolygon(pt point){
        point.x-=translate.x;
        point.y-=translate.y;
        if(seq[0].cross(point) != 0 && sgn(seq[0].cross(point))
            != sgn(seq[0].cross(seq[n - 1])))
            return false;
        if(seq[n - 1].cross(point) != 0 && sgn(seq[n -
            1].cross(point)) != sgn(seq[n - 1].cross(seq[0])))
            return false;
        if(seq[0].cross(point) == 0)
            return seq[0].sqrLen() >= point.sqrLen();
        int l = 0, r = n - 1;
        while(r - l > 1){
            int mid = (l + r)/2;
            int pos = mid;
            if(seq[pos].cross(point) >= 0) l = mid;
            else r = mid;
        }
        int pos = l;
        return pointInTriangle(seq[pos], seq[pos + 1], pt(0,
            0), point);
    }
    ~pointLocationInPolygon(){
        seq.clear();
    }
};
class Minkowski{
    static void reorder_polygon(vector<pt> & P){
        size_t pos = 0;
        for(size_t i = 1; i < P.size(); i++){

```

```

        if(P[i].y < P[pos].y || (P[i].y == P[pos].y &&
            P[i].x < P[pos].x))
            pos = i;
    }
    rotate(P.begin(), P.begin() + pos, P.end());
public:
    static vector<pt> minkowski(vector<pt> P, vector<pt> Q){
        // the first vertex must be the lowest
        reorder_polygon(P);
        reorder_polygon(Q);
        // we must ensure cyclic indexing
        P.push_back(P[0]);
        P.push_back(P[1]);
        Q.push_back(Q[0]);
        Q.push_back(Q[1]);
        // main part
        vector<pt> result;
        size_t i = 0, j = 0;
        while(i < P.size() - 2 || j < Q.size() - 2){
            result.push_back(P[i] + Q[j]);
            auto cross = (P[i + 1] - P[i]).cross(Q[j + 1] -
                Q[j]);
            if(cross >= 0)
                ++i;
            if(cross <= 0)
                ++j;
        }
        return result;
    };
};
vector<pt> circle_line_intersections(circle cir, line l){
    double r = cir.r, a = l.a, b = l.b, c = l.c + l.a*cir.x +
        l.b*cir.y;
    vector<pt> ans;
    double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
    if (c*c > r*r*(a*a+b*b)+EPS){
        else if (abs (c*c - r*r*(a*a+b*b)) < EPS){
            pt p;
            p.x=x0;
            p.y=y0;
            ans.push_back(p);
        }
        else{
            double d = r*r - c*c/(a*a+b*b);
            double mult = sqrt (d / (a*a+b*b));
            double ax, ay, bx, by;
            ax = x0 + b * mult;
            bx = x0 - b * mult;
            ay = y0 - a * mult;
            by = y0 + a * mult;
            pt p;
            p.x = ax;
            p.y = ay;
            ans.push_back(p);
            p.x = bx;
            p.y = by;
            ans.push_back(p);
        }
        for(int i=0;i<ans.size();i++){
            ans[i] = ans[i] + cir;
        }
        return ans;
    }
};
double circle_polygon_intersection(circle c,vector<pt> &V){
    int n = V.size();
    double ans = 0;
    for(int i=0; i<n; i++){
        line l(V[i],V[(i+1)%n]);
        vector<pt> lpts = circle_line_intersections(c,l);
        int sz=lpts.size();
        for(int j=sz-1; j>=0; j--){
            if(!is_point_on_seg(V[i],V[(i+1)%n],lpts[j])){
                swap(lpts.back(),lpts[j]);
                lpts.pop_back();
            }
        }
        lpts.push_back(V[i]);
        lpts.push_back(V[(i+1)%n]);
        sort(lpts.begin(),lpts.end());
    }
}

```

```

        sz=lpts.size();
        if(V[(i+1)%n]<V[i])
            reverse(lpts.begin(),lpts.end());
        for(int j=1; j<sz; j++){
            if(insideCircle(c,lpts[j-1])
                &&insideCircle(c,lpts[j]))
                ans = ans + area(lpts[j-1],lpts[j],c);
            else{
                double ang = angle(lpts[j-1],c,lpts[j]);
                double aa = c.r*c.r*ang/2;
                if(ccw(lpts[j-1],lpts[j],c))
                    ans = ans+aa;
                else
                    ans = ans-aa;
            }
        }
        ans = abs(ans);
        return ans;
    }
};
void convex_hull(vector<pt>& a, bool include_collinear =
    false) {
    pt p0 = *min_element(a.begin(), a.end(), [](pt a, pt b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    });
    sort(a.begin(), a.end(), [&p0](const pt& a, const pt& b) {
        int o = orientation(p0, a, b);
        if (o == 0)
            return (p0.x-a.x)*(p0.x-a.x) + (p0.y-a.y)*(p0.y-a.y)
                < (p0.x-b.x)*(p0.x-b.x) + (p0.y-b.y)*(p0.y-b.y);
        return o < 0;
    });
    if (include_collinear) {
        int i = (int)a.size()-1;
        while (i >= 0 && collinear(p0, a[i], a.back())) i--;
        reverse(a.begin()+i+1, a.end());
    }
    vector<pt> st;
    for (int i = 0; i < (int)a.size(); i++) {
        while (st.size() > 1 && !cw(st[st.size()-2], st.back(),
            a[i], include_collinear))
            st.pop_back();
        st.push_back(a[i]);
    }
    a = st;
    int m = a.size();
    for(int i = 0; i<m-1-i; i++){
        swap(a[i], a[m-1-i]);
    }
}
double mindist;
pair<int,pair<int, int> > best_pair;
void upd_ans(const pt & a, const pt & b,const pt & c){
    double distC = sqrt((a.x - b.x)*(a.x - b.x) + (a.y -
        b.y)*(a.y - b.y));
    double distA = sqrt((c.x - b.x)*(c.x - b.x) + (c.y -
        b.y)*(c.y - b.y));
    double distB = sqrt((a.x - c.x)*(a.x - c.x) + (a.y -
        c.y)*(a.y - c.y));
    if (distA + distB + distC < mindist){
        mindist = distA + distB + distC;
        best_pair = make_pair(a.id,make_pair(b.id,c.id));
    }
}
vector<pt> t;
//Min possible triplet distance
void rec(int l, int r){
    if (r - l <= 3 && r - l >=2){
        for (int i = 1; i < r; ++i){
            for (int j = i + 1; j < r; ++j){
                for(int k=j+1;k<r;k++){
                    upd_ans(a[i],a[j],a[k]);
                }
            }
        }
    }
    sort(a.begin() + 1, a.begin() + r, cmp_y());
    return;
}
int m = (1 + r) >> 1;

```

```

int midx = a[m-1].x;
/*
 * Got WA in a team contest
 * for putting midx = a[m].x;
 * Don't know why. Maybe due to
 * floating point numbers.
 */
rec(1, m);
rec(m, r);
merge(a.begin() + 1, a.begin() + m, a.begin() + m,
    a.begin() + r, t.begin(), cmp_y());
copy(t.begin(), t.begin() + r - 1, a.begin() + 1);
int tsz = 0;
for (int i = 1; i < r; ++i){
    if (abs(a[i].x - midx) < mindist/2){
        for (int j = tsz - 1; j >= 0 && a[i].y - t[j].y <
            mindist/2; --j){
            if(i+1<r) upd_ans(a[i], a[i+1], t[j]);
            if(j>0) upd_ans(a[i], t[j-1], t[j]);
        }
        t[tsz++] = a[i];
    }
}
}
}

```

5.8 intersecting-segments-pair

```

const double EPS = 1E-9;
struct pt {
    double x, y;
};
struct seg {
    pt p, q;
    int id;
    double get_y(double x) const {
        if (abs(p.x - q.x) < EPS)
            return p.y;
        return p.y + (q.y - p.y) * (x - p.x) / (q.x - p.x);
    }
};
bool intersectId(double l1, double r1, double l2, double r2) {
    if (l1 > r1)
        swap(l1, r1);
    if (l2 > r2)
        swap(l2, r2);
    return max(l1, l2) <= min(r1, r2) + EPS;
}
int vec(const pt& a, const pt& b, const pt& c) {
    double s = (b.x - a.x) * (c.y - a.y) - (b.y - a.y) * (c.x
        - a.x);
    return abs(s) < EPS ? 0 : s > 0 ? +1 : -1;
}
bool intersect(const seg& a, const seg& b){
    return intersectId(a.p.x, a.q.x, b.p.x, b.q.x) &&
        intersectId(a.p.y, a.q.y, b.p.y, b.q.y) &&
        vec(a.p, a.q, b.p) * vec(a.p, a.q, b.q) <= 0 &&
        vec(b.p, b.q, a.p) * vec(b.p, b.q, a.q) <= 0;
}
bool operator<(const seg& a, const seg& b){
    double x = max(min(a.p.x, a.q.x), min(b.p.x, b.q.x));
    return a.get_y(x) < b.get_y(x) - EPS;
}
struct event {
    double x;
    int tp, id;
    event() {}
    event(double x, int tp, int id) : x(x), tp(tp), id(id) {}
    bool operator<(const event& e) const {
        if (abs(x - e.x) > EPS)
            return x < e.x;
        return tp > e.tp;
    }
};
set<seg> s;
vector<set<seg>::iterator> where;
set<seg>::iterator prev(set<seg>::iterator it) {
    return it == s.begin() ? s.end() : --it;
}
set<seg>::iterator next(set<seg>::iterator it) {

```

```

    return ++it;
}
pair<int, int> solve(const vector<seg>& a) {
    int n = (int)a.size();
    vector<event> e;
    for (int i = 0; i < n; ++i) {
        e.push_back(event(min(a[i].p.x, a[i].q.x), +1, i));
        e.push_back(event(max(a[i].p.x, a[i].q.x), -1, i));
    }
    sort(e.begin(), e.end());
    s.clear();
    where.resize(a.size());
    for (size_t i = 0; i < e.size(); ++i) {
        int id = e[i].id;
        if (e[i].tp == +1) {
            set<seg>::iterator nxt = s.lower_bound(a[id]), prv = prev(nxt);
            if (nxt != s.end() && intersect(*nxt, a[id]))
                return make_pair(nxt->id, id);
            if (prv != s.end() && intersect(*prv, a[id]))
                return make_pair(prv->id, id);
            where[id] = s.insert(nxt, a[id]);
        } else {
            set<seg>::iterator nxt = next(where[id]), prv = prev(where[id]);
            if (nxt != s.end() && prv != s.end() && intersect(*nxt, *prv))
                return make_pair(prv->id, nxt->id);
            s.erase(where[id]);
        }
    }
    return make_pair(-1, -1);
}

```

5.9 radiant-geo

```

typedef double Tf; typedef double Ti;
const Tf PI = acos(-1), EPS = 1e-9;
int dcmp(Tf x) {return abs(x)<EPS? 0 : (x<0?-1:1);}
struct PT {
    Ti x, y;
    bool operator == (const PT& u) const {
        return dcmp(x-u.x)==0 && dcmp(y-u.y)==0;}
    bool operator != (const PT& u) const {
        return !(*this == u); }
    friend istream &operator >> (istream &is, PT &p) {
        return is >> p.x >> p.y; }
    friend ostream &operator << (ostream &os, const PT &p) {return os<<p.x<<" "<<p.y; }
};
Ti dot(PT a, PT b) { return a.x*b.x + a.y*b.y; }
Ti cross(PT a, PT b) { return a.x*b.y - a.y*b.x; }
Ti length(PT a) { return sqrt(dot(a, a)); }
Ti sqLength(PT a) { return dot(a, a); }
Tf distance(PT a, PT b) {return length(a-b);}
Tf angle(PT u) { return atan2(u.y, u.x); }
Tf angleBetween(PT a, PT b) { //in range [-PI, PI]
    Tf ans = angle(b) - angle(a);
    return ans <= -PI ? ans + 2*PI :
        (ans > PI ? ans - 2*PI : ans);
}
PT rotate(PT a, Tf rad) {
    static_assert(is_same<Tf, Ti>::value);
    return PT(a.x * cos(rad) - a.y * sin(rad),
        a.x * sin(rad) + a.y * cos(rad));
}
// Rotate(a, rad) where cos(rad)=co, sin(rad)=si
PT rotatePrecise(PT a, Tf co, Tf si) {
    static_assert(is_same<Tf, Ti>::value);
    return PT(a.x*co - a.y*si, a.y*co + a.x*si);
}
PT rotate90(PT a) { return PT(-a.y, a.x); }
PT scale(PT a, Tf s) {
    static_assert(is_same<Tf, Ti>::value);
    return a / length(a) * s;
}
PT normal(PT a) {
    static_assert(is_same<Tf, Ti>::value);

```

```

    Tf l = length(a); return PT(-a.y / l, a.x / l);
}
// returns 1/0/-1 if c is left/on/right of ab
int orient(PT a, PT b, PT c) {
    return dcmp(cross(b - a, c - a));
}
//sort(v.begin(), v.end(), polarComp(0, dir))
struct polarComp {
    PT o, dir;
    polarComp(PT o = PT(0, 0), PT dir = PT(1, 0)) : o(o), dir(dir) {}
    bool half(PT p) {
        return dcmp(cross(dir, p)) < 0 ||
            (dcmp(cross(dir, p))==0&&dcmp(dot(dir, p))>0);
    }
    bool operator()(PT p, PT q) {
        return make_tuple(half(p-o), 0) <
            make_tuple(half(q-o), cross(p-o, q-o));
    }
};
struct Segment {
    PT a, b;
    Segment() {}
    Segment(PT aa, PT bb) : a(aa), b(bb) {}
}; typedef Segment Line;
struct Circle {
    PT o; Tf r;
    Circle(PT o = PT(0, 0), Tf r = 0) : o(o), r(r) {}
    bool contains(PT p) {
        return dcmp(sqLength(p - o) - r * r) <= 0; }
    PT point(Tf rad) {
        static_assert(is_same<Tf, Ti>::value);
        return PT(o.x+cos(rad)*r, o.y+sin(rad)*r);
    }
    Tf area(Tf rad = PI + PI) { return rad * r * r/2;}
    Tf sector(Tf alpha) {
        return r*r*0.5*(alpha-sin(alpha)); }
};
namespace Linear {
bool onSegment(PT p, Segment s) { //Is p on S?
    return dcmp(cross(s.a - p, s.b - p)) == 0 &&
        dcmp(dot(s.a - p, s.b - p)) <= 0; }
}
bool segmentsIntersect(Segment p, Segment q) {
    if (onSegment(p.a,q)||onSegment(p.b,q))return 1;
    if (onSegment(q.a,p)||onSegment(q.b,p))return 1;
    Ti c1 = cross(p.b - p.a, q.a - p.a);
    Ti c2 = cross(p.b - p.a, q.b - p.a);
    Ti c3 = cross(q.b - q.a, p.a - q.a);
    Ti c4 = cross(q.b - q.a, p.b - q.a);
    return dcmp(c1)*dcmp(c2)<0&&dcmp(c3)*dcmp(c4)<0;
}
bool linesParallel(Line p, Line q) {
    return dcmp(cross(p.b - p.a, q.b - q.a)) == 0;
}
//returns if lines (p, p+v) && (q, q+w) intersect
bool lineLineIntersect(PT p,PT v,PT q,PT w,PT&o) {
    static_assert(is_same<Tf, Ti>::value);
    if (dcmp(cross(v, w)) == 0) return false;
    PT u = p - q; o = p + v*(cross(w,u)/cross(v,w));
    return true;
}
bool lineLineIntersect(Line p, Line q, PT& o) {
    return lineLineIntersect(p.a, p.b - p.a, q.a,
        q.b - q.a, o);
}
Tf distancePointLine(PT p, Line l) {
    return abs(cross(l.b-l.a, p-l.a)/length(l.b-l.a));
}
Tf distancePointSegment(PT p, Segment s) {
    if (s.a == s.b) return length(p - s.a);
    PT v1 = s.b - s.a, v2 = p - s.a, v3 = p - s.b;
    if (dcmp(dot(v1, v2)) < 0) return length(v2);
    else if (dcmp(dot(v1, v3)) > 0) return length(v3);
    else return abs(cross(v1, v2) / length(v1));
}

```

```

Tf distanceSegmentSegment(Segment p, Segment q) {
    if (segmentsIntersect(p, q)) return 0;
    Tf ans = distancePointSegment(p.a, q);
    ans = min(ans, distancePointSegment(p.b, q));
    ans = min(ans, distancePointSegment(q.a, p));
    ans = min(ans, distancePointSegment(q.b, p));
    return ans;
}
PT projectPointLine(PT p, Line l) {
    static_assert(is_same<Tf, Ti>::value);
    PT v = l.b - l.a;
    return l.a + v * ((Tf) dot(v, p-l.a)/dot(v, v));
} // namespace Linear
namespace Polygonal {
// cannot be all collinear
Polygon RemoveCollinear(const Polygon& poly) {
    Polygon ret;
    int n = poly.size();
    for (int i = 0; i < n; i++) {
        PT a = poly[i];
        PT b = poly[(i + 1) % n];
        PT c = poly[(i + 2) % n];
        if (dcmp(cross(b-a, c-b))!=0 && (ret.empty() ||
            b != ret.back())) ret.push_back(b);
    }
    return ret;
}
Tf signedPolygonArea(const Polygon &p) {
    Tf ret = 0;
    for (int i = 0; i < (int) p.size() - 1; i++)
        ret += cross(p[i]-p[0], p[i+1]-p[0]);
    return ret / 2;
}
// returns inside = -1, on = 0, outside = 1
int pointInPolygon(const Polygon &p, PT o) {
    using Linear::onSegment; int wn=0, n = p.size();
    for (int i = 0; i < n; i++) {
        int j = (i + 1) % n; if (onSegment(o,
            Segment(p[i], p[j])) || o == p[i]) return 0;
        int k = dcmp(cross(p[j] - p[i], o - p[i]));
        int d1=dcmp(p[i].y-o.y), d2=dcmp(p[j].y-o.y);
        if (k > 0 && d1 <= 0 && d2 > 0) wn++;
        if (k < 0 && d2 <= 0 && d1 > 0) wn--;
    }
    return wn ? -1 : 1;
}
// returns (longest segment, total length)
pair<Tf, Tf> linePolygonIntersection(Line l,
    const Polygon &p) {
    using Linear::lineLineIntersect;
    int n = p.size(); vector<pair<Tf, int>> ev;
    for (int i=0; i<n; ++i) {
        PT a = p[i], b = p[(i+1)%n], z = p[(i+1+n)%n];
        int ora=orient(l.a,l.b,a), orb =
            orient(l.a,l.b,b), orz=orient(l.a,l.b,z);
        if (!ora) {
            Tf d = dot(a - l.a, l.b - l.a);
            if (orz && orb) {
                if (orz != orb) ev.emplace_back(d, 0);
                //else // PT Touch
            } else if (orz) ev.emplace_back(d, orz);
            else if (orb) ev.emplace_back(d, orb);
        }
        else if (ora == -orb) {
            PT ins;
            lineLineIntersect(l, Line(a, b), ins);
            ev.emplace_back(dot(ins-l.a, l.b-l.a), 0);
        }
    }
    sort(ev.begin(), ev.end());
    Tf ans = 0, len = 0, last = 0, tot = 0;
    bool active = false; int sign = 0;
    for (auto &qq : ev) {
        int tp = qq.second;
        Tf d = qq.first; //current Seg is (last, d)
        if (sign) { //On Border
            len+=d-last; tot+=d-last; ans=max(ans,len);

```

```

    if(tp != sign) active = !active;
    sign = 0;
}
else {
    if(active) { ///Strictly Inside
        len+=d-last;tot+=d-last;ans=max(ans,len);
    }
    if(tp == 0) active=!active; else sign = tp;
}
last = d; if(!active) len = 0;
}
ans /= length(l.b-l.a); tot /= length(l.b-l.a);
return {ans, tot};
} } /// namespace Polygonal
#####
namespace Convex {
///{min area, min perimeter} rectangle containing p
pair<Tf,Tf>rotatingCalipersBBox(const Polygon &p){
    using Linear::distancePointLine;
    static_assert(is_same<Tf, Ti>::value);
    int n = p.size(); int l = 1, r = 1, j = 1;
    Tf area = 1e100; Tf perimeter = 1e100;
    for(int i = 0; i < n; i++) {
        PT v=p[(i+1)%n]-p[i];length(p[(i+1)%n]-p[i]);
        while(dcmp(dot(v, p[r%n] - p[i]) -
            dot(v, p[(r+1)%n] - p[i])) < 0) r++;
        while(j < r || dcmp(cross(v, p[j%n] - p[i]) -
            cross(v, p[(j+1)%n] - p[i])) < 0) j++;
        while(l < j || dcmp(dot(v, p[l%n] - p[i]) -
            dot(v, p[(l+1)%n] - p[i])) > 0) l++;
        Tf w = dot(v,p[r%n]-p[i])-dot(v,p[l%n]-p[i]);
        Tf h = distancePointLine(p[j%n],
            Line(p[i], p[(i+1)%n]));
        area = min(area, w * h);
        perimeter = min(perimeter, 2 * w + 2 * h);
    }
    return make_pair(area, perimeter);
}
/// returns the left half of u on left on ray ab
Polygon cutPolygon(Polygon u, PT a, PT b) {
    using Linear::lineLineIntersect;
    using Linear::onSegment;
    Polygon ret; int n = u.size();
    for(int i = 0; i < n; i++) {
        PT c = u[i], d = u[(i + 1) % n];
        if(dcmp(cross(b-a, c-a))>0) ret.push_back(c);
        if(dcmp(cross(b-a, d-c)) != 0) {
            PT t; lineLineIntersect(a, b-a, c, d-c, t);
            if(onSegment(t,Segment(c,d)))ret.push_back(t);
        }
    }
    return ret;
}
bool pointInTriangle(PT a, PT b, PT c, PT p) {
    return dcmp(cross(b - a, p - a)) >= 0
        && dcmp(cross(c - b, p - b)) >= 0
        && dcmp(cross(a - c, p - c)) >= 0;
}
int pointInConvexPolygon(const Polygon &pt, PT p){
    int n = pt.size(); assert(n >= 3);
    int lo = 1, hi = n - 1;
    while(hi - lo > 1) {
        int mid = (lo + hi) / 2;
        if(dcmp(cross(pt[mid]-pt[0], p - pt[0])) > 0)
            lo = mid;
        else hi = mid;
    }
    bool in=pointInTriangle(pt[0],pt[lo],pt[hi],p);
    if(!in) return 1;
    if(dcmp(cross(pt[lo]-pt[lo-1],p-pt[lo-1]))==0)
        return 0; if(dcmp(cross(pt[hi]-pt[lo],
        p-pt[lo]))==0) return 0; if(dcmp(cross(pt[hi]-
        pt[(hi+1)%n], p-pt[(hi+1)%n]))==0) return 0;
    return -1;
}
/// most extreme Point in the direction u
int extremePoint(const Polygon &poly, PT u) {
    int n = (int) poly.size();
    int a = 0, b = n;
    while(b - a > 1) {

```

```

        int c = (a + b) / 2;
        if(dcmp(dot(poly[c]-poly[(c+1)%n], u))>=0 &&
            dcmp(dot(poly[c]-poly[(c-1+n)%n], u))>=0) {
            return c; }
        bool a_up=dcmp(dot(poly[(a+1)%n]-poly[a],u))>=0;
        bool c_up=dcmp(dot(poly[(c+1)%n]-poly[c],u))>=0;
        bool a_above_c=dcmp(dot(poly[a]-poly[c],u))>0;
        if(a_up && !c_up) b = c;
        else if(!a_up && c_up) a = c;
        else if(a_up && c_up) {
            if(a_above_c) b = c; else a = c;
        }
        else {
            if(!a_above_c) b = c; else a = c;
        }
    }
    if(dcmp(dot(poly[a]-poly[(a+1)%n],u))>0 &&
        dcmp(dot(poly[a]-poly[(a-1+n)%n],u))>0)
        return a;
    return b % n;
}
/// return list of segs of p that touch/intersect l
/// the i'th segment is (p[i], p[(i + 1)%p])
/// #1 If a side is collinear, only that returned
/// #2 If l goes through p[i], i'th segment is added
vector<int> lineConvexPolyIntersection(
    const Polygon &p, Line l) {
    assert((int) p.size() >= 3); assert(l.a != l.b);
    int n = p.size(); vector<int> ret;
    PT v = l.b - l.a;
    int lf = extremePoint(p, rotate90(v));
    int rt = extremePoint(p, rotate90(v) * Ti(-1));
    int olf = orient(l.a, l.b, p[lf]);
    int ort = orient(l.a, l.b, p[rt]);
    if(!olf || !ort) {
        int idx = (!olf ? lf : rt);
        if(orient(l.a, l.b, p[(idx - 1 + n) % n]) == 0)
            ret.push_back((idx - 1 + n) % n);
        else ret.push_back(idx);
        return ret;
    }
    if(olf == ort) return ret;
    for(int i=0; i<2; ++i) {
        int lo = i ? rt : lf, hi = i ? lf : rt;
        int olo = i ? ort : olf;
        while(true) {
            int gap = (hi - lo + n) % n;
            if(gap < 2) break;
            int mid = (lo + gap / 2) % n;
            int omid = orient(l.a, l.b, p[mid]);
            if(!omid) {lo = mid; break;}
            if(omid == olo) lo = mid;
            else hi = mid;
        }
        ret.push_back(lo);
    }
    return ret;
}
/// [ACW, CW] tangent pair from an external point
constexpr int CW = -1, ACW = 1;
bool isGood(PT u, PT v, PT Q, int dir) {
    return orient(Q, u, v) != -dir; }
PT better(PT u, PT v, PT Q, int dir) {
    return orient(Q, u, v) == dir ? u : v; }
PT pointPolyTangent(const Polygon &pt, PT Q,
    int dir, int lo, int hi) {
    while(hi - lo > 1) {
        int mid = (lo + hi) / 2;
        bool pvs = isGood(pt[mid], pt[mid-1], Q, dir);
        bool nxt = isGood(pt[mid], pt[mid+1], Q, dir);
        if(pvs && nxt) return pt[mid];
        if(!pvs || !nxt) {
            PT p1 = pointPolyTangent(pt,Q,dir,mid+1,hi);
            PT p2 = pointPolyTangent(pt,Q,dir,lo,mid-1);
            return better(p1, p2, Q, dir);
        }
    }
    if(!pvs) {
        if(orient(Q,pt[mid],pt[lo])==dir) hi=mid-1;
        else if(better(pt[lo],pt[hi],Q,dir)==pt[lo])
            hi = mid - 1; else lo = mid + 1;
    }
}

```

```

    }
    if(!nxt) {
        if(orient(Q,pt[mid],pt[lo])==dir) lo=mid+1;
        else if(better(pt[lo],pt[hi],Q,dir)==pt[lo])
            hi = mid - 1; else lo = mid + 1;
    }
}
PT ret = pt[lo];
for(int i = lo + 1; i <= hi; i++)
    ret = better(ret, pt[i], Q, dir);
return ret;
}
/// [ACW, CW] Tangent
pair<PT,PT> pointPolyTangents(
    const Polygon &pt,PT Q) {
    int n = pt.size();
    PT acw_tan = pointPolyTangent(pt, Q, ACW,0,n-1);
    PT cw_tan = pointPolyTangent(pt, Q, CW, 0, n-1);
    return make_pair(acw_tan, cw_tan);
}
#####
namespace Circular {
/// returns intersections in order of ray (l.a,l.b)
vector<PT>circleLineIntersection(Circle c,Line l){
    static_assert(is_same<Tf, Ti>::value);
    vector<PT> ret;
    PT b = l.b - l.a, a = l.a - c.o;
    Tf A = dot(b, b), B = dot(a, b);
    Tf C = dot(a, a) - c.r * c.r, D = B*B - A*C;
    if (D < -EPS) return ret;
    ret.push_back(l.a + b * (-B-sqrt(D + EPS)) / A);
    if (D > EPS)
        ret.push_back(l.a + b * (-B + sqrt(D)) / A);
    return ret;
}
/// circle(c.o, c.r) x triangle(c.o,s.a,s.b) (ccw)
Tf circleTriInterArea(Circle c, Segment s){
    using Linear::distancePointSegment;
    Tf OA = length(c.o-s.a), OB = length(c.o-s.b);
    if(dcmp(distancePointSegment(c.o, s) - c.r) >= 0)
        return angleBetween(s.a-c.o,s.b-c.o)*c.r*c.r/2;
    if(dcmp(OA - c.r) <= 0 && dcmp(OB - c.r) <= 0)
        return cross(c.o - s.b, s.a - s.b) / 2.0;
    vector<PT> Sect = circleLineIntersection(c, s);
    return circleTriInterArea(c,Segment(s.a,Sect[0]))
        +circleTriInterArea(c,Segment(Sect[0],Sect[1]))
        + circleTriInterArea(c,Segment(Sect[1],s.b));
}
Tf circlePolyIntersectionArea(Circle c, Polygon p){
    Tf res = 0;
    int n = p.size();
    for(int i = 0; i < n; ++i)
        res +=circleTriInterArea(c,
            Segment(p[i], p[(i + 1) % n]));
    return abs(res);
}
/// locates circle c2 relative to c1: intersect = 0
/// inside = -2, inside touch = -1,
/// outside touch = 1, outside = 2
int circleCirclePosition(Circle c1, Circle c2) {
    Tf d = length(c1.o - c2.o);
    int in = dcmp(d - abs(c1.r - c2.r)),
        ex = dcmp(d - (c1.r + c2.r));
    return in<0?-2:in==0?-1: ex==0?1: ex>0?2:0;
}
vector<PT> circleCircleInter(Circle c1, Circle c2){
    static_assert(is_same<Tf, Ti>::value);
    vector<PT> ret;
    Tf d = length(c1.o - c2.o);
    if(dcmp(d) == 0) return ret;
    if(dcmp(c1.r + c2.r - d) < 0) return ret;
    if(dcmp(abs(c1.r - c2.r) - d) > 0) return ret;
    PT v = c2.o - c1.o;
    Tf co = (c1.r * c1.r + sqLength(v) - c2.r*c2.r)
        / (2 * c1.r * length(v));
    Tf si = sqrt(abs(1.0 - co * co));
    PT p1 = scale(rotatePrecise(v,co,-si),c1.r)+c1.o;
    PT p2 = scale(rotatePrecise(v,co,si),c1.r)+c1.o;
    ret.push_back(p1);
}

```

```

    if(p1 != p2) ret.push_back(p2); return ret;
}
Tf circleCircleInterArea(Circle c1, Circle c2) {
    PT AB = c2.o - c1.o; Tf d = length(AB);
    if(d >= c1.r + c2.r) return 0;
    if(d + c1.r <= c2.r) return PI * c1.r * c1.r;
    if(d + c2.r <= c1.r) return PI * c2.r * c2.r;
    Tf alpha1 = acos((c1.r*c1.r + d*d - c2.r*c2.r)
        / (2.0 * c1.r * d));
    Tf alpha2 = acos((c2.r*c2.r + d*d - c1.r*c1.r)
        / (2.0 * c2.r * d));
    return c1.sector(2*alpha1)+c2.sector(2*alpha2);
}
// returns tangents from a point p to circle c
vector<PT> pointCircleTangents(PT p, Circle c) {
    static_assert(is_same<Tf, Ti>::value);
    vector<PT> ret; PT u = c.o - p; Tf d = length(u);
    if(d < c.r) ;
    else if(dcmp(d - c.r) == 0) {
        ret = { rotate(u, PI / 2) }; }
    else {
        Tf ang = asin(c.r / d);
        ret = { rotate(u, -ang), rotate(u, ang) };
    } return ret;
}
//returns points on tangents that touches circle c
vector<PT> pointCircleTangencyPoints(PT p, Circle c){
    static_assert(is_same<Tf, Ti>::value);
    PT u = p - c.o; Tf d = length(u);
    if(d < c.r) return {};
    else if(dcmp(d - c.r) == 0) return {c.o + u};
    else {
        Tf ang = acos(c.r / d); u = u/length(u) * c.r;
        return{c.o+rotate(u,-ang), c.o+rotate(u,ang)};
    }
}
// finds a, b st a[i] on c1, b[i] on c2, Segment
// a[i], b[i] touches c1, c2. if c1, c2 touch at x
// (x, x) is also returned, -1 returned if c1 = c2
int circleCircleTangencyPoints(Circle c1, Circle c2,
    vector<PT> &a, vector<PT> &b) {
    a.clear(), b.clear(); int cnt = 0;
    if(dcmp(c1.r-c2.r)<0) {swap(c1, c2);swap(a, b);}
    Tf d2 = sqLength(c1.o - c2.o);
    Tf rdif = c1.r - c2.r, rsum = c1.r + c2.r;
    if(dcmp(d2 - rdif * rdif) < 0) return 0;
    if(dcmp(d2)==0 && dcmp(c1.r-c2.r)==0) return -1;
    Tf base = angle(c2.o - c1.o);
    if(dcmp(d2 - rdif * rdif) == 0) {
        a.push_back(c1.point(base));
        b.push_back(c2.point(base));
        cnt++; return cnt;
    }
    Tf ang = acos((c1.r - c2.r) / sqrt(d2));
    a.push_back(c1.point(base + ang));
    b.push_back(c2.point(base + ang)); cnt++;
    a.push_back(c1.point(base - ang));
    b.push_back(c2.point(base - ang)); cnt++;
    if(dcmp(d2 - rsum * rsum) == 0) {
        a.push_back(c1.point(base));
        b.push_back(c2.point(PI + base)); cnt++;
    }
    else if(dcmp(d2 - rsum * rsum) > 0) {
        Tf ang = acos((c1.r + c2.r) / sqrt(d2));
        a.push_back(c1.point(base + ang));
        b.push_back(c2.point(PI + base + ang)); cnt++;
        a.push_back(c1.point(base - ang));
        b.push_back(c2.point(PI + base - ang)); cnt++;
    } return cnt;
} } // namespace Circular
#####
namespace EnclosingCircle{
// returns false if points are collinear
bool inCircle(PT a, PT b, PT c, Circle &p) {
    using Linear::distancePointLine;
    static_assert(is_same<Tf, Ti>::value);
    if(orient(a, b, c) == 0) return false;

```

```

    Tf u=length(b-c), v=length(c-a), w=length(a-b);
    p.o = (a * u + b * v + c * w) / (u + v + w);
    p.r = distancePointLine(p.o, Line(a, b));
    return true;
}
// set of points A(x, y) st PA : QA = rp : rq
Circle apolloniusCircle(PT P, PT Q, Tf rp, Tf rq){
    static_assert(is_same<Tf, Ti>::value);
    rq *= rq; rp *= rp; Tf a=rq-rp; assert(dcmp(a));
    Tf g = (rq*P.x-rp*Q.x)/a, h = (rq*P.y-rp*Q.y)/a;
    Tf c = (rq*P.x*P.x - rp*Q.x*Q.x +
        rq*P.y*P.y - rp*Q.y*Q.y)/a;
    PT o(g, h); Tf R = sqrt(g * g + h * h - c);
    return Circle(o, R);
}
// returns false if points are collinear
bool circumCircle(PT a, PT b, PT c, Circle &p) {
    using Linear::lineLineIntersect;
    if(orient(a, b, c) == 0) return false;
    PT d = (a + b) / 2, e = (a + c) / 2;
    PT vd = rotate90(b - a), ve = rotate90(a - c);
    bool f = lineLineIntersect(d, vd, e, ve, p.o);
    if(f) p.r = length(a - p.o);
    return f;
}
// finds a circle that goes all of p, |p| <= 3.
Circle boundary(const vector<PT> &p) {
    Circle ret; int sz = p.size();
    if(sz == 0) ret.r = 0;
    else if(sz == 1) ret.o = p[0], ret.r = 0;
    else if(sz == 2) ret.o = (p[0] + p[1]) / 2,
        ret.r = length(p[0] - p[1]) / 2;
    else if(!circumCircle(p[0], p[1], p[2], ret))
        ret.r = 0;
    return ret;
}
// Min circle enclosing p[fr....n-1],
//with points in b on the boundary, |b| <= 3.
Circle welzl(const vector<PT> &p,
    int fr, vector<PT> &b) {
    if(fr >= (int) p.size() || b.size() == 3)
        return boundary(b);
    Circle c = welzl(p, fr + 1, b);
    if(!c.contains(p[fr])) {
        b.push_back(p[fr]); c = welzl(p, fr + 1, b);
        b.pop_back();
    } return c;
}
// MEC of p, using welzl's algo. amortized O(n).
Circle MEC(vector<PT> p) {
    random_shuffle(p.begin(), p.end());
    vector<PT> q; return welzl(p, 0, q);
}
#####
// Given list of segments v, finds a pair (i, j) st
// v[i], v[j] intersects. If none, returns {-1, -1}
namespace IntersectingSegments {
struct Event {
    Tf x; int tp, id;
    bool operator < (const Event &p) const {
        if(dcmp(x-p.x)) return x<p.x; return tp>p.tp;
    }
};
pair<int, int> anyInters(const vector<Segment> &v){
    using Linear::segmentsIntersect;
    static_assert(is_same<Tf, Ti>::value);
    vector<Event> ev;
    for(int i=0; i<v.size(); i++) {
        ev.push_back({min(v[i].a.x, v[i].b.x), +1, i});
        ev.push_back({max(v[i].a.x, v[i].b.x), -1, i});
    }
    sort(ev.begin(), ev.end());
    auto comp = [&v] (int i, int j) {
        Segment p = v[i], q = v[j];
        Tf x=max(min(p.a.x,p.b.x), min(q.a.x, q.b.x));
        auto yvalSegment = [&x] (const Line &s) {
            if(dcmp(s.a.x - s.b.x) == 0) return s.a.y;
            return s.a.y + (s.b.y - s.a.y)

```

```

        * (x - s.a.x) / (s.b.x - s.a.x);
    };
    return dcmp(yvalSegment(p)-yvalSegment(q))<0;
};
multiset<int, decltype(comp)> st(comp);
typedef decltype(st)::iterator iter;
auto prev = [&st](iter it) {
    return it == st.begin() ? st.end() : --it;
};
auto next = [&st](iter it) {
    return it == st.end() ? st.end() : ++it;
};
vector<iter> pos(v.size());
for(auto &cur : ev) {
    int id = cur.id;
    if(cur.tp == 1) {
        iter nxt = st.lower_bound(id), pre=prev(nxt);
        if(pre != st.end() && segmentsIntersect
            (v[*pre], v[id])) return {*pre, id};
        if(nxt != st.end() && segmentsIntersect
            (v[*nxt], v[id])) return {*nxt, id};
        pos[id] = st.insert(nxt, id);
    }
    else {
        iter nxt=next(pos[id]), pre=prev(pos[id]);
        if(pre != st.end() && nxt != st.end() &&
            segmentsIntersect(v[*pre], v[*nxt]))
            return {*pre, *nxt};
        st.erase(pos[id]);
    }
} return {-1, -1};
} }
#####

```

5.10 vertical-decomposition

```

typedef double dbl;
const dbl eps = 1e-9;
inline bool eq(dbl x, dbl y){
    return fabs(x - y) < eps;
}
inline bool lt(dbl x, dbl y){
    return x < y - eps;
}
inline bool gt(dbl x, dbl y){
    return x > y + eps;
}
inline bool le(dbl x, dbl y){
    return x < y + eps;
}
inline bool ge(dbl x, dbl y){
    return x > y - eps;
}
struct pt{
    dbl x, y;
    inline pt operator - (const pt &p)const{
        return pt{x - p.x, y - p.y};
    }
    inline pt operator + (const pt &p)const{
        return pt{x + p.x, y + p.y};
    }
    inline pt operator * (dbl a)const{
        return pt{x * a, y * a};
    }
    inline dbl cross(const pt &p)const{
        return x * p.y - y * p.x;
    }
    inline dbl dot(const pt &p)const{
        return x * p.x + y * p.y;
    }
    inline bool operator == (const pt &p)const{
        return eq(x, p.x) && eq(y, p.y);
    }
};
struct Line{
    pt p[2];
    Line(){
        Line(pt a, pt b):p{a, b}{}
        pt vec()const{

```

```

    return p[i] - p[0];
}
pt& operator [](size_t i){
    return p[i];
}
};
inline bool lexComp(const pt & l, const pt & r){
    if(fabs(l.x - r.x) > eps){
        return l.x < r.x;
    }
    else return l.y < r.y;
}
vector<pt> interSegSeg(Line l1, Line l2){
    if(eq(l1.vec().cross(l2.vec()), 0)){
        if(!eq(l1.vec().cross(l2[0] - l1[0]), 0))
            return {};
        if(!lexComp(l1[0], l1[1]))
            swap(l1[0], l1[1]);
        if(!lexComp(l2[0], l2[1]))
            swap(l2[0], l2[1]);
        pt l = lexComp(l1[0], l2[0]) ? l2[0] : l1[0];
        pt r = lexComp(l1[1], l2[1]) ? l1[1] : l2[1];
        if(l == r)
            return {l};
        else return lexComp(l, r) ? vector<pt>{l, r} :
            vector<pt>{};
    }
    else{
        dbl s = (l2[0] - l1[0]).cross(l2.vec()) /
            l1.vec().cross(l2.vec());
        pt inter = l1[0] + l1.vec() * s;
        if(ge(s, 0) && le(s, 1) && le((l2[0] - inter).dot(l2[1]
            - inter), 0))
            return {inter};
        else
            return {};
    }
}
inline char get_segtype(Line segment, pt other_point){
    if(eq(segment[0].x, segment[1].x))
        return 0;
    if(!lexComp(segment[0], segment[1]))
        swap(segment[0], segment[1]);
    return (segment[1] - segment[0]).cross(other_point -
        segment[0]) > 0 ? 1 : -1;
}
dbl union_area(vector<tuple<pt, pt, pt> > triangles){
    vector<Line> segments(3 * triangles.size());
    vector<char> segtype(segments.size());
    for(size_t i = 0; i < triangles.size(); i++){
        pt a, b, c;
        tie(a, b, c) = triangles[i];
        segments[3 * i] = lexComp(a, b) ? Line(a, b) : Line(b, a);
        segtype[3 * i] = get_segtype(segments[3 * i], c);
        segments[3 * i + 1] = lexComp(b, c) ? Line(b, c) : Line(c, b);
        segtype[3 * i + 1] = get_segtype(segments[3 * i + 1], a);
        segments[3 * i + 2] = lexComp(c, a) ? Line(c, a) : Line(a, c);
        segtype[3 * i + 2] = get_segtype(segments[3 * i + 2], b);
    }
    vector<dbl> k(segments.size()), b(segments.size());
    for(size_t i = 0; i < segments.size(); i++){
        if(segtype[i]){
            k[i] = (segments[i][1].y - segments[i][0].y) /
                (segments[i][1].x - segments[i][0].x);
            b[i] = segments[i][0].y - k[i] * segments[i][0].x;
        }
    }
    dbl ans = 0;
    for(size_t i = 0; i < segments.size(); i++){
        if(!segtype[i])
            continue;
        dbl l = segments[i][0].x, r = segments[i][1].x;
        vector<pair<dbl, int> > evts;
        for(size_t j = 0; j < segments.size(); j++){
            if(!segtype[j] || i == j)
                continue;
            dbl l1 = segments[j][0].x, r1 = segments[j][1].x;
            if(ge(l1, r) || ge(l, r1))

```

```

                continue;
            dbl common_l = max(l, l1), common_r = min(r, r1);
            auto pts = interSegSeg(segments[i], segments[j]);
            if(pts.empty()){
                dbl y11 = k[j] * common_l + b[j];
                dbl y1 = k[i] * common_l + b[i];
                if(lt(y11, y1) == (segtype[i] == 1)){
                    int evt_type = -segtype[i] * segtype[j];
                    evts.emplace_back(common_l, evt_type);
                    evts.emplace_back(common_r, -evt_type);
                }
            }
            else if(pts.size() == 1u){
                dbl y1 = k[i] * common_l + b[i], y11 = k[j] * common_l + b[j];
                int evt_type = -segtype[i] * segtype[j];
                if(lt(y11, y1) == (segtype[i] == 1)){
                    evts.emplace_back(common_l, evt_type);
                    evts.emplace_back(pts[0].x, -evt_type);
                }
            }
            y1 = k[i] * common_r + b[i], y11 = k[j] * common_r + b[j];
            if(lt(y11, y1) == (segtype[i] == 1)){
                evts.emplace_back(pts[0].x, evt_type);
                evts.emplace_back(common_r, -evt_type);
            }
        }
        else{
            if(segtype[j] != segtype[i] || j > i){
                evts.emplace_back(common_l, -2);
                evts.emplace_back(common_r, 2);
            }
        }
    }
    evts.emplace_back(l, 0); sort(evts.begin(), evts.end());
    size_t j = 0; int balance = 0;
    while(j < evts.size()){
        size_t ptr = j;
        while(ptr < evts.size() && eq(evts[j].first,
            evts[ptr].first)){
            balance += evts[ptr].second;
            ++ptr;
        }
        if(!balance && !eq(evts[j].first, r)){
            dbl next_x = ptr == evts.size() ? r :
                evts[ptr].first;
            ans -= segtype[i] * k[i] * (next_x +
                evts[j].first) + 2 * b[i] * (next_x -
                evts[j].first);
        }
        j = ptr;
    }
    return ans/2;
}
pair<dbl,dbl> union_perimeter(vector<tuple<pt, pt, pt> >
    triangles){
    //Same as before
    pair<dbl,dbl> ans = make_pair(0,0);
    for(size_t i = 0; i < segments.size(); i++){
        //Same as before
        double dist=(segments[i][1].x-segments[i][0].x)
            *(segments[i][1].x-segments[i][0].x)
            +(segments[i][1].y-segments[i][0].y)
            *(segments[i][1].y-segments[i][0].y);
        dist=sqrt(dist);
        while(j < evts.size()){
            size_t ptr = j;
            while(ptr < evts.size() && eq(evts[j].first,
                evts[ptr].first)){
                balance += evts[ptr].second; ++ptr;
            }
            if(!balance && !eq(evts[j].first, r)){
                dbl next_x = ptr == evts.size() ? r :
                    evts[ptr].first;
                ans.first += dist * (next_x - evts[j].first) /
                    (r-l);
                if(eq(segments[i][1].y, segments[i][0].y))
                    ans.second += (next_x - evts[j].first);
            }
        }
    }
}

```

```

    }
    j = ptr;
}
return ans;
}

```

6 Graph

6.1 DMST with solution

```

// not tested yet
const int INF = 1029384756;
#define MAXN 1000
#define FOR(i,x) for(auto i : x)
struct edge_t {
    int u,v,w;
    set<pair<int,int> > add, sub;
    edge_t() : u(-1), v(-1), w(0) {}
    edge_t(int _u, int _v, int _w) {
        u = _u;
        v = _v;
        w = _w;
        add.insert({u, v});
    }
    edge_t& operator += (const edge_t& obj) {
        w += obj.w;
        for (auto it : obj.add) {
            if (!sub.count(it)) add.insert(it);
            else sub.erase(it);
        }
        for (auto it : obj.sub) {
            if (!add.count(it)) sub.insert(it);
            else add.erase(it);
        }
        return *this;
    }
    edge_t& operator -= (const edge_t& obj) {
        w -= obj.w;
        for (auto it : obj.sub) {
            if (!sub.count(it)) add.insert(it);
            else sub.erase(it);
        }
        for (auto it : obj.add) {
            if (!add.count(it)) sub.insert(it);
            else add.erase(it);
        }
        return *this;
    }
} eg[MAXN*MAXN], prv[MAXN], EDGE_INF(-1,-1,INF);
int N,M;
int cid,incyc[MAXN],contracted[MAXN];
vector<int> E[MAXN];
edge_t dmst(int rt) {
    edge_t cost;
    for (int i=0; i<N; i++) {
        contracted[i] = incyc[i] = 0;
        prv[i] = EDGE_INF;
    }
    cid = 0;
    int u,v;
    while (true) {
        for (v=0; v<N; v++) {
            if (v != rt && !contracted[v] && prv[v].w == INF)
                break;
        }
        if (v >= N) break; // end
        for (int i=0; i<M; i++) {
            if (eg[i].v == v && eg[i].w < prv[v].w)
                prv[v] = eg[i];
        }
        if (prv[v].w == INF) // not connected
            return EDGE_INF;
        cost += prv[v];
        for (u=prv[v].u; u!=v && u!=-1; u=prv[u].u);
        if (u == -1) continue;
        incyc[v] = ++cid;
        for (u=prv[v].u; u!=v; u=prv[u].u) {
            contracted[u] = 1;
            incyc[u] = cid;
        }
    }
}

```

```

for (int i=0; i<M; i++) {
    if (incyc[eg[i].u] != cid && incyc[eg[i].v] == cid) {
        eg[i] -= prv[eg[i].v];
    }
}
for (int i=0; i<M; i++) {
    if (incyc[eg[i].u] == cid) eg[i].u = v;
    if (incyc[eg[i].v] == cid) eg[i].v = v;
    if (eg[i].u == eg[i].v) eg[i--] = eg[--M];
}
for (int i=0; i<N; i++) {
    if (contracted[i]) continue;
    if (prv[i].u>0 && incyc[prv[i].u] == cid)
        prv[i].u = v;
}
prv[v] = EDGE_INF;
}
return cost;
}
#define F first
#define S second
void solve() {
    edge_t cost = dmst(0);
    for (auto it : cost.add) { // find a solution
        E[it.F].push_back(it.S);
        prv[it.S] = edge_t(it.F, it.S, 0);
    }
}
}

```

6.2 DMST

```

// tested on https://lightoj.com/problem/teleport
const int inf = 1e9;
struct edge {
    int u, v, w;
    edge() {}
    edge(int a, int b, int c) : u(a), v(b), w(c) {}
    bool operator < (const edge& o) const {
        if (u == o.u)
            if (v == o.v) return w < o.w;
            else return v < o.v;
        return u < o.u;
    }
};
int dmst(vector<edge> &edges, int root, int n) {
    int ans = 0;
    int cur_nodes = n;
    while (true) {
        vector<int> lo(cur_nodes, inf), pi(cur_nodes, inf);
        for (int i = 0; i < edges.size(); ++i) {
            int u = edges[i].u, v = edges[i].v, w = edges[i].w;
            if (w < lo[v] and u != v) {
                lo[v] = w;
                pi[v] = u;
            }
        }
        lo[root] = 0;
        for (int i = 0; i < lo.size(); ++i) {
            if (i == root) continue;
            if (lo[i] == inf) return -1;
        }
        int cur_id = 0;
        vector<int> id(cur_nodes, -1), mark(cur_nodes, -1);
        for (int i = 0; i < cur_nodes; ++i) {
            ans += lo[i];
            int u = i;
            while (u != root and id[u] < 0 and mark[u] != i) {
                mark[u] = i;
                u = pi[u];
            }
            if (u != root and id[u] < 0) { // Cycle
                for (int v = pi[u]; v != u; v = pi[v]) id[v] = cur_id;
                id[u] = cur_id++;
            }
        }
        if (cur_id == 0) break;
        for (int i = 0; i < cur_nodes; ++i)
            if (id[i] < 0) id[i] = cur_id++;
    }
}

```

```

for (int i = 0; i < edges.size(); ++i) {
    int u = edges[i].u, v = edges[i].v, w = edges[i].w;
    edges[i].u = id[u];
    edges[i].v = id[v];
    if (id[u] != id[v]) edges[i].w -= lo[v];
}
cur_nodes = cur_id;
root = id[root];
return ans;
}

```

6.3 Flow With Demands

Finding an arbitrary flow Consider flow networks, where we additionally require the flow of each edge to have a certain amount, i.e. we bound the flow from below by a **demand** function $d(e)$:

$$d(e) \leq f(e) \leq c(e)$$

So next each edge has a minimal flow value, that we have to pass along the edge.

We make the following changes in the network. We add a new source s' and a new sink t' , a new edge from the source s' to every other vertex, a new edge for every vertex to the sink t' , and one edge from t to s . Additionally we define the new capacity function c' as:

- $c'((s', v)) = \sum_{u \in V} d((u, v))$ for each edge (s', v) .
- $c'((v, t')) = \sum_{w \in V} d((v, w))$ for each edge (v, t') .
- $c'((u, v)) = c((u, v)) - d((u, v))$ for each edge (u, v) in the old network.
- $c'((t, s)) = \infty$

If the new network has a saturating flow (a flow where each edge outgoing from s' is completely filled, which is equivalent to every edge incoming to t' is completely filled), then the network with demands has a valid flow, and the actual flow can be easily reconstructed from the new network. Otherwise there doesn't exist a flow that satisfies all conditions. Since a saturating flow has to be a maximum flow, it can be found by any maximum flow algorithm.

Minimal flow Note that along the edge (t, s) (from the old sink to the old source) with the capacity ∞ flows the entire flow of the corresponding old network. I.e. the capacity of this edge effects the flow value of the old network. By giving this edge a sufficient large capacity (i.e. ∞), the flow of the old network is unlimited. By limiting this edge by smaller capacities, the flow value will decrease. However if we limit this edge by a too small value, than the network will not have a saturated solution, e.g. the corresponding solution for the original network will not satisfy the demand of the edges. Obviously here can use a binary search to find the lowest value with which all constraints are still satisfied. This gives the minimal flow of the original network.

6.4 articulation-vertex

```

int n; // number of nodes
vector<vector<int>> adj; // adjacency list of graph
vector<bool> visited;
vector<int> tin, low;
int timer;
void dfs(int v, int p = -1) {
    visited[v] = true;
    tin[v] = low[v] = timer++;
    int children=0;
    for (int to : adj[v]) {
        if (to == p) continue;
        if (visited[to]) {
            low[v] = min(low[v], tin[to]);
        } else {
            dfs(to, v);
            low[v] = min(low[v], low[to]);
            if (low[to] >= tin[v] && p != -1)
                IS_CUTPOINT(v);
            ++children;
        }
    }
    if (p == -1 && children > 1)
        IS_CUTPOINT(v);
}
void find_cutpoints() {
    timer = 0;
    visited.assign(n, false);
    tin.assign(n, -1);
    low.assign(n, -1);
    for (int i = 0; i < n; ++i) {
        if (!visited[i])
            dfs(i);
    }
}

```

6.5 bellman-ford

```

struct Edge {
    int a, b, cost;
};
int n, m;
vector<Edge> edges;
const int INF = 1000000000;
void solve() {
    vector<int> d(n);
    vector<int> p(n, -1);
    int x;
    for (int i = 0; i < n; ++i) {
        x = -1;
        for (Edge e : edges) {
            if (d[e.a] + e.cost < d[e.b]) {
                d[e.b] = d[e.a] + e.cost;
                p[e.b] = e.a;
                x = e.b;
            }
        }
    }
    if (x == -1) {
        cout << "No negative cycle found.";
    } else {
        for (int i = 0; i < n; ++i)
            x = p[x];
        vector<int> cycle;
        for (int v = x;; v = p[v]) {
            cycle.push_back(v);
            if (v == x && cycle.size() > 1)
                break;
        }
        reverse(cycle.begin(), cycle.end());
        cout << "Negative cycle: ";
        for (int v : cycle)
            cout << v << ' ';
        cout << endl;
    }
}

```

6.6 bridge

```

const int vmax = 2e5+10, emax = 2e5+10;
namespace Bridge {///edge, nodes, comps 1 indexed
    vector<int> adj[vmax]; /// edge-id
    pair<int, int> edges[emax]; /// (u, v)
    bool isBridge[emax];
    int visited[vmax]; ///0-unvis,1-vising,2-vis
    int st[vmax], low[vmax], clk = 0, edgeId = 0;
    /// For bridge tree components
    int who[vmax], compId = 0;
    vector<int> stk;
    /// For extra end time calc
    int en[vmax];
    void dfs(int u, int parEdge) {
        visited[u] = 1; low[u] = st[u] = ++clk;
        stk.push_back(u);
        for (auto e : adj[u]) {
            if (e == parEdge) continue;
            int v=edges[e].first^edges[e].second^u;
            if (visited[v] == 1) {
                low[u] = min(low[u], st[v]);
            } else if (visited[v] == 0) {
                dfs(v, e); low[u] = min(low[u], low[v]);
            }
        }
        visited[u] = 2;
        if(st[u] == low[u]){/// found
            ++compId; int cur;
            do{
                cur = stk.back(); stk.pop_back();
                who[cur] = compId;
            }while(cur != u);
            if(parEdge != -1){isBridge[parEdge] = true;}
        }
        en[u] = clk;
    }
    void clearAll(int n){
        for(int i = 0; i<n; i++) {
            adj[i].clear(); visited[i] = st[i] = 0; }
        for(int i = 0; i<=edgeId; i++) isBridge[i]=0;
        clk = compId = edgeId = 0;
    }
    void findBridges(int n){
        for(int i = 1; i<=n; i++){
            if(visited[i] == 0) dfs(i, -1); }
    }
    bool isReplacable(int eid, int u, int v){
        if(!isBridge[eid]) return true;
        int a=edges[eid].first,b=edges[eid].second;
        if(st[a] > st[b]) swap(a, b);
        return (st[b] <= st[u] && st[u] <= en[b])
            != (st[b] <= st[v] && st[v] <= en[b]);
    }
    void addEdge(int u, int v){
        edgeId++; edges[edgeId] = {u, v};
        adj[u].emplace_back(edgeId);
        adj[v].emplace_back(edgeId);
    }
}

```

6.7 edmond-blossom

```

/****Copied from https://codeforces.com/blog/entry/49402****/
/*
GETS:
V->number of vertices
E->number of edges
pair of vertices as edges (vertices are 1..V)
GIVES:
output of edmonds() is the maximum matching
match[i] is matched pair of i (-1 if there isn't a matched pair)
*/
const int M=500;
struct struct_edge
{
    int v;
    struct_edge* n;
};

```

```

typedef struct_edge* edge;
struct_edge pool[M*M*2];
edge top=pool,adj[M];
int V,E,match[M],qh,qt,q[M],father[M],base[M];
bool inq[M],inb[M],ed[M][M];
void add_edge(int u,int v)
{
    top->v=v,top->n=adj[u],adj[u]=top++;
    top->v=u,top->n=adj[v],adj[v]=top++;
}
int LCA(int root,int u,int v)
{
    static bool inp[M];
    memset(inp,0,sizeof(inp));
    while(1)
    {
        inp[u=base[u]]=true;
        if (u==root) break;
        u=father[match[u]];
    }
    while(1)
    {
        if (inp[v=base[v]]) return v;
        else v=father[match[v]];
    }
}
void mark_blossom(int lca,int u)
{
    while (base[u]!=lca)
    {
        int v=match[u];
        inb[base[u]]=inb[base[v]]=true;
        u=father[v];
        if (base[u]!=lca) father[u]=v;
    }
}
void blossom_contraction(int s,int u,int v)
{
    int lca=LCA(s,u,v);
    memset(inb,0,sizeof(inb));
    mark_blossom(lca,u);
    mark_blossom(lca,v);
    if (base[u]!=lca)
        father[u]=v;
    if (base[v]!=lca)
        father[v]=u;
    for (int u=0; u<V; u++)
        if (inb[base[u]])
        {
            base[u]=lca;
            if (!inq[u])
                inq[q[++qt]]=u=true;
        }
}
int find_augmenting_path(int s)
{
    memset(inq,0,sizeof(inq));
    memset(father,-1,sizeof(father));
    for (int i=0; i<V; i++) base[i]=i;
    inq[q[qh=qt=0]=s]=true;
    while (qh<=qt)
    {
        int u=q[qh++];
        for (edge e=adj[u]; e; e=e->n)
        {
            int v=e->v;
            if (base[u]!=base[v]&&match[u]!=v)
            {
                if ((v==s)|| (match[v]!=-1 &&
                    father[match[v]]!=-1))
                    blossom_contraction(s,u,v);
                else if (father[v]==-1)
                {
                    father[v]=u;
                    if (match[v]==-1)
                        return v;
                    else if (!inq[match[v]])
                        inq[q[++qt]=match[v]]=true;
                }
            }
        }
    }
}

```

```

    }
    return -1;
}
int augment_path(int s,int t)
{
    int u=t,v=w;
    while (u!=-1)
    {
        v=father[u];
        w=match[v];
        match[v]=u;
        match[u]=v;
        u=w;
    }
    return t!=-1;
}
int edmonds()//Gives number of matchings
{
    int matchc=0;
    memset(match,-1,sizeof(match));
    for (int u=0; u<V; u++)
        if (match[u]==-1)
            matchc+=augment_path(u,find_augmenting_path(u));
    return matchc;
}
//To add edge add_edge(u-1,v-1); ed[u-1][v-1]=ed[v-1][u-1]=true;

```

6.8 euler-path

```

int main() {
    int n;
    vector<vector<int>>> g(n, vector<int>(n));
    /// reading the graph in the adjacency matrix
    vector<int> deg(n);
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < n; ++j)
            deg[i] += g[i][j];
    }
    int first = 0;
    while (first < n && !deg[first])
        ++first;
    if (first == n) {
        cout << -1;
        return 0;
    }
    int v1 = -1, v2 = -1;
    bool bad = false;
    for (int i = 0; i < n; ++i) {
        if (deg[i] & 1) {
            if (v1 == -1)
                v1 = i;
            else if (v2 == -1)
                v2 = i;
            else
                bad = true;
        }
    }
    if (v1 != -1)
        ++g[v1][v2], ++g[v2][v1];
    stack<int> st;
    st.push(first);
    vector<int> res;
    while (!st.empty()) {
        int v = st.top();
        int i;
        for (i = 0; i < n; ++i)
            if (g[v][i])
                break;
        if (i == n) {
            res.push_back(v);
            st.pop();
        } else {
            --g[v][i];
            --g[i][v];
            st.push(i);
        }
    }
    if (v1 != -1) {
        for (size_t i = 0; i + 1 < res.size(); ++i) {
            if ((res[i] == v1 && res[i + 1] == v2) ||
                (res[i] == v2 && res[i + 1] == v1)) {

```



```

vector<int> res2;
for (size_t j = i + 1; j < res.size(); ++j)
    res2.push_back(res[j]);
for (size_t j = 1; j <= i; ++j)
    res2.push_back(res[j]);
res = res2;
break;
    }
}
for (int i = 0; i < n; ++i) {
    for (int j = 0; j < n; ++j) {
        if (g[i][j])
            bad = true;
    }
}
if (bad) {
    cout << -1;
} else {
    for (int x : res)
        cout << x << " ";
}
}

```

6.9 hopcraft-karp

```

/** Source: https://iq.opengenus.org/hopcroft-karp-algorithm/
**/
// A class to represent Bipartite graph for
// Hopcroft Karp implementation
class BGraph{
    // m and n are number of vertices on left
    // and right sides of Bipartite Graph
    int m, n;
    // adj[u] stores adjacents of left side
    // vertex 'u'. The value of u ranges from 1 to m.
    // 0 is used for dummy vertex
    std::list<int> *adj;
    // pointers for hopcroftKarp()
    int *pair_u, *pair_v, *dist;
public:
    BGraph(int m, int n); // Constructor
    void addEdge(int u, int v); // To add edge
    // Returns true if there is an augmenting path
    bool bfs();
    // Adds augmenting path if there is one beginning
    // with u
    bool dfs(int u);
    // Returns size of maximum matching
    int hopcroftKarpAlgorithm();
};
// Returns size of maximum matching
int BGraph::hopcroftKarpAlgorithm(){
    // pair_u[u] stores pair of u in matching on left side of
    // Bipartite Graph.
    // If u doesn't have any pair, then pair_u[u] is NIL
    pair_u = new int[m + 1];
    // pair_v[v] stores pair of v in matching on right side of
    // Bipartite Graph.
    // If v doesn't have any pair, then pair_v[v] is NIL
    pair_v = new int[n + 1];
    // dist[u] stores distance of left side vertices
    dist = new int[m + 1];
    // Initialize NIL as pair of all vertices
    for (int u = 0; u <= m; u++)
        pair_u[u] = NIL;
    for (int v = 0; v <= n; v++)
        pair_v[v] = NIL;
    // Initialize result
    int result = 0;
    // Keep updating the result while there is an
    // augmenting path possible.
    while (bfs()){
        // Find a free vertex to check for a matching
        for (int u = 1; u <= m; u++)
            // If current vertex is free and there is
            // an augmenting path from current vertex
            // then increment the result

```

```

        if (pair_u[u] == NIL && dfs(u))
            result++;
    }
    return result;
}
// Returns true if there is an augmenting path available, else
// returns false
bool BGraph::bfs(){
    std::queue<int> q; //an integer queue for bfs
    // First layer of vertices (set distance as 0)
    for (int u = 1; u <= m; u++){
        // If this is a free vertex, add it to queue
        if (pair_u[u] == NIL){
            // u is not matched so distance is 0
            dist[u] = 0;
            q.push(u);
        }
        // Else set distance as infinite so that this vertex is
        // considered next time for availability
        else
            dist[u] = INF;
    }
    // Initialize distance to NIL as infinite
    dist[NIL] = INF;
    // q is going to contain vertices of left side only.
    while (!q.empty()){
        // dequeue a vertex
        int u = q.front();
        q.pop();
        // If this node is not NIL and can provide a shorter
        // path to NIL then
        if (dist[u] < dist[NIL]){
            // Get all the adjacent vertices of the dequeued
            // vertex u
            std::list<int>::iterator it;
            for (it = adj[u].begin(); it != adj[u].end(); ++it){
                int v = *it;
                // If pair of v is not considered so far
                // i.e. (v, pair_v[v]) is not yet explored edge.
                if (dist[pair_v[v]] == INF){
                    // Consider the pair and push it to queue
                    dist[pair_v[v]] = dist[u] + 1;
                    q.push(pair_v[v]);
                }
            }
        }
    }
    // If we could come back to NIL using alternating path of
    // distinct
    // vertices then there is an augmenting path available
    return (dist[NIL] != INF);
}
// Returns true if there is an augmenting path beginning with
// free vertex u
bool BGraph::dfs(int u){
    if (u != NIL){
        std::list<int>::iterator it;
        for (it = adj[u].begin(); it != adj[u].end(); ++it){
            // Adjacent vertex of u
            int v = *it;
            // Follow the distances set by BFS search
            if (dist[pair_v[v]] == dist[u] + 1){
                // If dfs for pair of v also return true then
                // (dfs(pair_v[v]) == true){ // new matching
                // possible, store the matching
                pair_v[v] = u;
                pair_u[u] = v;
                return true;
            }
        }
    }
    // If there is no augmenting path beginning with u then.
    dist[u] = INF;
    return false;
}
return true;
}
// Constructor for initialization
BGraph::BGraph(int m, int n){

```

```

    this->m = m;
    this->n = n;
    adj = new std::list<int>[m + 1];
}
// function to add edge from u to v
void BGraph::addEdge(int u, int v){
    adj[u].push_back(v); // Add v to us list.
}

```

6.10 hungarian-algorithm

```

class HungarianAlgorithm{
    int N, inf, n, max_match;
    int *lx, *ly, *xy, *yx, *slack, *slackx, *prev;
    int **cost;
    bool *S, *T;
    void init_labels(){
        for (int x = 0; x < n; x++) lx[x] = 0;
        for (int y = 0; y < n; y++) ly[y] = 0;
        for (int x = 0; x < n; x++)
            for (int y = 0; y < n; y++)
                lx[x] = max(lx[x], cost[x][y]);
    }
    void update_labels(){
        int x, y, delta = inf; //init delta as infinity
        for (y = 0; y < n; y++) //calculate delta using slack
            if (!T[y])
                delta = min(delta, slack[y]);
        for (x = 0; x < n; x++) //update X labels
            if (S[x]) lx[x] -= delta;
        for (y = 0; y < n; y++) //update Y labels
            if (T[y]) ly[y] += delta;
        for (y = 0; y < n; y++) //update slack array
            if (!T[y])
                slack[y] -= delta;
    }
    void add_to_tree(int x, int prevx)
    // x - current vertex, prevx - vertex from X before x in the
    // alternating path,
    // so we add edges (prevx, xy[x]), (xy[x], x){
        S[x] = true; //add x to S
        prev[x] = prevx; //we need this when augmenting
        for (int y = 0; y < n; y++) //update slacks, because we
            // add new vertex to S
            if (lx[x] + ly[y] - cost[x][y] < slack[y]){
                slack[y] = lx[x] + ly[y] - cost[x][y];
                slackx[y] = x;
            }
    }
    void augment() //main function of the algorithm{
        if (max_match == n) return; //check wether matching is
        // already perfect
        int x, y, root; //just counters and root vertex
        int q[N], wr = 0, rd = 0; //q - queue for bfs, wr, rd -
        // write and read
        //pos in queue
        //memset(S, false, sizeof(S)); //init set S
        for (int i = 0; i < n; i++) S[i] = false;
        //memset(T, false, sizeof(T)); //init set T
        for (int i = 0; i < n; i++) T[i] = false;
        //memset(prev, -1, sizeof(prev)); //init set prev - for
        // the alternating tree
        for (int i = 0; i < n; i++) prev[i] = -1;
        for (x = 0; x < n; x++) //finding root of the tree{
            if (xy[x] == -1){
                q[wr++] = root = x;
                prev[x] = -2;
                S[x] = true;
                break;
            }
        }
        for (y = 0; y < n; y++) //initializing slack array{
            slack[y] = lx[root] + ly[y] - cost[root][y];
            slackx[y] = root;
        }
        while (true) //main cycle{
            while (rd < wr) //building tree with bfs cycle{
                x = q[rd++]; //current vertex from X part

```

```

    for (y = 0; y < n; y++) //iterate through all
        edges in equality graph{
            if (cost[x][y] == lx[x] + ly[y] && !T[y]){
                if (yx[y] == -1) break; //an exposed
                    vertex in Y found, so
//augmenting path exists!
                T[y] = true; //else just add y to T,
                q[wr++] = yx[y]; //add vertex yx[y],
                    which is matched
//with y, to the queue
                add_to_tree(yx[y], x); //add edges (x,y)
                    and (y,yx[y]) to the tree
            }
        }
        if (y < n) break; //augmenting path found!
    }
    if (y < n) break; //augmenting path found!
    update_labels(); //augmenting path not found, so
        improve labeling
    wr = rd = 0;
    for (y = 0; y < n; y++){
        //in this cycle we add edges that were added to
            the equality graph as a
//result of improving the labeling, we add edge (slackx[y], y)
        to the tree if
//and only if !T[y] && slack[y] == 0, also with this edge we
        add another one
//((y, yx[y]) or augment the matching, if y was exposed
        if (!T[y] && slack[y] == 0){
            if (yx[y] == -1) //exposed vertex in Y found
                - augmenting path exists!{
                    x = slackx[y];
                    break;
            }
            else{
                T[y] = true; //else just add y to T,
                if (!S[yx[y]]){
                    q[wr++] = yx[y]; //add vertex yx[y],
                        which is matched with
//y, to the queue
                    add_to_tree(yx[y], slackx[y]); //and
                        add edges (x,y) and (y,
//yx[y]) to the tree
                }
            }
        }
        if (y < n) break; //augmenting path found!
    }
    if (y < n) //we found augmenting path!{
        max_match++; //increment matching
//in this cycle we inverse edges along augmenting path
        for (int cx = x, cy = y, ty; cx != -2; cx =
            prev[cx], cy = ty){
            ty = xy[cx];
            yx[cy] = cx;
            xy[cx] = cy;
        }
        augment(); //recall function, go to step 1 of the
            algorithm
    }
}
} //end of augment() function
public:
    HungarianAlgorithm(int vv,int inf=1000000000){
        N=vv;
        n=N;
        max_match=0;
        this->inf=inf;
        lx=new int[N];
        ly=new int[N]; //labels of X and Y parts
        xy=new int[N]; //xy[x] - vertex that is matched with x,
        yx=new int[N]; //yx[y] - vertex that is matched with y
        slack=new int[N]; //as in the algorithm description
        slackx=new int[N]; //slackx[y] such a vertex, that
            l(slackx[y]) + l(y) - w(slackx[y],y) = slack[y]
        prev=new int[N]; //array for memorizing alternating paths
        S=new bool[N];
        T=new bool[N]; //sets S and T in algorithm

```

```

        cost=new int*[N]; //cost matrix
        for(int i=0; i<N; i++){
            cost[i]=new int[N];
        }
    }
    HungarianAlgorithm(){
        delete [] lx;
        delete [] ly;
        delete [] xy;
        delete [] yx;
        delete [] slack;
        delete [] slackx;
        delete [] prev;
        delete [] S;
        delete [] T;
        int i;
        for(i=0; i<N; i++){
            delete [] (cost[i]);
        }
        delete [] cost;
    }
    void setCost(int i,int j,int c){
        cost[i][j]=c;
    }
    int* matching(bool first=true){
        int *ans;
        ans=new int[N];
        for(int i=0; i<N; i++){
            if(first) ans[i]=xy[i];
            else ans[i]=yx[i];
        }
        return ans;
    }
    int hungarian(){
        int ret = 0; //weight of the optimal matching
        max_match = 0; //number of vertices in current matching
        for(int x=0; x<n; x++) xy[x]=-1;
        for(int y=0; y<n; y++) yx[y]=-1;
        init_labels(); //step 0
        augment(); //steps 1-3
        for (int x = 0; x < n; x++) //forming answer there
            ret += cost[x][xy[x]];
        return ret;
    }
}

```

6.11 max-flow-dinic

```

#include<bits/stdc++.h>
#include<vector>
using namespace std;
#define MAX 100
#define HUGE_FLOW 1000000000
#define BEGIN 1
#define DEFAULT_LEVEL 0
struct FlowEdge {
    int v, u;
    long long cap, flow = 0;
    FlowEdge(int v, int u, long long cap) : v(v), u(u),
        cap(cap) {}
};
struct Dinic {
    const long long flow_inf = 1e18;
    vector<FlowEdge> edges;
    vector<vector<int>> adj;
    int n, m = 0;
    int s, t;
    vector<int> level, ptr;
    queue<int> q;
    Dinic(int n, int s, int t) : n(n), s(s), t(t) {
        adj.resize(n);
        level.resize(n);
        ptr.resize(n);
    }
    void add_edge(int v, int u, long long cap) {
        edges.emplace_back(v, u, cap);
        edges.emplace_back(u, v, 0);
        adj[v].push_back(m);
        adj[u].push_back(m + 1);
        m += 2;
    }

```

```

}
bool bfs() {
    while (!q.empty()) {
        int v = q.front();
        q.pop();
        for (int id : adj[v]) {
            if (edges[id].cap - edges[id].flow < 1)
                continue;
            if (level[edges[id].u] != -1)
                continue;
            level[edges[id].u] = level[v] + 1;
            q.push(edges[id].u);
        }
    }
    return level[t] != -1;
}
long long dfs(int v, long long pushed) {
    if (pushed == 0)
        return 0;
    if (v == t)
        return pushed;
    for (int& cid = ptr[v]; cid < (int)adj[v].size();
        cid++) {
        int id = adj[v][cid];
        int u = edges[id].u;
        if (level[v] + 1 != level[u] || edges[id].cap -
            edges[id].flow < 1)
            continue;
        long long tr = dfs(u, min(pushed, edges[id].cap -
            edges[id].flow));
        if (tr == 0)
            continue;
        edges[id].flow += tr;
        edges[id ^ 1].flow -= tr;
        return tr;
    }
    return 0;
}
long long flow() {
    long long f = 0;
    while (true) {
        fill(level.begin(), level.end(), -1);
        level[s] = 0;
        q.push(s);
        if (!bfs())
            break;
        fill(ptr.begin(), ptr.end(), 0);
        while (long long pushed = dfs(s, flow_inf)) {
            f += pushed;
        }
    }
    return f;
}
int main(){
    return 0;
}

```

6.12 min-cost-max-flow

```

struct Edge{ int from, to, capacity, cost; };
vector<vector<int>> adj, cost, capacity;
const int INF = 1e9;
void shortest_paths(int n,int v0,vector<int>&d,vector<int>&p){
    d.assign(n, INF); d[v0] = 0; vector<bool> inq(n, false);
    queue<int> q; q.push(v0); p.assign(n, -1);
    while (!q.empty()) {
        int u = q.front(); q.pop(); inq[u] = false;
        for (int v : adj[u]) {
            if (capacity[u][v] > 0 && d[v] > d[u]+cost[u][v]){
                d[v] = d[u] + cost[u][v]; p[v] = u;
                if (!inq[v]) { inq[v] = true; q.push(v); }
            }
        }
    }
}
int min_cost_flow(int N,vector<Edge> edges,int K,int s,int t) {
    adj.assign(N,vector<int>()); cost.assign(N,vector<int>(N,0));
    capacity.assign(N, vector<int>(N, 0));

```

```

for (Edge e : edges) {
    adj[e.from].push_back(e.to); adj[e.to].push_back(e.from);
    cost[e.from][e.to] = e.cost; cost[e.to][e.from] = -e.cost;
    capacity[e.from][e.to] = e.capacity; }
int flow = 0; int cost = 0;
vector<int> d, p;
while (flow < K) {
    shortest_paths(N, s, d, p); if (d[t] == INF) break;
    // find max flow on that path
    int f = K - flow; int cur = t;
    while (cur != s) {
        f = min(f, capacity[p[cur]][cur]); cur = p[cur];
    }
    // apply flow
    flow += f; cost += f * d[t]; cur = t;
    while (cur != s) {
        capacity[p[cur]][cur] -= f; capacity[cur][p[cur]] += f;
        cur = p[cur]; }
    }
    if (flow < K) return -1;
    else return cost;
}

```

6.13 online-bridge

```

vector<int> par, dsu_2ecc, dsu_cc, dsu_cc_size;
int bridges; int lca_iteration;
vector<int> last_visit;
void init(int n) {
    par.resize(n); dsu_2ecc.resize(n); dsu_cc.resize(n);
    dsu_cc_size.resize(n); lca_iteration=0; last_visit.assign(n,0);
    for (int i=0; i<n; ++i) {
        dsu_2ecc[i] = i; dsu_cc[i] = i; dsu_cc_size[i] = 1;
        par[i] = -1;
    }
    bridges = 0;
}
int find_2ecc(int v) {
    if (v == -1) return -1;
    return dsu_2ecc[v]==v?v:dsu_2ecc[v]=find_2ecc(dsu_2ecc[v]);
}
int find_cc(int v) {
    v = find_2ecc(v);
    return dsu_cc[v] == v ? v : dsu_cc[v] = find_cc(dsu_cc[v]);
}
void make_root(int v) {
    v = find_2ecc(v); int root = v; int child = -1;
    while (v != -1) {
        int p = find_2ecc(par[v]); par[v] = child;
        dsu_cc[v] = root; child = v; v = p;
    }
    dsu_cc_size[root] = dsu_cc_size[child];
}
void merge_path (int a, int b) {
    ++lca_iteration; vector<int> path_a, path_b; int lca = -1;
    while (lca == -1) {
        if (a != -1) {
            a = find_2ecc(a); path_a.push_back(a);
            if (last_visit[a] == lca_iteration){
                lca = a; break; }
            last_visit[a] = lca_iteration; a = par[a];
        }
        if (b != -1) {
            b = find_2ecc(b); path_b.push_back(b);
            if (last_visit[b] == lca_iteration){
                lca = b; break; }
            last_visit[b] = lca_iteration; b = par[b];
        }
    }
    for (int v : path_a) {
        dsu_2ecc[v] = lca; if (v == lca) break; --bridges;
    }
    for (int v : path_b) {
        dsu_2ecc[v] = lca; if (v == lca) break; --bridges;
    }
}
void add_edge(int a, int b) {
    a = find_2ecc(a); b = find_2ecc(b);
    if (a == b) return;

```

```

int ca = find_cc(a); int cb = find_cc(b);
if (ca != cb) {
    ++bridges;
    if (dsu_cc_size[ca] > dsu_cc_size[cb]) {
        swap(a, b); swap(ca, cb); }
    make_root(a); par[a] = dsu_cc[a] = b;
    dsu_cc_size[cb] += dsu_cc_size[a];
} else {
    merge_path(a, b);
}
}

```

6.14 scc + 2 Sat

```

namespace SCC { //Everything 0-indexed.
const int N = 2e6+7; int which[N], vis[N], cc;
vector<int> adj[N], adjr[N]; vector<int> order;
void addEdge(int u, int v) {
    adj[u].push_back(v); adjr[v].push_back(u);
}
void dfs1(int u){
    if (vis[u]) return; vis[u] = true;
    for(int v: adj[u]) dfs1(v); order.push_back(u);
}
void dfs2(int u, int id) {
    if(vis[u]) return; vis[u] = true;
    for(int v: adjr[u]) dfs2(v, id); which[u] = id;
}
int last = 0;
void findSCC(int n) {
    cc=0,last=n; order.clear(); fill(vis, vis+n, 0);
    for(int i=0; i<n; i++) if(!vis[i]) dfs1(i);
    reverse(order.begin(), order.end());
    fill(vis, vis+n, 0);
    for (int u: order) {
        if (vis[u]) continue; dfs2(u, cc); ++cc;
    }
}
void clear() {
    for (int i=0; i<last; i++)
        adj[i].clear(), adjr[i].clear();
}
}
struct TwoSat {
    int n; int vars = 0; vector<bool> ans;
    TwoSat(int n) : n(n), ans(n) {
        SCC::clear(); vars = 2*n;
    }
    void implies(int x, int y) {
        SCC::addEdge(x, y); SCC::addEdge(y^1, x^1);
    }
    void OR(int x, int y) {
        SCC::addEdge(x^1, y); SCC::addEdge(y^1, x);
    }
    void XOR(int x, int y) {
        implies(x, y^1); implies(x^1, y);
    }
    void atmostOne(vector<int> v) {
        int k = v.size();
        for (int i=0; i<k; i++) {
            if (i+1<k) implies(vars+2*i, vars+2*i+2);
            implies(v[i], vars+2*i);
            if (i>0) implies(v[i], vars+2*i-1);
        }
        vars += 2*k;
    }
    bool solve() {
        SCC::findSCC(vars); ans.resize(vars/2);
        for (int i=0; i<vars; i+=2) {
            if (SCC::which[i]==SCC::which[i+1])return 0;
            if (i<2*n)
                ans[i/2] = SCC::which[i]>SCC::which[i+1];
        }
        return true;
    }
};

```

7 Math

7.1 BerleKampMassey

```

const int MOD = 998244353;
vector<LL> berlekampMassey(vector<LL> s) {
    if (s.empty()) return {};
    int n = s.size(), L = 0, m = 0;
    vector<LL> C(n), B(n), T;
    C[0] = B[0] = 1; LL b = 1;
    for (int i = 0; i < n; ++i) {
        ++m; LL d = s[i] % MOD;
        for (int j = 1; j <= L; ++j) d = (d + C[j] * s[i - j]) % MOD;
        if (!d) continue;
        T = C; LL coeff = d * bigMod(b, -1) % MOD;
        for (int j = m; j < n; ++j) C[j] = (C[j] - coeff * B[j - m]) % MOD;
        if (2*L > i) continue;
        L = i+1-L, B = T, b = d, m = 0;
    }
    C.resize(L + 1), C.erase(C.begin());
    for (LL &x : C) x = (MOD - x) % MOD;
    return C;
}

```

7.2 FloorSum

```

LL mod(LL a, LL m) {
    LL ans = a%m;
    return ans < 0 ? ans+m : ans;
}
//Sum(floor((ax+b)/m)) for i=0 to n-1, (n,m >= 0)
LL floorSum(LL n, LL m, LL a, LL b) {
    LL ra = mod(a, m), rb = mod(b, m), k = (ra*n+rb);
    LL ans = ((a-ra)/m) * n*(n-1)/2 + ((b-rb)/m) * n;
    if (k < m) return ans;
    return ans + floorSum(k/m, ra, m, k%m);
}

```

7.3 Stern Brocot Tree

```

//finds x/y with min y st: L <= (x/y) < R
pair<LL,LL>solve(LD L, LD R){
    pair<LL,LL> l(0, 1), r(1, 1);
    if(L==0.0) return l; // corner case
    while(true) {
        pair<int, int> m(l.x+r.x, l.y+r.y);
        if(m.x<L*m.y){ // move to the right
            LL kl=1, kr=1;
            while(l.x+kr*r.x <= L*(l.y+kr*r.y)) kr*=2;
            while(kl!=kr){
                LL km = (kl+kr)/2;
                if(l.x+km*r.x < L*(l.y+km*r.y)) kl=km+1;
                else kr=km;
            }
            l={l.x+(kl-1)*r.x,l.y+(kl-1)*r.y};
        }
        else if(m.x>=R*m.y){ //move to left
            LL kl=1, kr=1;
            while(r.x+kr*l.x>=R*(r.y+kr*l.y)) kr*=2;
            while(kl!=kr){
                LL km = (kl+kr)/2;
                if(r.x+km*l.x>=R*(r.y+km*l.y)) kl = km+1;
                else kr = km;
            }
            r={r.x+(kl-1)*l.x,r.y+(kl-1)*l.y};
        }
        else return m;
    }
}

```

7.4 Sum Of Kth Power

```

LL mod; LL S[105][105];
// Find 1^k+2^k+...+n^k % mod
void solve() {
    LL n, k;
    /* x^k = sum (i=1 to k) Stirling2(k, i) * i! * ncr(x, i)
    sum (x = 0 to n) x^k
    = sum (i=0 to k) Stirling2(k, i) * i! * sum (x=0 to n)ncr(x, i)
    = sum (i=0 to k) Stirling2(k, i) * i! * ncr(n+1, i+1)
    = sum (i=0 to k) Stirling2(k, i) * i! * (n+1)! / (i+1)! / (n-i)!
    = sum (i=0 to k) Stirling2(k, i) * (n-i+1) *

```

```

    (n - i + 2) * ... (n + 1) / (i + 1) */
    S[0][0] = 1 % mod;
    for (int i = 1; i <= k; i++) {
        for (int j = 1; j <= i; j++) {
            if (i == j) S[i][j] = 1 % mod;
        }
        else S[i][j] = (j * S[i - 1][j] + S[i - 1][j - 1]) % mod;
    }
    LL ans = 0;
    for (int i = 0; i <= k; i++) {
        LL fact = 1, z = i + 1;
        for (LL j = n - i + 1; j <= n + 1; j++) {
            LL mul = j;
            if (mul % z == 0) {
                mul /= z; z /= z;
            }
            fact = (fact * mul) % mod;
        }
        ans = (ans + S[k][i] * fact) % mod;
    }
}

```

7.5 combination-generator

```

bool next_combination(vector<int>& a, int n) {
    int k = (int)a.size();
    for (int i = k - 1; i >= 0; i--) {
        if (a[i] < n - k + i + 1) {
            a[i]++;
            for (int j = i + 1; j < k; j++)
                a[j] = a[j - 1] + 1;
            return true;
        }
    }
    return false;
}
vector<int> ans;
void gen(int n, int k, int idx, bool rev) {
    if (k > n || k < 0)
        return;
    if (!n) {
        for (int i = 0; i < idx; ++i) {
            if (ans[i])
                cout << i + 1;
        }
        cout << "\n";
        return;
    }
    ans[idx] = rev;
    gen(n - 1, k - rev, idx + 1, false);
    ans[idx] = !rev;
    gen(n - 1, k - !rev, idx + 1, true);
}
void all_combinations(int n, int k) {
    ans.resize(n);
    gen(n, k, 0, false);
}

```

7.6 continued-fractions

```

auto fraction(int p, int q) {
    vector<int> a;
    while(q) {
        a.push_back(p / q);
        tie(p, q) = make_pair(q, p % q);
    }
    return a;
}
auto convergents(vector<int> a) {
    vector<int> p = {0, 1};
    vector<int> q = {1, 0};
    for(auto it: a) {
        p.push_back(p[p.size() - 1] * it + p[p.size() - 2]);
        q.push_back(q[q.size() - 1] * it + q[q.size() - 2]);
    }
    return make_pair(p, q);
}

```

7.7 crt anchor

```

/// Chinese remainder theorem (special case): find z st z%m1 =
r1, z%m2 = r2.
/// z is unique modulo M = lcm(m1, m2). Returns (z, M). On
failure, M = -1.
PLL CRT(LL m1, LL r1, LL m2, LL r2) {
    LL s, t;
    LL g = egcd(m1, m2, s, t);
    if (r1%g != r2%g) return PLL(0, -1);
    LL M = m1*m2;
    LL ss = ((s*r2)%m2)*m1;
    LL tt = ((t*r1)%m1)*m2;
    LL ans = ((ss+tt)%M+M)%M;
    return PLL(ans/g, M/g);
}
// expected: 23 105
// 11 12
PLL ans = CRT({3,5,7}, {2,3,2});
cout << ans.first << " " << ans.second << endl;
ans = CRT({4,6}, {3,5});
cout << ans.first << " " << ans.second << endl;

```

7.8 discrete-root

```

#define MAX 100000
int prime[MAX+1], Phi[MAX+1];
vector<int> pr;
void sieve() {
    for (int i=2; i <= N; ++i) {
        if (prime[i] == 0) {
            prime[i] = i;
            pr.push_back(i);
        }
        for (int j=0; j < (int)pr.size() && pr[j] <= prime[i]
            && i*pr[j] <= N; ++j) {
            prime[i * pr[j]] = pr[j];
        }
    }
}
void PhiWithSieve() {
    int i;
    for(i=2; i<=MAX; i++){
        if(prime[i]==i){
            Phi[i]=i-1;
        }
        else if((i/prime[i])%prime[i]==0){
            Phi[i]=Phi[i/prime[i]]*prime[i];
        }
        else{
            Phi[i]=Phi[i/prime[i]]*(prime[i]-1);
        }
    }
}
int powmod (int a, int b, int p) {
    int res = 1;
    while (b)
        if (b & 1)
            res = int (res * 1ll * a % p), --b;
        else
            a = int (a * 1ll * a % p), b >>= 1;
    return res;
}
int PrimitiveRoot(int p){
    vector<int>fact;
    int phi=Phi[p];
    int n=phi;
    while(n>1){
        if(prime[n]==n){
            fact.push_back(n);
            n=1;
        }
        else{
            int f=prime[n];
            while(n%f==0){
                n=n/f;
            }
            fact.push_back(f);
        }
    }
    int res;
    for(res=p-1; res>1; --res){

```

```

        for(n=0; n<fact.size(); n++){
            if(powmod(res,phi/fact[n],p)==1){
                break;
            }
        }
        if(n==fact.size()) return res;
    }
    return -1;
}
int DiscreteLog(int a, int b, int m) {
    a %= m, b %= m;
    int n = sqrt(m) + 1;
    map<int, int> vals;
    for (int p = 1; p <= n; ++p)
        vals[powmod(a, (int) (1ll * p * n % m, m))] = p;
    for (int q = 0; q <= n; ++q) {
        int cur = (powmod(a, q, m) * 1ll * b) % m;
        if (vals.count(cur)) {
            int ans = vals[cur] * n - q;
            return ans;
        }
    }
    return -1;
}
vector<int> DiscreteRoot(int n, int a, int k){
    int g = PrimitiveRoot(n);
    vector<int> ans;
    int any_ans = DiscreteLog(powmod(g, k, n), a, n);
    if (any_ans == -1){
        return ans;
    }
    int delta = (n-1) / gcd(k, n-1);
    for (int cur = any_ans % delta; cur < n-1; cur += delta)
        ans.push_back(powmod(g, cur, n));
    sort(ans.begin(), ans.end());
    return ans;
}

```

7.9 fast-fourier-transform

```

using cd = complex<double>;
const double PI = acos(-1);
typedef long long ll;
void fft(vector<cd>& a, bool invert) {
    int n = a.size();
    for(int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for(; j & bit; bit >>= 1) {
            j ^= bit;
        }
        j ^= bit;
        if(i < j)
            swap(a[i], a[j]);
    }
    for(int len = 2; len <= n; len <= 1) {
        double ang = 2*PI/len*(invert ? -1 : 1);
        cd wlen(cos(ang), sin(ang));
        for(int i = 0; i < n; i += len) {
            cd w(1);
            for(int j = 0; j < len/2; j++) {
                cd u = a[i+j], v = a[i+j+len/2]*w;
                a[i+j] = u+v;
                a[i+j+len/2] = u-v;
                w *= wlen;
            }
        }
    }
    if(invert){
        for(cd &x: a)
            x /= n;
    }
}
vector<int> multiply(vector<int> const& a, vector<int>
    const& b) {
    vector<cd> fa(a.begin(), a.end());
    vector<cd> fb(b.begin(), b.end());
    int n = 1;
    while(n < a.size()+b.size())
        n <= 1;
    fa.resize(n);

```

```

fb.resize(n);
fft(fa, false);
fft(fb, false);
for(int i = 0; i < n; i++)
    fa[i] *= fb[i];
fft(fa, true);
vector<int> result(n);
for(int i = 0; i < n; i++)
    result[i] = round(fa[i].real());
return result;
}
/*Number Theoretic Transformation
ll int gcd(ll int a, ll int b){
    if(b==0) return a;
    else return gcd(b,a%b);
}
ll int egcd(ll int a, ll int b, ll int &x, ll int &y) {
    if (a == 0) {
        x = 0;
        y = 1;
        return b;
    }
    ll int x1, y1;
    ll int d = egcd(b % a, a, x1, y1);
    x = y1 - (b / a) * x1;
    y = x1;
    return d;
}
ll int ModuloInverse(ll int a, ll int n){
    ll int x,y;
    x=gcd(a,n);
    a=a/x;
    n=n/x;
    ll int res = egcd(a,n,x,y);
    x=(x%n+n)%n;
    return x;
}
const int mod = 998244353;
const int root = 15311432;
const int root_1 = 469870224;
const int root_pw = 1 << 23;
998244353 = 119 * 2^23 + 1 , primitive root = 3
985661441 = 235 * 2^22 + 1 , primitive root = 3
1012924417 = 483 * 2^21 + 1 , primitive root = 5
void fft(vector<int> &a, bool invert) {
    int n = a.size();
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1)
            j ^= bit;
        j ^= bit;
        if (i < j)
            swap(a[i], a[j]);
    }
    for (int len = 2; len <= n; len <= 1) {
        int wlen = invert ? root_1 : root;
        for (int i = len; i < root_pw; i <= 1)
            wlen = (int)(1LL * wlen * wlen % mod);
        for (int i = 0; i < n; i += len) {
            int w = 1;
            for (int j = 0; j < len / 2; j++) {
                int u = a[i+j], v = (int)(1LL * a[i+j+len/2] * w % mod);
                a[i+j] = u + v < mod ? u + v : u + v - mod;
                a[i+j+len/2] = u - v >= 0 ? u - v : u - v + mod;
                w = (int)(1LL * w * wlen % mod);
            }
        }
    }
    if (invert) {
        int n_1 = (int) ModuloInverse(n, mod);
        for (int &x : a)
            x = (int)(1LL * x * n_1 % mod);
    }
}
vector<int> multiply(vector<int> const&a, vector<int> const&b){
    vector<int> fa(a.begin(), a.end());
    vector<int> fb(b.begin(), b.end());
    int n = 1;
    while(n < a.size()+b.size())

```

```

        n <= 1;
        fa.resize(n);
        fb.resize(n);
        fft(fa, false);
        fft(fb, false);
        for(int i = 0; i < n; i++)
            fa[i] = (int) (1LL*fa[i]*fb[i]%mod);
        fft(fa, true);
        vector<int> result(n);
        for(int i = 0; i < n; i++)
            result[i] = fa[i];
        return result;
    }
}
*/

```

7.10 fast-walsh-hadamard

```

void FWHT(vector<LL> &p, bool inv) {
    int n = p.size(); assert((n&(n-1))==0);
    for (int len=1; 2*len<=n; len <= 1) {
        for (int i = 0; i < n; i += len+len){
            for (int j = 0; j < len; j++) {
                LL u = p[i+j], v = p[i+len+j];
                //XOR p[i+j]=u+v; p[i+len+j]=u-v;
                ///OR if(!inv) p[i+j]=u, p[i+len+j]=u+v;
                ///OR else p[i+j]=-u+v, p[i+len+j]=u;
                ///AND if(!inv) p[i+j]=u+v, p[i+len+j]=u;
                ///AND else p[i+j]=u, p[i+len+j]=u-v;
            }
        }
    }
    //XOR if(inv) for(int i=0;i<n;i++) p[i]/=n;
}
vector<LL> convo(vector<LL> a, vector<LL> b) {
    int n = 1, sz = max(a.size(), b.size());
    while(n<sz) n*=2;
    a.resize(n); b.resize(n); vector<LL>res(n, 0);
    FWHT(a, 0); FWHT(b, 0);
    for(int i=0;i<n;i++) res[i] = a[i] * b[i];
    FWHT(res, 1);
    return res;
}

```

7.11 find-root

```

double sqrt_newton(double n) {
    const double eps = 1E-15;
    double x = 1;
    for (;;) {
        double nx = (x + n / x) / 2;
        if (abs(x - nx) < eps)
            break;
        x = nx;
    }
    return x;
}
int isqrt_newton(int n) {
    int x = 1;
    bool decreased = false;
    for (;;) {
        int nx = (x + n / x) >> 1;
        if (x == nx || nx > x && decreased)
            break;
        decreased = nx < x;
        x = nx;
    }
    return x;
}

```

7.12 formulas

Binomial Coefficient List

- $\sum_{m=0}^n \binom{m}{k} = \binom{n+1}{k+1}.$
- $\sum_{k=0}^m \binom{n+k}{k} = \binom{n+m+1}{m}.$
- $\binom{n}{0}^2 + \binom{n}{1}^2 + \dots + \binom{n}{n}^2 = \binom{2n}{n}.$

- $1\binom{n}{1} + 2\binom{n}{2} + \dots + n\binom{n}{n} = n2^{n-1}$
- $\binom{n}{0} + \binom{n-1}{1} + \dots + \binom{n-k}{k} + \dots + \binom{0}{n} = F_{n+1}$

Catalan's Triangle

- $C(n, 0) = 1, n \geq 0.$
- $C(n, 1) = n, n \geq 1.$
- $C(n+1, k) = C(n+1, k-1) + C(n, k), 1 < k < n+1.$
- $C(n, k) = \binom{n+k}{k} - \binom{n+k}{k-1} = \frac{n-k+1}{n+1} \binom{n+k}{k}.$

Fibonacci Numbers

- $F_{n-1}F_{n+1} - F_n^2 = (-1)^n.$
- $F_{n+k} = F_kF_{n+1} + F_{k-1}F_n.$
- $GCD(F_m, F_n) = F_{GCD(m, n)}.$

7.13 integer-factorization

```

long long pollards_p_minus_1(long long n) {
    int B = 10; long long g = 1;
    while (B <= 1000000 && g < n) {
        long long a = 2 + rand() % (n - 3); g = gcd(a, n);
        if (g > 1) return g;
        // compute a^M
        for (int p : primes) {
            if (p >= B) continue; long long p_power = 1;
            while (p_power * p <= B) p_power *= p;
            a = power(a, p_power, n); g = gcd(a - 1, n);
            if (g > 1 && g < n) return g;
        }
        B *= 2;
    }
    return 1;
}
long long mult(long long a, long long b, long long mod) {
    long long result = 0;
    while (b) {
        if (b & 1) result = (result + a) % mod;
        a = (a + a) % mod; b >>= 1;
    }
    return result;
}
long long f(long long x, long long c, long long mod) {
    return (mult(x, x, mod) + c) % mod;
}
long long rho(long long n, long long x0=2, long long c=1) {
    long long x = x0; long long y = x0; long long g = 1;
    while (g == 1) {
        x = f(x, c, n); y = f(y, c, n); y = f(y, c, n);
        g = gcd(abs(x - y), n);
    }
    return g;
}
long long brent(long long n, long long x0=2, long long c=1) {
    long long x = x0; long long g = 1; long long q = 1;
    long long xs, y; int m = 128; int l = 1;
    while (g == 1) {
        y = x; int k = 0;
        for (int i = 1; i < l; i++) x = f(x, c, n);
        while (k < l && g == 1) {
            xs = x;
            for (int i = 0; i < m && i < l - k; i++) {
                x = f(x, c, n); q = mult(q, abs(y - x), n);
            }
            g = gcd(q, n); k += m;
        }
    }
}

```

```

    1 *= 2;
}
if (g == n) {
    do {
        xs = f(xs, c, n); g = gcd(abs(xs - y), n);
    } while (g == 1);
}
return g;
}

```

7.14 integration-simpson

```

const int N = 1000 * 1000; // number of steps (already
    multiplied by 2)
double simpson_integration(double a, double b){
    double h = (b - a) / N;
    double s = f(a) + f(b); // a = x_0 and b = x_2n
    for (int i = 1; i <= N - 1; ++i) { // Refer to final
        Simpson's formula
        double x = a + h * i;
        s += f(x) * ((i & 1) ? 4 : 2);
    }
    s *= h / 3;
    return s;
}

```

7.15 linear-diophantine-equation-gray-code

```

int gcd(int a, int b, int& x, int& y) {
    if (b == 0) {
        x = 1;
        y = 0;
        return a;
    }
    int x1, y1;
    int d = gcd(b, a % b, x1, y1);
    x = y1;
    y = x1 - y1 * (a / b);
    return d;
}

bool find_any_solution(int a, int b, int c, int &x0, int &y0,
    int &g) {
    g = gcd(abs(a), abs(b), x0, y0);
    if (c % g) {
        return false;
    }
    x0 *= c / g;
    y0 *= c / g;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}

void shift_solution(int &x, int &y, int a, int b, int cnt) {
    x += cnt * b;
    y -= cnt * a;
}

int find_all_solutions(int a, int b, int c, int minx, int
    maxx, int miny, int maxy) {
    int x, y, g;
    if (!find_any_solution(a, b, c, x, y, g))
        return 0;
    a /= g;
    b /= g;
    int sign_a = a > 0 ? +1 : -1;
    int sign_b = b > 0 ? +1 : -1;
    shift_solution(x, y, a, b, (minx - x) / b);
    if (x < minx)
        shift_solution(x, y, a, b, sign_b);
    if (x > maxx)
        return 0;
    int lx1 = x;
    shift_solution(x, y, a, b, (maxx - x) / b);
    if (x > maxx)
        shift_solution(x, y, a, b, -sign_b);
    int rx1 = x;
    shift_solution(x, y, a, b, -(miny - y) / a);
    if (y < miny)
        shift_solution(x, y, a, b, -sign_a);
    if (y > maxy)
        return 0;
}

```

```

int lx2 = x;
shift_solution(x, y, a, b, -(maxy - y) / a);
if (y > maxy)
    shift_solution(x, y, a, b, sign_a);
int rx2 = x;
if (lx2 > rx2)
    swap(lx2, rx2);
int lx = max(lx1, lx2);
int rx = min(rx1, rx2);
if (lx > rx)
    return 0;
return (rx - lx) / abs(b) + 1;
}

```

```

int g(int n) {
    return n ^ (n >> 1);
}

```

```

int rev_g(int g) {
    int n = 0;
    for (; g; g >>= 1)
        n ^= g;
    return n;
}

```

7.16 linear-equation-system

```

const double EPS = 1e-9;
const int INF = 2; // it doesn't actually have to be infinity
    or a big number
int gauss(vector<vector<double>> &a, vector<double> &ans) {
    int n = (int) a.size();
    int m = (int) a[0].size() - 1;
    vector<int> where(m, -1);
    for (int col=0, row=0; col<m && row<n; ++col) {
        int sel = row;
        for (int i=row; i<n; ++i)
            if (abs(a[i][col]) > abs(a[sel][col]))
                sel = i;
        if (abs(a[sel][col]) < EPS)
            continue;
        for (int i=col; i<m; ++i)
            swap(a[sel][i], a[row][i]);
        where[col] = row;
        for (int i=0; i<n; ++i)
            if (i != row) {
                double c = a[i][col] / a[row][col];
                for (int j=col; j<m; ++j)
                    a[i][j] -= a[row][j] * c;
            }
        ++row;
    }
    ans.assign(m, 0);
    for (int i=0; i<m; ++i)
        if (where[i] != -1)
            ans[i] = a[where[i]][m] / a[where[i]][i];
    for (int i=0; i<n; ++i) {
        double sum = 0;
        for (int j=0; j<m; ++j)
            sum += ans[j] * a[i][j];
        if (abs(sum - a[i][m]) > EPS)
            return 0;
    }
    for (int i=0; i<m; ++i)
        if (where[i] == -1)
            return INF;
    return 1;
}

```

7.17 matrix-determinant

```

const double EPS = 1E-9;
int n;
vector<vector<double>> &a(n, vector<double>(n));
double det = 1;
for (int i=0; i<n; ++i) {
    int k = i;
    for (int j=i+1; j<n; ++j)
        if (abs(a[j][i]) > abs(a[k][i]))
            k = j;
    if (abs(a[k][i]) < EPS) {
        det = 0;
        break;
    }
}

```

```

}
swap(a[i], a[k]);
if (i != k)
    det = -det;
det *= a[i][i];
for (int j=i+1; j<n; ++j)
    a[i][j] /= a[i][i];
for (int j=0; j<n; ++j)
    if (j != i && abs(a[j][i]) > EPS)
        for (int k=i+1; k<n; ++k)
            a[j][k] -= a[i][k] * a[j][i];
}
cout << det;

```

7.18 matrix-rank

```

const double EPS = 1E-9;
int compute_rank(vector<vector<double>> &A) {
    int n = A.size(); int m = A[0].size(); int rank = 0;
    vector<bool> row_selected(n, false);
    for (int i = 0; i < m; ++i) {
        int j;
        for (j = 0; j < n; ++j) {
            if (!row_selected[j] && abs(A[j][i]) > EPS) break;
        }
        if (j != n) {
            ++rank; row_selected[j] = true;
            for (int p = i + 1; p < m; ++p) A[j][p] /= A[j][i];
            for (int k = 0; k < n; ++k) {
                if (k != j && abs(A[k][i]) > EPS) {
                    for (int p = i + 1; p < m; ++p)
                        A[k][p] -= A[j][p] * A[k][i];
                }
            }
        }
    }
    return rank;
}

```

7.19 nCr mod p^a

```

LL F[1000009];
void pre(LL mod, LL pp) { // mod is pp^a, pp is prime
    F[0] = 1;
    REPL(i, 1, mod) { // we keep in F factorial with
        // the terms which are coprime with pp
        if (i % pp != 0) F[i] = (F[i-1] * i) % mod;
        else F[i] = F[i-1];
    }
}

LL fact2(LL nn, LL mod) {
    LL cycle = nn / mod;
    LL n2 = nn % mod;
    return (bigmod(F[mod], cycle, mod) * F[n2]) % mod;
}

// returns highest power of pp that divides N and the coprime
// with pp part of N! % mod
PLL fact(LL N, LL pp, LL mod) {
    LL nn = N; LL ord = 0;
    while (nn > 0) { nn /= pp; ord += nn; }
    LL ans = 1; nn = N;
    while (nn > 0) { ans = (ans * fact2(nn, mod)) % mod;
        nn /= pp; }
    return MP(ord, ans);
}

LL ncrp(ULL n, ULL r, LL prm, LL pr) { // ncr mod prm^pr
    LL mod = bigmod(prm, pr, INF); temp;
    pre(mod, prm);
    PLL x = fact(n, prm, mod), y = fact(r, prm, mod), z = fact(n-r, prm, mod);
    LL guun = x.second * modInverse(y.second, mod, prm);
    guun %= mod; guun *= modInverse(z.second, mod, prm);
    guun %= mod;
    LL guun2 = x.first - y.first - z.first;
    guun *= bigmod(prm, guun2, mod);
    guun %= mod;
    return guun;
}

```

7.20 primality-test

```

using u64 = uint64_t;
using u128 = __uint128_t;

```

```

u64 binpower(u64 base, u64 e, u64 mod) {
    u64 result = 1; base %= mod;
    while (e) {
        if (e & 1) result = (u128)result * base % mod;
        base = (u128)base * base % mod; e >>= 1;
    }
    return result;
}
bool check_composite(u64 n, u64 a, u64 d, int s) {
    u64 x = binpower(a, d, n);
    if (x == 1 || x == n - 1) return false;
    for (int r = 1; r < s; r++) {
        x = (u128)x * x % n;
        if (x == n - 1) return false;
    }
    return true;
};
// returns true if n is prime, else returns false.
bool MillerRabin(u64 n) {
    if (n < 2) return false;
    int r = 0; u64 d = n - 1;
    while ((d & 1) == 0) {
        d >>= 1; r++;
    }
    for (int a : {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37})
        if (n == a) return true;
        if (check_composite(n, a, d, r)) return false;
    return true;
}
bool probablyPrimeFermat(int n, int iter=5) {
    if (n < 4) return n == 2 || n == 3;
    for (int i = 0; i < iter; i++) {
        int a = 2 + rand() % (n - 3);
        if (binpower(a, n - 1, n) != 1)
            return false;
    }
    return true;
}

```

7.21 prime counting function

```

#define MAXN 500
#define MAXM 100010
#define MAXP 666666
#define MAX 10000010
#define ll long long int
#define chkbit(ar,i) (((ar[(i)>>6])&(1<<(((i)>>1)&31))))
#define setbit(ar,i) (((ar[(i)>>6])|= (1<<(((i)>>1)&31))))
#define isprime(x) (((x)&&((x)&1)&&(!chkbit(ar,(x))))||((x)==2))
namespace pcf{
    long long dp[MAXN][MAXM];
    unsigned int ar[(MAX>>6)+5] = {0};
    int len=0, primes[MAXP], counter[MAX];
    void Sieve(){ setbit(ar,0), setbit(ar,1);
        for (int i=3;(i*i)<MAX;i++,i++){
            if(!chkbit(ar,i)){ int k=i<<1;
                for(int j=(i*i);j<MAX;j+=k) setbit(ar,j);
            }
        }
        for(int i=1;i<MAX;i++){ counter[i]=counter[i-1];
            if(isprime(i)) primes[len++]=i, counter[i]++;
        }
    }
    void init(){
        Sieve();
        for(int n=0;n<MAX;n++){
            for(int m=0;m<MAX;m++){
                if(!n) dp[n][m]=m;
                else dp[n][m]=dp[n-1][m]-dp[n-1][m/primes[n-1]];
            }
        }
    }
    ll phi(ll m,int n){
        if(n==0) return m; if(primes[n-1]>=m) return 1;
        if(m<MAXM && n<MAXN) return dp[n][m];
        return phi(m,n-1) - phi(m/primes[n-1],n-1);
    }
    ll Lehmer(long long m){

```

```

        if(m<MAX) return counter[m];
        ll w,res=0; int i,a,s,c,x,y;
        s=sqrt(0.9+m), y=c=cbrt(0.9+m);
        a=counter[y], res=phi(m,a)+a-1;
        for(i=a;primes[i]<=s;i++){
            res=res-Lehmer(m/primes[i])+Lehmer(primes[i])-1;
        }
        return res;
    }
}

```

8 String

8.1 Hashing

```

ll fmod(ll a, ll b, int md=mods[0]) {
    unsigned long long x = (long long) a * b;
    unsigned xh = (unsigned) (x >> 32), xl = (unsigned) x, d, m;
    asm(
        "div %4; \n\t"
        : "=a" (d), "=d" (m)
        : "d" (xh), "a" (xl), "r" (md)
    );
    return m;
}
void Build1(const string &str) {
    for(ll i = str.size() - 1; i >= 0; i--){
        hsh[i] = fmod(hsh[i + 1], bases[j], mods[j]) + str[i];
        if (hsh[i] > mods[j]) hsh[i] -= mods[j];
    }
}
ll getSingleHash(ll i, ll j) {
    assert(i <= j);
    ll tmp1 = (hsh[i] - fmod(hsh[j+1], pwbase[0][j-i+1]));
    if(tmp1 < 0) tmp1 += mods[0]; return tmp1;
}

```

8.2 aho-corasick

```

const int K = 26;
struct Vertex {
    int next[K]; bool leaf = false; int p = -1; char pch;
    int link = -1; int go[K];
    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};
vector<Vertex> t(1);
void add_string(string const& s) { int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (t[v].next[c] == -1) {
            t[v].next[c] = t.size(); t.emplace_back(v, ch);
        }
        v = t[v].next[c];
    }
    t[v].leaf = true;
}
int go(int v, char ch);
int get_link(int v) {
    if (t[v].link == -1) {
        if (v == 0 || t[v].p == 0) t[v].link = 0;
        else t[v].link = go(get_link(t[v].p), t[v].pch);
    }
    return t[v].link;
}
int go(int v, char ch) {
    int c = ch - 'a';
    if (t[v].go[c] == -1) {
        if (t[v].next[c] != -1) t[v].go[c] = t[v].next[c];
        else t[v].go[c] = v == 0 ? 0 : go(get_link(v), ch);
    }
    return t[v].go[c];
}

```

8.3 manacher

```

char s[MAX]; vector<int> d1(n); vector<int> d2(n);
for (int i = 0, l = 0, r = -1; i < n; i++){
    int k = (i > r) ? 1 : min(d1[l + r - i], r - i + 1);

```

```

    while (0 <= i - k && i + k < n && s[i - k] == s[i + k])
        k++;
    d1[i] = k--;
    if (i + k > r) { l = i - k; r = i + k; }
}
for (int i = 0, l = 0, r = -1; i < n; i++){
    int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
    while (0 <= i - k - 1 && i + k < n && s[i - k - 1] == s[i + k])
        k++;
    d2[i] = k--;
    if (i + k > r) { l = i - k - 1; r = i + k; }
}

```

8.4 palindromic tree

```

struct node {
    int next[26]; int len; int sufflink; int num; };
int len; char s[MAXN]; node tree[MAXN];
int num; // node 1 - root with len -1, node 2 - root with len 0
int suff; // max suffix palindrome
bool addLetter(int pos) {
    int cur = suff, curlen = 0; int let = s[pos] - 'a';
    while (true) {
        curlen = tree[cur].len;
        if (pos - 1 - curlen >= 0 && s[pos - 1 - curlen] == s[pos])
            break;
        cur = tree[cur].sufflink;
    }
    if (tree[cur].next[let]) {
        suff = tree[cur].next[let]; return false;
    }
    num++; suff = num; tree[num].len = tree[cur].len + 2;
    tree[cur].next[let] = num;
    if (tree[num].len == 1) { tree[num].sufflink = 2;
        tree[num].num = 1; return true;
    }
    while (true) {
        cur = tree[cur].sufflink; curlen = tree[cur].len;
        if (pos - 1 - curlen >= 0 && s[pos - 1 - curlen] == s[pos]) {
            tree[num].sufflink = tree[cur].next[let]; break;
        }
    }
    tree[num].num = 1 + tree[tree[num].sufflink].num; return true;
}
void initTree() {
    num = 2; suff = 2; // memset tree must
    tree[1].len = -1; tree[1].sufflink = 1;
    tree[2].len = 0; tree[2].sufflink = 1;
}
int main() { gets(s); len = strlen(s); initTree();
    for (int i = 0; i < len; i++) { addLetter(i);
        ans += tree[suff].num; }
    cout << ans << endl; return 0;
}

```

8.5 suffix array da

```

/* sa => ith smallest suffix of the string
rak => rak[i] indicates the position of suffix(i) in the suffix
array; height => height[i] indicates the LCP of i-1 and i th
suffix; LCP of suffix(i) & suffix(j) = { L = rak[i], R = rak[j]
, min(height[L+1, R]); } */
const int maxn = 5e5+5;
int wa[maxn], wb[maxn], wv[maxn], wc[maxn];
int r[maxn], sa[maxn], rak[maxn], height[maxn], dp[maxn][22],
    jump[maxn], SIGMA = 0;

int cmp(int *r, int a, int b, int l) {
    return r[a] == r[b] && r[a+l] == r[b+l];
}
void da(int *r, int *sa, int *sa, int n, int m) {
    int i, j, p, *x = wa, *y = wb, *t;
    for (i = 0; i < m; i++) wc[i] = 0;
    for (i = 0; i < n; i++) wc[x[i]] = r[i]++;
    for (i = 1; i < m; i++) wc[i] += wc[i-1];
    for (i = n-1; i >= 0; i--) sa[--wc[x[i]]] = i;
    for (j = 1, p = 1; p < n; j *= 2, m = p) {
        for (p = 0, i = n-j; i < n; i++) y[p++] = i;
        for (i = 0; i < n; i++) if (sa[i] >= j) y[p++] = sa[i] - j;
        for (i = 0; i < n; i++) wv[i] = x[y[i]];
        for (i = 0; i < m; i++) wc[i] = 0;
    }
}

```

```

    for(i=0;i<n;i++) wc[wv[i]] ++;
    for(i=1;i<m;i++) wc[i] += wc[i-1];
    for(i=n-1;i>=0;i--) sa[--wc[wv[i]]] = y[i];
    for(t=x,x=y,y=t,p=1,x[sa[0]] = 0,i=1;i<n;i++)
        x[sa[i]] = cmp(y,sa[i-1],sa[i],j) ? p-1:p++;
}
}
void calheight(int *r,int *sa,int n){
    int i,j,k=0;
    for(i=1;i<n;i++) rak[sa[i]] = i;
    for(i=0;i<n,height[rak[i++]] = k) {
        for(k?k--:0, j=sa[rak[i]-1] ; r[i+k] == r[j+k] ; k ++);
    }
}
void initRMQ(int n){
    for(int i=0;i<n;i++) dp[i][0] = height[i];
    for(int j=1;(1<<j) <= n; j++) {
        for(int i=0; i+(1<<j)-1 <= n; i++) {
            dp[i][j] = min(dp[i][j-1], dp[i+(1<<(j-1))][j-1]);
        }
        for(int i=1; i<= n; i++) {
            int k=0; while((1<<(k+1)) <= i) k++; jump[i] = k;
        }
    }
}
int askRMQ(int L,int R){
    int k = jump[R-L+1];
    return min(dp[L][k], dp[R - (1<<k) + 1][k]);
}
int main(){
    scanf("%s",s); int n = strlen(s);
    for(int i=0; i<n; i++) {
        r[i] = s[i]-'a' + 1; SIGMA = max(SIGMA, r[i]);
    }
    r[n] = 0; da(r,sa,n+1,SIGMA + 1);
    calheight(r,sa,n);
    /* don't forget SIGMA + 1. It will ruin you.*/
}

```

8.6 suffix-automaton

```

class SuffixAutomaton{
    bool complete; int last;
    set<char> alphabet;
    struct state{
        int len, link, endpos, first_pos,snas,height;
        long long substrings,sublen;
        bool is_clone;
        map<char, int> next;
        vector<int> inv_link;
        state(int leng=0,int li=0){
            len=leng; link=li;
            first_pos=-1; substrings=0;
            sublen=0; // length of all substrings
            snas=0; // shortest_non_appearing_string
            endpos=1; is_clone=false; height=0;
        }
    };
    vector<state> st;
    void process(int node){
        map<char, int> ::iterator mit;
        st[node].substrings=1;
        st[node].snas=st.size();
        if((int) st[node].next.size()<(int) alphabet.size())
            st[node].snas=1;
        for(mit=st[node].next.begin(); mit!=st[node].next.end();++mit){
            if(st[mit->second].substrings==0) process(mit->second);
            st[node].height=max(st[node].height,1+st[mit->second].height);
            st[node].substrings=
                st[node].substrings+st[mit->second].substrings;
            st[node].sublen=st[node].sublen
                +st[mit->second].sublen+st[mit->second].substrings;
            st[node].snas=min(st[node].snas,
                1+st[mit->second].snas);
        }
        if(st[node].link!=-1)
            st[st[node].link].inv_link.push_back(node);
    }
    void set_suffix_links(int node){
        int i;

```

```

        for(i=0; i<st[node].inv_link.size(); i++){
            set_suffix_links(st[node].inv_link[i]);
            st[node].endpos=
                st[node].endpos+st[st[node].inv_link[i]].endpos; }
    }
    void output_all_occurrences(int v,int P_length,vector<int>&pos){
        if (!st[v].is_clone)
            pos.push_back(st[v].first_pos - P_length + 1);
        for (int u : st[v].inv_link)
            output_all_occurrences(u, P_length, pos);
    }
    void kth_smallest(int node,int k,vector<char> &str){
        if(k==0) return;
        map<char, int> ::iterator mit;
        for(mit=st[node].next.begin(); mit!=st[node].next.end();++mit){
            if(st[mit->second].substrings<k)k=k-st[mit->second].substrings;
            else{
                str.push_back(mit->first);
                kth_smallest(mit->second,k-1,str);
                return;
            }
        }
    }
    int find_occurrence_index(int node,int index,vector<char>&str){
        if(index==str.size()) return node;
        if(!st[node].next.count(str[index])) return -1;
        else return find_occurrence_index(st[node].next[str[index]],
            index+1,str);
    }
    void klen_smallest(int node,int k,vector<char> &str){
        if(k==0) return;
        map<char, int> ::iterator mit;
        for(mit=st[node].next.begin(); mit!=st[node].next.end();++mit){
            if(st[mit->second].height>=k-1){
                str.push_back(mit->first);
                klen_smallest(mit->second,k-1,str);
                return;
            }
        }
    }
    void minimum_non_existing_string(int node,vector<char> &str){
        map<char, int> ::iterator mit;
        set<char> ::iterator sit;
        for(mit=st[node].next.begin(),sit=alphabet.begin();
            sit!=alphabet.end(); ++sit,++mit){
            if(mit==st[node].next.end()||mit->first!=(*sit)){
                str.push_back(*sit);
                return;
            }
            else if(st[node].snas==1+st[mit->second].snas){
                str.push_back(*sit);
                minimum_non_existing_string(mit->second,str);
                return;
            }
        }
    }
    void find_substrings(int node,int index,vector<char> &str,
        vector<pair<long long,long long> > &sub_info){
        sub_info.push_back(make_pair(st[node].substrings,
            st[node].sublen+st[node].substrings*index));
        if(index==str.size()) return;
        if(st[node].next.count(str[index])){ find_substrings(
            st[node].next[str[index]],index+1,str,sub_info);return;
        }
        else{
            sub_info.push_back(make_pair(0,0));
        }
    }
    void check(){
        if(!complete){
            process(0);
            set_suffix_links(0);
            int i;
            complete=true;
        }
    }
public:
    SuffixAutomaton(set<char> &alpha){
        st.push_back(state(0,-1));

```

```

        last=0;
        complete=false;
        set<char> ::iterator sit;
        for(sit=alpha.begin(); sit!=alpha.end(); sit++)
            alphabet.insert(*sit);
        st[0].endpos=0;
    }
    void sa_extend(char c){
        int cur = st.size();
        st.push_back(state(st[last].len + 1));
        st[cur].first_pos=st[cur].len-1;
        int p = last;
        while (p != -1 && !st[p].next.count(c)){
            st[p].next[c] = cur;
            p = st[p].link;
        }
        if (p == -1){
            st[cur].link = 0;
        }
        else{
            int q = st[p].next[c];
            if (st[p].len + 1 == st[q].len){
                st[cur].link = q;
            }
            else{
                int clone = st.size();
                st.push_back(state(st[p].len + 1,st[q].link));
                st[clone].next = st[q].next;
                st[clone].is_clone=true;
                st[clone].endpos=0;
                st[clone].first_pos=st[q].first_pos;
                while (p != -1 && st[p].next[c] == q){
                    st[p].next[c] = clone; p = st[p].link;
                }
                st[q].link = st[cur].link = clone;
            }
        }
        last = cur;
        complete=false;
    }
    ~SuffixAutomaton(){
        int i;
        for(i=0; i<st.size(); i++){
            st[i].next.clear();
            st[i].inv_link.clear();
        }
        st.clear();
        alphabet.clear();
    }
    void kth_smallest(int k,vector<char> &str){
        check();
        kth_smallest(0,k,str);
    }
    int FindFirstOccurrenceIndex(vector<char> &str){
        check();
        int ind=find_occurrence_index(0,0,str);
        if(ind==0) return -1;
        else if(ind==-1) return st.size();
        else return st[ind].first_pos+1-(int) str.size();
    }
    void FindAll0ccurrenceIndex(vector<char> &str,vector<int>&pos){
        check();
        int ind=find_occurrence_index(0,0,str);
        if(ind!=-1) output_all_occurrences(ind,str.size(),pos);
    }
    int Occurrences(vector<char> &str){
        check();
        int ind=find_occurrence_index(0,0,str);
        if(ind==0) return 1;
        else if(ind==-1) return 0;
        else return st[ind].endpos;
    }
    void klen_smallest(int k,vector<char> &str){
        check();
        if(st[0].height>=k) klen_smallest(0,k,str);
    }
    void minimum_non_existing_string(vector<char> &str){
        check();
        int ind=find_occurrence_index(0,0,str);

```



```
        if(ind!=-1) minimum_non_existing_string(ind,str);
    }
};
```

8.7 z-algorithm

```
vector<int> z_function(string s) {
```

```
int n = (int) s.length();
vector<int> z(n);
for (int i = 1, l = 0, r = 0; i < n; ++i) {
    if (i <= r)
        z[i] = min (r - i + 1, z[i - l]);
    while (i + z[i] < n && s[z[i]] == s[i + z[i]])
```

```
        ++z[i];
    if (i + z[i] - 1 > r)
        l = i, r = i + z[i] - 1;
}
return z;
}
```
