

Contents

1 DP	1
1.1 divide-and-conquer-optimization	1
1.2 knuth-optimization	1
1.3 li-chao-tree	1
1.4 zero-matrix	1
2 DS	1
2.1 BIT	1
2.2 Heavy-Light-Decomposition	1
2.3 LCA	2
2.4 Lazy Propagation	2
2.5 MO with update	2
2.6 bipartite-disjoint-set-union	2
2.7 centroid decomposition	2
2.8 dsu-rollback	3
2.9 fenwick-tree-2d	3
2.10 link cut tree	3
2.11 monotone _{ht}	4
2.12 segment tree beats	4
2.13 sparse table 2d	5
2.14 treap	5
3 Extra	6
3.1 Header	6
4 Game	6
4.1 HackenBush	6
5 Geo	6
5.1 3dGeo	6
5.2 Circle Cover	7
5.3 Circle Union Area	7
5.4 basic-area-geometry	7
5.5 geo-formulae	8
5.6 half-plane-intersection	8
5.7 heart-of-geometry-2d	8
5.8 intersecting-segments-pair	10
5.9 radiant-geo	11
5.10 trianlge-ear-clipping	13
5.11 vertical-decomposition	13
6 Graph	14
6.1 DMST	14
6.2 Flow With Demands	15
6.3 LCA	15
6.4 articulation-vertex	15
6.5 bellman-ford	15
6.6 bridge	15
6.7 edmond-blossom	16
6.8 euler-path	16
6.9 hopcraft-karp	16
6.10 hungarian-algorithm	17
6.11 max-flow-dinic	18
6.12 min-cost-max-flow	18
6.13 online-bridge	18
6.14 scc + 2 Sat	19
7 Math	19
7.1 BerleKampMassey	19
7.2 FloorSum	19
7.3 Stern Brocot Tree	19
7.4 Sum Of Kth Power	19
7.5 combination-generator	20
7.6 continued-fractions	20
7.7 convolution	20
7.8 crt anachor	20
7.9 discrete-root	20
7.10 fast-walsh-hadamard	20
7.11 fft	21
7.12 formulas	21
7.13 integer-factorization	21
7.14 integration-simpson	21
7.15 linear-diophantine-equation-gray-code	21
7.16 linear-equation-system	22
7.17 math	22
7.18 nCr mod p^a	22
7.19 ntt	22
7.20 primality-test	23
7.21 prime counting function	23
8 String	23
8.1 Hashing	23
8.2 KMP	23
8.3 aho-corasick	23
8.4 manacher	23
8.5 palindromic tree	23
8.6 suffix array da	24
8.7 suffix-automaton	24
8.8 z-algorithm	25
1 DP	1
1.1 divide-and-conquer-optimization	14

```

dp[i][j]=min{dp[i-1][k]+c[k][j]} a[i][j]<=a[i][j+1]
suf condition: C[a][c]+C[b][d]<=C[a][d]+C[b][c] a<=b<=c<=d
int m, n;
vector<long long> dp_before(n), dp_cur(n);
long long C(int i, int j);
// compute dp_cur[l], ... dp_cur[r] (inclusive)
void compute(int l, int r, int optl, int optr){
    if (l > r)
        return;
    int mid = (l + r) >> 1;
    pair<long long, int> best = {LLONG_MAX, -1};
    for (int k = optl; k <= min(mid, optr); k++){
        best = min(best, {(k ? dp_before[k - 1] : 0) + C(k,
            mid), k});
    }
    dp_cur[mid] = best.first;
    int opt = best.second;

```

```

compute(l, mid - 1, optl, opt);
compute(mid + 1, r, opt, optr);
}
int solve(){
    for (int i = 0; i < n; i++)
        dp_before[i] = C(0, i);
    for (int i = 1; i < m; i++){
        compute(0, n - 1, 0, n - 1);
        dp_before = dp_cur;
    }
    return dp_before[n - 1];
}

```

1.2 knuth-optimization

```

suf cond: quadrangle and C[b][c]<=C[a][d]
int solve() {
    int N;
    ... // read N and input
    int dp[N][N], opt[N][N];
    auto C = [&](int i, int j) {
        ... // Implement cost function C.
    };
    for (int i = 0; i < N; i++) {
        opt[i][i] = i;
        ... // Initialize dp[i][i] according to the problem
    }
    for (int i = N-2; i >= 0; i--) {
        for (int j = i+1; j < N; j++) {
            int mn = INT_MAX;
            int cost = C(i, j);
            for (int k = opt[i][j-1]; k <= min(j-1,
                opt[i+1][j]); k++) {
                if (mn >= dp[i][k] + dp[k+1][j] + cost) {
                    opt[i][j] = k;
                    mn = dp[i][k] + dp[k+1][j] + cost;
                }
            }
            dp[i][j] = mn;
        }
    }
    cout << dp[0][N-1] << endl;
}

```

1.3 li-chao-tree

```

typedef long long ll;
class LiChaoTree{
    ll L,R;
    bool minimize;
    int lines;
    struct Node{
        pair<ll,ll> line;
        Node *children[2];
        Node(pair<ll,ll> ln= {0,1000000000000000000}){
            line=ln;
            children[0]=0;
            children[1]=0;
        }
    } *root;
    ll f(pair<ll,ll> a, ll x){
        return a.first*x+a.second;
    }
    void clear(Node* &node){
        if (node->children[0]){
            clear(node->children[0]);
        }
        if (node->children[1]){
            clear(node->children[1]);
        }
        delete node;
    }
    void add_line(pair<ll,ll> nw, Node* &node, ll l, ll r){
        if (node==0){
            node=new Node(nw);
            return;
        }
        ll m = (l + r) / 2;
        bool lef = (f(nw, l) < f(node->line,
            l))&&minimize||(!minimize)&&f(nw, l) >

```

```

    f(node->line, l));
    bool mid = (f(nw, m) < f(node->line,
m)&&minimize)||(!minimize)&&f(nw, m) >
    f(node->line, m));
    if(mid){
        swap(node->line, nw);
    }
    if(r - 1 == 1){
        return;
    }
    else if(l == mid){
        add_line(nw, node->children[0], 1, m);
    }
    else{
        add_line(nw, node->children[1], m, r);
    }
}
ll get(ll x, Node* &node, ll l, ll r){
    ll m = (l + r) / 2;
    if(r - l == 1){
        return f(node->line, x);
    }
    else if(x < m){
        if(node->children[0]==0) return f(node->line, x);
        if(minimize) return min(f(node->line, x), get(x,
node->children[0], 1, m));
        else return max(f(node->line, x), get(x,
node->children[0], 1, m));
    }
    else{
        if(node->children[1]==0) return f(node->line, x);
        if(minimize) return min(f(node->line, x), get(x,
node->children[1], m, r));
        else return max(f(node->line, x), get(x,
node->children[1], m, r));
    }
}
public:
LiChaoTree(ll l=-1000000001, ll r=1000000001, bool mn=false){
    L=l;
    R=r;
    root=0;
    minimize=mn;
    lines=0;
}
void AddLine(pair<ll,ll> ln){
    add_line({ln.first,ln.second},root,L,R);
    lines++;
}
int number_of_lines(){
    return lines;
}
ll getOptimumValue(ll x){
    return get(x,root,L,R);
}
~LiChaoTree(){
    if(root!=0) clear(root);
}
};

```

1.4 zero-matrix

```

int zero_matrix(vector<vector<int>> a) {
    int n = a.size();
    int m = a[0].size();
    int ans = 0;
    vector<int> d(m, -1), d1(m), d2(m);
    stack<int> st;
    for (int i = 0; i < n; ++i) {
        for (int j = 0; j < m; ++j) {
            if (a[i][j] == 1)
                d[j] = i;
        }
        for (int j = 0; j < m; ++j) {
            while (!st.empty() && d[st.top()] <= d[j])
                st.pop();
            d1[j] = st.empty() ? -1 : st.top();
            st.push(j);
        }
        while (!st.empty())

```

```

            st.pop();
        for (int j = m - 1; j >= 0; --j) {
            while (!st.empty() && d[st.top()] <= d[j])
                st.pop();
            d2[j] = st.empty() ? m : st.top();
            st.push(j);
        }
        while (!st.empty())
            st.pop();
        for (int j = 0; j < m; ++j)
            ans = max(ans, (i - d1[j]) * (d2[j] - d1[j] - 1));
    }
    return ans;
}

```

2 DS

2.1 BIT

```

#include<bits/stdc++.h>
using namespace std;
const int MaxIdx=1e+5;
int tree[MaxIdx+1];
int read(int idx) {int sum = 0;
    while (idx > 0) {sum += tree[idx];idx -= (idx & -idx);}
    return sum;}
void update(int idx, int val) {while (idx <= MaxIdx) {
    tree[idx] += val;idx += (idx & -idx);}}
int readSingle(int idx) {
    int sum = tree[idx];
    if (idx > 0) { int z = idx - (idx & -idx);idx--;
        while (idx != z) { sum -= tree[idx];idx -= (idx & -idx);}}
    return sum;}
int findG(int cumFre) {int idx = 0;int bitMask=(1<<16);
    while (bitMask != 0) {int tIdx = idx + bitMask;bitMask >>=
        1;
        if (tIdx > MaxIdx)continue;
        if (cumFre >= tree[tIdx]) {idx = tIdx;cumFre -=
            tree[tIdx];}}
    if (cumFre != 0)return -1;else return idx;}

```

2.2 Heavy-Light-Decomposition

```

namespace HLD{
    struct Node{
        int mn=INT_MAX,unp=INT_MAX;
        Node(){}
        Node(int mn,int unp): mn(mn),unp(unp){};
        inline Node combine(Node a,Node b){
            return {min(a.mn,b.mn),INT_MAX};}
        inline Node propagate(Node to,Node from,int len){
            if (from.unp==INT_MAX)
                return to;
            to.mn=min(to.mn,from.unp);
            to.unp=min(to.unp,from.unp);
            return to;}
#define MAX_SIZE 100001
vector<vector<int>> >G;
vector<int> parent,depth, heavy,head,pos;
vector<int> node_val;
vector<int> node_val_order;
SegTree<Node> sgt( MAX_SIZE,combine,propagate);
int cur_pos;
int dfs(int node){
    int sz=1;
    int max_c_size=0;
    for(auto c:G[node]){
        if(c!=parent[node]){
            parent[c]=node;
            depth[c]=depth[node]+1;
            int c_size=dfs(c);
            sz+=c_size;
            if(c_size>max_c_size){
                max_c_size=c_size;
                heavy[node]=c; }}}
    return sz;}
void decompose(int node,int h){
    pos[node]=cur_pos++;
    head[node]=h;
    if(heavy[node]!=-1)

```

```

        decompose(heavy[node],h);
    for(int c:G[node]){
        if(c!=parent[node]&& c!=heavy[node])
            decompose(c,c);}
    return;}
//for query on path the node_val of a node is the cost of
//the edge to parent
//exclude=true for query on path,it excludes the value
//stored in lca(a,b)
int query(int a,int b,int n,bool exclude=false){//n number
//of node in the tree
Node res;//not really generalized,for min max update
//accordingly
while(head[a]!=head[b]){
    if(depth[head[a]]> depth[head[b]])swap(a,b);
    res=combine(res, sgt.query(pos[head[b]],pos[b]));
    b=parent[head[b]];}
if(depth[a]>depth[b])swap(a,b);
res=combine(res,exclude? sgt.query(pos[a]+1,pos[b])
:sgt.query(pos[a],pos[b]));
return res.mn;}
// void update(int node,int val)
// {
//     sgt.update(pos[node],val);
// }
void update(int a,int b,int val){
    while(head[a]!=head[b]){
        if(depth[head[a]]> depth[head[b]])
            swap(a,b);
        //res=combine(res,sgt.query(pos[head[b]],pos[b]));
        sgt.update(pos[head[b]], pos[b],{0,val});
        b=parent[head[b]];
    }
    if(depth[a]>depth[b])swap(a,b);
    //res=combine(res,exclude? sgt.query(pos[a]+1, pos[b]):
    //sgt.query(pos[a],pos[b]));
    sgt.update(pos[a],pos[b],{0,val});
    //return res.mn;}
void init(int n){
    parent.resize(n);
    depth.resize(n);
    heavy.assign(n,-1);
    head.resize(n);
    pos.resize(n);
    parent[0]=0;//might change later
    dfs(0);
    cur_pos=0;
    decompose(0,0);
    node_val_order.resize(n);
    for(int i=0;i<n;++i){
        node_val_order[pos[i]]= node_val[i];}
    sgt.n=n;
    sgt.build(node_val_order, 1,0,n-1); }
}

```

2.3 LCA

```

int lca(int u,int v)
{
    if(depth[v]>depth[u])
        v=pth_ancestor(v,depth[v]-depth[u]);
    if(depth[u]>depth[v])
        u=pth_ancestor(u,depth[u]-depth[v]);
    if(u==v)
        return u;
    for(int i=log2(n-1);i>=0;i--){
        if(bparent[u][i]!=bparent[v][i]){
            u=bparent[u][i];
            v=bparent[v][i];
        }
    }
    return bparent[u][0];}

```

2.4 Lazy Propagation

```

struct node{
    int sum, prop;
    node(){sum=0, prop=0;}
} st[500000];
void propagate(int p, int c, int len){
    st[c].prop+=st[p].prop;

```

```

    st[c].sum+=len*st[p].prop;
void combine(int v, int l, int r){
    st[v].prop=0;
    st[v].sum=st[l].sum+st[r].sum;
void update(int v, int vl, int vr, int l, int r, int u){
    if(l>r) return;
    if(vl==l and vr==r){
        st[v].sum+=(vr-vl+1)*u;
        st[v].prop+=u;
        return;
    }
    int mid=(vl+vr)/2;
    propagate(v, 2*v, mid-vl+1);
    propagate(v, 2*v+1, vr-mid);
    if(r<=mid) update(2*v, vl, mid, l, r, u);
    else if(l>mid) update(2*v+1, mid+1, vr, l, r, u);
    else {
        update(2*v, vl, mid, l, mid, u);
        update(2*v+1, mid+1, vr, mid+1, r, u);
    }
    combine(v, 2*v, 2*v+1);
int query(int v, int vl, int vr, int l, int r){
    if(l>r) return 0;
    if(vl==l and vr==r) return st[v].sum;
    int mid=(vl+vr)/2;
    propagate(v, 2*v, mid-vl+1);
    propagate(v, 2*v+1, vr-mid);
    int qres;
    if(r<=mid) qres=query(2*v, vl, mid, l, r);
    else if(l>mid) qres=query(2*v+1, mid+1, vr, l, r);
    else qres=query(2*v, vl, mid, l, mid)+query(2*v+1, mid+1,
        vr, mid+1, r);
    combine(v, 2*v, 2*v+1);
    return qres;
}

```

2.5 MO with update

```

const int N = 1e5 + 5;
const int P = 2000; //block size = (2*n^2)^(1/3)
struct query{
    int t, l, r, k, i;
};
vector<query> q;
vector<array<int, 3>> upd;
vector<int> ans;
void add(int x); void rem(int x); int get_answer();
void mos_algorithm(){
    sort(q.begin(), q.end(), [](const query &a, const query &b){
        if (a.t / P != b.t / P) return a.t < b.t;
        if (a.l / P != b.l / P) return a.l < b.l;
        if ((a.l / P) & 1) return a.r < b.r;
        return a.r > b.r;
    });
    for(int i=upd.size()-1; i>=0; --i) a[upd[i][0]] = upd[i][1];
    int L = 0, R = -1, T = 0;
    auto apply = [&](int i, int fl){
        int p = upd[i][0], x = upd[i][fl + 1];
        if (L <= p && p <= R){ rem(a[p]); add(x); }
        a[p] = x;
    };
    ans.clear(); ans.resize(q.size());
    for (auto qr : q){
        int t = qr.t, l = qr.l, r = qr.r, k = qr.k;
        while (T < t) apply(T++, 1);
        while (T > t) apply(--T, 0);
        while (R < r) add(a[++R]);
        while (L > l) add(a[--L]);
        while (R > r) rem(a[R--]);
        while (L < l) rem(a[L++]);
        ans[qr.i] = get_answer();
    }
}
void TEST_CASES(int cas){
    cin>>n>m; a.resize(n); for(int i=0; i<n; i++) cin>>a[i];
    for(int i=0; i<m; i++){ int tp; scanf("%d", &tp);
        if (tp == 1){ int l, r, k; cin>>l>r>k;
            q.push_back({upd.size(), l - 1, r - 1, k, q.size()});
        } else{ int p, x; cin>>p>x; --p;
            upd.push_back({p, a[p], x}); a[p] = x;
        }
    }
}

```

```

}
mos_algorithm();

```

2.6 bipartite-disjoint-set-union

```

void make_set(int v) {
    parent[v] = make_pair(v, 0); rank[v] = 0; bipartite[v] = true;
}
pair<int, int> find_set(int v) { if (v != parent[v].first) {
    int parity = parent[v].second; parent[v] = find_set(
        parent[v].first); parent[v].second ^= parity;
    return parent[v];
}
void add_edge(int a, int b) {
    pair<int, int> pa = find_set(a);
    a = pa.first; int x = pa.second;
    pair<int, int> pb = find_set(b); b = pb.first;
    int y = pb.second;
    if (a == b) {
        if (x == y) bipartite[a] = false;
    } else {
        if (rank[a] < rank[b]) swap (a, b);
        parent[b] = make_pair(a, x^y^1);
        bipartite[a] ^= bipartite[b];
        if (rank[a] == rank[b]) ++rank[a];
    }
}
bool is_bipartite(int v){ return bipartite[find_set(v).first];
}

```

2.7 centroid decomposition

```

vector<int> tree[sz], ctree[sz];
int sub[sz], vis[sz], cparent[sz];
void dfs(int a, int p) {
    sub[a] = 1;
    //printf("loop\n");
    for(auto v: tree[a]){
        if(v!=p && vis[v]==0){
            dfs(v, a);
            sub[a] += sub[v];
        }
    }
    //cout<<a<<" "<<sub[a]<<endl;
}
int findCentroid(int a, int p, int num) {
    //printf("loop\n");
    bool sig=true;
    while(sig){
        sig=false;
        for(auto v: tree[a]){
            if(v!=p && vis[v]==0 && 2*sub[v]>num){
                p=a;
                a=v;
                sig=true;
                break;
            }
        }
    }
    return a;
}
int Decompose(int a, int p, int num) {
    dfs(a, p);
    int centroid=findCentroid(a, p, num);
    vis[centroid]=1;
    //printf("%d\n", centroid);
    for(auto v: tree[centroid]){
        if(vis[v]==0){
            if(sub[v]>sub[centroid])
                ctree[centroid].pb(Decompose(v, centroid, num-sub[centroid]));
        } else
            ctree[centroid].pb(Decompose(v, centroid, sub[v]));
        cparent[ctree[centroid].back()]=centroid;
    }
    return centroid;
}

```

2.8 dsu-rollback

```

struct dsu_save {
    int v, rnkv, u, rnku; dsu_save() {}
    dsu_save(int _v, int _rnkv, int _u, int _rnku)
        : v(_v), rnkv(_rnkv), u(_u), rnku(_rnku) {}
};
struct dsu_with_rollback {
    vector<int> p, rnk; int comps; stack<dsu_save> op;
    dsu_with_rollback() {}
    dsu_with_rollback(int n) { p.resize(n); rnk.resize(n);
        for (int i = 0; i < n; i++) { p[i] = i; rnk[i] = 0; }
        comps = n;
    }
    int find_set(int v){return (v == p[v])?v:find_set(p[v]);}
    bool unite(int v, int u) { v = find_set(v); u = find_set(u);
        if (v == u) return false; comps--;
        if (rnk[v] > rnk[u]) swap(v, u);
        op.push(dsu_save(v, rnk[v], u, rnk[u])); p[v] = u;
        if (rnk[u] == rnk[v]) rnk[u]++; return true;
    }
    void rollback() { if (op.empty()) return;
        dsu_save x = op.top(); op.pop(); comps++; p[x.v] = x.v;
        rnk[x.v] = x.rnkv; p[x.u] = x.u; rnk[x.u] = x.rnku;
    }
};
struct query {
    int v, u; bool united;
    query(int _v, int _u) : v(_v), u(_u) {}
};
struct QueryTree {
    vector<vector<query>> t; dsu_with_rollback dsu; int T;
    QueryTree() {}
    QueryTree(int _T, int n) : T(_T) {
        dsu = dsu_with_rollback(n); t.resize(4 * T + 4);
    }
    void add_to_tree(int v, int l, int r, int ul, int ur, query& q){
        if (ul > ur) return;
        if (l == ul && r == ur) { t[v].push_back(q); return; }
        int mid = (l + r) / 2;
        add_to_tree(2 * v, l, mid, ul, min(ur, mid), q);
        add_to_tree(2*v+1, mid+1, r, max(ul, mid + 1), ur, q);
    }
    void add_query(query q, int l, int r) {
        add_to_tree(1, 0, T - 1, l, r, q);
    }
    void dfs(int v, int l, int r, vector<int>& ans) {
        for (query& q : t[v]) q.united = dsu.unite(q.v, q.u);
        if (l == r) ans[l] = dsu.comps;
        else { int mid = (l + r) / 2;
            dfs(2 * v, l, mid, ans); dfs(2 * v + 1, mid + 1, r, ans);
            for (query q : t[v]) { if (q.united) dsu.rollback(); }
        }
    }
    vector<int> solve() {
        vector<int> ans(T); dfs(1, 0, T - 1, ans); return ans;
    }
};

```

2.9 fenwick-tree-2d

```

struct FenwickTree2D {
    vector<vector<int>> bit;
    int n, m;
    // init(...) { ... }
    int sum(int x, int y) {
        int ret = 0;
        for (int i = x; i >= 0; i = (i & (i + 1)) - 1)
            for (int j = y; j >= 0; j = (j & (j + 1)) - 1)
                ret += bit[i][j];
        return ret;
    }
    void add(int x, int y, int delta) {
        for (int i = x; i < n; i = i | (i + 1))
            for (int j = y; j < m; j = j | (j + 1))
                bit[i][j] += delta;
    }
};

```

2.10 link cut tree

```

const int MOD = 998244353;
int sum(int a, int b) {
    return a+b >= MOD ? a+b-MOD : a+b;
}
int mul(int a, int b) {
    return (a*1LL*b)%MOD;
}
typedef pair< int , int >Linear;
Linear compose(const Linear &p, const Linear &q) {
    return Linear(mul(p.first, q.first), sum(mul(q.second,
        p.first), p.second));
}
struct SplayTree {
    struct Node {
        int ch[2] = {0, 0}, p = 0;
        long long self = 0, path = 0; // Path aggregates
        long long sub = 0, vir = 0; // Subtree aggregates
        bool flip = 0; // Lazy tags
        int size = 1;
        Linear _self[1, 0], _path_shoja[1, 0], _path_ulta[1, 0];
    };
    vector<Node> T;
    SplayTree(int n) : T(n + 1) {
        T[0].size = 0;
    }
    void push(int x) {
        if (!x || !T[x].flip) return;
        int l = T[x].ch[0], r = T[x].ch[1];
        T[l].flip ^= 1, T[r].flip ^= 1;
        swap(T[x].ch[0], T[x].ch[1]);
        T[x].flip = 0;
        swap(T[x]._path_shoja, T[x]._path_ulta);
    }
    void pull(int x) {
        int l = T[x].ch[0], r = T[x].ch[1]; push(l); push(r);
        T[x].size = T[l].size + T[r].size + 1;
        T[x].path = T[l].path + T[x].self + T[r].path;
        T[x].sub = T[x].vir + T[l].sub + T[r].sub + T[x].self;
        T[x]._path_shoja = compose(T[l]._path_shoja,
            compose(T[x]._self, T[l]._path_shoja));
        T[x]._path_ulta = compose(T[r]._path_ulta,
            compose(T[x]._self, T[r]._path_ulta));
    }
    void set(int x, int d, int y) {
        T[x].ch[d] = y; T[y].p = x; pull(x);
    }
    void splay(int x) {
        auto dir = [&](int x) {
            int p = T[x].p; if (!p) return -1;
            return T[p].ch[0] == x ? 0 : T[p].ch[1] == x ? 1 :
                -1;
        };
        auto rotate = [&](int x) {
            int y = T[x].p, z = T[y].p, dx = dir(x), dy =
                dir(y);
            set(y, dx, T[x].ch[!dx]);
            set(x, !dx, y);
            if (~dy) set(z, dy, x);
            T[x].p = z;
        };
        for (push(x); ~dir(x); ) {
            int y = T[x].p, z = T[y].p;
            push(z); push(y); push(x);
            int dx = dir(x), dy = dir(y);
            if (~dy) rotate(dx != dy ? x : y);
            rotate(x);
        }
    }
    int KthNext(int x, int k) {
        assert(k > 0);
        splay(x);
        x = T[x].ch[1];
        if (T[x].size < k) return -1;
        while (true) {
            push(x);
            int l = T[x].ch[0], r = T[x].ch[1];
            if (T[l].size+1 == k) return x;
        }
    }
};

```

```

        if (k <= T[l].size) x = l;
        else k -= T[l].size+1, x = r;
    }
};
struct LinkCut : SplayTree {
    LinkCut(int n) : SplayTree(n) {}
    int access(int x) {
        int u = x, v = 0;
        for (; u; v = u, u = T[u].p) {
            splay(u);
            int& ov = T[u].ch[1];
            T[u].vir += T[ov].sub;
            T[u].vir -= T[v].sub;
            ov = v; pull(u);
        }
        splay(x);
        return v;
    }
    void reroot(int x) {
        access(x); T[x].flip ^= 1; push(x);
    }
    //makes v parent of u (optional: u must be a root)
    void Link(int u, int v) {
        reroot(u); access(v);
        T[v].vir += T[u].sub;
        T[u].p = v; pull(v);
    }
    //removes edge between u and v
    void Cut(int u, int v) {
        int _u = FindRoot(u);
        reroot(u); access(v);
        T[v].ch[0] = T[u].p = 0; pull(v);
        reroot(_u);
    }
    // Rooted tree LCA. Returns 0 if u and v arent connected.
    int LCA(int u, int v) {
        if (u == v) return u;
        access(u); int ret = access(v);
        return T[u].p ? ret : 0;
    }
    // Query subtree of u where v is outside the subtree.
    long long Subtree(int u, int v) {
        int _v = FindRoot(v);
        reroot(v); access(u);
        long long ans = T[u].vir + T[u].self;
        reroot(_v);
        return ans;
    }
    // Query path [u..v]
    long long Path(int u, int v) {
        int _u = FindRoot(u);
        reroot(u); access(v);
        long long ans = T[v].path;
        reroot(_u);
        return ans;
    }
    Linear _Path(int u, int v) {
        reroot(u); access(v); return T[v]._path_shoja;
    }
    // Update vertex u with value v
    void Update(int u, long long v) {
        access(u); T[u].self = v; pull(u);
    }
    // Update vertex u with value v
    void _Update(int u, Linear v) {
        access(u); T[u]._self = v; pull(u);
    }
    int FindRoot(int u) {
        access(u);
        while (T[u].ch[0]) {
            u = T[u].ch[0];
        }
        push(u);
        access(u);
        return u;
    }
    //k-th node (0-indexed) on the path from u to v
    int KthOnPath(int u, int v, int k) {

```

```

        if (u == v) return k == 0 ? u : -1;
        int _u = FindRoot(u);
        reroot(u); access(v);
        int ans = KthNext(u, k);
        reroot(_u);
        return ans;
    }
};
int main() {
    cin >> n >> q;
    LinkCut lct(n);
    for (int i = 1; i <= n; i++) {
        Linear l;
        cin >> l.first >> l.second;
        lct._Update(i, l);
    }
    for (int i = 1; i < n; i++) {
        int u, v;
        cin >> u >> v;
        lct.Link(u+1, v+1);
    }
    while (q--) {
        int op;
        cin >> op;
        if (op == 0) {
            int u, v, w, x;
            cin >> u >> v >> w >> x;
            lct.Cut(u+1, v+1);
            lct.Link(w+1, x+1);
        } else if (op == 1) {
            int p; Linear l;
            cin >> p >> l.first >> l.second;
            lct._Update(p+1, l);
        } else {
            int u, v, x;
            cin >> u >> v >> x;
            Linear l = lct._Path(u+1, v+1);
            cout << sum(mul(l.first, x), l.second) << "\n";
        }
    }
    return 0;
}

```

2.11 monotone_{cht}

```

/*Fully Generalized implementation for Monotone
slope, Arbitrary query
runtime insert() O(1) query() O(logn) */
class MonotoneCHT {
    deque<Line> Q;
    int type;
    void insertBack(Line nl) {
        //handle parallel line insertion
        if (!Q.empty() && Q.back().parallel(nl)) {
            if (type < 2) {
                if (Q.back().c > nl.c)
                    Q.pop_back();
                else
                    return;
            } else {
                if (Q.back().c < nl.c)
                    Q.pop_back();
                else
                    return;
            }
        }
        while (Q.size() > 1 && Q.back().intersect(nl) < Q[Q.size()-2].intersect(nl))
            Q.pop_back();
        Q.push_back(nl);
    }
    void insertFront(Line nl) {
        if (!Q.empty() && Q[0].parallel(nl)) {
            if (type < 2) {
                if (Q[0].c > nl.c)
                    Q.pop_front();
                else
                    return;
            } else {
                if (Q[0].c < nl.c)
                    Q.pop_front();
                else
                    return;
            }
        }
        while (Q.size() > 1 && Q[0].intersect(nl) > Q[1].intersect(nl))
            Q.pop_front();
    }
};

```



```

Q.push_front(n1);}
pii bSearch(ll x){
if(Q.size()==1||Q[0].intersect(Q[1]).first>=x)
return {0,0};
int l=1,r=(int)Q.size()-1;
while(r>l+1){
int mid=(l+r)/2;
if(Q[mid].intersect(Q[mid-1]).first<x)
l=mid;
else
r=mid;}
return {l,r};}

public:
//slope increasing or decreasing(not query point
//query point is arbitrary),querying for maximum or minimum
MonotoneCHT(bool increasing,bool maximum){
type=increasing;
if(maximum)
type=2;}
void insert(Line nl){
if(type==3||type==0)
insertBack(nl);
else
insertFront(nl);}
ll fastQuery(ll x)//if monotone query satisfied //not
tested,although it should be ok
{
#ifdef INCREASING_QUERY
while(Q.size()>1&&Q[0].intersect(Q[1]).first<x)
Q.pop_front();
return Q[0](x);
#else
while(Q.size()>1&&Q.back().intersect(Q[(int)Q.size()-2]).first>x)
Q.pop_back();
return Q.back()(x);
#endif}
ll query(ll x){
pii indx=bSearch(x);
if(type<2)
return min(Q[indx.first](x),Q[indx.second](x));
return max(Q[indx.first](x),Q[indx.second](x));}
void clear()
{Q.clear();};}

```

2.12 segment tree beats

```

#include <bits/stdc++.h>
using namespace std;
using ll = long long;
const int MAXN = 200001; // 1-based
int N;
ll A[MAXN];
struct Node {
ll sum,max1,max2,maxc,min1,
min2,minc,lazy;
//max1->ith max,maxc->maxcount
} T[MAXN * 4];
void merge(int t) {
// sum
T[t].sum = T[t << 1].sum + T[t << 1 | 1].sum;
// max
if (T[t << 1].max1 == T[t << 1 | 1].max1) {
T[t].max1 = T[t << 1].max1;
T[t].max2 = max(T[t << 1].max2, T[t << 1 | 1].max2);
T[t].maxc = T[t << 1].maxc + T[t << 1 | 1].maxc;
} else {
if (T[t << 1].max1 > T[t << 1 | 1].max1) {
T[t].max1 = T[t << 1].max1;
T[t].max2 = max(T[t << 1].max2, T[t << 1 | 1].max1);
T[t].maxc = T[t << 1].maxc;
} else {
T[t].max1 = T[t << 1 | 1].max1;
T[t].max2 = max(T[t << 1].max1, T[t << 1 | 1].max2);
T[t].maxc = T[t << 1 | 1].maxc;
}
}
// min
if (T[t << 1].min1 == T[t << 1 | 1].min1) {
T[t].min1 = T[t << 1].min1;
T[t].min2 = min(T[t << 1].min2, T[t << 1 | 1].min2);

```

```

T[t].minc = T[t << 1].minc + T[t << 1 | 1].minc;
} else {
if (T[t << 1].min1 < T[t << 1 | 1].min1) {
T[t].min1 = T[t << 1].min1;
T[t].min2 = min(T[t << 1].min2, T[t << 1 | 1].min1);
T[t].minc = T[t << 1].minc;
} else {
T[t].min1 = T[t << 1 | 1].min1;
T[t].min2 = min(T[t << 1].min1, T[t << 1 | 1].min2);
T[t].minc = T[t << 1 | 1].minc;
}
}
}
}
void push_add(int t, int tl, int tr, ll v) {
if (v == 0)
return;
T[t].sum += (tr - tl + 1) * v;
T[t].max1 += v;
if (T[t].max2 != -11INF) {
T[t].max2 += v;
}
T[t].min1 += v;
if (T[t].min2 != 11INF) {
T[t].min2 += v;
}
T[t].lazy += v;
}
// corresponds to a chmin update
void push_max(int t, ll v, bool l) {
if (v >= T[t].max1)
return;
T[t].sum -= T[t].max1 * T[t].maxc;
T[t].sum += T[t].max1 * v;
if (l) {
T[t].min1 = T[t].max1;
} else {
if (v <= T[t].min1) {
T[t].min1 = v;
} else if (v < T[t].min2) {
T[t].min2 = v;
}
}
}
// corresponds to a chmax update
void push_min(int t, ll v, bool l) {
if (v <= T[t].min1)
return;
T[t].sum -= T[t].min1 * T[t].minc;
T[t].min1 = v;
T[t].sum += T[t].min1 * T[t].minc;
if (l) {
T[t].max1 = T[t].min1;
} else {
if (v >= T[t].max1) {
T[t].max1 = v;
} else if (v > T[t].max2) {
T[t].max2 = v;
}
}
}
}
void pushdown(int t, int tl, int tr) {
if (tl == tr)
return;
// sum
int tm = (tl + tr) >> 1;
push_add(t << 1, tl, tm, T[t].lazy);
push_add(t << 1 | 1, tm + 1, tr, T[t].lazy);
T[t].lazy = 0;
// max
push_max(t << 1, T[t].max1, tl == tm);
push_max(t << 1 | 1, T[t].max1, tm + 1 == tr);
// min
push_min(t << 1, T[t].min1, tl == tm);
push_min(t << 1 | 1, T[t].min1, tm + 1 == tr);
}
void build(int t=1, int tl=0, int tr=N-1) {
T[t].lazy = 0;
if (tl == tr) {
T[t].sum = T[t].max1 = T[t].min1 = A[tl];

```

```

T[t].maxc = T[t].minc = 1;
T[t].max2 = -11INF;
T[t].min2 = 11INF;
return;
}
int tm = (tl + tr) >> 1;
build(t << 1, tl, tm);
build(t << 1 | 1, tm + 1, tr);
merge(t);
}
void update_add(int l, int r, ll v, int t=1, int tl=0, int
tr=N-1) {
if (r < tl || tr < l)
return;
if (l <= tl && tr <= r) {
push_add(t, tl, tr, v);
return;
}
pushdown(t, tl, tr);
int tm = (tl + tr) >> 1;
update_add(l, r, v, t << 1, tl, tm);
update_add(l, r, v, t << 1 | 1, tm + 1, tr);
merge(t);
}
void update_chmin(int l, int r, ll v, int t=1, int tl=0, int
tr=N-1) {
if (r < tl || tr < l || v >= T[t].max1) {
return;
}
if (l <= tl && tr <= r && v > T[t].max2) {
push_max(t, v, tl == tr);
return;
}
pushdown(t, tl, tr);
int tm = (tl + tr) >> 1;
update_chmin(l, r, v, t << 1, tl, tm);
update_chmin(l, r, v, t << 1 | 1, tm + 1, tr);
merge(t);
}
void update_chmax(int l, int r, ll v, int t=1, int tl=0, int
tr=N-1) {
if (r < tl || tr < l || v <= T[t].min1)
return;
if (l <= tl && tr <= r && v < T[t].min2) {
push_min(t, v, tl == tr);
return;
}
pushdown(t, tl, tr);
int tm = (tl + tr) >> 1;
update_chmax(l, r, v, t << 1, tl, tm);
update_chmax(l, r, v, t << 1 | 1, tm + 1, tr);
merge(t);
}
ll query_sum(int l, int r, int t=1, int tl=0, int tr=N-1) {
if (r < tl || tr < l)
return 0;
if (l <= tl && tr <= r)
return T[t].sum;
pushdown(t, tl, tr);
int tm = (tl + tr) >> 1;
return query_sum(l, r, t << 1, tl, tm) + query_sum(l, r, t
<< 1 | 1, tm + 1, tr);
}
}
int main() {
int Q;
cin >> N >> Q;
for (int i = 0; i < N; i++) {
cin >> A[i];
}
build();
for (int q = 0; q < Q; q++) {
int t; cin >> t;
if (t == 0) {
int l, r;
ll x;
cin >> l >> r >> x;
update_chmin(l, r - 1, x);
} else if (t == 1) {
int l, r;
ll x;

```

```

    cin >> l >> r >> x;
    update_chmax(l, r - 1, x);
} else if (t == 2) {
    int l, r;
    ll x;
    cin >> l >> r >> x;
    update_add(l, r - 1, x);
} else if (t == 3) {
    int l, r;
    cin >> l >> r;
    cout << query_sum(l, r - 1) << '\n';
}
}
}

```

2.13 sparse table 2d

```

const int N=500; const int K = 8 ; // k >= ceil(lg22(n)) + 1
int arr[N][N]; int st[K+1][K+1][N][N]; int lg2[N+1];
void ini(){ lg2[1] = 0;
    for (int i = 2; i <= N; i++) lg2[i] = lg2[i/2] + 1; }
int f(int i,int j){ return max(i,j); }
void pre( int n,int m){
    for(int x=0;x<=K;x++){
        for(int y=0;y<=K;y++){
            for(int i=0;i<n;i++){
                for(int j=0;j<m;j++){
                    if(i+(1<<x)>n or j+(1<<y) > m) continue;
                    if(x>0) st[x][y][i][j] = f(st[x-1][y][i][j] ,
                        st[x-1][y][i+(1<<(x-1))][j]);
                    else if(y>0) st[x][y][i][j] = f(st[x][y-1][i][j] ,
                        st[x][y-1][i][j+(1<<(y-1))]);
                    else st[x][y][i][j] = f(arr[i][j] , arr[i][j]);
                } } } }
    int getf( int R1 ,int C1 , int R2 , int C2){
        if(R1>R2) swap(R1,R2); if(C1>C2) swap(C1,C2);
        int x = lg2[R2 - R1 + 1]; int y = lg2[C2 - C1 + 1];
        return f(f(st[x][y][R1][C1],st[x][y][R2-(1<<x)+1][C1]),
            st[x][y][R1][C2-(1<<y)+1],st[x][y][R2-(1<<x)+1][C2-(1<<y)+1]);
    }
}

```

2.14 treap

```

struct node {
    int prior, size;
    ll val, sum, lazy, rev;
    node *l, *r;
    node(int v = 0) {
        val = sum = v;
        lazy = 0; rev = 0;
        prior = rand();
        size = 1;
        l = r = NULL;
    }
} *root;
//If you initialize the root (root = new node()) then treap
//will be 1 based indexing and root will be the 0th index
//Otherwise it will be 0 based indexing, so decide carefully
typedef node* pnode;

int sz(pnode t) { return t ? t->size : 0; }
void upd_sz(pnode t) { if(t) t->size = sz(t->l) + 1 + sz(t->r); }

void push(pnode t) {
    if(!t) return;
    if(t->lazy){
        t->val += t->lazy;
        t->sum += t->lazy * sz(t);
        if(t->l) t->l->lazy += t->lazy;
        if(t->r) t->r->lazy += t->lazy;
        t->lazy = 0;
    }
    //Reverse
    if(t->rev){
        swap(t->l,t->r);
        if(t->l) t->l->rev ^= t->rev;
        if(t->r) t->r->rev ^= t->rev;
        t->rev = 0;
    }
}

```

```

}
}

void combine(pnode t) {
    // Note: This function should reset datas of t first (MUST!!)
    // Then update datas from l and r.
    if(!t) return;
    push(t->l);
    push(t->r);
    t->sum = t->val; // Reset
    if(t->l) t->sum += t->l->sum;
    if(t->r) t->sum += t->r->sum;
}

void split(pnode t, pnode &l, pnode &r, int pos, int add = 0) {
    if(!t) return void(l = r = NULL);
    push(t);
    int curr = sz(t->l) + add;
    if(curr <= pos)
        split(t->r, t->r, r, pos, curr + 1), l = t;
    else split(t->l, l, t->l, pos, add), r = t;
    upd_sz(t);
    combine(t);
}

void merge(pnode &t, pnode l, pnode r) {
    push(l), push(r);
    if(!l || !r)
        t = l ? l : r;
    else if(l->prior > r->prior)
        merge(l->r, l->r, r), t = l;
    else merge(r->l, l, r->l), t = r;
    upd_sz(t);
    combine(t);
}

ll query(pnode t, int l, int r) {
    pnode L, mid, R;
    split(t, L, mid, l - 1);
    split(mid, t, R, r - l);
    ll ans = t->sum;
    merge(mid, L, t);
    merge(t, mid, R);
    return ans;
}

void update(pnode t, int l, int r, ll v) {
    pnode L, mid, R;
    split(t, L, mid, l - 1);
    split(mid, t, R, r - l);
    t->lazy += v;
    merge(mid, L, t);
    merge(t, mid, R);
}

void insert(pnode &t, int pos, int v) {
    pnode L, R, tmp, y = new node(v);
    split(t, L, R, pos - 1);
    merge(tmp, L, y);
    merge(t, tmp, R);
}

void Del(pnode &t, int pos) {
    pnode L, R, mid;
    split(t, L, mid, pos - 1);
    split(mid, t, R, 0);
    pnode tmp = t;
    merge(t, L, R);
    free(tmp);
}

void Reverse(pnode t, int l, int r) {
    pnode L, mid, R;
    split(t, L, mid, l - 1);
    split(mid, t, R, r - l);
    t->rev ^= 1;
    merge(mid, L, t);
    merge(t, mid, R);
}

```

3 Extra

3.1 Header

```

#include <bits/stdc++.h>
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>
#include <ext/pb_ds/detail/standard_policies.hpp>
using namespace std;
typedef long long ll;
typedef pair<int, int> pii;
typedef pair<ll, ll> pll;
typedef double ftype;
typedef pair<ftype,ftype> pff;
#define all(a) a.begin(), a.end()
#define some(a,l,r) a.begin()+l,a.begin()+(r+1)
#define csort(a) sort(all(a))
#define pub push_back
#define puf push_front
#define pob pop_back
#define pof pop_front
#define fi first
#define se second
#define fastio ios_base::sync_with_stdio(false);cin.tie(NULL)
#ifdef COMEDIANS
#define infile ;
#define outfile ;
#define Gene template< class
#define Rics printer& operator,
Gene c> struct rge{c b, e};
Gene c> rge<c> range(c i, c j){ return {i, j};}
struct printer{
    ~printer(){cerr<<endl;}
    Gene c >Rics(c x){ cerr<<boolalpha<<x; return *this;}
    Rics(string x){cerr<<x;return *this;}
    Gene c, class d >Rics(pair<c, d> x){ return
        *this,"(",x.first," ",x.second,")";}
    Gene ... d, Gene ...> class c >Rics(c<d...> x){ return
        *this, range(begin(x), end(x));}
    Gene c >Rics(rge<c> x){
        *this,"["; for(auto it = x.b; it != x.e; ++it)
            *this,(it==x.b?"":" "),*it; return *this,"]";}
};
#define stop getchar()
#define debug() cerr<<"LINE "<<__LINE__<<" >> ", printer()
#define dbg(x) debug(), "[",#x," ",(x),"] "
#define test_handle(T) cin>>T

void err(istream_iterator<string> it) {cout<<endl;}
template<typename T, typename... Args>
void err(istream_iterator<string> it, T a, Args... args){
    cout << *it << " = " << a << " ";err(++it, args...);
}
template<class T1, class T2>
ostream &operator <<(ostream &os, pair<T1,T2>&p) {
    os<<"{"<<p.first<<" , "<<p.second<<" }";
    return os;
}
#define dbg2(args...) { string _s = #args; replace(_s.begin(),
    _s.end(), ',', ' '); stringstream _ss(_s);
    istream_iterator<string> _it(_ss); err(_it, args); }
#else
#define dbg(x) ;
#define infile ;
#define outfile ;
#define test_handle(T) T = 1
#define dbg2(args...) ;
#endif
//Use -DCOMEDIANS in compiler flag in others tab, or remove
#ifdef
mt19937
rng(chrono::steady_clock::now().time_since_epoch().count());
const ftype EPS = 1e-10;
const ftype PI = acos(-1);
const int MAX = 3e5+5;
const int BMAX = 18;
const int MOD = 1e9+7;
using namespace __gnu_pbds;
/*
find_by_order(k) --> returns iterator to the kth largest
element counting from 0
*/

```

```

order_of_key(val) --> returns the number of items in a set
that are strictly smaller than our item
*/
typedef tree<
int,
null_type,
less<int>,
rb_tree_tag,
tree_order_statistics_node_update>
ordered_set;
//#pragma GCC optimize("O3,unroll-loops")
//#pragma GCC target("avx2,bmi,bmi2,lzcnt")
//mt19937
rng(chrono::system_clock::now().time_since_epoch().count());
#include <ext/pb_ds/assoc_container.hpp>
using namespace __gnu_pbds;
struct custom_hash {
static uint64_t splitmix64(uint64_t x) {
x += 0x9e3779b97f4a7c15; //Random
x=(x<>>30))*0xbf58476d1ce4e5b9; //Random
x=(x<>>27))*0x94d049bb133111eb; //Random
return x<>>31;
}
const uint64_t FIXED_RANDOM = chrono::
steady_clock::now().time_since_epoch().count();
size_t operator()(uint64_t x) const {
return splitmix64(x + FIXED_RANDOM);
}
size_t operator()(pair<int, int> x) const {
return splitmix64((uint64_t(x.first)<<32) +
x.second + FIXED_RANDOM);
}
};
gp_hash_table<pair<int,int>,int,custom_hash> ht;
namespace my_gcc_ints {
#pragma GCC diagnostic push
#pragma GCC diagnostic ignored "-Wpedantic"
using int128 = __int128;
#pragma GCC diagnostic pop
}
# stresstester GENERATOR SOL1 SOL2 ITERATIONS
for i in $(seq 1 "$4") ; do
echo -en "\rAttempt $i/$4"
$1 > in.txt
$2 < in.txt > out1.txt
$3 < in.txt > out2.txt
diff -y out1.txt out2.txt > diff.txt
if [ $? -ne 0 ] ; then
echo -e "\nTestcase Found:"; cat in.txt
echo -e "\nOutputs:"; cat diff.txt
exit
fi
done
//generate all submask
int s = m;
while (s > 0) {
s = (s-1) & m;}

```

4 Game

4.1 HackenBush

```

/* tree case: g[u] = for all v : XOR[ g[v] + 1]
lose if no moves available
1. Colon Principle: Grundy number of a tree is the
xor of Grundy number of child subtrees.
2. Fusion Principle: Consider a pair of adjacent
vertices u, v that has another path (i.e.,
they are in a cycle). Then, we can contract u
and v without changing Grundy number.
We first decompose graph into two-edge connected
components. Then, by contracting each components by
using Fusion Principle, we obtain a tree (and many
self loops) that has the same Grundy number to the
original graph. By using Colon Principle, we can
compute the Grundy number. O(m + n). */
struct hackenbush {
int n; vector<vector<int>> adj;
hackenbush(int n) : n(n), adj(n) {}
void add_edge(int u, int v) {
adj[u].push_back(v);

```

```

if(u!=v) adj[v].push_back(u);
}
int Grundy(int r) {
vector<int> num(n), low(n); int t = 0;
function<int(int, int)> dfs=[&](int p,int u) {
num[u] = low[u] = ++t; int ans = 0;
for (int v : adj[u]) {
if (v == p) { p += 2 * n; continue; }
if (num[v] == 0) {
int res = dfs(u, v);
low[u] = min(low[u], low[v]);
if (low[v] > num[u]) ans ^= (1+res)^1;
else ans ^= res; // non bridge
}
else low[u] = min(low[u], num[v]);
}
if (p > n) p -= 2 * n;
for (int v : adj[u])
if (v != p && num[u] <= num[v]) ans ^= 1;
return ans;
};
return dfs(-1, r);
}
};

```

5 Geo

5.1 3dGeo

```

int dcmp(double x) { return abs(x) < EPS ? 0 : (x<0 ? -1 : 1); }
double degreeToRadian(double rad) { return rad*PI/180; }
struct Point {
double x, y, z; Point() : x(0), y(0), z(0) {}
Point(double X, double Y, double Z) : x(X), y(Y), z(Z) {}
Point operator + (const Point& u) const {
return Point(x + u.x, y + u.y, z + u.z); }
Point operator - (const Point& u) const {
return Point(x - u.x, y - u.y, z - u.z); }
Point operator * (const double u) const {
return Point(x * u, y * u, z * u); }
Point operator / (const double u) const {
return Point(x / u, y / u, z / u); }
};
double dot(Point a, Point b) { return a.x*b.x+a.y*b.y+a.z*b.z; }
Point cross(Point a, Point b) { return
Point(a.y*b.z - a.z*b.y, a.z*b.x - a.x*b.z, a.x*b.y - a.y*b.x); }
double length(Point a) { return sqrt(dot(a, a)); }
double distance(Point a, Point b) { return length(a-b); }
Point unit(const Point &p) { return p/length(p); }
// Rotate p around axis x, with angle radians.
Point rotate(Point p, Point axis, double angle) {
axis = unit(axis); Point comp1 = p * cos(angle);
Point comp2 = axis * (1-cos(angle)) * dot(axis, p);
Point comp3 = cross(axis, p) * sin(angle);
return comp1 + comp2 + comp3;
}
struct Line {Point a, v;}; //a+tv
// returns the distance from point a to line l
double distancePointLine(Point p, Line l) {
return length(cross(l.v, p - l.a)) / length(l.v); }
// distance from Line ab to Line cd
double distanceLineLine(Line a, Line b) {
Point cr = cross(a.v, b.v); double crl = length(cr);
if (dcmp(crl) == 0) return distancePointLine(a.a, b);
return abs(dot(cr, a.a-b.a))/crl; }
struct Plane {
Point normal; // Normal = (A, B, C)
double d; // dot(Normal) = d <--> Ax + By + Cz = d
Point P; // anyPoint on the plane, optional
Plane(Point normal, double d) {
double len = length(normal); assert(dcmp(len) > 0);
normal = normal / len; d = d / len;
if (dcmp(normal.x)) P = Point(d/normal.x, 0, 0);
else if (dcmp(normal.y)) P = Point(0, d/normal.y, 0);
else P = Point(0, 0, d/normal.z);
}
//Plane given by three Non-Collinear Points

```

```

Plane(Point a, Point b, Point c) {
normal = unit(cross(b-a, c-a)); d = dot(normal,a); P=a;
}
bool onPlane(Point a) { return dcmp(dot(normal,a)-d)== 0;}
double distance(Point a) { return abs(dot(normal, a) - d);}
double isParallel(Line l){return dcmp(dot(l.v,normal))==0;}
//return t st l.a + t*l.v is a point on the plane, check
//parallel first
double intersectLine(Line l) {
return dot(P-l.a, normal)/dot(l.v, normal); } };

```

5.2 Circle Cover

```

//Check if the all of the area of circ(0, R) in
//Circ(00, RR) is covered by some other circle
bool CoverCircle(PT O, double R, vector<PT> &cen,
vector<double> &rad, PT OO, double RR) {
int n = cen.size();
vector<pair<double, double>> arcs;
for (int i=0; i<n; i++) {
PT P = cen[i]; double r = rad[i];
if (i!=0 && R + sqrt(dist2(O, P))<r) return 1;
if (i==0 && r + sqrt(dist2(O, P))<R) return 1;
vector<PT> inter =
CircleCircleIntersection(O, P, R, r);
if (inter.size() <= 1) continue;
PT X = inter[0], Y = inter[1];
if (cross(O, X, Y) < 0) swap(X, Y);
if (!(cross(O, X, P) >= 0 &&
cross(O, Y, P) <= 0)) swap(X, Y);
if (i==0) swap(X, Y);
X = X-O; Y=Y-O;
double ll = atan2(X.y, X.x);
double rr = atan2(Y.y, Y.x);
if (rr < ll) rr += 2*PI;
arcs.emplace_back(ll, rr);
}
if (arcs.empty()) return false;
sort(arcs.begin(), arcs.end());
double st = arcs[0].ff, en = arcs[0].ss, ans = 0;
for (int i=1; i<arcs.size(); i++) {
if (arcs[i].first <= en + EPS)
en = max(en, arcs[i].second);
else st = arcs[i].first, en = arcs[i].second;
ans = max(ans, en-st);
}
return ans >= 2*PI;
}

```

5.3 Circle Union Area

```

struct Point {
LD x, y;
LD operator*(const Point &a)const {
return x*a.y-y*a.x;}
LD operator/(const Point &a)const {
return sqrt((a.x-x)*(a.x-x)+(a.y-y)*(a.y-y));}
}po[N];
LD r[N];
int sgn(LD x) {return fabs(x)<EPS?0:(x>0.0?1:-1);}
pair<LD,bool> ARG[2*N];
LD cir_union(Point c[],LD r[],int n) {
LD sum = 0.0, sum1 = 0.0, d,p1,p2,p3;
for(int i = 0; i < n; i++) {
bool f = 1;
for(int j = 0; j < n; j++) {
if(i!=j && sgn(r[j]-r[i]-c[i]/c[j])!=-1)f=0;
if(!f) swap(r[i],r[--n]),swap(c[i--],c[n]);
}
for(int i = 0; i < n; i++) {
int k = 0, cnt = 0;
for(int j = 0; j < n; j++) {
if(i!=j&&sgn((d=c[i]/c[j])-r[i]-r[j])<=0){
p3=acos((r[i]*r[i]+d*d-r[j]*r[j])/
(2.0*r[i]*d));
p2=atan2(c[j].y-c[i].y,c[j].x-c[i].x);
p1 = p2-p3; p2 = p2+p3;
if(sgn(p1+PI)==-1) p1+=2*PI,cnt++;
if(sgn(p2-PI)==1) p2-=2*PI,cnt++;
}
}

```

```

    ARG[k++] = make_pair(p1,0);
    ARG[k++] = make_pair(p2,1);
}
}
if(k) {
    sort(ARG,ARG+k);
    p1 = ARG[k-1].first-2*PI;
    p3 = r[i]*r[i];
    for(int j = 0; j < k; j++) {
        p2 = ARG[j].first;
        if(cnt==0) {
            sum+=(p2-p1-sin(p2-p1))*p3;
            sum1+=(c[i]+Point(cos(p1),sin(p1))*
                r[i])*(c[i]+
                Point(cos(p2),sin(p2))*r[i]);
        }
        p1 = p2;
        ARG[j].second ? cnt--:cnt++;
    }
    else sum += 2*PI*r[i]*r[i];
}
return (sum+fabs(sum1))*0.5;
}

```

5.4 basic-area-geometry

```

struct point2d {
    ftype x, y; point2d() {}
    point2d(ftype x, ftype y): x(x), y(y) {}
    point2d& operator+=(const point2d &t) {
        x += t.x; y += t.y; return *this;
    }
    point2d& operator--=(const point2d &t) {
        x -= t.x; y -= t.y; return *this;
    }
    point2d& operator+=(ftype t) {
        x += t; y += t; return *this;
    }
    point2d& operator-=(ftype t) {
        x -= t; y -= t; return *this;
    }
    point2d& operator+=(const point2d &t) const {
        return point2d(*this) += t;
    }
    point2d& operator-(const point2d &t) const {
        return point2d(*this) -= t;
    }
    point2d& operator*(ftype t) const {
        return point2d(*this) *= t;
    }
    point2d& operator/(ftype t) const {
        return point2d(*this) /= t;
    }
};

point2d operator*(ftype a, point2d b) {
    return b * a;
}

struct point3d {
    ftype x, y, z; point3d() {}
    point3d(ftype x, ftype y, ftype z): x(x), y(y), z(z) {}
    point3d& operator+=(const point3d &t) {
        x += t.x; y += t.y; z += t.z; return *this;
    }
    point3d& operator--=(const point3d &t) {
        x -= t.x; y -= t.y; z -= t.z; return *this;
    }
    point3d& operator+=(ftype t) {
        x += t; y += t; z += t; return *this;
    }
    point3d& operator-=(ftype t) {
        x -= t; y -= t; z -= t; return *this;
    }
    point3d& operator/(ftype t) {
        x /= t; y /= t; z /= t; return *this;
    }
    point3d& operator+(const point3d &t) const {
        return point3d(*this) += t;
    }
    point3d& operator-(const point3d &t) const {
        return point3d(*this) -= t;
    }
}

```

```

}
point3d operator*(ftype t) const {
    return point3d(*this) *= t;
}
point3d operator/(ftype t) const {
    return point3d(*this) /= t;
}
};

point3d operator*(ftype a, point3d b) {
    return b * a;
}

ftype dot(point2d a, point2d b) {
    return a.x * b.x + a.y * b.y;
}

ftype dot(point3d a, point3d b) {
    return a.x * b.x + a.y * b.y + a.z * b.z;
}

ftype norm(point2d a) {
    return dot(a, a);
}

double abs(point2d a) {
    return sqrt(norm(a));
}

double proj(point2d a, point2d b) {
    return dot(a, b) / abs(b);
}

double angle(point2d a, point2d b) {
    return acos(dot(a, b) / abs(a) / abs(b));
}

point3d cross(point3d a, point3d b) {
    return point3d(a.y * b.z - a.z * b.y,
        a.z * b.x - a.x * b.z, a.x * b.y - a.y * b.x);
}

ftype triple(point3d a, point3d b, point3d c) {
    return dot(a, cross(b, c));
}

ftype cross(point2d a, point2d b) {
    return a.x * b.y - a.y * b.x;
}

point2d intersect(point2d a1, point2d d1,
    point2d a2, point2d d2) {
    return a1 + cross(a2 - a1, d2) / cross(d1, d2) * d1;
}

point3d intersect(point3d a1, point3d n1, point3d a2,
    point3d n2, point3d a3, point3d n3) {
    point3d x(n1.x, n2.x, n3.x); point3d y(n1.y, n2.y, n3.y);
    point3d z(n1.z, n2.z, n3.z);
    point3d d(dot(a1, n1), dot(a2, n2), dot(a3, n3));
    return point3d(triple(d, y, z), triple(x, d, z),
        triple(x, y, d)) / triple(n1, n2, n3);
}

int signed_area_parallelogram(point2d p1, point2d p2, point2d p3) {
    return cross(p2 - p1, p3 - p2);
}

double triangle_area(point2d p1, point2d p2, point2d p3) {
    return abs(signed_area_parallelogram(p1, p2, p3)) / 2.0;
}

bool clockwise(point2d p1, point2d p2, point2d p3) {
    return signed_area_parallelogram(p1, p2, p3) < 0;
}

bool counter_clockwise(point2d p1, point2d p2, point2d p3) {
    return signed_area_parallelogram(p1, p2, p3) > 0;
}

double area(const vector<point>& fig) {
    double res = 0;
    for (unsigned i = 0; i < fig.size(); i++) {
        point p = i? fig[i - 1] : fig.back(); point q = fig[i];
        res += (p.x - q.x) * (p.y + q.y);
    }
    return fabs(res) / 2;
}

//Pick: S = I + B/2 - 1
int count_lattices(Fraction k, Fraction b, long long n) {
    auto fk = k.floor(); auto fb = b.floor(); auto cnt = 0LL;
    if (k >= 1 || b >= 1) {
        cnt+=(fk*(n - 1) + 2 * fb) * n / 2; k -= fk; b -= fb;
    }
    auto t = k * n + b; auto ft = t.floor();
}

```

```

if (ft >= 1)
cnt += count_lattices(1 / k, (t - t.floor()) / k, t.floor());
return cnt;
}

```

5.5 geo-formulae

Triangle Centers and Radii

- Incenter: $\left(\frac{ax_1+bx_2+cx_3}{a+b+c}, \frac{ay_1+by_2+cy_3}{a+b+c}\right)$.
- Inradius: $\sqrt{\frac{(s-a)(s-b)(s-c)}{s}}$.
- Excenter: $\left(\frac{-ax_1+bx_2+cx_3}{-a+b+c}, \frac{-ay_1+by_2+cy_3}{-a+b+c}\right)$.
- Exradius: $\sqrt{\frac{s(s-b)(s-c)}{(s-a)}}$.
- Circumcenter: $\left(\frac{x_1 \sin 2A + x_2 \sin 2B + x_3 \sin 2C}{\sin 2A + \sin 2B + \sin 2C}, \frac{y_1 \sin 2A + y_2 \sin 2B + y_3 \sin 2C}{\sin 2A + \sin 2B + \sin 2C}\right)$.
- Circumradius: $\frac{abc}{\sqrt{(a+b+c)(b+c-a)(c+a-b)(a+b-c)}}$.

5.6 half-plane-intersection

```

class HalfPlaneIntersection{
    static double eps, inf;
public:
    struct Point{
        double x, y;
        explicit Point(double x = 0, double y = 0) : x(x), y(y) {}
        // Addition, subtraction, multiply by constant, cross product.
        friend Point operator + (const Point& p, const Point& q){
            return Point(p.x + q.x, p.y + q.y);
        }
        friend Point operator - (const Point& p, const Point& q){
            return Point(p.x - q.x, p.y - q.y);
        }
        friend Point operator * (const Point& p, const double& k){
            return Point(p.x * k, p.y * k);
        }
        friend double cross(const Point& p, const Point& q){
            return p.x * q.y - p.y * q.x;
        }
    };
    // Basic half-plane struct.
    struct Halfplane{
        // 'p' is a passing point of the line and 'pq' is the direction vector of the line.
        Point p, pq;
        double angle;
        Halfplane() {}
        Halfplane(const Point& a, const Point& b) : p(a), pq(b - a){
            angle = atan2(pq.y, pq.x);
        }
        // Check if point 'r' is outside this half-plane.
        // Every half-plane allows the region to the LEFT of its line.
        bool out(const Point& r){
            return cross(pq, r - p) < -eps;
        }
        // Comparator for sorting.
        // If the angle of both half-planes is equal, the leftmost one should go first.
        bool operator < (const Halfplane& e) const{
            if (fabs(angle - e.angle) < eps) return cross(pq,
                e.p - p) < 0;
            return angle < e.angle;
        }
    };
}

```



```

}
// We use equal comparator for std::unique to easily
// remove parallel half-planes.
bool operator==(const Halfplane& e) const{
    return fabs(angle - e.angle) < eps;
}
// Intersection point of the lines of two half-planes.
// It is assumed they're never parallel.
friend Point inter(const Halfplane& s, const Halfplane&
t){
    double alpha = cross((t.p - s.p), t.pq) /
        cross(s.pq, t.pq);
    return s.p + (s.pq * alpha);
}
};
static vector<Point> hp_intersect(vector<Halfplane>& H){
    Point box[4] = // Bounding box in CCW order{
        Point(-inf, inf),
        Point(inf, inf),
        Point(inf, -inf),
        Point(-inf, -inf)
    };
    for(int i = 0; i < 4; i++) // Add bounding box
        half-planes.{
            Halfplane aux(box[i], box[(i+1) % 4]);
            H.push_back(aux);
        }
    // Sort and remove duplicates
    sort(H.begin(), H.end());
    H.erase(unique(H.begin(), H.end()), H.end());
    deque<Halfplane> dq;
    int len = 0;
    for(int i = 0; i < int(H.size()); i++){
        // Remove from the back of the deque while last
        // half-plane is redundant
        while (len > 1 && H[i].out(inter(dq[len-1],
            dq[len-2]))){
            dq.pop_back();
            --len;
        }
        // Remove from the front of the deque while first
        // half-plane is redundant
        while (len > 1 && H[i].out(inter(dq[0], dq[1]))){
            dq.pop_front();
            --len;
        }
        // Add new half-plane
        dq.push_back(H[i]);
        ++len;
    }
    // Final cleanup: Check half-planes at the front
    // against the back and vice-versa
    while (len > 2 && dq[0].out(inter(dq[len-1],
        dq[len-2]))){
        dq.pop_back();
        --len;
    }
    while (len > 2 && dq[len-1].out(inter(dq[0], dq[1]))){
        dq.pop_front();
        --len;
    }
    // Report empty intersection if necessary
    if (len < 3) return vector<Point>();
    // Reconstruct the convex polygon from the remaining
    // half-planes.
    vector<Point> ret(len);
    for(int i = 0; i < len; i++){
        ret[i] = inter(dq[i], dq[i+1]);
    }
    ret.back() = inter(dq[len-1], dq[0]);
    return ret;
}
};
double HalfPlaneIntersection::eps=1e-9;
double HalfPlaneIntersection::inf=1e9;

```

5.7 heart-of-geometry-2d

```
typedef double ftype;
```

```

const double EPS = 1E-9;
struct pt{
    ftype x, y;
    int id;
    pt() {}
    pt(ftype _x, ftype _y):x(_x), y(_y) {}
    pt operator+(const pt & p) const{
        return pt(x + p.x, y + p.y);
    }
    pt operator-(const pt & p) const{
        return pt(x - p.x, y - p.y);
    }
    ftype cross(const pt & p) const{
        return x * p.y - y * p.x;
    }
    ftype dot(const pt & p) const{
        return x * p.x + y * p.y;
    }
    ftype cross(const pt & a, const pt & b) const{
        return (a - *this).cross(b - *this);
    }
    ftype dot(const pt & a, const pt & b) const{
        return (a - *this).dot(b - *this);
    }
    ftype sqrLen() const{
        return this->dot(*this);
    }
    bool operator<(const pt& p) const{
        return x < p.x - EPS || (abs(x - p.x) < EPS && y < p.y
            - EPS);
    }
    bool operator==(const pt& p) const{
        return abs(x-p.x)<EPS && abs(y-p.y)<EPS;
    }
};
int sign(double x) { return (x > EPS) - (x < -EPS); }
inline int orientation(pt a, pt b, pt c) { return
    sign(a.cross(b,c)); }
bool is_point_on_seg(pt a, pt b, pt p) {
    if (fabs(b.cross(p,a)) < EPS) {
        if (p.x < min(a.x, b.x) - EPS || p.x > max(a.x, b.x) +
            EPS) return false;
        if (p.y < min(a.y, b.y) - EPS || p.y > max(a.y, b.y) +
            EPS) return false;
        return true;
    }
    return false;
}
bool is_point_on_polygon(vector<pt> &p, const pt& z) {
    int n = p.size();
    for (int i = 0; i < n; i++) {
        if (is_point_on_seg(p[i], p[(i + 1) % n], z)) return 1;
    }
    return 0;
}
int winding_number(vector<pt> &p, const pt& z) { // 0(n)
    if (is_point_on_polygon(p, z)) return 1e9;
    int n = p.size(), ans = 0;
    for (int i = 0; i < n; ++i) {
        int j = (i + 1) % n;
        bool below = p[i].y < z.y;
        if (below != (p[j].y < z.y)) {
            auto orient = orientation(z, p[j], p[i]);
            if (orient == 0) return 0;
            if (below == (orient > 0)) ans += below ? -1 : 1;
        }
    }
    return ans;
}
double dist_sqr(pt a,pt b){
    return ((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y));
}
double dist(pt a, pt b){
    return sqrt((a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y));
}
double angle(pt a,pt b,pt c){
    if(b==a || b==c) return 0;
    double A2 = dist_sqr(b,c);

```

```

double C2 = dist_sqr(a,b);
double B2 = dist_sqr(c,a);
double A = sqrt(A2), C = sqrt(C2);
double ans = (A2 + C2 - B2)/(A*C*2);
if(ans<-1) ans=acos(-1);
else if(ans>1) ans=acos(1);
else ans = acos(ans);
return ans;
}
bool cmp(pt a, pt b){
    return a.x < b.x || (a.x == b.x && a.y < b.y);
}
bool ccw(pt a, pt b, pt c, bool include_collinear=false) {
    int o = orientation(a, b, c);
    return o > 0 || (include_collinear && o == 0);
}
bool cw(pt a, pt b, pt c, bool include_collinear=false) {
    int o = orientation(a, b, c);
    return o < 0 || (include_collinear && o == 0);
}
bool collinear(pt a, pt b, pt c) { return orientation(a, b, c)
    == 0; }
double area(pt a, pt b, pt c){
    return (a.x*(b.y-c.y)+b.x*(c.y-a.y)+c.x*(a.y-b.y))/2;
}
struct cmp_x{
    bool operator()(const pt & a, const pt & b) const{
        return a.x < b.x || (a.x == b.x && a.y < b.y);
    }
};
struct cmp_y{
    bool operator()(const pt & a, const pt & b) const{
        return a.y < b.y || (a.y == b.y && a.x < b.x);
    }
};
struct circle : pt {
    ftype r;
};
bool insideCircle(circle c, pt p){
    return dist_sqr(c,p) <= c.r*c.r + EPS;
}
struct line {
    ftype a, b, c;
    line() {}
    line(pt p, pt q){
        a = p.y - q.y;
        b = q.x - p.x;
        c = -a * p.x - b * p.y;
        norm();
    }
    void norm(){
        double z = sqrt(a * a + b * b);
        if (abs(z) > EPS)
            a /= z, b /= z, c /= z;
    }
    line getParallel(pt p){
        line ans = *this;
        ans.c = -(ans.a*p.x+ans.b*p.y);
        return ans;
    }
    ftype getValue(pt p){
        return a*p.x+b*p.y+c;
    }
    line getPerpend(pt p){
        line ans;
        ans.a=this->b;
        ans.b=-(this->a);
        ans.c = -(ans.a*p.x+ans.b*p.y);
        return ans;
    }
    //dist formula is wrong but don't change
    double dist(pt p) const { return a * p.x + b * p.y + c; }
};
double sqr (double a) {
    return a * a;
}
double det(double a, double b, double c, double d) {
    return a*d - b*c;
}

```

```

bool intersect(line m, line n, pt & res) {
    double zn = det(m.a, m.b, n.a, n.b);
    if (abs(zn) < EPS)
        return false;
    res.x = -det(m.c, m.b, n.c, n.b) / zn;
    res.y = -det(m.a, m.c, n.a, n.c) / zn;
    return true;
}

bool parallel(line m, line n) {
    return abs(det(m.a, m.b, n.a, n.b)) < EPS;
}

bool equivalent(line m, line n) {
    return abs(det(m.a, m.b, n.a, n.b)) < EPS
        && abs(det(m.a, m.c, n.a, n.c)) < EPS
        && abs(det(m.b, m.c, n.b, n.c)) < EPS;
}

double det(double a, double b, double c, double d){
    return a * d - b * c;
}

inline bool betw(double l, double r, double x){
    return min(l, r) <= x + EPS && x <= max(l, r) + EPS;
}

inline bool intersect_1d(double a, double b, double c, double d){
    if (a > b)
        swap(a, b);
    if (c > d)
        swap(c, d);
    return max(a, c) <= min(b, d) + EPS;
}

bool intersect_segment(pt a, pt b, pt c, pt d, pt& left, pt& right){
    if (!intersect_1d(a.x, b.x, c.x, d.x) ||
        !intersect_1d(a.y, b.y, c.y, d.y))
        return false;
    line m(a, b);
    line n(c, d);
    double zn = det(m.a, m.b, n.a, n.b);
    if (abs(zn) < EPS) {
        if (abs(m.dist(c)) > EPS || abs(n.dist(a)) > EPS)
            return false;
        if (b < a)
            swap(a, b);
        if (d < c)
            swap(c, d);
        left = max(a, c);
        right = min(b, d);
        return true;
    } else {
        left.x = right.x = -det(m.c, m.b, n.c, n.b) / zn;
        left.y = right.y = -det(m.a, m.c, n.a, n.c) / zn;
        return betw(a.x, b.x, left.x) && betw(a.y, b.y, left.y)
            && betw(c.x, d.x, left.x) && betw(c.y, d.y, left.y);
    }
}

void tangents (pt c, double r1, double r2, vector<line> & ans)
{
    double r = r2 - r1;
    double z = sqrt(c.x) + sqrt(c.y);
    double d = z - sqrt(r);
    if (d < -EPS) return;
    d = sqrt (abs (d));
    line l;
    l.a = (c.x * r + c.y * d) / z;
    l.b = (c.y * r - c.x * d) / z;
    l.c = r1;
    ans.push_back (l);
}

vector<line> tangents (circle a, circle b) {
    vector<line> ans;
    for (int i=-1; i<=1; i+=2)
        for (int j=-1; j<=1; j+=2)
            tangents (b-a, a.r*i, b.r*j, ans);
    for (size_t i=0; i<ans.size(); ++i)
        ans[i].c -= ans[i].a * a.x + ans[i].b * a.y;
    return ans;
}

class pointLocationInPolygon{

```

```

    bool lexComp(const pt & l, const pt & r){
        return l.x < r.x || (l.x == r.x && l.y < r.y);
    }
    int sgn(ftype val){
        return val > 0 ? 1 : (val == 0 ? 0 : -1);
    }
    vector<pt> seq;
    int n;
    pt translate;
    bool pointInTriangle(pt a, pt b, pt c, pt point){
        ftype s1 = abs(a.cross(b, c));
        ftype s2 = abs(point.cross(a, b)) + abs(point.cross(b, c)) + abs(point.cross(c, a));
        return s1 == s2;
    }
public:
    pointLocationInPolygon(){
    }
    pointLocationInPolygon(vector<pt> & points){
        prepare(points);
    }
    void prepare(vector<pt> & points){
        seq.clear();
        n = points.size();
        int pos = 0;
        for(int i = 1; i < n; i++){
            if(lexComp(points[i], points[pos]))
                pos = i;
        }
        translate.x=points[pos].x;
        translate.y=points[pos].y;
        rotate(points.begin(), points.begin() + pos, points.end());
        n--;
        seq.resize(n);
        for(int i = 0; i < n; i++)
            seq[i] = points[i + 1] - points[0];
    }
    bool pointInConvexPolygon(pt point){
        point.x-=translate.x;
        point.y-=translate.y;
        if(seq[0].cross(point) != 0 && sgn(seq[0].cross(point))
            != sgn(seq[0].cross(seq[n - 1])))
            return false;
        if(seq[n - 1].cross(point) != 0 && sgn(seq[n - 1].cross(point))
            != sgn(seq[n - 1].cross(seq[0])))
            return false;
        if(seq[0].cross(point) == 0)
            return seq[0].sqrLen() >= point.sqrLen();
        int l = 0, r = n - 1;
        while(r - l > 1){
            int mid = (l + r)/2;
            int pos = mid;
            if(seq[pos].cross(point) >= 0) l = mid;
            else r = mid;
        }
        int pos = l;
        return pointInTriangle(seq[pos], seq[pos + 1], pt(0, 0), point);
    }
    ~pointLocationInPolygon(){
        seq.clear();
    }
}

class Minkowski{
    static void reorder_polygon(vector<pt> & P){
        size_t pos = 0;
        for(size_t i = 1; i < P.size(); i++){
            if(P[i].y < P[pos].y || (P[i].y == P[pos].y && P[i].x < P[pos].x))
                pos = i;
        }
        rotate(P.begin(), P.begin() + pos, P.end());
    }
public:
    static vector<pt> minkowski(vector<pt> P, vector<pt> Q){
        // the first vertex must be the lowest
        reorder_polygon(P);
        reorder_polygon(Q);
    }

```

```

        // we must ensure cyclic indexing
        P.push_back(P[0]);
        P.push_back(P[1]);
        Q.push_back(Q[0]);
        Q.push_back(Q[1]);
        // main part
        vector<pt> result;
        size_t i = 0, j = 0;
        while(i < P.size() - 2 || j < Q.size() - 2){
            result.push_back(P[i] + Q[j]);
            auto cross = (P[i + 1] - P[i]).cross(Q[j + 1] - Q[j]);
            if(cross >= 0)
                ++i;
            if(cross <= 0)
                ++j;
        }
        return result;
    }
};

vector<pt> circle_line_intersections(circle cir, line l){
    double r = cir.r, a = l.a, b = l.b, c = l.c + l.a*cir.x + l.b*cir.y;
    vector<pt> ans;
    double x0 = -a*c/(a*a+b*b), y0 = -b*c/(a*a+b*b);
    if (c*c > r*r*(a*a+b*b)+EPS);
    else if (abs (c*c - r*r*(a*a+b*b)) < EPS){
        pt p;
        p.x=x0;
        p.y=y0;
        ans.push_back(p);
    }
    else{
        double d = r*r - c*c/(a*a+b*b);
        double mult = sqrt (d / (a*a+b*b));
        double ax, ay, bx, by;
        ax = x0 + b * mult;
        bx = x0 - b * mult;
        ay = y0 - a * mult;
        by = y0 + a * mult;
        pt p;
        p.x = ax;
        p.y = ay;
        ans.push_back(p);
        p.x = bx;
        p.y = by;
        ans.push_back(p);
    }
    for(int i=0; i<ans.size(); i++){
        ans[i] = ans[i] + cir;
    }
    return ans;
}

double circle_polygon_intersection(circle c, vector<pt> &V){
    int n = V.size();
    double ans = 0;
    for(int i=0; i<n; i++){
        line l(V[i], V[(i+1)%n]);
        vector<pt> lpts = circle_line_intersections(c, l);
        int sz=lpts.size();
        for(int j=sz-1; j>=0; j--){
            if(!is_point_on_seg(V[i], V[(i+1)%n], lpts[j])){
                swap(lpts.back(), lpts[j]);
                lpts.pop_back();
            }
        }
        lpts.push_back(V[i]);
        lpts.push_back(V[(i+1)%n]);
        sort(lpts.begin(), lpts.end());
        sz=lpts.size();
        if(V[(i+1)%n]<V[i])
            reverse(lpts.begin(), lpts.end());
        for(int j=1; j<sz; j++){
            if(insideCircle(c, lpts[j-1])
                && insideCircle(c, lpts[j]))
                ans = ans + area(lpts[j-1], lpts[j], c);
            else{
                double ang = angle(lpts[j-1], c, lpts[j]);
                double aa = c.r*c.r*ang/2;
                if(ccw(lpts[j-1], lpts[j], c))

```

```

        ans = ans+aa;
    else
        ans = ans-aa;
    }
}
ans = abs(ans);
return ans;
}

void convex_hull(vector<pt>& a, bool include_collinear = false) {
    pt p0 = *min_element(a.begin(), a.end(), [](pt a, pt b) {
        return make_pair(a.y, a.x) < make_pair(b.y, b.x);
    });
    sort(a.begin(), a.end(), [&p0](const pt& a, const pt& b) {
        int o = orientation(p0, a, b);
        if (o == 0)
            return (p0.x-a.x)*(p0.x-a.x) + (p0.y-a.y)*(p0.y-a.y)
                < (p0.x-b.x)*(p0.x-b.x) + (p0.y-b.y)*(p0.y-b.y);
        return o < 0;
    });
    if (include_collinear) {
        int i = (int)a.size()-1;
        while (i >= 0 && collinear(p0, a[i], a.back())) i--;
        reverse(a.begin()+i+1, a.end());
    }
    vector<pt> st;
    for (int i = 0; i < (int)a.size(); i++) {
        while (st.size() > 1 && !cw[st.size()-2], st.back(),
            a[i], include_collinear))
            st.pop_back();
        st.push_back(a[i]);
    }
    a = st;
    int m = a.size();
    for(int i = 0; i<m-1-i; i++){
        swap(a[i], a[m-1-i]);
    }
}

double mindist;
pair<int, pair<int, int>> best_pair;
void upd_ans(const pt & a, const pt & b, const pt & c){
    double distC = sqrt((a.x - b.x)*(a.x - b.x) + (a.y - b.y)*(a.y - b.y));
    double distA = sqrt((c.x - b.x)*(c.x - b.x) + (c.y - b.y)*(c.y - b.y));
    double distB = sqrt((a.x - c.x)*(a.x - c.x) + (a.y - c.y)*(a.y - c.y));
    if (distA + distB + distC < mindist){
        mindist = distA + distB + distC;
        best_pair = make_pair(a.id, make_pair(b.id, c.id));
    }
}

vector<pt> t;
//Min possible triplet distance
void rec(int l, int r){
    if (r - l <= 3 && r - l >= 2){
        for (int i = l; i < r; ++i){
            for (int j = i + 1; j < r; ++j){
                for (int k = j + 1; k < r; ++k){
                    upd_ans(a[i], a[j], a[k]);
                }
            }
        }
    }
    sort(a.begin() + l, a.begin() + r, cmp_y());
    return;
}

int m = (l + r) >> 1;
int midx = a[m-1].x;
/*
 * Got WA in a team contest
 * for putting midx = a[m].x;
 * Don't know why. Maybe due to
 * floating point numbers.
 */
rec(l, m);
rec(m, r);
merge(a.begin() + l, a.begin() + m, a.begin() + m,
    a.begin() + r, t.begin(), cmp_y());
copy(t.begin(), t.begin() + r - l, a.begin() + l);

```

```

int tsz = 0;
for (int i = l; i < r; ++i){
    if (abs(a[i].x - midx) < mindist/2){
        for (int j = tsz - 1; j >= 0 && a[i].y - t[j].y <
            mindist/2; --j){
            if (i+1<r) upd_ans(a[i], a[i+1], t[j]);
            if (j>0) upd_ans(a[i], t[j-1], t[j]);
        }
        t[tsz++] = a[i];
    }
}
}

```

5.8 intersecting-segments-pair

```

const double EPS = 1E-9;
struct pt {
    double x, y;
};
struct seg {
    pt p, q;
    int id;
    double get_y(double x) const {
        if (abs(p.x - q.x) < EPS)
            return p.y;
        return p.y + (q.y - p.y) * (x - p.x) / (q.x - p.x);
    }
};

bool intersectId(double l1, double r1, double l2, double r2) {
    if (l1 > r1) swap(l1, r1);
    if (l2 > r2) swap(l2, r2);
    return max(l1, l2) <= min(r1, r2) + EPS;
}

int vec(const pt& a, const pt& b, const pt& c) {
    double s = (b.x - a.x) * (c.y - a.y) - (b.y - a.y) * (c.x - a.x);
    return abs(s) < EPS ? 0 : s > 0 ? +1 : -1;
}

bool intersect(const seg& a, const seg& b){
    return intersectId(a.p.x, a.q.x, b.p.x, b.q.x) &&
        intersectId(a.p.y, a.q.y, b.p.y, b.q.y) &&
        vec(a.p, a.q, b.p) * vec(a.p, a.q, b.q) <= 0 &&
        vec(b.p, b.q, a.p) * vec(b.p, b.q, a.q) <= 0;
}

bool operator<(const seg& a, const seg& b){
    double x = max(min(a.p.x, a.q.x), min(b.p.x, b.q.x));
    return a.get_y(x) < b.get_y(x) - EPS;
}

struct event {
    double x;
    int tp, id;
    event() {}
    event(double x, int tp, int id) : x(x), tp(tp), id(id) {}
    bool operator<(const event& e) const {
        if (abs(x - e.x) > EPS)
            return x < e.x;
        return tp > e.tp;
    }
};

set<seg> s;
vector<set<seg>::iterator> where;
set<seg>::iterator prev(set<seg>::iterator it) {
    return it == s.begin() ? s.end() : --it;
}

set<seg>::iterator next(set<seg>::iterator it) {
    return ++it;
}

pair<int, int> solve(const vector<seg>& a) {
    int n = (int)a.size();
    vector<event> e;
    for (int i = 0; i < n; ++i) {
        e.push_back(event(min(a[i].p.x, a[i].q.x), +1, i));
        e.push_back(event(max(a[i].p.x, a[i].q.x), -1, i));
    }
    sort(e.begin(), e.end());
    s.clear();
    where.resize(a.size());
}

```

```

for (size_t i = 0; i < e.size(); ++i) {
    int id = e[i].id;
    if (e[i].tp == +1) {
        set<seg>::iterator nxt = s.lower_bound(a[id]), prv = prev(nxt);
        if (nxt != s.end() && intersect(*nxt, a[id]))
            return make_pair(nxt->id, id);
        if (prv != s.end() && intersect(*prv, a[id]))
            return make_pair(prv->id, id);
        where[id] = s.insert(nxt, a[id]);
    } else {
        set<seg>::iterator nxt = next(where[id]), prv = prev(where[id]);
        if (nxt != s.end() && prv != s.end() && intersect(*nxt, *prv))
            return make_pair(prv->id, nxt->id);
        s.erase(where[id]);
    }
    return make_pair(-1, -1);
}
}

```

5.9 radiant-geo

```

typedef double Tf; typedef double Ti;
const Tf PI = acos(-1), EPS = 1e-9;
int dcmp(Tf x) {return abs(x)<EPS? 0 : (x<0?-1:1);}
struct PT {
    Ti x, y;
    bool operator == (const PT& u) const {
        return dcmp(x-u.x)==0 && dcmp(y-u.y)==0;
    }
    bool operator != (const PT& u) const {
        return !(*this == u);
    }
    friend istream &operator >> (istream &is, PT &p) {
        return is >> p.x >> p.y;
    }
    friend ostream &operator << (ostream &os, const PT &p) {return os<<p.x<<" "<<p.y; }
};

Ti dot(PT a, PT b) { return a.x*b.x + a.y*b.y; }
Ti cross(PT a, PT b) { return a.x*b.y - a.y*b.x; }
Tf length(PT a) { return sqrt(dot(a, a)); }
Ti sqLength(PT a) { return dot(a, a); }
Tf distance(PT a, PT b) {return length(a-b);}
Tf angle(PT u) { return atan2(u.y, u.x); }
Tf angleBetween(PT a, PT b) { //in range [-PI, PI]
    Tf ans = angle(b) - angle(a);
    return ans <= -PI ? ans + 2*PI :
        (ans > PI ? ans - 2*PI : ans);
}

PT rotate(PT a, Tf rad) {
    static_assert(is_same<Tf, Ti>::value);
    return PT(a.x * cos(rad) - a.y * sin(rad),
        a.x * sin(rad) + a.y * cos(rad));
}

// Rotate(a, rad) where cos(rad)=co, sin(rad)=si
PT rotatePrecise(PT a, Tf co, Tf si) {
    static_assert(is_same<Tf, Ti>::value);
    return PT(a.x*co - a.y*si, a.y*co + a.x*si);
}

PT rotate90(PT a) { return PT(-a.y, a.x); }
PT scale(PT a, Tf s) {
    static_assert(is_same<Tf, Ti>::value);
    return a / length(a) * s;
}

PT normal(PT a) {
    static_assert(is_same<Tf, Ti>::value);
    Tf l = length(a); return PT(-a.y / l, a.x / l);
}

// returns 1/0/-1 if c is left/on/right of ab
int orient(PT a, PT b, PT c) {
    return dcmp(cross(b - a, c - a));
}

//sort(v.begin(), v.end(), polarComp(0, dir))
struct polarComp {
    PT O, dir;
    polarComp(PT O = PT(0, 0), PT dir = PT(1, 0))
        : O(O), dir(dir) {}
    bool half(PT p) {

```

```

    return dcmp(cross(dir, p)) < 0 ||
    (dcmp(cross(dir, p)) == 0 && dcmp(dot(dir, p)) > 0);
}
bool operator()(PT p, PT q) {
    return make_tuple(half(p-0), 0) <
    make_tuple(half(q-0), cross(p-0, q-0));
}
};
struct Segment {
    PT a, b;
    Segment() {}
    Segment(PT aa, PT bb) : a(aa), b(bb) {}
};
typedef Segment Line;
struct Circle {
    PT o; Tf r;
    Circle(PT o = PT(0, 0), Tf r = 0) : o(o), r(r) {}
    bool contains(PT p) {
        return dcmp(sqrLength(p - o) - r * r) <= 0;
    }
    PT point(Tf rad) {
        static_assert(is_same<Tf, Ti>::value);
        return PT(o.x + cos(rad)*r, o.y + sin(rad)*r);
    }
    Tf area(Tf rad = PI + PI) { return rad * r * r / 2; }
    Tf sector(Tf alpha) {
        return r * r * 0.5 * (alpha - sin(alpha));
    }
};
#####
namespace Linear {
bool onSegment(PT p, Segment s) { //Is p on S?
    return dcmp(cross(s.a - p, s.b - p)) == 0 &&
    dcmp(dot(s.a - p, s.b - p)) <= 0;
}
bool segmentsIntersect(Segment p, Segment q) {
    if(onSegment(p.a,q)||onSegment(p.b,q))return 1;
    if(onSegment(q.a,p)||onSegment(q.b,p))return 1;
    Ti c1 = cross(p.b - p.a, q.a - p.a);
    Ti c2 = cross(p.b - p.a, q.b - p.a);
    Ti c3 = cross(q.b - q.a, p.a - q.a);
    Ti c4 = cross(q.b - q.a, p.b - q.a);
    return dcmp(c1)*dcmp(c2)<0&&dcmp(c3)*dcmp(c4)<0;
}
bool linesParallel(Line p, Line q) {
    return dcmp(cross(p.b - p.a, q.b - q.a)) == 0;
}
//returns if lines (p, p+v) && (q, q+w) intersect
bool lineLineIntersect(PT p, PT v, PT q, PT w, PT&o) {
    static_assert(is_same<Tf, Ti>::value);
    if(dcmp(cross(v, w)) == 0) return false;
    PT u = p - q; o = p + v * (cross(w, u) / cross(v, w));
    return true;
}
bool lineLineIntersect(Line p, Line q, PT& o) {
    return lineLineIntersect(p.a, p.b - p.a, q.a,
    q.b - q.a, o);
}
Tf distancePointLine(PT p, Line l) {
    return abs(cross(l.b-l.a, p-l.a)/length(l.b-l.a));
}
Tf distancePointSegment(PT p, Segment s) {
    if(s.a == s.b) return length(p - s.a);
    PT v1 = s.b - s.a, v2 = p - s.a, v3 = p - s.b;
    if(dcmp(dot(v1, v2)) < 0) return length(v2);
    else if(dcmp(dot(v1, v3)) > 0) return length(v3);
    else return abs(cross(v1, v2) / length(v1));
}
Tf distanceSegmentSegment(Segment p, Segment q) {
    if(segmentsIntersect(p, q)) return 0;
    Tf ans = distancePointSegment(p.a, q);
    ans = min(ans, distancePointSegment(p.b, q));
    ans = min(ans, distancePointSegment(q.a, p));
    ans = min(ans, distancePointSegment(q.b, p));
    return ans;
}
PT projectPointLine(PT p, Line l) {
    static_assert(is_same<Tf, Ti>::value);
    PT v = l.b - l.a;
    return l.a + v * ((Tf) dot(v, p-l.a)/dot(v, v));
}
}

```

```

} } // namespace Linear
#####
typedef vector<PT> Polygon;
namespace Polygonal {
// cannot be all collinear
Polygon RemoveCollinear(const Polygon& poly) {
    Polygon ret;
    int n = poly.size();
    for(int i = 0; i < n; i++) {
        PT a = poly[i];
        PT b = poly[(i + 1) % n];
        PT c = poly[(i + 2) % n];
        if(dcmp(cross(b-a, c-b)) != 0 && (ret.empty() ||
        b != ret.back())) ret.push_back(b);
    }
    return ret;
}
Tf signedPolygonArea(const Polygon& p);
// returns inside = -1, on = 0, outside = 1
int pointInPolygon(const Polygon& p, PT o);
// returns (longest segment, total length)
pair<Tf, Tf> linePolygonIntersection(Line l,
    const Polygon& p) {
    using Linear::lineLineIntersect;
    int n = p.size(); vector<pair<Tf, int>> ev;
    for(int i=0; i<n; ++i) {
        PT a = p[i], b = p[(i+1)%n], z = p[(i-1+n)%n];
        int ora=orient(l.a,l.b,a), orb =
        orient(l.a,l.b,b), orz=orient(l.a,l.b,z);
        if(!ora) {
            Tf d = dot(a - l.a, l.b - l.a);
            if(orz && orb) {
                if(orz != orb) ev.emplace_back(d, 0);
                //else // PT Touch
            } else if(orz) ev.emplace_back(d, orz);
            else if(orb) ev.emplace_back(d, orb);
        } else if(ora == -orb) {
            PT ins;
            lineLineIntersect(l, Line(a, b), ins);
            ev.emplace_back(dot(ins-l.a, l.b-l.a), 0);
        }
    }
    sort(ev.begin(), ev.end());
    Tf ans = 0, len = 0, last = 0, tot = 0;
    bool active = false; int sign = 0;
    for(auto &qq : ev) {
        int tp = qq.second;
        Tf d = qq.first; //current Seg is (last, d)
        if(sign) { //On Border
            len+=d-last; tot+=d-last; ans=max(ans,len);
            if(tp != sign) active = !active;
            sign = 0;
        } else {
            if(active) { //Strictly Inside
                len+=d-last; tot+=d-last; ans=max(ans,len);
            }
            if(tp == 0) active=!active; else sign = tp;
        }
        last = d; if(!active) len = 0;
    }
    ans /= length(l.b-l.a); tot /= length(l.b-l.a);
    return {ans, tot};
} } // namespace Polygonal
#####
namespace Convex {
//[min area, min perimeter] rectangle containing p
pair<Tf,Tf>rotatingCalipersBBBox(const Polygon&p){
    using Linear::distancePointLine;
    static_assert(is_same<Tf, Ti>::value);
    int n = p.size(); int l = 1, r = 1, j = 1;
    Tf area = 1e100; Tf perimeter = 1e100;
    for(int i = 0; i < n; i++) {
        PT v=(p[(i+1)%n]-p[i])/length(p[(i+1)%n]-p[i]);
        while(dcmp(dot(v, p[r%n]-p[i]) -
        dot(v, p[(r+1)%n]-p[i])) < 0) r++;
        while(j < r || dcmp(cross(v, p[j%n]-p[i]) -

```

```

        cross(v, p[(j+1)%n]-p[i])) < 0) j++;
        while(l < j || dcmp(dot(v, p[l%n]-p[i]) -
        dot(v, p[(l+1)%n]-p[i])) > 0) l++;
        Tf w = dot(v, p[r%n]-p[i]) - dot(v, p[l%n]-p[i]);
        Tf h = distancePointLine(p[j%n],
        Line(p[i], p[(i+1)%n]));
        area = min(area, w * h);
        perimeter = min(perimeter, 2 * w + 2 * h);
    }
    return make_pair(area, perimeter);
}
// returns the left half of u on left on ray ab
Polygon cutPolygon(Polygon u, PT a, PT b) {
    using Linear::lineLineIntersect;
    using Linear::onSegment;
    Polygon ret; int n = u.size();
    for(int i = 0; i < n; i++) {
        PT c = u[i], d = u[(i + 1) % n];
        if(dcmp(cross(b-a, c-a)) >= 0) ret.push_back(c);
        if(dcmp(cross(b-a, d-c)) != 0) {
            PT t; lineLineIntersect(a, b-a, c, d-c, t);
            if(onSegment(t, Segment(c, d))) ret.push_back(t);
        }
    }
    return ret;
}
bool pointInTriangle(PT a, PT b, PT c, PT p) {
    return dcmp(cross(b - a, p - a)) >= 0
    && dcmp(cross(c - b, p - b)) >= 0
    && dcmp(cross(a - c, p - c)) >= 0;
}
int pointInConvexPolygon(const Polygon& p, PT p);
// most extreme Point in the direction u
int extremePoint(const Polygon& poly, PT u) {
    int n = (int) poly.size();
    int a = 0, b = n;
    while(b - a > 1) {
        int c = (a + b) / 2;
        if(dcmp(dot(poly[c]-poly[(c+1)%n], u)) >= 0 &&
        dcmp(dot(poly[c]-poly[(c-1+n)%n], u)) >= 0) {
            return c;
        }
        bool a_up=dcmp(dot(poly[(a+1)%n]-poly[a],u))>=0;
        bool c_up=dcmp(dot(poly[(c+1)%n]-poly[c],u))>=0;
        bool a_above_c=dcmp(dot(poly[a]-poly[c],u))>0;
        if(a_up && !c_up) b = c;
        else if(!a_up && c_up) a = c;
        else if(a_up && c_up) {
            if(a_above_c) b = c; else a = c;
        } else {
            if(!a_above_c) b = c; else a = c;
        }
    }
    if(dcmp(dot(poly[a]-poly[(a+1)%n],u))>0 &&
    dcmp(dot(poly[a]-poly[(a-1+n)%n],u))>0)
        return a;
    return b % n;
}
// return list of segs of p that touch/intersect l
// the i'th segment is [p[i], p[(i + 1)%p]]
// #1 If a side is collinear, only that returned
// #2 If l goes through p[i], ith segment is added
vector<int> lineConvexPolyIntersection(
    const Polygon& p, Line l) {
    assert((int) p.size() >= 3); assert(l.a != l.b);
    int n = p.size(); vector<int> ret;
    PT v = l.b - l.a;
    int lf = extremePoint(p, rotate90(v));
    int rt = extremePoint(p, rotate90(v) * Ti(-1));
    int olf = orient(l.a, l.b, p[lf]);
    int ort = orient(l.a, l.b, p[rt]);
    if(!olf || !ort) {
        int idx = (!olf ? lf : rt);
        if(orient(l.a, l.b, p[(idx - 1 + n) % n]) == 0)
            ret.push_back((idx - 1 + n) % n);
        else ret.push_back(idx);
        return ret;
    }
    if(olf == ort) return ret;
}

```



```

for(int i=0; i<2; ++i) {
    int lo = i ? rt : lf, hi = i ? lf : rt;
    int olo = i ? ort : olf;
    while(true) {
        int gap = (hi - lo + n) % n;
        if(gap < 2) break;
        int mid = (lo + gap / 2) % n;
        int omid = orient(l.a, l.b, p[mid]);
        if(!omid) {lo = mid; break;}
        if(omid == olo) lo = mid;
        else hi = mid;
    } ret.push_back(lo);
} return ret;
}

// [ACW, CW] tangent pair from an external point
constexpr int CW = -1, ACW = 1;
bool isGood(PT u, PT v, PT Q, int dir) {
    return orient(Q, u, v) != -dir;
}
PT better(PT u, PT v, PT Q, int dir) {
    return orient(Q, u, v) == dir ? u : v;
}
PT pointPolyTangent(const Polygon &pt, PT Q,
                    int dir, int lo, int hi) {
    while(hi - lo > 1) {
        int mid = (lo + hi) / 2;
        bool pvs = isGood(pt[mid], pt[mid-1], Q, dir);
        bool nxt = isGood(pt[mid], pt[mid+1], Q, dir);
        if(pvs && nxt) return pt[mid];
        if(!(pvs || nxt)) {
            PT p1 = pointPolyTangent(pt, Q, dir, mid+1, hi);
            PT p2 = pointPolyTangent(pt, Q, dir, lo, mid-1);
            return better(p1, p2, Q, dir);
        }
        if(!pvs) {
            if(orient(Q, pt[mid], pt[lo]) == dir) hi = mid-1;
            else if(better(pt[lo], pt[hi], Q, dir) == pt[lo])
                hi = mid - 1; else lo = mid + 1;
        }
        if(!nxt) {
            if(orient(Q, pt[mid], pt[lo]) == dir) lo = mid+1;
            else if(better(pt[lo], pt[hi], Q, dir) == pt[lo])
                hi = mid - 1; else lo = mid + 1;
        }
    }
    PT ret = pt[lo];
    for(int i = lo + 1; i <= hi; i++)
        ret = better(ret, pt[i], Q, dir);
    return ret;
}

// [ACW, CW] Tangent
pair<PT, PT> pointPolyTangents(
    const Polygon &pt, PT Q) {
    int n = pt.size();
    PT acw_tan = pointPolyTangent(pt, Q, ACW, 0, n-1);
    PT cw_tan = pointPolyTangent(pt, Q, CW, 0, n-1);
    return make_pair(acw_tan, cw_tan);
}

namespace Circular {
// returns intersections in order of ray (l.a, l.b)
vector<PT> circleLineIntersection(Circle c, Line l) {
    static_assert(is_same<Tf, Ti>::value);
    vector<PT> ret;
    PT b = l.b - l.a, a = l.a - c.o;
    Tf A = dot(b, b), B = dot(a, b);
    Tf C = dot(a, a) - c.r * c.r, D = B*B - A*C;
    if(D < -EPS) return ret;
    ret.push_back(l.a + b * (-B - sqrt(D + EPS)) / A);
    if(D > EPS)
        ret.push_back(l.a + b * (-B + sqrt(D)) / A);
    return ret;
}

// circle(c.o, c.r) x triangle(c.o, s.a, s.b) (ccw)
Tf circleTriInterArea(Circle c, Segment s) {
    using Linear::distancePointSegment;
    Tf OA = length(c.o - s.a), OB = length(c.o - s.b);
    if(dcmp(distancePointSegment(c.o, s) - c.r) >= 0)
        return angleBetween(s.a - c.o, s.b - c.o) * c.r * c.r / 2;
    if(dcmp(OA - c.r) <= 0 && dcmp(OB - c.r) <= 0)
        return cross(c.o - s.b, s.a - s.b) / 2.0;
}

vector<PT> Sect = circleLineIntersection(c, s);
return circleTriInterArea(c, Segment(s.a, Sect[0]))
    + circleTriInterArea(c, Segment(Sect[0], Sect[1]))
    + circleTriInterArea(c, Segment(Sect[1], s.b));
}

Tf circlePolyIntersectionArea(Circle c, Polygon p);
// locates circle c2 relative to c1: intersect = 0
// inside = -2, inside touch = -1,
// outside touch = 1, outside = 2
int circleCirclePosition(Circle c1, Circle c2) {
    Tf d = length(c1.o - c2.o);
    int in = dcmp(d - abs(c1.r - c2.r)),
        ex = dcmp(d - (c1.r + c2.r));
    return in<0?-2:in==0?-1:ex==0?1:ex>0?2:0;
}

vector<PT> circleCircleInter(Circle c1, Circle c2) {
    static_assert(is_same<Tf, Ti>::value);
    vector<PT> ret;
    Tf d = length(c1.o - c2.o);
    if(dcmp(d) == 0) return ret;
    if(dcmp(c1.r + c2.r - d) < 0) return ret;
    if(dcmp(abs(c1.r - c2.r) - d) > 0) return ret;
    PT v = c2.o - c1.o;
    Tf co = (c1.r * c1.r + sqLength(v) - c2.r*c2.r)
        / (2 * c1.r * length(v));
    Tf si = sqrt(abs(1.0 - co * co));
    PT p1 = scale(rotatePrecise(v, co, -si), c1.r) + c1.o;
    PT p2 = scale(rotatePrecise(v, co, si), c1.r) + c1.o;
    ret.push_back(p1);
    if(p1 != p2) ret.push_back(p2); return ret;
}

Tf circleCircleInterArea(Circle c1, Circle c2) {
    PT AB = c2.o - c1.o; Tf d = length(AB);
    if(d >= c1.r + c2.r) return 0;
    if(d + c1.r <= c2.r) return PI * c1.r * c1.r;
    if(d + c2.r <= c1.r) return PI * c2.r * c2.r;
    Tf alpha1 = acos((c1.r*c1.r + d*d - c2.r*c2.r)
        / (2.0 * c1.r * d));
    Tf alpha2 = acos((c2.r*c2.r + d*d - c1.r*c1.r)
        / (2.0 * c2.r * d));
    return c1.sector(2*alpha1) + c2.sector(2*alpha2);
}

// returns tangents from a point p to circle c
vector<PT> pointCircleTangents(PT p, Circle c) {
    static_assert(is_same<Tf, Ti>::value);
    vector<PT> ret; PT u = c.o - p; Tf d = length(u);
    if(d < c.r) return ret;
    else if(dcmp(d - c.r) == 0) {
        ret = { rotate(u, PI / 2) };
    }
    else {
        Tf ang = asin(c.r / d);
        ret = { rotate(u, -ang), rotate(u, ang) };
    }
    return ret;
}

// returns points on tangents that touches circle c
vector<PT> pointCircleTangencyPoints(PT p, Circle c) {
    static_assert(is_same<Tf, Ti>::value);
    PT u = p - c.o; Tf d = length(u);
    if(d < c.r) return {};
    else if(dcmp(d - c.r) == 0) return {c.o + u};
    else {
        Tf ang = acos(c.r / d); u = u/length(u) * c.r;
        return {c.o + rotate(u, -ang), c.o + rotate(u, ang)};
    }
}

// finds a, b st a[i] on c1, b[i] on c2, Segment
// a[i], b[i] touches c1, c2. if c1, c2 touch at x
// (x, x) is also returned, -1 returned if c1 = c2
int circleCircleTangencyPoints(Circle c1, Circle c2,
    vector<PT> &a, vector<PT> &b) {
    a.clear(), b.clear(); int cnt = 0;
    if(dcmp(c1.r - c2.r) < 0) {swap(c1, c2); swap(a, b);}
    Tf d2 = sqLength(c1.o - c2.o);
    Tf rdif = c1.r - c2.r, rsum = c1.r + c2.r;
    if(dcmp(d2 - rdif * rdif) < 0) return 0;
    if(dcmp(d2) == 0 && dcmp(c1.r - c2.r) == 0) return -1;
    Tf base = angle(c2.o - c1.o);
    if(dcmp(d2 - rdif * rdif) == 0) {
        a.push_back(c1.point(base));
        b.push_back(c2.point(base));
        cnt++; return cnt;
    }
    Tf ang = acos((c1.r - c2.r) / sqrt(d2));
    a.push_back(c1.point(base + ang));
    b.push_back(c2.point(base + ang)); cnt++;
    a.push_back(c1.point(base - ang));
    b.push_back(c2.point(base - ang)); cnt++;
    if(dcmp(d2 - rsum * rsum) == 0) {
        a.push_back(c1.point(base));
        b.push_back(c2.point(PI + base)); cnt++;
    }
    else if(dcmp(d2 - rsum * rsum) > 0) {
        Tf ang = acos((c1.r + c2.r) / sqrt(d2));
        a.push_back(c1.point(base + ang));
        b.push_back(c2.point(PI + base + ang)); cnt++;
        a.push_back(c1.point(base - ang));
        b.push_back(c2.point(PI + base - ang)); cnt++;
    }
    return cnt;
}

// namespace Circular
// returns false if points are collinear
bool inCircle(PT a, PT b, PT c, Circle &p) {
    using Linear::distancePointLine;
    static_assert(is_same<Tf, Ti>::value);
    if(orient(a, b, c) == 0) return false;
    Tf u=length(b-c), v=length(c-a), w=length(a-b);
    p.o = (a * u + b * v + c * w) / (u + v + w);
    p.r = distancePointLine(p.o, Line(a, b));
    return true;
}

// set of points A(x, y) st PA : QA = rp : rq
Circle apolloniusCircle(PT P, PT Q, Tf rp, Tf rq) {
    static_assert(is_same<Tf, Ti>::value);
    rq *= rq; rp *= rp; Tf a=rq-rp; assert(dcmp(a));
    Tf g = (rq*P.x-rp*Q.x)/a, h = (rq*P.y-rp*Q.y)/a;
    Tf c = (rq*P.x*P.x - rp*Q.x*Q.x +
        rq*P.y*P.y - rp*Q.y*Q.y)/a;
    PT o(g, h); Tf R = sqrt(g * g + h * h - c);
    return Circle(o, R);
}

// returns false if points are collinear
bool circumCircle(PT a, PT b, PT c, Circle &p) {
    using Linear::lineLineIntersect;
    if(orient(a, b, c) == 0) return false;
    PT d = (a + b) / 2, e = (a + c) / 2;
    PT vd = rotate90(b - a), ve = rotate90(a - c);
    bool f = lineLineIntersect(d, vd, e, ve, p.o);
    if(f) p.r = length(a - p.o);
    return f;
}

// finds a circle that goes all of p, |p| <= 3.
Circle boundary(const vector<PT> &p) {
    Circle ret; int sz = p.size();
    if(sz == 0) ret.r = 0;
    else if(sz == 1) ret.o = p[0], ret.r = 0;
    else if(sz == 2) ret.o = (p[0] + p[1]) / 2,
        ret.r = length(p[0] - p[1]) / 2;
    else if(!circumCircle(p[0], p[1], p[2], ret))
        ret.r = 0;
    return ret;
}

// Min circle enclosing p[fr....n-1],
// with points in b on the boundary, |b| <= 3.
Circle welzl(const vector<PT> &p,
    int fr, vector<PT> &b) {
    if(fr >= (int) p.size() || b.size() == 3)
        return boundary(b);
    Circle c = welzl(p, fr + 1, b);
    if(!c.contains(p[fr])) {
        b.push_back(p[fr]); c = welzl(p, fr + 1, b);
        b.pop_back();
    }
    return c;
}

// MEC of p, using welzl's algo. amortized O(n).
Circle MEC(vector<PT> p) {

```

```

    random_shuffle(p.begin(), p.end());
    vector<PT> q; return welzl(p, 0, q);
} }
#####
// Given list of segments v, finds a pair (i, j) st
// v[i],v[j] intersects. If none, returns {-1, -1}
namespace IntersectingSegments {
struct Event {
    Tf x; int tp, id;
    bool operator < (const Event &p) const {
        if(dcmp(x-p.x)) return x<p.x; return tp>p.tp;
    }
};
pair<int, int> anyInters(const vector<Segment> &v){
    using Linear::segmentsIntersect;
    static_assert(is_same<Tf, Ti>::value);
    vector<Event> ev;
    for(int i=0; i<v.size(); i++) {
        ev.push_back({min(v[i].a.x, v[i].b.x), +1, i});
        ev.push_back({max(v[i].a.x, v[i].b.x), -1, i});
    }
    sort(ev.begin(), ev.end());
    auto comp = [&v] (int i, int j) {
        Segment p = v[i], q = v[j];
        Tf x=max(min(p.a.x,p.b.x), min(q.a.x, q.b.x));
        auto yvalSegment = [&x](const Line &s) {
            if(dcmp(s.a.x - s.b.x) == 0) return s.a.y;
            return s.a.y + (s.b.y - s.a.y)
                * (x - s.a.x) / (s.b.x - s.a.x);
        };
        return dcmp(yvalSegment(p)-yvalSegment(q))<0;
    };
    multiset<int, decltype(comp)> st(comp);
    typedef decltype(st)::iterator iter;
    auto prev = [&st](iter it) {
        return it == st.begin() ? st.end() : --it;
    };
    auto next = [&st](iter it) {
        return it == st.end() ? st.end() : ++it;
    };
    vector<iter> pos(v.size());
    for(auto &cur : ev) {
        int id = cur.id;
        if(cur.tp == 1) {
            iter nxt = st.lower_bound(id), pre=prev(nxt);
            if(pre != st.end() && segmentsIntersect(
                v[*pre], v[id])) return {*pre, id};
            if(nxt != st.end() && segmentsIntersect(
                v[*nxt], v[id])) return {*nxt, id};
            pos[id] = st.insert(nxt, id);
        }
        else {
            iter nxt=next(pos[id]), pre=prev(pos[id]);
            if(pre != st.end() && nxt != st.end() &&
                segmentsIntersect(v[*pre], v[*nxt]))
                return {*pre, *nxt};
            st.erase(pos[id]);
        }
    }
    return {-1, -1};
} }
#####

```

5.10 trianlge-ear-clipping

```

///O(n^3) v bad brute force implementation,implement better
    algorithm later
template<class T>
int area(pair<T,T>& p1,pair<T,T>& p2,pair<T,T>& p3){
    return
        (p1.first*p2.second+p2.first*p3.second+p3.first*p1.second
        -p1.second*p2.first-p2.second*p3.first-p3.second*p1.first);
}
template<class T>
bool inside(pair<T,T>& a,pair<T,T>& b,pair<T,T>& c,pair<T,T>&
    p)
{
    int ar=abs(area(a,b,c));
    int t=abs(area(a,b,p))+abs(area(b,c,p))+abs(area(c,a,p));
}

```

```

    return ar==t;
}
template<class T>
void triangulate(vector<pair<T,T> > p,vector<pair<T,T> >&out)
{
    int pindx=0;
    if((int)p.size()<=3)
    {
        out.resize(p.size());
        copy(p.begin(),p.end(),out.begin());
        return;
    }
    while(p.size()>3)
    {
        int n=(int)p.size();
        int i,j,k;
        for(i=0;i<n;i++)
        {
            j=i+1;
            k=i+2;
            j=j>=n?j-n:j;
            k=k>=n?k-n:k;
            if(area(p[i],p[j],p[k])<0)
            {
                continue;
            }
            bool chk=true;
            for(int l=0;l<n;l++)
            {
                if(l==i||l==j||l==k)
                    continue;
                if(inside(p[i],p[j],p[k],p[l]))
                {
                    chk=false;
                    break;
                }
            }
            if(chk)
                break;
        }
        out[pindx++]=p[i];
        out[pindx++]=p[j];
        out[pindx++]=p[k];
        p.erase(p.begin()+j);
    }
    for(auto e:p)
        out[pindx++]=e;
}

```

5.11 vertical-decomposition

```

typedef double dbl;
const dbl eps = 1e-9;
inline bool eq(dbl x, dbl y){
    return fabs(x - y) < eps;
}
inline bool lt(dbl x, dbl y){
    return x < y - eps;
}
inline bool gt(dbl x, dbl y){
    return x > y + eps;
}
inline bool le(dbl x, dbl y){
    return x < y + eps;
}
inline bool ge(dbl x, dbl y){
    return x > y - eps;
}
struct pt{
    dbl x, y;
    inline pt operator - (const pt & p)const{
        return pt{x - p.x, y - p.y};
    }
    inline pt operator + (const pt & p)const{
        return pt{x + p.x, y + p.y};
    }
    inline pt operator * (dbl a)const{
        return pt{x * a, y * a};
    }
    inline dbl cross(const pt & p)const{

```

```

        return x * p.y - y * p.x;
    }
    inline dbl dot(const pt & p)const{
        return x * p.x + y * p.y;
    }
    inline bool operator == (const pt & p)const{
        return eq(x, p.x) && eq(y, p.y);
    }
};
struct Line{
    pt p[2];
    Line(){
        Line(pt a, pt b):p{a, b}{}
    }
    pt vec()const{
        return p[1] - p[0];
    }
    pt& operator [] (size_t i){
        return p[i];
    }
};
inline bool lexComp(const pt & l, const pt & r){
    if(fabs(l.x - r.x) > eps){
        return l.x < r.x;
    }
    else return l.y < r.y;
}
vector<pt> interSegSeg(Line l1, Line l2){
    if(eq(l1.vec().cross(l2.vec()), 0)){
        if(!eq(l1.vec().cross(l2[0] - l1[0]), 0))
            return {};
        if(!lexComp(l1[0], l1[1]))
            swap(l1[0], l1[1]);
        if(!lexComp(l2[0], l2[1]))
            swap(l2[0], l2[1]);
        pt l = lexComp(l1[0], l2[0]) ? l2[0] : l1[0];
        pt r = lexComp(l1[1], l2[1]) ? l1[1] : l2[1];
        if(l == r)
            return {l};
        else return lexComp(l, r) ? vector<pt>{l, r} :
            vector<pt>{};
    }
    else{
        dbl s = (l2[0] - l1[0]).cross(l2.vec()) /
            l1.vec().cross(l2.vec());
        pt inter = l1[0] + l1.vec() * s;
        if(ge(s, 0) && le(s, 1) && le((l2[0] - inter).dot(l2[1]
            - inter), 0))
            return {inter};
        else
            return {};
    }
}
inline char get_segtype(Line segment, pt other_point){
    if(eq(segment[0].x, segment[1].x))
        return 0;
    if(!lexComp(segment[0], segment[1]))
        swap(segment[0], segment[1]);
    return (segment[1] - segment[0]).cross(other_point -
        segment[0]) > 0 ? 1 : -1;
}
dbl union_area(vector<tuple<pt, pt, pt> > triangles){
    vector<Line> segments(3 * triangles.size());
    vector<char> segtype(segments.size());
    for(size_t i = 0; i < triangles.size(); i++){
        pt a, b, c;
        tie(a, b, c) = triangles[i];
        segments[3 * i] = lexComp(a, b) ? Line(a, b) : Line(b, a);
        segtype[3 * i] = get_segtype(segments[3 * i], c);
        segments[3 * i + 1] = lexComp(b, c) ? Line(b, c) : Line(c, b);
        segtype[3 * i + 1] = get_segtype(segments[3 * i + 1], a);
        segments[3 * i + 2] = lexComp(c, a) ? Line(c, a) : Line(a, c);
        segtype[3 * i + 2] = get_segtype(segments[3 * i + 2], b);
    }
    vector<dbl> k(segments.size(), b(segments.size()));
    for(size_t i = 0; i < segments.size(); i++){
        if(segtype[i]){
            k[i] = (segments[i][1].y - segments[i][0].y) /

```

```

        (segments[i][1].x - segments[i][0].x);
        b[i] = segments[i][0].y - k[i] * segments[i][0].x;
    }
    dbl ans = 0;
    for(size_t i = 0; i < segments.size(); i++){
        if(!segtype[i])
            continue;
        dbl l = segments[i][0].x, r = segments[i][1].x;
        vector<pair<dbl, int>> evts;
        for(size_t j = 0; j < segments.size(); j++){
            if(!segtype[j] || i == j)
                continue;
            dbl l1 = segments[j][0].x, r1 = segments[j][1].x;
            if(ge(l1, r) || ge(l, r1))
                continue;
            dbl common_l = max(l, l1), common_r = min(r, r1);
            auto pts = interSegSeg(segments[i], segments[j]);
            if(pts.empty()){
                dbl y1 = k[j] * common_l + b[j];
                dbl y2 = k[i] * common_l + b[i];
                if(1e-10 < y1 - y2){
                    int evt_type = -segtype[i] * segtype[j];
                    evts.emplace_back(common_l, evt_type);
                    evts.emplace_back(common_r, -evt_type);
                }
            }
            else if(pts.size() == 1u){
                dbl y1 = k[i] * common_l + b[i], y2 = k[j] * common_l + b[j];
                int evt_type = -segtype[i] * segtype[j];
                if(1e-10 < y1 - y2){
                    evts.emplace_back(common_l, evt_type);
                    evts.emplace_back(common_r, -evt_type);
                }
            }
            y1 = k[i] * common_r + b[i], y2 = k[j] * common_r + b[j];
            if(1e-10 < y1 - y2){
                evts.emplace_back(pts[0].x, evt_type);
                evts.emplace_back(common_r, -evt_type);
            }
        }
        else{
            if(segtype[j] != segtype[i] || j > i){
                evts.emplace_back(common_l, -2);
                evts.emplace_back(common_r, 2);
            }
        }
    }
    evts.emplace_back(1, 0); sort(evts.begin(), evts.end());
    size_t j = 0; int balance = 0;
    while(j < evts.size()){
        size_t ptr = j;
        while(ptr < evts.size() && eq(evts[j].first, evts[ptr].first)){
            balance += evts[ptr].second;
            ++ptr;
        }
        if(!balance && !eq(evts[j].first, r)){
            dbl next_x = ptr == evts.size() ? r : evts[ptr].first;
            ans -= segtype[i] * (k[i] * (next_x + evts[j].first) + 2 * b[i]) * (next_x - evts[j].first);
        }
        j = ptr;
    }
    return ans/2;
}
pair<dbl,dbl> union_perimeter(vector<tuple<pt, pt, pt>> triangles){
    //Same as before
    pair<dbl,dbl> ans = make_pair(0,0);
    for(size_t i = 0; i < segments.size(); i++){
        //Same as before
        double dist=(segments[i][1].x-segments[i][0].x)
            *(segments[i][1].x-segments[i][0].x)
            +(segments[i][1].y-segments[i][0].y)
            *(segments[i][1].y-segments[i][0].y);

```

```

        dist=sqrt(dist);
        while(j < evts.size()){
            size_t ptr = j;
            while(ptr < evts.size() && eq(evts[j].first, evts[ptr].first)){
                balance += evts[ptr].second; ++ptr;
            }
            if(!balance && !eq(evts[j].first, r)){
                dbl next_x = ptr == evts.size() ? r : evts[ptr].first;
                ans.first += dist * (next_x - evts[j].first) / (r-1);
                if(eq(segments[i][1].y, segments[i][0].y))
                    ans.second += (next_x - evts[j].first);
            }
            j = ptr;
        }
    }
    return ans;
}

```

6 Graph

6.1 DMST

```

// tested on https://lightoj.com/problem/teleport
const int inf = 1e9;
struct edge {
    int u, v, w;
    edge() {}
    edge(int a, int b, int c) : u(a), v(b), w(c) {}
    bool operator < (const edge& o) const {
        if (u == o.u)
            if (v == o.v) return w < o.w;
            else return v < o.v;
        return u < o.u;
    }
};
int dmst(vector<edge> &edges, int root, int n) {
    int ans = 0;
    int cur_nodes = n;
    while (true) {
        vector<int> lo(cur_nodes, inf), pi(cur_nodes, inf);
        for (int i = 0; i < edges.size(); ++i) {
            int u = edges[i].u, v = edges[i].v, w = edges[i].w;
            if (w < lo[v] and u != v) {
                lo[v] = w;
                pi[v] = u;
            }
        }
        lo[root] = 0;
        for (int i = 0; i < lo.size(); ++i) {
            if (i == root) continue;
            if (lo[i] == inf) return -1;
        }
        int cur_id = 0;
        vector<int> id(cur_nodes, -1), mark(cur_nodes, -1);
        for (int i = 0; i < cur_nodes; ++i) {
            ans += lo[i];
            int u = i;
            while (u != root and id[u] < 0 and mark[u] != i) {
                mark[u] = i;
                u = pi[u];
            }
            if (u != root and id[u] < 0) { // Cycle
                for (int v = pi[u]; v != u; v = pi[v]) id[v] = cur_id;
                id[u] = cur_id++;
            }
        }
        if (cur_id == 0) break;
        for (int i = 0; i < cur_nodes; ++i)
            if (id[i] < 0) id[i] = cur_id++;
        for (int i = 0; i < edges.size(); ++i) {
            int u = edges[i].u, v = edges[i].v, w = edges[i].w;
            edges[i].u = id[u];
            edges[i].v = id[v];
            if (id[u] != id[v]) edges[i].w -= lo[v];
        }
        cur_nodes = cur_id;
    }
}

```

```

        root = id[root];
    }
    return ans;
}

```

6.2 Flow With Demands

Finding an arbitrary flow Consider flow networks, where we additionally require the flow of each edge to have a certain amount, i.e. we bound the flow from below by a **demand** function $d(e)$:

$$d(e) \leq f(e) \leq c(e)$$

So next each edge has a minimal flow value, that we have to pass along the edge.

We make the following changes in the network. We add a new source s' and a new sink t' , a new edge from the source s' to every other vertex, a new edge for every vertex to the sink t' , and one edge from t to s . Additionally we define the new capacity function c' as:

- $c'((s', v)) = \sum_{u \in V} d((u, v))$ for each edge (s', v) .
- $c'((v, t')) = \sum_{w \in V} d((v, w))$ for each edge (v, t') .
- $c'((u, v)) = c((u, v)) - d((u, v))$ for each edge (u, v) in the old network.
- $c'((t, s)) = \infty$

If the new network has a saturating flow (a flow where each edge outgoing from s' is completely filled, which is equivalent to every edge incoming to t' is completely filled), then the network with demands has a valid flow, and the actual flow can be easily reconstructed from the new network. Otherwise there doesn't exist a flow that satisfies all conditions. Since a saturating flow has to be a maximum flow, it can be found by any maximum flow algorithm.

Minimal flow Note that along the edge (t, s) (from the old sink to the old source) with the capacity ∞ flows the entire flow of the corresponding old network. I.e. the capacity of this edge effects the flow value of the old network. By giving this edge a sufficient large capacity (i.e. ∞), the flow of the old network is unlimited. By limiting this edge by smaller capacities, the flow value will decrease. However if we limit this edge by a too small value, than the network will not have a saturated solution, e.g. the corresponding solution for the original network will not satisfy the demand of the edges. Obviously here can use a binary search to find the lowest value with which all constraints are still satisfied. This gives the minimal flow of the original network.

6.3 LCA

```

int n; //beware n is declared global
int bparent[MAXN][LOG], depth[MAXN];
bool vis[MAXN];
void dfs(int a){
    vis[a]=true;
    for(auto v: g[a]){
        if(!vis[v]){
            bparent[v][0]=a;

```

```

        depth[v]=1+depth[a];
        dfs(v);}}
void build_ancestor(){
    dfs(1);
    for(int i=1;(1<i)<n;i++)
        for(int j=1;j<=n;j++)
            bparent[j][i]=bparent[bparent[j][i-1]][i-1];
int pth_ancestor(int a,int p){
    for(int i=0;(1<i)<=p;i++)
        if((1<i)&p) a=bparent[a][i];
    return a;
int lca(int u,int v){
    if(depth[v]>depth[u])
        v=pth_ancestor(v,depth[v]-depth[u]);
    if(depth[u]>depth[v])
        u=pth_ancestor(u,depth[u]-depth[v]);
    if(u==v) return u;
    for(int i=log2(n-1);i>=0;i--){
        if(bparent[u][i]!=bparent[v][i]){
            u=bparent[u][i];
            v=bparent[v][i];}}
    return bparent[u][0];}

```

6.4 articulation-vertex

```

int n; // number of nodes
vector<vector<int>> adj; // adjacency list of graph
vector<bool> visited;
vector<int> tin, low;
int timer;
void dfs(int v, int p = -1) {
    visited[v] = true;
    tin[v] = low[v] = timer++;
    int children=0;
    for (int to : adj[v]) {
        if (to == p) continue;
        if (visited[to]) {
            low[v] = min(low[v], tin[to]);
        } else {
            dfs(to, v);
            low[v] = min(low[v], low[to]);
            if (low[to] >= tin[v] && p!=-1)
                IS_CUTPOINT(v);
            ++children;
        }
    }
    if(p == -1 && children > 1)
        IS_CUTPOINT(v);
}
void find_cutpoints() {
    timer = 0;
    visited.assign(n, false);
    tin.assign(n, -1);
    low.assign(n, -1);
    for (int i = 0; i < n; ++i) {
        if (!visited[i])
            dfs(i);
    }
}

```

6.5 bellman-ford

```

struct Edge {
    int a, b, cost;
};
int n, m;
vector<Edge> edges;
const int INF = 1000000000;
void solve(){
    vector<int> d(n);
    vector<int> p(n, -1);
    int x;
    for (int i = 0; i < n; ++i) {
        x = -1;
        for (Edge e : edges) {
            if (d[e.a] + e.cost < d[e.b]) {
                d[e.b] = d[e.a] + e.cost;
                p[e.b] = e.a;
                x = e.b;
            }
        }
    }
}

```

```

    }
}
if (x == -1) {
    cout << "No negative cycle found.";
} else {
    for (int i = 0; i < n; ++i)
        x = p[x];
    vector<int> cycle;
    for (int v = x; v = p[v]) {
        cycle.push_back(v);
        if (v == x && cycle.size() > 1)
            break;
    }
    reverse(cycle.begin(), cycle.end());
    cout << "Negative cycle: ";
    for (int v : cycle)
        cout << v << ' ';
    cout << endl;
}
}
}

```

6.6 bridge

```

const int vmax = 2e5+10, emax = 2e5+10;
namespace Bridge {///edge, nodes, comps 1 indexed
    vector<int> adj[vmax]; /// edge-id
    pair<int, int> edges[emax]; /// (u, v)
    bool isBridge[emax];
    int visited[vmax]; ///0-unvis,1-vising,2-vis
    int st[vmax], low[vmax], clk = 0, edgeId = 0;
    /// For bridge tree components
    int who[vmax], compId = 0;
    vector<int> stk;
    /// For extra end time calc
    int en[vmax];
    void dfs(int u, int parEdge) {
        visited[u] = 1; low[u] = st[u] = ++clk;
        stk.push_back(u);
        for (auto e : adj[u]) {
            if (e == parEdge) continue;
            int v=edges[e].first^edges[e].second^u;
            if (visited[v] == 1) {
                low[u] = min(low[u], st[v]);
            } else if(visited[v] == 0){
                dfs(v, e); low[u] = min(low[u], low[v]);
            }
        }
        visited[u] = 2;
        if(st[u] == low[u]){/// found
            ++compId; int cur;
            do{
                cur = stk.back(); stk.pop_back();
                who[cur] = compId;
            }while(cur != u);
            if(parEdge != -1){isBridge[parEdge] = true;}
        }
        en[u] = clk;
    }
    void clearAll(int n){
        for(int i = 0; i<=n; i++) {
            adj[i].clear(); visited[i] = st[i] = 0; }
        for(int i = 0; i<=edgeId; i++) isBridge[i]=0;
        clk = compId = edgeId = 0;
    }
    void findBridges(int n){
        for(int i = 1; i<=n; i++){
            if(visited[i] == 0) dfs(i, -1); }
    }
    bool isReplacable(int eid, int u, int v){
        if(!isBridge[eid]) return true;
        int a=edges[eid].first,b=edges[eid].second;
        if(st[a] > st[b]) swap(a, b);
        return (st[b] <= st[u] && st[u] <= en[b])
            != (st[b] <= st[v] && st[v] <= en[b]);
    }
    void addEdge(int u, int v){
        edgeId++; edges[edgeId] = {u, v};
        adj[u].emplace_back(edgeId);
    }
}

```

```
adj[v].emplace_back(edgeId);
}
```

6.7 edmond-blossom

```

/**Copied from https://codeforces.com/blog/entry/49402***/
/*
GETS:
V->number of vertices
E->number of edges
pair of vertices as edges (vertices are 1..V)
GIVES:
output of edmonds() is the maximum matching
match[i] is matched pair of i (-1 if there isn't a matched pair)
*/
const int M=500;
struct struct_edge
{
    int v;
    struct_edge* n;
};
typedef struct_edge* edge;
struct_edge pool[M*M*2];
edge top=pool,adj[M];
int V,E,match[M],qh,qt,q[M],father[M],base[M];
bool inq[M],inb[M],ed[M][M];
void add_edge(int u,int v)
{
    top->v=v,top->n=adj[u],adj[u]=top++;
    top->v=u,top->n=adj[v],adj[v]=top++;
}
int LCA(int root,int u,int v)
{
    static bool inp[M];
    memset(inp,0,sizeof(inp));
    while(1)
    {
        inp[u=base[u]]=true;
        if (u==root) break;
        u=father[match[u]];
    }
    while(1)
    {
        if (inp[v=base[v]]) return v;
        else v=father[match[v]];
    }
}
void mark_blossom(int lca,int u)
{
    while (base[u]!=lca)
    {
        int v=match[u];
        inb[base[u]]=inb[base[v]]=true;
        u=father[v];
        if (base[u]!=lca) father[u]=v;
    }
}
void blossom_contraction(int s,int u,int v)
{
    int lca=LCA(s,u,v);
    memset(inb,0,sizeof(inb));
    mark_blossom(lca,u);
    mark_blossom(lca,v);
    if (base[u]!=lca)
        father[u]=v;
    if (base[v]!=lca)
        father[v]=u;
    for (int u=0; u<V; u++)
        if (inb[base[u]])
        {
            base[u]=lca;
            if (!inq[u])
                inq[q[++qt]=u]=true;
        }
}
int find_augmenting_path(int s)
{
}

```



```

memset(inq,0,sizeof(inq));
memset(father,-1,sizeof(father));
for (int i=0; i<V; i++) base[i]=i;
inq[q[qh=qt=0]=s]=true;
while (qh<=qt)
{
    int u=q[qh++];
    for (edge e=adj[u]; e; e=e->n)
    {
        int v=e->v;
        if (base[u] != base[v] && match[u] != v)
            if ((v==s) || (match[v] != -1 &&
                father[match[v]] != -1))
                blossom_contraction(s,u,v);
            else if (father[v] == -1)
            {
                father[v]=u;
                if (match[v] == -1)
                    return v;
                else if (!inq[match[v]])
                    inq[q[++qt]=match[v]]=true;
            }
    }
}
return -1;
}
int augment_path(int s,int t)
{
    int u=t,v,w;
    while (u!=-1)
    {
        v=father[u];
        w=match[v];
        match[v]=u;
        match[u]=v;
        u=w;
    }
    return t!=-1;
}
int edmonds()//Gives number of matchings
{
    int matchc=0;
    memset(match,-1,sizeof(match));
    for (int u=0; u<V; u++)
        if (match[u] == -1)
            matchc+=augment_path(u,find_augmenting_path(u));
    return matchc;
}
//To add edge add_edge(u-1,v-1);
ed[u-1][v-1]=ed[v-1][u-1]=true;

```

6.8 euler-path

```

class EulerGraph{
public:
    struct Edge{
        int other;
        int oi;
        bool vis;
        Edge(int other, int oi): other(other), oi(oi){
            vis=false;
        };
    };
    vector<vector<Edge>> adj;
    int* cnt;
    bool* sig;
    EulerGraph(int n){
        adj.resize(n);
        cnt=new int[n];
        sig=new bool[n];
        memset(cnt, 0, sizeof(int)*n);
        memset(sig, 0, n);
    }
    void addEdge(int u, int v){
        int un=adj[u].size(), vn=adj[v].size();
        adj[u].eb(v, vn), adj[v].eb(u, un);
    }
    deque<int> getCircuit(int src){
        deque<int> circuit;
        circuit.push_back(src);
        int ecnt=adj[src].size();
        while(ecnt){
            int v=circuit.back();
            sig[v]=true;

```

```

        if(cnt[v]==adj[v].size()){
            circuit.pop_back();
            circuit.push_front(circuit.back());
        }
        else if(adj[v][cnt[v]].vis){
            cnt[v]++;
            ecnt--;
        }
        else {
            int other=adj[v][cnt[v]].other;
            int oi=adj[v][cnt[v]].oi;
            adj[other][oi].vis=true;
            circuit.push_back(other);
            if(!sig[other]) ecnt+=adj[other].size();

            cnt[v]++;
            ecnt--;
        }
        return circuit;
    };
}

```

6.9 hopcraft-karp

```

/** Source: https://iq.opengenus.org/hopcroft-karp-algorithm/
**/
// A class to represent Bipartite graph for
// Hopcroft Karp implementation
class BGraph{
    // m and n are number of vertices on left
    // and right sides of Bipartite Graph
    int m, n;
    // adj[u] stores adjacents of left side
    // vertex 'u'. The value of u ranges from 1 to m.
    // 0 is used for dummy vertex
    std::list<int> *adj;
    // pointers for hopcroftKarp()
    int *pair_u, *pair_v, *dist;
public:
    BGraph(int m, int n); // Constructor
    void addEdge(int u, int v); // To add edge
    // Returns true if there is an augmenting path
    bool bfs();
    // Adds augmenting path if there is one beginning
    // with u
    bool dfs(int u);
    // Returns size of maximum matching
    int hopcroftKarpAlgorithm();
};
// Returns size of maximum matching
int BGraph::hopcroftKarpAlgorithm(){
    // pair_u[u] stores pair of u in matching on left side of
    // Bipartite Graph.
    // If u doesn't have any pair, then pair_u[u] is NIL
    pair_u = new int[m + 1];
    // pair_v[v] stores pair of v in matching on right side of
    // Bipartite Graph.
    // If v doesn't have any pair, then pair_u[v] is NIL
    pair_v = new int[n + 1];
    // dist[u] stores distance of left side vertices
    dist = new int[m + 1];
    // Initialize NIL as pair of all vertices
    for (int u = 0; u <= m; u++)
        pair_u[u] = NIL;
    for (int v = 0; v <= n; v++)
        pair_v[v] = NIL;
    // Initialize result
    int result = 0;
    // Keep updating the result while there is an
    // augmenting path possible.
    while (bfs()){
        // Find a free vertex to check for a matching
        for (int u = 1; u <= m; u++)
            // If current vertex is free and there is
            // an augmenting path from current vertex
            // then increment the result
            if (pair_u[u] == NIL && dfs(u))
                result++;
    }
    return result;
}
// Returns true if there is an augmenting path available, else
// returns false

```

```

bool BGraph::bfs(){
    std::queue<int> q; //an integer queue for bfs
    // First layer of vertices (set distance as 0)
    for (int u = 1; u <= m; u++){
        // If this is a free vertex, add it to queue
        if (pair_u[u] == NIL){
            // u is not matched so distance is 0
            dist[u] = 0;
            q.push(u);
        }
        // Else set distance as infinite so that this vertex is
        // considered next time for availability
        else
            dist[u] = INF;
    }
    // Initialize distance to NIL as infinite
    dist[NIL] = INF;
    // q is going to contain vertices of left side only.
    while (!q.empty()){
        // dequeue a vertex
        int u = q.front();
        q.pop();
        // If this node is not NIL and can provide a shorter
        // path to NIL then
        if (dist[u] < dist[NIL]){
            // Get all the adjacent vertices of the dequeued
            // vertex u
            std::list<int>::iterator it;
            for (it = adj[u].begin(); it != adj[u].end(); ++it){
                int v = *it;
                // If pair of v is not considered so far
                // i.e. (v, pair_v[v]) is not yet explored edge.
                if (dist[pair_v[v]] == INF){
                    // Consider the pair and push it to queue
                    dist[pair_v[v]] = dist[u] + 1;
                    q.push(pair_v[v]);
                }
            }
        }
        // If we could come back to NIL using alternating path of
        // distinct
        // vertices then there is an augmenting path available
        return (dist[NIL] != INF);
    }
    // Returns true if there is an augmenting path beginning with
    // free vertex u
    bool BGraph::dfs(int u){
        if (u != NIL){
            std::list<int>::iterator it;
            for (it = adj[u].begin(); it != adj[u].end(); ++it){
                // Adjacent vertex of u
                int v = *it;
                // Follow the distances set by BFS search
                if (dist[pair_v[v]] == dist[u] + 1){
                    // If dfs for pair of v also return true then
                    // if (dfs(pair_v[v]) == true){ // new matching
                    // possible, store the matching
                    pair_v[v] = u;
                    pair_u[u] = v;
                    return true;
                }
            }
            // If there is no augmenting path beginning with u then.
            dist[u] = INF;
            return false;
        }
        return true;
    }
    // Constructor for initialization
    BGraph::BGraph(int m, int n){
        this->m = m;
        this->n = n;
        adj = new std::list<int>[m + 1];
    }
    // function to add edge from u to v
    void BGraph::addEdge(int u, int v){
        adj[u].push_back(v); // Add v to us list.
    }
}

```

}

6.10 hungarian-algorithm

```

class HungarianAlgorithm{
    int N,inf,n,max_match;
    int *lx,*ly,*xy,*yx,*slack,*slackx,*prev;
    int **cost;
    bool *S,*T;
    void init_labels(){
        for(int x=0;x<n;x++) lx[x]=0;
        for(int y=0;y<n;y++) ly[y]=0;
        for (int x = 0; x < n; x++){
            for (int y = 0; y < n; y++){
                lx[x] = max(lx[x], cost[x][y]);
            }
        }
        void update_labels(){
            int x, y, delta = inf; //init delta as infinity
            for (y = 0; y < n; y++) //calculate delta using slack
                if (!T[y])
                    delta = min(delta, slack[y]);
            for (x = 0; x < n; x++) //update X labels
                if (S[x]) lx[x] -= delta;
            for (y = 0; y < n; y++) //update Y labels
                if (T[y]) ly[y] += delta;
            for (y = 0; y < n; y++) //update slack array
                if (!T[y])
                    slack[y] -= delta;
        }
        void add_to_tree(int x, int prevx)
        //x - current vertex,prevx - vertex from X before x in the
        //alternating path,
        //so we add edges (prevx, xy[x]), (xy[x], x){
            S[x] = true; //add x to S
            prev[x] = prevx; //we need this when augmenting
            for (int y = 0; y < n; y++) //update slacks, because we
            //add new vertex to S
                if (lx[x] + ly[y] - cost[x][y] < slack[y]){
                    slack[y] = lx[x] + ly[y] - cost[x][y];
                    slackx[y] = x;
                }
        }
        void augment() //main function of the algorithm{
            if (max_match == n) return; //check wether matching is
            //already perfect
            int x, y, root; //just counters and root vertex
            int q[N], wr = 0, rd = 0; //q - queue for bfs, wr,rd -
            //write and read
            //pos in queue
            //memset(S, false, sizeof(S)); //init set S
            for(int i=0;i<n;i++) S[i]=false;
            //memset(T, false, sizeof(T)); //init set T
            for(int i=0;i<n;i++) T[i]=false;
            //memset(prev, -1, sizeof(prev)); //init set prev - for
            //the alternating tree
            for(int i=0;i<n;i++) prev[i]=-1;
            for (x = 0; x < n; x++) //finding root of the tree{
                if (xy[x] == -1){
                    q[wr++] = root = x;
                    prev[x] = -2;
                    S[x] = true;
                    break;
                }
            }
            for (y = 0; y < n; y++) //initializing slack array{
                slack[y] = lx[root] + ly[y] - cost[root][y];
                slackx[y] = root;
            }
            while (true) //main cycle{
                while (rd < wr) //building tree with bfs cycle{
                    x = q[rd++]; //current vertex from X part
                    for (y = 0; y < n; y++) //iterate through all
                    //edges in equality graph{
                        if (cost[x][y] == lx[x] + ly[y] && !T[y]){
                            if (yx[y] == -1) break; //an exposed
                            //vertex in Y found, so
                            //augmenting path exists!
                            T[y] = true; //else just add y to T,
                }
            }
        }
    }
}

```

```

        q[wr++] = yx[y]; //add vertex yx[y],
        //which is matched
        //with y, to the queue
        add_to_tree(yx[y], x); //add edges (x,y)
        //and (y,yx[y]) to the tree
    }
    }
    if (y < n) break; //augmenting path found!
}
if (y < n) break; //augmenting path found!
update_labels(); //augmenting path not found, so
//improve labeling
wr = rd = 0;
for (y = 0; y < n; y++){
    //in this cycle we add edges that were added to
    //the equality graph as a
    //result of improving the labeling, we add edge (slackx[y], y)
    //to the tree if
    //and only if !T[y] && slack[y] == 0, also with this edge we
    //add another one
    //(y, yx[y]) or augment the matching, if y was exposed
    if (!T[y] && slack[y] == 0){
        if (yx[y] == -1) //exposed vertex in Y found
            - augmenting path exists!{
                x = slackx[y];
                break;
            }
        else{
            T[y] = true; //else just add y to T,
            if (!S[yx[y]]){
                q[wr++] = yx[y]; //add vertex yx[y],
                //which is matched with
                //y, to the queue
                add_to_tree(yx[y], slackx[y]); //and
                //add edges (x,y) and (y,
                //yx[y]) to the tree
            }
        }
    }
    if (y < n) break; //augmenting path found!
}
if (y < n) //we found augmenting path!{
    max_match++; //increment matching
    //in this cycle we inverse edges along augmenting path
    for (int cx = x, cy = y, ty; cx != -2; cx =
        prev[cx], cy = ty){
        ty = xy[cx];
        yx[cy] = cx;
        xy[cx] = cy;
    }
    augment(); //recall function, go to step 1 of the
    //algorithm
}
} //end of augment() function
public:
HungarianAlgorithm(int vv,int inf=1000000000){
    N=vv;
    n=N;
    max_match=0;
    this->inf=inf;
    lx=new int[N];
    ly=new int[N]; //labels of X and Y parts
    xy=new int[N]; //xy[x] - vertex that is matched with x,
    yx=new int[N]; //yx[y] - vertex that is matched with y
    slack=new int[N]; //as in the algorithm description
    slackx=new int[N]; //slackx[y] such a vertex, that
    //l(slackx[y]) + l(y) - w(slackx[y],y) = slack[y]
    prev=new int[N]; //array for memorizing alternating paths
    S=new bool[N];
    T=new bool[N]; //sets S and T in algorithm
    cost=new int*[N]; //cost matrix
    for(int i=0; i<N; i++){
        cost[i]=new int[N];
    }
}
HungarianAlgorithm(){
    delete []lx;
}

```

```

    delete []ly;
    delete []xy;
    delete []yx;
    delete []slack;
    delete []slackx;
    delete []prev;
    delete []S;
    delete []T;
    int i;
    for(i=0; i<N; i++){
        delete []cost[i];
    }
    delete []cost;
}
void setCost(int i,int j,int c){
    cost[i][j]=c;
}
int* matching(bool first=true){
    int *ans;
    ans=new int[N];
    for(int i=0;i<N;i++){
        if(first) ans[i]=xy[i];
        else ans[i]=yx[i];
    }
    return ans;
}
int hungarian(){
    int ret = 0; //weight of the optimal matching
    max_match = 0; //number of vertices in current matching
    for(int x=0;x<n;x++){ xy[x]=-1;
        for(int y=0;y<n;y++){ yx[y]=-1;
            init_labels(); //step 0
            augment(); //steps 1-3
            for (int x = 0; x < n; x++) //forming answer there
                ret += cost[x][xy[x]];
            return ret;
        }
    }
};

```

6.11 max-flow-dinic

```

namespace Dinic {
    typedef long long LL;
    const int N = 2e4+100, K = 60; const LL INF = 1e18;
    struct Edge { int frm, to; LL cap, flow; };
    int s, t, n, level[N], ptr[N];
    vector<Edge> edges; vector<int> adj[N];
    void init(int nodes) {
        n = nodes; edges.clear();
        for (int i=0; i<n; i++) adj[i].clear();
        //adding undirected edge call addEdge(u,v,c,c);
        int addEdge(int a, int b, LL cap, LL revcap = 0) {
            edges.push_back({a, b, cap, 0});
            edges.push_back({b, a, revcap, 0});
            adj[a].push_back(edges.size()-2);
            adj[b].push_back(edges.size()-1);
            return edges.size()-2;
        }
        bool bfs(LL lim) {
            fill(level, level+n, -1); level[s] = 0;
            queue<int> q; q.push(s);
            while (!q.empty() && level[t] == -1) {
                int v = q.front(); q.pop();
                for (int id: adj[v]) {
                    Edge e = edges[id];
                    if (level[e.to] == -1 && e.cap-e.flow>=lim) {
                        q.push(e.to); level[e.to] = level[v] + 1;
                    }
                }
            }
            return level[t] != -1;
        }
        LL dfs(int v, LL flow) {
            if (v == t || !flow) return flow;
            for (; ptr[v] < adj[v].size(); ptr[v]++) {
                int eid = adj[v][ptr[v]];
                Edge &e = edges[eid];
                if (level[e.to] != level[v] + 1) continue;
                if (LL pushed=dfs(e.to,min(flow,e.cap-e.flow))) {
                    e.flow+=pushed; edges[eid^1].flow -= pushed;
                    return pushed;
                }
            }
            return 0;
        }
        LL maxFlow(int source,int sink,bool SCALING=false){
            s = source, t = sink;
        }
    }
}

```

```

long long flow = 0;
for (LL lim=SCALING?(1LL<<K):1; lim>0; lim>=1){
    while (bfs(lim)) {
        fill(ptr, ptr+n, 0);
        while (LL pushed = dfs(s,INF)) flow+=pushed;
    }
}
return flow;

```

6.12 min-cost-max-flow

```

namespace MCMF {
    typedef long long F; typedef long long C;
    const F infF = 1e18; const C infC = 1e18;
    const int N = 5005;
    typedef pair<C, F> PCF;
    struct Edge {int frm, to; C cost; F cap, flow;};
    int n, s, t;
    vector<Edge> edges;
    vector<int> adj[N];
    C pi[N], dis[N];
    F fl[N];
    int prv[N], vis[N];
    void init(int nodes, int source, int sink) {
        n = nodes, s = source, t = sink;
        for (int i=0; i<n; i++) pi[i] = 0, adj[i].clear();
        edges.clear();
    }
    void addEdge(int u, int v, F cap, C cost) {
        edges.push_back({u, v, cost, cap, 0});
        edges.push_back({v, u, -cost, 0, 0});
        adj[u].push_back(edges.size()-2);
        adj[v].push_back(edges.size()-1);
    }
    bool SPFA() {
        for (int i=0; i<n; i++) {
            dis[i] = infC; fl[i] = 0;
            vis[i] = 0; prv[i] = -1;
        }
        queue<int> q;
        q.push(s);
        dis[s] = 0; fl[s] = infF; vis[s] = 1;
        while (!q.empty()) {
            int u = q.front(); q.pop();
            vis[u] = 0;
            for (int eid : adj[u]) {
                Edge &e = edges[eid];
                if (e.cap == e.flow) continue;
                if (dis[u] + e.cost < dis[e.to]) {
                    dis[e.to] = dis[u] + e.cost;
                    fl[e.to] = min(fl[u], e.cap - e.flow);
                    prv[e.to] = eid+1;
                    if (!vis[e.to]) q.push(e.to);
                }
            }
        }
        return fl[t] > 0;
    }
    PCF solveSPFA() {
        C cost = 0; F flow = 0;
        while (SPFA()) {
            C pathcost = dis[t];
            cost += pathcost*fl[t]; flow += fl[t];
            for (int u=t, e=prv[u]; e!=-1; u=edges[e].to, e=prv[u]) {
                edges[e].flow -= fl[t];
                edges[e^1].flow += fl[t];
            }
        }
        return {cost, flow};
    }
    void normalize() {
        SPFA();
        for (int i=0; i<n; i++) pi[i] = dis[i];
    }
    bool Dijkstra() {
        for (int i=0; i<n; i++) {
            dis[i] = infC; fl[i] = 0;
            vis[i] = 0; prv[i] = -1;
        }
        priority_queue<pair<C, int>> pq;
        pq.emplace(0, s);
        dis[s] = 0; fl[s] = infF;
        while (!pq.empty()) {
            int u = pq.top().second; pq.pop();
            if (vis[u]) continue;
            vis[u] = 1;
            for (int eid : adj[u]) {
                Edge &e = edges[eid];
                if (vis[e.to] || e.cap == e.flow) continue;
                C nw = dis[u] + e.cost - pi[e.to] + pi[u];
                if (nw < dis[e.to]) {
                    dis[e.to] = nw;
                    fl[e.to] = min(fl[u], e.cap - e.flow);
                    prv[e.to] = eid+1;
                    pq.emplace(-dis[e.to], e.to);
                }
            }
        }
        return fl[t] > 0;
    }
    PCF solveDijkstra() {
        normalize();
        C cost = 0; F flow = 0;
        while (Dijkstra()) {
            for (int i=0; i<n; i++)
                if (fl[i]) pi[i] += dis[i];
            C pathcost = pi[t]-pi[s];
            cost += pathcost*fl[t]; flow += fl[t];
            for (int u=t, e=prv[u]; e!=-1; u=edges[e].to, e=prv[u]) {
                edges[e].flow -= fl[t];
                edges[e^1].flow += fl[t];
            }
        }
        return {cost, flow};
    }
}

```

```

}
priority_queue<pair<C, int>> pq;
pq.emplace(0, s);
dis[s] = 0; fl[s] = infF;
while (!pq.empty()) {
    int u = pq.top().second; pq.pop();
    if (vis[u]) continue;
    vis[u] = 1;
    for (int eid : adj[u]) {
        Edge &e = edges[eid];
        if (vis[e.to] || e.cap == e.flow) continue;
        C nw = dis[u] + e.cost - pi[e.to] + pi[u];
        if (nw < dis[e.to]) {
            dis[e.to] = nw;
            fl[e.to] = min(fl[u], e.cap - e.flow);
            prv[e.to] = eid+1;
            pq.emplace(-dis[e.to], e.to);
        }
    }
}
return fl[t] > 0;
}
PCF solveDijkstra() {
    normalize();
    C cost = 0; F flow = 0;
    while (Dijkstra()) {
        for (int i=0; i<n; i++)
            if (fl[i]) pi[i] += dis[i];
        C pathcost = pi[t]-pi[s];
        cost += pathcost*fl[t]; flow += fl[t];
        for (int u=t, e=prv[u]; e!=-1; u=edges[e].to, e=prv[u]) {
            edges[e].flow -= fl[t];
            edges[e^1].flow += fl[t];
        }
    }
    return {cost, flow};
}

```

6.13 online-bridge

```

vector<int> par, dsu_2ecc, dsu_cc, dsu_cc_size;
int bridges; int lca_iteration;
vector<int> last_visit;
void init(int n) {
    par.resize(n); dsu_2ecc.resize(n); dsu_cc.resize(n);
    dsu_cc_size.resize(n); lca_iteration=0; last_visit.assign(n,0);
    for (int i=0; i<n; i++) {
        dsu_2ecc[i] = i; dsu_cc[i] = i; dsu_cc_size[i] = 1;
        par[i] = -1;
    }
    bridges = 0;
}
int find_2ecc(int v) {
    if (v == -1) return -1;
    return dsu_2ecc[v]==v?v:dsu_2ecc[v]=find_2ecc(dsu_2ecc[v]);
}
int find_cc(int v) {
    v = find_2ecc(v);
    return dsu_cc[v]==v?v : dsu_cc[v] = find_cc(dsu_cc[v]);
}
void make_root(int v) {
    v = find_2ecc(v); int root = v; int child = -1;
    while (v != -1) {
        int p = find_2ecc(par[v]); par[v] = child;
        dsu_cc[v] = root; child = v; v = p;
    }
    dsu_cc_size[root] = dsu_cc_size[child];
}
void merge_path (int a, int b) {
    ++lca_iteration; vector<int> path_a, path_b; int lca = -1;
    while (lca == -1) {
        if (a != -1) {
            a = find_2ecc(a); path_a.push_back(a);
            if (last_visit[a] == lca_iteration){
                lca = a; break;
            }
        }
        last_visit[a] = lca_iteration; a = par[a];
    }
}

```

```

}
if (b != -1) {
    b = find_2ecc(b); path_b.push_back(b);
    if (last_visit[b] == lca_iteration){
        lca = b; break;
    }
    last_visit[b] = lca_iteration; b = par[b];
}
for (int v : path_a) {
    dsu_2ecc[v] = lca; if (v == lca) break; --bridges;
}
for (int v : path_b) {
    dsu_2ecc[v] = lca; if (v == lca) break; --bridges;
}
}
void add_edge(int a, int b) {
    a = find_2ecc(a); b = find_2ecc(b);
    if (a == b) return;
    int ca = find_cc(a); int cb = find_cc(b);
    if (ca != cb) {
        ++bridges;
        if (dsu_cc_size[ca] > dsu_cc_size[cb]) {
            swap(a, b); swap(ca, cb);
        }
        make_root(a); par[a] = dsu_cc[a] = b;
        dsu_cc_size[cb] += dsu_cc_size[a];
    } else {
        merge_path(a, b);
    }
}
}

```

6.14 scc + 2 Sat

```

namespace SCC { //Everything 0-indexed.
    const int N = 2e6+7; int which[N], vis[N], cc;
    vector<int> adj[N], adjr[N]; vector<int> order;
    void addEdge(int u, int v) {
        adj[u].push_back(v); adjr[v].push_back(u);
    }
    void dfs1(int u){
        if (vis[u]) return; vis[u] = true;
        for(int v: adj[u]) dfs1(v); order.push_back(u);
    }
    void dfs2(int u, int id) {
        if(vis[u]) return; vis[u] = true;
        for(int v: adjr[u]) dfs2(v, id); which[u] = id;
    }
    int last = 0;
    void findSCC(int n) {
        cc=0;last=n; order.clear(); fill(vis, vis+n, 0);
        for(int i=0; i<n; i++) if(!vis[i]) dfs1(i);
        reverse(order.begin(), order.end());
        fill(vis, vis+n, 0);
        for (int u: order) {
            if (vis[u]) continue; dfs2(u, cc); ++cc;
        }
    }
    void clear() {
        for (int i=0; i<last; i++)
            adj[i].clear(), adjr[i].clear();
    }
}
struct TwoSat {
    int n; int vars = 0; vector<bool> ans;
    TwoSat(int n) : n(n), ans(n) {
        SCC::clear(); vars = 2*n;
    }
    void implies(int x, int y) {
        SCC::addEdge(x, y); SCC::addEdge(y^1, x^1);
    }
    void OR(int x, int y) {
        SCC::addEdge(x^1, y); SCC::addEdge(y^1, x);
    }
    void XOR(int x, int y) {
        implies(x, y^1); implies(x^1, y);
    }
    void atmostOne(vector<int> v) {
        int k = v.size();
        for (int i=0; i<k; i++) {
            if (i+1<k) implies(vars+2*i, vars+2*i+2);
            implies(v[i], vars+2*i);
        }
    }
}

```

```

    if (i>0)    implies(v[i], vars+2*i-1);
}
vars += 2*k;
}
bool solve() {
    SCC::findSCC(vars); ans.resize(vars/2);
    for (int i=0; i<vars; i+=2) {
        if (SCC::which[i]==SCC::which[i+1])return 0;
        if (i<2*n)
            ans[i/2] = SCC::which[i]>SCC::which[i+1];
        return true;
    }
}
};

```

7 Math

7.1 BerleKampMassey

```

const int MOD = 998244353;
vector<LL> berlekampMassey(vector<LL> s) {
    if (s.empty()) return {};
    int n = s.size(), L = 0, m = 0;
    vector<LL> C(n), B(n), T;
    C[0] = B[0] = 1; LL b = 1;
    for (int i = 0; i < n; ++i) {
        ++m; LL d = s[i] % MOD;
        for (int j = 1; j <= L; ++j) d = (d + C[j] * s[i - j]) % MOD;
        if (!d) continue;
        T = C; LL coeff = d * bigMod(b, -1) % MOD;
        for (int j = m; j < n; ++j) C[j] = (C[j] - coeff * B[j - m]) % MOD;
        if (2*L > i) continue;
        L = i+1-L, B = T, b = d, m = 0;
    }
    C.resize(L + 1), C.erase(C.begin());
    for (LL &x : C) x = (MOD - x) % MOD;
    return C;
}

```

7.2 FloorSum

```

LL mod(LL a, LL m) {
    LL ans = a%m;
    return ans < 0 ? ans+m : ans;
}
//Sum(floor((ax+b)/m)) for i=0 to n-1, (n,m >= 0)
LL floorSum(LL n, LL m, LL a, LL b) {
    LL ra = mod(a, m), rb = mod(b, m), k = (ra*n+rb);
    LL ans = ((a-ra)/m) * n*(n-1)/2 + ((b-rb)/m) * n;
    if (k < m) return ans;
    return ans + floorSum(k/m, ra, m, k%m);
}

```

7.3 Stern Brocot Tree

```

//finds x/y with min y st: L <= (x/y) < R
pair<LL,LL> solve(LD L, LD R){
    pair<LL, LL> l(0, 1), r(1, 1);
    if(L==0.0) return l; // corner case
    while(true) {
        pair<int, int> m(l.x+r.x, l.y+r.y);
        if(m.x<L*m.y){ // move to the right
            LL kl=1, kr=1;
            while(l.x+kr*r.x <= L*(l.y+kr*r.y)) kr*=2;
            while(kl!=kr){
                LL km = (kl+kr)/2;
                if(l.x+km*r.x < L*(l.y+km*r.y)) kl=km+1;
                else kr=km;
            }
            l={l.x+(kl-1)*r.x,l.y+(kl-1)*r.y};
        }
        else if(m.x>R*m.y){ //move to left
            LL kl=1, kr=1;
            while(r.x+kr*k.l.x>R*(r.y+kr*l.y)) kr*=2;
            while(kl!=kr){
                LL km = (kl+kr)/2;
                if(r.x+km*l.x>R*(r.y+km*l.y)) kl = km+1;
                else kr = km;
            }
        }
    }
}

```

```

    r={r.x+(kl-1)*l.x,r.y+(kl-1)*l.y};
}
else return m;
}
}

```

7.4 Sum Of Kth Power

```

LL mod; LL S[105][105];
// Find 1^k+2^k+...+n^k % mod
void solve() {
    LL n, k;
    /* x^k = sum (i=1 to k) Stirling2(k, i) * i! * ncr(x, i)
    sum (x = 0 to n) x^k
    = sum (i=0 to k) Stirling2(k, i) * i! * sum (x=0 to n) ncr(x, i)
    = sum (i=0 to k) Stirling2(k, i) * i! * ncr(n + 1, i + 1)
    = sum (i=0 to k) Stirling2(k, i) * i! * (n + 1)! / (i+1)! / (n-i)!
    = sum (i=0 to k) Stirling2(k, i) * (n - i + 1) *
        (n - i + 2) * ... (n + 1) / (i + 1) */
    S[0][0] = 1 % mod;
    for (int i = 1; i <= k; i++) {
        for (int j = 1; j <= i; j++) {
            if (i == j) S[i][j] = 1 % mod;
            else S[i][j] = (j * S[i - 1][j] + S[i - 1][j - 1]) % mod;
        }
    }
    LL ans = 0;
    for (int i = 0; i <= k; i++) {
        LL fact = 1, z = i + 1;
        for (LL j = n - i + 1; j <= n + 1; j++) {
            LL mul = j;
            if (mul % z == 0) {
                mul /= z; z /= z;
            }
            fact = (fact * mul) % mod;
        }
        ans = (ans + S[k][i] * fact) % mod;
    }
}

```

7.5 combination-generator

```

bool next_combination(vector<int>& a, int n) {
    int k = (int)a.size();
    for (int i = k - 1; i >= 0; i--) {
        if (a[i] < n - k + i + 1) {
            a[i]++;
            for (int j = i + 1; j < k; j++)
                a[j] = a[j - 1] + 1;
            return true;
        }
    }
    return false;
}
vector<int> ans;
void gen(int n, int k, int idx, bool rev) {
    if (k > n || k < 0)
        return;
    if (!n) {
        for (int i = 0; i < idx; ++i) {
            if (ans[i])
                cout << i + 1;
        }
        cout << "\n";
        return;
    }
    ans[idx] = rev;
    gen(n - 1, k - rev, idx + 1, false);
    ans[idx] = !rev;
    gen(n - 1, k - rev, idx + 1, true);
}
void all_combinations(int n, int k) {
    ans.resize(n);
    gen(n, k, 0, false);
}

```

7.6 continued-fractions

```

auto fraction(int p, int q) {
    vector<int> a;

```

```

    while(q) {
        a.push_back(p / q);
        tie(p, q) = make_pair(q, p % q);
    }
    return a;
}
auto convergents(vector<int> a) {
    vector<int> p = {0, 1};
    vector<int> q = {1, 0};
    for(auto it: a) {
        p.push_back(p[p.size() - 1] * it + p[p.size() - 2]);
        q.push_back(q[q.size() - 1] * it + q[q.size() - 2]);
    }
    return make_pair(p, q);
}

```

7.7 convolution

```

//zeta transform or sos dp
void zeta(vll& d,int m){
    int n=1<<m;
    for(int len=2;len<=n;len*=2){
        for(int i=0;i<n;i+=len){
            int l2=len>>1;
            for(int j=i;j<i+l2;j++){
                d[j+l2]+= d[j];
            }
        }
    }
//zeta_inverse or mobius transform
void zinv(vll &d,int m){
    int n=1<<m;
    for(int len=2;len<=n;len*=2){
        for(int i=0;i<n;i+=len){
            int l2=len>>1;
            for(int j=i;j<i+l2;j++){
                d[j+l2]-=d[j];
            }
        }
    }
//subset sum convolution
//not fully tested,got some error if used with mod
#define MAX_SIZE 1<<20
ll f[MAX_SIZE];
ll g[MAX_SIZE];
ll res[MAX_SIZE];
ll fhat[20][MAX_SIZE];
ll ghat[20][MAX_SIZE];
ll h[20][MAX_SIZE];
void subsetConvolution(int m){
    int n=1<<m;
    memset(fhat,0,sizeof(fhat));
    memset(ghat,0,sizeof(ghat));
    memset(res,0,sizeof(res));
    memset(h,0,sizeof(h));
    for(int i=0;i<n;i++){
        fhat[__builtin_popcount(i)][i]=f[i];
        ghat[__builtin_popcount(i)][i]=g[i];
    }
    for (int i=0; i<m; i++) {
        zeta(fhat[i],m);
        zeta(ghat[i],m);
        for (int j=0; j<=i; j++){
            for (int mask = 0; mask < n; mask++){
                h[i][mask] += fhat[j][mask]*ghat[i-j][mask];
            }
        }
        zinv(h[i],m);
    }
    for(int i=0;i<n;i++)
        res[i]=h[__builtin_popcount(i)][i];
}

```

7.8 crt anachor

```

// Chinese remainder theorem (special case): find z st z%m1 = r1, z%m2 = r2.
// z is unique modulo M = lcm(m1, m2). Returns (z, M). On failure, M = -1.
PLL CRT(LL m1, LL r1, LL m2, LL r2) {
    LL s, t;
    LL g = egcd(m1, m2, s, t);
    if (r1%g != r2%g) return PLL(0, -1);
    LL M = m1*m2;
    LL ss = ((s*r2)%m2)*m1;
    LL tt = ((t*r1)%m1)*m2;
    LL ans = ((ss+tt)%M+M)%M;
    return PLL(ans/g, M/g);
}
// expected: 23 105

```



```
//      11 12
PLL ans = CRT({3,5,7}, {2,3,2});
cout << ans.first << " " << ans.second << endl;
ans = CRT({4,6}, {3,5});
cout << ans.first << " " << ans.second << endl;
```

7.9 discrete-root

```
#define MAX 100000
int prime[MAX+1], Phi[MAX+1];
vector<int> pr;
void sieve(){
    for (int i=2; i <= N; ++i) {
        if (prime[i] == 0) {
            prime[i] = i;
            pr.push_back(i);
        }
        for (int j=0; j < (int)pr.size() && pr[j] <= prime[i]
            && i*pr[j] <= N; ++j) {
            prime[i * pr[j]] = pr[j];
        }
    }
}
void PhiWithSieve(){
    int i;
    for(i=2; i<=MAX; i++){
        if(prime[i]==i){
            Phi[i]=i-1;
        }
        else if((i/prime[i])%prime[i]==0){
            Phi[i]=Phi[i/prime[i]]*prime[i];
        }
        else{
            Phi[i]=Phi[i/prime[i]]*(prime[i]-1);
        }
    }
}
int powmod (int a, int b, int p) {
    int res = 1;
    while (b)
        if (b & 1)
            res = int (res * 1ll * a % p), --b;
        else
            a = int (a * 1ll * a % p), b >>= 1;
    return res;
}
int PrimitiveRoot(int p){
    vector<int> fact;
    int phi=Phi[p];
    int n=phi;
    while(n>1){
        if(prime[n]==n){
            fact.push_back(n);
            n=1;
        }
        else{
            int f=prime[n];
            while(n%f==0){
                n=n/f;
            }
            fact.push_back(f);
        }
    }
    int res;
    for(res=p-1; res>1; --res){
        for(n=0; n<fact.size(); n++){
            if(powmod(res,phi/fact[n],p)==1){
                break;
            }
        }
        if(n==fact.size()) return res;
    }
    return -1;
}
ll DiscreteLog(ll a,ll b,ll mod){
    ll n,p,q;
    n=(ll)sqrt((double)mod)+1ll;
    ll an=powmod(a,n,mod);
    map<ll,ll> map_;
    ll cur=an;
```

```
for(p=1;p<=n;p++){
    if(map_.find(cur)==map_.end()){
        map_.insert({cur,p});
    }
    cur=(cur*a)%mod;
}
cur=b;
ll mn=LLONG_MAX;
for(q=0;q<=n;q++){
    if(map_.find(cur)!=map_.end()){
        mn=min((n*map_[cur])-q,mn);
    }
    cur=(cur*a)%mod;
}
if(mn==LLONG_MAX)return -1;
else return mn;
}
vector<int> DiscreteRoot(int n,int a,int k){
    int g = PrimitiveRoot(n);
    vector<int> ans;
    int any_ans = DiscreteLog(powmod(g,k,n),a,n);
    if (any_ans == -1){
        return ans;
    }
    int delta = (n-1) / gcd(k, n-1);
    for (int cur = any_ans % delta; cur < n-1; cur += delta)
        ans.push_back(powmod(g, cur, n));
    sort(ans.begin(), ans.end());
    return ans;
}
```

7.10 fast-walsh-hadamard

```
void FWHT(vector<LL> &p, bool inv) {
    int n = p.size(); assert((n&(n-1))==0);
    for (int len=1; 2*len<=n; len<= 1) {
        for (int i = 0; i < n; i += len+len){
            for (int j = 0; j < len; j++) {
                LL u = p[i+j], v = p[i+len+j];
                ///XOR p[i+j]=u+v; p[i+len+j]=u-v;
                ///OR if(!inv) p[i+j]=v, p[i+len+j]=u+v;
                ///OR else p[i+j]=-u+v, p[i+len+j]=u;
                ///AND if(!inv) p[i+j]=u+v, p[i+len+j]=u;
                ///AND else p[i+j]=v, p[i+len+j]=u-v;
            }
        }
    }
    ///XOR if(inv) for(int i=0;i<n;i++) p[i]/=n;
}
vector<LL> convo(vector<LL> a, vector<LL> b) {
    int n = 1, sz = max(a.size(), b.size());
    while(n<sz) n*=2;
    a.resize(n); b.resize(n); vector<LL> res(n, 0);
    FWHT(a, 0); FWHT(b, 0);
    for(int i=0;i<n;i++) res[i] = a[i] * b[i];
    FWHT(res, 1);
    return res;
}
```

7.11 fft

```
struct CD {
    double x, y;
    CD(double x=0, double y=0) :x(x), y(y) {}
    CD operator+(const CD& o) { return {x+o.x, y+o.y};}
    CD operator-(const CD& o) { return {x-o.x, y-o.y};}
    CD operator*(const CD& o) { return {x*o.x-y*o.y,
        x*o.y+o.x*y};}
    void operator /= (double d) { x/=d; y/=d;}
    double real() {return x;}
    double imag() {return y;}
}
CD conj(const CD &c) {return CD(c.x, -c.y);}
const double PI = acos(-1.0L);
namespace FFT {
    int N;
    vector<int> perm;
    vector<CD> wp[2];
    void precalculate(int n) {
        assert((n & (n-1)) == 0);
```

```
N = n;
perm = vector<int> (N, 0);
for (int k=1; k<N; k<=1) {
    for (int i=0; i<k; i++) {
        perm[i] <= 1;
        perm[i+k] = 1 + perm[i];}
}
wp[0] = wp[1] = vector<CD>(N);
for (int i=0; i<N; i++) {
    wp[0][i] = CD( cos(2*PI*i/N), sin(2*PI*i/N) );
    wp[1][i] = CD( cos(2*PI*i/N), -sin(2*PI*i/N) );}
void fft(vector<CD> &v, bool invert = false) {
    if (v.size() != perm.size()) precalculate(v.size());
    for (int i=0; i<N; i++)
        if (i < perm[i])
            swap(v[i], v[perm[i]]);
    for (int len = 2; len <= N; len *= 2) {
        for (int i=0, d = N/len; i<N; i+=len) {
            for (int j=0, idx=0; j<len/2; j++, idx += d) {
                CD x = v[i+j];
                CD y = wp[invert][idx]*v[i+j+len/2];
                v[i+j] = x+y;
                v[i+j+len/2] = x-y;}}
    }
    if (invert) {
        for (int i=0; i<N; i++) v[i]/=N;}}
void pairfft(vector<CD> &a, vector<CD> &b, bool invert =
    false) {
    int N = a.size();
    vector<CD> p(N);
    for (int i=0; i<N; i++) p[i] = a[i] + b[i] * CD(0, 1);
    fft(p, invert);
    p.push_back(p[0]);
    for (int i=0; i<N; i++) {
        if (invert) {
            a[i] = CD(p[i].real(), 0);
            b[i] = CD(p[i].imag(), 0);}
        else {
            a[i] = (p[i]+conj(p[N-i]))*CD(0.5, 0);
            b[i] = (p[i]-conj(p[N-i]))*CD(0, -0.5);}}
}
vector<ll> multiply(const vector<ll> &a, const vector<ll>
    &b) {
    int n = 1;
    while (n < a.size()+ b.size()) n<=1;
    vector<CD> fa(a.begin(), a.end()), fb(b.begin(), b.end());
    fa.resize(n); fb.resize(n);
    // fft(fa); fft(fb);
    pairfft(fa, fb);
    for (int i=0; i<n; i++) fa[i] = fa[i] * fb[i];
    fft(fa, true);
    vector<ll> ans(n);
    for (int i=0; i<n; i++) ans[i] = round(fa[i].real());
    return ans;
}
const int M = 1e9+7, B = sqrt(M)+1;
vector<ll> anyMod(const vector<ll> &a, const vector<ll> &b) {
    int n = 1;
    while (n < a.size()+ b.size()) n<=1;
    vector<CD> al(n), ar(n), bl(n), br(n);
    for (int i=0; i<a.size(); i++) al[i] = a[i]%M/B, ar[i] =
        a[i]%M/B;
    for (int i=0; i<b.size(); i++) bl[i] = b[i]%M/B, br[i] =
        b[i]%M/B;
    pairfft(al, ar); pairfft(bl, br);
    // fft(al); fft(ar); fft(bl); fft(br);
    for (int i=0; i<n; i++) {
        CD l1 = (al[i] * bl[i]), lr = (al[i] * br[i]);
        CD r1 = (ar[i] * bl[i]), rr = (ar[i] * br[i]);
        al[i] = l1; ar[i] = lr;
        bl[i] = r1; br[i] = rr;
    }
    pairfft(al, ar, true); pairfft(bl, br, true);
    // fft(al, true); fft(ar, true); fft(bl, true); fft(br,
        true);
    vector<ll> ans(n);
    for (int i=0; i<n; i++) {
        ll right = round(br[i].real()), left =
            round(al[i].real());
        ll mid = round(round(bl[i].real()) + round(ar[i].real()));
        ans[i] = ((left%M)*B*B + (mid%M)*B + right)%M;
    }
    return ans;}
```

7.12 formulas

Binomial Coefficient List

- $\sum_{k=0}^m \binom{n+k}{k} = \binom{n+m+1}{m}.$
- $\binom{n}{0} + \binom{n-1}{1} + \dots + \binom{n-k}{k} + \dots + \binom{0}{n} = F_{n+1}$

Catalan's Triangle

- $C(n, 0) = 1, n \geq 0.$
- $C(n, 1) = n, n \geq 1.$
- $C(n+1, k) = C(n+1, k-1) + C(n, k), 1 < k < n+1.$
- $C(n, k) = \binom{n+k}{k} - \binom{n+k}{k-1} = \frac{n-k+1}{n+1} \binom{n+k}{k}.$

Fibonacci Numbers

- $F_{n-1}F_{n+1} - F_n^2 = (-1)^n.$
- $F_{n+k} = F_kF_{n+1} + F_{k-1}F_n.$

7.13 integer-factorization

```
typedef long long LL;
typedef unsigned long long ULL;

namespace Rho {
ULL mult(ULL a, ULL b, ULL mod) {
    LL ret = a * b - mod * (ULL)(1.0L/mod*a*b);
    return ret+mod*(ret<0) - mod*(ret>=(LL) mod);
}
ULL power(ULL x, ULL p, ULL mod){
    ULL s=1, m=x;
    while(p) {
        if(p&1) s = mult(s, m, mod);
        p>>=1; m = mult(m, m, mod);
    } return s;
}
vector<LL> bases =
{2,3,5,7,11,13,17,19,23,29,31,37,41,43,47,53,59,61,67,71,73,79,83,89,97,101,103,107,109,113,127,131,137,139,149,151,157,163,167,173,179,181,187,191,193,197,199,211,223,227,229,233,239,241,251,257,263,269,271,277,281,283,293,307,311,313,317,331,337,347,349,353,359,367,373,379,383,389,397,401,409,419,421,431,433,439,443,449,457,461,463,467,473,479,487,491,499,503,509,521,523,527,531,539,547,557,563,569,571,577,587,593,599,601,607,613,617,619,623,629,631,637,641,643,647,653,659,661,667,671,673,677,683,687,691,697,701,709,713,719,727,733,739,743,751,757,761,769,773,787,797,809,811,823,827,833,839,847,853,857,863,869,877,881,883,887,893,897,907,911,913,919,929,937,941,947,953,967,971,973,977,983,991,997};
bool isprime(LL n) {
    if (n<2) return 0;
    if (n%2==0) return n==2;
    ULL s = __builtin_ctzll(n-1), d = n>>s;
    for (ULL x: bases) {
        ULL p = power(x%n, d, n), t = s;
        while (p!=1&&p!=n-1&&x%n&&t-->0) p=mult(p,p,n);
        if (p!=n-1 && t != s) return 0;
    } return 1;
}
mt19937_64 rng(chrono::system_clock::
    now().time_since_epoch().count());
ULL FindFactor(ULL n) {
    if (n == 1 || isprime(n)) return n;
    ULL c=1, x=0, y=0, t=0, prod = 2, x0 = 1, q;
    auto f = [&](ULL X) { return mult(X, X, n) + c; };
    while (t++ % 128 or __gcd(prod, n) == 1) {
        if (x == y) c = rng()%(n-1)+1, x = x0, y=f(x);
        if ((q=mult(prod, max(x, y) - min(x, y), n)))
            prod = q;
        x = f(x), y = f(f(y));
    } return __gcd(prod, n);
}
```

7.14 integration-simpson

```
const int N = 1000 * 1000; // number of steps (already
    multiplied by 2)
double simpson_integration(double a, double b){
    double h = (b - a) / N;
    double s = f(a) + f(b); // a = x_0 and b = x_2n
    for (int i = 1; i <= N - 1; ++i) { // Refer to final
        // Simpson's formula
        double x = a + h * i;
        s += f(x) * ((i & 1) ? 4 : 2);
    }
    s *= h / 3;
    return s;
}
```

7.15 linear-diophantine-equation-gray-code

```
int gcd(int a, int b, int& x, int& y) {
    if (b == 0) {
        x = 1;
        y = 0;
        return a;
    }
    int x1, y1;
    int d = gcd(b, a % b, x1, y1);
    x = y1;
    y = x1 - y1 * (a / b);
    return d;
}
bool find_any_solution(int a, int b, int c, int &x0, int &y0,
    int &g) {
    g = gcd(abs(a), abs(b), x0, y0);
    if (c % g) {
        return false;
    }
    x0 *= c / g;
    y0 *= c / g;
    if (a < 0) x0 = -x0;
    if (b < 0) y0 = -y0;
    return true;
}
void shift_solution(int &x, int &y, int a, int b, int cnt) {
    x += cnt * b;
    y -= cnt * a;
}
int find_all_solutions(int a, int b, int c, int minx, int
    maxx, int miny, int maxy) {
    int x, y, g;
    if (!find_any_solution(a, b, c, x, y, g))
        return 0;
    a /= g;
    b /= g;
    int sign_a = a > 0 ? +1 : -1;
    int sign_b = b > 0 ? +1 : -1;
    shift_solution(x, y, a, b, (minx - x) / b);
    if (x < minx)
        shift_solution(x, y, a, b, sign_b);
    if (x > maxx)
        return 0;
    int lx1 = x;
    shift_solution(x, y, a, b, (maxx - x) / b);
    if (x > maxx)
        shift_solution(x, y, a, b, -sign_b);
    int rx1 = x;
    shift_solution(x, y, a, b, -(miny - y) / a);
    if (y < miny)
        shift_solution(x, y, a, b, -sign_a);
    if (y > maxy)
        return 0;
    int lx2 = x;
    shift_solution(x, y, a, b, -(maxy - y) / a);
    if (y > maxy)
        shift_solution(x, y, a, b, sign_a);
    int rx2 = x;
    if (lx2 > rx2)
        swap(lx2, rx2);
    int lx = max(lx1, lx2);
    int rx = min(rx1, rx2);
    if (lx > rx)
```

```
    return 0;
    return (rx - lx) / abs(b) + 1;
}
int g (int n) {
    return n ^ (n >> 1);
}
int rev_g (int g) {
    int n = 0;
    for (; g; g >>= 1)
        n ^= g;
    return n;
}
```

7.16 linear-equation-system

```
const double EPS = 1e-9;
const int INF = 2; // it doesn't actually have to be infinity
    or a big number
int gauss (vector<vector<double>> a, vector<double> &ans) {
    int n = (int) a.size();
    int m = (int) a[0].size() - 1;
    vector<int> where (m, -1);
    for (int col=0, row=0; col<m && row<n; ++col) {
        int sel = row;
        for (int i=row; i<n; ++i)
            if (abs (a[i][col]) > abs (a[sel][col]))
                sel = i;
        if (abs (a[sel][col]) < EPS)
            continue;
        for (int i=col; i<=m; ++i)
            swap (a[sel][i], a[row][i]);
        where[col] = row;
        for (int i=0; i<n; ++i)
            if (i != row) {
                double c = a[i][col] / a[row][col];
                for (int j=col; j<=m; ++j)
                    a[i][j] -= a[row][j] * c;
            }
        ++row;
    }
    ans.assign (m, 0);
    for (int i=0; i<m; ++i)
        if (where[i] != -1)
            ans[i] = a[where[i]][m] / a[where[i]][i];
    for (int i=0; i<n; ++i) {
        double sum = 0;
        for (int j=0; j<m; ++j)
            sum += ans[j] * a[i][j];
        if (abs (sum - a[i][m]) > EPS)
            return 0;
    }
    for (int i=0; i<m; ++i)
        if (where[i] == -1)
            return INF;
    return 1;
}
```

7.17 math

```
/******finding all factor below n in O(nlogn)*****/
int *pfactor;
void build(int n){//prime factor of every number below n
    pfactor=new int[n+1];
    memset(pfactor,0,sizeof(int)*(n+1));
    int i,j;
    for(i=2;i<=n;i++){
        if(pfactor[i]==0){
            for(j=i;j<=n;j+=i){
                pfactor[j]=i;}}
    }
    return;
}
int get_p_factor(vector<int>& pf,vector<int>& pfp,int n){//pf
    and pfp must have size>log(n) returns number of prime
    factor
    int i=0;
    int j,pw;
    while(n>1){
        j=pfactor[n];
        pw=0;
        while(!(n%j)){
            n/=j;
```

```

    pw++;}
    pf[i]=j;
    pfp[i]=pw;
    i++;}
    return i;}
int get_all_factor(vector<int>& pf,vector<int>& pfp,int
    sz,vector<int> &vct){
    vct[0]=1;
    int i,j,k,l,r,s=1;
    for(i=0;i<sz;i++){
        l=0;
        for(j=0;j<pfp[i];j++){
            r=s;
            for(k=1;k<r;k++,s++){
                vct[s]=(vct[k]*pf[i]);}
            l=r;}}
    return s;}
/*****General multiplicative function*****/
int *mf;
int base_case(int p,int k){//base case for p^k
    return k+1;}
void comp_mult_func(int n){
    mf=new int[n+1];
    memset(mf,-1,sizeof(int)*(n+1));
    int i,k,k2;ll l;
    mf[1]=1;
    for(i=2;i<=n;i++){
        if(mf[i]==-1){
            for(l=i+1;l<=n;l+=i)
                mf[l]=-1;
            l=i;k=1;
            while(l<=(ll)n){
                mf[l]=base_case(i,k);
                k++;
                l*=i;}}
        for(i=2;i<=n;i++){
            if(mf[i]<0){
                mf[i]=-mf[i];
                k=i;
                while(!(k%mf[i])){
                    k/=mf[i];
                }
                mf[i]=mf[k]*mf[i/k];}}
    return;}
int mu[N];
void mobius(){
    memset(mu,-1,sizeof mu); mu[1] = 1;
    for(int i = 2; i < N; i++)
        for(int j = (i << 1) ; j < N; j += i)mu[j] -= mu[i];
}

```

7.18 nCr mod p^a

```

LL F[1000009];
void pre(LL mod,LL pp){ // mod is pp^a, pp is prime
    F[0] = 1;
    REPL(i,1,mod){ // we keep in F factorial with
        // the terms which are coprime with pp
        if(i%pp!= 0) F[i]=(F[i-1]*i)%mod;
        else F[i]=F[i-1];
    }
}
LL fact2(LL nn,LL mod){
    LL cycle = nn/mod;
    LL n2=nn%mod;
    return (bigmod(F[mod],cycle,mod)*F[n2])%mod;
}
// returns highest power of pp that divides N and the coprime
// with pp part of N! %mod
PLL fact(LL N,LL pp,LL mod){
    LL nn = N; LL ord = 0;
    while(nn > 0){nn /= pp;ord += nn;}
    LL ans = 1; nn = N;
    while(nn > 0){ ans =(ans*fact2(nn,mod))%mod;
        nn/=pp;}
    return MP(ord,ans);
}
LL ncrp(ULL n,ULL r,LL prm,LL pr){ //ncr mod prm^pr
    LL mod=bigmod(prm,pr,INF),temp;
    pre(mod,prm);
}

```

```

PLL x=fact(n,prm,mod),y=fact(r,prm,mod),z=fact(n-r,prm,mod);
LL guun=x.second*modInverse(y.second,mod,prm);
guun%=mod;guun*=modInverse(z.second,mod,prm);
guun%=mod;
LL guun2=x.first-y.first-z.first;
guun*=bigmod(prm,guun2,mod);
guun%=mod;
return guun;
}

```

7.19 ntt

```

7340033 = 7 * 2^20, G = 3
645922817 = 77 * 2^23, G = 3
897581057 = 107 * 2^23, G = 3
998244353 = 119 * 2^23, G = 3
namespace NTT {
    vector<int> perm, wp[2];
    const int mod = 998244353, G = 3; ///G is the primitive root
    of M
    int root, inv, N, invN;
    int power(int a, int p) {
        int ans = 1;
        while (p) {
            if (p & 1) ans = (1LL*ans*a)%mod;
            a = (1LL*a*a)%mod;
            p >>= 1;}
        return ans;}
    void precalculate(int n) {
        assert( (n&(n-1)) == 0 && (mod-1)%n==0);
        N = n;
        invN = power(N, mod-2);
        perm = wp[0] = wp[1] = vector<int>(N);

        perm[0] = 0;
        for (int k=1; k<N; k<=(1)
            for (int i=0; i<k; i++) {
                perm[i] <= 1;
                perm[i+k] = 1 + perm[i];}
        root = power(G, (mod-1)/N);
        inv = power(root, mod-2);
        wp[0][0]=wp[1][0]=1;
        for (int i=1; i<N; i++) {
            wp[0][i] = (wp[0][i-1]*1LL*root)%mod;
            wp[1][i] = (wp[1][i-1]*1LL*inv)%mod;}}
    void fft(vector<int> &v, bool invert = false) {
        if (v.size() != perm.size()) precalculate(v.size());
        for (int i=0; i<N; i++)
            if (i < perm[i])
                swap(v[i], v[perm[i]]);
        for (int len = 2; len <= N; len *= 2) {
            for (int i=0, d = N/len; i<N; i+=len) {
                for (int j=0, idx=0; j<len/2; j++, idx += d) {
                    int x = v[i+j];
                    int y = (wp[invert][idx]* 1LL*v[i+j+len/2])%mod;
                    v[i+j] = (x+y)%mod ? x+y-mod : x+y;
                    v[i+j+len/2] = (x-y)%mod ? x-y : x-y+mod;}}
            if (invert) {
                for (int &x : v) x = (x*1LL*invN)%mod;}}
        vector<int> multiply(vector<int> a, vector<int> b) {
            int n = 1;
            while (n < a.size()+ b.size()) n<=1;
            a.resize(n);
            b.resize(n);
            fft(a);
            fft(b);
            for (int i=0; i<n; i++) a[i] = (a[i] * 1LL * b[i])%mod;
            fft(a, true);
            return a;}};
}

```

7.20 primality-test

```

using u64 = uint64_t;
using u128 = __uint128_t;
u64 binpower(u64 base, u64 e, u64 mod) {
    u64 result = 1; base %= mod;
    while (e) {
        if (e & 1) result = (u128)result * base % mod;
        base = (u128)base * base % mod; e >>= 1;
    }
}

```

```

}
return result;
}
bool check_composite(u64 n, u64 a, u64 d, int s) {
    u64 x = binpower(a, d, n);
    if (x == 1 || x == n - 1) return false;
    for (int r = 1; r < s; r++) {
        x = (u128)x * x % n;
        if (x == n - 1) return false;
    }
    return true;
};
// returns true if n is prime, else returns false.
bool MillerRabin(u64 n) {
    if (n < 2) return false;
    int r = 0; u64 d = n - 1;
    while ((d & 1) == 0) {
        d >>= 1; r++;
    }
    for (int a : {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37})
        if (n == a) return true;
        if (check_composite(n, a, d, r)) return false;
    }
    return true;
}
}

```

7.21 prime counting function

```

#define MAXN 500
#define MAXM 100010
#define MAXP 666666
#define MAX 10000010
#define ll long long int
#define chkbit(ar,i) (((ar[(i)>>6])&(1 << (((i) >> 1) & 31))))
#define setbit(ar, i) (((ar[(i) >> 6]) |= (1 << (((i)>>1)&31))))
#define isprime(x) (((x)&&((x)&1)&&(!chkbit(ar,(x))))||((x)==2))
namespace pc{
    long long dp[MAXN][MAXM];
    unsigned int ar[(MAX>>6)+5] = {0};
    int len=0, primes[MAXP], counter[MAX];
    void Sieve(){ setbit(ar,0), setbit(ar,1);
        for (int i=3;(i*i)<MAX;i++,i++){
            if(!chkbit(ar, i)){ int k=i<<1;
                for(int j=(i*i);j<MAX;j+=k) setbit(ar,j);
            }
        }
        for(int i=1;i<MAX;i++){ counter[i]=counter[i - 1];
            if(isprime(i)) primes[len++]=i, counter[i]++;
        }
    }
    void init(){
        Sieve();
        for(int n=0;n<MAXN;n++){
            for(int m=0;m<MAXM;m++){
                if(!n) dp[n][m]=m;
                else dp[n][m]=dp[n-1][m]-dp[n-1][m/primes[n-1]];
            }
        }
    }
    ll phi(ll m,int n){
        if(n==0) return m; if(primes[n-1]>=m) return 1;
        if(m<MAXM && n<MAXN) return dp[n][m];
        return phi(m,n-1) - phi(m/primes[n-1],n-1);
    }
    ll Lehmer(long long m){
        if(m<MAX) return counter[m];
        ll w,res=0; int i,a,s,c,x,y;
        s=sqrt(0.9+m), y=cbrt(0.9+m);
        a=counter[y], res=phi(m,a)+a-1;
        for(i=a;primes[i]<=s;i++)
            res=res-Lehmer(m/primes[i])+Lehmer(primes[i]-1;
        return res;
    }
}
}

```

8 String

8.1 Hashing

```

11 fmod(11 a, 11 b, int md=mods[0]) {
    unsigned long long x = (long long) a * b;
    unsigned xh = (unsigned) (x >> 32), xl = (unsigned) x, d, m;
    asm(
        "div %4; \n\t"
        : "=a" (d), "=d" (m)
        : "d" (xh), "a" (xl), "r" (md)
    );
    return m;
}
void Build1(const string &str) {
    for(11 i = str.size() - 1; i >= 0; i--){
        hsh[i] = fmod(hsh[i + 1], bases[j], mods[j]) + str[i];
        if (hsh[i] > mods[j]) hsh[i] -= mods[j];
    }
}
11 getSingleHash(11 i, 11 j) {
    assert(i <= j);
    11 tmp1 = (hsh[i] - fmod(hsh[j+1], pwbase[0][j-i+1]));
    if(tmp1 < 0) tmp1 += mods[0]; return tmp1;
}

```

8.2 KMP

```

int failure[1000001];
void build_failure(string &str)
{
    int i, j, k;
    int cur;
    memset(failure, 0, sizeof failure);
    failure[0] = 0;
    failure[1] = 0;
    for(i=2; i<=str.length(); i++){
        cur=i-1;
        while(cur!=0){
            if(str[failure[cur]]==str[i-1]){
                failure[i]=failure[cur]+1;
                break;
            }
            cur=failure[cur];
        }
    }
}
int kmp(string &text, string &pat)
{
    int i, j, k;
    int cur=0;
    int ocur=0;
    for(i=0; i<text.length(); i++){
        if(cur==pat.length()){
            ocur++;
        }
        while(cur and text[i]!=pat[cur]){
            cur=failure[cur];
        }
        if(text[i]==pat[cur])
            cur++;
    }
    if(cur==pat.length())
        ocur++;
    return ocur;
}

```

8.3 aho-corasick

```

const int K = 26;
struct Vertex {
    int next[K]; bool leaf = false; int p = -1; char pch;
    int link = -1; int go[K];
    Vertex(int p=-1, char ch='$') : p(p), pch(ch) {
        fill(begin(next), end(next), -1);
        fill(begin(go), end(go), -1);
    }
};
vector<Vertex> t(1);
void add_string(string const& s) { int v = 0;
    for (char ch : s) {
        int c = ch - 'a';
        if (t[v].next[c] == -1) {
            t[v].next[c] = t.size(); t.emplace_back(v, ch);
        }
    }
}

```

```

        v = t[v].next[c];
    }
    t[v].leaf = true;
}
int go(int v, char ch);
int get_link(int v) {
    if (t[v].link == -1) {
        if (v == 0 || t[v].p == 0) t[v].link = 0;
        else t[v].link = go(get_link(t[v].p), t[v].pch);
    }
    return t[v].link;
}
int go(int v, char ch) {
    int c = ch - 'a';
    if (t[v].go[c] == -1) {
        if (t[v].next[c] != -1) t[v].go[c] = t[v].next[c];
        else t[v].go[c] = v == 0 ? 0 : go(get_link(v), ch);
    }
    return t[v].go[c];
}

```

8.4 manacher

```

char s[MAX]; vector<int> d1(n); vector<int> d2(n);
for (int i = 0, l = 0, r = -1; i < n; i++){
    int k = (i > r) ? 1 : min(d1[l + r - i], r - i + 1);
    while (0 <= i - k && i + k < n && s[i - k] == s[i + k])
        { k++; }
    d1[i] = k--;
    if (i + k > r) { l = i - k; r = i + k; }
}
for (int i = 0, l = 0, r = -1; i < n; i++){
    int k = (i > r) ? 0 : min(d2[l + r - i + 1], r - i + 1);
    while (0 <= i - k - 1 && i + k < n && s[i - k - 1] == s[i + k])
        { k++; }
    d2[i] = k--;
    if (i + k > r) { l = i - k - 1; r = i + k; }
}

```

8.5 palindromic tree

```

struct node {
    int next[26]; int len; int sufflink; int num; };
int len; char s[MAXN]; node tree[MAXN];
int num; // node 1 - root with len -1, node 2 - root with len 0
int suff; // max suffix palindrome
bool addLetter(int pos) {
    int cur = suff, curlen = 0; int let = s[pos] - 'a';
    while (true) {
        curlen = tree[cur].len;
        if (pos-1-curlen >= 0 && s[pos-1-curlen] == s[pos])
            break;
        cur = tree[cur].sufflink;
    }
    if (tree[cur].next[let]) {
        suff = tree[cur].next[let]; return false;
    }
    num++; suff = num; tree[num].len = tree[cur].len + 2;
    tree[cur].next[let] = num;
    if (tree[num].len == 1) { tree[num].sufflink = 2;
        tree[num].num = 1; return true;
    }
    while (true) {
        cur = tree[cur].sufflink; curlen = tree[cur].len;
        if (pos-1-curlen >= 0 && s[pos-1-curlen] == s[pos]) {
            tree[num].sufflink = tree[cur].next[let]; break;
        }
    }
    tree[num].num = 1 + tree[tree[num].sufflink].num; return true;
}
void initTree() {
    num = 2; suff = 2; // memset tree must
    tree[1].len = -1; tree[1].sufflink = 1;
    tree[2].len = 0; tree[2].sufflink = 1;
}
int main() { gets(s); len = strlen(s); initTree();
    for (int i = 0; i < len; i++) { addLetter(i);
        ans += tree[suff].num; }
    cout << ans << endl; return 0;
}

```

8.6 suffix array da

```

/* sa => ith smallest suffix of the string
rak => rak[i] indicates the position of suffix(i) in the suffix
array; height => height[i] indicates the LCP of i-1 and i th
suffix; LCP of suffix(i) & suffix(j) = { L = rak[i], R = rak[j]
, min(height[L+1, R])};*/
const int maxn = 5e5+5;
int wa[maxn], wb[maxn], wv[maxn], wc[maxn];
int r[maxn], sa[maxn], rak[maxn], height[maxn], dp[maxn][22],
jump[maxn], SIGMA = 0;
int cmp(int *r, int a, int b, int l)
{ return r[a]==r[b] && r[a+l]==r[b+l]; }
void da(int *r, int *sa, int n, int m) {
    int i, j, p, *x=wa, *y=wb, *t;
    for(i=0; i<m; i++) wc[i]=0;
    for(i=0; i<n; i++) wc[x[i]=r[i]]++;
    for(i=1; i<m; i++) wc[i] += wc[i-1];
    for(i=n-1; i>=0; i--) sa[wc[i]] = i;
    for(j=1, p=1; p<n; j*=2, m=p){
        for(p=0, i=n-j; i<n; i++) y[p++] = i;
        for(i=0; i<n; i++) if(sa[i] >= j) y[p++] = sa[i] - j;
        for(i=0; i<n; i++) wv[i] = x[y[i]];
        for(i=0; i<n; i++) wc[wv[i]]++;
        for(i=1; i<m; i++) wc[i] += wc[i-1];
        for(i=n-1; i>=0; i--) sa[wc[i]] = y[i];
        for(t=x, x=y, y=t, p=1, x[sa[0]] = 0, i=1; i<n; i++)
            x[sa[i]] = cmp(y, sa[i-1], sa[i], j) ? p-1 : p++;
    }
}
void calheight(int *r, int *sa, int n) {
    int i, j, k=0;
    for(i=1; i<n; i++) rak[sa[i]] = i;
    for(i=0; i<n; height[rak[i++]] = k) {
        for(k?k--:0, j=sa[rak[i]-1]; r[i+k] == r[j+k]; k++);
    }
}
void initRMQ(int n) {
    for(int i=0; i<n; i++) dp[i][0] = height[i];
    for(int j=1; (1<<j) <= n; j++) {
        for(int i=0; i+(1<<j)-1 <= n; i++) {
            dp[i][j] = min(dp[i][j-1], dp[i+(1<<(j-1))][j-1]);
        }
    }
    for(int i=1; i<= n; i++) {
        int k=0; while((1<<(k+1)) <= i) k++; jump[i] = k;
    }
}
int askRMQ(int L, int R) {
    int k = jump[R-L+1];
    return min(dp[L][k], dp[R - (1<<k) + 1][k]);
}
int main() {
    scanf("%s", s); int n = strlen(s);
    for(int i=0; i<n; i++) {
        r[i] = s[i] - 'a' + 1; SIGMA = max(SIGMA, r[i]);
    }
    r[n] = 0; da(r, sa, n+1, SIGMA + 1);
    calheight(r, sa, n);
    /* don't forget SIGMA + 1. It will ruin you.*/
}

```

8.7 suffix-automaton

```

class SuffixAutomaton {
    bool complete; int last;
    set<char> alphabet;
    struct state {
        int len, link, endpos, first_pos, snas, height;
        long long substrings, sublen;
        bool is_clone;
        map<char, int> next;
        vector<int> inv_link;
        state(int leng=0, int li=0) {
            len=leng; link=li;
            first_pos=-1; substrings=0;
            sublen=0; // length of all substrings
            snas=0; // shortest_non_appearing_string
            endpos=1; is_clone=false; height=0;
        }
    };
};

```



```

    }
};
vector<state> st;
void process(int node){
    map<char, int> ::iterator mit;
    st[node].substrings=1;
    st[node].snas=st.size();
    if((int) st[node].next.size()<(int) alphabet.size())
        st[node].snas=1;
    for(mit=st[node].next.begin(); mit!=st[node].next.end();++mit){
        if(st[mit->second].substrings==0) process(mit->second);
    }
    st[node].height=max(st[node].height,1+st[mit->second].height);
    st[node].substrings=
        st[node].substrings+st[mit->second].substrings;
    st[node].sublen=st[node].sublen
        +st[mit->second].sublen+st[mit->second].substrings;
    st[node].snas=min(st[node].snas,
        1+st[mit->second].snas);
    }
    if(st[node].link!=-1)
        st[st[node].link].inv_link.push_back(node);
}
void set_suffix_links(int node){
    int i;
    for(i=0; i<st[node].inv_link.size(); i++){
        set_suffix_links(st[node].inv_link[i]);
        st[node].endpos=
            st[node].endpos+st[st[node].inv_link[i]].endpos;
    }
}
void output_all_occurrences(int v,int
    P_length,vector<int>&pos){
    if (!st[v].is_clone)
        pos.push_back(st[v].first_pos - P_length + 1);
    for (int u : st[v].inv_link)
        output_all_occurrences(u, P_length, pos);
}
void kth_smallest(int node,int k,vector<char> &str){
    if(k==0) return;
    map<char, int> ::iterator mit;
    for(mit=st[node].next.begin(); mit!=st[node].next.end();++mit){
        if(st[mit->second].substrings<k)k=k-st[mit->second].substrings;
        else{
            str.push_back(mit->first);
            kth_smallest(mit->second,k-1,str);
            return;
        }
    }
}
int find_occurrence_index(int node,int index,vector<char>&str){
    if(index==str.size()) return node;
    if(!st[node].next.count(str[index])) return -1;
    else return find_occurrence_index(st[node].next[str[index]]
        ,index+1,str);
}
}
void klen_smallest(int node,int k,vector<char> &str){
    if(k==0) return;
    map<char, int> ::iterator mit;
    for(mit=st[node].next.begin(); mit!=st[node].next.end();++mit){
        if(st[mit->second].height>=k-1){
            str.push_back(mit->first);
            klen_smallest(mit->second,k-1,str);
            return;
        }
    }
}
}
void minimum_non_existing_string(int node,vector<char> &str){
    map<char, int> ::iterator mit;
    set<char>::iterator sit;

```

```

    for(mit=st[node].next.begin(),sit=alphabet.begin();
        sit!=alphabet.end(); ++sit,++mit){
        if(mit==st[node].next.end()||mit->first!=(*sit)){
            str.push_back(*sit);
            return;
        }
        else if(st[node].snas==1+st[mit->second].snas){
            str.push_back(*sit);
            minimum_non_existing_string(mit->second,str);
            return;
        }
    }
}
void find_substrings(int node,int index,vector<char> &str,
    vector<pair<long long,long long> > &sub_info){
    sub_info.push_back(make_pair(st[node].substrings,
        st[node].sublen+st[node].substrings*index));
    if(index==str.size()) return;
    if(st[node].next.count(str[index])){ find_substrings(
        st[node].next[str[index]],index+1,str,sub_info);return;
    }
    else{
        sub_info.push_back(make_pair(0,0));
    }
}
void check(){
    if(!complete){
        process(0);
        set_suffix_links(0);
        int i;
        complete=true;
    }
}
public:
    SuffixAutomaton(set<char> &alpha){
        st.push_back(state(0,-1));
        last=0;
        complete=false;
        set<char>::iterator sit;
        for(sit=alpha.begin(); sit!=alpha.end(); sit++){
            alphabet.insert(*sit);
            st[0].endpos=0;
        }
    }
    void sa_extend(char c){
        int cur = st.size();
        st.push_back(state(st[last].len + 1));
        st[cur].first_pos=st[cur].len-1;
        int p = last;
        while (p != -1 && !st[p].next.count(c)){
            st[p].next[c] = cur;
            p = st[p].link;
        }
        if (p == -1){
            st[cur].link = 0;
        }
        else{
            int q = st[p].next[c];
            if (st[p].len + 1 == st[q].len){
                st[cur].link = q;
            }
            else{
                int clone = st.size();
                st.push_back(state(st[p].len + 1,st[q].link));
                st[clone].next = st[q].next;
                st[clone].is_clone=true;
                st[clone].endpos=0;
                st[clone].first_pos=st[q].first_pos;
            }
        }
    }

```

```

        while (p != -1 && st[p].next[c] == q){
            st[p].next[c] = clone; p = st[p].link;
        }
        st[q].link = st[cur].link = clone;
    }
    }
    last = cur;
    complete=false;
}
~SuffixAutomaton(){
    int i;
    for(i=0; i<st.size(); i++){
        st[i].next.clear();
        st[i].inv_link.clear();
    }
    st.clear();
    alphabet.clear();
}
void kth_smallest(int k,vector<char> &str){
    check();
    kth_smallest(0,k,str);
}
int FindFirstOccurrenceIndex(vector<char> &str){
    check();
    int ind=find_occurrence_index(0,0,str);
    if(ind==0) return -1;
    else if(ind==-1) return st.size();
    else return st[ind].first_pos+1-(int) str.size();
}
void FindAllOccurrenceIndex(vector<char> &str,vector<int>&pos){
    check();
    int ind=find_occurrence_index(0,0,str);
    if(ind!=-1) output_all_occurrences(ind,str.size(),pos);
}
int Occurrences(vector<char> &str){
    check();
    int ind=find_occurrence_index(0,0,str);
    if(ind==0) return 1;
    else if(ind==-1) return 0;
    else return st[ind].endpos;
}
void klen_smallest(int k,vector<char> &str){
    check();
    if(st[0].height>=k) klen_smallest(0,k,str);
}
void minimum_non_existing_string(vector<char> &str){
    check();
    int ind=find_occurrence_index(0,0,str);
    if(ind!=-1) minimum_non_existing_string(ind,str);
}
}
};

```

8.8 z-algorithm

```

vector<int> z_function(string s) {
    int n = (int) s.length();
    vector<int> z(n);
    for (int i = 1, l = 0, r = 0; i < n; ++i) {
        if (i <= r)
            z[i] = min (r - i + 1, z[i - l]);
        while (i + z[i] < n && s[z[i]] == s[i + z[i]])
            ++z[i];
        if (i + z[i] - 1 > r)
            l = i, r = i + z[i] - 1;
    }
    return z;
}

```