

Native CTS Solver Implementation Notes

AthenaK code-reading guide

May 21, 2026

1 Purpose and Big Picture

The native initial-data solver lives primarily in `src/z4c/id_solve.cpp` and `src/z4c/id_solve.hpp`. It solves a conformal thin sandwich (CTS) system for four correction variables,

$$u = (\delta\Psi, \delta\beta^x, \delta\beta^y, \delta\beta^z),$$

stored in `IDConformalThinSandwich::u_cts`. The correction is added to a fixed background/free-data state stored in `u_free`. After the multigrid solve, the code reconstructs physical ADM variables and converts them into Z4c evolution variables.

At a high level, the flow is:

1. A problem generator initializes ADM-like seed data.
2. Z4c setup converts that seed to Z4c variables and computes initial diagnostics.
3. At the start of the Z4c task list, `Z4c_IDSolve` runs once if `pmy_pack->pid_solve` exists.
4. The CTS solver builds free data from the current ADM variables.
5. The multigrid driver solves for $\delta\Psi$ and $\delta\beta^i$.
6. `ApplySolution()` writes solved physical ADM fields, converts them to Z4c variables, refreshes boundary/ghost zones, and recomputes ADM constraints.
7. Normal hyperbolic Z4c evolution proceeds from the solved data.

2 File-by-File Map

File	Role in CTS/Z4c initial-data path
<code>src/z4c/id_solve.hpp</code>	Declares the native CTS classes and variable enums. Defines the four solved variables <code>ID_CTS_*</code> , all free-data slots <code>ID_FREE_*</code> , the <code>IDCTSMultigrid</code> subclass, the <code>IDCTSMultigridDriver</code> , and the owner class <code>IDConformalThinSandwich</code> .

File	Role in CTS/Z4c initial-data path
src/z4c/id_solve.cpp	Main implementation. Contains finite-difference helpers, conformal geometry helpers, the CTS residual operator, smoothing/defect/FAS kernels, multigrid driver construction and solve loop, free-data construction, ADM application, and constraint diagnostics.
src/z4c/z4c_tasks.cpp	Queues <code>IDConformalThinSandwich::SolveTask</code> as <code>Z4c_IDSolve</code> in the <code>Task_Start</code> phase after <code>Z4c_Recv</code> . Also shows the evolution task sequence that follows: copy, RHS, boundary RHS, RK update, restriction, send/recv, physical BCs, prolongation, algebraic constraints, ADM conversion, diagnostics, tracking, CCE, and horizon finding.
src/z4c/z4c.cpp	Constructs Z4c options and boundary buffers. Maps <code>z4c/spatial_order</code> to <code>opt.fd_stencil</code> : 2nd order $\rightarrow$ 2, 4th order $\rightarrow$ 3, 6th order $\rightarrow$ 4. Allocates <code>pbval_u</code> and <code>pbval_weyl</code> .
src/z4c/z4c_adm.cpp	Implements <code>ADMTToZ4c</code> , <code>Z4cToADM</code> , and <code>ADMConstraints</code> . This is the conversion bridge between solved ADM data and Z4c evolution arrays.
src/pgen/z4c_critical_kerr_formation.cpp	Problem generator for the compact-support conformal-metric seed. Builds $\bar{\gamma}_{ij}$, a trace-free time-derivative/extrinsic-curvature seed, zero shift, and chosen lapse; then converts ADM to Z4c before the CTS task runs.
src/multigrid/multigrid.hpp	Base multigrid data structures. Defines <code>Multigrid</code> , <code>MGOctet</code> , task IDs, storage for <code>u</code> , <code>src</code> , <code>def</code> , <code>coeff</code> , and generic restriction/prolongation/smoothing interfaces.
src/multigrid/multigrid.cpp	Generic multigrid operations: load finest data/source/coefficient arrays, restrict coefficients, retrieve solved data, restrict residuals, prolong and correct, compute defect norms, root-grid transfers.
src/multigrid/multigrid_driver.cpp	Base multigrid driver: hierarchy setup, V-cycle and FMG orchestration, root-grid boundary treatment, octet/coarse-fine bridge support, default multigrid boundary condition selection.
src/multigrid/multigrid_tasks.cpp	Task-list wiring for multigrid cycles: boundary receive/send, physical boundary fill, fine-coarse ghost fill, red/black smoothing, restriction, prolongation, and cleanup dependencies.
src/utils/finite_diff.hpp	Generated finite-difference stencils used by CTS and Z4c. The template parameter <code>NGHOST=2,3,4</code> corresponds to 2nd, 4th, and 6th-order centered operators.
inputs/z4c/gw_collapse/z4c_critical_kerr_formation.athinput	Representative input file. Sets mesh boundaries, <code>z4c/spatial_order</code> , <code>id_solve</code> controls, and the critical-Kerr seed parameters.

3 Objects and Data Arrays

3.1 Solved Variables

src/z4c/id_solve.hpp defines:

```
enum IDCTSUVar {  
    ID_CTS_PSI,  
    ID_CTS_BETAX,  
    ID_CTS_BETAY,  
    ID_CTS_BETAZ,  
    ID_CTS_NVAR  
};
```

The multigrid unknown `u_cts` stores corrections to a base conformal factor and base shift. The actual fields used by the residual are assembled with `TotalU()`:

$$\Psi = \text{ID_FREE_BASE_PSI} + u_\Psi, \quad \beta^i = \text{ID_FREE_BASE_BETA}^i + u_{\beta^i}.$$

In the current critical-Kerr seed, the base values are $\Psi = 1$ and $\beta^i = 0$, so the solver starts from no correction.

3.2 Free-Data Variables

IDCTSTFreeVar includes:

- ID_FREE_GXX ... ID_FREE_GZZ: conformal metric $\bar{\gamma}_{ij}$.
- ID_FREE_GDOTXX ... ID_FREE_GDOTZZ: contravariant trace-free tensor $\bar{u}_{TF}^{ij}$. The names say GDOT, but the comment in the header clarifies the actual stored quantity.
- ID_FREE_K: trace K .
- ID_FREE_DKX ... ID_FREE_DKZ: $\bar{D}^i K$.
- ID_FREE_ALPHA: conformal lapse-like field used by the operator.
- ID_FREE_E, ID_FREE_PX/PY/PZ: matter source terms.
- ID_FREE_SOURCE: extra scalar source in the Hamiltonian equation.
- ID_FREE_MASK: active-cell mask for the residual and smoother.
- ID_FREE_BASE_PSI, ID_FREE_BASE_BETAX/BETAY/BETAZ: base values to which corrections are added.

4 Problem-Generator Seed Path

src/pgen/z4c_critical_kerr_formation.cpp is the current compact-support test seed. The important functions are:

- ReadOptions(): reads problem/* options such as amplitude, support radius, helicity, phase, lapse, and radial coefficients.
- RadialProfileAndDerivative(): constructs a compact bump profile and radial derivative using Legendre modes.

- **FillCriticalKerrFreeDataADM()**: fills ADM fields on active and ghost cells. It constructs a regular $\ell = m = 2$ solid-harmonic tensor perturbation, builds $q_{ij} = \delta_{ij} + h_{ij} + h_{ij}^2/2$, rescales it to unit determinant, and stores it as an ADM spatial metric seed. It also builds a trace-free $\dot{u}_{ij}$ -like tensor and stores $K_{ij} = 0.5 \dot{u}_{ij}$, with zero shift and configured lapse.
- **ConvertADMToZ4cAndConstraints()**: dispatches to **ADMToZ4c<2/3/4>** based on **pz4c->opt.fd_stencil**, computes ADM constraints, then calls **Z4cToADM()** so the ADM view is consistent with the Z4c storage.
- **ProblemGenerator::UserProblem()**: checks that **z4c**, **adm**, and **id_solve** exist, fills the seed, optionally sets a pre-collapsed lapse, converts to Z4c, and returns.

5 Task Scheduling and Handoff Timing

The solve is inserted in **src/z4c/z4c_tasks.cpp**. In **Z4c::QueueZ4cTasks()**, the start phase is:

```
Z4c_Recv = Z4c::InitRecv
Z4c_IRecvW = Z4c::InitRecvWeyl
Z4c_IDSolve = IDConformalThinSandwich::SolveTask, depends on Z4c_Recv
```

This means Z4c boundary receives are posted before the ID solve. The solve is still before the hyperbolic RHS and RK update. After the solve, regular evolution continues through **CopyU**, **CalcRHS**, **Z4cBoundaryRHS**, **ExpRKUpdate**, mesh communication, physical BCs, prolongation, algebraic constraint enforcement, and **Z4cToADM**.

Inside **IDConformalThinSandwich::SolveTask()**:

1. Optionally write “before” constraint diagnostics.
2. Call **IDCTSMultigridDriver::Solve()**.
3. If a solution was accepted, call **RefreshZ4cBoundariesAfterSolve()**.
4. Recompute constraints on the refreshed solution.
5. Optionally write “after” diagnostics.

The refresh step is important. **ApplySolution()** writes Z4c data, but ghost zones and physical boundaries need to be made consistent before evolution and before final diagnostics.

6 Free-Data Construction

IDConformalThinSandwich::BuildFreeData() converts the current ADM fields into the free-data arrays consumed by the CTS residual.

6.1 Metric, Lapse, Shift, and Trace

For every active and ghost cell:

- $\bar{\gamma}_{ij}$ is copied from **admvars.g_dd**.
- The inverse metric is computed locally.
- $K = \gamma^{ij} K_{ij}$ is computed from **admvars.vK_dd**.
- **ID_FREE_ALPHA** is copied from **admvars.alpha**.

- The base conformal factor is set to 1.
- The base shift is copied from `admvars.beta_u`.
- The correction variables in `u_cts` are reset to zero.

6.2 Matter Sources and Masks

If `pmy_pack->ptmunu` exists, the code reads Eulerian energy density `tmunu.E` and raises the covariant momentum `S_d` using the conformal metric inverse. Otherwise $E = 0$ and $p^i = 0$.

The mask controls where the residual and smoother are active. If `id_solve/mask_horizon_defect=true`, cells inside `horizon_mask_radius` get `ID_FREE_MASK=0`. If `id_solve/fill_horizon_junk=true`, source terms inside `horizon_fill_radius` are adjusted by `FillHorizonJunk()`.

6.3 $\bar{u}_{TF}^{ij}$ and $\bar{D}^i K$

`BuildGammaDotAndDK<NGHOST>()` computes:

- $\bar{D}^i K = \bar{\gamma}^{ij} \partial_j K$, stored in `ID_FREE_DKX/DKY/DKZ`.
- The trace-free extrinsic-curvature seed $\hat{A}^{ij}$ by raising the trace-free part of K_{ij} using the conformal metric.
- The conformal longitudinal shift operator $(\bar{L}\beta)^{ij}$.
- The stored tensor

$$\bar{u}_{TF}^{ij} = 2\alpha\hat{A}^{ij} - (\bar{L}\beta)^{ij}.$$

The halo width needed here follows the same nested-stencil logic as $D_j \hat{A}^{ij}$: $\hat{A}$ contains derivatives, and its divergence may require an additional outer stencil.

7 CTS Residual Operator

`CTSOperator<NGHOST>()` evaluates the four residual equations at one cell. Its inputs are:

- `u`: current multigrid correction variables.
- `free`: coefficient/free-data array.
- `idx`: inverse grid spacing.
- `fd_stencil`: base derivative stencil selector.
- `div_ahat_stencil`: outer stencil used for $D_j \hat{A}^{ij}$.

7.1 Geometry Helpers

- `MetricInverse()` computes $\bar{\gamma}^{ij}$.
- `Christoffel<NGHOST>()` computes $\bar{\Gamma}^i_{jk}$ using centered finite differences of the conformal metric.
- `RicciScalar<NGHOST>()` computes $\bar{R}$ from first and second finite differences of $\bar{\gamma}_{ij}$.
- `DxTotal()`, `DxxTotal()`, and `DxyTotal()` differentiate base-plus-correction quantities.

7.2 $\hat{A}^{ij}$

`AHatUU<NGHOST>()` computes:

$$\hat{A}^{ij} = \frac{\bar{u}_{TF}^{ij} + (\bar{L}\beta)^{ij}}{2\alpha}.$$

The implementation recomputes the Christoffels and $\partial_i \beta^j$ at the cell where $\hat{A}^{ij}$ is requested. `DxAHatUU()` then computes a centered finite-difference derivative of $\hat{A}^{ij}$ by sampling `AHatUU()` at neighboring cells.

7.3 Hamiltonian Residual

The implemented scalar residual is:

$$\bar{D}^2 \Psi - \frac{1}{8} \bar{R} \Psi + \frac{1}{8} \hat{A}_{ij} \hat{A}^{ij} \Psi^{-7} + 2\pi E \Psi^5 - \frac{1}{12} K^2 \Psi^5 - S = 0.$$

Here S is `ID_FREE_SOURCE`. In vacuum critical-Kerr tests, $E = S = 0$.

7.4 Momentum Residual

For each component i , the implemented residual is:

$$2\bar{D}_j \hat{A}^{ij} - \frac{4}{3} \Psi^6 \bar{D}^i K - 16\pi \Psi^6 P^i = 0.$$

$\bar{D}_j \hat{A}^{ij}$ is assembled from $\partial_j \hat{A}^{ij}$ plus Christoffel terms.

7.5 Stencil and Halo Selection

`z4c/spatial_order` maps to `fd_stencil` as:

$$2 \mapsto 2, \quad 4 \mapsto 3, \quad 6 \mapsto 4.$$

`NGHOST=2,3,4` in `finite_diff.hpp` gives 2nd, 4th, and 6th-order centered derivative formulas.

The $D_j \hat{A}^{ij}$ path is nested: an outer derivative samples $\hat{A}^{ij}$, and each $\hat{A}^{ij}$ evaluation contains inner derivatives of β^i and $\bar{\gamma}_{ij}$. The current required halo is:

$$n_{\text{ghost}}^{\text{required}} = (\text{fd_stencil} - 1) + (\text{div_ahat_stencil} - 1).$$

Therefore:

Spatial order	fd_stencil	order-matched div_ahat_stencil	required ghost cells
2	2	2	2
4	3	3	4
6	4	4	6

The current code now refuses to silently downshift `div_ahat_stencil` in auto mode. If the halo is too small, it asks for more ghost cells or an explicit lower-order fallback.

8 Smoothing Kernel

The smoother is in `SmoothImpl()` and is called by `IDCTSMultigrid::SmoothPack()`. The driver reads `id_solve/smoother`; the default is the original red-black, pointwise, diagonally preconditioned nonlinear relaxation:

$$u_v \leftarrow u_v - \omega \frac{\mathcal{F}_v(u) - \text{src}_v}{D_v}.$$

Here D_v is the approximate diagonal coefficient returned by `CTSOperator()`. The scalar equation uses a diagonal built from the centered Laplacian coefficient and local nonlinear derivatives. The shift equations use a diagonal approximation to the vector Laplacian-like principal part divided by α .

This diagonal mode has the following properties:

- The update is in-place and red-black colored.
- It does not solve a coupled local 4×4 Newton system for (Ψ, β^i) .
- It ignores off-diagonal Jacobian couplings between Ψ and β^i , and between shift components.
- It is therefore closer to an under-relaxed diagonal Newton/Jacobi-GS smoother.

The optional `smoother = newton_gs` path applies a coupled local Newton update at each active red/black point. At a fixed cell, it forms the local residual

$$R_v = \mathcal{F}_v(u) - \text{src}_v$$

for $v = (\Psi, \beta^x, \beta^y, \beta^z)$, builds a 4×4 Jacobian by finite differencing the full local CTS operator with respect to the four cell- centered unknowns, solves

$$J_{vw} \delta u_w = -R_v,$$

and updates $u \leftarrow u + \omega \delta u$. The finite-difference Jacobian uses a read-only local perturbed view of the solution, so neighboring threads never observe a temporary perturbation of the shared grid. If the local 4×4 solve is singular or ill-conditioned, the code falls back to the diagonal update at that cell.

The Newton-Gauss-Seidel option is closer to the relaxation described by East et al. (arXiv:1208.3473), because it keeps the in-place red-black Gauss-Seidel ordering but includes the local coupling among Ψ and the three shift components. It is still damped by ω ; for the current critical-Kerr CTS tests, $\omega = 1$ is too aggressive and small values such as $\omega \simeq 0.02$ remain safer.

Properties common to both smoother modes:

- The update is active only where `ID_FREE_MASK >= 0.5`.
- MeshBlock smoothing and root-octet smoothing use the same smoother mode.
- After each point update it floors Ψ at 10^{-8} .

The default/used solver controls are read in `IDCTSMultigridDriver::IDCTSMultigridDriver()`:

- `id_solve/omega`: relaxation factor.
- `id_solve/smoother`: `diagonal` (default) or `newton_gs`.
- `id_solve/ngs_iterations`: number of local Newton updates per smoothing visit when `smoother = newton_gs`.
- `id_solve/ngs_jacobian_eps`: relative perturbation used to finite-difference the local 4×4 Jacobian.

- `id_solve/ngs_max_update`: optional absolute limiter on each component update; 0 disables this limiter.
- `id_solve/npresmooth`, `id_solve/npostsmooth`: V-cycle smoothing counts.
- `id_solve/niteration`: fixed V-cycle budget when `threshold < 0`.
- `id_solve/threshold`: convergence threshold when nonnegative.
- `id_solve/full_multigrid`: optional FMG solve.
- `id_solve/keep_best_solution` and `id_solve/stop_on_defect_increase`: guards for unstable or over-relaxed runs.

9 Multigrid Solve Lifecycle

`IDCTSMultigridDriver::Solve()` does the following:

1. `PrepareForAMR()` constructs root-grid and octet bookkeeping.
2. Guards reject adaptive AMR and currently reject sixth-order CTS on SMR.
3. `owner_->BuildFreeData()` builds `u_free` and resets `u_cts`.
4. `mglevels_->LoadFinestData(owner_->u_cts, ...)` loads the correction initial guess.
5. `LoadSource(owner_->u_defect, ..., 0.0)` sets the source to zero. This makes the problem $F(u) = 0$ on the finest level; FAS modifies source arrays on coarser levels.
6. `LoadCoefficients(owner_->u_free, ...)` loads free-data coefficients into the multigrid coefficient arrays.
7. `RestrictCoefficients()` restricts free-data arrays down the block hierarchy.
8. `SetupMultigrid()` initializes levels, tasks, root grids, and octets.
9. `TransferCoefficientsFromBlocksToRoot()` populates root and octet coefficient storage.
10. Initial defect norms are computed with `CalculateDefectNorm()`.
11. The code runs FMG, thresholded V-cycles, or fixed-count V-cycles.
12. If accepted, `RetrieveResult()` copies the solved correction back into `owner_->u_cts`.
13. `owner_->ApplySolution()` reconstructs ADM and Z4c data.

10 Restriction, Prolongation, and Defect Norms

`src/multigrid/multigrid.cpp` provides the generic transfer operations:

- `RestrictPack()`: computes the defect and restricts it to the coarser source. It also restricts the current solution.
- `ProlongateAndCorrectPack()`: computes a coarse-grid correction and prolongates it to the next-finer solution.

- `FMGProlongatePack()`: direct FMG prolongation.
- `CalculateDefectNorm()`: computes L1/L2/Linf norms. The current L1 and L2 paths multiply by cell volume, so the L2 norm is volume-normalized after the driver scale factor is applied.

The V-cycle task lists in `src/multigrid/multigrid_tasks.cpp` perform boundary exchange before smoothing/restriction/prolongation, then call `PhysicalBoundary()` and `FillFCBoundary()` before using ghost cells.

11 Boundary Conditions

11.1 CTS Multigrid Boundary Conditions

The base multigrid constructor in `src/multigrid/multigrid_driver.cpp` initializes multigrid boundary conditions from the mesh:

- Periodic mesh faces remain periodic.
- Every non-periodic mesh face defaults to `mg_zerofixed`.

For the critical-Kerr input file, all mesh faces are `outflow`; therefore the CTS multigrid correction variables currently use `mg_zerofixed` on all six physical faces.

The physical boundary fill in `MultigridDriver::PhysicalBoundary()` and `MGRootBoundary()` implements:

- `mg_zerofixed`: odd reflection of the correction variable, approximately enforcing zero Dirichlet value at the boundary.
- `mg_zerograd`: even reflection, enforcing zero normal derivative.
- `periodic`: periodic copy.
- `mg_multipole`: multipole potential boundary support, inherited from gravity multigrid, but not currently exposed by `id_solve` input parameters.

Unlike the gravity driver, the CTS driver does not currently parse an `id_solve/mg_bc` override. So the practical choice today is: periodic if the mesh is periodic, otherwise zero-fixed corrections.

11.2 Coefficient and Coarse/Fine Boundaries

The free-data coefficients are loaded into multigrid coefficient arrays and restricted down levels. For SMR/octet handling:

- `TransferCoefficientsFromBlocksToRoot()` copies block coefficients to root cells or refined octets.
- Refined coefficient octets are restricted upward/downward as needed.
- Same-level octet neighbors copy boundary data.
- Coarse/fine octet boundaries use interpolation/prolongation helpers.
- Physical coefficient boundaries are filled by `ApplyCoefficientPhysicalBoundaries()` using Lagrange extrapolation for non-mask coefficients and direct copy for masks.

11.3 Z4c Boundary Conditions After Handoff

After `ApplySolution()` has written Z4c variables, the solve task refreshes Z4c boundaries:

1. `RestrictU()`
2. `SendU()`
3. `ClearSend()`
4. `ClearRecv()`
5. `RecvU()`
6. `Z4cBoundaryRHS()`
7. `ApplyPhysicalBCs()`
8. `Prolongate()`
9. `InitRecv()` again if evolution will continue

`Z4c::ApplyPhysicalBCs()` calls `pbval_u->Z4cBCs(...)` unless the mesh is strictly periodic, then optional user boundary conditions from the pgen. Thus, CTS solve boundary conditions and Z4c evolution boundary conditions are separate:

- CTS solves corrections with multigrid correction BCs.
- The resulting Z4c fields are then put through normal Z4c ghost exchange and physical BC machinery before evolution.

12 Applying the Solution

`IDConformalThinSandwich::ApplySolution()` is the handoff from elliptic variables to evolution variables.

At each active cell:

- Compute $\Psi = \text{base_psi} + \delta\Psi$, then Ψ^4 .
- Set physical ADM metric

$$\gamma_{ij} = \Psi^4 \bar{\gamma}_{ij}.$$

- Set `admvars.psi4` from $\Psi^4 \det(\bar{\gamma})^{1/3}$.
- Copy lapse from `ID_FREE_ALPHA`.
- Set physical shift

$$\beta^i = \beta_{\text{base}}^i + \delta\beta^i.$$

- Recompute $\hat{A}^{ij}$ from the solved shift.
- Lower $\hat{A}^{ij}$ with the conformal metric and reconstruct

$$K_{ij} = \Psi^{-2} \hat{A}_{ij} + \frac{1}{3} \gamma_{ij} K.$$

Then `ApplySolution()` calls:

1. `ADMTToZ4c<fd>()`: populate Z4c evolution variables.
2. `Z4cToADM()`: make the ADM diagnostic view consistent with Z4c.
3. `ADMConstraints<fd>()`: compute constraint diagnostics on the active region.

Finally, `SolveTask()` performs the boundary refresh described above and recomputes constraints one more time on the boundary-consistent state.

13 Current Critical-Kerr Input Choices

In `inputs/z4c/gw_collapse/z4c_critical_kerr_formation.athinput`, the current representative setup is:

- Mesh BCs: `outflow` on all faces.
- ADM dynamic: `true`.
- Z4c spatial order: 4, so `fd_stencil=3`.
- CTS enabled and solve-once.
- `omega=0.02` in the file, though convergence sweeps found `omega=0.03` useful for stable second-order native CTS runs.
- `smoother=diagonal` by default. Set `smoother=newton_gs` to use the coupled local Newton-Gauss-Seidel relaxation.
- `threshold=-1.0`: fixed V-cycle count mode.
- `niteration=1` in the input file; convergence tests override this.
- `npresmooth=2`, `npostsmooth=2`.
- `mg_nghost=4`, `div_ahat_stencil=3`: order-matched for 4th order. For 6th order, use `mesh/nghost=6` and `id_solve/mg_nghost=6`.
- `reject_worse=false`, `keep_best_solution=true`.

14 Known Implementation Caveats

- The default smoother remains the diagonal approximate Newton smoother for continuity with previous runs. The optional `newton_gs` smoother solves a local coupled 4×4 Newton system, but it is still under-relaxed and currently builds the Jacobian by finite differences rather than analytic derivatives.
- The matter-source convention in the residual uses $E\Psi^5$ and $P^i\Psi^6$. In vacuum this is irrelevant, but for matter runs the intended conformal scaling should be documented or corrected.
- `ApplySolution()` currently copies `ID_FREE_ALPHA` directly to `admvars.alpha`. If `ID_FREE_ALPHA` is interpreted as the CTS conformal lapse $\tilde{\alpha}$, the physical lapse would require additional conformal scaling.
- The CTS driver does not yet expose an `id_solve/mg_bc` input override. Boundary control is inherited from mesh periodicity/nonperiodic defaults.
- Sixth-order CTS on SMR is explicitly guarded off because the current octet coarse/fine bridge is not widened enough for the required stencil.

15 Where to Start Reading

A good code-reading order is:

1. `src/z4c/id_solve.hpp`: understand variable enums and class layout.
2. `src/pgen/z4c_critical_kerr_formation.cpp`: see how the seed data are constructed.
3. `src/z4c/z4c_tasks.cpp`: see where the solve is queued.
4. `src/z4c/id_solve.cpp`, starting with: `IDConformalThinSandwich::SolveTask()`, `IDCTSMultigridDriver::BuildFreeData()`, `CTSOperator()`, `SmoothImpl()`, and `ApplySolution()`.
5. `src/multigrid/multigrid_driver.cpp` and `src/multigrid/multigrid_tasks.cpp`: see how V-cycles, red/black smoothing, and boundary exchanges are scheduled.
6. `src/z4c/z4c_adm.cpp`: see the ADM/Z4c conversion and constraint diagnostics.