


# Social Network Analysis Day 1

Advanced Winter School in  
Computational Social Science 2025

Carl Nordlund  
Maël Lecoursonnais  
Kazuki Sakamoto






# Day 1: Friday 5<sup>th</sup> Dec

---

- Introduction to module
- Relational thinking and research design
- Communities and other cohesive subgroups
- Role structures and blockmodeling
- Lab details



# Day 2:

## Monday 8<sup>th</sup> Dec

---

- Comparing networks (QAP)
- Network null models: rewiring, configuration models, backboning
- Simulations
- Relations and nodal attributes: introduction to network dynamics
- Research design considerations

# Social Network Research Design component

Available on the Winter  
CSS Github!

Read through these  
papers before Monday  
8<sup>th</sup> December!

Put special focus on their research  
design!

- Research questions
- Data and operationalization
- Methods

Special focus  
One paper/student

## Three papers

- Gerbrands P, Unger B, Getzner M, et al. (2022) The effect of anti-money laundering policies: an empirical network analysis. *EPJ Data Sci.* 11, 15. <https://doi.org/10.1140/epjds/s13688-022-00328-8>
- Thiemann C, Theis F, Grady D, Brune R, Brockmann D (2010) The Structure of Borders in a Small World. *PLoS ONE* 5(11): e15422. <https://doi.org/10.1371/journal.pone.0015422>
- Yang Y, Chawla N V, Uzzi B (2019) A network's gender composition and communication pattern predict women's leadership success. *PNAS*, 116(6), pp. 2033-2038. <https://www.pnas.org/cgi/doi/10.1073/pnas.1721438116>



# Paper assignments

Name	Paper
Great Uchechukwu Udochi	Gerbrands et al
Yevhen Voronin	Thiemann et al
Lu Yan	Yang et al
Ratna Aini Hadi	Gerbrands et al
Carlos Villalobos	Thiemann et al
Clara Englert	Yang et al
Bulin Li	Gerbrands et al
Eric Ngo	Thiemann et al
Leon Klingborg	Yang et al
Jasper Darin	Gerbrands et al
Landry Botokou	Thiemann et al
Milos Milovanovic	Yang et al
Florencia Piñeyrúa	Gerbrands et al



# Aim and Purpose


- Introduction to network thinking
- Get gears running
  - Seeing networks
  - Foundational tools/starters
  - Pave the way forward (RQs, more advanced methods)
- Limitations
  - Only 2 days
  - First principles assumed
  - More structural (less attributional)
  - Much more in the SNA toolbox





Some repetition and  
recognition from CSS  
Summer school

# Relational vs attributional data

- Entities: actors / nodes / vertices (here: social ones, e.g. individuals)
- Actor attributes (“traditional” data table)
- Relations: data *between* entities (e.g. friendship, kinship, shared affiliations)




Label	Age	Income	Education	Gender
A	35	40k	BSc	Male
B	20	30k	MA	Female
C	41	42k	n/a	Female
D	52	53k	n/a	Male
E	21	34k	MA	Male
F	56	28k	PhD	Female



Friendship (reciprocated) [matrix-format]

	A	B	C	D	E	F
A	-	1	1	1	0	0
B	-	-	0	1	0	0
C	0	-	-	1	0	0
D	1	1	-	-	1	0
E	0	0	1	-	-	1
F	0	0	0	0	1	-



# Relational data

- Capturing the in-between
- Inter-dependence of observations
  - Removing a 'data point' can have grand implications
- Sampling typically problematic
  - System boundaries for full populations important
- Supplementing 'conventional' (attributional) data


Ethical considerations!

## The Robins reminders

- Incorporating network data and metrics far more than a mere methodological extension
- Explicit theoretical commitments about structure and dependence: *that the in-between matters!*
- Going beyond *Hobbesession* with individual, assumedly independent entities to understand social world

### Friendship (reciprocated) [matrix-format]

	A	B	C	D	E	F
A	-	1	1	1	0	0
B	1	-	0	1	0	0
C	1	0	-	1	0	0
D	1	1	1	-	1	0
E	0	0	0	1	-	1
F	0	0	0	0	1	-





# Understanding high-school student performance



Classes of high-school students

Understanding drivers behind performance

Variables (attributes)

- Grades, test scores
- Gender
- Ethnicity
- Parents' education, SES
- Previous grades
- Eye sight (!)

Relational data

- Friendship (self-reported)
- Social interaction (observed)
- Antagonism
- Kinship (siblings)
- Note-borrowing
- Residential neighbors

Affiliation (2-mode) data

- Student clubs/associations
- Sports/hobbies
- Spoken languages

# National economic development



## Nations as units

- Population
- GDP/capita
- Gini coefficients
- Sectorial employment
- Value-added (creation, trade-in)
- Main exports/imports
- Trade agreements
- Organizational memberships
- Labor demographics
- R & D expenditure

## Relational data

- Bilateral trade flows (aggregated)
- Bilateral trade flows (detailed)
- Geographical contiguity
- Trade envoys
- Sanctions, boycotts and military conflicts
- Cultural exchange
- Airline traffic, other infrastructure

## Affiliation (2-mode) data

- Trade/treaty agreements
- Organizational memberships

# Becoming a (soccer) hooligan



## Individuals as units

- Gender
- Age
- Ethnicity
- Interests
- School grades
- Substance abuse
- Family situation
- Employment
- Criminal records

## Relational data

- Social exposure
- Peer influence
- Friendships (various domains)
- Rivalry and antagonism

## Affiliation (2-mode) data

- Trade/treaty agreements
- Organizational memberships

# Employee productivity




## Individuals as units

- Age
- Education
- Job title
- Salary
- Health care plan
- Tasks completed
- Evaluations
- Skills

## Relational data

- Organizational structure (formal)
- Organizational structure (actual!)
- Information flows (individuals and units)
- Inter-personal ties
  - Friendship
  - Antagonism
  - Reports-to
  - Advice-seeking



# Popular Norrköping museums



## Venues

- Daily visitors
- Type (art, history, contemporary, gallery)
- Entry cost
- Opening hours
- Popularity
- Time spent
- Media mentions
- Online reviews

## Relational data

- Road network (betweenness centrality etc.)
- Mobility flows (“bilateral” pedestrians)
- Collaborations with other venues

## Affiliation (2-mode) data

- Co-visits (individuals vs. venue)
- Media mentions (as 2-mode)

# Relational turn → Novel questions and theory

## Novel theoretical considerations

- From endogenous to exogenous explanations
- Interplay of attributional and relational variables
- Going beyond '*Hobbesession*' of assumed independent atomic units

## Are relations relevant?

- Contextual
- Certain theoretical frameworks purely relational/attributional
- E.g. post-war development studies:
  - **Modernization school**  
Harrod-Domar domestic capital formation, national policy, stages of economic development
  - **Dependency/world-system tradition**  
External constraints, power-relations, delinking, development of underdevelopment etc







# Reasons for network analysis

- To understand how individuals in certain social position have different individual outcome
- To understand how individuals affect social structure
- To facilitate this: (as always) intricate interplay between:
  - Research question
  - Data
  - Methods
  - Theory



Robins (2015), *Doing Social Network Research: Network-based Research Design for Social Scientists*



# Social groups and communities

- Social group: core notion in sociology and social sciences
  - Where we influence each other
  - Reflecting homophily
  - Development of group norms and standards
- Groups typically defined relationally
  - Could of course also be based on attributes



# Communities (aka cohesive subgroups)


- The shared relational notion of cohesive subgroup
  - A subset of actors/nodes that are more connected to others within the set than what they are with the outside
- As notion of social group is quite generic
  - Many possible definitions of cohesive subsets
  - A plurality of operationalizations that reflects a plurality of conceptualizations (e.g. Freeman (1992) on the sociological concept of group)
- Let's explore some of these classical types of cohesive subgroups



## Meso-level statistics:

# Cliques

- A maximal complete subgraph of 3 or more actors, where...
  - All actors are connected to each other
  - No other actors that are equally connected to all actors in the clique
- A network typically consists of a lot of cliques of various sizes (particularly triads, i.e.  $n=3$ )
- These cliques often overlap each other
- A clique of size 4 contains several cliques of size 3, but the latter ones ignored (see above)






## Meso-level statistics:

# Cliques: Little League TI

- Igraph function: `max_cliques()`
- 8 cliques
  - 4 cliques of size 4 (marked in red)
    - Tom\_\_2, Ron\_\_1, Frank\_3, Boyd\_4
    - Tom\_\_2, Ron\_\_1, Frank\_3, Darrin\_11
    - Frank\_3, Ron\_\_1, Tim\_\_5, Boyd\_4
    - Tom\_\_2, Sandy\_9, Jay\_\_8, Jeff\_7
  - 4 cliques of size 3
    - Arnie\_13, Tim\_\_5, John\_6
    - John\_6, Jerry\_10, Ben\_12
    - Ron\_\_1, Jerry\_10, Darrin\_11
    - Ron\_\_1, Jerry\_10, Ben\_12
- Note that there are more triads inside the cliques of size 4, but as they are within larger cliques, they are not maximum cliques








## Meso-level statistics: n-cliques

- A clique requires that each node is maximum one edge away from all others
- The n-clique relaxes this
- An n-clique is a maximum subgraph where distances between all pairs of nodes is no more than n
- Maximum: there can be no other additional node
- When  $n=1$ : standard clique
- Varieties:
  - n-clan  
Additional condition: max diameter no longer than n
  - n-club



Example of 2-cliques (there are more)






- Maximal subgraph with  $n$  nodes in which each node is adjacent to no fewer than  $(n-k)$  nodes in subgraph
- Introduced in Seidman & Foster (1978)
- Ignores self-ties
- A clique is a 1-plex
- Testing hypothetical 3-plex (figure to the right)
  - $n=8$
  - Max 3 missing ties (including self-tie)
  - Must have ties to no fewer than 5 in subgroup
  - 'can' only has 4 within-group ties: this is not a 3-plex!

[illegible]



# Meso-level statistics: Communities


- A plethora of SNA-style cohesive subgroup definitions
- From network science: a more practical and generic take on cohesive subgroups
- ‘Community’ instead of ‘cohesive subgroup’
- Less contextual, yet widely used among social scientists as well
- References:
  - Newman & Girwan (2004)
  - Vincent et al (2008)
  - Clauset, Newman & Moore (2004)
  - Coscia et al (2011)
  - Peel et al (2017)
- Most using notion of modularity to measure separation of groups, but different heuristics to get there





## Meso-level statistics: Newman-Girwan edge betweenness


- Recall betweenness centrality: captures how often node is on shortest path between all pairs of nodes
- Edge betweenness: how often an edge (relation) is on shortest path between all pairs of nodes
- Reasonable that edges with a high edge betweenness are those between communities!
- Newman-Girwan heuristic:
  - Calculate edge betweenness for all edges
  - Remove edges with highest edge betweenness
  - Evaluate how well-separated potential communities are
- Evaluation based on notion of modularity





# Meso-level statistics: Modularity


- Measures how well-separated communities are
- Given a partition of nodes into distinct non-overlapping sets
- Modularity reflects the fraction of edges within such sets, minus the expected fraction of edges if they were distributed randomly
- In-build null model consideration  
Clauset, Newman & Moore (2004)





## Meso-level statistics: Newman-Girwan edge betweenness


- Identifying communities using the Newman-Girwan edge betweenness heuristic
- 4 communities identified
- Modularity: 0.285 (not that high)





# Meso-level statistics: Louvain heuristic

- Search algorithm to maximize modularity
- Starts with each node as community of its own (singleton)
- Vertices merged when this increases modularity (searching for optimal merge)
- Stops when either single community or no longer possible to increase modularity
- From Blondel, Guillaume, Lambiotte & Lefebvre (2008)
- 3 communities identified
- Modularity: 0.307








## Meso-level statistics: Fast and greedy heuristic


- Fast search algorithm
- Particularly for large networks
- From Clauset, Newman & Moore (2004)
- 3 communities identified
- Modularity: 0.294






# Meso-level statistics: Optimal modularity

- Naïve search algorithm
- Tests all possible partitions
- Only viable for small networks
- Guaranteed to find partition with highest modularity
- 3 communities identified
- Modularity: 0.307
- Identical to what was found with Louvain!



Optimal







# Meso-level statistics: Communities: interpretational aspects

- So which one to pick?
- Different approaches potentially yields different partitions
- Not always finding most optimal (w.r.t. modularity)
- And is modularity all we need to evaluate community structures in all contexts?
- Peel et al (2017):
  - Seldom a ground truth in community detection
  - No Free Lunch Theorem: “There can be no algorithm that is optimal for all possible community detection tasks”
- Coscia et al (2011): Classification of methods for community detection


Edge betweenness (mod=0.032)




Louvain (mod=0.167)



Fast greedy (mod=0.161)




Optimal (mod=0.167)




# Structures vs. attributes

- Do observed communities reflect nodal attributes?
- Introducing the EIES example data
  - 32 scholars attending an early SNA conference
  - Reported acquaintances (directional, Likert 1-4)
  - Disciplinary backgrounds: Sociology (17), Anthropology (6), Mathematics (3), Other (6)
- Dichotomized ( $\geq 2$ ) and min-symmetrized
- Pre-conference (also data for post-conference)
- You will explore communities in this network in the lab today!




# Structures vs. attributes

- Finding some communities in this data
- Do observed communities reflect nodal attributes?
- Ocular inspection:
  - Sociologists indeed seem to stick together
  - Anthropologists as well
  - Maths and Others more dispersed
- But to properly test for assortative mixing, we instead start off with the attributes
- Using assortativity coefficient of Newman (2003) most viable
- High coefficient: connected nodes tend to share same (nominal) attribute



# Structures vs. attributes

- Igraph: assortativity\_nominal()
- Assortativity coefficient = 0.106
- So slight assortative mixing, but not much!
- In visualization, it indeed looks like a lot of sociologists hanging together
- But bear in mind: many sociologists
  - Quite likely that they would mix by chance as well







# Social roles

- Early 1970s, sociologists thought about the notion of social role
- Harrison White: can this be defined in a purely relational form?
- Society IS social structure
  - Multiplex network of inter-personal relations
- Roles and identities in society are “reciprocally defined”
- Only emerging in the interactions

Conceptual notions of role and position

# At a hospital

- Four types of actors:
  - Doctors
  - Nurses
  - Admins
  - Patients
- Different roles, as reflected in their interaction patterns:
  - Doctors relate to each other, and to patients
  - Nurses relate to doctors, patients and admins
  - Admins relate to patients
  - Patients relate to all, but not other patients



## Conceptual notions of role and position

# Schools

---

- Three types of actors:
  - Kids
  - Teachers
  - Parents
- Different roles, as reflected in their interaction patterns:
  - Parents within a family relate to each other, and to some other parents
  - Parents relate to their own kids, not to other kids
  - Teachers relate to all kids, some parents, some teachers
  - Kids relate to other kids



# Conceptual notions of role and position

## Patterns of relations

- Seemingly overlap between actor attributes and relational patterns
- Relations not necessarily reflecting cohesive subgroups
  - Patients visiting a hospital have no functional relations with other patients
  - Parents might interact with other parents, but not necessarily
- Being a teacher, parent, doctor etc thus seems to associate with certain relational patterns
  - ...that might or might not be cohesive subgroups
- Role analysis and blockmodeling: tools for identifying specific roles on the basis of relational patterns





# Conceptual notions of role and position

## Patterns of relations

### Role-analysis:

- Identifying sets of nodes that share similar relational patterns
  - Notion of being (structurally) equivalent
- i.e. on the basis of relational patterns alone
- Mapping the overarching patterns of relations between such identified sets of equivalent nodes

### Blockmodeling:


- The quintessential technique for role analysis






- 

[illegible]

[illegible]






## Regular equivalence blockmodeling

[illegible]



# Meso-level statistics: Role-analysis and blockmodeling



- As each of these blocks perfectly match an ideal block type, we can ‘collapse’ the blockmodel into a so-called blockimage – or an image graph
- Nodes in the image graph now represent positions (i.e. subsets of equivalent actors)
- The blockimage and image graph thus captures the underlying anatomy of the network
- In this case, this corresponds to a core-periphery network
- Roles:
  - Role of P1 is to be connected to others in P1, and having sporadic ties to and from P2
  - Role of P2 is to have no ties to others in P2, and singular ties to P1

		P1				P2								
		a	g	k	c	l	f	i	b	e	h	m	j	d
P1	a		1	1	1	1	1	0	0	0	0	0	0	0
	g	1			1	1	0	0	1	0	0	0	0	0
	k	1	1		1	0	0	0	0	1	1	0	0	0
	c	1	1	1		0	0	0	0	0	0	1	1	1
P2	l	1	0	0	0		0	0	0	0	0	0	0	0
	f	1	0	0	0	0		0	0	0	0	0	0	0
	i	0	1	0	0	0	0		0	0	0	0	0	0
	b	0	1	0	0	0	0	0		0	0	0	0	0
	e	0	0	1	0	0	0	0	0		0	0	0	0
	h	0	0	1	0	0	0	0	0	0		0	0	0
	m	0	0	0	1	0	0	0	0	0	0		0	0
	j	0	0	0	1	0	0	0	0	0	0	0		0
	d	0	0	0	1	0	0	0	0	0	0	0	0	

1	1	1	1	1
1	1	1	1	1
1	1	1	1	1
1	1	1	1	1
1	1	1	1	1


The complete block (com)

0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0

The null block (nul)

1	0	1	0	0
0	0	0	1	0
0	1	0	0	1
0	0	0	0	0
0	0	0	0	0

The regular block (reg)




	P1	P2
P1	com	reg
P2	reg	nul



# Meso-level statistics: Role-analysis and blockmodeling

## Why blockmodeling and role-analysis?

- A blockmodel reduces a complex network into its fundamental structure (functional anatomy)
- In the Galtung network, we (obviously) find an ideal core-periphery structure
- For a network many times the size, the same block image would appear
- Allows for comparing complex networks that might differ in size, context, distributions



		P1				P2											
		a	g	k	c	l	f	l	b	e	h	m	j	d			
P1	a		1	1	1	1	1	0	0	0	0	0	0	0			
	g	1		1	1	0	0	1	1	0	0	0	0	0			
	k	1	1		1	0	0	0	0	1	1	0	0	0			
	c	1	1	1		0	0	0	0	0	0	1	1	1			
P2	l	1	0	0	0		0	0	0	0	0	0	0	0			
	f	1	0	0	0	0		0	0	0	0	0	0	0			
	l	0	1	0	0	0	0		0	0	0	0	0	0			
	b	0	1	0	0	0	0	0		0	0	0	0	0			
	e	0	0	1	0	0	0	0	0		0	0	0	0			
	h	0	0	1	0	0	0	0	0	0		0	0	0			
	m	0	0	0	1	0	0	0	0	0	0		0	0			
	j	0	0	0	1	0	0	0	0	0	0	0		0			
	d	0	0	0	1	0	0	0	0	0	0	0	0				




	P1	P2
P1	com	reg
P2	reg	nul



## Meso-level statistics: Role-analysis and blockmodeling

- Galtung example turned out to be a core-periphery structure
- There are a multitude of other possibilities
  - Hierarchies
  - Transitive structures
  - Cohesive subgroups
  - Something very specific
- An ideal community structure is a special case (one possible outcome) of blockmodeling
- So: NOT EXPLICITLY looking for community structure, OR core-periphery structure
  - Rather: look for regularities in relational patterns
  - ...which COULD be a community structure, a core-periphery structure, or something different



	P1	P2	P3
P1	com	nul	nul
P2	nul	com	nul
P3	nul	nul	com



# Meso-level statistics:

## Types of equivalences

What is meant by equivalence in a network?

Different notions and usages exist

### Structural equivalence

- Two actors are structurally equivalent if they have identical sets of ties to the other actors
- Ideal blocks: complete and null blocks

### Regular equivalence

- Two actors are regular equivalent if they have ties to actors that in turn are also regular equivalent (!)
- Ideal blocks: null and regular blocks

1	1	1	1	1
1	1	1	1	1
1	1	1	1	1
1	1	1	1	1
1	1	1	1	1

	1	1	1	
1			1	1
1	1			1
1	1	1		

0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0

	0	0	0	
0			0	0
0	0			0
0	0	0		

1	0	1	0	0
0	0	0	1	0
0	1	0	0	1
0	0	1	0	0

	1	1	0	
1			1	0
0	0			1
0	1	0		

0	0	0	0	0
0	0	0	0	0
0	0	0	0	0
0	0	0	0	0




	0	0	0	
0			0	0
0	0			0
0	0	0		



# Meso-level statistics:

## Types of equivalences



- In the Galtung example, we managed to perfectly fit the network to ideal blocks – and on first attempt!
- Real-world networks are more messy
- Even our small example networks can be messy!
- The ambition with blockmodeling: find the best possible fit
- Two broad approaches for partitioning a network into equivalent positions
  - Direct methods
  - Indirect methods
  - (And also hypothesis testing)





# Meso-level statistics: Direct blockmodeling

- Starts with a random starting partition for a specified number of positions
- Local optimization search algorithm to move/swap actors between positions
- Using goodness-of-fit (criteria) function to evaluate resulting blockmodels
- Actual block image can be pre-specified (e.g. if explicitly searching for a core-periphery structure)
- Can also be flexible: then testing all available ideal blocks
- Typical goodness-of-fit measures
  - Hamming distances (number of inconsistencies)
  - (Weighted) correlation coefficients (also for valued networks)



com?			
✓	✓	✗	✗
✓	✗	✗	✗

pen=5

nul?			
✗	✗	✓	✓
✗	✓	✓	✓

pen=3

reg?			
✓	✓	✗	✗
✓		✗	✗

pen=4

## Advantage:

Deemed better

Allows for capturing complicated ideal blocks  
(generalized blockmodeling)

## Disadvantage:

Computationally heavy

Potentially finding local minima





# Meso-level statistics: Indirect blockmodeling


- Starts by calculating/determining a suitable indirect measure of equivalence
- Most often structural equivalence
- This results in a new (dis)similarity matrices indicating how structurally equivalent each pair of nodes is
- Apply hierarchical clustering
- Choose suitable number of positions
- Create and interpret blockmodel

## Advantage:

Works for large networks  
Analytical, not computational

## Disadvantage:

Restricted to certain notions of equivalence  
Generalized blockmodeling: nope!  
Lots of choices in the analysis



	Ron__1	Tom__2	Frank_3	Boyd_4	Tim__5	John_6	Jeff_7	Jay__8	Sandy_9	Jerry_10	Darrin_11	Ben_12	Arnie_13
Ron__1		0	1	1	1	0	0	0	0	0	0	0	0
Tom__2	1		1	0	0	0	0	0	0	0	1	0	0
Frank_3	1	0		1	0	0	0	0	0	0	1	0	0
Boyd_4	1	1	1		0	0	0	0	0	0	0	0	0
Tim__5	1	0	1	1		0	0	0	0	0	0	0	0
John_6	0	0	0	0	1		0	0	0	0	0	1	1
Jeff_7	0	1	0	0	0	0		1	1	0	0	0	0
Jay__8	0	1	0	0	0	0	1		1	0	0	0	0
Sandy_9	0	1	0	0	0	0	1	1		0	0	0	0
Jerry_10	1	0	0	0	0	1	0	0	0		0	0	0
Darrin_11	1	1	0	0	0	0	0	0	0	1		0	0
Ben_12	1	0	0	0	0	1	0	0	0	1	0		0
Arnie_13	0	0	0	0	1	1	0	0	0	0	0	0	



# Meso-level statistics: Indirect structural equivalence

## Structural equivalence

- That two actors have the same relational patterns to the other actors
- Let's pick two actors – Tom\_2 and Frank\_3 – and look at their respective rows and columns:

Rows:

Tom_2	1	1	0	0	0	0	0	0	0	0	1	0	0
Frank_3	1	0	1	0	0	0	0	0	0	0	1	0	0

Columns:

Tom_2	0	0	1	0	0	1	1	1	0	1	0	0
Frank_3	1	1	1	1	0	0	0	0	0	0	0	0

✓ 14  
✗ 7(+1)

- Ignore self-ties
- Check for reciprocity (once)

	Ron__1	Tom__2	Frank_3	Boyd_4	Tim__5	John_6	Jeff_7	Jay__8	Sandy_9	Jerry_10	Darrin_11	Ben_12	Arnie_13
Ron__1		0	1	1	1	0	0	0	0	0	0	0	0
Tom__2	1		1	0	0	0	0	0	0	0	1	0	0
Frank_3	1	0		1	0	0	0	0	0	0	1	0	0
Boyd_4	1	1	1		0	0	0	0	0	0	0	0	0
Tim__5	1	0	1	1		0	0	0	0	0	0	0	0
John_6	0	0	0	0	1		0	0	0	0	0	1	1
Jeff_7	0	1	0	0	0	0		1	1	0	0	0	0
Jay__8	0	1	0	0	0	0	1		1	0	0	0	0
Sandy_9	0	1	0	0	0	0	1	1		0	0	0	0
Jerry_10	1	0	0	0	0	1	0	0	0		0	0	0
Darrin_11	1	1	0	0	0	0	0	0	0	1		0	0
Ben_12	1	0	0	0	0	1	0	0	0	1	0		0
Arnie_13	0	0	0	0	1	1	0	0	0	0	0	0	

- Structural equivalence dissimilarity for Tom\_2 and Frank\_3 is 8
- Repeat for all pairs to create dissimilarity matrix




# Meso-level statistics: Indirect structural equivalence

- Start off with actual network
- Calculate indirect measure of structural equivalence
  - Here, using Hamming distance dissimilarity (number of inconsistencies)
- Apply clustering algorithm to identify structurally equivalent actors
  - Here, using (unweighted) average-link clustering

	Ron_1	Tom_2	Frank_3	Boyd_4	Tim_5	John_6	Jeff_7	Jay_8	Sandy_9	Jerry_10	Darrin_11	Ben_12	Arnie_13
Ron_1		0	1	1	1	0	0	0	0	0	0	0	0
Tom_2	1		1	0	0	0	0	0	0	0	1	0	0
Frank_3	1	0		1	0	0	0	0	0	0	1	0	0
Boyd_4	1	1	1		0	0	0	0	0	0	0	0	0
Tim_5	1	0	1	1		0	0	0	0	0	0	0	0
John_6	0	0	0	0	1		0	0	0	0	0	1	1
Jeff_7	0	1	0	0	0	0		1	1	0	0	0	0
Jay_8	0	1	0	0	0	0	1		1	0	0	0	0
Sandy_9	0	1	0	0	0	0	1	1		0	0	0	0
Jerry_10	1	0	0	0	0	1	0	0	0		0	0	0
Darrin_11	1	1	0	0	0	0	0	0	0	1		0	0
Ben_12	1	0	0	0	0	1	0	0	0	1	0		0
Arnie_13	0	0	0	0	1	1	0	0	0	0	0	0	




	Ron_1	Tom_2	Frank_3	Boyd_4	Tim_5	John_6	Jeff_7	Jay_8	Sandy_9	Jerry_10	Darrin_11	Ben_12	Arnie_13
Ron_1		11	5	6	8	10	15	15	15	9	10	13	11
Tom_2	11		8	9	10	14	8	8	8	8	7	10	11
Frank_3	5	8		3	6	13	12	12	12	9	7	9	10
Boyd_4	6	9	3		5	12	9	9	9	8	5	8	9
Tim_5	8	10	6	5		9	11	11	11	8	9	6	6
John_6	10	14	13	12	9		11	11	11	7	11	6	3
Jeff_7	15	8	12	9	11	11		0	0	9	8	9	8
Jay_8	15	8	12	9	11	11	0		0	9	8	9	8
Sandy_9	15	8	12	9	11	11	0	0		9	8	9	8
Jerry_10	9	8	9	8	8	7	9	9	9		6	3	5
Darrin_11	10	7	7	5	9	11	8	8	8	6		5	8
Ben_12	13	10	9	8	6	6	9	9	9	3	5		3
Arnie_13	11	11	10	9	6	3	8	8	8	5	8	3	





## Meso-level statistics: Indirect structural equivalence



- Examine dendrogram of hierarchical clustering (complete-link here)
- Identify suitable partition
  - P1:  
Tom\_2, Jeff\_7, Jay\_8, Sandy\_9, Darrin\_11
  - P2:  
Ron\_1, Frank\_3, Boyd\_4, Tim\_5
  - P3:  
John\_6, Jerry\_10, Ben\_12, Arnie\_13,



# Meso-level statistics: Indirect structural equivalence

- Back to original matrix
- Sort according to identified partitions
- For binary blockmodels, calculating block densities can be useful
- Ideally, block densities should be close to 0 (null) or 1 (complete)


- Not very “crisp” densities
- Community structure (com on diagonal)
- Inconsistencies: 27 (quite high)
  - Which explains why we have uncertain densities

	Ron_1	Tom_2	Frank_3	Boyd_4	Tim_5	John_6	Jeff_7	Jay_8	Sandy_9	Jerry_10	Darrin_11	Ben_12	Arnie_13
Ron_1		0	1	1	1	0	0	0	0	0	0	0	0
Tom_2	1		1	0	0	0	0	0	0	0	1	0	0
Frank_3	1	0		1	0	0	0	0	0	0	1	0	0
Boyd_4	1	1	1		0	0	0	0	0	0	0	0	0
Tim_5	1	0	1	1		0	0	0	0	0	0	0	0
John_6	0	0	0	0	1		0	0	0	0	0	1	1
Jeff_7	0	1	0	0	0	0		1	1	0	0	0	0
Jay_8	0	1	0	0	0	0	1		1	0	0	0	0
Sandy_9	0	1	0	0	0	0	1	1		0	0	0	0
Jerry_10	1	0	0	0	0	1	0	0	0		0	0	0
Darrin_11	1	1	0	0	0	0	0	0	0	1		0	0
Ben_12	1	0	0	0	0	1	0	0	0	1	0		0
Arnie_13	0	0	0	0	1	1	0	0	0	0	0	0	

		P1					P2				P3			
		Tom_2	Jeff_7	Jay_8	Sandy_9	Darrin_11	Ron_1	Frank_3	Boyd_4	Tim_5	John_6	Jerry_10	Ben_12	Arnie_13
P1	Tom_2		0	0	0	1	1	1	0	0	0	0	0	0
	Jeff_7	1		1	1	0	0	0	0	0	0	0	0	0
	Jay_8	1	1		1	0	0	0	0	0	0	0	0	0
	Sandy_9	1	1	1		0	0	0	0	0	0	0	0	0
	Darrin_11	1	0	0	0		1	0	0	0	0	1	0	0
P2	Ron_1	0	0	0	0	0		1	1	1	0	0	0	0
	Frank_3	0	0	0	0	1	1		1	0	0	0	0	0
	Boyd_4	1	0	0	0	0	1	1		0	0	0	0	0
	Tim_5	0	0	0	0	0	1	1	1		0	0	0	0
P3	John_6	0	0	0	0	0	0	0	0	1		0	1	1
	Jerry_10	0	0	0	0	0	1	0	0	0	1		0	0
	Ben_12	0	0	0	0	0	1	0	0	0	1	1		0
	Arnie_13	0	0	0	0	0	0	0	0	1	1	0	0	

	P1	P2	P3
P1	0.55	0.15	0.05
P2	0.10	0.83	0.00
P3	0.00	0.25	0.50

	P1	P2	P3
P1	com	nul	nul
P2	nul	com	nul
P3	nul	nul	com



The image shows a screenshot of the **socnet.se** website and a terminal window. The website header includes links for **socnet.se**, **Download**, **Documentation**, and **nordint.net**. The main heading is **socnet.se: The blockmodeling console app (Win/Linux/Mac)**. Below this, it states the **Current version: Version 1.1 (October 2023)** with a **Download page >>** link. The text describes Socnet as a free CLI-based software client for doing blockmodeling analysis of networks, developed in C# .Net, available as self-contained binaries for Windows, MacOS and Linux. It mentions that Socnet runs as a console/terminal app where specific commands are used to load networks, view results, and save them. A small image of a coral-like network structure is shown. The terminal window shows the command `socnet.exe -i` being executed, resulting in the following output:

```
socnet.exe -i
Socnet - Network analysis in C#
=====
Version 1.1 (October 2023)
Developed by Carl Nordlund - carl.nordlund@liu.se
Socnet.se was supported by NordForsk through the funding to The Network Dynamics of Ethnic Integration, pr
oject number 105147
Nordint.net: https://nordint.net

How to cite Socnet.se:
Nordlund, C. (2023). Socnet.se: The Blockmodeling Console App [computer software]. Available from https://
socnet.se
How to cite specific methods, type in 'citeinfo()'.

Entering interactive mode (type 'quit' to quit, 'help' for help):
> ^A
```

# Socnet.se

## Client for direct blockmodeling

- A fast (compiled) CLI-based client for direct blockmodeling
- Version 1.4
- Goodness-of-fit functions:
  - Hamming distances
  - Weighted correlations
- Equivalences:
  - Structural
  - Regular
  - Generalized
- Free-search or specified blockimage

# Socnet.se

## Client for direct blockmodeling

Socnet code to do direct blockmodeling of Little League TI data:

```
# Set working directory to where your network files are
setwd(C:\\Users\\pekpi\\Dropbox\\work\\Winter CSS school\\data)

# Load the matrix file (and rename it to llti)
loadmatrix(file=little_league_ti.txt, name=llti)

# Specify a non-specified 3-positional blockimage for structural equivalence
bi = blockimage(size=3, pattern=com;nul)

# Initialize the search engine
bminit(network=llti, blockimage=bi, searchtype=exhaustive, method=hamming)

# Start search (can take a while)
bmstart()

# Explore solutions
structures

# To view a Blockmodel (you should have 12), use:
bmview(bm_llti_bi_0)
```

```
> bmview(bm_llti_bi_0)
Blockmodel:
+-----+
| \  x |   |XX|   |      0_Tom__2
| \  xx|   |  x|   |      0_John_6
| x\   |   | x |   |      0_Jerry_10
| x x\  |   | x |   |      0_Darrin_11
| xx \  |   | x |   |      0_Ben_12
| x   \ |   | x |   |      0_Arnie_13
+-----+
| x     | \xx|   |      1_Jeff_7
| x     | x\x|   |      1_Jay__8
| x     | xx\ |   |      1_Sandy_9
+-----+
|      | \xxx|   |      2_Ron__1
|      | x\x|   |      2_Frank_3
| x     | xx\ |   |      2_Boyd_4
|      | xxx\ |   |      2_Tim__5
+-----+
Blockimage:
      P0      P1      P2
P0      nul      nul      nul
P1      nul      com      nul
P2      nul      nul      com
Goodness-of-fit: 23 (hamming)
```

Notably, direct blockmodeling finds a better partition (lower goodness-of-fit)

Actually finds two equally optimal solutions (and several isomorphic solutions that are excluded)



# Socnet.se

## Client for direct blockmodeling

Instead of Hamming, we can use (weighted) correlations as GoF

Then we can't use 'exhaustive', but instead the 'ljubljana' local opt algorithm

```
# Set working directory to where your network files are
setwd(C:\Users\pekpi\Dropbox\work\Winter CSS school\data)

# Load the matrix file (and rename it to llti)
loadmatrix(file=little_league_ti.txt, name=llti)

# Specify a non-specified 3-positional blockimage for structural equivalence
bi = blockimage(size=3, pattern=com;nul)

# Initialize the search engine
bminit(network=llti, blockimage=bi, searchtype=ljubljana, method=nordlund)

# Start search (can take a while with the 'Nordlund' option)
bmstart()

# Explore solutions
structures

# To view the Blockmodel (you should only have one now), use:
bmview(bm_llti_bi_94_0)
```

```
Blockmodel:
+-----+
|\xx|   | x |   |      0_Jeff_7
|x\x|   | x |   |      0_Jay__8
|xx\|   | x |   |      0_Sandy_9
+-----+
|      |\ xx|   x |   |      1_John_6
|      |x\  |x |   |      1_Jerry_10
|      |xx\ |x |   |      1_Ben_12
|      |x  \|  x |   |      1_Arnie_13
+-----+
|      |      |\ xxx|   |      2_Ron__1
|      |      |x\x x|   |      2_Tom__2
|      |      |x \x x|   |      2_Frank_3
|      |      |xxx\  |   |      2_Boyd_4
|      |      |x xx\  |   |      2_Tim__5
|      |x  |xx  \|   |      2_Darrin_11
+-----+
Blockimage:
      P0      P1      P2
P0      com      nul      nul
P1      nul      com      nul
P2      nul      nul      com
Goodness-of-fit: 0.5752 (nordlund)
```

When using correlation coefficient,  
more likely to find singular optimal  
solution

Arguably easier to compare and  
interpret the fit than an absolute  
number of deviations

# Socnet.se

Console/terminal application written in C#/.Net

Download at

<https://socnet.se/?page=download>

Code-signed executable/binaries for Win, Linux, MacOS (setup.exe for Windows)

Although codesigned, could give warning when DL:ing on Chrome (though not Edge)

Full documentation at

<https://socnet.se/?page=docs>

## socnet.se: The blockmodeling console app (Win/Linux/Mac)

**Current version:** Version 1.1 (October 2023)

Written in C# .Net, sharing the same underlying source code, Socnet is compiled as self-contained, single-file executables, each targeting a specific platform and processor. There is thus no need to install the .NET runtime when using Socnet.

### Instructions

Download the ZIP file that corresponds to your OS. Unsure about your OS and 32-vs-64-bit? Check out <https://whatsmyos.com/>.

### Windows

- Installation files (zipped setup.exe files):
  - x86: [ [64-bit](#) ] [ [32-bit](#) ]
  - ARM: [ [64-bit](#) ] [ [32-bit](#) ]
- ZIP files (zipped socnet.exe files):
  - x86: [ [64-bit](#) ] [ [32-bit](#) ]
  - ARM: [ [64-bit](#) ] [ [32-bit](#) ]

For the Installation files: unzip and run the setup-socnet[...].exe. Follow the installation guide. Easy to uninstall later.

For the zipped socnet.exe files: unpack where you want, and run the executable.

Note: You may get a warning when downloading the ZIP and/or running the EXE files. I'm in the process of installing my LiU code certificate, but still a bit of work to do.

### Linux

- ZIP files:
  - [64-bit AMD/Intel](#)
  - [64-bit ARM](#)
  - [32-bit ARM](#)

### For ZIP files:

1. Download your ZIP file above and unpack at a suitable location
2. Open a terminal and navigate to the folder containing the 'socnet' program

A photograph of various laboratory glassware containing a blue liquid, arranged on a shelf. From left to right: a large round-bottom flask, a small Erlenmeyer flask, a medium Erlenmeyer flask, a graduated cylinder, a test tube, a beaker, and another beaker. The background is a blurred laboratory setting. The text "Afternoon lab" is overlaid in white in the center.

# Afternoon lab

# Lab (13-16ish)

- Working with a bunch of classical datasets
  - Baker citation, EIES (t1, t2), Galtung, Hlebec notesharing, Knoke, Little league, Zachary karate club
  - Binary and valued, directional and symmetric
  - Single-layer
  - S50 data (Snijders' Teenage Friends and Lifestyle Study data)  
[https://www.stats.ox.ac.uk/~snijders/siena/s50\\_data.htm](https://www.stats.ox.ac.uk/~snijders/siena/s50_data.htm)
- R scripts
  - Lab\_day\_1.Rmd – exploring (also random graphs)
  - Cohesive\_subgroups, assortativity (EIES), rewiring

# Lab (13-16ish)

- Socnet.se
  - Command-line interface (CLI) console application
  - Download and install from <https://socnet.se/>
- Script file:  
socnet\_script.txt
- Copy and paste (non-commented) commands into Socnet.se client

```
Socnet.se
Socnet - Direct blockmodeling in C#
=====
Version 1.4 (October 2025)
Carl Nordlund - carl.nordlund@liu.se

Socnet.se was supported by NordForsk through the funding to
The Network Dynamics of Ethnic Integration, project number 105147
Nordint.net: https://nordint.net

How to cite specific methods, type in 'citeinfo()'.

Entering interactive mode (type 'quit' to quit, 'help' for help):
>|
```

```
2  # =====
3
4  # This lab script goes through examples on how to do direct blockmodeling
5  # using the Socnet.se client. This whole script can be loaded into Socnet.se
6  # using the 'loadscript()' command, but it is far better to simply run a line
7  # at a time in the CLI interface.
8
9  # To do that, copy all command lines (i.e. those not starting with a hashtag)
10 # to the CLI console and check the output!
11
12 # Note that lines starting with the hashtag are comments and will be
13 # ignored by the client. Also note that some commands below might have
14 # to be modified (due to stochastic nature of the ljubljana search
15 # algorithm)
16
17 # Details about all Socnet.se commands can be found online:
18 # https://socnet.se/?page=docs#funclist
19
20 # Or check out the specific info about a specific [command] here:
21 # https://socnet.se/?page=docs#f_[command]
22
23 # Set working directory
24 # =====
25 # For this to work, you need to have unzipped the 'example_data.zip' package
26 # at a suitable location on your system. If you obtained Socnet.se from source
27 # you will find the 'example_data' folder as part of the repository.
28
29 # Or use the /data folder provided to you in your lab, assuming that the data
```