



T no.



- SP : Start Pulse Timer
- SE : Start Extended Pulse Timer
- SD : Start On-Delay Timer
- SS : Start Retentive On-Delay Timer
- SF : Start Off-Delay Timer

Parameter English	Data Type	Memory Area	Description
no.	TIMER	T	Timer identification number. The range depends on the CPU.
S	BOOL	I, Q, M, D, L, T, C	Start input
TV	S5TIME	I, Q, M, D, L or constant	Preset time value (range 0-9999)
R	BOOL	I, Q, M, D, L, T, C	Reset input
BI	WORD	I, Q, M, D, L	Time remaining (value in integer format)
BCD	WORD	I, Q, M, D, L	Time remaining (value in BCD format)
Q	BOOL	I, Q, M, D, L	Status of the timer



- BCD_I : BCD to Integer
- I_BCD : Integer to BCD
- BCD_DI : BCD to Double Integer
- I_DI : Integer to Double Integer

Parameter	Data Type	Memory Area	Description
EN	BOOL	I, Q, M, D, L, T, C	Enable input
IN	WORD	I, Q, M, D, L or constant	Number in BCD format
OUT	INT	I, Q, M, D, L	Integer value of the BCD number
ENO	BOOL	I, Q, M, D, L	Enable output