

```
## Using the library
* Open Inkscape_Symbols_All.svg and copy the symbols of interest to your Inkscape sheet.
```

- * **Always draw on the grid!**
- * **Enable snapping!**
- * Grid on/off by # -key
- * Recommended way to move objects: drag them next to an endpoint (it makes a difference where you touch the component), to make sure to work on the rough grid (recommended, not the fine one).
- * Recommended way to move wires: mark area for mark-tool), press F2-key, click on the end of the line so that the fixed point becomes red, now you can move this point.
- * Recommended way to rotate the component: mark the component and use the 'rotate' buttons at the upper part of the toolbar.
- * Recommended way to mirror components: press v (vertical) or h (horizontal).
- * Recommended way to changes text: click on text, press 't' for editing mode.
- * Change Color of area: mark area, click on 'Color'.
- * Change Color of line: mark line, shift + click on 'Color'.
- * Colors used in this template: 'GNOME HIG Colors'.

					F_1
Fuse					
				R_1	
esistor	Varistor	Potentiometer			
esistor	Varistor	Potentiometer			
					C_1
pacitor					
	Polarized Cap.	Adjustable Cap.			
Inductor		Transformer			
				V_1	
Valve	Valve	Thyristor	Diode		
				V_1	
Valve	Valve	Thyristor	Diode		

Figure 1.10 shows the circuit symbols for the diodes. The diode symbol is a triangle pointing towards a vertical line. The symbols for the different diodes are: LED (a triangle pointing towards a vertical line with two short horizontal lines on the vertical line), Z-Diode (a triangle pointing towards a vertical line with a Z-shape on the vertical line), Schottky (a triangle pointing towards a vertical line with a small circle on the vertical line), and Bipolar Z-Diode (a triangle pointing towards a vertical line with a Z-shape and a small circle on the vertical line).

	MOSFET Depletion Type (normally-on)	
	MOSFET Enhancement Type (normally-off)	
	MOSFET Depletion Type (normally-on)	
	MOSFET Enhancement Type (normally-off)	
	IGBT Depletion Type (normally-on)	
	IGBT Enhancement Type (normally-off)	
	NPN Bipolar Transistor	
	GaN HEMPT Enhancement Type (normally off)	
	GaN GIT Enhancement Type (normally off)	
	Bidirectional GaN Transistor	

Diagram showing symbols for Voltage Source, Current Source, and Battery.

The diagram on the left shows a rectangular magnetic core with windings on both the vertical legs. The diagram on the right is a graph of magnetic flux density B versus magnetic field strength H . It shows two curves: a linear curve passing through the origin and a non-linear curve that starts at the origin and curves upwards, representing magnetic saturation.

 Switch
 Switch
 Opener

Spark gap Light bulb

text 12p $\downarrow U_{DC}$ $\uparrow i_{DC}$ F_1 R_1 L_1 C_1 P_{AC} $\downarrow U_{DC}$ $\uparrow i_{DC}$ T_1 D_1 V_1 M_1 U_1 I_1	text 8p $\downarrow U_{2k}$ $\uparrow i_{DC}$ F_1 R_1 L_1 C_1 P_{AC} $\downarrow U_{2k}$ $\uparrow i_{DC}$ T_1 D_1 V_1 M_1 U_1 I_1
3V3 5V 9V 12V 15V 24V +12V +15V -12V -15V	3V3 5V 9V 12V 15V 24V +12V +15V -12V -15V
αβγδεθκλμνπρστυφωθΦ ΔΘΣΨΩ	αβγδεθκλμνπρστυφωθΦ ΔΘΣΨΩ Font P052

- Coaxial
- 2x1 pin
- 3x1 pin
- 4x1 pin
- RS-232
- USB

Signal Generator

Scope

Impedance Analyzer

Transistor Housings

Source / Load

Power Analyzer

Coaxial cable

Server

SD card

CPU

Noise

Neural network

⚡⚡

Contacts		Coils		

The figure shows two circuit diagrams for three-level converters. The left diagram is labeled "Three Level NPC (Neutral Point Clamped)" and the right diagram is labeled "Three Level TNPC (T-Type Neutral Point Clamped)". Both diagrams show three phase legs connected to a common neutral point. The NPC converter uses a split DC source with two DC-link capacitors and clamping diodes to achieve three-level output. The TNPC converter uses a single DC source and T-type transistors to achieve three-level output.

Double pulse test'

