

Section	Item	Definition	Data Format	XML	Occurs	Examples & Notes
File Header				iati-organisation	1..1	
	IATI Version	The version of the IATI Standard that has been used to compile this file.	Text	iati-organisation/@version	1..1	<iati-organisation version="1.00">
	last-updated-datetime	The date and time this file was last updated.	DateTime	iati-organisation/@last-updated-datetime	1..1	<iati-organisation last-updated-datetime="2010-10-27T18:00:00">
	default language	This field allows a default language for an entire activity report. The language should be the same as is used in formal documents with the aid recipient. In most cases all the activity information will be provided in the same language. The ISO 639-1 language code.	Language Code	iati-organisation/@xml:lang	0..1	<iati-organisation xml:lang="en">
	default-currency	The default currency for an entire activity report. In most cases, all financial figures will be provided using the same currency. The ISO 4217 code.	Currency Code	iati-organisation/@default-currency	0..1	<iati-organisation default-currency="USD">
Organisation Identifier				iati-identifier	1..1	
	Organisation identifier	A unique identifier for the organisation.	Organisation Identifier	iati-identifier/text()	1..1	<iati-identifier>GB-1</iati-identifier>
Organisation name		The human-readable name of the organisation. May be repeated in different languages for reporting organisations with multilingual requirements.		name	0..*	
	Name	The name of the organisation	Text	name/text()	1..1	<name>Department for International Development</name>
	Language	ISO 639-1 code for the language of the name (only if different from the default language).	Language Code	name/@xml:lang	0..1	<name xml:lang="fr">Departement pour le developpement international</name>
Annual forward planning budget data for organisation		The total development budget for each of the next three years (or most detailed available) on a rolling basis. For donor agencies as submitted to parliament; for foundations or multilaterals as submitted to the board.		total-budget	0..*	
	period-start-date	ISO 8601 code for the start date of the reporting year (yyyy-mm-dd).	Date	total-budget/period-start/@iso-date	1..1	<period-start iso-date="2010-01-01"/>
	period-start-text	A free text description of the period start	Text	total-budget/period-start/text()	0..1	<period-start iso-date="2010-01-01">January 2010</period-start>

Section	Item	Definition	Data Format	XML	Occurs	Examples & Notes
	period-end-date	ISO 8601 code for the end date of the reporting year (yyyy-mm-dd).	Date	total-budget/period-end/@iso-date	1..1	<period-end iso-date="2010-12-31"/>
	period-end-text	A free text description of the period end	Text	total-budget/period-end/text()	0..1	<period-end iso-date="2010-12-31">December 2010</period-end>
	value	The total budget for the specified year in the specified currency. (Positive integer.)	Integer	total-budget/value/text()	1..1	<value value-date="2010-01-01">7000000000</value>
	currency	The ISO 4217 code for the currency in which the project is denominated. [only if different to default currency]	Currency Code	total-budget/value/@currency	0..1	<value currency="GBP" value-date="2010-01-01">7000000000</value>
	value-date	Date of value for currency conversions.(yyyy-mm-dd)	Date	total-budget/value/@value-date	1..1	<value value-date="2010-01-01">7000000000</value>
Annual forward planning budget data for funded institutions		The budget for each of the next three years (or most detailed available) on a rolling basis for each institution (i.e. multilateral organisations, INGOs, foundations and others) that receives core funding from the donor.		recipient-org-budget	0..*	
	recipient-identifier	A unique identifier for the institution receiving the funds.	Organisation Identifier	recipient-org-budget/recipient-org/@ref	1..1	<recipient-org ref="44000"/>
	recipient-name	The name of the institution receiving the funds.	Text	recipient-org-budget/recipient-org/text()	0..1	<recipient-org ref="44000">World Bank</recipient-org>
	period-start-date	ISO 8601 code for the start date of the reporting year (yyyy-mm-dd).	Date	total-budget/period-start/@iso-date	1..1	<period-start iso-date="2010-01-01"/>
	period-start-text	A free text description of the period start	Text	total-budget/period-start/text()	0..1	<period-start iso-date="2010-01-01"/>January 2010<period-start>
	period-end-date	ISO 8601 code for the end date of the reporting year (yyyy-mm-dd).	Date	total-budget/period-end/@iso-date	1..1	<period-end iso-date="2010-12-31"/>
	period-end-text	A free text description of the period end	Text	total-budget/period-end/text()	0..1	<period-end iso-date="2010-12-31">December 2010</period-end>
	value	The total budget for the specified year in the specified currency. (Positive integer.)	Integer	recipient-org-budget/value/text()	1..1	<value value-date="2010-01-01">5000000000</value>
	currency	The ISO 4217 code for the currency in which the project is denominated. [only if different to default currency]	Currency Code	recipient-org-budget/value/@currency	0..1	<value currency="USD" value-date="2010-01-01">5000000000</value>
	value-date	Date of value for currency conversions.(yyyy-mm-dd)	Date	recipient-org-budget/value/@value-date	1..1	<value currency="USD" value-date="2010-01-01">5000000000</value>

Section	Item	Definition	Data Format	XML	Occurs	Examples & Notes
Annual forward planning budget data for country		The budget for assistance to each recipient for each of the next three to five years (or most detailed available) on a rolling basis, using the recipient's financial year.		country-budget	0..*	
	recipient country code	ISO 3166 country code	Country Code	country-budget/recipient-country/@code	1..1	<recipient-country code="CG"/>
	recipient country name	Name of the country.	Text	country-budget/recipient-country/text()	0..1	<recipient-country code="CG">Democratic Republic of Congo</recipient-org>
	period-start-date	ISO 8601 code for the start date of the reporting year (yyyy-mm-dd).	Date	total-budget/period-start/@iso-date	1..1	<period-start iso-date="2010-01-01"/>
	period-start-text	A free text description of the period start	Text	total-budget/period-start/text()	0..1	<period-start iso-date="2010-01-01">January 2010</period-start>
	period-end-date	ISO 8601 code for the end date of the reporting year (yyyy-mm-dd).	Date	total-budget/period-end/@iso-date	1..1	<period-end iso-date="2010-12-31"/>
	period-end-text	A free text description of the period end	Text	total-budget/period-end/text()	0..1	<period-end iso-date="2010-12-31">December 2010</period-end>
	value	The total budget for the specified year in the specified currency. (Positive integer.)	Integer	country-budget/value/text()	1..1	<value currency="USD" value-date="2010-01-01">50000000</value>
	currency	The ISO 4217 code for the currency in which the project is denominated. [only if different to default currency]	Currency Code	country-budget/value/@currency	0..1	<value currency="USD" value-date="2010-01-01">50000000</value>
	value- date	Date of value for currency conversions.(yyyy-mm-dd)	Date	country-budget/value/@value-date	1..1	<value currency="USD" value-date="2010-01-01">50000000</value>
Activity Documents		Information pertaining to a published document that is related to an organisation		document-link	0..*	
	url	The web address where the document can be downloaded.	u.r.l.	document-link/@url	1..1	<document-link url="http://reporting.org/documents/xx546.doc">
	document format	The Internet Media Type ("MIME type") of the document linked to, as defined and maintained by the Internet Assigned Numbers Authority.	File Format Code	document-link/@format	0..1	<document-link format="application/msword">
	language	The ISO 639 code for the language of the document. Only required if different from the activity's default language.	Language Code	document-link/@xml:lang	0..1	<document-link xml:lang="en">
	category	The type of content contained within the document. If the document spans multiple		document-link/category	1..*	

Section	Item	Definition	Data Format	XML	Occurs	Examples & Notes
		content types this element should be repeated.				
	category-code	The code for the content type	Document Category Code	document-link/category/@code	1..1	<category code="A04"/>
	category-description	A description of the content type	Text	document-link/category/text()	0..1	<category code="A04">Conditions</category>
	title	The full title of the document	Text	document-link/title/text()	1..1	<title>Project Conditions</title>