

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
File Header				iati-activities	1..1	
	IATI Version	The version of the IATI Standard that has been used to compile this file.	Text	iati-activities/@version	1..1	<iati-activities version="1.01">
	generated-datetime	The date and time this file was generated.	DateTime	iati-activities/@generated-datetime	1..1	<iati-activities generated-datetime="2010-10-27T18:00:00">
Record Header				iati-activity	1..*	
	Default language	This field allows a default language for an entire activity report. The language should be the same as is used in formal documents with the aid recipient. In most cases all the activity information will be provided in the same language. The ISO 639-1 Language Code.	Language Code	iati-activity/@xml:lang	0..1	<iati-activity xml:lang="en">
	Default currency	The default currency for an entire activity report. In most cases, all financial figures will be provided using the same currency. The ISO 4217 code. Different currencies may be specified at transaction level.	Currency Code	iati-activity/@default-currency	0..1	<iati-activity default-currency="USD">
	Hierarchical position	Is the activity the parent or child of another reported activity? (Values are - parent, child.)		iati-activity/@hierarchy	0..1	<iati-activity hierarchy="child">GB-1-105838-1</iati-activity>
	last-updated-datetime	The date and time this record was last updated.	DateTime	iati-activity/@last-updated-datetime	1..1	<iati-activity last-updated-datetime="2010-10-27T18:00:00">
Reporting Organisation		The name and unique identifier of the organisation publishing the information.		reporting-org	1..1	
	identifier	A unique identifier for the organisation	Organisation Identifier	reporting-org/@ref	1..1	<reporting-org ref="GB-1"/>
	type	Type of organisation (government, multilateral, private, PPP, NGO, foundation, etc)	Organisation Type Code	reporting-org/@type	1..1	<reporting-org ref="GB-1" type = Government"/>
	name	The name of the organisation		reporting-org/text()	0..1	<reporting-org>Department for International Development</reporting-org>
	language	ISO 639-1 code for language of the name. [Only if different to default language.]	Language Code	reporting-org/@xml:lang	0..1	<reporting-org xml:lang="fr">Departement pour le developpement international</reporting-org>
IATI activity identifier		A globally unique identifier for this activity. This should be in the form of the IATI Organisation Identifier (for the reporting organisation) concatenated to that organisation's activity identifier.		iati-identifier	1..1	

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	IATI activity identification string	The IATI identification string.	Text	iati-identifier/text()	1..1	<iati-identifier>GB-1-105838-1</iati-identifier>
Participating Organisation		The identity and role of each organisation in the activity (including the reporting organisation).		participating-org	0..*	
	role	Roles: Funding - The country or institution which provides the funds; Extending - The government entity (central, state or local government agency or department), or agency within an institution, financing the activity from its own budget; Implementing - The intermediary between the extending agency and the ultimate beneficiary. Also known as executing agency or channel of delivery. They can be public sector, non-governmental agencies (NGOs), Public-Private partnerships, or multilateral institutions; Accountable - The government agency, civil society or private sector institution which is accountable for the implementation of the activity.	Organisation Role Code	participating-org/@role	1..1	<participating-org role="Extending" ref="41114">UNDP</participating-org>
	identifier	A unique identifier for the organisation. [ISO 3166 codes for countries]	Organisation Identifier	participating-org/@ref	0..1	<participating-org role="Extending" ref="41114">UNDP</participating-org>
	type	Type of organisation (government, multilateral, private, PPP, NGO, foundation, etc)	Organisation Type Code	participating-org/@type	1..1	<participating-org role="Extending" type="Multilateral" ref="41114">UNDP</participating-org>
	name	The name of the organisation (e.g. 'United Nations Children's Fund')	Text	participating-org/text()	0..1	<participating-org role="Extending" ref="41114">UNDP</participating-org>
	language	The ISO 639-1 code for the language of the name and acronym. [Only if different to default language.]	Language Code	participating-org/@xml:lang	0..1	<participating-org role="Extending" ref="41114" xml:lang="fr">PNUD</participating-org>
Recipient Country		The country(ies) for whose benefit the aid flow is provided, if applicable. Repeat for each country where known.		recipient-country	0..*	
	code	ISO 3166 country code	Country Code	recipient-country/@code	1..1	<recipient-country code="CG"/>
	name	Name of the country	Text	recipient-country/text()	0..1	<recipient-country code="CG">Democratic Republic of Congo</recipient-country>
	percentage	Percentage of activity commitment allocated to this	Integer	recipient-	0..1	<recipient-country code="CG"

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
		country (if available) if more than one country is involved. If percentages are shown for each country they must add to 100% for the activity being reported.		country/@percentage		percentage="60"/><recipient-country code="AO" percentage="40"/>
	language	The ISO 639-1 code for the language of the name. [Only if different to default language.]	Language Code	recipient-country/@xml:lang	0..1	<recipient-country code="CG" xml:lang="fr">Republique Democratique du Congo </recipient-country>
Recipient region		Supra-national: The geographical or administrative region grouping various countries (e.g. Sub-Saharan Africa, Mekong Delta). Use 'global' for activities benefiting substantially all developing countries. If percentages are shown for each region they must add to 100% for the activity being reported.		recipient-region	0..*	
	code	IATI region code	Region Code	recipient-region/@code	0..1	<recipient-region code="289"/>
	name	Name of the region	Text	recipient-region/text()	0..1	<recipient-region>Mano River Basin</recipient-region>
	percentage	Percentage of activity commitment allocated to this region (if available).	Integer	recipient-region/@percentage	0..1	<recipient-region code="289" percentage="60"/><recipient-region code="189" percentage="40"/>
	language	The ISO 639-1 code for the language of the name (only if different from the default language).	Language Code	recipient-region/@xml:lang	0..1	<recipient-region code="289" xml:lang="es">Africa subsahariana</recipient-region>
Activity Title		The title of the aid activity (preferably official name used in project documents - avoid obscure acronyms).		title	1..*	
	Text	The text for the title.	Text	title/text()	1..1	<title>Support to the Poverty Reduction Strategy Process</title>
	language	The ISO 639-1 code for the language of the text. [Only if different to default language.]	Language Code	title/@xml:lang	0..1	<title xml:lang="fr">Appui au processus de Strategie de Reduction</title>
Activity Description		Long description summarising the specific purpose or objective of the activity.		description	0..*	
	Type	The type of description (summary, objectives, etc.).	Description Type Code	description/@type	0..1	<description type="Objectives">The aims of the activity are to ... </description>
	Text	The text for the description.	Text	description/text()	1..1	<description>A general description of the activity. ...</description>
	language	The ISO 639-1 code for the language of the text. [Only if different to default language.]	Language Code	description/@xml:lang	0..1	Â <description xml:lang="en">A general description of the activity. ...</description>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
Collaboration Type		Identifier to show the type of collaboration. For official donors, shows if the activity is bilateral; earmarked multilateral; core multilateral; core contributions to NGOs; core contributions to PPPs; or multilateral outflow. Allows for additional types that might apply to foundations and NGOs.		collaboration-type	0..1	
	code	The code for this collaboration type (e.g. bilateral, core multilateral).	Collaboration Type Code	collaboration-type/@code	1..1	<collaboration-type code="1"/>
	name	The human-readable name of this collaboration type.	Text	collaboration-type/text()	0..1	<collaboration-type code="1">Bilateral</collaboration-type>
	language	The ISO 639-1 code for the language of the type name. [Only if different to default language.]	Language Code	collaboration-type/@xml:lang	0..1	<collaboration-type code="1" xml:lang="fr"> Bilateral</collaboration-type>
Default Flow Type		Identifier to show the classification of the flow. For official donors if the activity is Official Development Assistance (ODA), or Other Official Flows (OOF) [non-concessional but developmental, i.e. excluding export credits]. Allows for any types that might apply to foundations and NGOs. Default flow type can be overridden by flow type on any specific transaction within the activity.		default-flow-type	0..1	
	code	The IATI code for this flow type (e.g. ODA, OOF).	Flow Type Code	default-flow-type/@code	1..1	<default-flow-type code="10"/>
	name	The human-readable name of this flow type.	Text	default-flow-type/text()	0..1	<default-flow-type code="10">ODA</default-flow-type>
	language	The ISO 639-1 code for the language of the type name. [Only if different to default language.]	Language Code	default-flow-type/@xml:lang	0..1	<default-flow-type code="10" xml:lang="fr"> APD</default-flow-type>
Default Aid Type		Identifier to show the type of assistance provided. For official donors broad categories are budget support, pooled funds, project-type interventions, experts, scholarships, debt relief, administrative costs). Allows for any types that might apply to private donors. Default aid type can be overridden by aid type on any specific transaction within the activity.		default-aid-type	0..1	
	code	The code identifying the aid type (e.g. pooled).	Aid Type Code	default-aid-type/@code	1..1	<default-aid-type code="A02"/>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	name	Human-readable text describing the aid type.	Text	default-aid-type/text()	0..1	<default-aid-type code="A02">Sector Budget Support</default-aid-type>
	language	Language of the human-readable text. [Only if different to default language.]	Language Code	default-aid-type/@xml:lang	0..1	<default-aid-type code="A02" xml:lang="fr">Soutien budgétaire sectoriel</default-aid-type>
Default Finance Type		Identifier to show the financing mechanism of the aid activity (e.g. grant, loan, capital subscription, export credit, debt relief, equity). Default finance type can be overridden by finance type on any specific transaction within the activity.		default-finance-type	0..1	
	code	The code identifying the finance type (e.g. debt relief).	Finance Type Code	default-finance-type/@code	1..1	<default-finance-type code="100"/>
	name	Human-readable text describing the finance type.	Text	default-finance-type/text()	0..1	<default-finance-type code="100">Grant</default-finance-type>
	language	Language of the human-readable text. [Only if different to default language.]	Language Code	default-finance-type/@xml:lang	0..1	<default-finance-type code="100" xml:lang="fr">Don</default-finance-type>
Other activity identifiers		An activity can be defined and/or reported on by multiple organisations. All such identifiers can be reported here.		other-identifier	0..*	
	organisation-identifier	A unique identifier for the owner of this ID.	Organisation Identifier	other-identifier@owner-ref	0..1	<other-identifier owner-ref="GB-1">105838-1</other-identifier>
	organisation-name	A human-readable name for the owner of this ID	Text	other-identifier/@owner-name	0..1	<other-identifier owner-ref="GB-1" owner-name="DFID">105838-1</other-identifier>
	activity identification string	The activity identification string.	Text	other-identifier/text()	1..1	<other-identifier owner-ref="GB-1" owner-name="DFID">105838-1</other-identifier>
General / Detailed Sector		The specific area(s) of the recipient's economic or social development that the transfer intends to foster. Also known as purpose codes.		sector	0..*	
	vocabulary	The sector vocabulary (DAC, OCHA, World Bank, AidData, etc.). If omitted, assume DAC. Allows for donors to enter their own internal sector codes. But where they have a mapping to the DAC standard (e.g. DAC members, WB, Reg Banks, UN agencies) should also record that here for international comparability.	Vocabulary Code	sector/@vocabulary	0..1	<sector vocabulary="WB" code="BC">Central government administration</sector>
	code	The code for the sector.	Sector Code	sector/@code	0..1	<sector code="13040"/>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	description	The description of the sector.	Text	sector/text()	0..1	<sector code="13040">STD control including HIV/AIDS</sector>
	percentage	Percentage share of commitment for this sector within the vocabulary. Shares required if more than one sector within any vocabulary for an activity and must add to 100% within that vocabulary.	Integer	sector/@percentage	0..1	<sector code="13040" percentage="32"/><sector code="13062" percentage="68"/>
	language	The ISO 639-1 code for the language of the sector name. [Only if different to default language.]	Language Code	sector/@xml:lang	0..1	Ã <sector code="13040" xml:lang="en">STD control including HIV/AIDS</sector>
Activity Dates		The expected and actual start and completion dates of the activity, where start is the date of first disbursement for the activity and completion is the date of last disbursement for the activity.		activity-date	0..*	
	Type	Date type (e.g. start-planned, end-actual).	Activity Date Type Code	activity-date/@type	1..1	<activity-date type="start-planned">2011</activity-date>
	iso-date	ISO 8601 date (yyyy-mm-dd).	Date	activity-date/@iso-date	0..1	<activity-date type="start-actual" iso-date="2010-03-22"/>
	text-date	General date text (e.g. 2011Q1). For recording less specific dates (month, quarter, year) where full (iso) date is not known.	Text	activity-date/text()	0..1	<activity-date type="start-planned">2011</activity-date>
	language	The language of the general date text. [Only if different to default language.]	Language Code	activity-date/@xml:lang	0..1	<activity-date type="start-planned" xml:lang="en">First Quarter 2011</activity-date>
Default Tied Aid Status		Amounts by degree of restriction on where procurement of goods or services can take place, classified as untied (open procurement), partially tied (donor and developing countries) and tied (donor or group not including most developing countries). Note that there is both a default for the entire activity, and an optional status for each transaction, for when different contributions to an activity have different tied statuses.		default-tied-status	0..1	
	code	The IATI code for the tied status (e.g. tied, untied).	Tied Status Code	default-tied-status/@code	1..1	<default-tied-status code="5"/>
	name	The human-readable description of the status.	Text	default-tied-status/text()	0..1	<default-tied-status code="5">Untied</default-tied-status>
	language	The ISO 639-1 code for the language of the description.	Language	default-tied-	0..1	<default-tied-status code="5"

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
		[Only if different to default language.]	Code	status/@xml:lang		xml:lang="fr">Aide non-liee</default-tied-status>
Policy/ Thematic Markers		Indicators tracking key policy issues. This can be also used for donor specific thematic classifications		policy-marker	0..*	
	score	A score indicating if the activity addresses the policy/theme as a principal or significant objective or not at all.	Policy Significance Code	policy-marker/@significance	0..1	<policy-marker vocabulary="DAC" code="04" significance="2"/>
	vocabulary	Policy vocabulary used (e.g. DAC, World Bank).	Vocabulary Code	policy-marker/@vocabulary	0..1	<policy-marker vocabulary="DAC" code="04"/>
	code	Policy marker code.	Policy Marker Code	policy-marker/@code	0..1	<policy-marker vocabulary="DAC" code="04"/>
	name	The name of the policy marker (e.g. Gender equality, Environment).	Text	policy-marker/text()	0..1	<policy-marker>Trade Development</policy-marker>
	language	ISO 639-1 code for the marker name language. [Only if different to default language.]	Language Code	policy-marker/@xml:lang	0..1	<policy-marker xml:lang="fr">Developpement du commerce</policy-marker>
Activity Status		The current stage of the aid activity at the time the IATI information is published/updated. The stages are based on an activity lifecycle.		activity-status	0..1	
	code	A code for the status (e.g. implementation).	Activity Status Code	activity-status/@code	1..1	<activity-status code="2"/>
	Text	Text describing the status.	Text	activity-status/@text	0..1	<activity-status code="2">Implementation</activity-status>
	language	The ISO 639-1 code for the language of the status text. [Only if different to default language.]	Language Code	activity-status/@xml:lang	0..1	<activity-status code="2"> xml:lang="fr">Implementation </activity-status>
Activity Contacts		Contact details for the activity. Can be either a generic contact or specific individual providing there are no privacy concerns and there is an automatic update when individual changes job.		contact-info	0..*	
	organisation name	The name of the contact's organisation.	Text	contact-info/organisation/text()	0..1	<organisation>DFID</organisation>
	name	The name of the contact at the organisation.	Text	contact-info/person-name/text()	0..1	<person-name>Joe Brown</person-name>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	telephone	The contact's telephone number.	Text	contact-info/telephone/text()	0..*	<telephone>+442071239876</telephone>
	email	The contact's email address.	Email address	contact-info/email/text()	0..*	<email>jbrown@dfid.gov</email>
	address	The contact's mailing address.	Text	contact-info/ mailing-address/text()	0..*	<mailing-address>1 Palace Street, London SW1E 5HE</mailing-address>
Activity Web Site		Web site with more information about the activity		activity-website	0..*	
	URL	Web URL of the site	url	activity-website/text()	1..1	<activity-website>http://projects.dfid.gov.uk/ProjectDetails.asp?projcode=105838-101</activity-website>
Related Activity		Link to other reported activities related to this activity.		related-activity	0..*	
	Type	Type of relationship (Parent, child, sibling)	Related Activity Type Code	related-activity/@type	1..1	<related-activity type="1" ref="GB-1-105838">Trade Sector Programme</related-activity>
	identifier	IATI identifier for the activity.	Text	related-activity/@ref	1..1	<related-activity type="1" ref="GB-1-105838"/>
	Title	Title of the activity.	Text	related-activity/text()	0..*	<related-activity type="1" ref="GB-1-105838">Trade Sector Programme</related-activity>
	language	Language of the title. [Only if different to default language.]	Language Code	related-activity/@xml:lang	0..*	<related-activity type="1" ref="GB-1-105838" xml:lang="fr"> Programme du secteur commercial </related-activity>
Financial transaction		Details of each financial transaction by the donor.		transaction	0..*	
transaction type		Values: Commitment - a firm written obligation by the donor to provide resources of a specified amount under specified financial terms and conditions and for specified purposes for the benefit of the recipient; Disbursement - the amount placed at the disposal of a recipient country or agency (in the case of internal development-related expenditures, the outlay of funds); Expenditure - the outlay by the implementing agency on goods and services for the activity; Loan Repayment- the actual amount of principal (amortisation) repaid, including any arrears; Interest Repayment - the actual amount of interest repaid; Incoming Funds		transaction/transaction-type	1..1	

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	transaction type code	A code for the transaction type	Transaction Type Code	transaction/transaction-type/@code	1..1	<transaction-type code="C"/>
	transaction type description	Plain-text description of the transaction type.	Text	transaction/transaction-type/text()	0..1	<transaction-type code="C">Commitment</transaction-type>
Transaction provider		Details of the organisation making the financial transaction (receiving in the case of loan and interest repayments).		transaction/provider-org	0..1	
	provider name	The full name of the organisation making the financial transaction (receiving in the case of loan and interest repayments).	Text	transaction/provider-org/text()	0..1	<provider-org>DFID</provider-org>
	provider organisation identifier	The unique Organisation Identifier for the provider.	Organisation Identifier	transaction/provider-org/@ref	0..1	<provider-org ref="GB-1"/>
	provider activity id	If the funds are being provided from another reported activity, this must record the unique activity identifier for that activity.	Text	transaction/provider-org/@provider-activity-id	0..1	<provider-org provider-activity-id="GB-1-10538"/>
Transaction receiver		Details of the organisation receiving the financial transaction (paying in the case of loan and interest repayments).		transaction/receiver-org	0..1	
	receiver name	The full name of the organisation receiving the financial transaction (making in the case of loan and interest repayments).	Text	transaction/receiver-org/text()	0..1	<receiver-org ref> Ministere du Plan, RDC </receiver-org>
	receiver organisation identifier	The unique identifier for the receiver.	Organisation Identifier	transaction/receiver-org/@ref	0..1	<receiver-org ref="CG-3"/>
	receiver activity id	If the funds are being provided to another reported activity, this must record the unique activity identifier for that activity.	Text	transaction/receiver-org/@receiver-activity-id	0..1	<receiver-org receiver-activity-id="CG-3-1440"/>
Transaction value		Monetary details of the transaction		transaction/value	1..1	
	value	The monetary value of the transaction in the specified currency – negative for repayments or reduced/cancelled commitments. (positive or negative integer only).	Integer	transaction/value/text()	1..1	<value>25000</value>
	currency	ISO 4217 code for the currency in which the value is specified (e.g. 'EUR') [only if different to default currency]	Currency Code	transaction/value/@currency	0..1	<value currency="GBP">25000</value>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	value date	A reference date to use for converting to other currencies. ISO 8601 date (yyyy-mm-dd).	Date	transaction/value/@value-date	1..1	<value value-date="2010-05-27">25000</value>
transaction description		A note or comment on the transaction		transaction/description	0..1	
	Text	Text description	Text	transaction/description/text()	0..1	<description>Less disbursed than budgeted due to targets not being met</description>
	language	ISO 639-1 code for the language of the human-readable facet values. [only if different to default language]	Language Code	transaction/description/@xml:lang	0..1	<description xml:lang="en">Less disbursed than budgeted due to targets not being met</description>
transaction date		Date in the lifecycle of the financial transaction (e.g. when committed or when paid).		transaction/transaction-date	0..1	<transaction-date iso-date="2010-05-27">27 May 2010</transaction-date>
	transaction iso-date	ISO 8601 date (yyyy-mm-dd).	Date	transaction/transaction-date/@iso-date	1..1	<transaction-date iso-date="2010-05-27"/>
	transaction date text	Text describing the date of a financial transaction. For recording less specific dates (month, quarter, year) where full (iso) date is not known.	Text	transaction/transaction-date/text()	0..1	<transaction-date>May 2010</transaction-date>
Transaction flow type		Only to be entered if value is different from default-flow-type.		transaction/flow-type	0..1	
	code	The IATI code for this flow type (e.g. ODA, OOF).	Flow Type Code	transaction/flow-type/@code	1..1	<flow-type code="10"/>
	name	The human-readable name of this flow type.	Text	transaction/flow-type/text()	0..1	<flow-type>ODA</flow-type>
	language	The ISO 639-1 code for the language of the type name. [Only if different to default language.]	Language Code	transaction/flow-type/@xml:lang	0..1	<flow-type code="10" xml:lang="fr">APD</flow-type>
Transaction finance type		Only to be entered if value is different from default-finance-type.		transaction/finance-type	0..1	
	code	The code identifying the finance type (e.g. debt relief).	Finance Type Code	transaction/finance-type/@code	1..1	<finance-type code="100"/>
	name	Human-readable text describing the finance type.	Text	transaction/finance-type/text()	0..1	<finance-type>Grant</finance-type>
	language	Language of the human-readable text. [Only if different to default language.]	Language Code	transaction/finance-type/@xml:lang	0..1	<finance-type xml:lang="fr">Don</finance-type>
Transaction aid type		Only to be entered if value is different from default-aid-type		transaction/aid-type	0..1	
	code	The code identifying the aid type (e.g. pooled).	Aid Type	transaction/aid-type/@code	1..1	<aid-type code="A02"/>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
			Code			
	name	Human-readable text describing the aid type.	Text	transaction/aid-type/text()	0..1	<aid-type>Sector Budget Support</aid-type>
	language	Language of the human-readable text. [Only if different to default language.]	Language Code	transaction/aid-type/@xml:lang	0..1	<aid-type code="A02" xml:lang="fr">Soutien budgetaire sectoriel</aid-type>
Transaction Channel of disbursement				transaction/disbursement-channel	0..1	
	Disbursement-channel-code	The code for the channel of disbursement	Disbursement Channel Code	transaction/disbursement-channel/@code	1..1	<disbursement-channel code="1"/>
	Disbursement-channel-description	A description of the channel of disbursement	Text	transaction/disbursement-channel/text()	0..1	<disbursement-channel code="1">Cash to treasury</disbursement-channel-code>
Transaction tied aid status		Only to be entered if value is different from default-tied-status		transaction/tied-status	0..1	
	code	The IATI code for the tied status (e.g. tied, untied).	Tied Status Code	transaction/tied-status/@code	1..1	<tied-status code="5"/>
	name	The human-readable description of the status.	Text	transaction/tied-status/text()	0..1	<tied-status>Untied</tied-status>
	language	The ISO 639-1 code for the language of the description. [Only if different to default language.]	Language Code	transaction/tied-status/@xml:lang	0..1	<tied-status code="5" xml:lang="fr">Aide non-liee</tied-status>
Activity Documents		Information pertaining to a published document that is related to an activity		document-link	0..*	
	url	The web address where the document can be downloaded.	u.r.l.	document-link/@url	1..1	<document-link url="http://reporting.org/activities/documents/xx546.doc">
	document format	The Internet Media Type ("MIME type") of the document linked to, as defined and maintained by the Internet Assigned Numbers Authority.	File Format Code	document-link/@format	0..1	<document-link format="application/msword">
	language	The ISO 639 code for the language of the document. Only required if different from the activity's default language.	Language Code	document-link/@xml:lang	0..1	<document-link xml:lang="en">
	category	The type of content contained within the document. If the document spans multiple content types this element should be repeated.		document-link/category	1..*	

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	category-code	The code for the content type	Document Category Code	document-link/category/@code	1..1	<category code="A04"/>
	category-description	A description of the content type	Text	document-link/category/text()	0..1	<category code="A04">Conditions</category>
	title	The full title of the document	Text	document-link/title/text()	1..1	<title>Project Conditions</title>
Activity Budgets	budget	The value of the aid activity's budget for each financial year as in the original project document.		budget	0..*	This is most useful by the financial year of the recipient country. (If that is not available, can be provided for each calendar year and/or financial year of the donor.)
	type	Is budget original or revised	Budget Type Code	budget/@type	1..1	<budget type="original">
	period-start	ISO 8601 code for the start date of the reporting period (yyyy-mm-dd).	Date	budget/period-start	1..1	<period-start>2011-01-01</period-start>
	period-end	ISO 8601 code for the end date of the reporting period (yyyy-mm-dd).	Date	budget/period-end	1..1	<period-end>2011-12-31</period-end>
	value	The total budget for the specified period in the specified currency. (Positive integer.)	Integer	budget/value/text()	1..1	<value value-date="2010-10-01">700000</value>
	value-date	Date of value for currency conversions.(yyyy-mm-dd)	Date	budget/value/@value-date	1..1	<value value-date="2010-10-01">700000</value>
	currency	The ISO 4217 code for the currency in which the project is denominated. [only if different to default currency]	Currency Code	budget/value/@currency	0..1	<value currency="GBP" value-date="2010-10-01">700000</value>
Planned Disbursements	planned-disbursement	The amount it is planned to disburse on the activity in each of the next three financial years.		planned-disbursement	0..*	This is most useful by the financial year of the recipient country. (If that is not available, can be provided for each calendar year and/or financial year of the donor.)
	date-updated	The date on which this line of information was last updated. Previous updates for the same period should also be reported.	Date	planned-disbursement/@updated		<planned-disbursement updated="2010-12-01">
	period-start	ISO 8601 code for the start date of the reporting period (yyyy-mm-dd).	Date	planned-disbursement/period-start	1..1	<period-start>2011-01-01</period-start>
	period-end	ISO 8601 code for the end date of the reporting period	Date	planned-	1..1	<period-end>2011-12-31</period-end>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
		(yyyy-mm-dd).		disbursement/period-end		
	value	The amount to be disbursed in the specified currency. (Positive integer.)	Integer	planned-disbursement/value/text()	1..1	<value value-date="2010-11-01">7000</value>
	value-date	Date of value for currency conversions.(yyyy-mm-dd)	Date	planned-disbursement/value/@value-date	1..1	<value value-date="2010-11-01">7000</value>
	currency	The ISO 4217 code for the currency of the disbursement. [only if different to default currency	Currency Code	planned-disbursement/value/@currency	0..1	<value currency="GBP" value-date="2010-11-01">7000</value>
Conditions				conditions	0..1	
	attached	A yes/no (1/0) value stating whether there are conditions attached to the activity	Boolean	conditions/@attached	1..1	<conditions attached="0" />
	condition	Multiple conditions allowed		conditions/condition	1..*	
	type	Condition type – e.g. policy, performance.	Condition Type Code	conditions/condition/@type	0..1	<condition type="policy" />
	description	The text describing the conditions attached to the activity	Text	conditions/condition/text()	0..1	<condition type="policy"> <i>text of conditions to go here</i> </condition>
Recipient Country Budget Identifier		Under development				
Sub-national Geographic Location (Optional)				location	0..*	<location percentage="5"/>
	percentage	If more than one location is reported, percentage of activity commitment allocated to this location (if available).	Integer	location/@percentage	0..1	
	type	The type of location - relevant to this activity. E.g. Kampala may be a city or a district.	Location Type Code	location/location-type/@ode	1..1	<location-type code="PPL"/>
	name	The name of the location	Text	location/name/text()	1..*	<name>Buwenge</name>
	language	For reporting the name in multiple languages where a location is commonly known by different names in different languages. (e.g. Ivory Coast, Cote D'ÃIvoire).	Language Code	location/name/@xml:lang	0..*	
	description	A free text description to clarify, if necessary, what the actual target of the activity is.	Text	location/description/text()	0..1	<description>Buwenge hospital</locdesc>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	administrative	Definition of national and sub-national administrative divisions		location/administrative	0..1	<administrative country="AF" adm1="KAN">Kandahar Province, Afghanistan</administrative>
	country	Only required for multi-country activities.	Country Code	location/administrative/@country	0..1	
	adm1	The first-level administrative subdivision code	Admin-1 Code	location/administrative/@adm1	0..1	
	adm2	The second-level administrative subdivision code	Admin-2 Code	location/administrative/@adm2	0..1	
	administrative-description	Text description of national and sub-national administrative divisions	Text	location/administrative/text()	0..1	
	coordinates	The geographic coordinates of the location		location/coordinates	0..1	<coordinates latitude="0.651922" longitude="33.16983" precision="1"/>
	latitude	The latitude coordinates. Decimal format. North = positive. South = negative.	Decimal	location/coordinates/@latitude	1..1	
	longitude	The longitude coordinates. Decimal format. East = positive. West = negative.	Decimal	location/coordinates/@longitude	1..1	
	precision	The precision category which defines the context of the reported coordinates	Precision Code	location/coordinates/@precision	1..1	
	gazetteer-entry	Gazetteers are public registries of geographical data which store a range of attributes for each defined object. Coordinates, administrative areas, type of location, etc can all be retrieved from a gazetteer identifier.		location/gazetteer-entry	0..*	<gazetteer-entry gazetteer-ref="geonames.org"> 167483</gazetteer-entry>
	gazetteer-agency	The agency/gazetteer for which the corresponding identifier is a record key.	Gazetteer Agency Code	location/gazetteer-entry/@gazetteer-ref	1..1	
	gazetteer-identifier	The identifier that links coordinates to a gazetteer database record	Integer	location/gazetteer-entry/text()	1..1	
Results	result			result	0..*	<result>
	result-type	Whether it is an output, outcome, or impact indicator	Result Type Code	result/@type	1..1	<result type="output"/>
	result-title	A title or brief text description of the result the activity is aiming to achieve e.g. build 10 schools. Repeated for different languages.		result/title	0..*	
	title	A title or brief text description	Text	result/title/text()	1..1	<title>Build 10 schools</title>
	language	The ISO 639 code for the language of the title. Only	Language	result/title/@xml:lang	0..1	<title xml:lang="en">Build 10

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
		required if different from the activity's default language.	Code			schools</title>
	result-description	A longer text description of the result the activity is aiming to achieve. Repeated for different languages.		result/description	0..*	
	description	A longer text description	Text	result/description/text()	1..1	<title>Build 10 schools</title> <description>A longer description</description>
	language	The ISO 639 code for the language of the description. Only required if different from the activity's default language.	Language Code	result/description/@xml:lang	0..1	<result type="output"/> <description xml:lang="en">long description</description> </result>
	indicator	The indicator(s) that meet the results. There can be multiple indicators for each 'result'		result/indicator	0..*	
	measure	The type of measurement for the indicator value e.g. unit, percentage	Indicator Measure Code	result/indicator/@measure	1..1	<indicator measure="unit">
	Indicator-title	The title of the indicator. Repeated for different languages.			0..*	
	title	The title of the indicator.	Text	result/indicator/title/text()	1..1	<title>gross primary school enrolment rate</title>
	language	The ISO 639 code for the language of the title. Only required if different from the activity's default language.	Language Code	result/indicator/title/@xml:lang	0..1	<title xml:lang="en">Gross primary school enrolment rate</title>
	indicator-description	The description of the indicator. Repeated for different languages.			0..*	
	description	The description of the indicator.	Text	result/indicator/description/text()	1..1	<description>A longer description of the indicator</description>
	language	The ISO 639 code for the language of the description. Only required if different from the activity's default language.	Language Code	result/indicator/description/@xml:lang	0..1	<description xml:lang="en">A longer description of the indicator</description>
	baseline	The baseline measure for the indicator		result/indicator/baseline	0..1	
	baseline-year	The year the baseline measure was taken	YYYY	result/indicator/baseline/@year	1..1	<baseline year="2008" value="55%">Baseline comment</baseline>

Section	Item	Definition	Data Format	XML	Occur	Examples and Notes
	baseline-value	The baseline measure.	Text	result/indicator/baseline/@value	1..1	
	baseline-comment	A comment on the baseline measure	Text	result/indicator/baseline/text()	0..1	
	target	There can be many targets set as milestone measures.		result/indicator/target	0..*	<target year="2015" value="85%">Target Comment</target>
	target-year	The year the result is aiming to be realised. There can be many targets set as milestone measures.	YYYY	result/indicator/target/@year	1..1	
	target-value	The target value	Text	result/indicator/target/@value	1..1	
	target-comment	The target comment for the indicator.	Text	result/indicator/target/text()	0..1	
	actual	A record of the achieved result, or interim measures to track progress		result/indicator/actual	0..*	<actual year="2010" value="62%">Actual Comment</actual>
	actual-year	The year the actual measure was taken	YYYY	result/indicator/actual/@year	1..1	
	actual-value	The actual measure.	Text	result/indicator/actual/@value	1..1	
	actual-comment	A comment on the achieved result, or an interim measure to track progress	Text	result/indicator/actual/text()	0..1	