


































# IATI Publisher: Activity Standard

This document provides all content about each data field of the IATI Activity Standard that is found on [IATI Publisher](https://iatistandard.org/en/publisher/). Please contact the IATI Helpdesk: [support@iatistandard.org](mailto:support@iatistandard.org) for any queries about the following information.

Click a category of data

 title	 reporting-org	 iati-identifier	 other-identifier	 description	 activity-status
 activity-date	 activity-scope	 recipient-country	 recipient-region	 sector	 tag
 policy-marker	 collaboration-type	 default-flow-type	 default-finance-type	 default-aid-type	 default-tied-status
 country-budget-items	 humanitarian-scope	 capital-spend	 related-activity	 conditions	 legacy-data
 document-link	 contact-info	 location	 planned-disbursement	 participating-org	 budget
 result	 transactions	 <b>Core Elements</b> Core elements include the IATI Standard's “mandatory and recommended” elements and it is important to provide this data to ensure your data is usable and useful.			

## title

Data field	IATI Standard Reference definition	Explanation
<b>title</b>	A short, human-readable title that contains a meaningful summary of the activity. May be repeated for different languages. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide the title for this activity. For example: "Water for Women Malawi".
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.

## reporting org

Data field	IATI Standard Reference definition	Explanation
<b>reporting organisation</b>	<p>The organisation issuing the report. May be a primary source (reporting on its own activity as donor, implementing agency, etc) or a secondary source (reporting on the activities of another organisation).</p> <p>Specifying the @ref attribute is mandatory. May contain the organisation name as content.</p> <p><a href="#">IATI Standard Reference</a></p>	This is your IATI Organisation Identifier (it is the unique ID that was generated for your organisation when you registered). <a href="#">For more information.</a>
narrative	The name of the organisation. May be repeated for different languages. <a href="#">IATI Standard Reference</a>	This is the name you provided for your organisation when you registered.

language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, then your default language is assumed.
----------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------

## iati identifier

Data field	IATI Standard Reference definition	Explanation
<b>iati identifier</b>	<p>A globally unique identifier for the activity.</p> <p>This MUST be prefixed with EITHER the current IATI organisation identifier for the reporting organisation (reporting-org/@ref) OR a previous identifier reported in other-identifier, and suffixed with the organisation's own activity identifier. The prefix and the suffix should be separated by a hyphen "-".</p> <p>Once an activity has been reported to IATI its identifier MUST NOT be changed in subsequent updates. <a href="#">IATI Standard Reference</a></p>	<p>This is autogenerated by adding your activity-identifier to the end of your Organisation Identifier (this is the unique ID that was generated for your organisation when you registered). <a href="#">Further guidance</a>.</p> <p>Once an activity has been reported to IATI its identifier MUST NOT be changed in subsequent updates. <a href="#">For more information</a>.</p>
activity-identifier		<p>Enter a unique series of letters and / or numbers to identify your activity. For example PROJECT-00120467 or AFG-COVAX.</p> <p>You must make sure:</p> <p>Each IATI identifier you publish is unique.</p> <p>Each IATI identifier should not start or end with whitespace.</p> <p>Only use numbers, letters and dashes to form your IATI identifiers. Once you have published an activity its IATI identifier must not change. <a href="#">Further guidance</a>.</p>

## other identifier

Data field	IATI Standard Reference definition	Explanation
<b>other identifier</b>	Another identifier for the activity. This may be a publishers own identifier that it wishes to record with the activity. This element is also used to trace changes to activity identifiers, for example when an organisation has changed it's organisation identifier. <a href="#">IATI Standard Reference</a>	
reference	The identifier you wish to report. This can be used to report a number of different types of identifiers. See the OtherIdentifierType codelist for details and options.  This attribute is required. <a href="#">IATI Standard Reference</a>	Please provide the identifier related to this activity.
type	The type of identifier being reported, taken from the OtherIdentifierType codelist.  This attribute is required. <a href="#">IATI Standard Reference</a>	If you want to record another identifier related to this activity, you <b>must</b> select which type of identifier you are providing. See descriptions of all possible types in the <a href="#">Other Identifier Type codelist</a> .
owner org	Where applicable, the organisation that owns the other identifier being reported. When used, then either other-identifier/owner-org/@ref or other-identifier/owner-org/narrative/text() MUST be present. <a href="#">IATI Standard Reference</a>	
reference	Where applicable, the organisation that owns the other identifier being reported. When used, then either other-identifier/owner-org/@ref or other-identifier/owner-org/narrative/text() MUST be present. IATI Standard Reference	Please provide the Organisation Identifier of the owner of the other identifier for the activity. If your organisation is not the owner, you can search other organisations in the <a href="#">IATI Publisher List</a> . If you cannot find the organisation, see <a href="#">further guidance</a> .
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide a description of the other identifier for the activity.

language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, then your default language is assumed.
----------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----------------------------------------------------------------------------------------------------------------------------------

## description

Data field	IATI Standard Reference definition	Explanation
<b>description</b>	A longer, human-readable description containing a meaningful description of the activity. May be repeated for different languages. <a href="#">IATI Standard Reference</a>	
type	Activity description types. (General, objectives, etc)  <a href="#">IATI Standard Reference</a>	Select the type of description that best describes your activity.  1. <b>General</b> - Unstructured, long description of the activity  2. <b>Objectives</b> - Specific objectives for the activity, e.g. taken from logical framework  3. <b>Target Groups</b> - Details of groups that are intended to benefit from the activity  4. <b>Other</b> - For miscellaneous use. A further classification or breakdown may be included in the narrative
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a> .	Provide a description for your activity. For example: "This project will improve maternal and child health seeking behaviours among 800 pregnant women and 6,500 caregivers of children under five in [location], thereby contributing to a reduction in the high maternal and under-five mortality and morbidity rates in these communities".
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.

	present, the default language is assumed. <a href="#">IATI Standard Reference</a>	
--	-----------------------------------------------------------------------------------	--

## activity status

Data field	IATI Standard Reference definition	Explanation
<b>activity status</b>	The current status of the activity.. <a href="#">IATI Standard Reference</a>	An activity status should be provided. This describes the lifecycle status of the activity from pipeline to completion. You can publish activities that are already completed, currently happening or not yet started. As the activity progresses over time, the activity status should be updated.
code	<p>An IATI code defining the current status of the activity.</p> <p>This attribute is required. <a href="#">IATI Standard Reference</a></p>	<p>Select an option that defines the current status of your activity.</p> <ol style="list-style-type: none"> <li>1. <b>Pipeline/identification:</b> The activity is being scoped or planned</li> <li>2. <b>Implementation:</b> The activity is currently being implemented</li> <li>3. <b>Finalisation:</b> Physical activity is complete or the final disbursement has been made, but the activity remains open pending financial sign off or M&amp;E</li> <li>4. <b>Closed:</b> Physical activity is complete or the final disbursement has been made</li> <li>5. <b>Canceled:</b> The activity has been canceled</li> <li>6. <b>Suspended:</b> The activity has been temporarily suspended</li> </ol>

## activity date

Data field	IATI Standard Reference definition	Explanation
<b>activity date</b>	The planned and actual start and completion dates of the activity. Start dates may reflect either the commencement of funding, planning or physical activity. End dates should, wherever possible, reflect the ending of physical activity. <a href="#">IATI Standard Reference</a>	
type	An IATI code defining the type of activity date being reported.  This attribute is required. <a href="#">IATI Standard Reference</a>	Please select the type of activity date that you will report. <ol style="list-style-type: none"> <li>1. <b>Planned start:</b> The date on which the activity is planned to start, for example the date of the first planned disbursement or when physical activity starts.</li> <li>2. <b>Actual start:</b> The actual date the activity starts, for example the date of the first disbursement or when physical activity starts.</li> <li>3. <b>Planned End:</b> The date on which the activity is planned to end, for example the date of the last planned disbursement or when physical activity is complete.</li> <li>4. <b>Actual end:</b> The actual date the activity ends, for example the date of the last disbursement or when physical activity is complete.</li> </ol>
iso date	This attribute is required. This value must be of type xsd:date. 1: The planned start date of the activity must be before the planned end date. 2: The actual start date of the activity must be before the actual end date. 3: The actual start date of the activity must not be in the future.	Provide the date of your activity.

	4: The actual end date of the activity must not be in the future. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide any accompanying information or explanation for your chosen activity status.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, the default language is assumed.

## activity scope

Data field	IATI Standard Reference definition	Explanation
<b>activity scope</b>	The geographical scope of the activity: regional, national, sub-national, etc. <a href="#">IATI Standard Reference</a>	
code	The geographical scope.. This attribute is required. <a href="#">IATI Standard Reference</a>	<p>Select an option that best describes the scope of this activity.</p> <ol style="list-style-type: none"> <li>1. <b>Global</b> - The activity scope is global. For example, some activities, such as research, are not based in or benefitting particular countries or regions</li> <li>2. <b>Regional</b> - The activity scope is a supranational region</li> <li>3. <b>Multi-national</b> - The activity scope covers multiple countries, that don't constitute a region</li> <li>4. <b>National</b> - The activity scope covers one country</li> <li>5. <b>Sub-national: Multi-first-level administrative areas</b> - The activity scope covers more than one first-level subnational administrative areas (e.g. counties, provinces, states)</li> </ol>



		<p>6. <b>Sub-national: Single first-level administrative area</b> - The activity scope covers one first-level subnational administrative area (e.g. country, province, state)</p> <p>7. <b>Sub-national: Single second-level administrative area</b> - The activity scope covers one second-level subnational administrative area (e.g. municipality or district)</p> <p>8. <b>Single location</b> - The activity scope covers one single location (e.g. town, village, farm)</p> <p><a href="#">Further guidance</a>.</p>
--	--	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

## recipient country

Data field	IATI Standard Reference definition	Explanation
<b>recipient country</b>	<p>A country that will benefit from this activity. If a specific country is not known the recipient-region element should be used instead. For geographical location, use the location element.</p> <p>Multiple countries and regions can be reported, in which case the percentage attribute <b>MUST</b> be used to specify the share of total commitments across all reported countries and regions.</p> <p>The country can also be specified at transaction rather than activity level. If recipient-country OR recipient-region are reported at the transaction level, <b>ALL</b> transactions <b>MUST</b> contain a recipient-country or recipient-region element and iati-activity/recipient-country and iati-activity/recipient-region <b>MUST NOT</b> be used.</p> <p><a href="#">IATI Standard Reference</a></p>	<p>Each activity in IATI should specify the country (e.g. China) in which the activity is taking place, or the places that will benefit from the activity. If the country is not known, then a supra-national region or regions (e.g. East Asia) must be added.</p> <p>There are several ways you can publish information on which country and/or region will benefit from this activity.</p> <p>If just <b>one</b> country or region is benefitting from this activity, you should simply select the country or region below. This means that only one country or region will be benefitting from 100% of the funding that you publish for this activity.</p> <p>However if <b>multiple</b> countries and/or regions are benefitting from your activity you can:</p> <ol style="list-style-type: none"> <li>1. Publish the recipient country or region for every individual transaction you publish for this activity. You will be required</li> </ol>

		<p>to publish data on at least one transaction for every activity that you publish (publish data on transactions). Each transaction represents money flowing in or out of the activity. You can select a different country or region for each transaction that you publish.</p> <p>If you want to provide the recipient country or region for your individual transactions, then you <b>should not</b> select a country or region for the entire activity below.</p> <ol style="list-style-type: none"> <li>2. You can select multiple countries or regions for the entire activity below. If you choose to do this, you must allocate a percentage of funding for the activity to each country and/or region.</li> <li>3. You can choose to create a separate activity for every country that is benefitting from this activity's funding.</li> </ol> <p><a href="#">Further guidance.</a></p>
code	ISO 3166-1 alpha-2 code for the country. This attribute is required. <a href="#">IATI Standard Reference</a>	Select a country benefiting from this activity. However, <b>do not</b> select a country here if you want to specify the recipient country benefiting from the individual transactions within this activity.
percentage	The percentage of total commitments or total activity budget to this item. Content must be a decimal number between 0 and 100 inclusive, with no percentage sign. Percentages for all reported countries and regions within a vocabulary MUST add up to 100. <a href="#">IATI Standard Reference</a>	Select the percentage of funding benefitting this country. Percentages for all reported countries and regions MUST add up to 100. <a href="#">Further guidance.</a>
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Add the free text name and/or description regarding the country benefitting from the activity.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not	Select the language of the text you provided in the narrative. If no language is selected, then your default language is assumed.

	present, the default language is assumed. <a href="#">IATI Standard Reference</a>	
--	-----------------------------------------------------------------------------------	--

## recipient region

Data field	IATI Standard Reference definition	Explanation
<b>recipient region</b>	A supranational geopolitical region that will benefit from this activity. For sub-national geographical location, use the location element. Multiple countries and regions can be reported, in which case the percentage attribute MUST be used to specify the share of total commitments across all reported countries and regions. Recipient-region must not be used merely to describe the region of a country reported in recipient-country, but ONLY if the region is a recipient IN ADDITION to the country. <a href="#">IATI Standard Reference</a>	<p>If you cannot identify the specific country/countries benefiting from this activity, then you should provide the region instead.</p> <p>If a region is included, it must be <i>in addition</i> to any countries specified. If the recipient country(ies) is known, then the corresponding recipient region <b>should not</b> also be added. For example, if 100% of the funding is going to Uganda, then you should record Uganda as the recipient country and you should not add that the funding is going to the region of Africa.</p> <p>However, if you know that at least 80% of the expected funding is going to Uganda, you can specify that the unknown 20% is going to the region of Africa.</p> <p><a href="#">More information</a></p>
vocabulary	Either an OECD DAC or UN region code. Codelist is determined by vocabulary attribute. This attribute is required. <a href="#">IATI Standard Reference</a>	<p>There are two lists of regions; the <a href="#">OECD DAC</a> and <a href="#">UN region</a> code lists. Please select one. IATI recommends that you use the OECD DAC codelist. Otherwise you can use another list of regions by selecting the option: 'Reporting Organisation' and providing the URI where this internal list is defined.</p> <p>If you do not choose an option, then the code list 'OECD DAC' is assumed.</p>
code	An IATI code for the vocabulary from which the region code is drawn. If it is not present 1 - 'OECD DAC' is assumed. <a href="#">IATI Standard Reference</a>	Select the region benefitting from this activity.

vocabulary uri	The URI where this vocabulary is defined. If the vocabulary is 99 (reporting organisation), the URI where this internal vocabulary is defined. While this is an optional field it is STRONGLY RECOMMENDED that all publishers use it to ensure that the meaning of their codes are fully understood by data users. <a href="#">IATI Standard Reference</a>	If you have selected the option: 'Reporting Organisation' please provide the URI where this internal list is defined.
percentage	The percentage of total commitments or total activity budget to this item. Content must be a decimal number between 0 and 100 inclusive, with no percentage sign. Percentages for all reported countries and regions within a vocabulary MUST add up to 100. <a href="#">IATI Standard Reference</a>	The percentage of total commitments or total activity budget to this item. Percentages for all reported countries and regions MUST add up to 100. <a href="#">Further guidance</a> .
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Add the free text name of this region benefitting from the activity.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, then your default value is assumed.

## Sector

Data field	IATI Standard Reference definition	Explanation
------------	------------------------------------	-------------

sector	A recognised code, from a recognised vocabulary, classifying the purpose of the activity. Sector MUST EITHER be reported here OR at transaction level for ALL transactions. <a href="#">IATI Standard Reference</a>	Provide information on the sector which the activity targets or supports. For example, primary education or agriculture. You can select more than one sector but you must provide <b>at least one</b> .
vocabulary	An IATI code for the vocabulary (see codelist) used for sector classifications. If omitted, OECD DAC 5-digit Purpose Codes are assumed. It is recommended that OECD DAC 5-digit Purpose Codes are used wherever possible. It is also recommended that if a publisher has its own classification system or systems then the vocabularies 99 or 98 (Reporting Organisation's own vocabularies) should be used in addition to DAC codes. <a href="#">IATI Standard Reference</a>	<p>Please choose the sector list from which you will select the sectors that your activity targets. IATI recommends choosing the OECD DAC 5-digit sector codelist, in which you can make a selection from over 300 sectors.</p> <p>In addition to the OECD DAC 5-digit codelist, you can also choose to use another list (see <a href="#">information on all possible options</a>). If you want to use your organisation's own list of internal sector classifications, select the option: 'Reporting Organisation'.</p> <p>You can choose to use multiple lists. If you use more than one internal sector classification, select 'Reporting Organisation 2' (which has the code 98) for the additional list.</p> <p><a href="#">Further guidance</a>.</p>
vocabulary-uri	The URI where this vocabulary is defined. If the vocabulary is 99 or 98 (reporting organisation), the URI where this internal vocabulary is defined. While this is an optional field it is STRONGLY RECOMMENDED that all publishers use it to ensure that the meaning of their codes are fully understood by data users. <a href="#">IATI Standard Reference</a>	If you have chosen to use an internal sector classification codelist, please provide a link to it.
code	The code for the sector. This attribute is required. <a href="#">IATI Standard Reference</a>	Select the sector which the activity is targeting or supporting. You can choose more than one sector.
percentage	The percentage of total commitments or total activity budget to this item. Content must be a decimal number between 0 and 100 inclusive, with no percentage sign. All reported sectors from the same vocabulary MUST add up to 100. <a href="#">IATI Standard Reference</a>	If you have selected more than one sector (from the same list), each sector must be given a percentage. These percentages can then be applied to the funding amounts to estimate the resources allocated to each sector. For example, using the OECD DAC 5-digit sector codelist you could allocate 50% of the funding for the activity to the

		sector code 'teacher training' (11130) and 50% to 'primary education' (11220).
narrative	The description of a sector defined by the reporting organisation. (Only to be used when the reporting organisation's own vocabulary is being used). <a href="#">IATI Standard Reference</a>	If you have chosen a sector from an internal sector classification codelist, please provide a description of this sector.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the description. If no language is selected, your default language is assumed.

## tag

Data field	IATI Standard Reference definition	Explanation
<b>tag</b>	Categorisations from established taxonomies that enrich the classification of the activity but that, unlike those reported in the sector element, cannot be associated with percentage splits on finances. <a href="#">IATI Standard Reference</a>	<p>You can provide other useful information about your activity through 'tagging' it to categorisations from established taxonomies.</p> <p>For example, IATI recommends that, if possible, you should tag your activity according to which UN Sustainable Development Goal(s) it is contributing to. <a href="#">Please read guidance on reporting data on the UN Sustainable Development Goals.</a></p>
code	The code for the tag as defined in the specified vocabulary. This attribute is required. <a href="#">IATI Standard Reference</a>	Choose an option from this list.
vocabulary	An IATI code for the vocabulary or taxonomy (see non-embedded codelist) used for tag classifications. <a href="#">IATI Standard Reference</a>	Choose a list. <a href="#">See information on all options.</a> You may choose to tag your activity according to an internal category list, by choosing 'Reporting Organisation'.
vocabulary-uri	The URI where this vocabulary is defined. <a href="#">IATI Standard Reference</a>	Provide a link to your chosen list.

narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	You can provide additional information on the option that you have chosen.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.

## policy marker

Data field	IATI Standard Reference definition	Explanation
<b>policy marker</b>	A policy or theme addressed by the activity. This element was designed for the reporting of OECD DAC CRS policy markers (columns 20-23 and 28-31 of the CRS++ reporting format) but the vocabulary attribute allows it use by other (including local) systems. This element can be repeated for each policy marker. <a href="#">IATI Standard Reference</a>	Provide information about the policy or theme addressed by your activity, for example: climate change mitigation or disability. An activity can have multiple policy-markers and percentages <b>do not</b> need to be added to each policy-marker.
vocabulary	An IATI code for the vocabulary to be used to define policy markers. If omitted then the OECD DAC vocabulary is assumed. <a href="#">IATI Standard Reference</a>	<p>Select a list that includes the policy marker(s) related to your activity.</p> <p><b>1 OECD DAC CRS</b> - IATI recommends that you select this list which has <a href="#">12 options</a> to choose from.</p> <p><b>99 Reporting Organisation</b> - choose this option if you want to provide a code for a policy marker that is defined and tracked by your organisation.</p>
vocabulary-uri	If the vocabulary is 99 (reporting organisation), the URI where this internal vocabulary is defined. <a href="#">IATI Standard Reference</a>	If you have selected 99 Reporting Organisation (above), please provide a link to where your chosen policy marker is listed.

code	A policy marker code from the codelist specified in the vocabulary. This attribute is required. <a href="#">IATI Standard Reference</a>	Provide the code for the policy or theme addressed by your activity. If you are using the OECD DAC CRS policy-marker list, please make a selection from <a href="#">these options</a> .
significance	An OECD DAC CRS code indicating the significance of the policy marker for this activity. This attribute MUST be used for all OECD DAC CRS vocabularies. <a href="#">IATI Standard Reference</a>	If you have chosen a policy or theme from the policy-marker OECD DAC CRS list, then you must indicate how significant it is for your activity. For example, it could be the principal objective or a significant objective for your activity. Please read <a href="#">information on all options before making a selection</a> .
narrative	A description of the policy marker. This MUST ONLY be used if vocabulary is 99 (the reporting organisation's own marker vocabulary). May be repeated for multiple languages. <a href="#">IATI Standard Reference</a>	If you have selected 99 Reporting Organisation (above), please provide a description for the policy marker(s) that you have chosen.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. This value should be on the Language codelist. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.

## collaboration type

Data field	IATI Standard Reference definition	Explanation
<b>collaboration type</b>	The type of collaboration involved in the activity's disbursements, e.g. "bilateral" or "multilateral". <a href="#">IATI Standard Reference</a>	You can describe how funds are flowing between organisations within this activity. For example, funds could be flowing bilaterally, meaning between two governments. This is largely applicable to bilateral and multilateral organisations.
code	A code from the OECD DAC CRS "Bi_Multi" codelist. <a href="#">IATI Standard Reference</a>	Please select a collaboration type, if there is an option that is applicable to your activity. See <a href="#">information on all options</a> . Otherwise, leave this blank.



## default flow type

Data field	IATI Standard Reference definition	Explanation
<b>default flow type</b>	Whether the activity is funded by Official Development Assistance (ODA), Other Official Flows (OOF), etc <a href="#">IATI Standard Reference</a>	Flow type is another way to categorise financial flows. It distinguishes the flow as official development assistance (ODA), other official flows (OOF), or several types of private flows, including private grants often provided by NGOs and other civil society organisations.
code	A code from the OECD DAC CRS “Type of flow” codelist. This attribute is required. <a href="#">IATI Standard Reference</a>	If this activity’s funds can be classified by the <a href="#">following options</a> , please make a selection here. Otherwise, leave blank.

## default finance type

Data field	IATI Standard Reference definition	Explanation
<b>default finance type</b>	The type of finance (e.g. grant, loan, debt relief, etc). This is the default value for all transactions in the activity report; it can be overridden by individual transactions. <a href="#">For more information</a>	Finance type specifies the financial instrument that is being used for this activity. For example, financing is most commonly delivered as a grant or a loan.
code	A code from the OECD DAC CRS “Type of finance” codelist. This attribute is required. <a href="#">For more information</a>	Please select a finance type for this activity from the <a href="#">following options</a> .

## default aid type

Data field	IATI Standard Reference definition	Explanation
------------	------------------------------------	-------------

<b>default aid type</b>	<p>The type of aid being supplied (project-type intervention, budget support, debt relief, etc.). This element specifies a default for all the activity's financial transactions; it can be overridden at the individual transaction level. <a href="#">For more information</a></p>	<p>You can provide information about the type of aid that is being delivered. This is most commonly referred to as the aid modality and IATI recommends that an aid type from the OECD DAC codelist be selected for all activities.</p> <p>Examples from this codelist include: project-type interventions which provide support to a particular project, budget support which is a financial contribution to a recipient government's budget. Project-type interventions is the most common aid type for NGOs and CSOs but many other options are found <a href="#">here</a>.</p> <p>If your activity is addressing a humanitarian event, you can provide specific information on the type of funds for it. This includes providing information on the level of earmarking of the activity's funds and if the activity is providing funds through cash or vouchers. <a href="#">More information on publishing aid-types related to humanitarian activities</a>.</p>
<b>vocabulary</b>	<p>A code for the vocabulary aid-type classifications. If omitted the AidType (OECD DAC) codelist is assumed. The code must be a valid value in the AidTypeVocabulary codelist. <a href="#">For more information</a></p>	<p>Select a list that includes the aid-type related to your activity (if any are applicable). Otherwise leave this blank. You can choose to select an aid-type from more than one list.</p> <p><b>1 OECD DAC</b> - IATI recommends that you select this list which has <a href="#">over 20 options</a> to choose from. Then, in addition you can select an option from another list</p> <p><b>2 Earmarking Category</b> - select <a href="#">this list</a> to categorise how flexible humanitarian funding is. There are 4 earmarking categories. Understand more about the categories in <a href="#">Annex 1</a></p> <p><b>3 Earmarking Modality</b> - use this list to choose the specific earmarking modality to describe your activity's humanitarian funding. All earmarking modality options are <a href="#">listed in Annex 1</a></p> <p><b>4 Cash and Voucher Modalities</b> - select this list to specify if your activity is responding to a humanitarian event by providing cash and voucher assistance. <a href="#">More information</a>.</p>

code	A code from the specified vocabulary. This attribute is required. <a href="#">For more information</a>	Select the aid-type related to your activity.
------	--------------------------------------------------------------------------------------------------------	-----------------------------------------------

## default tied status

Data field	IATI Standard Reference definition	Explanation
<b>default tied status</b>	Whether the aid is untied, tied, or partially tied. This element specifies a default for all the activity's financial transactions; it can be overridden at the individual transaction level. <a href="#">For more information</a>	You can state the tied status of this transaction. Here you can specify if funds are tied - where they must be spent on goods or services procured from a particular country (e.g. donor country) or group of countries. Or if funds are untied, this is where the recipient organisation is allowed to procure from any country.
code	An IATI code interpreting the usage of Columns 36-38 of the CRS++ reporting format. (Amount tied, Amount partially untied, Amount tied). <a href="#">For more information</a>	Select a default-tied-status, if applicable to your activity. See <a href="#">descriptions of all options</a> . Otherwise leave blank.

## country budget items

Data field	IATI Standard Reference definition	Explanation
country-budget-items	This item encodes the alignment of activities with both the functional and administrative classifications used in the recipient country's Chart of Accounts. This applies to both on- and off-budget activities. <a href="#">IATI Standard Reference</a>	
vocabulary	An IATI code for the common functional classification or country system (This allows for common codes, country-specific, or any other classification agreed between countries and donors). <a href="#">IATI Standard Reference</a>	

budget-item	Identifier for a single item in the recipient-country budget. If more than one identifier is reported the percentage share must be reported and all percentages should add up to 100 percent. <a href="#">IATI Standard Reference</a>	
code	A code for the budget-item from the vocabulary specified. This attribute is required. <a href="#">IATI Standard Reference</a>	
percentage	When multiple budget-item elements are declared within a single country-budget-items element, then, for each vocabulary used, the percentage values should sum 100%. <a href="#">IATI Standard Reference</a>	If no value is selected, default value is assumed.
description	A longer, human-readable description of the budget-item. May be repeated for different languages. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.

## humanitarian scope

Data field	IATI Standard Reference definition	Explanation
<b>humanitarian</b>	Classification of emergencies, appeals and other humanitarian events and actions.	The 'humanitarian-scope' element can be used to specify the emergency and/or appeal that your activity is responding to

	<a href="#">IATI Standard Reference</a>	
type	<p>A code for the type of event or action being classified.</p> <p><a href="#">IATI Standard Reference</a></p>	<p>Select which type of information you can provide:</p> <ul style="list-style-type: none"> <li> <b>Emergencies (type 1)</b>            Select this option if you can provide the <a href="#">GLIDE number</a> for the specific humanitarian emergency that your activity is responding to. Alternatively, select this option if you can declare a code for the emergency from another public list.         </li> <li> <b>Appeals (type 2)</b>            Select this option if your activity is contributing to a UN Office for the Coordination of Humanitarian Affairs (OCHA) <a href="#">Humanitarian Response Plan or Flash Appeal</a>. These codes are created by UN OCHA for use in their Financial Tracking Service (FTS). Alternatively, select this option if you can declare a code for the appeal from another public list.         </li> </ul>
vocabulary	<p>A code for a recognised vocabulary of terms classifying the event or action.</p> <p>This attribute is required. <a href="#">IATI Standard Reference</a></p>	<p>Select the list that you will use to identify the emergency or appeal that your activity is responding to:</p> <p><b>1-2 <a href="#">Glide</a></b>  <b>2-1 <a href="#">Humanitarian Plan</a></b>  <b>99 Reporting Organisation</b> - select this option if you can declare a code for the emergency or appeal from an alternative public list.</p>
vocabulary-uri	<p>A u.r.i. for the vocabulary specified which provides access to the list of codes and descriptions. <a href="#">IATI Standard Reference</a></p>	<p>Provide a link to the list of emergencies or appeals that you will use, which includes its codes and descriptions.</p>
code	<p>A code for the event or action from the vocabulary specified. <a href="#">IATI Standard Reference</a></p>	<p>Provide the code for the specific emergency or appeal that your activity is responding to.</p> <p>For example, if you are providing a code for an emergency that has a <a href="#">Glide Number</a>, the format for this code would be: [Emergency Type] + [Year] + [Number] + [Country].</p>
narrative	<p>The description of the code specified. <a href="#">IATI Standard Reference</a></p>	<p>If you have used a code for the emergency or appeal from an alternative public list (i.e. you have selected 99 Reporting</p>

		Organisation above), please provide a description of the code that you have specified.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.

## capital spend

Data field	IATI Standard Reference definition	Explanation
<b>capital spend</b>	The percentage of the total commitment that is for capital spending. <a href="#">IATI Standard Reference</a>	Please indicate how much of the total activity's funding will be spent on capital. Capital describes physical assets with a useful life of more than one year. For example, a road.
<b>percentage</b>	The percentage of the total commitment allocated to or planned for capital expenditure. Content must be a decimal number between 0 and 100 inclusive, with no percentage sign. <a href="#">IATI Standard Reference</a>	Percentage must not exceed 100.

## related activity

Data field	IATI Standard Reference definition	Explanation
<b>related-activity</b>	Another separately reported IATI activity that is related to this one. The 'type' attribute describes	If this activity is part of a programme with multiple activities within one organisation, you should include details of all related activities.

	the type of relationship: (eg. parent, child, multifunded). It is strongly recommended that linkage between activities in a hierarchical group should always be managed by use of this element with @type of 1 (parent) or 2 (child). <a href="#">IATI Standard Reference</a>	Please read more about the <a href="#">types of related activities</a> that you can report.  Please only refer to <b>your own</b> activities here.
<b>reference</b>	A valid activity identifier (as defined in iati-activity/iati-identifier). <a href="#">IATI Standard Reference</a>	If you have a related activity to report, please provide its full activity-id (including the organisation-id part). See <a href="#">more information on activity-ids</a> . You can ask the person(s) who reported the related activity for this, or search for the activity on d-portal.org. <a href="#">See further guidance</a> .
<b>type</b>	An IATI code for the type of relationship. <a href="#">IATI Standard Reference</a>	Please select the type of relationship between the activity being reported and the related activity <a href="#">from this list</a> .

## conditions

Data field	IATI Standard Reference definition	Explanation
<b>conditions</b>	Specific terms and conditions attached to the activity that, if not met, may influence the delivery of commitments made by participating organisations. <a href="#">IATI Standard Reference</a>	<p>Please declare any conditions or specific terms that are attached to this activity. For example, requirements issued by your funder or a six month review to assess whether or not the activity is worth continuing.</p> <p>If a condition relates to the whole organisation, such as organisation-wide terms and conditions, it should not be reported within this activity. Instead, you should report this in the document-link element in your organisation file.</p> <p><a href="#">Further guidance</a>.</p>
attached	A yes/no (1/0) value stating whether there are conditions attached to the activity. It is strongly recommended that this attribute is reported, even if there are no conditions attached (i.e. attached="0"). <a href="#">IATI Standard Reference</a>	Please select 'Yes' if your activity has a condition attached to it or 'No' if it does not.

condition	The text of a specific condition attached to the activity. Organisation-wide terms and conditions that apply to all activities should not be reported here, but in either iati-organisation/document-link or iati-activity-document-link. <a href="#">IATI Standard Reference</a>	
type	An IATI code defining the type of condition. <a href="#">IATI Standard Reference</a>	<p>Select the type of condition that you want to report. Three types of condition can be reported:</p> <p><b>Policy:</b> e.g. a particular policy needs to be implemented by the organisation receiving funds.</p> <p><b>Performance:</b> e.g. certain outputs or outcomes need to be achieved.</p> <p><b>Fiduciary:</b> e.g. the recipient is required to use certain public financial management or public accountability measures.</p> <p><a href="#">Full description of types.</a></p>
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	<p>Provide a short description of the condition here.</p> <p>You can provide more information by adding a link to a relevant document or webpage in the activity document-link element.</p>
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.

## legacy data

Data field	IATI Standard Reference definition	Explanation
<b>legacy-data</b>	The legacy data element allows for the reporting of values held in a field in the reporting organisation's	You can link this activity to your organisation's internal data and record which IATI Standard element it most relates to.



	system which is similar, but not identical to an IATI element. <a href="#">IATI Standard Reference</a>	
name	The original field name in the reporting organisation's system. <a href="#">IATI Standard Reference</a>	
value	The original field value in the reporting organisation's system. <a href="#">IATI Standard Reference</a>	
iati-equivalent	The name of the equivalent IATI element. <a href="#">IATI Standard Reference</a>	

## document link

Data field	IATI Standard Reference definition	Explanation
<b>document link</b>	A link to an online, publicly accessible web page or document. <a href="#">For more information</a>	<p>You can report further information about this activity by providing a publicly accessible link to a document or webpage.</p> <p>If documents are available in other languages and stored separately, please provide them by creating additional document elements.</p> <p><a href="#">Further guidance</a></p>
url	The target URL of the external document, e.g. " <a href="http://www.example.org/doc.odt">http://www.example.org/doc.odt</a> ". <a href="#">For more information</a>	The URL must begin with either 'http://' or 'https://'.
format	An IANA code for the MIME type of the document being referenced, e.g. "application/pdf". <a href="#">For more information</a>	If you know the format of the document file, please type it <a href="#">using an option from this list</a> .
title	A short, human-readable title. <a href="#">For information</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">For more information</a>	Provide a short title for the document or webpage.
language	A code specifying the language of text in this	Select the language of the text in the narrative. If no language is

	element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">For more information</a>	selected, your default language is assumed.
description	A description of the document contents, or guidance on where to access the relevant information in the document. <a href="#">For more information</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">For more information</a>	Provide a short description of the document or webpage, including any instructions on where to find relevant information.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">For more information</a>	Select the language of the text in the description. If no language is selected, your default language is assumed.
category	IATI Document Category Code. <a href="#">For more information</a>	You must select a category of the document or webpage that you have provided.
code	An IATI code defining the category of the document. <a href="#">For more information</a>	Select a category of the document or webpage that you have provided from <a href="#">this list</a> .
language	The ISO 639-1 language code in which target document is written, e.g. "en". Can be repeated to describe multi-lingual documents. <a href="#">For more information</a>	
code	ISO 639-1 language code. <a href="#">For more information</a>	Select the language of the document or webpage.
document date	The date of publication of the document that is being linked to. (@iso-date). <a href="#">For more information</a>	
date	The date of publication of the document that is being linked to. <a href="#">For more information</a>	Provide the date of publication for the document or webpage, or provide the date that it was last updated.

## contact info

Data field	IATI Standard Reference definition	Explanation
------------	------------------------------------	-------------

<b>contact info</b>	Contact information for the activity. Specify whatever is available. You may repeat this element for each contact person. <a href="#">IATI Standard Reference</a>	
type	The type of contact. See IATI codelist for values. <a href="#">IATI Standard Reference</a>	
organisation	The name of the organisation to contact IATI Standard Reference about the activity. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide the name of the organisation to contact for more information about the activity.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, then your default language is assumed.
department	The department within the organisation to contact IATI Standard Reference about the activity. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide the name of the department within the organisation to contact for more information about the activity.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
person name	The name of the contact person for the activity. <a href="#">IATI Standard Reference</a>	

narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide the name of the contact for more information about the activity.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, the default language is assumed.
job title	The job title of the contact person at the organisation. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide the job title of the contact at the organisation.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, then your default language is assumed.
telephone	The contact telephone number. May be repeated for multiple numbers. <a href="#">IATI Standard Reference</a>	
email	The contact email address. May be repeated for multiple addresses. <a href="#">IATI Standard Reference</a>	
website	The contact web address. May be repeated for multiple sites. <a href="#">IATI Standard Reference</a>	
mailing address	The contact mailing address. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide any further information about this contact.
language	A code specifying the language of text in this element. It is recommended that wherever possible	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.

	only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	
--	---------------------------------------------------------------------------------------------------------------------------------	--

## location

Data field	IATI Standard Reference definition	Explanation
<b>location</b>	The sub-national geographical identification of the target locations of an activity. These can be described by gazetteer reference, coordinates, administrative areas or a textual description. Any number of locations may be reported. <a href="#">IATI Standard Reference</a>	<p>Provide the sub-national location/s of an activity, if it is known. However <b>location data should only be added when it is safe to do so</b>. It is the publishing organisation's responsibility to ensure that the data it publishes is safe.</p> <p>You can provide geographic coordinates of a location, the name and description of a location, the administrative area or other features of the location e.g. health centre, village etc.</p> <p><a href="#">Further guidance</a>.</p>
reference	An internal reference that describes the location in the reporting organisation's own system. <a href="#">IATI Standard Reference</a>	You can provide an internal reference used by your organisation to describe the location for example: AF-KAN.
location reach	Does this location describe where the activity takes place or where the intended beneficiaries reside? <a href="#">IATI Standard Reference</a>	Please specify if the location describes where the <i>activity takes place</i> or where the <i>intended beneficiaries reside</i> .
code	An IATI code for the geographic scope of the activity. This attribute is required. <a href="#">IATI Standard Reference</a>	<p>Please choose an option to describe the reach of the location.</p> <ol style="list-style-type: none"> <li><b>Activity</b> - The location specifies where the activity is carried out</li> <li><b>Intended Beneficiaries</b> - The location specifies where the intended beneficiaries of the activity live</li> </ol>

location-id	A unique code describing the location according to a recognised gazetteer or administrative boundary repository. Administrative areas should only be reported here if the location being defined is the administrative area itself. For describing the administrative area/s within which a more specific location falls the location/administrative element should be used. <a href="#">IATI Standard Reference</a>	You can provide a unique code describing the location according to a recognised gazetteer or administrative boundary repository. You can select an option of a gazetteer or administrative boundary repository from the list below.
vocabulary	An IATI code for a recognised gazetteer or administrative boundary repository.  This attribute is required. <a href="#">IATI Standard Reference</a>	Please select the gazetteer or administrative boundary repository that you will provide a code from. <a href="#">View more information about each option</a> .
code	A code from the gazetteer or administrative boundary repository specified by the vocabulary  <a href="#">IATI Standard Reference</a>	Provide a unique code describing the location with a recognised gazetteer or administrative boundary repository ( <a href="#">see list</a> ).
name	The human readable name for the location. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide the free text name of the location of the activity.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, then your default language is assumed.
description	A description that qualifies the location, not the activity. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide a description of the location of the activity.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not	Select the language of the text in the narrative. If no language is selected, your default language is assumed.

	present, the default language is assumed. <a href="#">IATI Standard Reference</a>	
activity description	A description that qualifies the activity taking place at the location. This should not duplicate information provided in the main activity description, and should typically be used to distinguish between activities at multiple locations within a single iati-activity record. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.
administrative	Coded identification of national and sub-national divisions according to recognised administrative boundary repositories. Multiple levels may be reported. <a href="#">IATI Standard Reference</a>	You can provide a unique code to describe the activity location according to an administrative boundary repository.
vocabulary	The code for the administrative area being reported from the vocabulary specified. <a href="#">IATI Standard Reference</a>	Select an <a href="#">administrative boundary list</a> that includes a code to represent your activity location.
code	An IATI code for a recognised administrative boundary repository. <a href="#">IATI Standard Reference</a>	Provide a code to represent your activity location (from your chosen <a href="#">administrative boundary list</a> ).
level	A number defining a subdivision within a hierarchical system of administrative areas. The precise system for defining the particular meaning of each @level value is determined by the @vocabulary being used. <a href="#">IATI Standard Reference</a>	Within your chosen <a href="#">administrative boundary list</a> , you can provide a number to define a subdivision within a hierarchical system of administrative areas.
point	The point element is based on a subset of the GML 3.3 Point element.	You can provide geo-coordinates for the location, in the format of latitude and longitude coordinates.

	<a href="#">IATI Standard Reference</a>	<p>Coordinates are published using the point and pos elements. The point element is always: &lt;point srsName="http://www.opengis.net/def/crs/EPSSG/0/4326"&gt;</p> <p>The pos element then contains the latitude coordinate (the first number), followed by the longitude coordinate (the second number) e.g. -46.7733 167.6321.</p> <p>Please note that coordinates can refer to an 'exact' or an 'approximate' location. This should be specified using the location exactness element.</p> <p><a href="#">More information.</a></p>
srs Name	The name of the spatial reference system used by the coordinates. <a href="#">IATI Standard Reference</a>	This value never changes.
pos	The latitude and longitude coordinates in the format "lat lng". <a href="#">IATI Standard Reference</a>	<p>Add latitude and longitude separated by a space e.g. 31.616944 65.716944</p> <p>If you don't already have a way to find the coordinates for an activity, there are some online platforms to help, e.g. <a href="#">Google Maps</a> and <a href="#">Latlong.net</a>. To find the coordinates for an activity on Google Maps, right-click over the location of the activity and select 'what's here?'. The coordinates will then be presented. Alternatively, type in the coordinates and the location of the activity that will be pinpointed on the map.</p> <p><a href="#">More information.</a></p>
exactness	Defines whether the location represents the most distinct point reasonably possible for this type of activity or is an approximation due to lack of more detailed information. <a href="#">IATI Standard Reference</a>	
code	A code from the Geographic Exactness Codelist. This attribute is required. <a href="#">IATI Standard Reference</a>	If you have provided the geo-coordinates for the activity location, then select an option from the <a href="#">Geographic Exactness list</a> to specify whether the location is exact or approximate.



location class	Whether the location refers to a structure, a populated place (e.g. city or village), an administrative division, or another topological feature (e.g. river, nature reserve). <a href="#">IATI Standard Reference</a>	
code	A code from the Location Class codelist. This attribute is required. <a href="#">IATI Standard Reference</a>	Please specify the form of the activity location from the <a href="#">Geographic Location Class list</a> . For example a populated place (town, farm), or topographical feature (mountain, river).
feature designation	A more refined coded classification of the type of feature referred to by this location. <a href="#">IATI Standard Reference</a>	
code	A feature designation code from the authorised list (maintained by the US National Geospatial-Intelligence Agency). <a href="#">IATI Standard Reference</a>	You can provide more detail on the type of your activity's location (e.g. beach, well or college). Please make a selection from the <a href="#">Location Type list</a> .

## planned disbursement

Data field	IATI Standard Reference definition	Explanation
<b>planned disbursement</b>	The planned disbursement element should only be used to report specific planned cash transfers. These should be reported for a specific date or a meaningfully predictable period. <a href="#">IATI Standard Reference</a>	<p>You can publish data on your planned cash transfers to organisations (or between two other organisations) as part of this activity.</p> <p>The purpose of planned disbursements is to publish predefined payment schedules. Planned disbursements should be reported for a specific date or a meaningfully predictable period. Planned disbursements should be reported in addition and should not replace the activity's budget.</p>

type	The purpose of planned-disbursement is to describe any predefined payment schedule. <a href="#">IATI Standard Reference</a>	Specify if this is an 'original' planned disbursement (prepared when the original commitment was made) or has subsequently been 'revised'.
period-start	The exact date of the planned disbursement OR the starting date of the period in which this specific disbursement will be made. <a href="#">IATI Standard Reference</a>	
date	The exact date of the planned disbursement OR the starting date of the period in which this specific disbursement will be made. <a href="#">IATI Standard Reference</a>	
period-end	The ending date for the period in which this specific disbursement will be made. <a href="#">IATI Standard Reference</a>	
date	The ending date for the period in which this specific disbursement will be made. <a href="#">IATI Standard Reference</a>	
value	The amount that is planned to be disbursed in the specified currency. <a href="#">IATI Standard Reference</a>	
currency	A three letter ISO 4217 code for the original currency of the amount. This is required for all currency amounts unless the iati-organisation/@default-currency attribute is specified. <a href="#">IATI Standard Reference</a>	Select the currency that you have provided the value in. If no value is selected, default value is assumed.
value-date	The date to be used for determining the exchange rate for currency conversions. This attribute is required. <a href="#">IATI Standard Reference</a>	Provide the date on which the planned disbursement was agreed.
provider organisation	The organisation from which the planned disbursement will originate. If omitted the reporting-org is assumed.	Will your organisation be disbursing these funds? If so then you are the provider organisation. If not, please provide information on the organisation who will be disbursing these funds.

	<a href="#">IATI Standard Reference</a>	
reference	Machine-readable identification string for the organisation issuing the report. Must be in the format {RegistrationAgency}-{RegistrationNumber} where {RegistrationAgency} is a valid code in the Organisation Registration Agency code list and {RegistrationNumber} is a valid identifier issued by the {RegistrationAgency}. If this is not present then the narrative MUST contain the name of the organisation. <a href="#">IATI Standard Reference</a>	Please type the provider organisation's <i>IATI Organisation Identifier</i> . The quickest way to find this is to search for the organisation in the <a href="#">IATI Publisher List</a> . If you cannot find the organisation, see <a href="#">further guidance</a> .
provider-activity-id	The identifier for the activity in which the planned disbursement will be reported. If omitted the current activity is assumed. <a href="#">IATI Standard Reference</a>	The provider organisation may have published IATI data on these funds in their own activity. If so, please provide the activity-id for their activity that includes information on this funding. You can ask the provider organisation for this activity-id, or search for their activity on d-portal.org. <a href="#">See further guidance</a> .  If you are the provider organisation then leave this blank.
type	The type of organisation providing the funds. <a href="#">IATI Standard Reference</a>	Select the type that best describes the provider organisation (if this is not your organisation). <a href="#">Information on all organisation types</a> .
narrative	The name of the organisation. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If the provider organisation does not have an IATI Organisation Identifier, the name of the organisation must be given.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the name provided. If no language is selected, your default language is assumed.
receiver organisation	The organisation receiving the money from the planned disbursement. <a href="#">IATI Standard Reference</a>	Provide information on which organisation will be receiving the funds.
reference	Machine-readable identification string for the organisation issuing the report. Must be in the format {RegistrationAgency}-{RegistrationNumber} where {RegistrationAgency} is a valid code in the	Please provide the receiver organisation's <i>IATI Organisation Identifier</i> (org-ID). The quickest way to find this is to search for the organisation in the <a href="#">IATI Publisher List</a> . If you cannot find the organisation, see <a href="#">further guidance</a> .

	Organisation Registration Agency code list and {RegistrationNumber} is a valid identifier issued by the {RegistrationAgency}. If this is not present then the narrative MUST contain the name of the organisation. <a href="#">IATI Standard Reference</a>	
receiver-activity-id	If outgoing funds are being provided to another activity that is reported to IATI, this may, if possible, record the unique IATI activity identifier for that activity. <a href="#">IATI Standard Reference</a>	If possible, please provide the activity-id for the receiver's activity which will receive this disbursement. You can ask the receiver organisation for this activity-id, or search for their activity on d-portal.org. <a href="#">See further guidance</a> .
type	The type of organisation receiving the funds. <a href="#">IATI Standard Reference</a>	Select the type that best describes the receiver organisation. <a href="#">Information on all organisation types</a> .
narrative	The name of the organisation. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Add the name of the receiver organisation.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, then your default language is assumed.

## participating organisation

<b>participating organisation</b>	<p>An organisation involved with the activity. May be a donor, funder, implementing agency, etc. Specifying the @ref identifier is strongly recommended. May contain the organisation name as narrative.</p> <p>If the reporting organisation plays a role in the activity it should be repeated here. One organisation may play more than one role (eg, funding and implementing): in such a case each role should be reported and the name of the organisation repeated. <a href="#">IATI Standard Reference</a></p>	Specify which organisations are involved with this activity, and what their individual roles are. For example they could be a donor, funder, implementing agency, etc.
-----------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------

reference	Machine-readable identification string for the organisation issuing the report. Must be in the format {RegistrationAgency}-{RegistrationNumber} where {RegistrationAgency} is a valid code in the Organisation Registration Agency code list and {RegistrationNumber} is a valid identifier issued by the {RegistrationAgency}. If this is not present then the narrative MUST contain the name of the organisation. <a href="#">IATI Standard Reference</a>	Please provide the participating organisation's IATI Organisation Identifier. The quickest way to find this is to search for the organisation in the <a href="#">IATI Publisher List</a> . If you cannot find the organisation, see <a href="#">further guidance</a> .
type	The type of organisation issuing the report. <a href="#">IATI Standard Reference</a>	Select the type that best describes the participating organisation. <a href="#">Information on all organisation types</a> .
role	An IATI code describing the organisation's role in the activity (donor, agency, etc.).  This attribute is required. <a href="#">IATI Standard Reference</a>	Select an option that describes the organisation's role in the activity (funder, implementing agency, etc.):  <ol style="list-style-type: none"> <li>1. <b>Funding</b> - The government or organisation which provides funds to the activity</li> <li>2. <b>Accountable</b> - An organisation responsible for oversight of the activity and its outcomes</li> <li>3. <b>Extending</b> - An organisation that manages the budget and direction of an activity on behalf of the funding organisation</li> <li>4. <b>Implementing</b> - The organisation that physically carries out the activity or intervention.</li> </ol>
activity-id	A valid activity identifier published by the participating organisation which points to the activity that it has published to IATI that describes its role in this activity.  <a href="#">IATI Standard Reference</a>	If the participating organisation has published an activity to IATI for this activity, please provide the activity-id for their activity. You can ask the participating organisation for this, or search for their activity on d-portal.org. <a href="#">Further guidance</a> .
crs-channel-code	Under CRS++ Reporting Directives this code identifies the implementing agency. Codes ending in '00' are generic and are similar to the OrganisationType code.	

	<a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide the name of the participating organisation.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.

## budget

Data field	IATI Standard Reference definition	Explanation
<b>budget</b>	The value of the activity's budget for each financial quarter or year over the lifetime of the activity. The purpose of this element is to provide predictability for recipient planning on an annual basis. The status explains whether the budget being reported is indicative or has been formally committed. <a href="#">For more information</a>	<p>Provide the amount of finance expected to be spent as part of this activity. You need to provide budget(s) broken down by time periods of a year or less covering the whole life of the activity. Publishing budgets for each quarter is helpful for data users. A budget must not span more than 12 months.</p> <p>You should provide your budget(s) for your activity as soon as possible. You can then update this over time as more or less funding comes in, or the scope of the activity changes. <a href="#">More information</a>.</p>
type	Whether this is the original budget (prepared when the original commitment was made) or has subsequently been revised. <a href="#">For more information</a>	<p>Select the type of budget that you are providing:</p> <p><b>1 Original</b> The original budget allocated to the activity. Select this option if you are publishing information about this budget for the first time.</p> <p><b>2 Revised</b> The updated budget for an activity. Select this option if you are revising your original budget.</p> <p>For example: an activity lasts a year. The original budget was \$10,000 and was later decreased by \$2,000. The final total budget</p>

		<p>for the activity is \$8,000. You would need to create two budgets for this time period. Firstly you would add a budget with the type 'original' with the start and end date for the year, with the value of \$10,000. Once you know that the budget has been revised, you would then add another budget for the same dates, with the type 'revised' with a value of \$8,000.</p> <p>If there are further changes to the revised budget, you should change the value in the 'revised' budget. Do <u>not</u> create additional 'revised' budgets for the same time period.</p> <p>Therefore only <b>one</b> original and <b>one</b> revised budget should be published for each time period. <a href="#">More information</a>.</p>
status	<p>The status explains whether the budget being reported is indicative or has been formally committed. The value should appear within the BudgetStatus codelist. <a href="#">For more information</a></p>	<p>Please select a status for this budget:</p> <p><b>1 Indicative:</b> a non-binding estimate for the described budget</p> <p><b>2 committed</b> a binding agreement for the described budget</p> <p>If this budget changes status, you should change the status of this budget here. You should <u>not</u> create a new budget for the same time period with a different status. <a href="#">More information</a>.</p>
period-start	<p>The start of the budget period. <a href="#">For more information</a></p>	5.
date	<p>This attribute is required.</p> <p>This value must be of type xsd:date. <a href="#">For more information</a></p>	Provide the start date of the budget.
period-end	<p>The end of the period (which must not be greater than one year). <a href="#">For more information</a></p>	
date	<p>This attribute is required. This value must be of type xsd:date. <a href="#">For more information</a></p>	Provide the end date of the budget.
value	<p>The budget for this period. <a href="#">For more information</a></p>	Provide the total finance for this budget.
currency	<p>A three letter ISO 4217 code for the original currency of the amount. This is required for all</p>	Select the currency that you have provided the value in.

	currency amounts unless the iati-organisation/@default-currency attribute is specified. <a href="#">For more information</a>	
value-date	The date to be used for determining the exchange rate for currency conversions. This attribute is required. <a href="#">For more information</a>	

result

Data field	IATI Standard Reference definition	Explanation
------------	------------------------------------	-------------



result	A container for reporting outputs, outcomes, impacts and other results that stem directly from the activity. This may be repeated for each type of result reported. <a href="#">IATI Standard Reference</a> .	<p>Results describe the benefit or intended benefits of an activity; these can be broken down into types: <b>outputs</b>, <b>outcomes</b> and <b>impacts</b>. You can provide multiple results for your activity. Updating results regularly means that data users can track an activity's progress, including whether the activity was a success and what challenges were faced. Both positive and negative results should be included. See guidance for more information: <a href="#">Results Information</a> and <a href="#">Understanding results data</a>.</p> <p>Please note: security implications may prevent results data from being published, or require results to be aggregated. Any security considerations should be outlined in an organisation's <a href="#">exclusion policy</a>.</p>
type	An IATI code for the type of result being reported. <a href="#">IATI Standard Reference</a> .	<p>Select the type of result that your activity is aiming to achieve or has already achieved.</p> <p><b>Output</b> - Results of the activity that came about as a direct effect of your work and specifically, what is done, and what communities are reached. For example, X number of individuals trained.</p> <p><b>Outcome</b> - Results of the activity that produce an effect on the overall communities or issues you serve. For example lower rate of infection after a vaccination programme.</p> <p><b>Impact</b> - The long term effects of the outcomes, that lead to larger, overarching results, such as improved life-expectancy.</p> <p><b>Other</b> - Another type of result, not specified above</p>
aggregation-status	Flag indicating whether the data in the result set are suitable for aggregation. <a href="#">IATI Standard Reference</a> .	Select yes if the results data that you provide is suitable for aggregation (the data user should be able to add them up to get the total).

title	A short, human-readable title. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide a title for the result. For example 'People have access to independent media covering a diverse range of outcomes'.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text that you provided in the narrative. If no language is selected, then your default value is assumed.
description	A longer, human-readable description. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide a longer description for the result.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text that you provided in the narrative. If no language is selected, your default language is assumed.
document-link	A link to an online, publicly accessible web page or document expanding on the result. <a href="#">IATI Standard Reference</a>	You may provide more information about the result by providing a link to an online, publicly accessible web page or document.
url	The target URL of the external document, e.g. "http://www.example.org/doc.odt" <a href="#">IATI Standard Reference</a> .	Type the URL for the document that provides more information about the result. Make sure it includes "https://..."
format	An IANA code for the MIME type of the document being referenced, e.g. "application/pdf". <a href="#">IATI Standard Reference</a>	

title	A short, human-readable title. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link then you must provide a title for the document.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text that you provided in the narrative. If no language is selected, your default language is assumed.
description	A description of the document contents, or guidance on where to access the relevant information in the document. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link, then you can provide a description of the document.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text that you provided in the narrative. If no language is selected, your default language is assumed.
category	IATI Document Category Code. <a href="#">IATI Standard Reference</a>	If you have provided a document link, then you must select a category that best describes the document.
code	An IATI code defining the category of the document. <a href="#">IATI Standard Reference</a>	Select a document category from <a href="#">this list</a> .

language	The ISO 639-1 language code in which the document is written, e.g. “en”. Can be repeated to describe multi-lingual documents. <a href="#">IATI Standard Reference</a>	
code	ISO 639-1 language code. <a href="#">IATI Standard Reference</a>	Select the language that the document is written in.
document-date	The date of publication of the document that is being linked to. (@iso-date). <a href="#">IATI Standard Reference</a>	
date	The date of publication of the document that is being linked to. <a href="#">IATI Standard Reference</a>	Provide the date for when the document was published.
reference	A reference element to allow for the coded identification of results framework. <a href="#">IATI Standard Reference</a>	<p>If this result is contained in a results framework, then you may provide information about it. You can choose to provide a reference to a results framework in two ways:</p> <ol style="list-style-type: none"> <li>1. You can provide a reference to a results framework for the result here OR</li> <li>2. You can provide a reference to a results framework for each individual indicator that measures this result. For every result that you publish, you will be required to provide an indicator (which measures the result).</li> </ol> <p><b>Option 2 is recommended.</b> To implement this option, leave the next three fields blank: code, vocabulary, vocabulary-uri.</p> <p>Do note: You cannot provide a reference to a results framework for <b>both</b> the result and indicator. See guidance for more information: <a href="#">Results Information</a></p>
code	A code from the codelist identified in vocabulary that identifies a results framework. <a href="#">IATI Standard Reference</a>	

vocabulary	A code for the results framework vocabulary. The code must be a valid value in the ResultVocabulary codelist. <a href="#">IATI Standard Reference</a>	
vocabulary uri	The URI where this vocabulary is defined. If the vocabulary is 99 (reporting organisation), the URI where this internal vocabulary is defined. While this is an optional field it is STRONGLY RECOMMENDED that all publishers use it to ensure that the meaning of their codes are fully understood by data users. <a href="#">IATI Standard Reference</a>	
indicator	The indicator(s) that are measured to meet the results. There can be multiple indicators for each result. <a href="#">IATI Standard Reference</a>	<p>Indicators describe how the activity's progress towards the result is measured. Multiple indicators can be published for each result.</p> <p><b>Example usage:</b> An activity is working towards the outcome: 'people to have access to independent media covering a diverse range of outcomes'. One of the ways this is being measured is through 'the percentage of journalists who feel free to express their opinion' (which is an indicator). This is measured through a bi-annual survey where they are asked to score how free they feel on a scale of 1 - 4.</p> <p>See <a href="#">Results Information</a> for more details on this example and <a href="#">Understanding results data</a> for further examples.</p>
measure	An IATI code defining the unit of measure in which the value is reported. <a href="#">IATI Standard Reference</a>	<p>Select the unit of measurement for the indicator:</p> <p><b>Unit</b> - The indicator is measured in units e.g. number of workshops delivered.</p> <p><b>Percentage</b> - The indicator is measured in percentages e.g. percentage of the population who have received a vaccine.</p> <p><b>Nominal</b> - The indicator is measured as a quantitative nominal scale. For example gender, race etc.</p>

		<p><b>Ordinal</b> - The indicator is measured as a quantitative ordinal scale. For example: “very satisfied,” “satisfied,” “dissatisfied,” and “very dissatisfied.” In an ordinal scale, the order of answer options is what’s significant—you can’t quantify the exact difference between each answer option. The difference between responses like “very satisfied” and “satisfied,” for example, is relative, not exact.</p> <p><b>Qualitative</b> - The indicator is qualitative and this is often a description, such as detailing more favourable attitudes towards gender equality amongst trained staff.</p>
ascending	A flag describing the behaviour of the indicator. It is “true” if the indicator improves from small to large (e.g. clinics built); false if it improves from large to small (e.g. cases of a disease). <a href="#">IATI Standard Reference</a>	Select an option here if your indicator is a numerical (quantitative) measure. If a high number shows improvement, select 1 (true). If a low number shows improvement, select 0 (false).
aggregation status	Flag indicating whether the data in the result set are suitable for aggregation. <a href="#">IATI Standard Reference</a>	Select yes if the results data that you provide is suitable for aggregation (the data user should add them up to get the total).
title	A short, human-readable title. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	<p>Provide a title or brief description of the indicator. Using the same example above, a narrative could be: “The percentage of journalists who feel free to express their opinion (scoring 3 or 4 with a scale of 1 - 4)”.</p> <p>See <a href="#">Results Information</a> for more details on this example.</p>
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
description	A longer, human-readable description. <a href="#">IATI Standard Reference</a>	

narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	<p>You can provide a longer description or additional information to help explain what's being measured and how.</p> <p>Using the example above this additional information could be:</p> <p>“1 = Not at all free  2 = No, not entirely free  3 = Yes, up to some level  4 = Yes, entirely free  This is measured through a bi-annual survey amongst journalists.”</p> <p>See <a href="#">Results Information</a> for more details on this example.</p>
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text that you provided in the narrative. If no language is selected, your default language is assumed.
document link	A link to an online, publicly accessible web page or document expanding on the result. <a href="#">IATI Standard Reference</a>	You may provide more information about the result indicator by providing a link to an online, publicly accessible web page or document.
url	The target URL of the external document, e.g. "http://www.example.org/doc.odt" <a href="#">IATI Standard Reference</a> .	Provide the link to a specific results indicator being reported. Make sure it includes "https://..."
format	An IANA code for the MIME type of the document being referenced, e.g. "application/pdf". <a href="#">IATI Standard Reference</a>	
title	A short, human-readable title. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link then you must provide a title for the document.

language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">For more information</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
description	A description of the document contents, or guidance on where to access the relevant information in the document. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link, then you can provide a description of the document.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
category	IATI Document Category Code. <a href="#">IATI Standard Reference</a>	If you have provided a document link, then select a category that best describes the document.
code	An IATI code defining the category of the document. <a href="#">IATI Standard Reference</a>	Select a document category.
language	The ISO 639-1 language code in which target document is written, e.g. "en". Can be repeated to describe multi-lingual documents. <a href="#">IATI Standard Reference</a>	
code	ISO 639-1 language code. <a href="#">IATI Standard Reference</a>	Select the language that the document is written in.
document date	The date of publication of the document that is being linked to. (@iso-date). <a href="#">IATI Standard Reference</a>	



date	The date of publication of the document that is being linked to. <a href="#">IATI Standard Reference</a>	Provide the date of publication for the document.
reference	A reference element to allow for the coded identification of results framework. <a href="#">IATI Standard Reference</a>	If the indicator that you report is included in an existing results framework, please provide information on it here.
code	A code from the codelist identified in vocabulary that identifies a results framework. <a href="#">IATI Standard Reference</a>	If you selected a results framework, then provide the code for the indicator as specified in this results framework.
vocabulary	A code for the results framework vocabulary. The code must be a valid value in the ResultVocabulary codelist. <a href="#">IATI Standard Reference</a>	Select the results framework that your indicator is included in. If the results framework is not listed, select '99 Reporting Organisation'.
indicator uri	The URI where this vocabulary is defined. If the vocabulary is 99 (reporting organisation), the URI where this internal vocabulary is defined. While this is an optional field it is STRONGLY RECOMMENDED that all publishers use it to ensure that the meaning of their codes are fully understood by data users. <a href="#">IATI Standard Reference</a>	If you selected a results framework, provide a link to it. If you selected 99 (Reporting Organisation), it is strongly recommended that a link to the codelist is included here. This helps ensure that users can understand the meaning of the code.
baseline	The baseline value for the indicator. <a href="#">IATI Standard Reference</a>	<p>For each indicator please provide a baseline value, a target and the actual result achieved. The baseline is the starting point. The target is a result an organisation wants an activity to achieve in a certain period of time. The actual result is what was achieved at the end of that period.</p> <p>For example: The starting value (baseline) was 15% of journalists felt free to express their opinions. At the end of the chosen time period, the target was set at 50%. The activity achieved its target, as by the end of the period (actual) 53% of journalists felt free to express their opinions.</p> <p>See <a href="#">Results Information</a> for more details on this example and <a href="#">Understanding results data</a> for further examples.</p>

date	The date of baseline value was taken. <a href="#">IATI Standard Reference</a>	Provide the date for when the indicator's baseline was measured.
year	The year the baseline value was taken (yyyy). <a href="#">IATI Standard Reference</a>	Provide the year when the indicator's baseline was measured.
value	The baseline value. <a href="#">IATI Standard Reference</a>	Provide the baseline value. For example if the value is 15 percent, just type 15 (as you have provided the unit of measure above).  Please leave this blank if this indicator uses a qualitative measure (and add your baseline in the comment field below).
comment	A human-readable comment associated with a piece of aid information. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If the indicator is a qualitative measure, provide a descriptive baseline here.  You may also add other descriptive information about your baseline here. For example: "Baseline measured in a survey amongst 1083 journalists in country X".
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed.	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
dimension	A category used for disaggregating the result by gender, age, etc. <a href="#">IATI Standard Reference</a>	Please note: A baseline can have multiple dimensions.
name	Freetext description of a category being disaggregated. <a href="#">IATI Standard Reference</a>	For example an activity could declare the dimension's name as 'sex', with a value of 'female'.
value	Description of the value being disaggregated. <a href="#">IATI Standard Reference</a>	
document link	A link to an online, publicly accessible web page or document expanding on the result. <a href="#">IATI Standard Reference</a>	You may provide more information about the indicator baseline by providing a link to an online, publicly accessible web page or document.

url	The target URL of the external document, e.g. "http://www.example.org/doc.odt". <a href="#">IATI Standard Reference</a>	Type the URL for the document that provides more information about the indicator baseline. Make sure it includes "https://...
format	An IANA code for the MIME type of the document being referenced, e.g. "application/pdf". <a href="#">IATI Standard Reference</a>	
category	IATI Document Category Code. <a href="#">IATI Standard Reference</a>	If you have provided a document link, select a category that best describes the document.
code	An IATI code defining the category of the document. <a href="#">IATI Standard Reference</a>	Select a document category.
description	A description of the document contents, or guidance on where to access the relevant information in the document. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link, then you can provide a description of the document.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
document date	The date of publication of the document that is being linked to. <a href="#">IATI Standard Reference</a>	
date	The date of publication of the document that is being linked to. <a href="#">IATI Standard Reference</a>	Provide the date for when the document was published.
language	The ISO 639-1 language code in which target document is written, e.g. "en". Can be repeated to describe multi-lingual documents. <a href="#">IATI Standard Reference</a>	Select the language that the document is written in.

code	ISO 639-1 language code. <a href="#">IATI Standard Reference</a>	
title	A short, human-readable title. <a href="#">IATI Standard Reference</a>	If you have provided a document link then, provide a title for the document.
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
location	A location already defined and described in the iati-activity/location element. <a href="#">IATI Standard Reference</a>	
reference	A cross-reference to the internal reference assigned to a defined location: iati-activity/location/@ref. <a href="#">IATI Standard Reference</a>	
period	The period covered for the results reported. Multiple periods can be reported for a single indicator. <a href="#">IATI Standard Reference</a>	Each indicator can have a given time period with a start and an end date. This is the time period in which the indicator is being measured, e.g. agricultural season or school term.
period start	The start of the reporting period. <a href="#">IATI Standard Reference</a>	
iso date	The start of the reporting period. <a href="#">IATI Standard Reference</a>	
period-end	The end of the reporting period. <a href="#">IATI Standard Reference</a>	
date	The end of the reporting period. <a href="#">IATI Standard Reference</a>	
target	The target milestone for this period. <a href="#">IATI Standard Reference</a>	The target is a result an organisation wants an activity to achieve in a certain period of time.

value	The target value. <a href="#">IATI Standard Reference</a>	<p>Add a target value if your indicator is a numerical (quantitative) measure e.g. measured by units or percentages.</p> <p>Please leave this blank if this indicator uses a qualitative measure (and add your target in the comment field below).</p>
comment	A human-readable comment associated with a piece of aid information. <a href="#">IATI Standard Reference</a>	<p>If the indicator is a qualitative measure, provide a descriptive target here.</p> <p>You may also add other descriptive information about the target here.</p>
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
dimension	A category used for disaggregating the result by gender, age, etc. <a href="#">IATI Standard Reference</a>	
name	Freetext description of a category being disaggregated. <a href="#">IATI Standard Reference</a>	For example an activity could declare the dimension's name as 'sex', with a value of 'female'.
value	Description of the value being disaggregated. <a href="#">IATI Standard Reference</a>	
document link	A link to an online, publicly accessible web page or document expanding on the result. <a href="#">IATI Standard Reference</a>	You may provide more information about the indicator target by providing a link to an online, publicly accessible web page or document.
url	The target URL of the external document, e.g. "http://www.example.org/doc.odt". <a href="#">IATI Standard Reference</a>	Type the URL for the document that provides more information about the indicator target. Make sure it includes "https://..."
format	An IANA code for the MIME type of the document being referenced, e.g. "application/pdf". <a href="#">IATI Standard Reference</a>	

category	IATI Document Category Code. <a href="#">IATI Standard Reference</a>	If you have provided a document link, select a category that best describes the document.
code	An IATI code defining the category of the document. <a href="#">IATI Standard Reference</a>	Select a document category.
description	A description of the document contents, or guidance on where to access the relevant information in the document. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link, then you can provide a description of the document.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
document date	The date of publication of the document that is being linked to. <a href="#">IATI Standard Reference</a>	
iso date	The date of publication of the document that is being linked to. <a href="#">IATI Standard Reference</a>	Provide the date for when the document was published.
language	The ISO 639-1 language code in which target document is written, e.g. "en". Can be repeated to describe multi-lingual documents. <a href="#">IATI Standard Reference</a>	
code	ISO 639-1 language code. <a href="#">IATI Standard Reference</a>	Select the language that the document is written in.
title	A short, human-readable title. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link then you must provide a title for the document.

language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
location	A location already defined and described in the iati-activity/location element. <a href="#">IATI Standard Reference</a>	
reference	A cross-reference to the internal reference assigned to a defined location: iati-activity/location/@ref. <a href="#">IATI Standard Reference</a>	
actual	A record of the achieved result for this period. <a href="#">IATI Standard Reference</a>	The actual is what was achieved at the end of that period.
value	The actual measure. <a href="#">IATI Standard Reference</a>	<p>Add the actual value achieved, if your indicator is a numerical (quantitative) measure e.g. measured by units or percentages.</p> <p>Please leave this blank if this indicator uses a qualitative measure (and add your actual in the comment field below).</p>
comment	A human-readable comment associated with a piece of aid information. <a href="#">IATI Standard Reference</a>	<p>If the indicator is a qualitative measure, provide a descriptive of the actual result reported here.</p> <p>You may also add other descriptive information about the actual result here.</p>
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.

dimension	A category used for disaggregating the result by gender, age, etc. <a href="#">IATI Standard Reference</a>	
name	Freetext description of a category being disaggregated. <a href="#">IATI Standard Reference</a>	For example an activity could declare the dimension's name as 'sex', with a value of 'female'.
value	Description of the value being disaggregated. <a href="#">IATI Standard Reference</a>	
document link	A link to an online, publicly accessible web page or document expanding on the result. <a href="#">IATI Standard Reference</a>	You may provide more information about the actual value or result by providing a link to an online, publicly accessible web page or document.
url	The target URL of the external document, e.g. "http://www.example.org/doc.odt". <a href="#">IATI Standard Reference</a>	Type the URL for the document that provides more information about the actual value or result. Make sure it includes "https://..."
format	An IANA code for the MIME type of the document being referenced, e.g. "application/pdf". <a href="#">IATI Standard Reference</a>	
category	IATI Document Category Code. <a href="#">IATI Standard Reference</a>	If you have provided a document link, select a category that best describes the document.
code	An IATI code defining the category of the document. <a href="#">IATI Standard Reference</a>	Select a document category.
description	A description of the document contents, or guidance on where to access the relevant information in the document. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link, then you can provide a description of the document.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.



document-date	The date of publication of the document that is being linked to. <a href="#">IATI Standard Reference</a>	
date	The date of publication of the document that is being linked to. <a href="#">IATI Standard Reference</a>	Provide the date for when the document was published.
language	The ISO 639-1 language code in which target document is written, e.g. "en". Can be repeated to describe multi-lingual documents. <a href="#">IATI Standard Reference</a>	
code	ISO 639-1 language code. <a href="#">IATI Standard Reference</a>	Select the language that the document is written in.
title	A short, human-readable title. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If you have provided a document link then provide a title for the document.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text you provided in the narrative. If no language is selected, your default language is assumed.
location	A location already defined and described in the iati-activity/location element. <a href="#">IATI Standard Reference</a>	
reference	A cross-reference to the internal reference assigned to a defined location: iati-activity/location/@ref. <a href="#">IATI Standard Reference</a>	

## transaction

Data field	IATI Standard Reference definition	Explanation
<b>transaction</b>	Transactions recording committed or actual funds flowing in or out of an aid activity. <a href="#">IATI Standard Reference</a> .	<p>Please provide a record of how your activity is being financed and how the finance is being used. Each incoming and outgoing flow should be published as a transaction.</p> <p>If an organisation makes many small transactions, these can be grouped together. For example, all travel expenses for one month could be published as one expenditure transaction. When deciding whether (or how) to aggregate transactions, it is recommended that publishers consider the needs of data users, as too much aggregation can inhibit the usability of the data</p> <p>Please note, you should not group together flows of funds to or from multiple external organisations (e.g. a disbursement to CARE should not be combined with a disbursement to IRC).</p> <p><a href="#">Guidance on publishing financial transactions</a></p>
reference	An internal reference linking this transaction back to the publisher's financial management system. <a href="#">IATI Standard Reference</a>	You can provide a reference that you use to identify this transaction in your organisation's internal financial management system.
humanitarian	A process flag to indicate that this transaction relates entirely or partially to humanitarian aid. <a href="#">IATI Standard Reference</a>	<p>You can flag if this transaction relates to humanitarian aid by selecting 'yes'.</p> <p>If this entire activity relates to humanitarian aid you should select yes using IATI Activity humanitarian flag, rather than for each transaction.</p> <p>See <a href="#">guidance on all the ways to publish humanitarian data</a>.</p>

transaction type	The type of the transaction (e.g. commitment, disbursement, expenditure, etc.). <a href="#">IATI Standard Reference</a>	Please choose the type of transaction that best reflects the flow of money in or out of this activity. Types include incoming funds, outgoing commitments, disbursement, expenditure.
code	A code from the specified vocabulary. <a href="#">IATI Standard Reference</a>	Please provide a type for this transaction. <a href="#">Read all options with descriptions</a> .
transaction date	The date on which the transaction was made or (in the case of commitments) agreed. <a href="#">IATI Standard Reference</a>	
date	This value must be of type xsd:date. <a href="#">IATI Standard Reference</a>	Provide the date on which the transaction was made or (in the case of commitments) agreed.
value	The amount of the contribution. <a href="#">IATI Standard Reference</a>	
currency	A three letter ISO 4217 code for the original currency of the amount. <a href="#">IATI Standard Reference</a>	Select the currency of this transaction.  This value must be on the <a href="#">Currency codelist</a> .
value-date	The date to be used for determining the exchange rate for currency conversions.	This date must not be in the future.
description	A human-readable description of the transaction. <a href="#">IATI Standard Reference</a>	
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Provide a short description of the transaction e.g. what it was for.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.

provider organisation	For incoming funds this is the organisation from which the transaction originated. If omitted on outgoing funds the reporting-org is assumed. <a href="#">IATI Standard Reference</a>	For each transaction it is strongly recommended that you publish information on both the provider and receiver organisations of the funds. This includes instances where your organisation is either the provider or the receiver.  If you do not provide information on the provider organisation for <i>incoming</i> transactions, then it is presumed that your organisation is the provider of the funds.
reference	Machine-readable identification string for the organisation issuing the report. <a href="#">IATI Standard Reference</a>	Please type the provider organisation's <i>IATI Organisation Identifier</i> . The quickest way to find this is to search for the organisation in the <a href="#">IATI Publisher List</a> . If you cannot find the organisation, see <a href="#">further guidance</a> .  If your organisation is the provider, please type your <i>IATI Organisation Identifier</i> . Your organisation created its org-ID when it first registered as an IATI publisher.
provider-activity-id	If incoming funds are being provided from the budget of another activity that is reported to IATI, it is STRONGLY RECOMMENDED that this should record the provider's unique IATI activity identifier for that activity. <a href="#">IATI Standard Reference</a>	The provider organisation may have published IATI data on these funds in their own activity. If so, please provide the activity-id for their activity that includes information on this funding. You can ask the provider organisation for this activity-id, or search for their activity on d-portal.org. <a href="#">See further guidance</a> .  If you are the provider organisation then leave this blank.
type	The type of organisation providing the funds. <a href="#">IATI Standard Reference</a>	Select the type that best describes the provider organisation. <a href="#">Information on all organisation types</a> .  If your organisation is the provider, please select the organisation type that your organisation provided when it first registered.
narrative	The name of the organisation. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	If the provider organisation does not have an IATI Organisation Identifier, you must provide the text name of the organisation.  <b>Please do not type a code here for the provider organisation.</b>

language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.
receiver- organisation	The organisation receiving the money from the transaction. <a href="#">IATI Standard Reference</a>	Please provide the organisation that will/has received the funds as part of this transaction. If your organisation is the receiver, please provide your organisation's details.
reference	Machine-readable identification string for the organisation issuing the report. <a href="#">IATI Standard Reference</a> .	<p>Please provide the receiver organisation's <i>IATI Organisation Identifier</i> (org-ID). The quickest way to find this is to search for the organisation in the <a href="#">IATI Publisher List</a>. If you cannot find the organisation, see <a href="#">further guidance</a>.</p> <p>If your organisation is the receiver, please type your <i>IATI Organisation Identifier</i> (org-ID). Your organisation created its org-ID when it first registered as an IATI publisher.</p>
receiver-activity-id	If outgoing funds are being provided to another activity that is reported to IATI, this may, if possible, record the unique IATI activity identifier for that activity. <a href="#">IATI Standard Reference</a>	<p>The receiver organisation may have published IATI data on receiving these funds in their own activity. If so, please provide the activity-id for their activity that includes information on this funding. You can ask the receiver organisation for this activity-id, or search for their activity on d-portal.org <a href="#">See further guidance</a>.</p> <p>If you are the provider organisation then leave this blank.</p>
type	The type of organisation receiving the funds. <a href="#">IATI Standard Reference</a>	<p>Select the type that best describes the receiver organisation. <a href="#">Information on all organisation types</a>.</p> <p>If your organisation is the receiver, please select the organisation type that your organisation provided when it first registered.</p>
narrative	The name of the organisation. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	<p>If the receiver organisation does not have an IATI Organisation Identifier, the text name of the organisation must be given.</p> <p><b>Please do not type a code here for the receiver organisation.</b></p>

language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.
disbursement-channel	The channel through which the funds will flow for this transaction, from an IATI codelist. <a href="#">IATI Standard Reference</a> .	Select the best option for how your disbursements are channeled (e.g. through the recipient government or outside of the recipient government).
code	An IATI code defining channels of disbursement. <a href="#">IATI Standard Reference</a>	Please read the list of <a href="#">disbursement channels</a> and choose the option that applies to this transaction (if any are applicable).
sector	A recognised code, from a recognised vocabulary, classifying the purpose of this transaction. <a href="#">IATI Standard Reference</a>	<p>You can specify <b>one</b> sector that this individual transaction is supporting. For example, primary education or agriculture. If you do this, then you must specify a sector for <b>every</b> transaction that you publish.</p> <p>You <b>should not</b> specify a sector for any of your transactions if you want to provide data on the sector(s) of this entire activity. <b>Sectors must only be provided at either the activity or transaction level and not both.</b></p> <p>Once your organisation decides where to publish information about which sectors it is working in, you should be consistent across all activities that you publish. This means you should publish all sector information at either activity level or for all transactions. <a href="#">More information</a>.</p>
vocabulary	An IATI code for the vocabulary (codelist) used for sector classifications. If omitted, OECD DAC 5-digit Purpose Codes are assumed. <a href="#">IATI Standard Reference</a>	<p>If you decide to publish what sector this transaction is supporting, then you need to choose a list of sectors. IATI recommends choosing the OECD DAC 5-digit sector codelist, in which you can make a selection from <a href="#">over 300 sectors</a>.</p> <p>You can choose to use another list (see <a href="#">information on all possible options</a>). If you want to use your organisation's own list of internal sector classifications, select the option: 'Reporting Organisation'.</p>

		<p>You can choose to use multiple lists. If you use more than one internal sector classification, please select 'Reporting Organisation 2' (which has the code 98) for the additional list. <a href="#">Additional guidance</a>.</p> <p><b>Do not select a list if you have / will choose a sector list for the entire activity.</b></p>
vocabulary-uri	The URI where this vocabulary is defined. If the vocabulary is 99 or 98 (reporting organisation), the URI where this internal vocabulary is defined. <a href="#">IATI Standard Reference</a>	If you have chosen to use an internal sector classification codelist, please provide a link to it.
code	The code for the sector. <a href="#">IATI Standard Reference</a>	Select the sector that the transaction's funds are supporting. You must only choose <b>one sector</b> from each list that you use.
narrative	The description of a sector defined by the reporting organisation. (Only to be used when the reporting organisation's own vocabulary is being used). <a href="#">IATI Standard Reference</a>	If you have chosen a sector from an internal sector classification codelist, please provide a description of this sector.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.
recipient-country	A country that will benefit from this transaction. <a href="#">IATI Standard Reference</a>	<p>You can specify <b>one</b> country or region that an individual transaction is taking place in, or the place that will benefit from it.</p> <p>You <b>should not</b> specify a country or region for any of your transactions if you want to provide the recipient country or region of this entire activity. <b>Recipient countries or regions) must only be provided at either the activity or transaction level and not both.</b></p> <p>Once your organisation decides where to publish information about its recipient countries (or regions), it should be consistent across all activities that it publishes. This means you should publish all recipient country or region information at either activity level or for all transactions. <a href="#">More information</a>.</p>

code	ISO 3166-1 alpha-2 code for the country. <a href="#">IATI Standard Reference</a>	Select <b>one</b> country that this transaction is taking place in, or will benefit from its funds.  <b>Do not select a country if you have / will choose a recipient country for the entire activity.</b>
narrative	The free text name or description of the item being described. This can be repeated in multiple languages. <a href="#">IATI Standard Reference</a>	Add the free text name and/or description for the country benefitting from the transaction.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.
recipient region	A supranational geopolitical region that will benefit from this transaction. If a specific country is not known, then this element MUST be used. <a href="#">IATI Standard Reference</a>	If you cannot identify the specific country benefitting from this transaction, then you can provide the recipient region instead. <b>Do not provide both a recipient country and a region.</b>  For example, if the funding is going to Uganda, then you should record Uganda as the recipient country and you should not add that the funding is also going to the region of Africa.
code	Either an OECD DAC or UN region code. Codelist is determined by vocabulary attribute. <a href="#">IATI Standard Reference</a>	Select the region benefitting from this transaction.
vocabulary	An IATI code for the vocabulary from which the region code is drawn. If it is not present 1 - 'OECD DAC' is assumed. <a href="#">IATI Standard Reference</a>	There are two lists of regions; the OECD DAC and UN region code lists. Please select one. IATI recommends that you use the <a href="#">OECD DAC codelist</a> . Otherwise you can use another list of regions by selecting the option: 'Reporting Organisation' and providing the URI where this internal list is defined. If you do not choose an option, then the code list 'OECD DAC' is assumed.
vocabulary-url	The URI where this vocabulary is defined. If the vocabulary is 99 (reporting organisation), the URI where this internal vocabulary is defined. <a href="#">IATI Standard Reference</a>	If you have selected the option: 'Reporting Organisation' please provide the URI where this internal list is defined.



narrative	The description of a sector defined by the reporting organisation. (Only to be used when the reporting organisation's own vocabulary is being used). <a href="#">IATI Standard Reference</a>	If you have selected the option: 'Reporting Organisation' please add the free text name and/or description regarding this region benefitting from the activity.
language	A code specifying the language of text in this element. It is recommended that wherever possible only codes from ISO 639-1 are used. If not present, the default language is assumed. <a href="#">IATI Standard Reference</a>	Select the language of the text in the narrative. If no language is selected, your default language is assumed.
flow type	Optional element to override the top-level default-flow-type element. <a href="#">IATI Standard Reference</a>	Flow type is another way to categorise financial flows. It distinguishes the flow as official development assistance (ODA), other official flows (OOF), or several types of private flows, including private grants often provided by NGOs and other civil society organisations.
code	A code from the OECD DAC CRS "Type of flow" codelist. <a href="#">IATI Standard Reference</a>	<p>Please select a flow type for this transaction from the <a href="#">following options</a>.</p> <p>Do note: if you select a flow-type for this transaction, this will override the <b>default flow type</b> for the entire activity, enabling you to choose a flow-type on a transaction-by-transaction basis, if needed.</p>
finance type	Optional element to override the top-level default-finance-type element on a transaction-by-transaction basis, if needed. <a href="#">IATI Standard Reference</a>	Finance type specifies the financial instrument that is being used. For example, financing is most commonly delivered as a grant or a loan.
code	A code from the OECD DAC CRS "Type of finance" codelist. <a href="#">IATI Standard Reference</a>	<p>Please select a finance type for this transaction from the <a href="#">following options</a>.</p> <p>Do note: if you select a finance-type for this transaction, this will override the <b>default finance type</b> for the entire activity, enabling you to choose a finance-type on a transaction-by-transaction basis, if needed.</p>

aid type	Optional element to override the top-level default-aid-type element (debt relief, etc.) on a transaction-by-transaction basis if needed. <a href="#">IATI Standard Reference</a>	<p>You can provide information about the type of aid that is being delivered. This is most commonly referred to as the aid modality and IATI recommends that an aid type from the OECD DAC codelist be selected for all activities. Examples from this codelist include: project-type interventions which provide support to a particular project and budget support which is a financial contribution to a recipient government's budget. Project-type interventions is the most common aid type for NGOs and CSOs but many other options are found <a href="#">here</a>.</p> <p>If your transaction is addressing a humanitarian event, you can provide specific information on the type of funds for it. This includes providing information on the level of earmarking of the transaction's funds and if the transaction is providing funds through cash or vouchers. <a href="#">More information on publishing aid-types related to humanitarian transactions</a>.</p> <p>Do note: if you select an aid-type for this transaction, this will override the <b>default aid type</b> for the entire activity, enabling you to choose an aid-type on a transaction-by-transaction basis, if needed.</p>
code	A code from the specified vocabulary. <a href="#">IATI Standard Reference</a>	Select the aid-type related to your transaction.
vocabulary	A code for the vocabulary aid-type classifications. If omitted the AidType (OECD DAC) codelist is assumed. The code must be a valid value in the AidTypeVocabulary codelist. <a href="#">IATI Standard Reference</a>	<p>Select a list that includes the aid-type list related to your transaction. You can choose to select one aid-type from more than one list.</p> <p><b>1 OECD DAC</b> - IATI recommends that you select this list which has <a href="#">over 20 options</a> to choose from. Then, in addition you can select an option from another list</p> <p><b>2 Earmarking Category</b> - select <a href="#">this list</a> to categorise how flexible humanitarian funding is. There are 4 earmarking categories. Understand more about the categories in <a href="#">Annex 1</a></p> <p><b>3 Earmarking Modality</b> - use this list to choose the specific earmarking modality to describe your activity's humanitarian funding. All earmarking modality options are <a href="#">listed in Annex 1</a></p>

		<p><b>4 Cash and Voucher Modalities</b> - select this list to specify if your transaction is responding to a humanitarian event by providing cash and voucher assistance. <a href="#">More information</a>.</p>
tied status	<p>Optional element to override the top-level default-tied-status element on a transaction-by-transaction basis if needed. <a href="#">IATI Standard Reference</a></p>	<p>You can state the tied status of this transaction. Here you can specify if funds are tied - where they must be spent on goods or services procured from a particular country (e.g. donor country) or group of countries. Or if funds are untied, this is where the recipient organisation is allowed to procure from any country.</p> <p>Do note: if you select a tied status for this transaction, this will override the <b>default tied status</b> for the entire activity, enabling you to choose a tied status on a transaction-by-transaction basis, if needed.</p>
code	<p>An IATI code interpreting the usage of Columns 36-38 of the CRS++ reporting format. (Amount tied, Amount partially untied, Amount tied)</p>	<p>Select a default-tied-status, if applicable to your transaction. <a href="#">Descriptions of all options</a>. Otherwise leave blank.</p>