Linux x86-64 System Calls — Numerical Reference

375 syscall entries, sorted by syscall number. Common calls include C-style prototypes. For less-common calls, the synopsis explicitly points to the syscall-specific man page rather than guessing argument types. The syscall ABI is kernel-facing; libc wrappers may differ.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
0	read	`ssize_t read(int fd, void *buf, size_t count)`	Read bytes from a file descriptor.
1	write	`ssize_t write(int fd, const void *buf, size_t count)`	Write bytes to a file descriptor.
2	open	`int open(const char *path, int flags, mode_t mode)`	Open or create a file.
3	close	`int close(int fd)`	Close a file descriptor.
4	stat	`int stat(const char *path, struct stat *buf)`	Kernel interface for stat operations.
5	fstat	`int fstat(int fd, struct stat *buf)`	Kernel interface for fstat operations.
6	lstat	`int lstat(const char *path, struct stat *buf)`	Kernel interface for lstat operations.
7	poll	`int poll(struct pollfd *fds, nfds_t nfds, int timeout)`	Kernel interface for poll operations.
8	lseek	`off_t lseek(int fd, off_t offset, int whence)`	Kernel interface for lseek operations.
9	mmap	`void *mmap(void *addr, size_t len, int prot, int flags, int fd, off_t off)`	Map file-backed or anonymous memory.
10	mprotect	`int mprotect(void *addr, size_t len, int prot)`	Change memory-page permissions.
11	munmap	`int munmap(void *addr, size_t len)`	Unmap a memory region.
12	brk	`int brk(void *addr)`	Adjust the process heap boundary.
13	rt_sigaction	`int rt_sigaction(int sig, const struct sigaction *act, struct sigaction *oldact, size_t sigsetsize)`	Manage real-time signal state or delivery.
14	rt_sigprocmask	`int rt_sigprocmask(int how, const sigset_t *set, sigset_t *oldset, size_t sigsetsize)`	Manage real-time signal state or delivery.
15	rt_sigreturn	`long rt_sigreturn(/* see syscall-specific man page for argument types */)`	Manage real-time signal state or delivery.
16	ioctl	`int ioctl(int fd, unsigned long request, ...)`	Perform device-specific control operations.
17	pread64	`ssize_t pread(int fd, void *buf, size_t count, off_t offset)`	Kernel interface for pread64 operations.
18	pwrite64	`ssize_t pwrite(int fd, const void *buf, size_t count, off_t offset)`	Kernel interface for pwrite64 operations.
19	readv	`ssize_t readv(int fd, const struct iovec *iov, int iovcnt)`	Kernel interface for readv operations.
20	writev	`ssize_t writev(int fd, const struct iovec *iov, int iovcnt)`	Kernel interface for writev operations.
21	access	`int access(const char *path, int mode)`	Kernel interface for access operations.
22	pipe	`int pipe(int pipefd[2])`	Kernel interface for pipe operations.
23	select	`long select(/* see syscall-specific man page for argument types */)`	Kernel interface for select operations.
24	sched_yield	`long sched_yield(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
25	mremap	`long mremap(/* see syscall-specific man page for argument types */)`	Kernel interface for mremap operations.
26	msync	`long msync(/* see syscall-specific man page for argument types */)`	Kernel interface for msync operations.
27	mincore	`long mincore(/* see syscall-specific man page for argument types */)`	Kernel interface for mincore operations.
28	madvise	`long madvise(/* see syscall-specific man page for argument types */)`	Kernel interface for madvise operations.
29	shmget	`long shmget(/* see syscall-specific man page for argument types */)`	Manage System V shared memory.
30	shmat	`long shmat(/* see syscall-specific man page for argument types */)`	Manage System V shared memory.
31	shmctl	`long shmctl(/* see syscall-specific man page for argument types */)`	Manage System V shared memory.
32	dup	`int dup(int oldfd)`	Kernel interface for dup operations.
33	dup2	`int dup2(int oldfd, int newfd)`	Kernel interface for dup2 operations.
34	pause	`long pause(/* see syscall-specific man page for argument types */)`	Kernel interface for pause operations.
35	nanosleep	`long nanosleep(/* see syscall-specific man page for argument types */)`	Suspend execution for a time interval.
36	getitimer	`long getitimer(/* see syscall-specific man page for argument types */)`	Kernel interface for getitimer operations.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
37	alarm	`long alarm(/* see syscall-specific man page for argument types */)`	Kernel interface for alarm operations.
38	setitimer	`long setitimer(/* see syscall-specific man page for argument types */)`	Kernel interface for setitimer operations.
39	getpid	`pid_t getpid(void)`	Return the process ID.
40	sendfile	`ssize_t sendfile(int out_fd, int in_fd, off_t *offset, size_t count)`	Transfer data between descriptors in-kernel.
41	socket	`int socket(int domain, int type, int protocol)`	Create a network communication endpoint.
42	connect	`int connect(int fd, const struct sockaddr *addr, socklen_t len)`	Connect a socket to a peer.
43	accept	`int accept(int fd, struct sockaddr *addr, socklen_t *len)`	Accept a pending connection.
44	sendto	`ssize_t sendto(int fd, const void *buf, size_t len, int flags, const struct sockaddr *dst, socklen_t addrlen)`	Send a message to a destination.
45	recvfrom	`ssize_t recvfrom(int fd, void *buf, size_t len, int flags, struct sockaddr *src, socklen_t *addrlen)`	Receive a message and source address.
46	sendmsg	`ssize_t sendmsg(int fd, const struct msghdr *msg, int flags)`	Kernel interface for sendmsg operations.
47	recvmsg	`ssize_t recvmsg(int fd, struct msghdr *msg, int flags)`	Kernel interface for recvmsg operations.
48	shutdown	`int shutdown(int fd, int how)`	Kernel interface for shutdown operations.
49	bind	`int bind(int fd, const struct sockaddr *addr, socklen_t len)`	Assign a local address to a socket.
50	listen	`int listen(int fd, int backlog)`	Mark a socket as listening.
51	getsockname	`long getsockname(/* see syscall-specific man page for argument types */)`	Kernel interface for getsockname operations.
52	getpeername	`long getpeername(/* see syscall-specific man page for argument types */)`	Kernel interface for getpeername operations.
53	socketpair	`long socketpair(/* see syscall-specific man page for argument types */)`	Kernel interface for socketpair operations.
54	setsockopt	`long setsockopt(/* see syscall-specific man page for argument types */)`	Kernel interface for setsockopt operations.
55	getsockopt	`long getsockopt(/* see syscall-specific man page for argument types */)`	Kernel interface for getsockopt operations.
56	clone	`long clone(unsigned long flags, void *stack, int *ptid, int *ctid, unsigned long tls)`	Create a process or thread.
57	fork	`pid_t fork(void)`	Create a child process.
58	vfork	`pid_t vfork(void)`	Create a child that temporarily shares the parent's address space.
59	execve	`int execve(const char *path, char *const argv[], char *const envp[])`	Replace the current process image with a program.
60	exit	`void _exit(int status)`	Terminate the calling thread.
61	wait4	`pid_t wait4(pid_t pid, int *status, int options, struct rusage *usage)`	Wait for a child and collect its status.
62	kill	`int kill(pid_t pid, int sig)`	Kernel interface for kill operations.
63	uname	`int uname(struct utsname *buf)`	Kernel interface for uname operations.
64	semget	`long semget(/* see syscall-specific man page for argument types */)`	Operate System V semaphores.
65	semop	`long semop(/* see syscall-specific man page for argument types */)`	Operate System V semaphores.
66	semctl	`long semctl(/* see syscall-specific man page for argument types */)`	Operate System V semaphores.
67	shmdt	`long shmdt(/* see syscall-specific man page for argument types */)`	Manage System V shared memory.
68	msgget	`long msgget(/* see syscall-specific man page for argument types */)`	Operate System V message queues.
69	msgsnd	`long msgsnd(/* see syscall-specific man page for argument types */)`	Operate System V message queues.
70	msgrcv	`long msgrcv(/* see syscall-specific man page for argument types */)`	Operate System V message queues.
71	msgctl	`long msgctl(/* see syscall-specific man page for argument types */)`	Operate System V message queues.
72	fcntl	`int fcntl(int fd, int cmd, ...)`	Manipulate descriptor flags and file locks.
73	flock	`long flock(/* see syscall-specific man page for argument types */)`	Kernel interface for flock operations.
74	fsync	`int fsync(int fd)`	Kernel interface for fsync operations.
75	fdatasync	`int fdatasync(int fd)`	Kernel interface for fdatasync operations.
76	truncate	`int truncate(const char *path, off_t length)`	Kernel interface for truncate operations.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
77	ftruncate	`int ftruncate(int fd, off_t length)`	Kernel interface for ftruncate operations.
78	getdents	`int getdents(unsigned int fd, struct linux_dirent *dirp, unsigned int count)`	Kernel interface for getdents operations.
79	getcwd	`char *getcwd(char *buf, size_t size)`	Kernel interface for getcwd operations.
80	chdir	`int chdir(const char *path)`	Kernel interface for chdir operations.
81	fchdir	`long fchdir(/* see syscall-specific man page for argument types */)`	Kernel interface for fchdir operations.
82	rename	`long rename(/* see syscall-specific man page for argument types */)`	Kernel interface for rename operations.
83	mkdir	`int mkdir(const char *path, mode_t mode)`	Kernel interface for mkdir operations.
84	rmdir	`int rmdir(const char *path)`	Kernel interface for rmdir operations.
85	creat	`long creat(/* see syscall-specific man page for argument types */)`	Kernel interface for creat operations.
86	link	`int link(const char *oldpath, const char *newpath)`	Kernel interface for link operations.
87	unlink	`int unlink(const char *path)`	Kernel interface for unlink operations.
88	symlink	`int symlink(const char *target, const char *linkpath)`	Kernel interface for symlink operations.
89	readlink	`ssize_t readlink(const char *path, char *buf, size_t bufsiz)`	Kernel interface for readlink operations.
90	chmod	`int chmod(const char *path, mode_t mode)`	Kernel interface for chmod operations.
91	fchmod	`long fchmod(/* see syscall-specific man page for argument types */)`	Kernel interface for fchmod operations.
92	chown	`int chown(const char *path, uid_t owner, gid_t group)`	Kernel interface for chown operations.
93	fchown	`long fchown(/* see syscall-specific man page for argument types */)`	Kernel interface for fchown operations.
94	lchown	`long lchown(/* see syscall-specific man page for argument types */)`	Kernel interface for lchown operations.
95	umask	`mode_t umask(mode_t mask)`	Kernel interface for umask operations.
96	gettimeofday	`int gettimeofday(struct timeval *tv, struct timezone *tz)`	Read wall-clock time (legacy interface).
97	getrlimit	`int getrlimit(int resource, struct rlimit *rlim)`	Kernel interface for getrlimit operations.
98	getrusage	`int getrusage(int who, struct rusage *usage)`	Kernel interface for getrusage operations.
99	sysinfo	`int sysinfo(struct sysinfo *info)`	Kernel interface for sysinfo operations.
100	times	`long times(/* see syscall-specific man page for argument types */)`	Kernel interface for times operations.
101	ptrace	`long ptrace(enum __ptrace_request request, pid_t pid, void *addr, void *data)`	Inspect or control another process, commonly for debugging.
102	getuid	`uid_t getuid(void)`	Return the real user ID.
103	syslog	`long syslog(/* see syscall-specific man page for argument types */)`	Kernel interface for syslog operations.
104	getgid	`gid_t getgid(void)`	Return the real group ID.
105	setuid	`long setuid(/* see syscall-specific man page for argument types */)`	Kernel interface for setuid operations.
106	setgid	`long setgid(/* see syscall-specific man page for argument types */)`	Kernel interface for setgid operations.
107	geteuid	`uid_t geteuid(void)`	Return the effective user ID.
108	getegid	`gid_t getegid(void)`	Return the effective group ID.
109	setpgid	`long setpgid(/* see syscall-specific man page for argument types */)`	Kernel interface for setpgid operations.
110	getppid	`long getppid(/* see syscall-specific man page for argument types */)`	Kernel interface for getppid operations.
111	getpgrp	`long getpgrp(/* see syscall-specific man page for argument types */)`	Kernel interface for getpgrp operations.
112	setsid	`long setsid(/* see syscall-specific man page for argument types */)`	Kernel interface for setsid operations.
113	setreuid	`long setreuid(/* see syscall-specific man page for argument types */)`	Kernel interface for setreuid operations.
114	setregid	`long setregid(/* see syscall-specific man page for argument types */)`	Kernel interface for setregid operations.
115	getgroups	`long getgroups(/* see syscall-specific man page for argument types */)`	Kernel interface for getgroups operations.
116	setgroups	`long setgroups(/* see syscall-specific man page for argument types */)`	Kernel interface for setgroups operations.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
117	setresuid	`long setresuid(/* see syscall-specific man page for argument types */)`	Kernel interface for setresuid operations.
118	getresuid	`long getresuid(/* see syscall-specific man page for argument types */)`	Kernel interface for getresuid operations.
119	setresgid	`long setresgid(/* see syscall-specific man page for argument types */)`	Kernel interface for setresgid operations.
120	getresgid	`long getresgid(/* see syscall-specific man page for argument types */)`	Kernel interface for getresgid operations.
121	getpgid	`long getpgid(/* see syscall-specific man page for argument types */)`	Kernel interface for getpgid operations.
122	setfsuid	`long setfsuid(/* see syscall-specific man page for argument types */)`	Kernel interface for setfsuid operations.
123	setfsgid	`long setfsgid(/* see syscall-specific man page for argument types */)`	Kernel interface for setfsgid operations.
124	getsid	`long getsid(/* see syscall-specific man page for argument types */)`	Kernel interface for getsid operations.
125	capget	`long capget(/* see syscall-specific man page for argument types */)`	Kernel interface for capget operations.
126	capset	`long capset(/* see syscall-specific man page for argument types */)`	Kernel interface for capset operations.
127	rt_sigpending	`long rt_sigpending(/* see syscall-specific man page for argument types */)`	Manage real-time signal state or delivery.
128	rt_sigtimedwait	`long rt_sigtimedwait(/* see syscall-specific man page for argument types */)`	Manage real-time signal state or delivery.
129	rt_sigqueueinfo	`long rt_sigqueueinfo(/* see syscall-specific man page for argument types */)`	Manage real-time signal state or delivery.
130	rt_sigsuspend	`long rt_sigsuspend(/* see syscall-specific man page for argument types */)`	Manage real-time signal state or delivery.
131	sigaltstack	`long sigaltstack(/* see syscall-specific man page for argument types */)`	Kernel interface for sigaltstack operations.
132	utime	`long utime(/* see syscall-specific man page for argument types */)`	Kernel interface for utime operations.
133	mknod	`long mknod(/* see syscall-specific man page for argument types */)`	Kernel interface for mknod operations.
134	uselib	`long uselib(/* see syscall-specific man page for argument types */)`	Kernel interface for uselib operations.
135	personality	`long personality(/* see syscall-specific man page for argument types */)`	Kernel interface for personality operations.
136	ustat	`long ustat(/* see syscall-specific man page for argument types */)`	Kernel interface for ustat operations.
137	statfs	`long statfs(/* see syscall-specific man page for argument types */)`	Kernel interface for statfs operations.
138	fstatfs	`long fstatfs(/* see syscall-specific man page for argument types */)`	Kernel interface for fstatfs operations.
139	sysfs	`long sysfs(/* see syscall-specific man page for argument types */)`	Kernel interface for sysfs operations.
140	getpriority	`long getpriority(/* see syscall-specific man page for argument types */)`	Kernel interface for getpriority operations.
141	setpriority	`long setpriority(/* see syscall-specific man page for argument types */)`	Kernel interface for setpriority operations.
142	sched_setparam	`long sched_setparam(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
143	sched_getparam	`long sched_getparam(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
144	sched_setscheduler	`long sched_setscheduler(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
145	sched_getscheduler	`long sched_getscheduler(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
146	sched_get_priority_max	`long sched_get_priority_max(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
147	sched_get_priority_min	`long sched_get_priority_min(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
148	sched_rr_get_interval	`long sched_rr_get_interval(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
149	mlock	`long mlock(/* see syscall-specific man page for argument types */)`	Kernel interface for mlock operations.
150	munlock	`long munlock(/* see syscall-specific man page for argument types */)`	Kernel interface for munlock operations.
151	mlockall	`long mlockall(/* see syscall-specific man page for argument types */)`	Kernel interface for mlockall operations.
152	munlockall	`long munlockall(/* see syscall-specific man page for argument types */)`	Kernel interface for munlockall operations.
153	vhangup	`long vhangup(/* see syscall-specific man page for argument types */)`	Kernel interface for vhangup operations.
154	modify_ldt	`long modify_ldt(/* see syscall-specific man page for argument types */)`	Kernel interface for modify ldt operations.
155	pivot_root	`long pivot_root(/* see syscall-specific man page for argument types */)`	Kernel interface for pivot root operations.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
156	_sysctl	`long _sysctl(/* see syscall-specific man page for argument types */)`	Kernel interface for sysctl operations.
157	prctl	`int prctl(int option, unsigned long arg2, ...)`	Kernel interface for prctl operations.
158	arch_prctl	`int arch_prctl(int code, unsigned long addr)`	Set/query architecture-specific thread state such as FS/GS bases.
159	adjtimex	`long adjtimex(/* see syscall-specific man page for argument types */)`	Kernel interface for adjtimex operations.
160	setrlimit	`long setrlimit(/* see syscall-specific man page for argument types */)`	Kernel interface for setrlimit operations.
161	chroot	`long chroot(/* see syscall-specific man page for argument types */)`	Kernel interface for chroot operations.
162	sync	`long sync(/* see syscall-specific man page for argument types */)`	Kernel interface for sync operations.
163	acct	`long acct(/* see syscall-specific man page for argument types */)`	Kernel interface for acct operations.
164	settimeofday	`long settimeofday(/* see syscall-specific man page for argument types */)`	Kernel interface for settimeofday operations.
165	mount	`long mount(/* see syscall-specific man page for argument types */)`	Attach a filesystem to the directory tree.
166	umount2	`long umount2(/* see syscall-specific man page for argument types */)`	Detach a mounted filesystem.
167	swapon	`long swapon(/* see syscall-specific man page for argument types */)`	Kernel interface for swapon operations.
168	swapoff	`long swapoff(/* see syscall-specific man page for argument types */)`	Kernel interface for swapoff operations.
169	reboot	`long reboot(/* see syscall-specific man page for argument types */)`	Request reboot or system shutdown.
170	sethostname	`long sethostname(/* see syscall-specific man page for argument types */)`	Kernel interface for sethostname operations.
171	setdomainname	`long setdomainname(/* see syscall-specific man page for argument types */)`	Kernel interface for setdomainname operations.
172	iopl	`long iopl(/* see syscall-specific man page for argument types */)`	Kernel interface for iopl operations.
173	ioperm	`long ioperm(/* see syscall-specific man page for argument types */)`	Kernel interface for ioperm operations.
174	create_module	`long create_module(/* see syscall-specific man page for argument types */)`	Kernel interface for create module operations.
175	init_module	`long init_module(/* see syscall-specific man page for argument types */)`	Kernel interface for init module operations.
176	delete_module	`long delete_module(/* see syscall-specific man page for argument types */)`	Kernel interface for delete module operations.
177	get_kernel_syms	`long get_kernel_syms(/* see syscall-specific man page for argument types */)`	Kernel interface for get kernel syms operations.
178	query_module	`long query_module(/* see syscall-specific man page for argument types */)`	Kernel interface for query module operations.
179	quotactl	`long quotactl(/* see syscall-specific man page for argument types */)`	Kernel interface for quotactl operations.
180	nfsservctl	`long nfsservctl(/* see syscall-specific man page for argument types */)`	Kernel interface for nfsservctl operations.
181	getpmsg	`long getpmsg(/* see syscall-specific man page for argument types */)`	Kernel interface for getpmsg operations.
182	putpmsg	`long putpmsg(/* see syscall-specific man page for argument types */)`	Kernel interface for putpmsg operations.
183	afs_syscall	`long afs_syscall(/* see syscall-specific man page for argument types */)`	Kernel interface for afs syscall operations.
184	tuxcall	`long tuxcall(/* see syscall-specific man page for argument types */)`	Kernel interface for tuxcall operations.
185	security	`long security(/* see syscall-specific man page for argument types */)`	Kernel interface for security operations.
186	gettid	`pid_t gettid(void)`	Return the calling thread ID.
187	readahead	`long readahead(/* see syscall-specific man page for argument types */)`	Kernel interface for readahead operations.
188	setxattr	`long setxattr(/* see syscall-specific man page for argument types */)`	Set extended filesystem attributes.
189	lsetxattr	`long lsetxattr(/* see syscall-specific man page for argument types */)`	Kernel interface for lsetxattr operations.
190	fsetxattr	`long fsetxattr(/* see syscall-specific man page for argument types */)`	Kernel interface for fsetxattr operations.
191	getxattr	`long getxattr(/* see syscall-specific man page for argument types */)`	Read extended filesystem attributes.
192	lgetxattr	`long lgetxattr(/* see syscall-specific man page for argument types */)`	Kernel interface for lgetxattr operations.
193	fgetxattr	`long fgetxattr(/* see syscall-specific man page for argument types */)`	Kernel interface for fgetxattr operations.
194	listxattr	`long listxattr(/* see syscall-specific man page for argument types */)`	List extended filesystem attributes.
195	llistxattr	`long llistxattr(/* see syscall-specific man page for argument types */)`	Kernel interface for llistxattr operations.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
196	flistxattr	`long flistxattr(/* see syscall-specific man page for argument types */)`	Kernel interface for flistxattr operations.
197	removexattr	`long removexattr(/* see syscall-specific man page for argument types */)`	Remove extended filesystem attributes.
198	lremovexattr	`long lremovexattr(/* see syscall-specific man page for argument types */)`	Kernel interface for lremovexattr operations.
199	fremovexattr	`long fremovexattr(/* see syscall-specific man page for argument types */)`	Kernel interface for fremovexattr operations.
200	tkill	`long tkill(/* see syscall-specific man page for argument types */)`	Kernel interface for tkill operations.
201	time	`long time(/* see syscall-specific man page for argument types */)`	Kernel interface for time operations.
202	futex	`int futex(uint32_t *uaddr, int op, uint32_t val, ...)`	Perform low-level thread synchronization.
203	sched_setaffinity	`long sched_setaffinity(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
204	sched_getaffinity	`long sched_getaffinity(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
205	set_thread_area	`long set_thread_area(/* see syscall-specific man page for argument types */)`	Kernel interface for set thread area operations.
206	io_setup	`long io_setup(/* see syscall-specific man page for argument types */)`	Manage kernel asynchronous I/O.
207	io_destroy	`long io_destroy(/* see syscall-specific man page for argument types */)`	Manage kernel asynchronous I/O.
208	io_getevents	`long io_getevents(/* see syscall-specific man page for argument types */)`	Manage kernel asynchronous I/O.
209	io_submit	`long io_submit(/* see syscall-specific man page for argument types */)`	Manage kernel asynchronous I/O.
210	io_cancel	`long io_cancel(/* see syscall-specific man page for argument types */)`	Manage kernel asynchronous I/O.
211	get_thread_area	`long get_thread_area(/* see syscall-specific man page for argument types */)`	Kernel interface for get thread area operations.
212	lookup_dcookie	`long lookup_dcookie(/* see syscall-specific man page for argument types */)`	Kernel interface for lookup dcookie operations.
213	epoll_create	`long epoll_create(/* see syscall-specific man page for argument types */)`	Manage scalable I/O event notification.
214	epoll_ctl_old	`long epoll_ctl_old(/* see syscall-specific man page for argument types */)`	Manage scalable I/O event notification.
215	epoll_wait_old	`long epoll_wait_old(/* see syscall-specific man page for argument types */)`	Manage scalable I/O event notification.
216	remap_file_pages	`long remap_file_pages(/* see syscall-specific man page for argument types */)`	Kernel interface for remap file pages operations.
217	getdents64	`int getdents64(unsigned int fd, struct linux_dirent64 *dirp, unsigned int count)`	Read directory entries.
218	set_tid_address	`long set_tid_address(/* see syscall-specific man page for argument types */)`	Kernel interface for set tid address operations.
219	restart_syscall	`long restart_syscall(/* see syscall-specific man page for argument types */)`	Kernel interface for restart syscall operations.
220	semtimedop	`long semtimedop(/* see syscall-specific man page for argument types */)`	Operate System V semaphores.
221	fadvise64	`long fadvise64(/* see syscall-specific man page for argument types */)`	Kernel interface for fadvise64 operations.
222	timer_create	`long timer_create(/* see syscall-specific man page for argument types */)`	Create or manage kernel timers.
223	timer_settime	`long timer_settime(/* see syscall-specific man page for argument types */)`	Create or manage kernel timers.
224	timer_gettime	`long timer_gettime(/* see syscall-specific man page for argument types */)`	Create or manage kernel timers.
225	timer_getoverrun	`long timer_getoverrun(/* see syscall-specific man page for argument types */)`	Create or manage kernel timers.
226	timer_delete	`long timer_delete(/* see syscall-specific man page for argument types */)`	Create or manage kernel timers.
227	clock_settime	`long clock_settime(/* see syscall-specific man page for argument types */)`	Read or manage system clocks and timed waits.
228	clock_gettime	`int clock_gettime(clockid_t clockid, struct timespec *tp)`	Read a selected system clock.
229	clock_getres	`long clock_getres(/* see syscall-specific man page for argument types */)`	Read or manage system clocks and timed waits.
230	clock_nanosleep	`int clock_nanosleep(clockid_t id, int flags, const struct timespec *req, struct timespec *rem)`	Read or manage system clocks and timed waits.
231	exit_group	`void _exit(int status)`	Terminate all threads in the process.
232	epoll_wait	`int epoll_wait(int epfd, struct epoll_event *events, int maxevents, int timeout)`	Wait for I/O readiness events.
233	epoll_ctl	`int epoll_ctl(int epfd, int op, int fd, struct epoll_event *event)`	Add, modify, or remove an epoll interest.
234	tgkill	`long tgkill(/* see syscall-specific man page for argument types */)`	Kernel interface for tgkill operations.
235	utimes	`long utimes(/* see syscall-specific man page for argument types */)`	Kernel interface for utimes operations.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
236	vserver	`long vserver(/* see syscall-specific man page for argument types */)`	Kernel interface for vserver operations.
237	mbind	`long mbind(/* see syscall-specific man page for argument types */)`	Set NUMA policy for a memory range.
238	set_mempolicy	`long set_mempolicy(/* see syscall-specific man page for argument types */)`	Set NUMA memory policy.
239	get_mempolicy	`long get_mempolicy(/* see syscall-specific man page for argument types */)`	Query NUMA memory policy.
240	mq_open	`long mq_open(/* see syscall-specific man page for argument types */)`	Operate POSIX message queues.
241	mq_unlink	`long mq_unlink(/* see syscall-specific man page for argument types */)`	Operate POSIX message queues.
242	mq_timedsend	`long mq_timedsend(/* see syscall-specific man page for argument types */)`	Operate POSIX message queues.
243	mq_timedreceive	`long mq_timedreceive(/* see syscall-specific man page for argument types */)`	Operate POSIX message queues.
244	mq_notify	`long mq_notify(/* see syscall-specific man page for argument types */)`	Operate POSIX message queues.
245	mq_getsetattr	`long mq_getsetattr(/* see syscall-specific man page for argument types */)`	Operate POSIX message queues.
246	kexec_load	`long kexec_load(/* see syscall-specific man page for argument types */)`	Kernel interface for kexec load operations.
247	waitid	`long waitid(/* see syscall-specific man page for argument types */)`	Kernel interface for waitid operations.
248	add_key	`long add_key(/* see syscall-specific man page for argument types */)`	Add a key to a kernel keyring.
249	request_key	`long request_key(/* see syscall-specific man page for argument types */)`	Request a key from the kernel key service.
250	keyctl	`long keyctl(/* see syscall-specific man page for argument types */)`	Manage kernel keyring operations.
251	ioprio_set	`long ioprio_set(/* see syscall-specific man page for argument types */)`	Kernel interface for ioprio set operations.
252	ioprio_get	`long ioprio_get(/* see syscall-specific man page for argument types */)`	Kernel interface for ioprio get operations.
253	inotify_init	`long inotify_init(/* see syscall-specific man page for argument types */)`	Monitor filesystem changes.
254	inotify_add_watch	`long inotify_add_watch(/* see syscall-specific man page for argument types */)`	Monitor filesystem changes.
255	inotify_rm_watch	`long inotify_rm_watch(/* see syscall-specific man page for argument types */)`	Monitor filesystem changes.
256	migrate_pages	`long migrate_pages(/* see syscall-specific man page for argument types */)`	Migrate process memory pages between NUMA nodes.
257	openat	`int openat(int dirfd, const char *path, int flags, mode_t mode)`	Open a path relative to a directory descriptor.
258	mkdirat	`int mkdirat(int dirfd, const char *path, mode_t mode)`	Kernel interface for mkdirat operations.
259	mknodat	`long mknodat(/* see syscall-specific man page for argument types */)`	Kernel interface for mknodat operations.
260	fchownat	`long fchownat(/* see syscall-specific man page for argument types */)`	Kernel interface for fchownat operations.
261	futimesat	`long futimesat(/* see syscall-specific man page for argument types */)`	Kernel interface for futimesat operations.
262	newfstatat	`long newfstatat(/* see syscall-specific man page for argument types */)`	Kernel interface for newfstatat operations.
263	unlinkat	`int unlinkat(int dirfd, const char *path, int flags)`	Kernel interface for unlinkat operations.
264	renameat	`long renameat(/* see syscall-specific man page for argument types */)`	Kernel interface for renameat operations.
265	linkat	`long linkat(/* see syscall-specific man page for argument types */)`	Kernel interface for linkat operations.
266	symlinkat	`long symlinkat(/* see syscall-specific man page for argument types */)`	Kernel interface for symlinkat operations.
267	readlinkat	`long readlinkat(/* see syscall-specific man page for argument types */)`	Kernel interface for readlinkat operations.
268	fchmodat	`long fchmodat(/* see syscall-specific man page for argument types */)`	Kernel interface for fchmodat operations.
269	faccessat	`long faccessat(/* see syscall-specific man page for argument types */)`	Kernel interface for faccessat operations.
270	pselect6	`long pselect6(/* see syscall-specific man page for argument types */)`	Kernel interface for pselect6 operations.
271	ppoll	`long ppoll(/* see syscall-specific man page for argument types */)`	Kernel interface for ppoll operations.
272	unshare	`long unshare(/* see syscall-specific man page for argument types */)`	Kernel interface for unshare operations.
273	set_robust_list	`long set_robust_list(/* see syscall-specific man page for argument types */)`	Kernel interface for set robust list operations.
274	get_robust_list	`long get_robust_list(/* see syscall-specific man page for argument types */)`	Kernel interface for get robust list operations.
275	splice	`ssize_t splice(int fd_in, off_t *off_in, int fd_out, off_t *off_out, size_t len, unsigned int flags)`	Move data between descriptors without copying through userspace.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
276	tee	`long tee(/* see syscall-specific man page for argument types */)`	Kernel interface for tee operations.
277	sync_file_range	`long sync_file_range(/* see syscall-specific man page for argument types */)`	Kernel interface for sync file range operations.
278	vmsplice	`long vmsplice(/* see syscall-specific man page for argument types */)`	Kernel interface for vmsplice operations.
279	move_pages	`long move_pages(/* see syscall-specific man page for argument types */)`	Query or move pages between NUMA nodes.
280	utimensat	`long utimensat(/* see syscall-specific man page for argument types */)`	Kernel interface for utimensat operations.
281	epoll_pwait	`long epoll_pwait(/* see syscall-specific man page for argument types */)`	Manage scalable I/O event notification.
282	signalfd	`long signalfd(/* see syscall-specific man page for argument types */)`	Kernel interface for signalfd operations.
283	timerfd_create	`long timerfd_create(/* see syscall-specific man page for argument types */)`	Create or manage kernel timers.
284	eventfd	`long eventfd(/* see syscall-specific man page for argument types */)`	Kernel interface for eventfd operations.
285	fallocate	`long fallocate(/* see syscall-specific man page for argument types */)`	Kernel interface for fallocate operations.
286	timerfd_settime	`long timerfd_settime(/* see syscall-specific man page for argument types */)`	Create or manage kernel timers.
287	timerfd_gettime	`long timerfd_gettime(/* see syscall-specific man page for argument types */)`	Create or manage kernel timers.
288	accept4	`int accept4(int fd, struct sockaddr *addr, socklen_t *len, int flags)`	Kernel interface for accept4 operations.
289	signalfd4	`long signalfd4(/* see syscall-specific man page for argument types */)`	Kernel interface for signalfd4 operations.
290	eventfd2	`long eventfd2(/* see syscall-specific man page for argument types */)`	Kernel interface for eventfd2 operations.
291	epoll_create1	`int epoll_create1(int flags)`	Manage scalable I/O event notification.
292	dup3	`int dup3(int oldfd, int newfd, int flags)`	Kernel interface for dup3 operations.
293	pipe2	`int pipe2(int pipefd[2], int flags)`	Kernel interface for pipe2 operations.
294	inotify_init1	`long inotify_init1(/* see syscall-specific man page for argument types */)`	Monitor filesystem changes.
295	preadv	`long preadv(/* see syscall-specific man page for argument types */)`	Kernel interface for preadv operations.
296	pwritev	`long pwritev(/* see syscall-specific man page for argument types */)`	Kernel interface for pwritev operations.
297	rt_tgsigqueueinfo	`long rt_tgsigqueueinfo(/* see syscall-specific man page for argument types */)`	Manage real-time signal state or delivery.
298	perf_event_open	`long perf_event_open(/* see syscall-specific man page for argument types */)`	Kernel interface for perf event open operations.
299	recvmmsg	`long recvmmsg(/* see syscall-specific man page for argument types */)`	Kernel interface for recvmmsg operations.
300	fanotify_init	`long fanotify_init(/* see syscall-specific man page for argument types */)`	Configure filesystem event monitoring.
301	fanotify_mark	`long fanotify_mark(/* see syscall-specific man page for argument types */)`	Configure filesystem event monitoring.
302	prlimit64	`long prlimit64(/* see syscall-specific man page for argument types */)`	Kernel interface for prlimit64 operations.
303	name_to_handle_at	`long name_to_handle_at(/* see syscall-specific man page for argument types */)`	Kernel interface for name to handle at operations.
304	open_by_handle_at	`long open_by_handle_at(/* see syscall-specific man page for argument types */)`	Kernel interface for open by handle at operations.
305	clock_adjtime	`long clock_adjtime(/* see syscall-specific man page for argument types */)`	Read or manage system clocks and timed waits.
306	syncfs	`long syncfs(/* see syscall-specific man page for argument types */)`	Kernel interface for syncfs operations.
307	sendmmsg	`long sendmmsg(/* see syscall-specific man page for argument types */)`	Kernel interface for sendmmsg operations.
308	setns	`long setns(/* see syscall-specific man page for argument types */)`	Kernel interface for setns operations.
309	getcpu	`long getcpu(/* see syscall-specific man page for argument types */)`	Kernel interface for getcpu operations.
310	process_vm_readv	`ssize_t process_vm_readv(pid_t pid, const struct iovec *local, unsigned long liovcnt, const struct iovec *remote, unsigned long riovcnt, unsigned long flags)`	Read another process's memory using vectored I/O.
311	process_vm_writev	`ssize_t process_vm_writev(pid_t pid, const struct iovec *local, unsigned long liovcnt, const struct iovec *remote, unsigned long riovcnt, unsigned long flags)`	Write another process's memory using vectored I/O.
312	kcmp	`long kcmp(/* see syscall-specific man page for argument types */)`	Kernel interface for kcmp operations.
313	finit_module	`long finit_module(/* see syscall-specific man page for argument types */)`	Kernel interface for finit module operations.
314	sched_setattr	`long sched_setattr(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
315	sched_getattr	`long sched_getattr(/* see syscall-specific man page for argument types */)`	Manage CPU scheduling policy, priority, or affinity.
316	renameat2	`int renameat2(int olddirfd, const char *oldpath, int newdirfd, const char *newpath, unsigned int flags)`	Kernel interface for renameat2 operations.
317	seccomp	`int seccomp(unsigned int operation, unsigned int flags, void *args)`	Configure syscall filtering for sandboxing.
318	getrandom	`ssize_t getrandom(void *buf, size_t len, unsigned int flags)`	Obtain random bytes from the kernel.
319	memfd_create	`int memfd_create(const char *name, unsigned int flags)`	Create an anonymous memory-backed file.
320	kexec_file_load	`long kexec_file_load(/* see syscall-specific man page for argument types */)`	Kernel interface for kexec file load operations.
321	bpf	`int bpf(int cmd, union bpf_attr *attr, unsigned int size)`	Create and manage eBPF programs and maps.
322	execveat	`int execveat(int dirfd, const char *path, char *const argv[], char *const envp[], int flags)`	Kernel interface for execveat operations.
323	userfaultfd	`long userfaultfd(/* see syscall-specific man page for argument types */)`	Kernel interface for userfaultfd operations.
324	membarrier	`long membarrier(/* see syscall-specific man page for argument types */)`	Kernel interface for membarrier operations.
325	mlock2	`long mlock2(/* see syscall-specific man page for argument types */)`	Kernel interface for mlock2 operations.
326	copy_file_range	`ssize_t copy_file_range(int fd_in, off_t *off_in, int fd_out, off_t *off_out, size_t len, unsigned int flags)`	Copy file data in-kernel.
327	preadv2	`long preadv2(/* see syscall-specific man page for argument types */)`	Kernel interface for preadv2 operations.
328	pwritev2	`long pwritev2(/* see syscall-specific man page for argument types */)`	Kernel interface for pwritev2 operations.
329	pkey_mprotect	`long pkey_mprotect(/* see syscall-specific man page for argument types */)`	Manage memory protection keys.
330	pkey_alloc	`long pkey_alloc(/* see syscall-specific man page for argument types */)`	Manage memory protection keys.
331	pkey_free	`long pkey_free(/* see syscall-specific man page for argument types */)`	Manage memory protection keys.
332	statx	`int statx(int dirfd, const char *path, int flags, unsigned int mask, struct statx *buf)`	Retrieve extended file metadata.
333	io_pgetevents	`long io_pgetevents(/* see syscall-specific man page for argument types */)`	Manage kernel asynchronous I/O.
334	rseq	`long rseq(/* see syscall-specific man page for argument types */)`	Kernel interface for rseq operations.
335	uretprobe	`long uretprobe(/* see syscall-specific man page for argument types */)`	Kernel interface for uretprobe operations.
424	pidfd_send_signal	`int pidfd_send_signal(int pidfd, int sig, siginfo_t *info, unsigned int flags)`	Send a signal through a process descriptor.
425	io_uring_setup	`int io_uring_setup(unsigned int entries, struct io_uring_params *params)`	Create an asynchronous I/O ring.
426	io_uring_enter	`int io_uring_enter(unsigned int fd, unsigned int submit, unsigned int min_complete, unsigned int flags, const sigset_t *sig, size_t sigsz)`	Submit or wait for asynchronous I/O operations.
427	io_uring_register	`int io_uring_register(unsigned int fd, unsigned int opcode, void *arg, unsigned int nr_args)`	Register resources with an io_uring instance.
428	open_tree	`long open_tree(/* see syscall-specific man page for argument types */)`	Kernel interface for open tree operations.
429	move_mount	`long move_mount(/* see syscall-specific man page for argument types */)`	Kernel interface for move mount operations.
430	fsopen	`long fsopen(/* see syscall-specific man page for argument types */)`	Kernel interface for fsopen operations.
431	fsconfig	`long fsconfig(/* see syscall-specific man page for argument types */)`	Kernel interface for fsconfig operations.
432	fsmount	`long fsmount(/* see syscall-specific man page for argument types */)`	Kernel interface for fsmount operations.
433	fspick	`long fspick(/* see syscall-specific man page for argument types */)`	Kernel interface for fspick operations.
434	pidfd_open	`int pidfd_open(pid_t pid, unsigned int flags)`	Obtain a stable file descriptor referring to a process.
435	clone3	`long clone3(struct clone_args *args, size_t size)`	Create a process/thread using an extensible argument structure.
436	close_range	`int close_range(unsigned int first, unsigned int last, unsigned int flags)`	Close a range of file descriptors.
437	openat2	`int openat2(int dirfd, const char *path, struct open_how *how, size_t size)`	Open a path with extended resolution controls.
438	pidfd_getfd	`long pidfd_getfd(/* see syscall-specific man page for argument types */)`	Kernel interface for pidfd getfd operations.
439	faccessat2	`int faccessat2(int dirfd, const char *path, int mode, int flags)`	Kernel interface for faccessat2 operations.
440	process_madvise	`long process_madvise(/* see syscall-specific man page for argument types */)`	Give memory-use advice for another process.
441	epoll_pwait2	`long epoll_pwait2(/* see syscall-specific man page for argument types */)`	Manage scalable I/O event notification.

NR	SYSCALL	C-STYLE SYNOPSIS	PURPOSE
442	mount_setattr	`long mount_setattr(/* see syscall-specific man page for argument types */)`	Kernel interface for mount setattr operations.
443	quotactl_fd	`long quotactl_fd(/* see syscall-specific man page for argument types */)`	Kernel interface for quotactl fd operations.
444	landlock_create_ruleset	`int landlock_create_ruleset(const struct landlock_ruleset_attr *attr, size_t size, uint32_t flags)`	Create a Landlock filesystem access ruleset.
445	landlock_add_rule	`int landlock_add_rule(int ruleset_fd, enum landlock_rule_type type, const void *attr, uint32_t flags)`	Add a rule to a Landlock ruleset.
446	landlock_restrict_self	`int landlock_restrict_self(int ruleset_fd, uint32_t flags)`	Apply Landlock restrictions to the calling thread.
447	memfd_secret	`long memfd_secret(/* see syscall-specific man page for argument types */)`	Kernel interface for memfd secret operations.
448	process_mrelease	`long process_mrelease(/* see syscall-specific man page for argument types */)`	Kernel interface for process mrelease operations.
449	futex_waitv	`long futex_waitv(/* see syscall-specific man page for argument types */)`	Kernel interface for futex waitv operations.
450	set_mempolicy_home_node	`long set_mempolicy_home_node(/* see syscall-specific man page for argument types */)`	Set NUMA memory policy.
451	cachestat	`long cachestat(/* see syscall-specific man page for argument types */)`	Kernel interface for cachestat operations.
452	fchmodat2	`long fchmodat2(/* see syscall-specific man page for argument types */)`	Kernel interface for fchmodat2 operations.
453	map_shadow_stack	`long map_shadow_stack(/* see syscall-specific man page for argument types */)`	Kernel interface for map shadow stack operations.
454	futex_wake	`long futex_wake(/* see syscall-specific man page for argument types */)`	Kernel interface for futex wake operations.
455	futex_wait	`long futex_wait(/* see syscall-specific man page for argument types */)`	Kernel interface for futex wait operations.
456	futex_requeue	`long futex_requeue(/* see syscall-specific man page for argument types */)`	Kernel interface for futex requeue operations.
457	statmount	`long statmount(/* see syscall-specific man page for argument types */)`	Kernel interface for statmount operations.
458	listmount	`long listmount(/* see syscall-specific man page for argument types */)`	Kernel interface for listmount operations.
459	lsm_get_self_attr	`long lsm_get_self_attr(/* see syscall-specific man page for argument types */)`	Kernel interface for lsm get self attr operations.
460	lsm_set_self_attr	`long lsm_set_self_attr(/* see syscall-specific man page for argument types */)`	Kernel interface for lsm set self attr operations.
461	lsm_list_modules	`long lsm_list_modules(/* see syscall-specific man page for argument types */)`	Kernel interface for lsm list modules operations.
462	mseal	`long mseal(/* see syscall-specific man page for argument types */)`	Kernel interface for mseal operations.