

MORPHOS v2

Sharp, vibrant reaction–diffusion as the instrument

Design document · branch `morphos-v2`

IAmM3ta/morphogen

October 2026

Priority (top of the build order). v2 is a seamless, synesthetic convergence of *sharp* (high resolution, crisp, never blurred) and *vibrant, psychedelic* reaction–diffusion. The Gray–Scott field *is* the main visual. Sound drives the chemistry itself (feed/kill, diffusion ratio, anisotropy, onset seeding, palette); tilt and compass steer anisotropy and flow. A WebGPU compute port is the primary path; the existing WebGL2 field is strictly the fallback when `navigator.gpu` is absent or fails. Looks are colourings, lighting and optional kaleidoscopic symmetry of the simulated domain. Adaptive quality lowers the step count, then the simulation grid, and never the output resolution.

Contents

1 Sharp RD convergence (the core)	1
1.1 Reference: Karl Sims’ RD Tool	1
1.2 What “sharp” means here	2
1.3 Audio drives the chemistry	2
1.4 Sensors steer anisotropy and flow	3
1.5 Regimes morph	3
2 Build order	3
3 WebGPU architecture	3
3.1 Passes	3
3.2 Robustness	4
4 Adaptive quality: steps before scale, never blur	4
5 Looks: colourings of the field	4
6 Signal flow	5
7 Sound engine v2 (summary)	5
8 UI, accessibility and invariants	5
9 Wallpaper mode and PWA	5
10 Shipped vs. designed-but-pending	5
11 Risks	6
12 Test plan	6

1 Sharp RD convergence (the core)

1.1 Reference: Karl Sims’ RD Tool

The visual target is Karl Sims’ reaction–diffusion work: the tutorial (karlsims.com/rd.html) and the RD Tool (karlsims.com/rdtool.html, help page [rdtool-help.html](https://karlsims.com/rdtool-help.html)). We read both. What we took from them:

- **Model.** Gray–Scott with $D_A = 1$, $D_B = 0.5$, $f = 0.055$, $k = 0.062$, $\Delta t = 1$:

$$A' = A + (D_A \nabla^2 A - AB^2 + f(1 - A))\Delta t, \quad B' = B + (D_B \nabla^2 B + AB^2 - (k + f)B)\Delta t.$$

- **Laplacian.** 3×3 convolution: centre -1 , adjacent 0.2 , diagonals 0.05 . We use exactly this stencil.
- **Regimes.** The tutorial gives mitosis at $f = 0.0367$, $k = 0.0649$ and coral at $f = 0.0545$, $k = 0.062$. The pattern map spans $k \in [0.045, 0.07]$ and $f \in [0.01, 0.1]$.
- **Options the RD Tool exposes.** *Orientation* (anisotropic diffusion), *Style map* (feed/kill varying across the grid: radial, ring, random, horizontal, vertical), *Flow* (a velocity field that advects the chemicals), *Scale* (reaction rate vs. diffusion rate), brush seeding, 12 colour maps with emboss and invert, and colour controls (hue, saturation, brightness, contrast, frequency, phase).
- **Look.** The videos use embossed height-map lighting on B , with crisp edges at high resolution. The RD Tool runs on WebGL2 + EXT_color_buffer_float + WASM. We do the same job as WGSL compute on WebGPU.

1.2 What “sharp” means here

1. **The grid follows device pixels.** The long side is $\min(\text{cap}, \text{css} \times \text{dpr}) \times \text{scale}$. The cap is 2048 on desktop and 1600 on coarse-pointer devices. The DPR cap defaults to 3 (2 in wallpaper mode).
2. **Many steps per frame:** 6–40, governed (Section 4).
3. **Crisp render.** The colour index uses a threshold with derivative anti-aliasing, $\text{smoothstep}(t - a, t + a, B)$ where $a = \max(1.1 \text{fwidth}(B), 0.0012)$. Edges are therefore one output pixel wide at any zoom, never a blur kernel.
4. **Lighting comes from exact texel gradients.** The emboss normal is built from one-texel central differences of B . Specular and Fresnel terms give the gold and chrome looks.
5. **No resampled output.** The final pass reads the scene with `textureLoad` at the exact pixel. Bloom is a separate half-resolution layer that is *added*, so it never replaces detail.
6. **Quality never blurs.** The governor lowers steps first, then the sim grid. The canvas always matches device pixels (up to the DPR cap).

1.3 Audio drives the chemistry

All features are smoothed with asymmetric attack and release before they touch the solver. k_r is the user’s *Reactivity* (0–2).

Feature	RD parameter	Mapping (as implemented)
Bass (sub+bass)	feed f , swirl, bloom knee	$f \ += 0.0045 \bar{b} k_r$; swirl $\times (0.6 + 0.6\bar{b})$; bloom threshold $-0.08 \bar{b}$
Spectral centroid	kill k , palette	$k \ += 0.0035(\bar{c} - 0.4)k_r$; hue rotation and accent phase in the scene pass
Highs	diffusion ratio	$D_A \times (1 + 0.08 \bar{h} k_r)$ (on top of the v1 high-band term)
Onsets	local seeding	a new onset ripple plants B at its point, folded n -fold for mandala looks. Onsets under a finger and touch-down ripples do <i>not</i> seed
Drone pitch	fold order	order $= \text{round}(\text{foldBase} - 2 + 6 \text{pitch}_{\text{norm}}) \in [3, 12]$, changed only after the pitch holds
Spectrum peaks	Chladni style map	n, m of the Cymatic style map follow the dominant bands
RMS	bloom, haze	final pass gain

1.4 Sensors steer anisotropy and flow

Input	Effect
Tilt (x,y)	Direction of anisotropic diffusion ($\theta = \text{atan2}(t_y, t_x)$). Strength $+\min(0.3, 0.45 t)k_r$, capped at 0.6. Flow velocity $+0.35 t k_r$
Compass heading	Orientation angle when the device is flat; v1 heading→scale is kept
Neither	Slow orientation drift, so the field never freezes in one direction
Desktop	Wheel, Shift+wheel and the arrow keys emulate tilt and compass (<code>bindDesktopControls</code>)

Stability: the anisotropic term $a \cdot \frac{1}{2}(\partial_{dd} - \partial_{pp})$ is added to the 9-point Laplacian, and $D \Delta t$ is clamped to $1.8/(1.6 + 2a)$.

1.5 Regimes morph


RegimeDrift holds a regime, then glides feed and kill to the next: spots (0.0353, 0.0653), mitosis (0.0367, 0.0649), stripes (0.026, 0.061), labyrinth (0.029, 0.057), coral (0.0545, 0.062), worms (0.046, 0.063), holes (0.039, 0.058), waves (0.018, 0.051). The style map blends a second regime spatially (radial, ring, noise, vertical, Chladni), so two pattern families coexist and their border moves.

2 Build order

#	Phase	Content	Status
1	WebGPU RD core	WGSL compute Gray–Scott, 9-point + anisotropic Laplacian, style map, flow, seeding, pack, stats	shipped
2	Crisp render	Scene pass (AA threshold, emboss, specular, LUT, kaleido), bloom, final	shipped
3	Audio→RD	Features bus → feed/kill/diffusion/aniso/seeding/palette	shipped
4	Sensors→RD	Tilt/compass → anisotropy and flow	shipped (untested on device)
5	Looks	Eight RD colourings with lighting and symmetry	shipped
6	Governor	Steps→grid ladder, GPU backpressure	shipped
7	Fallback	WebGL2 RDEngine + palette-only looks; device-loss failover	shipped
8	Sound engine v2	Drone, bass, drums, transport, loop, WAV	shipped
9	v2 UI	Dock, panels, glass, fullscreen, keys	shipped
10	Wallpaper + PWA	/wallpaper, URL options, manifest	shipped
11	Docs	README, CHANGELOG, this document	shipped

3 WebGPU architecture

3.1 Passes



- **SIM**: a 16×16 workgroup. Per cell: the 9-point Laplacian plus the anisotropic term. Semi-Lagrangian bilinear advection runs only when $|v| > 0.02$. The style map blends f, k with a second regime. Brushes, the finger wake, beat seeding, onset seeds folded n -fold, MorphoMark lock planting, image modes, and noise are all handled here.
- **PACK**: writes $(A, B, \text{lockGhost})$ to an `rgba16float` storage texture, flipped so row 0 is the top.
- **SCENE**: folds the domain into a kaleidoscope (mandala core with a feathered radius, or the full field). It then applies the AA threshold, emboss normal, specular, thread and iso lines, and per-material shading (Section 5), followed by the MorphoMark ghosts, soft contour ripples for onsets (never a flash), and the play hue rotation.
- **BLOOM / FINAL**: half-resolution bright-pass bloom, then the exact-pixel composite with haze, vignette, soft clip, and grain.

- **RESAMPLE**: bilinear state transfer when the sim grid changes size, so the pattern survives the change.
- **Capture**: `capturePng` renders the full chain offscreen at 2048–3200 px.

3.2 Robustness

- `RDGpuEngine.create()` returns `{ok:false, reason}` instead of throwing. Failure cases: a 4s adapter timeout, WGSL compilation info errors, and a pipeline error scope.
- Uncaptured errors and device loss call `onLost`. The app marks WebGPU as failed for the session (`sessionStorage`), tears down, starts the WebGL2 field, and keeps playing. `?gpu=1` retries WebGPU.
- **Backpressure**. At most two frames are in flight (`onSubmittedWorkDone`). Over that, the frame is skipped but audio and UI keep ticking. The governor uses $\max(\text{rAF } \Delta t, \text{GPU time})$.
- **Auto layouts**. Every declared binding is statically used, so `layout:"auto"` keeps all of them. One defect of this kind was found and fixed during smoke testing (the bloom pass did not read its uniform).

4 Adaptive quality: steps before scale, never blur

- Step ladder: 6, 8, 10, 12, 16, 20, 24, 28, 32, 36, 40. The default cap is 32 on desktop and 20 on coarse devices.
- Grid ladder: $\times 1, 0.85, 0.72, 0.6, 0.5$. It is only touched once steps are already at the bottom.
- The EMA of frame time is compared with the budget (1000/fps cap, or 16.7 ms). Above $1.22\times$ the budget, step down (cool-down 90 frames). Below $0.82\times$, recover: grid first, once steps are ≥ 16 , then steps (cool-down 240).
- `quality=low` starts at 12 steps and grid $\times 0.6$. `high` disables the governor.
- The output canvas is never downscaled. Reduced motion slows simulated time ($\times 0.4$) and calms flow and swirl.
- rAF stops when the tab is hidden. Wallpaper mode defaults to 30 fps and DPR 2.


5 Looks: colourings of the field

Each look sets a 256×2 LUT: row 0 is the main map, with frequency and mirror baked in, and row 1 is an accent map. It also sets the lighting, thread lines, style map, anisotropy, swirl and symmetry. The palettes follow the MEMETiC brief: gold and bronze filigree, liquid rainbow chrome, teal beams and haze, UV magenta and violet, iridescent accents. There is no face rendering.

Look	Character	Kaleido	Style map	Light
Field	species palette, sharpened (v1 continuity)	none	none	emboss 0.35
Marble	silver veins, ink flow; iso lines	none	noise	emboss 0.45
Temple Gold	embossed gold filigree, iridescent mandala core, moiré halo	core, 8-fold	radial	emboss 1.0, spec 0.85
Chrome Bloom	liquid rainbow metal: normal-driven reflection LUT, Fresnel, dark mirror ground	none	noise	emboss 0.9, spec 1.0
Teal Beam	light shafts through the growth, cyan threads	none	vertical	emboss 0.3
UV Mandala	violet stage, iridescent threads, moiré, centre glow	full, 6-fold	ring	emboss 0.5
Projection	edge-to-edge cyclic LUT flow, strong swirl	none	noise	emboss 0.4
Cymatic	the sound's standing waves (Chladni n, m) steer growth	none	Chladni	emboss 0.6

On the WebGL2 fallback, a look maps to a four-stop palette (`fourStops`) through `runtime.v2Stops`. The fallback gets colour only; it has no kaleidoscope or materials.

6 Signal flow



Per frame, the engine's `onFrame` runs the v2 tick first (`tickFeatures` → `analyser` → `updateControl` → `sound.frame`), then the unchanged v1 per-frame work (Hum, theremin, Sync TD WS/MIDI, recording).

7 Sound engine v2 (summary)

Drone synth (voices, Hold, in-key or free), a refined 16-step bass with finger record, a four-lane drum machine with mute and solo, a swing transport with tap tempo, scenes A–D with copy, clear and undo, a drone lane with arm, overdub and bars, a Starter loop, and Export WAV. The output passes through a limiter and soft clip. Additive hooks on `audio-engine.ts` keep The Hum, theremin, Freeze/Release, Rec/Loop and Sync unchanged.

8 UI, accessibility and invariants

- The mode dock has Field, Drone, Bass, Loop and Look. The top bar gains Full, Glass and Keys. The shortcuts sheet opens with ?.
- Keys: M (mode), V/Shift+V (look), P (loop), G (glass), F (fullscreen), Esc (close). Keys are disabled in wallpaper mode.
- Locked copy is unchanged: “Tap to start sound. Drag to plant growth. Touch the field to hear it.” and “Freeze: stop growth. Release: let it grow again.” Schumann does not appear on the splash, meta or first screen.
- Enter never requests MIDI (verified headless). Icon-only controls carry `aria-label` and `title`. There is no double-tap copy or gesture.
- iOS motion permission and audio unlock happen only inside a user gesture; denial is graceful.
- Fullscreen uses the standard API with a webkit fallback. Where unavailable (iPhone Safari), the app shows Share → Add to Home Screen guidance.

9 Wallpaper mode and PWA

`/wallpaper` or `?wallpaper=1` gives no gate, no UI, no prompts, no sensors and no MIDI, and the cursor hides when idle. Options: `visual` (default `temple-gold`), `quality`, `fps` (default 30, 0 means uncapped), `dpr` (default 2), and `audio=1` (ambient held drone, where the host allows autoplay). The manifest adds `display_override: [fullscreen, standalone]`, 192 and 512 icons, and a Wallpaper shortcut.

Hosts. These facts come from the hosts' public documentation only, and MORPHOS has not been tested on any of them:

- **Lively Wallpaper (Windows):** Add wallpaper → Enter URL. Web wallpapers render in `WebView2` (Edge) or `CefSharp`. Autoplay is allowed. Lively pauses playback for fullscreen apps and can pause on battery. A packaged Lively wallpaper can receive system audio through `livelyAudioListener` (128 bins) when `LivelyInfo.json` has `-audio`. That bridge is *not* implemented.
- **Plash (macOS):** add the URL as a website. Audio is muted, it can deactivate on battery, and it injects the class `is-plash-app`.
- **Android:** third-party “website as live wallpaper” apps exist on Google Play. WebGPU inside their `WebViews` is unverified, so expect the WebGL2 field. The PWA plus the `/wallpaper` shortcut is the first-party route.

10 Shipped vs. designed-but-pending

Shipped: everything in the build-order table.

Pending or changed:

- The Tesseract look was dropped. The particle and beam overlay compositor was dropped in favour of driving the RD field directly.
- MorphoMark lock ghosts on the WebGPU path use the current LUT. Per-lock palettes are not preserved there.
- The finger wake (drag advection) is gentler than v1 on the GPU path.
- The WebGL2 fallback gets palette-only looks.
- The Lively system-audio bridge and Splash auto-detection are not implemented.
- The default look is Field (the species palette), so editions and Find stay consistent. Wallpaper mode defaults to Temple Gold at 30 fps.

11 Risks

- **iOS and iPadOS WebGPU** is untested on real hardware. Safari's limits and the thermal envelope may force the governor down quickly. The coarse caps (grid 1600, 20 steps) are guesses.
- **Real-device motion:** tilt and compass steering, the permission flow and denial are untested on iOS and Android hardware.
- **Canvas presentation could not be tested headless.** In this CI box, presenting a WebGPU canvas (SwiftShader) destroys the device. The pipeline was verified by redirecting `getCurrentTexture` to an offscreen texture and reading it back. Real GPU presentation and real-GPU performance are unmeasured.
- Device-loss failover was observed to work. In the headless sandbox, however, the WebGL2 context sometimes could not be created afterwards.
- Feed and kill modulation can push some regimes to extinction under sustained bass. The clamps are conservative but not exhaustively tuned.
- High grid sizes use $\sim 2048^2 \times 8 \text{ B} \approx 32 \text{ MB}$ per state buffer, plus locks and history. This is a memory-pressure risk on low-end phones.

12 Test plan

1. `npm tsc -noEmit` and `npm run build` pass. `node -test scripts/*.test.mjs` shows the same 10 failures as baseline (environment-related).
2. Headless Chrome with WebGPU (SwiftShader): the engine is created, all eight looks render with no GPU errors, and wallpaper mode renders.
3. Headless with no adapter: the app falls back to WebGL2 and plays, and the Look panel notes the fallback.
4. Splash copy is present, Schumann is absent, and Enter does not call `requestMIDIAccess`.
5. On device (pending): iPhone Safari (WebGPU on and off), Android Chrome, desktop Chrome, Edge and Safari. Check sharpness at DPR 2–3, governor behaviour, motion permission granted and denied, audio unlock, the hidden-tab pause, and reduced motion.
6. In hosts (pending): Lively, Splash, and an Android web-wallpaper app.