

Oracle Forms Advanced Interview Questions & Answers

1. What is a Property Class in Oracle Forms?

A property class is a reusable object that contains a list of properties and their settings. You can assign it to multiple items to ensure consistency.

2. What is an Object Group?

An object group is a container for logically related objects in a form, allowing easy reuse or copying across different forms.

3. How does Oracle Forms communicate with Oracle Reports?

Oracle Forms uses `RUN_REPORT_OBJECT` to call a report, passing parameters and setting report output formats and destinations.

4. What is a Parameter List in Oracle Forms?

A parameter list is a list of key-value pairs used to pass parameters from one form to another or to reports.

5. Explain the use of Alerts in Oracle Forms.

Alerts are pop-up messages with options like OK, Cancel. You use them for confirmations or error notifications using `SHOW_ALERT()`.

6. How do you pass data between forms?

You can use global variables, parameter lists, or database temporary tables to pass data between forms.

7. What are the types of canvases and when would you use each?

Content Canvas: default; Stacked Canvas: overlays for popups; Tab Canvas: for tabbed UI; Toolbar Canvas: for menus.

8. What is Record Status and how is it used?

Record status (`NEW`, `INSERT`, `CHANGED`, `QUERY`) tells the form engine how the record has

changed and determines behavior during POST or COMMIT.

9. What are the different modes in which a form can run?

Normal Mode, Debug Mode, and Component Mode (used for calling forms as subcomponents).

10. Explain how to create a master-detail form in Oracle Forms.

Create two data blocks and establish a relationship using Data Block properties. Use triggers like ON-CLEAR-DETAILS and POST-QUERY.

11. What is the difference between CALL_FORM, OPEN_FORM, and NEW_FORM?

CALL_FORM: opens another form and waits; OPEN_FORM: opens form independently; NEW_FORM: replaces current form.

12. What is a Program Unit and how is it used?

Program Unit is a container for reusable PL/SQL code (procedures/functions) that can be called from triggers or other units.

13. How can you handle multi-language support in Oracle Forms?

Use translation tables and dynamically populate labels, messages, and LOVs based on user-selected language.

14. How can you dynamically build LOVs at runtime?

Use Record Groups and populate them using `POPULATE\_GROUP\_WITH\_QUERY()`.

15. How do you integrate Oracle Forms with WebLogic Server?

You deploy forms as a part of a WAR file using Forms Services, configured via WebLogic's domain configuration tools.