

# INVENTORY MANAGEMENT SYSTEM FOR RETAILERS

Domain:CloudApplicationDevelopment

Team id: PNT2022TMID08254

## Team Members:

Rohini.S-AC19UIT040

Divya.R- AC19UIT008

Poorani.S - AC19UIT033

Vaishnavi.A- AC19UIT049

Giftlin priyanka.R- AC19UIT011

## Getting started with Container Registry

IBM Cloud® Container Registry provides a multi-tenant private image registry that you can use to store and share your container images with users in your IBM Cloud account.

The IBM Cloud console includes a brief Quick Start.

Do not put personal information in your container images, namespace names, description fields, or in any image configuration data (for example, image names or image labels).

Step 1: Install the Container Registry CLI

Install the IBM Cloud CLI so that you can run the IBM Cloud ibmcloud commands, see [Getting started with the IBM Cloud CLI](#).

Install the container-registry CLI plug-in.

Step 2: Set up a namespace

. The namespace is created

That you specify so that you can configure access to resources within the namespace at the resource group level. If you don't specify a resource group, and you don't target a resource group, the default resource group is used. Namespaces that are assigned to a resource group show in the Resource list page of the IBM Cloud console.

Log in to IBM Cloud.

Ibmcloud login

If you have a federated ID, use `ibmcloud login --sso` to log in. Enter your username and use the provided URL in your CLI output to retrieve your one-time passcode. If you have a federated ID, the login fails without the `--sso` and succeeds with the `--sso` option.

You don't need to log in to Container Registry until you want to push an image, see Step 5: Push images to your namespace.

Add a namespace to create your own image repository. Replace `<my_namespace>` with your preferred namespace.

The namespace must be unique across all IBM Cloud accounts in the same region. Namespaces must have 4 – 30 characters, and contain lowercase letters, numbers, hyphens (-), and underscores (\_) only. Namespaces must start and end with a letter or number.

`ibmcloud cr namespace-add <my_namespace>`

You can put the namespace in a resource group of your choice by using one of the following options.

Before you create the namespace, run the `ibmcloud target -g <resource_group>` command, where `<resource_group>` is the resource group. Specify the resource group by using the `-g` option on the `ibmcloud cr namespace-add` command.

If you have a problem when you try to create a namespace, see [Why can't I add a namespace?](#) For assistance.

To ensure that your namespace is created, run the `ibmcloud cr namespace-list` command.

```
ibmcloud cr namespace-list -v
```

Step 3: Pull images from a registry to your local computer

Install Docker or a tool of your choice, such as Podman.

Install the Docker Engine CLI. For Windows® 8, or OS X Yosemite 10.10.x or earlier, install Docker Desktop instead. For more information about the version of Docker that is supported by IBM Cloud Container Registry, see [Support for Docker](#). Install Podman.

Download (pull) the image to your local computer. Replace `<source_image>` with the repository of the image and `<tag>` with the tag of the image that you want to use, for example, `latest`. For example, depending on the tool that you are using, run one of the following commands.

If you are using Docker, run the following command.

```
Docker pull <source_image>:<tag>
```

Example, where `<source_image>` is `hello-world` and `<tag>` is `latest`:

```
Docker pull hello-world:latest
```

If you have problem when you try to pull a Docker image, see [Why can't I push or pull a Docker image?](#) For assistance. If you can't pull the most recent image by using the latest tag, see [Why can't I pull the newest image by using the latest tag?](#) For assistance.

If you are using Podman, run the following command.

```
Podman pull <source_image>:<tag>
```

Example, where <source\_image> is hello-world and <tag> is latest:

Podman pull hello-world:latest

#### Step 4: Tag the image

To tag the image, replace <source\_image> with the repository and <tag> with the tag of your local image that you pulled earlier. Replace <region> with the name of your region.

Replace <my\_namespace> with the namespace that you created in Set up a namespace. Define the repository and tag of the image that you want to use in your namespace by replacing <new\_image\_repo> and <new\_tag>. For example, depending on the tool that you are using, run one of the following commands.

To find the name of your region, run the ibmcloud cr region command.

If you are using Docker, run the following command.

```
Docker tag <source_image>:<tag> <region>.icr.io/<my_namespace>/<new_image_repo>:<new_tag>
```

Example, where <source\_image> is hello-world, <tag> is latest, <region> is uk, <my\_namespace> is namespace1, <new\_image\_repo> is hw\_repo, and <new\_tag> is 1:

```
Docker tag hello-world:latest uk.icr.io/namespace1/hw_repo:1
```

If you are using Podman, run the following command.

```
Podman tag <source_image>:<tag>  
<region>.icr.io/<my_namespace>/<new_image_repo>:<new_tag>
```

Example, where <source\_image> is hello-world, <tag> is latest, <region> is uk, <my\_namespace> is namespace1, <new\_image\_repo> is hw\_repo, and <new\_tag> is 1:

```
Podman tag hello-world:latest uk.icr.io/namespace1/hw_repo:1
```

Step 5: Push images to your namespace

Log in to IBM Cloud Container Registry by using one of the following options.

To log in by using Docker, run the `ibmcloud cr login` command to log your local Docker daemon in to IBM Cloud Container Registry.

```
ibmcloud cr login --client docker
```

To log in by using Podman, run the `ibmcloud cr login` command to log in to IBM Cloud Container Registry.

```
ibmcloud cr login --client podman
```

To log in by using other clients, see [Accessing your namespaces interactively](#).

If you have a problem when you try to log in, see [Why can't I log in to Container Registry?](#) For assistance.

Upload (push) the image to your namespace. Replace `<my_namespace>` with the namespace that you created in [Set up a namespace](#). Replace `<image_repo>` and `<tag>` with the repository and the tag of the image that you chose when you tagged the image. For example, depending on the tool that you are using, run one of the following commands.

If you are using Docker, run the following command.

```
Docker push <region>.icr.io/<my_namespace>/<image_repo>:<tag>
```

Example, where `<region>` is `uk`, `<my_namespace>` is `namespace1`, `<image_repo>` is `hw_repo`, and `<tag>` is `1`:

Docker push uk.icr.io/namespace1/hw\_repo:1

If you have a problem when you try to push a Docker image, see [Why can't I push or pull a Docker image?](#) For assistance.

If you are using Podman, run the following command.

Podman push <region>.icr.io/<my\_namespace>/<image\_repo>:<tag>

Example, where <region> is uk, <my\_namespace> is namespace1, <image\_repo> is hw\_repo, and <tag> is 1:

podman push uk.icr.io/namespace1/hw\_repo:1

## Step 6: Verify that the image was pushed

Verify that the image was pushed successfully by running the following command.

```
ibmcloud cr image-list
```

You set up a namespace in IBM Cloud Container Registry and pushed your first image to your namespace.

[Review your service plans.](#) Set up clusters and worker nodes.