


TEAM ID: PNT2022TMID32006

PROJECT NAME: DemandEst - AI powered Food DemandForecaster

Team Leader



Dropping Columns

Let's drop columns "center_id" and "meal_id" as they are not required for the further process. Display the changes of trainfinal table using head().

```
In [110]: trainfinal = trainfinal.drop(['center_id', 'meal_id'], axis=1)
trainfinal.head()
```

```
Out[110]:
```

	id	week	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	category	cuisine	city_code	region_code	center_type
0	1379560	1	136.83	152.29	0	0	177	Beverages	Thai	647	56	TYPE_C
1	1018704	2	135.83	152.29	0	0	323	Beverages	Thai	647	56	TYPE_C
2	1196273	3	132.92	133.92	0	0	96	Beverages	Thai	647	56	TYPE_C
3	1116527	4	135.86	134.86	0	0	163	Beverages	Thai	647	56	TYPE_C
4	1343872	5	146.50	147.50	0	0	215	Beverages	Thai	647	56	TYPE_C

Display the list of columns present in trainfinal table and store it in variable "cols"

```
In [111]: cols = trainfinal.columns.tolist()
print(cols)
```

```
['id', 'week', 'checkout_price', 'base_price', 'emailer_for_promotion', 'homepage_featured', 'num_orders', 'category', 'cuisine', 'city_code', 'region_code', 'center_type', 'op_area']
```

Rearrange the columns by slicing the columns of "cols" and print "cols"

```
In [112]: cols = cols[:2] + cols[9:] + cols[7:9] + cols[2:7]
print(cols)
```

```
['id', 'week', 'city_code', 'region_code', 'center_type', 'op_area', 'category', 'cuisine', 'checkout_price', 'base_price', 'emailer_for_promotion', 'homepage_featured', 'num_orders']
```

Store the changes of columns in trainfinal and display the datatypes of trainfinal using trainfinal.dtypes. Here, we can see that, we not only have numerical data but we also have object data.

```
In [113]: trainfinal = trainfinal[cols]
trainfinal.head()
```

```
Out[113]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num
0	1379560	1	647	56	TYPE_C	2.0	Beverages	Thai	136.83	152.29	0	0	0
1	1018704	2	647	56	TYPE_C	2.0	Beverages	Thai	135.83	152.29	0	0	0
2	1196273	3	647	56	TYPE_C	2.0	Beverages	Thai	132.92	133.92	0	0	0
3	1116527	4	647	56	TYPE_C	2.0	Beverages	Thai	135.86	134.86	0	0	0
4	1343872	5	647	56	TYPE_C	2.0	Beverages	Thai	146.50	147.50	0	0	0

```
In [114]: trainfinal.dtypes
```

```
Out[114]: id                int64
week                int64
```

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

Out[113]:

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders
0	1379560	1	647	56	TYPE_C	2.0	Beverages	Thai	136.83	152.29	0	0	
1	1018704	2	647	56	TYPE_C	2.0	Beverages	Thai	135.83	152.29	0	0	
2	1196273	3	647	56	TYPE_C	2.0	Beverages	Thai	132.92	133.92	0	0	
3	1116527	4	647	56	TYPE_C	2.0	Beverages	Thai	135.86	134.86	0	0	
4	1343872	5	647	56	TYPE_C	2.0	Beverages	Thai	146.50	147.50	0	0	

In [114]: trainfinal.dtypes

```
Out[114]: id                int64
week                int64
city_code           int64
region_code         int64
center_type         object
op_area             float64
category            object
cuisine             object
checkout_price       float64
base_price           float64
emailer_for_promotion int64
homepage_featured    int64
num_orders          int64
dtype: object
```

3

Team Member 1

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

Dropping Columns

Let's drop columns "center_id" and "meal_id" as they are not required for the further process. Display the changes of trainfinal table using head().

```
In [110]: trainfinal = trainfinal.drop(['center_id', 'meal_id'], axis=1)
trainfinal.head()
```

```
Out[110]:
```

	id	week	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	category	cuisine	city_code	region_code	center_type
0	1379560	1	136.83	152.29	0	0	177	Beverages	Thai	647	56	TYPE_C
1	1018704	2	135.83	152.29	0	0	323	Beverages	Thai	647	56	TYPE_C
2	1196273	3	132.92	133.92	0	0	96	Beverages	Thai	647	56	TYPE_C
3	1116527	4	135.86	134.86	0	0	163	Beverages	Thai	647	56	TYPE_C
4	1343872	5	146.50	147.50	0	0	215	Beverages	Thai	647	56	TYPE_C

Display the list of columns present in trainfinal table and store it in variable "cols"

```
In [111]: cols = trainfinal.columns.tolist()
print(cols)
```

```
['id', 'week', 'checkout_price', 'base_price', 'emailer_for_promotion', 'homepage_featured', 'num_orders', 'category', 'cuisine', 'city_code', 'region_code', 'center_type', 'op_area']
```

Rearrange the columns by slicing the columns of "cols" and print "cols"

Gmail YouTube Maps

Jupyter Code (autosaved) Python 3 (ipykernel) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted

Rearrange the columns by slicing the columns of "cols" and print "cols"

```
In [112]: cols = cols[:2] + cols[9:] + cols[7:9] + cols[2:7]
print(cols)
```

['id', 'week', 'city_code', 'region_code', 'center_type', 'op_area', 'category', 'cuisine', 'checkout_price', 'base_price', 'emailer_for_promotion', 'homepage_featured', 'num_orders']

Store the changes of columns in trainfinal and display the datatypes of trainfinal.dtypes. Here, we can see that, we not only have numerical data but we also have object data.

```
In [113]: trainfinal = trainfinal[cols]
trainfinal.head()
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders
0	1379560	1	647	56	TYPE_C	2.0	Beverages	Thai	136.83	152.29	0	0	
1	1018704	2	647	56	TYPE_C	2.0	Beverages	Thai	135.83	152.29	0	0	
2	1196273	3	647	56	TYPE_C	2.0	Beverages	Thai	132.92	133.92	0	0	
3	1116527	4	647	56	TYPE_C	2.0	Beverages	Thai	135.86	134.86	0	0	
4	1343872	5	647	56	TYPE_C	2.0	Beverages	Thai	146.50	147.50	0	0	

```
In [114]: trainfinal.dtypes
```

	id	week
	int64	int64

Gmail YouTube Maps

Jupyter Code (autosaved) Python 3 (ipykernel) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted

```
In [113]: trainfinal.head()
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders
0	1379560	1	647	56	TYPE_C	2.0	Beverages	Thai	136.83	152.29	0	0	
1	1018704	2	647	56	TYPE_C	2.0	Beverages	Thai	135.83	152.29	0	0	
2	1196273	3	647	56	TYPE_C	2.0	Beverages	Thai	132.92	133.92	0	0	
3	1116527	4	647	56	TYPE_C	2.0	Beverages	Thai	135.86	134.86	0	0	
4	1343872	5	647	56	TYPE_C	2.0	Beverages	Thai	146.50	147.50	0	0	

```
In [114]: trainfinal.dtypes
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	dtype
	int64	int64	int64	int64	object	float64	object	object	float64	float64	int64	int64	int64	object

Team Member 2

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

Dropping Columns

Let's drop columns "center_id" and "meal_id" as they are not required for the further process. Display the changes of trainfinal table using head().

```
In [110]: trainfinal = trainfinal.drop(['center_id', 'meal_id'], axis=1)
trainfinal.head()
```

```
Out[110]:
```

	id	week	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	category	cuisine	city_code	region_code	center_type
0	1379560	1	136.83	152.29	0	0	177	Beverages	Thai	647	56	TYPE_C
1	1018704	2	135.83	152.29	0	0	323	Beverages	Thai	647	56	TYPE_C
2	1196273	3	132.92	133.92	0	0	96	Beverages	Thai	647	56	TYPE_C
3	1116527	4	135.86	134.86	0	0	163	Beverages	Thai	647	56	TYPE_C
4	1343872	5	146.50	147.50	0	0	215	Beverages	Thai	647	56	TYPE_C

Display the list of columns present in trainfinal table and store it in variable "cols"

```
In [111]: cols = trainfinal.columns.tolist()
print(cols)
```

```
['id', 'week', 'checkout_price', 'base_price', 'emailer_for_promotion', 'homepage_featured', 'num_orders', 'category', 'cuisine', 'city_code', 'region_code', 'center_type', 'op_area']
```

Rearrange the columns by slicing the columns of "cols" and print "cols"

IBM Home Page - Select or create a n... Code - Jupyter Notebook

localhost:8891/notebooks/Downloads/SBSPS-Challenge-8325-Food-Demand-Forecasting-for-Food-Delivery-Company-using-IBM-Cloud-main/SBSPS-Challenge-...

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

Rearrange the columns by slicing the columns of "cols" and print "cols"

```
In [112]: cols = cols[:2] + cols[9:] + cols[7:9] + cols[2:7]
print(cols)
```

```
['id', 'week', 'city_code', 'region_code', 'center_type', 'op_area', 'category', 'cuisine', 'checkout_price', 'base_price', 'emailer_for_promotion', 'homepage_featured', 'num_orders']
```

Store the changes of columns in trainfinal and display the datatypes of trainfinal using trainfinal.dtypes. Here, we can see that, we not only have numerical data but we also have object data.

```
In [113]: trainfinal = trainfinal[cols]
trainfinal.head()
```

```
Out[113]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders
0	1379560	1	647	56	TYPE_C	2.0	Beverages	Thai	136.83	152.29	0	0	0
1	1018704	2	647	56	TYPE_C	2.0	Beverages	Thai	135.83	152.29	0	0	0
2	1196273	3	647	56	TYPE_C	2.0	Beverages	Thai	132.92	133.92	0	0	0
3	1116527	4	647	56	TYPE_C	2.0	Beverages	Thai	135.86	134.86	0	0	0
4	1343872	5	647	56	TYPE_C	2.0	Beverages	Thai	146.50	147.50	0	0	0

```
In [114]: trainfinal.dtypes
```

```
Out[114]: id                int64
week                int64
```

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

trainfinal.head()

```
Out[113]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders
0	1379560	1	647	56	TYPE_C	2.0	Beverages	Thai	136.83	152.29	0	0	
1	1018704	2	647	56	TYPE_C	2.0	Beverages	Thai	135.83	152.29	0	0	
2	1196273	3	647	56	TYPE_C	2.0	Beverages	Thai	132.92	133.92	0	0	
3	1116527	4	647	56	TYPE_C	2.0	Beverages	Thai	135.86	134.86	0	0	
4	1343872	5	647	56	TYPE_C	2.0	Beverages	Thai	146.50	147.50	0	0	

In [114]: trainfinal.dtypes

```
Out[114]:
```

id	int64
week	int64
city_code	int64
region_code	int64
center_type	object
op_area	float64
category	object
cuisine	object
checkout_price	float64
base_price	float64
emailer_for_promotion	int64
homepage_featured	int64
num_orders	int64
dtype:	object

Team Member 3

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

Dropping Columns

Let's drop columns "center_id" and "meal_id" as they are not required for the further process. Display the changes of trainfinal table using head().

```
In [110]: trainfinal = trainfinal.drop(['center_id', 'meal_id'], axis=1)
trainfinal.head()
```

```
Out[110]:
```

	id	week	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders	category	cuisine	city_code	region_code	center_type
0	1379560	1	136.83	152.29	0	0	177	Beverages	Thai	647	56	TYPE_C
1	1018704	2	135.83	152.29	0	0	323	Beverages	Thai	647	56	TYPE_C
2	1196273	3	132.92	133.92	0	0	96	Beverages	Thai	647	56	TYPE_C
3	1116527	4	135.86	134.86	0	0	163	Beverages	Thai	647	56	TYPE_C
4	1343872	5	146.50	147.50	0	0	215	Beverages	Thai	647	56	TYPE_C

Display the list of columns present in trainfinal table and store it in variable "cols"

```
In [111]: cols = trainfinal.columns.tolist()
print(cols)
```

```
['id', 'week', 'checkout_price', 'base_price', 'emailer_for_promotion', 'homepage_featured', 'num_orders', 'category', 'cuisine', 'city_code', 'region_code', 'center_type', 'op_area']
```

Rearrange the columns by slicing the columns of "cols" and print "cols"

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

Code

Rearrange the columns by slicing the columns of 'cols' and print 'cols'

```
In [112]: cols = cols[:2] + cols[9:] + cols[7:9] + cols[2:7]
print(cols)
```

['id', 'week', 'city_code', 'region_code', 'center_type', 'op_area', 'category', 'cuisine', 'checkout_price', 'base_price', 'em
ailer_for_promotion', 'homepage_featured', 'num_orders']

Store the changes of columns in trainfinal and display the datatypes of trainfinal using trainfinal.dtypes. Here, we can see that, we not only have numerical data but we also have object data.

```
In [113]: trainfinal = trainfinal[cols]
trainfinal.head()
```

```
Out[113]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders
0	1379560	1	647	56	TYPE_C	2.0	Beverages	Thai	136.83	152.29	0	0	
1	1018704	2	647	56	TYPE_C	2.0	Beverages	Thai	135.83	152.29	0	0	
2	1196273	3	647	56	TYPE_C	2.0	Beverages	Thai	132.92	133.92	0	0	
3	1116527	4	647	56	TYPE_C	2.0	Beverages	Thai	135.86	134.86	0	0	
4	1343872	5	647	56	TYPE_C	2.0	Beverages	Thai	146.50	147.50	0	0	

```
In [114]: trainfinal.dtypes
```

```
Out[114]: id                int64
week                int64
```

Gmail YouTube Maps

jupyter Code (autosaved) Logout

File Edit View Insert Cell Kernel Widgets Help Not Connected Not Trusted Python 3 (ipykernel)

Code

```
trainfinal.head()
```

```
Out[113]:
```

	id	week	city_code	region_code	center_type	op_area	category	cuisine	checkout_price	base_price	emailer_for_promotion	homepage_featured	num_orders
0	1379560	1	647	56	TYPE_C	2.0	Beverages	Thai	136.83	152.29	0	0	
1	1018704	2	647	56	TYPE_C	2.0	Beverages	Thai	135.83	152.29	0	0	
2	1196273	3	647	56	TYPE_C	2.0	Beverages	Thai	132.92	133.92	0	0	
3	1116527	4	647	56	TYPE_C	2.0	Beverages	Thai	135.86	134.86	0	0	
4	1343872	5	647	56	TYPE_C	2.0	Beverages	Thai	146.50	147.50	0	0	

```
In [114]: trainfinal.dtypes
```

```
Out[114]: id                int64
week                int64
city_code           int64
region_code         int64
center_type         object
op_area             float64
category            object
cuisine             object
checkout_price       float64
base_price           float64
emailer_for_promotion int64
homepage_featured    int64
num_orders          int64
dtype: object
```