

```

import cv2
import numpy as np
from keras.models import load_model
from keras.utils import load_img, img_to_array

class Video(object):
    def __init__(self):
        self.video = cv2.VideoCapture(0)
        self.roi_start = (50, 150)
        self.roi_end = (250, 350)
        self.model = load_model('G:\IBM\Conversation engine for deaf
and dumb\aslpng1.h5') # Execute Local Trained Model
        # self.model = load_model('IBM_Communication_Model.h5') #
Execute IBM Trained Model
        self.index=['A','B','C','D','E','F','G','H','I']
        self.y = None
    def __del__(self):
        self.video.release()
    def get_frame(self):
        ret,frame = self.video.read()
        frame = cv2.resize(frame, (640, 480))
        copy = frame.copy()
        copy = copy[150:150+200,50:50+200]
        # Prediction Start
        cv2.imwrite('image.jpg',copy)
        copy_img = load_img('image.jpg', target_size=(64,64))
        x = img_to_array(copy_img)
        x = np.expand_dims(x, axis=0)
        pred = np.argmax(self.model.predict(x), axis=1)
        self.y = pred[0]
        cv2.putText(frame,'The Predicted Alphabet is:
'+str(self.index[self.y]),(100,50),cv2.FONT_HERSHEY_SIMPLEX,1,(0,0,0),3)
        ret,jpg = cv2.imencode('.jpg', frame)
        return jpg.tobytes()

```