### **ASSIGNMENT – 4**

#### **WOKWI AND IBM CLOUD**

Assignment Date	17 November 2022
Student Name	Sowmya.P
Student Roll Number	311419106029
Maximum Marks	2 Marks

## Question-1:

Write code and connections in wokwi for ultrasonic sensor. Whenever the distance is less than 100 cms sent "alert" to IBM cloud and display in device recent events.

#### AIM:

To write code and connections in wokwi for ultrasonic sensor. Whenever the distance is less than 100 cms sent "alert" to IBM cloud and display in device recent events.

#### CODE:


```
#include <WiFi.h>//library for wifi
#include <PubSubClient.h>//library for MQtt
void callback (char* subscribetopic, byte* payload, unsigned int
payloadLength);
//-----/
//-----
WiFiClient wifiClient; // creating the instance for wificlient
PubSubClient client(server, 1883, callback ,wifiClient); //calling the
predefined client id by passing parame#define ORG "5xkpdy"
#define DEVICE_TYPE "115devicetype"
#define DEVICE_ID "115deviceid"//Device ID mentioned in ibm watson IOT
Platform
#define TOKEN "authentication" //Token
String data3;
float dist;
//----- Customise the above values ------
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";// Server Name
char publishTopic[] = "iot-2/evt/Data/fmt/json";// topic name and type of
event perform and format in which data to be send
```

```
char subscribetopic[] = "iot-2/cmd/test/fmt/String";// cmd REPRESENT command
type AND COMMAND IS TEST OF FORMAT STRING
char authMethod[] = "use-token-auth";// authentication method
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE TYPE ":" DEVICE ID;//client id by
passing parameter like server id, portand wificredential
int LED = 15;
int trig = 13;
int echo = 12;
void setup()
Serial.begin(115200);
pinMode(trig,OUTPUT);
pinMode(echo,INPUT);
pinMode(LED, OUTPUT);
delay(10);
wificonnect();
mqttconnect();
}
void loop()
{
 digitalWrite(trig,LOW);
  digitalWrite(trig,HIGH);
  delayMicroseconds(10);
  digitalWrite(trig,LOW);
  float dur = pulseIn(echo,HIGH);
  float dist = (dur * 0.0343)/2;
  Serial.print ("Distance in cm");
  Serial.println(dist);
  PublishData(dist);
  delay(1000);
  if (!client.loop()) {
   mqttconnect();
  }
}
/*....retrieving to
Cloud....*/
void PublishData(float dist) {
  mqttconnect();//function call for connecting to ibm
  /*
    creating the String in in form JSon to update the data to ibm cloud
  String object;
```


```
if (dist <100)</pre>
    digitalWrite(LED,HIGH);
    Serial.println("object is near");
    object = "Near";
  }
  else
  {
    digitalWrite(LED, LOW);
    Serial.println("no object found");
   object = "No";
  }
  String payload = "{\"distance\":";
  payload += dist;
  payload += "," "\"object\":\"";
  payload += object;
  payload += "\"}";
  Serial.print("Sending payload: ");
  Serial.println(payload);
  if (client.publish(publishTopic,(char*) payload.c_str())) {
    Serial.println("Publish ok");// if it sucessfully upload data on the cloud
then it will print publish ok in Serial monitor or else it will print publish
failed
  } else {
    Serial.println("Publish failed");
  }
void mqttconnect() {
  if (!client.connected()) {
    Serial.print("Reconnecting client to ");
    Serial.println(server);
   while (!!!client.connect(clientId, authMethod, token)) {
      Serial.print(".");
      delay(500);
    }
     initManagedDevice();
     Serial.println();
  }
}
void wificonnect() //function defination for wificonnect
{
  Serial.println();
```

```
Serial.print("Connecting to ");
  WiFi.begin("Wokwi-GUEST", "", 6);//passing the wifi credentials to establish
the connection
  while (WiFi.status() != WL CONNECTED) {
    delay(500);
    Serial.print(".");
  }
  Serial.println("");
  Serial.println("WiFi connected");
  Serial.println("IP address: ");
  Serial.println(WiFi.localIP());
}
void initManagedDevice() {
  if (client.subscribe(subscribetopic)) {
    Serial.println((subscribetopic));
    Serial.println("subscribe to cmd OK");
  } else {
   Serial.println("subscribe to cmd FAILED");
  }
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
  Serial.print("callback invoked for topic: ");
  Serial.println(subscribetopic);
  for (int i = 0; i < payloadLength; i++) {</pre>
    //Serial.print((char)payload[i]);
   data3 += (char)payload[i];
  }
 // Serial.println("data: "+ data3);
// if(data3=="Near")
// {
// Serial.println(data3);
// digitalWrite(LED,HIGH);
// }
// else
   {
// Serial.println(data3);
// digitalWrite(LED,LOW);
// }
data3="";
```

## **CONNECTIONS:**



# OUTPUT(WOKWI):



LINK: https://wokwi.com/projects/348226246133416531

# **OUTPUT (IBM CLOUD):**

