

Assignment 4

Signs with Smart Connectivity for Better Road Safety

Assignment Date	20 Oct 2022
Student Name	SANGEETH DHANAPAL V
Student Roll num	AC19UIT041
Maximum Marks	2 Marks

Question :

Write code and connections in wokwi for the ultrasonic sensor. Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device recent events. Upload document with wokwi share link and images of IBMcloud.

Code in Wokwi:

```
#include <WiFi.h> #include
<PubSubClient.h>
void callback(char* subscribtopic, byte* payload, unsigned intpayloadLength);
//-----credentials of IBM Accounts-----
#define ORG "confidential"//IBM ORGANITION ID
#define DEVICE_TYPE "gaya"//Device type mentioned in ibm watson IOT Platform#define DEVICE_ID
"0605"//Device ID mentioned in ibm watson IOT Platform #define TOKEN "confidential" //Token
String data3;
char server[] = ORG ".messaging.internetofthings.ibmcloud.com";char publishTopic[] =
"iot-2/evt/Data/fmt/json";
char subscribtopic[] = "iot-2/cmd/test/fmt/String";char authMethod[] =
"use-token-auth";
char token[] = TOKEN;
char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
WiFiClient wifiClient;
PubSubClient client(server, 1883, callback ,wifiClient);const int trigPin = 5;
const int echoPin = 18; #define
SOUND_SPEED 0.034long
duration;
float distance;void
setup() {
```

```

Serial.begin(115200);
pinMode(trigPin, OUTPUT);
pinMode(echoPin, INPUT);
wificonnect(); mqttconnect();
}
void loop()
{
digitalWrite(trigPin, LOW);
delayMicroseconds(2); digitalWrite(trigPin,
HIGH); delayMicroseconds(10);
digitalWrite(trigPin, LOW); duration =
pulseIn(echoPin, HIGH); distance = duration *
SOUND_SPEED/2; Serial.print("Distance (cm):
"); Serial.println(distance); if(distance<100)
{
Serial.println("ALERT!!!"); delay(1000);
PublishData(distance); delay(1000);
if (!client.loop()) {
mqttconnect();
}
}
delay(1000);
}
void PublishData(float dist) {
mqttconnect();
String payload = "{"Distance\":"; payload +=
dist;
payload += ", \"ALERT!!\":"; payload += "\"Distance less than 100cms\":"; payload += "}";
Serial.print("Sending payload: ");
Serial.println(payload);

if (client.publish(publishTopic, (char*) payload.c_str())) {Serial.println("Publish
ok");
} else {
Serial.println("Publish failed");
}
}
void mqttconnect() {

```

```

if (!client.connected()) { Serial.print("Reconnecting
client to ");Serial.println(server);
while (!client.connect(clientId, authMethod, token)) {Serial.print(".");
delay(500);
}
initManagedDevice();
Serial.println();
}
}
void wificonnect()
{
Serial.println(); Serial.print("Connecting to
"); WiFi.begin("Wokwi-GUEST", "", 6);
while (WiFi.status() != WL_CONNECTED) {
delay(500);
Serial.print(".");
}
Serial.println(""); Serial.println("WiFi
connected");Serial.println("IP address: ");
Serial.println(WiFi.localIP());
}
void initManagedDevice() {
if (client.subscribe(subscribetopic)) {
Serial.println((subscribetopic));
Serial.println("subscribe to cmd OK");
}
else {
Serial.println("subscribe to cmd FAILED");
}
}
void callback(char* subscribetopic, byte* payload, unsigned int payloadLength)
{
Serial.print("callback invoked for topic: ");
Serial.println(subscribetopic);
for (int i = 0; i < payloadLength; i++) {
//Serial.print((char)payload[i]);data3 +=
(char)payload[i];
}
Serial.println("data: "+ data3);data3="";
}

```

Wokwi sketch and Simulation:

```

1 #include <WiFi.h>
2 #include <PubSubClient.h>
3 void callback(char* topic, byte* payload, unsigned int
4   payloadLength);
5 //-----credentials of IBM Accounts-----
6 #define ORG " " //IBM ORGANITION ID
7 #define DEVICE_TYPE "gaya" //Device type mentioned in ibm watson IOT Platform
8 #define DEVICE_ID "0602" //Device ID mentioned in ibm watson IOT Platform
9 #define TOKEN " " //Token
10 String data3;
11 char server[] = ORG ".messaging.internetofthings.ibmcloud.com";
12 char publishTopic[] = "iot-2/evt/Data/fmt/json";
13 char subscribetopic[] = "iot-2/cmd/test/fmt/String";
14 char authMethod[] = "use-token-auth";
15 char token[] = TOKEN;
16 char clientId[] = "d:" ORG ":" DEVICE_TYPE ":" DEVICE_ID;
17 WiFiClient wificlient;
18 PubSubClient client(server, 1883, callback, wificlient);
19 const int trigPin = 5;
20 const int echoPin = 18;
21 #define SOUND_SPEED 0.034
22 long duration;
23 float distance;
24 void setup() {
25   Serial.begin(115200);
26   pinMode(trigPin, OUTPUT);
27   pinMode(echoPin, INPUT);
28   wificlient.connect();
29   mqttconnect();
30 }
31 void loop()
32 {
33   digitalWrite(trigPin, LOW);
34   delayMicroseconds(2);
35   digitalWrite(trigPin, HIGH);

```

Simulation
00:48.839 99%

Editing Ultrasonic Distance Sensor
✕

Distance:

2cm

Publish ok

Distance (cm): 1.99

ALERT!!

Sending payload: {"Distance":1.99,"ALERT!!":"Distance less than 100cms"}

Publish ok

Distance (cm): 1.99

ALERT!!

IBM Watson IOT Platform :

IBM Watson IoT Platform
910619106015@smartinternz.com
ID: [redacted]

Browse
Action
Device Types
Interfaces

Add Device

Device ID	Status	Device Type	Class ID	Date Added	Descriptive Location
0602	Connected	gaya	Device	1 Nov 2022 12:31	

Identity
Device Information
Recent Events
State
Logs

The recent events listed show the live stream of data that is coming and going from this device.

Event	Value	Format	Last Received
Data	{"Distance":1.99,"ALERT!!":"Distance less than 1...	json	a few seconds ago
Data	{"Distance":1.99,"ALERT!!":"Distance less than 1...	json	a few seconds ago
Data	{"Distance":1.99,"ALERT!!":"Distance less than 1...	json	a few seconds ago
Data	{"Distance":1.99,"ALERT!!":"Distance less than 1...	json	a few seconds ago
Data	{"Distance":1.99,"ALERT!!":"Distance less than 1...	json	a few seconds ago

0 Simulations running

*Whenever the distance is less than 100 cms send an "alert" to the IBM cloud and display in the device **Recent Events**.*